

TW128: A Tree-Structured Duplex Authenticated-Encryption Mode

Coda Hale

Hale Institute for Bicycle Appreciation

Abstract. We present TW128, a nonce-based authenticated-encryption mode with associated data built as a two-level tree of keyed duplexes over the KECCAK- p [1600, 12] permutation. A serial root duplex binds the key, nonce, and associated data, encrypts the first message chunk, and aggregates a tag from every remaining chunk into a single authentication tag; the remaining chunks are handled by independent leaf duplexes that share no state once the key and nonce are fixed and can therefore be evaluated in parallel across SIMD lanes.

We analyze TW128 in the public-permutation model, proving each bound first against an intermediate random oracle and then transferring it to the real permutation by the flat-sponge lift. We obtain concrete bounds for all-in-one authenticated encryption, multi-user indistinguishability, and the commitment security of the root tag. The last we obtain by proving that the wrapper returning the tag is a secure hash of the (K, N, A, M) context—collision-, second-preimage-, and preimage-resistant in the standard hash-function sense—so the single root tag is a compact commitment; full-input committing security (CMTDs-4) follows as a corollary, and we separately establish context discoverability. At the implemented parameters these notions meet a 128-bit security target. Vectorized `amd64` and `arm64` implementations realize the tree’s leaf parallelism, reaching multi-gigabyte-per-second throughput, a factor of 1.3 to 2 below hardware-accelerated AES-128-GCM.

Keywords: authenticated encryption · committing security · sponge constructions · duplex constructions · Keccak

1 Introduction

Authenticated encryption with associated data is the workhorse of applied cryptography, and the sponge and duplex constructions over a single public permutation offer an attractive route to it. The duplex of [BDPVA11] turns one permutation—here KECCAK- p [1600, 12], the round-reduced permutation underlying the [Nat15] standard—into a single-pass authenticated cipher with a small, constant memory footprint and no separate block cipher or universal-hash key schedule. Its security rests on the indistinguishability of the sponge from a random oracle [BDPVA08], which reduces analysis of the full construction to a random-oracle argument plus one capacity-birthday loss.

This compactness comes at a structural cost. A duplex is inherently *sequential*: each call absorbs its input into a state produced by the previous call, so a single duplex cannot exploit the wide SIMD and multicore parallelism of modern processors, on which competing designs built from AES reach many bytes per cycle. A second, orthogonal gap is *commitment*. Widely deployed AEADs such as AES-GCM and ChaCha20-Poly1305 are not key-committing: an adversary can craft a single ciphertext that decrypts to valid plaintexts under two or more keys [DGRW18, ADG⁺22]. Far from a curiosity, this enables concrete abuses—the “invisible salamander” that defeats Facebook’s attachment-franking scheme [DGRW18], ciphertexts that open to different well-formed files under different keys

[ADG⁺22], and partitioning-oracle attacks that recover passwords from systems built on non-committing AEAD [LGR21]. The committing-AE line that addresses these threats was initiated by [GLR17] and developed into formal committing notions with efficient generic transforms by [BH22]. Commitment has two facets: committing security is a collision requirement—no two contexts open one ciphertext—while its preimage counterpart, *context discoverability* [MLGR23], forbids an adversary from *finding* even one decrypting context for a target ciphertext. The latter’s absence underlies the recent context-discovery attacks that break GCM, CCM, EAX, SIV, and OCB3 [MLGR23], all of which delegate authenticity to an algebraically invertible MAC. A mode that targets these notions natively, rather than through an add-on transform, avoids the transform’s overhead and binds commitment to the same permutation it already uses for confidentiality and integrity.

TW128 (*Tree Wrap*) addresses both gaps with a two-level tree of keyed duplexes. A serial *root* duplex, initialized with the key K and nonce N , absorbs the associated data, encrypts the first message chunk, and absorbs a tag from every other chunk before emitting the final authentication tag. The remaining chunks are processed by independent *leaf* duplexes, each keyed by (K, N, j) and operating on disjoint state and disjoint input. Because the leaves share nothing once (K, N) is fixed, they can be evaluated in parallel across SIMD lanes, recovering the throughput a flat duplex forgoes; and because the root binds the associated data, the first chunk, and every leaf tag into the single output tag, that tag is the output of the sponge on the entire (K, N, A, M) input. The structure ensures only that distinct (K, N, A) triples reach distinct root transcripts; the committing and context-discoverability security rests on the indistinguishability of the sponge, which makes the root tag both collision- and preimage-resistant. Because both hold for the tag projection alone, the single 256-bit root tag is itself a secure, compact cryptographic commitment to the full (K, N, A, M) context (Section 8). Every duplex still operates on a bounded 1600-bit state, and the leaf tags are absorbed into the root as the leaves complete rather than buffered together, so the memory footprint remains constant in the message length.

We analyze TW128 in the public-permutation model and obtain concrete bounds for all-in-one authenticated encryption in the sense of [RS06], its multi-user indistinguishability lift in the sense of [BT16], and the commitment security of the root tag, stated as the [RS04] hash security of the tag wrapper—collision, second-preimage, and preimage resistance—from which the [BH22] full-input committing notion (CMTDs-4) follows as a corollary, alongside the [MLGR23] context-discoverability notion. Each bound is proved first against an intermediate random oracle and then transferred to the real permutation by the flat-sponge lift of [BDPVA08]. At the implemented parameters ($k = c = \tau_{\text{root}} = \tau_{\text{leaf}} = 256$), these guarantees meet a 128-bit security target for adversaries running up to $N_{\text{tot}} \leq 2^{63}$ KECCAK- $p[1600, 12]$ calls—on the order of 2^{71} bytes of processed data, beyond any realistic deployment lifetime. Optimized amd64 and arm64 implementations turn the tree’s leaf parallelism into measured throughput within a small factor of hardware-accelerated AES-128-GCM (Section 9).

1.1 Our Contributions

- **The TW128 mode.** We specify TW128, a nonce-based AEAD with associated data built as a two-level tree of strict [BDPVA11] duplexes over KECCAK- $p[1600, 12]$ (Section 3): a serial root duplex that binds (K, N, A) , the first chunk, and the leaf tags into a single authentication tag, over a set of parallel, independently keyed leaf duplexes. All phases are domain-separated within one permutation, and the state is constant-size regardless of message length.
- **All-in-one AE security.** We prove a concrete bound on the all-in-one AE advantage [RS06] in the public-permutation model (Theorem 1), obtained by composing random-oracle privacy and INT-CTXT bounds through the generic-composition argument of

- [BN00] and lifting the result to the real permutation.
- **Multi-user security.** We give a concrete multi-user indistinguishability bound [BT16] for D users (Theorem 2), obtained by a key-collision-stopped hybrid over the users that reuses the single-user privacy and INT-CTXT envelopes.
 - **Commitment via a secure hash.** We show that the wrapper H returning the root tag is a secure hash of the full (K, N, A, M) input in the sense of [RS04]—collision-, second-preimage-, and preimage-resistant (Theorems 3 to 5)—so the single 256-bit root tag is a binding, preimage-resistant compact commitment to the input, matching the compactly committing AEAD goal of [GLR17] natively, with no generic transform. The [BH22] full-input committing notions follow as corollaries: s -way CMTDs-4 from collision resistance (Corollary 1), and the remaining CMT/CMTD for $\ell \in \{1, 3, 4\}$ in Section C.
 - **Context discoverability.** We additionally prove that TW128 satisfies the published [MLGR23] context-discoverability notion CDY^* and its per-component variants—a ciphertext-level guarantee, distinct from preimage resistance of the tag, established with a concrete bound (Theorem 6)—so no adversary, given a target ciphertext fixed in advance, can find a decrypting context. This is the facet whose absence underlies the discovery attacks of [MLGR23]; Section 1.2 contrasts TW128’s sponge-based resistance with the algebraic-MAC inversion those attacks exploit.
 - **Proof methodology.** We carry out the analysis in a dedicated TW128 random-oracle model and transfer every bound to the public-permutation setting through the [BDPVA08] flat-sponge lift (Section B). A derived-adversary argument shows that each direct primitive query induces at most one random-oracle query, so the random-oracle envelopes are instantiated at the direct-query count N_{prim} rather than the total work N_{tot} , separating the single capacity-birthday loss $\text{Lift}_c(N_{\text{tot}})$ from the scheme-specific terms.
 - **Optimized implementations.** We describe and evaluate vectorized amd64 (AVX-512 and AVX2) and arm64 (NEON with the SHA-3 extension) implementations whose batched leaf cores realize the tree’s parallelism in practice, reaching multi-gigabyte-per-second throughput on contemporary hardware (Section 9).

1.2 Related Work

Sponge and duplex AEADs. Permutation-based authenticated encryption built on the sponge and duplex constructions of [BDPVA08, BDPVA11] is well established. Keyak [BDP⁺15] is a CAESAR candidate built on the duplex over round-reduced KECCAK- p , whose Motorist mode already admits parallel duplex instances. Ascon [DEMS21], the lightweight winner of the CAESAR competition and the basis of the NIST lightweight-cryptography standard, and Xoodyak [DHP⁺20], a finalist in that process whose Cyclist mode is a deliberately serial simplification of Motorist, are duplex AEADs over the Ascon and Xoodoo permutations. TW128 shares this single-permutation, constant-state duplex foundation but differs in structure: rather than one duplex session, it is a two-level tree whose leaves are *independently keyed* duplexes under domain-separated chunk identifiers. Like Keyak’s Motorist mode, the tree admits data-parallel evaluation across SIMD lanes; the designs differ in where the degree of parallelism lives. Keyak fixes it as a mode parameter—each named instance sets the number Π of parallel duplex instances across which a message is spread, so Π is part of the wire format and must be agreed by the encryptor and decryptor in advance. In TW128 the leaf decomposition is fixed by the mode, but the number of leaves evaluated simultaneously is not part of the transcript: an implementation chooses it at run time to match the host’s vector width, and the ciphertext

and tag are identical however it is chosen, so a wide-SIMD encryptor and a scalar decryptor interoperate.

Tree hashing. The two-level shape is inspired by tree hashing over the same permutation, in particular KangarooTwelve [BDP⁺16], which splits its input into fixed-size chunks hashed independently under KECCAK- p [1600, 12] and absorbs their chaining values into a root node. TW128 reuses the round count and the final-node/leaf split of that design and adapts it to authenticated encryption: each leaf chunk is encrypted and tagged independently, and the leaf tags are absorbed by the root in place of chaining values. It also inherits the short-message behavior of KangarooTwelve’s *kangaroo hopping*, which merges the first chunk with the hashing of the remaining chunks’ chaining values so that an input fitting in a single chunk incurs no tree overhead: in TW128 a single-chunk message engages no leaf duplexes and no aggregation phase, the root processing it directly and emitting the tag as a plain keyed duplex would. Short messages therefore pay none of the tree’s cost and retain the latency profile of an unstructured duplex (Section 9.4); the leaf layer, and its parallelism, engage only once a message spans more than one chunk.

Committing AEAD. The study of committing authenticated encryption was initiated by [GLR17], who introduced compactly committing AEAD for message franking, and by [DGRW18], who built it from a dedicated primitive (encryptment); [BH22] subsequently organized the notions into the CMT-1/3/4 and CMTD hierarchy and gave efficient generic transforms (UtC, RtC, HtE) that add commitment to a base scheme. A complementary line shows that widely used and dedicated AEADs fail these notions: the invisible-salamander [DGRW18] and partitioning-oracle [LGR21] attacks, multi-format ciphertexts [ADG⁺22], the context-discovery and commitment attacks that break CCM, EAX, SIV, GCM, and OCB3 [MLGR23], and an $O(1)$ key-committing attack against all variants of AEGIS [WP14] that refutes the prior belief that AEGIS was committing [IR23]. [MLGR23] also introduce context discoverability, the preimage facet of commitment, and show that their discovery attacks exploit schemes whose authenticity is delegated to a non-preimage-resistant MAC such as GHASH or CMAC. TW128 instead makes the root tag itself collision- and preimage-resistant as a sponge output, rather than delegating to a transform or an invertible MAC, so the [MLGR23] discovery attacks have no analogue against it.

Closest to TW128 is the recent work of [DHM⁺24], which likewise builds nonce-based AE natively on the SHA-3 functions and obtains CMT-4 from the collision resistance of the underlying function rather than from a transform; it targets session-based communication through a sequential duplex chain, where TW128 is a parallel two-level tree. Sections 9 and 10.3 detail the structural and throughput differences.

1.3 Paper Organization

Section 2 recalls the notation, sponge and duplex constructions over KECCAK- p , the authenticated-encryption, committing-security [BH22], and context-discoverability [MLGR23] notions used throughout, and the multi-user indistinguishability notion of [BT16]. Section 3 specifies the TW128 construction and its parameters. Section 4 fixes the public-permutation games, the intermediate random-oracle model, and the resource accounting that all later bounds reference. Section 5 states the headline AE, mu-ind, hash (collision, second-preimage, preimage), CMTDs-4, and context-discoverability theorems and their concrete TW128-parameter forms; Sections 6 and 7 prove the random-oracle privacy and INT-CTXT bounds that feed those theorems, and Section 8 proves the random-oracle hash and CMTDs-4 bounds. Section 9 reports the performance of the reference and optimized implementations. Section 10 compares TW128 to prior sponge AEADs and committing constructions and discusses limitations. Section 11 concludes. Section A

collects the structural decoding and accounting lemmas that form the proof core; Section B carries out the [BDPVA08] flat-sponge lift that converts each random-oracle bound to its public-permutation form; Section C gives the remaining [BH22] committing-security bounds; and Section E lists TW128 test vectors.

2 Preliminaries

2.1 Notation

Strings. Write $\{0, 1\}$ for the binary alphabet. For an integer $n \geq 0$, $\{0, 1\}^n$ denotes the set of n -bit strings, $\{0, 1\}^* = \bigcup_{n \geq 0} \{0, 1\}^n$ the set of all finite-length bit strings, and ε the empty string. For $x \in \{0, 1\}^*$, $|x|$ is the bit length and $x \parallel y$ is the concatenation; the bitwise XOR of two equal-length strings $x, y \in \{0, 1\}^n$ is $x \oplus y$. A *byte string* is an element of $(\{0, 1\}^8)^*$; its byte length is denoted $\|x\| = |x|/8$. For an integer $0 \leq n < 2^{64}$, $\langle n \rangle_8 \in \{0, 1\}^{64}$ is its eight-byte little-endian encoding. For a finite or infinite bit string x and $0 \leq \tau \leq |x|$ when x is finite, $[x]_\tau \in \{0, 1\}^\tau$ denotes the leading τ bits of x .

Sampling and probability. We write $x \leftarrow \$ S$ for sampling x uniformly at random from a finite set S , with implicit coins independent across samples. For an event E in a probability experiment, $\Pr[E]$ denotes its probability.

Sets of maps. For a set S , $\text{Perm}(S)$ denotes the set of permutations on S ; for a positive integer b , $\text{Perm}(\{0, 1\}^b)$ is the set of b -bit permutations.

Games and advantages. We write $\mathcal{A}^{O_1, \dots, O_k}$ for a (possibly randomized) adversary with oracle access to $O_1, \dots, O_k$, and $\Pr[\mathbf{G}^{\mathcal{A}} \Rightarrow 1]$ for the probability that a game $\mathbf{G}$ —an experiment that runs $\mathcal{A}$ against specified oracles and returns a Boolean outcome—returns 1. For a distinguishing experiment between two games $\mathbf{G}_0, \mathbf{G}_1$, the advantage of $\mathcal{A}$ against a scheme Π in notion $\mathbf{X}$ is the absolute difference

$$\text{Adv}_{\Pi}^{\mathbf{X}}(\mathcal{A}) = |\Pr[\mathbf{G}_0^{\mathcal{A}} \Rightarrow 1] - \Pr[\mathbf{G}_1^{\mathcal{A}} \Rightarrow 1]|.$$

For a win-event experiment without a hidden challenge bit it is instead $\Pr[\mathbf{G}^{\mathcal{A}} \text{ wins}]$, the probability the game returns 1; a bit-guessing experiment with a hidden challenge bit uses the rescaled form $|2 \Pr[\mathbf{G}^{\mathcal{A}} \text{ wins}] - 1|$, as in the multi-user notion of Section 2.4.

Concrete security. All bounds in this paper are concrete: each advantage is an explicit function of the resource caps introduced in Section 4.3. We make no use of asymptotic or negligibility conventions.

Reference summary. Table 1 summarizes the resource caps and loss terms used throughout. The caps are defined formally in Section 4.3, the loss terms in Section 5.1.

2.2 Sponges and Duplexes over Keccak- p

The Keccak- p permutation. The KECCAK- p family of permutations, introduced as part of the Keccak design and standardized within FIPS 202 [Nat15], is parameterized by a state width b and a round count n_r ; we write $\text{KECCAK-}p[b, n_r] \in \text{Perm}(\{0, 1\}^b)$ for the corresponding permutation. TW128 uses KECCAK- $p[1600, 12]$, the same primitive as KangarooTwelve [BDP⁺16], fixed throughout. In the public-permutation security model of Section 4.1 and the flat-sponge lift of Section B, this permutation is modeled as a uniformly random element of $\text{Perm}(\{0, 1\}^{1600})$.

Table 1: Resource caps and loss terms.

Symbol	Meaning	Defined
N	Construction-interface cost (KECCAK- $p[1600, 12]$ calls)	§ 4.3
N_{prim}	Direct primitive-interface queries	§ 4.3
N_{tot}	$N + N_{\text{prim}}$ (total query-sequence cost)	§ 4.3
q_v, Q_v	Valid verification queries / cap (INT-CTXT)	§ 4.3
$q_{\text{RO}}, Q_{\text{RO}}$	Direct random-oracle queries / cap (RO-model)	§ 4.3
$n_{\text{leaf}}, N_{\text{leaf}}$	Distinct construction-generated final leaf transcripts / cap	§ 4.3
$\text{Lift}_c(N_{\text{tot}})$	[BDPVA08] flat-sponge loss	§ 5.1
$\text{KeyGuess}_k(Q)$	Ideal-system key guess	§ 5.1
$\text{RootColl}_\tau(Q, s)$	s -way root-collision	§ 5.1
$\text{RootPre}_\tau(Q)$	Root-preimage	§ 5.1
$\text{LeafColl}_\tau(Q)$	Known-key leaf-collision	§ 5.1

The sponge construction. Following [BDPVA08], fix a permutation $\pi \in \text{Perm}(\{0, 1\}^b)$, a *sponge-compliant* padding rule pad , and a rate $1 \leq r < b$ with capacity $c = b - r$. A padding rule appends $\text{pad}[r](|M|)$, a bit string determined by the input length and the rate, to an input M , extending it to a sequence of r -bit blocks; it is sponge-compliant [BDPVA11, Definition 1] if $M \parallel \text{pad}[r](|M|)$ is never empty and, for all $M \neq M'$ and all $n \geq 0$, $M \parallel \text{pad}[r](|M|) \neq M' \parallel \text{pad}[r](|M'|) \parallel 0^{nr}$. The sponge function $\text{Sponge}[\pi, \text{pad}, r] : \{0, 1\}^* \times \mathbb{N} \rightarrow \{0, 1\}^*$ maps an input M and an output length ℓ to an ℓ -bit string by absorbing $M \parallel \text{pad}[r](|M|)$ into the all-zero b -bit state in r -bit blocks (each separated by an application of π) and squeezing ℓ bits in r -bit blocks from the resulting state. [BDPVA08, Theorem 2] shows that $\text{Sponge}[\pi, \text{pad}10^*, r]$, where the simple rule $\text{pad}10^*$ appends a single 1 bit followed by the minimum number of 0 bits reaching a multiple of r , is indistinguishable from a random oracle when π is uniformly random. We bound its distinguishing advantage by $\text{Lift}_c(N_{\text{tot}}) = N_{\text{tot}}(N_{\text{tot}} + 1)/2^{c+1}$, derived in Lemma 18 from the exact differentiating probabilities of [BDPVA08, Lemmas 4 and 5].

The duplex construction. The *duplex* construction of [BDPVA11] extends the sponge to a stateful interface. A duplex object $\text{Duplex}[\pi, \text{pad}, r]$ is initialized to the all-zero state. Each call $\text{duplexing}(\sigma, \ell)$, with $\ell \leq r$, absorbs an input string σ of at most $\rho_{\max}(\text{pad}, r)$ bits via π and returns the first ℓ bits of the resulting state. Here $\rho_{\max}(\text{pad}, r) = \min\{x : x + |\text{pad}[r](x)| > r\} - 1$ is the largest input length for which the padded input fits in a single r -bit block; for the $\text{pad}10^*1$ rule, $\rho_{\max}(\text{pad}10^*1, r) = r - 2$ [BDPVA11]. [BDPVA11, Lemma 3] establishes the duplex-to-sponge equality: for any call sequence $((\sigma_0, \ell_0), \dots, (\sigma_i, \ell_i))$, the i -th output equals

$$\text{Sponge}[\pi, \text{pad}, r](\sigma_0 \parallel \text{pad}_0 \parallel \dots \parallel \sigma_i, \ell_i),$$

where $\text{pad}_j = \text{pad}[r](|\sigma_j|)$ is the padding the duplex appends in its j -th call; the flattened input carries these interior paddings explicitly, and the sponge appends only the final pad_i . The flattening map is injective by [BDPVA11, Lemma 4]: the duplex-call sequence is recoverable from the flattened sponge input.

TW128 instantiation. TW128 fixes the padding rule $\text{pad}10^*1$ and the rate $r = 1344$, so the capacity is $c = 256$ bits. The largest input length per duplex call is therefore $\rho_{\max}(\text{pad}10^*1, 1344) = 1342$ bits.

Bridge to the H -input domain. The indistinguishability theorem of [BDPVA08] is stated for the simpler $\text{pad}10^*$ padding over its unpadded H -input domain, while TW128 uses $\text{pad}10^*1$ internally. [BDPVA11, Theorem 3] supplies an injective preprocessing bridge

$I[r, r_{\max}]$ between the two domains. For TW128, $r = r_{\max} = 1344$, so the bridge reduces to appending $1 \parallel 0^q$ with q determined by the input length modulo $r_{\max}$; on the bridge image, q is recovered as the trailing-zero count. Section 4.2 instantiates this bridge on typed TW128 duplex transcript prefixes as the map $\text{flat}(\cdot)$ used by the random-oracle proofs of Sections C and 6 to 8.

2.3 Authenticated Encryption with Associated Data

Syntax. A *nonce-based authenticated-encryption scheme with associated data* (AEAD scheme) is a pair $\text{SE} = (\text{Enc}, \text{Dec})$ of deterministic algorithms with associated key space $\mathcal{K} \subseteq (\{0, 1\}^8)^*$, nonce space $\mathcal{N} \subseteq (\{0, 1\}^8)^*$, associated-data space $\mathcal{A} \subseteq (\{0, 1\}^8)^*$, message space $\mathcal{M} \subseteq (\{0, 1\}^8)^*$, and ciphertext space $\mathcal{C} \subseteq (\{0, 1\}^8)^*$. The encryption algorithm $\text{Enc} : \mathcal{K} \times \mathcal{N} \times \mathcal{A} \times \mathcal{M} \rightarrow \mathcal{C}$ produces a ciphertext $C = \text{Enc}_K(N, A, M)$. The decryption algorithm $\text{Dec} : \mathcal{K} \times \mathcal{N} \times \mathcal{A} \times \mathcal{C} \rightarrow \mathcal{M} \cup \{\perp\}$ returns either a plaintext or the rejection symbol $\perp$. The *tag length in bytes* is the constant $\|\text{Enc}_K(N, A, M)\| - \|M\|$, fixed by the scheme. In this generic syntax, C denotes the full AEAD ciphertext, including any tag material. The TW128 algorithm section (Section 3) writes this same value as $C \parallel T$, with C the ciphertext body and T the root tag.

Correctness. For every $(K, N, A, M) \in \mathcal{K} \times \mathcal{N} \times \mathcal{A} \times \mathcal{M}$, $\text{Dec}_K(N, A, \text{Enc}_K(N, A, M)) = M$.

Privacy, integrity, and all-in-one AE. We use the standard nonce-based security notions, stated concretely for TW128 in Section 4.1. *Privacy* (IND-\$-CPA) is the distinguishing advantage $\text{Adv}_{\text{SE}}^{\text{priv}}(\mathcal{A})$ between the real encryption oracle Enc_K and a random-output oracle Rand that returns a fresh uniform byte string of the ciphertext length on each query, over nonce-respecting adversaries. *Ciphertext integrity* (INT-CTXT) is the winning probability $\text{Adv}_{\text{SE}}^{\text{int-ctxt}}(\mathcal{A})$ in the game that grants $\mathcal{A}$ the oracles Enc_K and a verification oracle Ver_K and declares a win when some verification query accepts a tuple (N, A, C) not produced by Enc_K ; no nonce uniqueness is imposed. *All-in-one AE* [RS06], instantiated for nonce-based AE following [BT16], combines the two into a single experiment that grants either $(\text{Enc}_K, \text{Ver}_K)$ or the ideal pair $(\text{Rand}, \text{Replay})$, where Replay accepts exactly the tuples Rand produced, and defines $\text{Adv}_{\text{SE}}^{\text{ae}}(\mathcal{A})$ as the distinguishing advantage between them over nonce-respecting adversaries.

Lemma 1 (Bellare–Namprempre Composition). *For every adversary $\mathcal{A}$ against the all-in-one AE security of SE, there exist adversaries $\mathcal{A}_{\text{priv}}$ and $\mathcal{A}_{\text{int-ctxt}}$ with the same resources as $\mathcal{A}$ such that*

$$\text{Adv}_{\text{SE}}^{\text{ae}}(\mathcal{A}) \leq \text{Adv}_{\text{SE}}^{\text{priv}}(\mathcal{A}_{\text{priv}}) + \text{Adv}_{\text{SE}}^{\text{int-ctxt}}(\mathcal{A}_{\text{int-ctxt}}).$$

Lemma 1 is the all-in-one form of the privacy-plus-integrity composition theorem of [BN00]. The standard proof inserts the hybrid $(\text{Enc}_K, \text{Replay})$, where Replay accepts exactly the tuples recorded by the real encryption oracle. The hop from $(\text{Enc}_K, \text{Ver}_K)$ to $(\text{Enc}_K, \text{Replay})$ is bounded by INT-CTXT: the two interfaces differ only if verification accepts a tuple not previously recorded by encryption. The hop from $(\text{Enc}_K, \text{Replay})$ to $(\text{Rand}, \text{Replay})$ is bounded by privacy: $\mathcal{A}_{\text{priv}}$ runs $\mathcal{A}$, forwards encryption queries to its own oracle, records the returned tuples, and answers verification queries by replay-table lookup. The lemma is applied in the random-oracle model in the proof of Theorem 1.

2.4 Multi-User Indistinguishability

The multi-user indistinguishability notion of [BT16, Fig. 3] is the multi-user lift of the single-user all-in-one notion of Section 2.3. The number of users u is adversary-determined:

it is the number of **New** queries the adversary makes, i.e., the final value of the user counter v in the game below. A challenge bit $b \leftarrow \{0, 1\}$ selects between the real construction interface (real ciphertexts, real verification) and an ideal interface (uniform strings of matching length, verification that accepts only previously-issued encryption tuples). The adversary also accesses a public primitive interface: the real permutation (π, π^{-1}) in the real world and the simulator $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$ in the ideal world. The adversary outputs a guess b' and wins if $b' = b$.

Game and advantage. The game $\text{G}_{\text{SE}}^{\text{mu-ind}}(\mathcal{A})$ of [BT16, Fig. 3] samples $b \leftarrow \{0, 1\}$ and maintains a user counter v , a set V of (d, N) pairs already used by encryption, and a set W of recorded encryption tuples; its **New**, **Enc**, and **Vf** oracles, together with the public primitive interface—the real permutation when $b = 1$ and the simulator when $b = 0$ —are instantiated for TW128 in Section 4.4. We write the user index as d and the associated-data input as A , where [BT16] writes i and H , and take the absolute value of their signed advantage so that

$$\text{Adv}_{\text{SE}}^{\text{mu-ind}}(\mathcal{A}) = |2 \Pr[\text{G}_{\text{SE}}^{\text{mu-ind}}(\mathcal{A}) \text{ returns } 1] - 1| = |\Pr[\mathcal{A}^{\text{Enc}, \text{Vf}, b=1} \Rightarrow 1] - \Pr[\mathcal{A}^{\text{Enc}, \text{Vf}, b=0} \Rightarrow 1]|,$$

the second equality holding because b is uniform. Thus $\text{Adv}_{\text{SE}}^{\text{mu-ind}}$ is the two-game distinguishing advantage between the real (**Enc**, **Ver**) pair and the ideal (**Rand**, **Replay**) pair instantiated per user. The single-user case $u = 1$ recovers the all-in-one AE notion of Section 2.3, augmented with the public primitive interface (the real permutation in the real world and the simulator in the ideal world).

Per-user nonce uniqueness. Nonce uniqueness is enforced per user via the set V : the same nonce may appear under distinct users but not twice under the same user. This is strictly weaker than the global nonce-uniqueness requirement that would force every (d, N) pair across all users to be unique.

2.5 Committing and Context-Discoverability Notions

[BH22] formalize a family of committing-security notions for nonce-based AEAD schemes, parameterized by how much of the encryption input is committed and by whether commitment is established through decryption (the D-notions) or through encryption agreement (the E-notions). We recall their definitions and the s -way generalization, the complementary *context-discoverability* notion of [MLGR23], and then frame the root tag itself as a hash function whose [RS04] security—collision, second-preimage, and preimage resistance—captures the binding and preimage facets of the tag as a compact commitment and yields the [BH22] committing notions as a consequence.

What-is-committed functions. For $\ell \in \{1, 3, 4\}$, the *what-is-committed* function WiC_ℓ projects an encryption input $(K, N, A, M) \in \mathcal{K} \times \mathcal{N} \times \mathcal{A} \times \mathcal{M}$ to the portion it should commit:

$$\begin{aligned} \text{WiC}_1(K, N, A, M) &= K, \\ \text{WiC}_3(K, N, A, M) &= (K, N, A), \\ \text{WiC}_4(K, N, A, M) &= (K, N, A, M). \end{aligned}$$

CMTDs- ℓ and CMTs- ℓ games. For $s \geq 2$, [BH22, Fig. 5] defines the s -way committing games on tuples $(K_i, N_i, A_i, M_i)_{i=1}^s$ with pairwise distinct WiC_ℓ -images, all entries in the scheme's syntactic domain and none equal to $\perp$. The s -way CMTDs- ℓ (decryption) game has the adversary output a ciphertext C alongside the tuples and returns 1 if $\text{Dec}_{K_i}(N_i, A_i, C) = M_i$ for every i ; the s -way CMTs- ℓ (encryption) game has the adversary

output the tuples alone and returns 1 if all encryptions $\text{Enc}_{K_i}(N_i, A_i, M_i)$ are equal. Advantages $\text{Adv}_{\text{SE}}^{\text{CMTDs-}\ell}(\mathcal{A})$ and $\text{Adv}_{\text{SE}}^{\text{CMTs-}\ell}(\mathcal{A})$ are the probabilities that the adversary wins the respective game; the parameter s is suppressed from the notation when clear from context. The two-tuple case $s = 2$ is the original CMTD- ℓ /CMT- ℓ pair of [BH22, Fig. 4]. These definitions are instantiated for TW128 in Section 4.1, with the public-permutation lift deferred to that section.

The root tag as a hash. Many uses of commitment store, transmit, or compare a short tag rather than the full ciphertext, and ask that the short string alone be binding—the compactly committing AEAD goal introduced by [GLR17] for message franking. TW128 ciphertexts are written $C \parallel T$ with T the τ_{root} -bit root tag, and we capture this goal directly, by treating the map from the encryption input to the tag as a hash function: write $H(K, N, A, M)$ for the root tag T of $\text{Enc}_K(N, A, M) = C \parallel T$, the TW128 wrapper that discards the ciphertext body and returns only the tag. Keyed by the permutation, this is a hash family, and we ask that it satisfy the standard security notions of [RS04], over the TW128 input domain:

Collision resistance (Coll). No adversary finds distinct inputs $X_1, \dots, X_s$ (any $s \geq 2$) with $H(X_1) = \dots = H(X_s)$.

Always-second-preimage resistance (aSec). For the fixed deployed permutation, given a challenge input X , no adversary finds $X' \neq X$ with $H(X') = H(X)$.

Preimage resistance (Pre). For a target tag T^* fixed in advance, no adversary finds X with $H(X) = T^*$.

Their advantages $\text{Adv}_{\text{TW128}}^{\text{Coll}}$, $\text{Adv}_{\text{TW128}}^{\text{aSec}}$, $\text{Adv}_{\text{TW128}}^{\text{Pre}}$ are the respective success probabilities, instantiated for TW128 in Section 4.1. Coll is the binding facet and Pre the preimage facet of the tag taken as a compact commitment to (K, N, A, M) —the two guarantees a cryptographic hash commitment provides. Of the [RS04] second-preimage notions, collision resistance already implies the everywhere and average-case forms (eSec and Sec), so we prove the always-form aSec, the one it does not imply, and with a sharper bound. Collision resistance moreover gives the [BH22] committing notions directly: a single ciphertext that two contexts both decrypt is a fortiori a pair of distinct inputs sharing a tag, so Coll bounds CMTDs- ℓ and CMTs- ℓ (Section 5.3).

Relations. [BH22, Figs. 4 and 5] record the implications among the notions. For the D-notions we use:

$$\text{CMTDs-4} \Rightarrow \text{CMTDs-}\ell \text{ for } \ell \in \{1, 3\}$$

(both immediate: pairwise distinct keys ($\ell = 1$) or pairwise distinct (K, N, A) triples ($\ell = 3$) are *a fortiori* pairwise distinct full tuples, so every CMTDs- ℓ winner is a CMTDs-4 winner). The E-notions are bounded directly in Section C by the same final-root candidate-collision argument, rather than through an encryption reduction.

Context discoverability. Where committing security forbids two contexts from colliding on one ciphertext, *context discoverability* [MLGR23] forbids an adversary from *finding* a decrypting context for a target ciphertext: it is to committing security what preimage resistance is to collision resistance. [MLGR23, Fig. 5] formalize it as the game $\text{CDY}[\text{ts}, S]$, in which a query-independent context selector S —a randomized algorithm taking no input—produces a target ciphertext together with the context components named by a target specifier $\text{ts} \subseteq \{k, n, a\}$, and the adversary, given the revealed components, supplies the remaining components of a decryption context (K, N, A) and wins if the target ciphertext decrypts under it without error. The *restricted* notion $\text{CDY}^*[\text{ts}]$ takes the worst case over

selectors S ; its three per-component variants CDY_k^* , CDY_n^* , CDY_a^* pin two of the three context components and have the adversary supply the third ($\text{ts} = \{n, a\}, \{k, a\}, \{k, n\}$ respectively). In every variant the selector fixes the *entire* target ciphertext. [MLGR23] show that schemes which delegate authenticity to a non-preimage-resistant MAC, including CCM, EAX, SIV, GCM, and OCB3, admit efficient discoverability attacks; the preimage character of the notion is what makes TW128’s root tag, a sponge output, resist them.

The preimage resistance of H (Pre, above) is the tag-level preimage guarantee that the [MLGR23] context-discoverability notion is the ciphertext-level counterpart of; the two are distinct, and TW128 is shown to satisfy both (Theorems 5 and 6).

3 The TW128 Construction

3.1 Design Overview

TW128 is a nonce-based authenticated-encryption scheme with associated data, built as a two-level tree of duplex objects over the KECCAK- $p[1600, 12]$ permutation. A single *root* duplex, initialized with the key K and nonce N , absorbs the associated data A when it is nonempty, emits keystream for the first plaintext chunk M_0 of at most β bytes, and absorbs the resulting ciphertext chunk C_0 ; when A is empty the associated-data phase is elided and the initialization call itself emits the initial M_0 keystream; the remaining plaintext is partitioned into *leaf* chunks $M_1, \dots, M_n$, each handled by an independent leaf duplex initialized with (K, N, j) . The leaf duplex emits the keystream for M_j , absorbs the resulting ciphertext chunk C_j , and produces a τ_{leaf} -bit leaf tag T_j . When $n \geq 1$ the leaf tags, together with the eight-byte little-endian leaf count $\langle n \rangle_8$, are absorbed into the root duplex, which emits a single τ_{root} -bit root tag T ; when $n = 0$ the aggregation phase is elided and the closing message-phase call of the root chunk emits T directly, mirroring the way a leaf duplex emits its leaf tag. The construction is depicted in Figure 1.

Three design properties motivate the tree shape. First, the leaf duplexes operate on disjoint state and consume disjoint inputs once (K, N) is fixed, so leaves $1, \dots, n$ can be evaluated in parallel across SIMD lanes; Section 9 quantifies the resulting throughput on AMD64 and ARM64 hardware. Second, every duplex operates on a bounded 1600-bit state regardless of message length, and the leaf tags are aggregated as a stream rather than buffered in full (Section 3.5), so the working memory is constant in $\|M\|$ at a fixed degree of parallelism, scaling only with the number of leaves evaluated simultaneously. Third, the explicit aggregation of leaf tags through a single deterministic root transcript gives the construction its commitment-security guarantees: by Opening Triple Separation (Proposition 1 and § 8), distinct (K, N, A) triples force distinct final root transcripts before aggregation values matter, the structural fact behind the CMTDs-4 headline of Section 5.3. Collision resistance of the root-tag wrapper (Theorem 3) treats the emitted root tag as the commitment string, distinct bodies merging only through its leaf tag collision term, and the same root tag, preimage-resistant as a sponge output, gives the preimage headline (Theorem 5).

3.2 Parameters and Domain

Table 2 lists the user-visible and derived scheme parameters. The implementation uses the same byte length for the root tag and each leaf tag, but the proofs of Sections 7 and 8 keep τ_{root} and τ_{leaf} as separate symbols.

The bound $M_{\text{max}} = 8183 \cdot 2^{64}$ bytes is the largest plaintext whose leaf index fits in $\langle \cdot \rangle_8$: writing $\text{leaves}(M) = \max(0, \lceil \|M\|/\beta \rceil - 1)$, every supported plaintext satisfies $0 \leq \text{leaves}(M) \leq 2^{64} - 1$, so leaf indices lie in $\{1, \dots, 2^{64} - 1\}$. The associated-data bound A_{max} is a fixed scheme parameter taken equal to M_{max} unless stated otherwise. Inputs




Figure 1: Schematic of TW128 for $n \geq 1$ leaves. The root duplex (bottom row) is initialized with (K, N) and absorbs in turn the associated data A , the root ciphertext chunk C_0 , each leaf tag $T_1, \dots, T_n$, and the eight-byte little-endian leaf count $\langle n \rangle_s$; it emits the root tag T . Each leaf duplex (top row) is initialized with (K, N, j) , emits keystream for plaintext chunk M_j , absorbs the resulting ciphertext chunk C_j , and produces T_j . Leaves can be evaluated in parallel. The ciphertext chunks $C_0, C_1, \dots, C_n$ are obtained by XORing the keystream emitted by the corresponding duplex with the plaintext chunks $M_0, M_1, \dots, M_n$. When $n = 0$ the diagram reduces to the bottom row without any T_j boxes or aggregation block: the aggregation phase is elided and the closing message-phase call on C_0 emits the root tag T directly. When the associated data is empty the A block is absent: the associated-data phase is elided and the initialization call emits the initial M_0 keystream directly.

exceeding these bounds are outside the scheme domain; every game in Section 4 rejects domain-violating queries.

The derived per-call absorption bound ρ follows the [BDPVA11] analysis: with $r = 1344$ and pad10^*1 padding, $\rho_{\max}(\text{pad10}^*1, r) = r - 2 = 1342$ bits. The byte-aligned data field shares this allotment with the four-bit phase suffix of Section 3.4, so ρ is the largest integer satisfying $8\rho + 4 \leq 1342$, giving $\rho = 167$ data bytes (and $8\rho + 4 = 1340 \leq 1342$).

3.3 Parameter Choice Rationale

The four free parameters c , k , $\tau_{\text{root}} = \tau_{\text{leaf}}$, and β (the rate $r = b - c$ is then determined by the capacity) are chosen to give 128-bit single-key security against every term of the concrete bounds derived in Section 5.4 while keeping per-byte cost low; the nonce width ν is fixed separately, by the headroom the wide permutation affords. Specifically:

- $c = 256$. The dominant single-key term is the [BDPVA08] flat-sponge loss

$$\text{Lift}_c(N_{\text{tot}}) = N_{\text{tot}}(N_{\text{tot}} + 1)/2^{c+1},$$

which reaches the 2^{-128} threshold at $N_{\text{tot}} \approx 2^{(c-127)/2} \approx 2^{64.5}$ KECCAK- $p[1600, 12]$ calls; the headline cap of $N_{\text{tot}} \leq 2^{63}$ used in Section 5.5 keeps this term at most $2^{-131} + 2^{-194}$, and hence below 2^{-130} . Setting $c = 256$ thereby delivers 128-bit single-key security on this term. Under the mu-ind bound of Section 5.3 the per-user security margin degrades by $\log D$ bits in D users; the concrete D -indexed envelope appears in Section 5.5.

- $r = 1344$. With state width $b = 1600$ fixed by the KECCAK- $p[1600, 12]$ choice, $r = b - c = 1344$ is the largest rate compatible with the chosen capacity. The 12-round KECCAK- $p[1600, 12]$ permutation matches KangarooTwelve’s choice [BDP⁺16],

Table 2: TW128 parameters.

Parameter	Value	Description
k	256	Key length (bits)
ν	256	Nonce length (bits)
τ_{root}	256	Root tag length (bits)
τ_{leaf}	256	Leaf tag length (bits)
β	8183	Plaintext chunk size (bytes)
M_{max}	$8183 \cdot 2^{64}$ bytes	Maximum plaintext length
A_{max}	$8183 \cdot 2^{64}$ bytes	Maximum associated-data length
b	1600	Permutation state width (bits)
n_r	12	Permutation rounds
r	1344	Sponge rate (bits)
c	256	Sponge capacity (bits)
ρ	167	Maximum byte-aligned absorption per duplex call (bytes)

with a substantial cryptanalytic safety margin relative to the 24-round version used in SHA-3 [Nat15].

- $\tau_{\text{root}} = \tau_{\text{leaf}} = 256$. Matching the capacity ensures that the per-tag collision terms in the authenticity and committing bounds (Section 5.4) are dominated by the capacity birthday rather than the tag length.
- $k = 256$. Matching the capacity ensures that the per-user key guess

$$\text{KeyGuess}_k(N_{\text{prim}}) = N_{\text{prim}}/2^k$$

remains below the capacity birthday at the target D of Section 5.5.

- $\beta = 8183$. The chunk size is set to $49\rho = 49 \cdot 167$ bytes, the largest multiple of the per-call absorption bound ρ not exceeding 2^{13} bytes. Taking β to be an exact multiple of ρ makes every full leaf split into exactly 49 fully utilized message duplex calls with no short final block, so a full leaf costs one initialization duplex call plus 49 message duplex calls. This amortizes the fixed per-leaf initialization cost over a large chunk while keeping the leaf state working set ($8183 < 2^{13}$ bytes) small enough for L1 cache; Section 9.3 reports the resulting cycles-per-byte figures.
- $\nu = 256$. The nonce width is not constrained by the concrete bounds, which assume a nonce-respecting adversary; it is set generously because the wide permutation makes a wide nonce nearly free. The root initialization absorbs $p_{\text{root}} \parallel K \parallel N$, 560 bits in all, in a single duplex call, comfortably within the 1336-bit ($\rho = 167$ -byte) data field (Section 3.2), so widening the nonce to 256 bits adds neither a permutation call nor any per-message cost. The width also removes any practical concern over random-nonce collisions: a uniformly random 256-bit nonce repeats over q messages with probability at most $(q/2)/2^{256}$, negligible at the work cap of Section 5.5. Deployments that do not require a full-width random nonce lose nothing by the choice: a narrower nonce—a 96-bit packet counter, say—is carried in the fixed ν -bit field by zero-padding, so a single mode serves both random-nonce and counter-based settings with no change of parameters.

3.4 Domain Separation

Distinct duplex instances and distinct phases within a duplex are kept separate at the transcript level by two mechanisms. First, the initialization strings carry a 6-byte ASCII

prefix and, for leaves, an eight-byte little-endian chunk index:

$$p_{\text{root}} = \text{"TW128R"} \in \{0, 1\}^{48},$$

$$p_{\text{leaf}} = \text{"TW128L"} \in \{0, 1\}^{48}.$$

The root duplex's first absorbed string is $p_{\text{root}} \parallel K \parallel N$, and the j -th leaf duplex's first absorbed string is $p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8$. Together with the fixed k -bit and ν -bit widths of K and N , these prefixes separate root from leaf transcripts and distinguish leaves with different chunk indices.

Second, every byte-aligned absorption carries a four-bit phase suffix. We identify each suffix with the four-bit string given by its Table 3 value written least-significant-bit first, so that a duplex call absorbing a byte-aligned block σ under a phase suffix σ_{ph} feeds the duplex interface of Section 2.2 the input $\sigma \parallel \sigma_{\text{ph}}$ before `pad10*1` padding. The seven phase suffixes are summarized in Table 3; they correspond to initialization, non-final and final associated-data blocks, non-final and final message blocks, and non-final and final aggregation blocks. The seven values are pairwise distinct, so any two transcripts that differ in the phase of any block also differ in the flattened sponge input.

Table 3: Phase suffixes (4 bits each, appended LSB-first).

Name	Hex	Use
σ_{init}	0xC	End of initialization (the sole init call)
σ_{ad}^-	0x9	Non-final associated-data block
σ_{ad}^+	0xD	Final associated-data block
σ_{msg}^-	0xA	Non-final message block
σ_{msg}^+	0xE	Final message block
σ_{agg}^-	0xB	Non-final aggregation block
σ_{agg}^+	0xF	Final aggregation block (emits root tag)

The combined effect of the initialization prefixes and the phase suffixes is that the flattened sponge input of any TW128 duplex call uniquely determines the duplex instance, the leaf index when applicable, the phase, and the duplex-call position within that phase. Definition 1 (Well-formed TW128 transcript prefixes), Lemma 5 (Transcript Injectivity), and its structural corollaries formalize this parsing fact for the proofs of Sections C and 6 to 8.

3.5 Encryption

Algorithm 2 specifies $\text{Enc}_K(N, A, M)$ in terms of two helper procedures, `ABSORB` and `STREAMENC`, defined in Algorithm 1. `ABSORB` drives a duplex through a sequence of blocks of a byte string with non-final σ^- and final σ^+ suffix tags, returning the output of the final call; the empty-input case yields a single empty block carrying the σ^+ tag. The streaming helpers use the same empty-input convention, so a zero-length chunk still performs one final message-phase duplex call and returns a zero-length body. Algorithm 2 invokes `ABSORB` for the associated-data phase only when $A \neq \varepsilon$; when $A = \varepsilon$ the phase is elided and the root σ_{init} call emits the initial M_0 keystream directly. `STREAMENC` encrypts a plaintext byte string block by block, XORing each plaintext block with the current keystream, absorbing the resulting ciphertext block back into the duplex with the appropriate phase tag, and using the duplex's output as the next keystream. This is the duplex-level presentation of the overwrite mechanism of [BDPVA11, §6.2 and Algorithm 5]: when the current rate prefix emitted as keystream is Z , XOR-absorbing $m \oplus Z$ has the same update on the message bytes as overwriting that prefix with m , with the phase tag still carried as part of the duplex input. The decryption helper `STREAMDEC` is identical

Algorithm 1 TW128 helper procedures.

```

1: procedure ABSORB( $D, s, \sigma^-, \sigma^+, \ell$ )
2:   Partition  $s$  into byte blocks  $s_1, \dots, s_t$  of exactly  $\rho$  bytes each, except that the last
   block may be shorter, with  $t \geq 1$  (the empty case yields the single empty block  $s_1 = \varepsilon$ ).
3:   for  $i \leftarrow 1$  to  $t - 1$  do
4:      $D.\text{duplexing}(s_i \parallel \sigma^-, 0)$ 
5:   end for
6:   return  $D.\text{duplexing}(s_t \parallel \sigma^+, \ell)$ 
7: end procedure

8: procedure STREAMENC( $D, m, Z, \sigma^-, \sigma^+, \ell$ )
9:   Partition  $m$  into byte blocks  $m_1, \dots, m_t$  of exactly  $\rho$  bytes each, except that the
   last block may be shorter, with  $t \geq 1$  (if  $m = \varepsilon$ , set  $t = 1$  and  $m_1 = \varepsilon$ ).
10:  for  $i \leftarrow 1$  to  $t - 1$  do
11:     $c_i \leftarrow m_i \oplus Z$ 
12:     $Z \leftarrow D.\text{duplexing}(c_i \parallel \sigma^-, 8\|m_{i+1}\|)$ 
13:  end for
14:   $c_t \leftarrow m_t \oplus Z$ 
15:   $Z' \leftarrow D.\text{duplexing}(c_t \parallel \sigma^+, \ell)$ 
16:  return  $(c_1 \parallel \dots \parallel c_t, Z')$ 
17: end procedure

```

to STREAMENC with the roles of the plaintext and ciphertext blocks exchanged: it takes ciphertext blocks c_i as input, recovers each plaintext block as $m_i = c_i \oplus Z$, absorbs the same c_i under the same phase suffix, and returns $(m_1 \parallel \dots \parallel m_t, Z')$; we omit its pseudocode. In both helpers, each duplex call absorbs a data block followed by its phase suffix— σ^- for a non-final block and σ^+ for the final block—and requests the output bits the caller consumes next: ℓ (possibly zero) on the final call, and the next block’s keystream length on non-final calls. Each call is the duplex interface of Section 2.2 applied to the suffixed input of Section 3.4.

The encryption procedure (Algorithm 2) instantiates the root duplex and obtains the initial keystream for the root chunk M_0 : when $A \neq \varepsilon$ it absorbs the associated data A , and when $A = \varepsilon$ it elides the associated-data phase and takes the keystream from the σ_{initcall} itself. It then encrypts M_0 while absorbing the resulting ciphertext chunk C_0 . When $n = 0$ the closing σ_{msg}^+ call of this root chunk requests τ_{root} output bits, which are the root tag T , and the aggregation phase is elided. When $n \geq 1$ it independently encrypts each leaf chunk M_j while absorbing C_j , producing the leaf tag T_j ; the leaf tags together with $\langle n \rangle_8$ are then absorbed into the root duplex, and the final σ_{agg}^+ call emits the root tag T . The ciphertext is the concatenation $C_0 \parallel C_1 \parallel \dots \parallel C_n$. Thus this section writes C for the ciphertext body and $C \parallel T$ for the full AEAD ciphertext returned by $\text{Enc}_K(N, A, M)$.

The keystream bit length requested for the first message block of M_0 is $8 \min(\|M_0\|, \rho)$, eight times the size of the next message block. It is emitted by the closing σ_{ad}^+ call when $A \neq \varepsilon$, and by the root σ_{initcall} itself when $A = \varepsilon$ and the associated-data phase is elided. Each leaf’s σ_{initcall} likewise emits $8 \min(\|M_j\|, \rho)$ keystream bits for M_j , so the empty-associated-data root σ_{initcall} plays exactly the role a leaf σ_{initcall} already plays. When the corresponding chunk is empty, the requested keystream length is zero and the next message-phase duplex call absorbs the empty ciphertext block carrying σ_{msg}^+ . The final σ_{msg}^+ call in the root chunk requests τ_{root} output bits when $n = 0$, namely the root tag T emitted by the elided-aggregation path, and zero output bits when $n \geq 1$ because the next duplex operation on the root is then the first aggregation block; the corresponding call on a leaf requests τ_{leaf} bits, namely the leaf tag. When $n \geq 1$ the final σ_{agg}^+ call requests

Algorithm 2 $\text{Enc}_K(N, A, M)$.**Require:** $K \in \{0, 1\}^k$, $N \in \{0, 1\}^\nu$, A with $\|A\| \leq A_{\max}$, M with $\|M\| \leq M_{\max}$.**Ensure:** $C \parallel T$ with $\|C\| = \|M\|$ and $T \in \{0, 1\}^{\tau_{\text{root}}}$.

```

1:  $M_0 \leftarrow$  first  $\min(\|M\|, \beta)$  bytes of  $M$  (possibly  $\varepsilon$ ).
2: Partition the remaining suffix into chunks  $M_1, \dots, M_n$  of exactly  $\beta$  bytes each, except
   that the last chunk may be shorter but nonempty, so  $n = \text{leaves}(M)$ .
3:  $D_{\text{root}} \leftarrow$  new Duplex
4: if  $A = \varepsilon$  then
5:    $Z \leftarrow D_{\text{root}}.\text{duplexing}(p_{\text{root}} \parallel K \parallel N \parallel \sigma_{\text{init}}, 8 \min(\|M_0\|, \rho))$ 
6: else
7:    $D_{\text{root}}.\text{duplexing}(p_{\text{root}} \parallel K \parallel N \parallel \sigma_{\text{init}}, 0)$ 
8:    $Z \leftarrow \text{ABSORB}(D_{\text{root}}, A, \sigma_{\text{ad}}^-, \sigma_{\text{ad}}^+, 8 \min(\|M_0\|, \rho))$ 
9: end if
10: if  $n = 0$  then
11:    $(C_0, T) \leftarrow \text{STREAMENC}(D_{\text{root}}, M_0, Z, \sigma_{\text{msg}}^-, \sigma_{\text{msg}}^+, \tau_{\text{root}})$ 
12:   return  $C_0 \parallel T$ 
13: end if
14:  $(C_0, \_) \leftarrow \text{STREAMENC}(D_{\text{root}}, M_0, Z, \sigma_{\text{msg}}^-, \sigma_{\text{msg}}^+, 0)$ 
15: for  $j \leftarrow 1$  to  $n$  in parallel do
16:    $D_j \leftarrow$  new Duplex
17:    $Z_j \leftarrow D_j.\text{duplexing}(p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8 \parallel \sigma_{\text{init}}, 8 \min(\|M_j\|, \rho))$ 
18:    $(C_j, T_j) \leftarrow \text{STREAMENC}(D_j, M_j, Z_j, \sigma_{\text{msg}}^-, \sigma_{\text{msg}}^+, \tau_{\text{leaf}})$ 
19: end for
20:  $G \leftarrow T_1 \parallel \dots \parallel T_n$ .
21:  $T \leftarrow \text{ABSORB}(D_{\text{root}}, G \parallel \langle n \rangle_8, \sigma_{\text{agg}}^-, \sigma_{\text{agg}}^+, \tau_{\text{root}})$ 
22: return  $C_0 \parallel C_1 \parallel \dots \parallel C_n \parallel T$ 

```

561 τ_{root} bits, which is the root tag T .

562 The leaf loop is annotated **in parallel** to make explicit that the n leaf computations
 563 are mutually independent; Section 9.1 discusses the SIMD realizations.

564 **Streaming aggregation.** The string $G = T_1 \parallel \dots \parallel T_n$ in Algorithms 2 and 3 names the
 565 leaf tags only for specification. The closing **ABSORB** consumes $G \parallel \langle n \rangle_8$ as ρ -byte blocks in
 566 leaf order and advances the root state after each, so an implementation need not hold G
 567 in full: it can absorb each leaf tag, or each SIMD batch of leaf tags, into the root as the
 568 corresponding leaves complete, buffering only a bounded number of tags at a time. With
 569 the bounded 1600-bit state of every duplex, this keeps the working memory constant in
 570 $\|M\|$ for a fixed degree of parallelism, growing only with the number of leaves evaluated at
 571 once rather than with the message length; Section 9.1 describes the batched realization.

572 3.6 Decryption

573 Algorithm 3 specifies $\text{Dec}_K(N, A, C \parallel T)$. The procedure mirrors **Enc** block for block:
 574 each ciphertext block c_i is absorbed into the appropriate duplex (root or leaf) under the
 575 corresponding σ_{msg}^- or σ_{msg}^+ suffix, and the plaintext block is recovered as $m_i = c_i \oplus Z^{(i)}$,
 576 writing $Z^{(i)}$ for the value the running keystream variable Z of **STREAMDEC** holds when
 577 block i is processed ($i < t$ inside the loop, $i = t$ after it), the same value the encryption
 578 procedure would have produced. The procedure absorbs ciphertext bytes before the final
 579 tag comparison, so the verification transcript is determined by (K, N, A, C) for every
 580 in-domain ciphertext, accepting or not. This property is used by the authenticity proof
 581 of Section 7 to argue that encryption-first and verification-first transcript classes are well

Algorithm 3 $\text{Dec}_K(N, A, C \parallel T)$.

Require: K, N, A as in Algorithm 2, ciphertext C with $\|C\| \leq M_{\max}$, candidate tag $T \in \{0, 1\}^{\tau_{\text{root}}}$.

Ensure: M with $\|M\| = \|C\|$, or $\perp$.

```

1:  $C_0 \leftarrow$  first  $\min(\|C\|, \beta)$  bytes of  $C$  (possibly  $\varepsilon$ ).
2: Partition the remaining suffix into chunks  $C_1, \dots, C_n$  of exactly  $\beta$  bytes each, except
   that the last chunk may be shorter but nonempty, so  $n = \text{leaves}(C)$ .
3:  $D_{\text{root}} \leftarrow$  new Duplex
4: if  $A = \varepsilon$  then
5:    $Z \leftarrow D_{\text{root}}.\text{duplexing}(p_{\text{root}} \parallel K \parallel N \parallel \sigma_{\text{init}}, 8 \min(\|C_0\|, \rho))$ 
6: else
7:    $D_{\text{root}}.\text{duplexing}(p_{\text{root}} \parallel K \parallel N \parallel \sigma_{\text{init}}, 0)$ 
8:    $Z \leftarrow \text{ABSORB}(D_{\text{root}}, A, \sigma_{\text{ad}}^-, \sigma_{\text{ad}}^+, 8 \min(\|C_0\|, \rho))$ 
9: end if
10: if  $n = 0$  then
11:    $(M_0, T') \leftarrow \text{STREAMDEC}(D_{\text{root}}, C_0, Z, \sigma_{\text{msg}}^-, \sigma_{\text{msg}}^+, \tau_{\text{root}})$ 
12:   return  $M_0$  if  $T' = T$  (compared in constant time), else  $\perp$ .
13: end if
14:  $(M_0, \_) \leftarrow \text{STREAMDEC}(D_{\text{root}}, C_0, Z, \sigma_{\text{msg}}^-, \sigma_{\text{msg}}^+, 0)$ 
15: for  $j \leftarrow 1$  to  $n$  in parallel do
16:    $D_j \leftarrow$  new Duplex
17:    $Z_j \leftarrow D_j.\text{duplexing}(p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8 \parallel \sigma_{\text{init}}, 8 \min(\|C_j\|, \rho))$ 
18:    $(M_j, T_j) \leftarrow \text{STREAMDEC}(D_j, C_j, Z_j, \sigma_{\text{msg}}^-, \sigma_{\text{msg}}^+, \tau_{\text{leaf}})$ 
19: end for
20:  $G \leftarrow T_1 \parallel \dots \parallel T_n$ .
21:  $T' \leftarrow \text{ABSORB}(D_{\text{root}}, G \parallel \langle n \rangle_8, \sigma_{\text{agg}}^-, \sigma_{\text{agg}}^+, \tau_{\text{root}})$ 
22: if  $T' = T$  (compared in constant time) then
23:   return  $M_0 \parallel M_1 \parallel \dots \parallel M_n$ 
24: else
25:   return  $\perp$ 
26: end if

```

582 defined regardless of the tag-comparison outcome.

583 The $n = 0$ and empty-body cases mirror their encryption counterparts (Section 3.5):
 584 for $n = 0$ the aggregation phase is elided and the closing σ_{msg}^+ call of the root chunk emits
 585 the candidate tag T' directly, and an empty body still performs the single empty σ_{msg}^+ call
 586 of Algorithm 1, requesting τ_{root} output bits.

587 **Correctness.** For every $K \in \{0, 1\}^k$, $N \in \{0, 1\}^\nu$, A with $\|A\| \leq A_{\max}$, and M with
 588 $\|M\| \leq M_{\max}$, $\text{Dec}_K(N, A, \text{Enc}_K(N, A, M)) = M$. This follows by inspection: every duplex
 589 call in Dec_K receives the same input as the corresponding call in Enc_K (each ciphertext
 590 block is absorbed under the same phase tag in both directions), so the duplex states and
 591 the recomputed root tag T' exactly match. The constant-time comparison $T' = T$ succeeds,
 592 and the recovered $m_i = c_i \oplus Z^{(i)} = (m_i \oplus Z^{(i)}) \oplus Z^{(i)} = m_i$ at every position.

593 4 Security Model

594 This section fixes the security model used throughout the paper. The scheme syntax
 595 and the authenticated-encryption and committing-security definitions of Section 2 are
 596 instantiated here for TW128 in the lifted public-permutation model (Section 4.1), and we
 597 define the intermediate random-oracle world through which every bound is first proved

(Section 4.2). Section 4.3 fixes the resource accounting that all later bounds reference, and Section 4.4 instantiates the multi-user indistinguishability game for TW128.

4.1 Public-Permutation Games

The lifted AE-style public-permutation advantages below compare a real execution, with sampled $\pi \leftarrow \$ \text{Perm}(\{0, 1\}^{1600})$ and direct primitive interface (π, π^{-1}) , to a simulator-ideal execution. In the simulator-ideal execution, the construction interface is the ideal interface specified by the game and the public primitive interface is $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$. The simulator $\mathcal{S}^{\text{RO}_{\text{flat}}}$ together with its inverse $\mathcal{S}^{-1, \text{RO}_{\text{flat}}}$ is the public-primitive simulator fixed in Section B; both directions share an internal lazy table for the random oracle RO_{flat} of Section 4.2. INT-CTXT and the committing-security games remain one-world real public-permutation success probabilities; the simulator appears for them only inside the reductions of Section B.

In the real authenticated-encryption games (privacy, INT-CTXT, all-in-one AE), the challenger additionally samples a key $K \leftarrow \$ \{0, 1\}^k$ and exposes the construction oracles $\text{Enc}_K[\pi]$ (the TW128 encryption algorithm of Algorithm 2 with the sampled π) and $\text{Ver}_K[\pi]$, defined by $\text{Ver}_K[\pi](N, A, C, T) = 1$ if $\text{Dec}_K[\pi](N, A, C \parallel T) \neq \perp$ and 0 otherwise. The committing-security games have no challenger-sampled key.

Validity convention. All construction-interface inputs are checked against TW128’s public syntax and domain before any construction computation or construction-internal primitive lookup is performed. An encryption input is valid when $N \in \{0, 1\}^\nu$, A is a byte string with $\|A\| \leq A_{\text{max}}$, and M is a byte string with $\|M\| \leq M_{\text{max}}$. A verification or decryption input is valid when $N \in \{0, 1\}^\nu$, A is a byte string with $\|A\| \leq A_{\text{max}}$, and the full ciphertext parses as $C \parallel T$ with $\|C\| \leq M_{\text{max}}$ and $T \in \{0, 1\}^{\tau_{\text{root}}}$. In the hash and committing games, each submitted input (K, N, A, M) must be a valid encryption input including $K \in \{0, 1\}^k$, and a submitted CMTDs ciphertext must be a valid verification/decryption ciphertext. Invalid encryption queries are rejected and not recorded, invalid verification queries return 0, and invalid committing-game outputs make the game return 0. Such rejected inputs contribute no construction cost and create no construction transcripts. Throughout, an *accepted* encryption query is one that passes this validity check and any game-specific nonce or user check.

Privacy. The privacy game compares the real encryption interface with the fresh output oracle Rand that, on every accepted query (N, A, M) , returns a uniformly random byte string of length $\|M\| + \tau_{\text{root}}/8$. The adversary is *nonce-respecting*: no two encryption queries may share a nonce, and a query that repeats an earlier nonce is rejected and not recorded.

$$\text{Adv}_{\text{TW128}}^{\text{priv}}(\mathcal{A}) = |\Pr[\mathcal{A}^{\text{Enc}_K[\pi], \pi, \pi^{-1}} \Rightarrow 1] - \Pr[\mathcal{A}^{\text{Rand}, \mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}}} \Rightarrow 1]|.$$

Ciphertext integrity (INT-CTXT). The INT-CTXT game exposes encryption, verification, and the public permutation interfaces π, π^{-1} . Each encryption query records the resulting tuple (N, A, C, T) . The adversary wins if some verification query returns 1 on a tuple (N, A, C, T) that was not previously recorded by the encryption oracle.

$$\text{Adv}_{\text{TW128}}^{\text{int-ctxt}}(\mathcal{A}) = \Pr[\mathcal{A}^{\text{Enc}_K[\pi], \text{Ver}_K[\pi], \pi, \pi^{-1}} \text{ wins}].$$

No nonce uniqueness is imposed.

All-in-one AE. The all-in-one authenticated-encryption game [RS06] replaces the construction interface by the ideal pair (Rand, Replay). On each accepted encryption query (N, A, M) , Rand samples a uniformly random byte string of length $\|M\| + \tau_{\text{root}}/8$, parses it as $C \parallel T$ with $T \in \{0, 1\}^{\tau_{\text{root}}}$, records (N, A, C, T) , and returns $C \parallel T$. The oracle Replay returns 1 exactly on recorded tuples (N, A, C, T) and 0 otherwise. The adversary is nonce-respecting on encryption queries.

$$\text{Adv}_{\text{TW128}}^{\text{ae}}(\mathcal{A}) = \left| \Pr[\mathcal{A}^{\text{Enc}_K[\pi], \text{Ver}_K[\pi], \pi, \pi^{-1}} \Rightarrow 1] - \Pr[\mathcal{A}^{\text{Rand, Replay}, \mathcal{S}^{\text{ROflat}}, \mathcal{S}^{-1, \text{ROflat}} \Rightarrow 1] \right|.$$

This lifted all-in-one AE advantage is the headline target of Section 5.3: a Bellare–Namprempre composition (Lemma 1) applied in the random-oracle model to derived privacy and INT-CTXT adversaries, combined with the flat-sponge lift, bounds it via the privacy and INT-CTXT envelopes of Section 5.2; the precise bound is Theorem 1.

Hash games. The collision, second-preimage, and preimage games for the wrapper H (Section 2.5) have no challenger-sampled key; all inputs are adversary-supplied. In the s -way collision game the adversary outputs s inputs, and the challenger returns 1 iff they are pairwise distinct, in the TW128 domain, and share a root tag:

$\pi \leftarrow \$ \text{Perm}(\{0, 1\}^{1600}), \quad (K_i, N_i, A_i, M_i)_{i=1}^s \leftarrow \$ \mathcal{A}^{\pi, \pi^{-1}},$
 return 0 unless the inputs are pairwise distinct and in the TW128 domain,
 return $[\text{H}[\pi](K_1, N_1, A_1, M_1) = \dots = \text{H}[\pi](K_s, N_s, A_s, M_s)]$,

with advantage $\text{Adv}_{\text{TW128}}^{\text{Coll}}(\mathcal{A}) = \Pr[\text{the game returns 1}]$; no nonce uniqueness is imposed. The always-second-preimage (aSec) game samples a challenge input X uniformly from the TW128 domain, gives it to $\mathcal{A}$, and returns 1 iff $\mathcal{A}$ outputs $X' \neq X$ in the domain with $\text{H}(X') = \text{H}(X)$, with advantage $\text{Adv}_{\text{TW128}}^{\text{aSec}}$; following [RS04] the always-notion concerns the fixed permutation, here the deployed instance the public-permutation model represents by a random π . The preimage game fixes a target tag $T^* \in \{0, 1\}^{\tau_{\text{root}}}$ before the primitive sampling and returns 1 iff $\mathcal{A}(T^*)$ outputs an input X in the domain with $\text{H}(X) = T^*$, the advantage $\text{Adv}_{\text{TW128}}^{\text{Pre}}$ taken as the worst case over query-independent targets.

Committing games. The [BH22] committing games are instantiated as in Section 2.5, with no challenger-sampled key. The s -way CMTDs- ℓ (decryption) game has the adversary output a ciphertext $C \parallel T$ and s tuples (K_i, N_i, A_i, M_i) with pairwise distinct WiC_ℓ -images, and returns 1 iff $\text{Dec}_{K_i}[\pi](N_i, A_i, C \parallel T) = M_i$ for every i , with the eager length rejection justified by Algorithm 3 ($\text{Dec}_K(N, A, C)$ returns $\perp$ or a message of length $\|C\|$); its advantage is $\text{Adv}_{\text{TW128}}^{\text{CMTDs-}\ell}(\mathcal{A})$. The CMTs- ℓ (encryption) game has the adversary output the s tuples alone and returns 1 iff the encryptions $\text{Enc}_{K_i}[\pi](N_i, A_i, M_i)$ are all equal; its advantage is $\text{Adv}_{\text{TW128}}^{\text{CMTs-}\ell}(\mathcal{A})$. A CMTDs-4 or CMTs-4 winner’s tuples share a common tag, hence are a collision of H, so Corollary 1 bounds CMTDs-4 through Theorem 9 and Section C forwards the remaining [BH22] notions to the same root-collision bound.

Context discoverability. The [MLGR23, Fig. 5] context-discoverability game (Section 2.5) is a ciphertext-level preimage notion, distinct from the preimage resistance of H above. It is parameterized by a target specifier ts and a query-independent context selector S that produces a target ciphertext C^* and reveals the ts -named components rev of a decryption

context; there is no challenger-sampled key.

```

681  $\pi \leftarrow \$ \text{Perm}(\{0, 1\}^{1600}), \quad (C^*, \text{rev}) \leftarrow \$ S[\pi],$ 
682  $(K, N, A) \leftarrow \$ \mathcal{A}^{\pi, \pi^{-1}}(C^*, \text{rev}),$ 
683 return 0 if  $C^*$  is not a valid TW128 ciphertext, if  $(K, N, A)$  is outside the domain,
684 or if  $(K, N, A)$  disagrees with  $\text{rev}$  on its  $\text{ts}$ -components,
685 return  $[\text{Dec}_K[\pi](N, A, C^*) \neq \perp]$ .

```

The restricted advantage $\text{Adv}_{\text{TW128}}^{\text{CDY}}(\mathcal{A})$ is the worst case over query-independent selectors S , matching $\text{CDY}^*[\text{ts}]$ and, at $\text{ts} = \{n, a\}, \{k, a\}, \{k, n\}$, its per-component variants $\text{CDY}_k^*, \text{CDY}_n^*, \text{CDY}_a^*$. Because the selector holds a hidden context, the TW128 bound (Theorem 6) carries a key-test term that the keyless preimage game of H does not. Section B lifts the hash and committing bounds of Section 8 to the public-permutation statements of Section 5.3.

4.2 The TW128 Random-Oracle Model

The proofs of Sections 6 to 8 and Section C, together with the headline reductions of Section 5.3, are carried out through an intermediate random-oracle model whose construction interfaces use the [BDPVA11] bridge of Section 2.2 to address a single random oracle. The flat-sponge lift of Section B then converts the resulting bounds to the public-permutation form.

The model has a single random oracle $\text{RO}_{\text{flat}} : \{0, 1\}^* \rightarrow \{0, 1\}^\infty$ over the unpadded H -input domain of the [BDPVA08] simple-padded sponge interface, with lazy sampling: each distinct input receives an independent infinite bit string, and repeated queries return the same string. A direct adversary query is finite-output: on input (Y, ℓ) with finite ℓ , the oracle returns the first ℓ bits of the lazy-sampled value for Y .

For a well-formed TW128 duplex transcript prefix X in the language of Definition 1, at one of the construction transcript lookup points formalized by Lemma 7 and Table 9, let $\text{flat}(X) = I[1344, 1344](\text{raw_flat}(X))$ be the bridged image of the native flattened input under the [BDPVA11, Theorem 3] preprocessing map of Section 2.2, and define

$$\text{RF}(X) = \text{RO}_{\text{flat}}(\text{flat}(X)).$$

The construction interfaces $\text{Enc}_K^{\text{RO}}, \text{Dec}_K^{\text{RO}},$ and Ver_K^{RO} are the TW128 algorithms of Section 3 with every root or leaf duplex output replaced by the corresponding requested projection of $\text{RF}(X)$; the projection length is the duplexing call's output parameter ℓ , which may be zero. The bridge and the typed-restriction convention are formalized in Lemma 7; the direct-query key-hit predicate ignores the adversary's requested output length and is formalized as KeyedTWOut in Lemma 7.

The random-oracle-model games are the construction-interface variants of Sections 4.1 and 4.4: the primitive interface is replaced by direct adversary access to RO_{flat} , and each construction oracle uses the corresponding RO algorithm, the ideal oracles ($\text{Rand}, \text{Replay}$) being unchanged. Under this substitution $\text{Adv}_{\text{RO}}^{\text{priv}}, \text{Adv}_{\text{RO}}^{\text{int-ctxt}},$ and $\text{Adv}_{\text{RO}}^{\text{ae}}$ are the Section 4.1 advantages with no simulator on the ideal side; the keyless hash advantages $\text{Adv}_{\text{RO}}^{\text{Coll}}(\mathcal{B}), \text{Adv}_{\text{RO}}^{\text{aSec}}(\mathcal{B}), \text{Adv}_{\text{RO}}^{\text{Pre}}(\mathcal{B})$ of H , the committing $\text{Adv}_{\text{RO}}^{\text{CMTDs-4}}(\mathcal{B})$, and, for $\ell \in \{1, 3, 4\}$, $\text{Adv}_{\text{RO}}^{\text{CMTs-}\ell}(\mathcal{B})$ are the probabilities that the corresponding random-oracle hash and committing games return 1, the CMTs challenger computing its deterministic encryption checks with Enc^{RO} . For mu-ind, $\text{Adv}_{\text{RO}}^{\text{mu-ind}}(\mathcal{B})$ denotes the Section 4.4 game with the same New interface and per-user nonce discipline—user d using $(\text{Enc}_{K_d}^{\text{RO}}, \text{Ver}_{K_d}^{\text{RO}})$ when $b = 1$ and $(\text{Rand}, \text{Replay})$ when $b = 0$ —equivalently, in the two-game notation of Section 2.4,

$$\text{Adv}_{\text{RO}}^{\text{mu-ind}}(\mathcal{B}) = |\Pr[\mathcal{B}^{\text{Real}^{\text{mu}}, \text{RO}_{\text{flat}}} \Rightarrow 1] - \Pr[\mathcal{B}^{\text{Ideal}^{\text{mu}}, \text{RO}_{\text{flat}}} \Rightarrow 1]|,$$

where the superscripts name the entire multi-user construction interface in the corresponding world. Adversary queries to RO_{flat} are finite-output and counted in $q_{\text{RO}}(\mathcal{B})$ of Section 4.3. Construction-internal $\text{RF}(\cdot)$ lookups — those made by Enc_K^{RO} , Dec_K^{RO} , Ver_K^{RO} , or a committing challenger — are not.

4.3 Resources

Adversary resources are measured by fixed, execution-uniform caps on the number and size of oracle queries. An execution-uniform cap is one that holds on every execution path, including over adversary randomness, oracle randomness, and adaptive query choices. Proofs may also introduce local execution-uniform caps, such as q_e for the number of accepted encryption queries, solely to index a finite hybrid sequence. Such local caps are part of the adversary’s fixed query bounds, but they are not listed as envelope parameters unless they affect the final bound.

N : the construction-interface cost, measured as the number of $\text{KECCAK-}p[1600, 12]$ calls that the adversary’s construction-interface queries induce in the real TW128 computation after the validity convention above has been applied. In ideal games, the same accounting applies to the corresponding real TW128 computation on the valid query, even when an ideal oracle answers by table lookup or without running the construction. N counts at per-block granularity, summing each root initialization, associated-data block, root message block, leaf initialization, leaf message block, and aggregation block across the entire query sequence. Valid INT-CTXT verification computations are counted whether they accept or reject. In the hash, committing, and discoverability games there is no adversary construction oracle: for the H collision game, N counts the s deterministic encryptions on the submitted inputs (and the one or two encryptions of the second-preimage and preimage games); for CMTDs- ℓ , N counts only the deterministic decryption checks performed by the challenger on the common ciphertext; for the context-discoverability game, N counts the worst-case selector’s encryption producing C^* together with the single deterministic decryption check the challenger performs on C^* ; while for the CMTs- ℓ source games of Section C, N counts only the deterministic encryption checks actually used by the challenger to compare the s ciphertexts.

N_{prim} : the number of direct adversary queries to the primitive interface (the pair (π, π^{-1}) in public-permutation games; the simulator’s RO_{flat} table is internal and is not exposed to the application adversary in those games).

$N_{\text{tot}} = N + N_{\text{prim}}$: the total query-sequence cost. The flat-sponge lift of Section B is applied at N_{tot} because the indistinguishability replacement sees both the construction-internal sponge calls counted by N and the adversary’s direct primitive-interface queries counted by N_{prim} in one chronological public-primitive transcript.

$q_v(\mathcal{A})$, Q_v : the number of verification queries with valid inputs, and a cap on it. Used in INT-CTXT and absorbed into the AE composition of Section 5.3. Every valid verification query contributes at least one verification/decryption construction call in the N accounting, so $q_v(\mathcal{A}) \leq N$.

$q_{\text{RO}}(\mathcal{B})$, Q_{RO} : the number of direct finite-output queries to RO_{flat} by a random-oracle-model adversary $\mathcal{B}$, and a cap on it. Repeated direct queries on the same Y are counted again. Construction-internal $\text{RF}(\cdot)$ lookups are not counted. After the derived-adversary construction, q_{RO} counts only simulator-induced RO_{flat} calls from the adversary’s direct primitive-interface queries, not the construction calls already counted in N for the flat-sponge lift.

$n_{\text{leaf}}(\mathcal{B})$, N_{leaf} : the number of distinct construction-generated final leaf transcripts in the execution of $\mathcal{B}$, and a cap on it. Distinct final leaf transcripts are generated by valid encryption computations, by valid INT-CTXT verification computations (whether they accept or reject), and by hash, committing, and discoverability challenger construction checks that pass the early validity checks.

For a byte string X ,

$$\text{leaves}(X) = \max(0, \lceil \|X\|/\beta \rceil - 1)$$

counts the leaf chunks induced by a body byte string of length $\|X\|$. Thus n_{leaf} is bounded by the sum of $\text{leaves}(X)$ over the valid construction computations that create final leaf transcripts, where X is the plaintext body for encryption computations and the submitted ciphertext body for verification and committing or discoverability decryption checks. Each distinct final leaf transcript contains a final leaf duplex call counted in N , so $n_{\text{leaf}}(\mathcal{B}) \leq N$ unconditionally. The ratio n_{leaf}/N is largest when most processed bytes lie in leaf chunks, where each full leaf contributes $1 + \beta/\rho = 50$ duplex calls to N per final leaf transcript.

All theorems are stated for adversaries whose execution-uniform caps hold at the stated bounds.

4.4 Multi-User Setting

This subsection instantiates the mu-ind game of [BT16] (Section 2.4) for TW128 in the lifted public-permutation model, using the same ideal-side simulator convention as the single-user AE-style games of Section 4.1. The challenger samples a challenge bit $b \leftarrow \$ \{0, 1\}$. If $b = 1$, it samples a permutation $\pi \leftarrow \$ \text{Perm}(\{0, 1\}^{1600})$ and exposes (π, π^{-1}) as the primitive interface; if $b = 0$, it exposes $(\mathcal{S}^{\text{RO}_{\text{nat}}}, \mathcal{S}^{-1, \text{RO}_{\text{nat}}})$ as the primitive interface. The adversary $\mathcal{A}$ creates users on demand via **New**, and the game maintains an active-user counter v . We write D for an execution-uniform cap on the number of **New** calls. Equivalently, the game may sample independent keys $K_1, \dots, K_D$ at the start of the experiment and let the d -th **New** call activate K_d ; inactive indices are never valid users.

The mu-ind construction oracles inherit the validity convention of Section 4.1. The encryption oracle on input (d, N, M, A) rejects, without recording, if (N, A, M) is outside the TW128 encryption domain, if $d \notin \{1, \dots, v\}$, or if $(d, N) \in V$; otherwise it sets $C = \text{Enc}_{K_d}[\pi](N, A, M)$ when $b = 1$, and samples $C \leftarrow \$ \{0, 1\}^{s\|M\| + \tau_{\text{root}}}$ when $b = 0$. The game records (d, N) in V and (d, N, C, A) in W , and returns C . The verification oracle on input (d, N, C, A) rejects if $d \notin \{1, \dots, v\}$ or if (N, A, C) is not a valid TW128 verification/decryption input; if $(d, N, C, A) \in W$ it returns **true**; if $b = 0$ it returns **false**; otherwise it returns $[\text{Dec}_{K_d}[\pi](N, A, C) \neq \perp]$. Nonce uniqueness is enforced per user by the set V .

After querying these oracles, $\mathcal{A}$ outputs $b' \in \{0, 1\}$. The mu-ind advantage of $\mathcal{A}$ against TW128 is

$$\text{Adv}_{\text{TW128}}^{\text{mu-ind}}(\mathcal{A}) = |2 \Pr[b' = b] - 1|.$$

Resource caps split per potential user $d \leq D$: $N^{(d)}$, $q_v^{(d)}$, $n_{\text{leaf}}^{(d)}$ are the per-user counts under Section 4.3, with inactive users contributing zero. The global totals $N = \sum_{d=1}^D N^{(d)}$, $q_v = \sum_{d=1}^D q_v^{(d)}$, $n_{\text{leaf}} = \sum_{d=1}^D n_{\text{leaf}}^{(d)}$ appear in the final bound: N through the lift term $\text{Lift}_c(N_{\text{tot}})$, and n_{leaf} and q_v through the leaf-collision and verification-tag terms. N_{prim} remains a single shared count over the primitive interface.

The mu-ind treatment applies only to indistinguishability. The committing-security games already give the adversary control of all s keys, so the s -way CMTDs- ℓ statements of Section 4.1 are themselves the multi-key committing statement and need no separate mu-cmt notion.

5 Main Results

This section states and instantiates TW128’s concrete security bounds. We first collect the recurring loss terms (Section 5.1) and the random-oracle envelopes and supporting bounds (Section 5.2) they rest on, then state the headline theorems (Section 5.3) and their concrete TW128-parameter forms (Sections 5.4 and 5.5), closing with a discussion of the bounds’ tightness (Section 5.6).

5.1 Loss Terms

Five closed-form expressions recur across the headline bounds of Section 5.3— Lift_c throughout, with KeyGuess_k , RootColl_τ , RootPre_τ , and LeafColl_τ in some. We define them here, ahead of the theorems that use them.

Flat-sponge loss. The flat-sponge differentiating loss is

$$\text{Lift}_c(N_{\text{tot}}) = N_{\text{tot}}(N_{\text{tot}} + 1)/2^{c+1}.$$

For $N_{\text{tot}} < 2^c$ it upper-bounds the [BDPVA08] sponge-differentiating advantage; Lemma 18 carries out the derivation from the [BDPVA08, Lemmas 4 and 5] product bounds through the Weierstrass product inequality. For $N_{\text{tot}} \geq 2^c$, $\text{Lift}_c(N_{\text{tot}}) \geq 1$ and the advantage bound is trivial without any appeal to indifferenciability, and already at $N_{\text{tot}} \geq 2^{c/2}$ the bound exceeds $1/2$ and provides no meaningful security.

Key-guessing term. The ideal-system key-guessing term of [BDPVA11] is

$$\text{KeyGuess}_k(Q) = Q/2^k.$$

It accounts for direct RO_{flat} queries whose inputs satisfy the decoder KeyedTWOut of Table 9. Each such query is an adaptive test of the decoded candidate key against the hidden key K , independent of the query’s requested output length. Lemma 9 bounds the probability that any of Q direct queries tests the right key by $Q/2^k$.

Root-collision term. The s -way root tag multi-collision term is

$$\text{RootColl}_\tau(Q, s) = \binom{Q+s}{s} / 2^{\tau(s-1)},$$

with the abbreviation $\text{RootColl}_{\tau_{\text{root}}}(Q, s) = \text{RootColl}_\tau(Q, s)$ at $\tau = \tau_{\text{root}}$. The $+s$ is candidate-sequence slack for the s final root transcript inputs generated by the committing challenger after the adversary outputs its tuples; these lookups are construction-internal and are not added to $q_{\text{RO}}(\mathcal{B})$. In the public-permutation CMTDs-4 and direct CMTs- ℓ bounds, the committing proof builds a chronological candidate sequence and bounds only the event that some s distinct candidates have equal root tag projections. The flat-sponge lift of Section B gives $Q = N_{\text{prim}}$: only the adversary’s N_{prim} direct primitive queries can induce simulator-side RO_{flat} queries that contribute to that sequence.

Root-preimage term. The root tag preimage term is

$$\text{RootPre}_\tau(Q) = (Q+1)/2^\tau,$$

with the abbreviation $\text{RootPre}_{\tau_{\text{root}}}(Q) = \text{RootPre}_\tau(Q)$ at $\tau = \tau_{\text{root}}$. It is the preimage analogue of RootColl_τ : a single query-independent target tag replaces the s -way internal collision, the $+s$ candidate-sequence slack collapses to the $+1$ of the single discoverability challenger decryption check, and the exponent drops from $\tau(s-1)$ to τ . As in the root-collision term, the flat-sponge lift gives $Q = N_{\text{prim}}$. The term bounds the query-independent target of context discoverability (Theorem 6).

Leaf-collision term. The known-key leaf tag collision term is

$$\text{LeafColl}_\tau(Q) = \binom{Q}{2} / 2^\tau.$$

It is the pairwise birthday bound on τ -bit leaf tag projections used by the collision-resistance and always-second-preimage theorems (Theorem 3, Theorem 4). Unlike the hidden-key leaf collision term in the INT-CTXT bound, the compact committing game has adversary-supplied keys, so direct primitive queries can pre-read candidate leaf tag points. The random-oracle proof therefore counts both direct leaf tag candidates and challenger-generated final leaf transcripts; after the flat-sponge lift this gives $Q = N_{\text{prim}} + N_{\text{leaf}}$.

5.2 Supporting Bounds

The headline theorems of Section 5.3 feed on six random-oracle-model bounds—the privacy and INT-CTXT envelopes, the CMTDs-4 bound, the collision bound, the second-preimage bound, and the preimage bound—whose proofs occupy Sections 6 to 8; the remaining committing-notion bounds live in Section C. Resource-indexed suprema range over flat-RO adversaries (Section 4.2) with the displayed resources, and the flat-sponge lift of Section B instantiates each envelope at $q_{\text{RO}} = N_{\text{prim}}$ when transferring to the public-permutation setting.

Privacy envelope. Define

$$\varepsilon_{\text{RO}}^{\text{priv}}(Q_{\text{RO}}) = \sup\{\text{Adv}_{\text{RO}}^{\text{priv}}(\mathcal{B}) : q_{\text{RO}}(\mathcal{B}) \leq Q_{\text{RO}}\},$$

the supremum taken over nonce-respecting privacy adversaries against Enc_K^{RO} . The flat-RO privacy theorem of Section 6 gives

$$\varepsilon_{\text{RO}}^{\text{priv}}(Q_{\text{RO}}) \leq \text{KeyGuess}_k(Q_{\text{RO}}).$$

INT-CTXT envelope. Define

$$\varepsilon_{\text{RO}}^{\text{int-ctxt}}(Q_{\text{RO}}, N_{\text{leaf}}, Q_v) = \sup\{\text{Adv}_{\text{RO}}^{\text{int-ctxt}}(\mathcal{B}) : q_{\text{RO}}(\mathcal{B}) \leq Q_{\text{RO}}, n_{\text{leaf}}(\mathcal{B}) \leq N_{\text{leaf}}, q_v(\mathcal{B}) \leq Q_v\}.$$

The flat-RO INT-CTXT theorem of Section 7 gives

$$\varepsilon_{\text{RO}}^{\text{int-ctxt}}(Q_{\text{RO}}, N_{\text{leaf}}, Q_v) \leq \text{KeyGuess}_k(Q_{\text{RO}}) + \frac{N_{\text{leaf}}(N_{\text{leaf}} - 1)}{2^{\tau_{\text{leaf}} + 1}} + \frac{Q_v}{2^{\tau_{\text{root}}}}.$$

CMTDs-4 bound. The flat-RO CMTDs-4 theorem of Section 8 is the direct root-collision bound

$$\text{Adv}_{\text{RO}}^{\text{CMTDs-4}}(\mathcal{B}) \leq \text{RootColl}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B}), s) = \binom{q_{\text{RO}}(\mathcal{B}) + s}{s} / 2^{\tau_{\text{root}}(s-1)},$$

with no key-guessing or leaf-collision term. The keys are adversary-supplied, so a direct query on an input accepted by the keyed transcript decoder $\text{KeyedTWO}_{\text{out}}$ is one of the adversary's visible RO_{flat} queries and is counted in $q_{\text{RO}}(\mathcal{B})$; leaf tag collisions cannot merge the final root transcripts whose tags are compared, since the common ciphertext body makes pairwise distinct full inputs yield pairwise distinct (K, N, A) triples; by Opening Triple Separation (Proposition 1) these reach distinct final root transcripts before any leaf tag is aggregated.

Collision bound. The flat-RO collision theorem of Section 8 is

$$\text{Adv}_{\text{RO}}^{\text{Coll}}(\mathcal{B}) \leq \text{LeafColl}_{\tau_{\text{leaf}}}(q_{\text{RO}}(\mathcal{B}) + n_{\text{leaf}}(\mathcal{B})) + \text{RootColl}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B}), s).$$

The root-collision part is the same final-root candidate argument as CMTDs-4. The additional known-key leaf-collision term is needed because colliding inputs may use different ciphertext bodies; absent such a leaf tag collision, pairwise distinct inputs force pairwise distinct final root transcripts before the common tag is compared.

Second-preimage bound. The flat-RO always-second-preimage theorem of Section 8 is

$$\text{Adv}_{\text{RO}}^{\text{aSec}}(\mathcal{B}) \leq \text{RootPre}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B})) + \text{LeafColl}_{\tau_{\text{leaf}}}(q_{\text{RO}}(\mathcal{B}) + n_{\text{leaf}}(\mathcal{B})).$$

The challenge tag is a fixed second-preimage target, so the candidate-collision argument becomes a candidate-preimage argument against the designated challenge candidate; the leaf-collision term is the same adversary-supplied-key accounting as the collision bound.

Preimage bound. The flat-RO preimage theorem of Section 8 is the direct root-preimage bound

$$\text{Adv}_{\text{RO}}^{\text{Pre}}(\mathcal{B}) \leq \text{RootPre}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B})) = (q_{\text{RO}}(\mathcal{B}) + 1)/2^{\tau_{\text{root}}},$$

again with no key-guessing or leaf-collision term, by the same adversary-supplied-key accounting. A single context replaces the s tuples, so the candidate-collision argument becomes a candidate-preimage argument against the query-independent target tag and no triple-separation is invoked.

Section B carries out the lift in two hops: Hop 1 (Lemma 18) replaces the real permutation by the [BDPVA08] public-primitive simulator and the flat-RO construction interface at cost at most $\text{Lift}_c(N_{\text{tot}})$, with $N_{\text{tot}} = N + N_{\text{prim}}$, and Hop 2 (Lemma 19) couples the result, without loss, to a derived flat-RO adversary $\mathcal{B} = \mathcal{B}_{\text{derived}}(\mathcal{A})$ whose simulator answers induce at most one RO_{flat} call each (Lemma 17), so $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$. The random-oracle envelopes of Section 5.2 are therefore instantiated at N_{prim} rather than N_{tot} ; the committing, hash, and discoverability challengers' encryption and decryption checks are construction-internal and counted in N .

5.3 Headline Theorems

TW128 delivers its headline guarantees in the lifted public-permutation model of Section 4.1: all-in-one AE security [RS06], its multi-user indistinguishability lift [BT16], and the commitment security of the root tag (Section 2.5). The last is stated as the [RS04] hash security of the wrapper H —collision, second-preimage, and preimage resistance—from which the [BH22] full-input CMTDs-4 committing bound follows as a corollary; the [MLGR23] context-discoverability notion, a ciphertext-level guarantee distinct from preimage resistance, is established separately (Theorem 6). For the AE-style notions the ideal side exposes the BDPV simulator; the committing, hash, and discoverability bounds remain real public-permutation success probabilities. Theorems 1 to 6 and Corollary 1 state these bounds in terms of the loss terms Lift_c , KeyGuess_k , RootColl_{τ} , LeafColl_{τ} , and RootPre_{τ} of Section 5.1 and the random-oracle envelopes $\varepsilon_{\text{RO}}^{\text{priv}}$, $\varepsilon_{\text{RO}}^{\text{int-ctxt}}$ of Section 5.2, both established above.

Theorem 1 (All-in-One AE Security). *For every nonce-respecting AE adversary $\mathcal{A}$ against TW128 with the resources of Section 4.3,*

$$\text{Adv}_{\text{TW128}}^{\text{ae}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \varepsilon_{\text{RO}}^{\text{priv}}(N_{\text{prim}}) + \varepsilon_{\text{RO}}^{\text{int-ctxt}}(N_{\text{prim}}, N_{\text{leaf}}, Q_v).$$

Proof. By the Lift Application corollary (Corollary 5) for the all-in-one AE game, there is a random-oracle AE adversary $\mathcal{B} = \mathcal{B}_{\text{derived}}(\mathcal{A})$ with $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$, $n_{\text{leaf}}(\mathcal{B}) \leq N_{\text{leaf}}$, and $q_v(\mathcal{B}) \leq Q_v$ such that

$$\text{Adv}_{\text{TW128}}^{\text{ae}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{Adv}_{\text{RO}}^{\text{ae}}(\mathcal{B}).$$

The all-in-one composition lemma (Lemma 1), applied in the random-oracle model, gives

$$\text{Adv}_{\text{RO}}^{\text{ae}}(\mathcal{B}) \leq \text{Adv}_{\text{RO}}^{\text{priv}}(\mathcal{B}_{\text{priv}}) + \text{Adv}_{\text{RO}}^{\text{int-ctxt}}(\mathcal{B}_{\text{int-ctxt}}),$$

for derived adversaries $\mathcal{B}_{\text{priv}}$ (which runs $\mathcal{B}$, records the outputs of its encryption-oracle queries, and answers each verification query by replay-table lookup) and $\mathcal{B}_{\text{int-ctxt}}$ (which runs $\mathcal{B}$, forwards encryption and verification queries to its own oracles, and halts on the first accepting non-replay verification response), both inheriting $\mathcal{B}$'s $(q_{\text{RO}}, n_{\text{leaf}}, q_v)$. Because $\mathcal{B}_{\text{priv}}$ forwards $\mathcal{B}$'s encryption queries unchanged and $\mathcal{B}$ inherits the nonce-respecting discipline of $\mathcal{A}$, the adversary $\mathcal{B}_{\text{priv}}$ is itself nonce-respecting, so the privacy envelope of Section 5.2 applies. Substituting the random-oracle envelopes of Section 5.2 gives the stated bound. $\square$

Theorem 2 (Multi-User Indistinguishability). *For every mu-ind adversary $\mathcal{A}$ against TW128 with execution-uniform user cap D and the global resources of Section 4.4,*

$$\text{Adv}_{\text{TW128}}^{\text{mu-ind}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \frac{D(D-1)}{2^{k+1}} + 2D \cdot \text{KeyGuess}_k(N_{\text{prim}}) + \frac{N_{\text{leaf}}(N_{\text{leaf}}-1)}{2^{\tau_{\text{leaf}}+1}} + \frac{Q_v}{2^{\tau_{\text{root}}}}.$$

Proof. Use the pre-sampled-key formulation of Section 4.4: sample keys $K_1, \dots, K_D$ at the start of the experiment, and let the d -th New call activate K_d , unused keys being ignored. By the Lift Application corollary (Corollary 5) for the mu-ind game, there is a random-oracle mu-ind adversary $\mathcal{B} = \mathcal{B}_{\text{derived}}(\mathcal{A})$ with $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$ and the per-user construction-side caps of Section 4.4 such that

$$\text{Adv}_{\text{TW128}}^{\text{mu-ind}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{Adv}_{\text{RO}}^{\text{mu-ind}}(\mathcal{B}).$$

Let coll denote the event that two of the pre-sampled keys $K_1, \dots, K_D$ collide; $\Pr[\text{coll}] \leq \binom{D}{2}/2^k = D(D-1)/2^{k+1}$ by union bound. In the random-oracle model, use a standard hybrid over the D users: H_d answers users $1, \dots, d$ with (Rand, Replay) and users $d+1, \dots, D$ with the real construction interface, so H_0 is the real mu-ind game and H_D is the ideal one. Let H_d^* be H_d with a fixed output bit on coll . Since coll has the same probability in all hybrids,

$$\text{Adv}_{\text{RO}}^{\text{mu-ind}}(\mathcal{B}) \leq \Pr[\text{coll}] + |\Pr[\mathcal{B}^{H_0^*} \Rightarrow 1] - \Pr[\mathcal{B}^{H_D^*} \Rightarrow 1]|.$$

By the triangle inequality, it remains to bound each adjacent stopped hybrid. For each d , Lemma 16 gives the adjacent hybrid bound

$$|\Pr[\mathcal{B}^{H_{d-1}^*} \Rightarrow 1] - \Pr[\mathcal{B}^{H_d^*} \Rightarrow 1]| \leq 2\text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})) + \frac{n_{\text{leaf}}^{(d)}(n_{\text{leaf}}^{(d)}-1)}{2^{\tau_{\text{leaf}}+1}} + \frac{q_v^{(d)}}{2^{\tau_{\text{root}}}}.$$

Using $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$, each hybrid step costs $2\text{KeyGuess}_k(N_{\text{prim}})$ plus the per-user leaf-collision and verification-tag terms. Summing across $d = 1, \dots, D$ gives $2D\text{KeyGuess}_k(N_{\text{prim}})$ for the key-guess contribution. The leaf-collision contribution satisfies

$$\sum_d \frac{n_{\text{leaf}}^{(d)}(n_{\text{leaf}}^{(d)}-1)}{2^{\tau_{\text{leaf}}+1}} = \frac{1}{2^{\tau_{\text{leaf}}}} \sum_d \binom{n_{\text{leaf}}^{(d)}}{2} \leq \frac{1}{2^{\tau_{\text{leaf}}}} \binom{\sum_d n_{\text{leaf}}^{(d)}}{2} \leq \frac{N_{\text{leaf}}(N_{\text{leaf}}-1)}{2^{\tau_{\text{leaf}}+1}},$$

the first inequality because the unordered pairs drawn within the per-user blocks are a subset of all unordered pairs among $\sum_d n_{\text{leaf}}^{(d)}$ items, and the second by $\sum_d n_{\text{leaf}}^{(d)} = n_{\text{leaf}} \leq N_{\text{leaf}}$ and monotonicity of $\binom{\cdot}{2}$. The verification-tag contribution satisfies

$$\sum_d q_v^{(d)} / 2^{\tau_{\text{root}}} \leq Q_v / 2^{\tau_{\text{root}}}.$$

979 Combining with the coll penalty $D(D-1)/2^{k+1}$ and $\text{Lift}_c(N_{\text{tot}})$ yields the stated bound. $\square$

980 **Theorem 3** (Collision Resistance of H). *For every $s \geq 2$ and every s -way collision*
 981 *adversary $\mathcal{A}$ against H with the resources of Section 4.3,*

$$982 \quad \text{Adv}_{TW128}^{\text{Coll}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{LeafColl}_{\tau_{\text{leaf}}}(N_{\text{prim}} + N_{\text{leaf}}) + \text{RootColl}_{\tau_{\text{root}}}(N_{\text{prim}}, s).$$

983 *Proof.* By the Lift Application corollary (Corollary 5) for the collision game, the derived
 984 random-oracle adversary $\mathcal{B}$ has $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$ and $n_{\text{leaf}}(\mathcal{B}) \leq N_{\text{leaf}}$. The random-oracle
 985 bound of Theorem 10 is nondecreasing in both $q_{\text{RO}}(\mathcal{B})$ and $n_{\text{leaf}}(\mathcal{B})$, so the monotone form
 986 of Corollary 5 gives the stated bound. The s colliding inputs may differ in their messages,
 987 hence in their ciphertext bodies; the LeafColl term accounts for the only way two distinct
 988 inputs sharing a context (K, N, A) can reach the same final root transcript—a collision
 989 among the leaf tags it absorbs—while distinct contexts already reach distinct final root
 990 transcripts by Opening Triple Separation (Proposition 1). $\square$

991 **Theorem 4** (Always-Second-Preimage Resistance of H). *For every aSec adversary $\mathcal{A}$*
 992 *against H with the resources of Section 4.3,*

$$993 \quad \text{Adv}_{TW128}^{\text{aSec}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{RootPre}_{\tau_{\text{root}}}(N_{\text{prim}}) + \text{LeafColl}_{\tau_{\text{leaf}}}(N_{\text{prim}} + N_{\text{leaf}}).$$

994 *Proof.* By the Lift Application corollary (Corollary 5) for the aSec game, the derived
 995 random-oracle adversary $\mathcal{B}$ has $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$ and $n_{\text{leaf}}(\mathcal{B}) \leq N_{\text{leaf}}$; the random-oracle
 996 bound of Theorem 12 is nondecreasing in both, so the monotone form of Corollary 5 gives
 997 the stated bound. Collision resistance (Theorem 3) already implies eSec and hence Sec in
 998 the sense of [RS04], both with the looser root-collision term; the always-notion is the one
 999 [RS04] shows collision resistance does not imply, and the direct argument replaces that
 1000 birthday term by the linear root-preimage term, the second preimage being sought against
 1001 the single fixed tag $H(X)$ of the challenge input X . $\square$

1002 **Corollary 1** (CMTDs-4 Committing Security). *For every $s \geq 2$ and every s -way CMTDs-4*
 1003 *adversary $\mathcal{A}$ against TW128 with the resources of Section 4.3,*

$$1004 \quad \text{Adv}_{TW128}^{\text{CMTDs-4}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{RootColl}_{\tau_{\text{root}}}(N_{\text{prim}}, s) = \text{Lift}_c(N_{\text{tot}}) + \frac{\binom{N_{\text{prim}}+s}{s}}{2^{\tau_{\text{root}}(s-1)}}.$$

1005 *Proof.* A CMTDs-4 winner exhibits s distinct inputs (K_i, N_i, A_i, M_i) whose encryptions
 1006 share one common ciphertext $C \parallel T$; in particular they share the tag T , so they are
 1007 an s -way collision of H, and $\text{Adv}_{TW128}^{\text{CMTDs-4}} \leq \text{Adv}_{TW128}^{\text{Coll}}$. The sharper no-LeafColl bound
 1008 is not obtained by specializing the displayed bound of Theorem 3, whose nonnegative
 1009 LeafColl summand survives any restriction of the adversary class. It comes instead from
 1010 the dedicated root-collision derivation of Theorem 9 for this all-bodies-equal case, lifted by
 1011 Corollary 5: the single shared body C forces the triples (K_i, N_i, A_i) pairwise distinct—by
 1012 Opening Triple Separation (Proposition 1)—so a leaf tag collision cannot merge two
 1013 openings and no LeafColl term arises. $\square$

1014 **Theorem 5** (Preimage Resistance of H). *For every target tag $T^* \in \{0, 1\}^{\tau_{\text{root}}}$ fixed in*
 1015 *advance and every preimage adversary $\mathcal{A}$ against H with the resources of Section 4.3,*

$$1016 \quad \text{Adv}_{TW128}^{\text{Pre}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{RootPre}_{\tau_{\text{root}}}(N_{\text{prim}}) = \text{Lift}_c(N_{\text{tot}}) + \frac{N_{\text{prim}} + 1}{2^{\tau_{\text{root}}}}.$$

1017 *Proof.* By the Lift Application corollary (Corollary 5) for the preimage game—whose
 1018 target T^* is fixed before the primitive sampling—the derived random-oracle adversary
 1019 $\mathcal{B}$ has $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$, and the random-oracle bound of Theorem 11 is nondecreasing in
 1020 $q_{\text{RO}}(\mathcal{B})$, so the monotone form of Corollary 5 gives the stated bound. Where Theorem 3

bounds the probability that s distinct inputs share a tag, this bounds the probability that a single input reaches a tag fixed in advance: the candidate-collision argument of Theorem 10 is replaced by the candidate-preimage argument of Theorem 11, dropping the exponent from $\tau_{\text{root}}(s - 1)$ to τ_{root} . $\square$

Theorem 6 (Context Discoverability of [MLGR23]). *For every target specifier $\mathbf{ts}$ and every adversary $\mathcal{A}$ against TW128, the restricted $\text{CDY}^*[\mathbf{ts}]$ advantage of [MLGR23, Fig. 5]—and in particular each per-component variant CDY_k^* , CDY_n^* , CDY_a^* —satisfies*

$$\text{Adv}_{\text{TW128}}^{\text{CDY}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{RootPre}_{\tau_{\text{root}}}(N_{\text{prim}}) + \text{KeyGuess}_k(N_{\text{prim}}).$$

Proof. The restricted advantage requires $\mathcal{A}$ to win against every query-independent selector, so it is at most the success probability against the selector S^* that samples a fresh context (K_0, N_0, A_0) —each of K_0 , N_0 , and A_0 uniform on a 256-bit space—encrypts a message under it to obtain the target ciphertext $C^* = C \parallel T^*$, and reveals only the $\mathbf{ts}$ -components. By the Lift Application corollary (Corollary 5), the derived random-oracle adversary $\mathcal{B}$ has $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$; it remains to bound the random-oracle success against S^* . Here $T^* = \lfloor \text{RF}(R_0) \rfloor_{\tau_{\text{root}}}$ is the root tag of the selector’s final root transcript R_0 under (K_0, N_0, A_0) , and a winning $\mathcal{A}$ outputs a context reaching a final root transcript R with $\text{RF}(R)$ projecting to T^* .

Let Z_0 be a context component $\mathcal{A}$ must itself supply—the key for $\mathbf{ts} \in \{\emptyset, \{n, a\}\}$, the nonce for $\mathbf{ts} = \{k, a\}$, the associated data for $\mathbf{ts} = \{k, n\}$ —which S^* sampled uniformly on $\{0, 1\}^w$ with $w = 256 \geq k$ and which $\mathcal{A}$ never sees: the only values revealed to it, the body and tag of C^* , are RF projections independent of Z_0 . If $R = R_0$, then $\mathcal{A}$ has reconstructed the selector’s transcript, in particular its Z_0 -component, which by Lemma 7 requires a candidate decoding under KeyedTWOut_{Z_0} to the hidden Z_0 ; since Z_0 stays uniform over the values no direct query has tested, Lemma 9 (hidden component Z_0 , $w = 256$) bounds this by $\text{KeyGuess}_k(N_{\text{prim}})$. If $R \neq R_0$, the win is that R collides with R_0 on its τ_{root} -bit projection, which the Root tag Candidate Sequence lemma (Lemma 2) and the second-preimage facet of Lemma 8, with the designated candidate $\text{flat}(R_0)$, bound by $\text{RootPre}_{\tau_{\text{root}}}(N_{\text{prim}})$. Adding the lift gives the bound, uniformly over $\mathbf{ts}$. $\square$

Corollary 2 (Root Tag as a Compact Commitment). *The wrapper $\mathbf{H}$ is a secure hash of the full encryption context (K, N, A, M) in the sense of [RS04]: collision-resistant (Theorem 3), second-preimage-resistant (Theorem 4), and preimage-resistant (Theorem 5). At the implemented parameters all three advantages are at most 2^{-128} (Corollary 3), so the single τ_{root} -bit root tag is a binding, preimage-resistant compact commitment to (K, N, A, M) , native to the mode.*

Proof. Collision resistance is Theorem 3, second-preimage resistance Theorem 4, and preimage resistance Theorem 5; all three quantify the adversary’s success at the same τ_{root} -bit projection of the final root transcript, and Corollary 3 evaluates them at the implemented parameters. Binding (collision resistance) is the property a compact commitment must have, and preimage resistance certifies that the tag alone reveals no opening; together they are the guarantees of a hash-based commitment. $\square$

5.4 Concrete TW128 Bounds

The implemented parameters of Section 3.2 fix

$$k = c = \tau_{\text{root}} = \tau_{\text{leaf}} = 256.$$

Substituting into Theorems 1 to 6 and Corollary 1 and using the random-oracle envelopes of Section 5.2 gives the following closed-form bounds.

All-in-one AE.

$$\text{Adv}_{\text{TW128}}^{\text{ae}}(\mathcal{A}) \leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{2N_{\text{prim}} + Q_v}{2^{256}} + \frac{N_{\text{leaf}}(N_{\text{leaf}} - 1)}{2^{257}}.$$

Multi-user indistinguishability.

$$\text{Adv}_{\text{TW128}}^{\text{mu-ind}}(\mathcal{A}) \leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{2DN_{\text{prim}} + Q_v}{2^{256}} + \frac{D(D - 1) + N_{\text{leaf}}(N_{\text{leaf}} - 1)}{2^{257}}.$$

s-way collision resistance of H. For every $s \geq 2$,

$$\text{Adv}_{\text{TW128}}^{\text{Coll}}(\mathcal{A}) \leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{\binom{N_{\text{prim}} + N_{\text{leaf}}}{2}}{2^{256}} + \frac{\binom{N_{\text{prim}} + s}{s}}{2^{256(s-1)}}.$$

For $s = 2$, this is the ordinary two-input collision bound:

$$\begin{aligned} \text{Adv}_{\text{TW128}}^{\text{Coll}}(\mathcal{A}) &\leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{(N_{\text{prim}} + N_{\text{leaf}})(N_{\text{prim}} + N_{\text{leaf}} - 1)}{2^{257}} \\ &\quad + \frac{(N_{\text{prim}} + 1)(N_{\text{prim}} + 2)}{2^{257}}. \end{aligned}$$

Always-second-preimage resistance of H. The linear root-preimage term replaces the collision bound's birthday root term:

$$\text{Adv}_{\text{TW128}}^{\text{aSec}}(\mathcal{A}) \leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{N_{\text{prim}} + 1}{2^{256}} + \frac{\binom{N_{\text{prim}} + N_{\text{leaf}}}{2}}{2^{256}}.$$

s-way CMTDs-4 committing security. For every $s \geq 2$, the all-bodies-equal special case drops the leaf tag term:

$$\text{Adv}_{\text{TW128}}^{\text{CMTDs-4}}(\mathcal{A}) \leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{\binom{N_{\text{prim}} + s}{s}}{2^{256(s-1)}}.$$

Remark 1 (Two-Key CMTD-4 Specialization). Setting $s = 2$ recovers the ordinary two-key CMTD-4 statement of [BH22]:

$$\text{Adv}_{\text{TW128}}^{\text{CMTDs-4}}(\mathcal{A}) \leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{\binom{N_{\text{prim}} + 2}{2}}{2^{256}} = \frac{N_{\text{tot}}(N_{\text{tot}} + 1) + (N_{\text{prim}} + 1)(N_{\text{prim}} + 2)}{2^{257}}.$$

Preimage resistance of H.

$$\text{Adv}_{\text{TW128}}^{\text{Pre}}(\mathcal{A}) \leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{N_{\text{prim}} + 1}{2^{256}}.$$

Context discoverability ([MLGR23]).

$$\text{Adv}_{\text{TW128}}^{\text{CDY}}(\mathcal{A}) \leq \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{257}} + \frac{2N_{\text{prim}} + 1}{2^{256}}.$$

5.5 Concrete Security Claim

Corollary 3 (Concrete TW128 Security). *Under the implemented parameters $k = c = \tau_{\text{root}} = \tau_{\text{leaf}} = 256$, every adversary with work cap $N_{\text{tot}} \leq 2^{63}$ —and, in the multi-user case, user cap $D \leq 2^{63}$ —has advantage at most 2^{-128} in each of TW128's notions: all-in-one AE (Theorem 1), multi-user indistinguishability (Theorem 2), the [RS04] hash security of H—s-way collision resistance for every $s \geq 2$, always-second-preimage resistance, and preimage resistance (Theorems 3 to 5)—the [BH22] CMTDs-4 committing bound it yields (Corollary 1), and [MLGR23] context discoverability (Theorem 6).*

Table 4: Concrete TW128 security at the work cap $N_{\text{tot}} \leq 2^{63}$ (with $D \leq 2^{63}$ for mu-ind), under $k = c = \tau_{\text{root}} = \tau_{\text{leaf}} = 256$ and the resource consequences $N_{\text{prim}}, Q_v, N_{\text{leaf}} \leq N_{\text{tot}}$ and $N_{\text{prim}} + N_{\text{leaf}} \leq N_{\text{tot}}$ of Section 4.3. The committing rows hold for every $s \geq 2$; larger s only shrinks the root-collision term.

Notion	Dominant term	At the cap
All-in-one AE	$\text{Lift}_c(N_{\text{tot}})$	$\leq 2^{-128}$
Multi-user ind.	$2D \text{KeyGuess}_k(N_{\text{prim}})$	$\leq 2^{-128}$
H collision (Coll)	$\text{Lift}_c(N_{\text{tot}})$	$\leq 2^{-128}$
H second-preimage (aSec)	$\text{Lift}_c(N_{\text{tot}})$	$\leq 2^{-128}$
H preimage (Pre)	$\text{Lift}_c(N_{\text{tot}})$	$\leq 2^{-128}$
CMTDs-4 [BH22]	$\text{Lift}_c(N_{\text{tot}})$	$\leq 2^{-128}$
CDY [MLGR23]	$\text{Lift}_c(N_{\text{tot}})$	$\leq 2^{-128}$

Proof. The claim instantiates the closed forms of Section 5.4 under the resource consequences of Section 4.3: $N_{\text{prim}} \leq N_{\text{tot}}$ by definition, and the pathwise bounds $q_v \leq N$ and $n_{\text{leaf}} \leq N$ let the envelope parameters Q_v and N_{leaf} be taken at most N_{tot} , so no separate top-level cap on Q_v or N_{leaf} is required; because $N_{\text{tot}} = N + N_{\text{prim}}$ counts construction-internal calls and direct queries disjointly, the same bound $n_{\text{leaf}} \leq N$ yields the joint constraint $N_{\text{prim}} + N_{\text{leaf}} \leq N_{\text{tot}}$. Only the mu-ind user cap D remains an independent hypothesis, since created-but-idle users need not contribute to N . At the headline work cap $N_{\text{tot}} \leq 2^{63}$ (and $D \leq 2^{63}$ for mu-ind) every bound is below 2^{-128} , with the flat-sponge loss $\text{Lift}_c(N_{\text{tot}})$ the dominant scale in all but the multi-user case (Table 4).

Term by term at the cap, with $N_{\text{prim}}, Q_v, N_{\text{leaf}} \leq N_{\text{tot}}$: the flat-sponge loss $\text{Lift}_c(N_{\text{tot}})$ and any leaf tag birthday term $N_{\text{leaf}}(N_{\text{leaf}} - 1)/2^{257}$ are each at most one 2^{-131} -sized term; the linear key-guess and verification contributions $(2N_{\text{prim}} + Q_v)/2^{256}$ are at most $3 \cdot 2^{-193}$; the two-key root-collision term $\text{RootColl}_{256}(N_{\text{prim}}, 2)$ likewise matches Lift_c as a 2^{-131} -sized term and is $\binom{N_{\text{prim}}+s}{s}/2^{256(s-1)}$, hence still well below Lift_c for $s \geq 3$ under the cap; the known-key $\text{LeafColl}_{256}(N_{\text{prim}} + N_{\text{leaf}})$, which the joint cap $N_{\text{prim}} + N_{\text{leaf}} \leq N_{\text{tot}}$ bounds by $\binom{N_{\text{tot}}}{2}/2^{256}$, is likewise $\leq 2^{-131}$; and the root-preimage term $(N_{\text{prim}} + 1)/2^{256}$ is at most $2 \cdot 2^{-193}$. The single-user totals are therefore dominated by Lift_c and stay below 2^{-128} . The multi-user bound is the exception: its hybrid-induced term $2D \cdot \text{KeyGuess}_k(N_{\text{prim}}) \leq 2DN_{\text{tot}}/2^{256}$ reaches $\approx 4\text{Lift}_c$ at the upper end and dominates—staying at most Lift_c once $D \leq N_{\text{tot}}(N_{\text{tot}} + 1)/(4N_{\text{prim}})$ (for $N_{\text{prim}} > 0$; when $N_{\text{prim}} = 0$ the hybrid-induced term vanishes), typical of any practical deployment—and the total there is at most $7 \cdot 2^{-131} + 2 \cdot 2^{-194} < 8 \cdot 2^{-131} = 2^{-128}$. Expressed in bytes, $N_{\text{tot}} \leq 2^{63}$ corresponds to at most $\rho \cdot 2^{63} = 167 \cdot 2^{63} < 2^{71}$ bytes of plaintext, associated data, ciphertext, and aggregation through the duplex (Section 3.2), well beyond any realistic deployment lifetime. $\square$

5.6 Discussion of the Bounds

The bounds of Section 5.4 aggregate the loss terms of Section 5.1, whose sizes at the work cap Table 4 records and whose dominance Section 5.5 discusses. We comment on their tightness.

Tightness.

- $\text{KeyGuess}_k(Q) = Q/2^k$. Tight at constants: a direct random-guess attack on a k -bit key matches the per-query success probability $1/2^k$. The multi-user bound's dominant term $2D \text{KeyGuess}_k(N_{\text{prim}}) = 2DN_{\text{prim}}/2^k$ is likewise tight up to the factor 2: against the D independent user keys each direct guess matches some key with probability

- 1124 $D/2^k$, so N_{prim} guesses recover a user key—and distinguish—with probability $\approx$
 1125 $DN_{\text{prim}}/2^k$.
- 1126 • $\text{RootColl}_\tau(Q, s) = \binom{Q+s}{s}/2^{\tau(s-1)}$. Tight up to lower-order terms: it is the standard
 1127 s -way multi-collision bound on a τ -bit projection of RO_{flat} , and a generic birthday-
 1128 style adversary against the random oracle matches the leading-order term. It is
 1129 the root term of the collision bound (H Coll, Theorem 3). Its N_{prim} counts every
 1130 primitive query, though by Output-Point Separation (Corollary 4) only those whose
 1131 induced RO_{flat} call lands at a root tag output point ($\mathcal{R}_{\text{tag}}$, or $\mathcal{R}_{\text{msg}}^+$ for single-chunk
 1132 ciphertexts) can enter the candidate sequence; a class-filtered count would be no
 1133 larger, and potentially smaller, but the headline keeps the N_{prim} form for uniformity
 1134 with Theorems 1 and 2, the birthday threshold at $\tau_{\text{root}} = 256$ being unaffected.
 - 1135 • $\text{RootPre}_\tau(Q) = (Q+1)/2^\tau$. Tight at constants: a generic preimage search against a
 1136 fixed τ -bit target matches the per-query $2^{-\tau}$ rate. It is the root term of the preimage
 1137 (Pre), always-second-preimage (aSec), and discoverability bounds, where the single
 1138 fixed target replaces the birthday RootColl of the collision bound by a linear term.
 - 1139 • *Leaf tag collision* $N_{\text{leaf}}(N_{\text{leaf}}-1)/2^{\tau_{\text{leaf}}+1}$. Tight for INT-CTXT, the notion it is proved
 1140 against: by reusing a nonce, an adversary detects a leaf tag birthday collision through
 1141 the matching root tags and splices the colliding leaf chunk into a fresh ciphertext
 1142 that still verifies, forging at the leading $N_{\text{leaf}}^2/2^{\tau_{\text{leaf}}+1}$ rate. The AE and multi-user
 1143 bounds carry the term only through the INT-CTXT envelope; their nonce-respecting
 1144 encryption rules this attack out, so there it is inherited slack.
 - 1145 • *Known-key leaf collision* $\text{LeafColl}_\tau(Q)$. The same birthday attack applies when keys
 1146 are adversary-supplied and direct queries can target leaf tag points; the collision and
 1147 always-second-preimage proofs use $Q = N_{\text{prim}} + N_{\text{leaf}}$.
 - 1148 • *Flat-sponge lift*. The term $\text{Lift}_c(N_{\text{tot}}) = N_{\text{tot}}(N_{\text{tot}}+1)/2^{c+1}$ dominates the random-
 1149 permutation differentiating bound $f_P(N_{\text{tot}})$ of [BDPVA08, Lemma 5] via Lemma 18.
 1150 The remaining slack is the unimproved tightness of the [BDPVA08] simulator itself,
 1151 which is an open problem on the sponge side and not specific to TW128.

1152 Cross-scheme bound-level comparisons against prior sponge AEADs and the committing-
 1153 AEAD line of [BH22] are deferred to Sections 10.1 to 10.3.

1154 6 Privacy

1155 This section proves the random-oracle privacy bound feeding the all-in-one AE composition
 1156 of Theorem 1. The public-permutation privacy statement follows by the flat-sponge lift of
 1157 Section B.

1158 **Theorem 7** (Random-Oracle Privacy). *For every nonce-respecting privacy adversary $\mathcal{B}$*
 1159 *in the TW128 random-oracle model (Section 4.2),*

$$1160 \quad \text{Adv}_{\text{RO}}^{\text{priv}}(\mathcal{B}) \leq \text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})) = q_{\text{RO}}(\mathcal{B})/2^k.$$

1161 *Equivalently, the resource-indexed envelope satisfies $\varepsilon_{\text{RO}}^{\text{priv}}(Q_{\text{RO}}) \leq \text{KeyGuess}_k(Q_{\text{RO}})$.*

1162 *Proof.* Let P_0 be the real-side random-oracle privacy game: the challenger samples $K \leftarrow \$$
 1163 $\{0,1\}^k$, $\mathcal{B}$ has direct access to RO_{flat} , and accepted construction-interface queries are
 1164 answered by Enc_K^{RO} . Let P_1 be the corresponding ideal-side game, augmented with an
 1165 independent auxiliary sample $K \leftarrow \$ \{0,1\}^k$: construction-interface queries are answered
 1166 by Rand , which returns a fresh uniformly random byte string of length $\|M\| + \tau_{\text{root}}/8$, and

direct queries are answered by the same lazy RO_{flat} interface. The auxiliary key is used only for the abort predicate below and is ignored by Rand , so the adversary's marginal view is the ideal term in the definition of $\text{Adv}_{\text{RO}}^{\text{priv}}(\mathcal{B})$. Let q_e be an execution-uniform cap on the number of accepted encryption queries made by $\mathcal{B}$, as in Section 4.3; this cap indexes the finite replacement hybrid sequence and will not enter the final privacy bound. Use the common abort event bad_{key} : a direct adversary query (Y, ℓ) to RO_{flat} satisfies

$$\text{KeyedTWOOut}(Y) = (K, \mathcal{C})$$

for this game's key K (the hidden key in P_0 , the auxiliary key in P_1) and some counted output-point class $\mathcal{C}$ of Table 9; the requested length ℓ is ignored.

Let P_0^{stop} and P_1^{stop} be the immediate-abort variants of P_0 and P_1 on this event. By the Privacy Stopped-Game Advantage Bound (Lemma 13) applied to the event $\mathcal{B} \Rightarrow 1$,

$$\text{Adv}_{\text{RO}}^{\text{priv}}(\mathcal{B}) = |\Pr[\mathcal{B}^{\text{P}_0} \Rightarrow 1] - \Pr[\mathcal{B}^{\text{P}_1} \Rightarrow 1]| \leq \text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})).$$

Taking the supremum over nonce-respecting privacy adversaries with $q_{\text{RO}}(\mathcal{B}) \leq Q_{\text{RO}}$ gives the envelope statement $\varepsilon_{\text{RO}}^{\text{priv}}(Q_{\text{RO}}) \leq \text{KeyGuess}_k(Q_{\text{RO}})$. $\square$

Lineage. The proof is the flat-random-oracle analog of the standard SpongeWrap privacy argument: stop on direct reads of hidden-key construction transcripts, replace each nonce-respecting encryption query by fresh random output under transcript freshness, and bound the stop event as an adaptive key test. The TW128-specific interfaces are Transcript Freshness (Lemma 11) and the privacy accounting lemmas (Lemmas 12 and 13).

7 Ciphertext Integrity

This section proves the random-oracle INT-CTXT bound feeding the all-in-one AE composition of Theorem 1. The public-permutation INT-CTXT statement follows by the flat-sponge lift of Section B.

Theorem 8 (Random-Oracle INT-CTXT). *For every INT-CTXT adversary $\mathcal{B}$ in the TW128 random-oracle model (Section 4.2),*

$$\text{Adv}_{\text{RO}}^{\text{int-ctxt}}(\mathcal{B}) \leq \text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})) + \frac{n_{\text{leaf}}(\mathcal{B})(n_{\text{leaf}}(\mathcal{B}) - 1)}{2^{\tau_{\text{leaf}} + 1}} + \frac{q_v(\mathcal{B})}{2^{\tau_{\text{root}}}}.$$

Equivalently, the resource-indexed envelope satisfies

$$\varepsilon_{\text{RO}}^{\text{int-ctxt}}(Q_{\text{RO}}, N_{\text{leaf}}, Q_v) \leq \text{KeyGuess}_k(Q_{\text{RO}}) + \frac{N_{\text{leaf}}(N_{\text{leaf}} - 1)}{2^{\tau_{\text{leaf}} + 1}} + \frac{Q_v}{2^{\tau_{\text{root}}}}.$$

Proof. Let G_0 be the real random-oracle INT-CTXT game: the challenger samples $K \leftarrow \{0, 1\}^k$, $\mathcal{B}$ has direct access to RO_{flat} , and construction queries are answered by Enc_K^{RO} and Ver_K^{RO} . Each encryption query (N, A, M) returns $C \parallel T = \text{Enc}_K^{\text{RO}}(N, A, M)$ and records the tuple (N, A, C, T) ; $\mathcal{B}$ wins if any verification query returns 1 on a tuple (N, A, C, T) that was not previously recorded by the encryption oracle.

Let bad_{key} be the event that some direct adversary query (Y, ℓ) to RO_{flat} satisfies $\text{KeyedTWOOut}(Y) = (K, \mathcal{C})$ for a counted output-point class $\mathcal{C}$ of Table 9; the requested length ℓ is ignored. Let G_1 be G_0 with an immediate abort on bad_{key} . The games are identical until this event, so

$$\Pr[\text{G}_0 \text{ wins}] \leq \Pr[\text{G}_1 \text{ wins}] + \Pr[\text{bad}_{\text{key}}].$$

Lemma 14 verifies the visible-prefix uniformity invariant required by the Adaptive Key-Test Bound (Lemma 9) in G_1 , with the set of already tested candidate keys recovered by KeyedTWOut. Therefore

$$\Pr[\text{bad}_{\text{key}}] \leq \text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})).$$

Let bad_{leaf} be the event that two distinct construction-generated final leaf transcripts under K receive the same τ_{leaf} -bit RF projection. Let G_2 be G_1 with an additional immediate abort on bad_{leaf} . The games are identical until this event, so

$$\Pr[G_1 \text{ wins}] \leq \Pr[G_2 \text{ wins}] + \Pr[\text{bad}_{\text{leaf}} \text{ before } \text{bad}_{\text{key}}].$$

Before bad_{key} , no direct query has pre-read the bridged input of a hidden-key final leaf transcript before the construction first creates that transcript: such a query would be decoded by KeyedTWOut to the hidden key K and its $\mathcal{L}_{\text{tag}}[j]$ class, independently of the requested output length, and would itself trigger bad_{key} . This supplies the event premise for the Leaf Tag Collision Bound (Lemma 10): thus $\{\text{bad}_{\text{leaf}} \text{ before } \text{bad}_{\text{key}}\}$ is contained in $\{\text{bad}_{\text{leaf}} \text{ before } \text{hit}_{\text{leaf}}\}$, where hit_{leaf} is the event of Lemma 10 that a direct query hits the bridged input of a hidden-key final leaf transcript before the construction first creates it; hence

$$\Pr[\text{bad}_{\text{leaf}} \text{ before } \text{bad}_{\text{key}}] \leq \frac{n_{\text{leaf}}(\mathcal{B})(n_{\text{leaf}}(\mathcal{B}) - 1)}{2^{\tau_{\text{leaf}} + 1}}.$$

Bound on $\Pr[G_2 \text{ wins}]$. In G_2 , every accepting non-replay verification submission belongs to a final root transcript class. If the class is encryption-first—first generated by an encryption query returning (N_e, A_e, C_e, T_e) —then, since bad_{leaf} has not occurred, the final-root determinacy of Lemma 5 and Leaf-Transcript Recovery (Lemma 6) give $(N, A, C) = (N_e, A_e, C_e)$ and the correct root tag is the value already returned as T_e , so the submission is a replay when $T = T_e$ and fails the tag comparison otherwise; it cannot be an accepting non-replay. The remaining accepting non-replay submissions are therefore verification-first. By Lemma 15, their total probability before $\text{bad}_{\text{key}} \cup \text{bad}_{\text{leaf}}$ is bounded by the root tag guessing term:

$$\Pr[G_2 \text{ wins}] \leq q_v(\mathcal{B})/2^{\tau_{\text{root}}}.$$

Conclusion. Combining the three stopped-game bounds,

$$\text{Adv}_{\text{RO}}^{\text{int-ctxt}}(\mathcal{B}) = \Pr[G_0 \text{ wins}] \leq \text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})) + \frac{n_{\text{leaf}}(\mathcal{B})(n_{\text{leaf}}(\mathcal{B}) - 1)}{2^{\tau_{\text{leaf}} + 1}} + \frac{q_v(\mathcal{B})}{2^{\tau_{\text{root}}}}.$$

Taking the supremum over INT-CTXT adversaries with $q_{\text{RO}}(\mathcal{B}) \leq Q_{\text{RO}}$, $n_{\text{leaf}}(\mathcal{B}) \leq N_{\text{leaf}}$, and $q_v(\mathcal{B}) \leq Q_v$ gives the envelope statement. $\square$

Lineage. The random-oracle decomposition of the bound into a key-guessing term and a tag-guessing term ($q2^{-k}$ and 2^{-t} in their notation) follows the authenticity bound of the ideal scheme $\mathcal{RO}_{\text{wrap}}[\rho]$ in the SpongeWrap analysis [BDPVA11, Lemma 6], which carries no sponge-capacity term. We realize the key-guessing term as the bad_{key} abort and the tag-guessing term as the residual root tag guessing bound on $\Pr[G_2 \text{ wins}]$, with a TW128-specific leaf tag birthday abort bad_{leaf} inserted between them. The sponge-capacity differentiating loss of [BDPVA11, §5, Theorem 1] does not appear at this random-oracle layer; it enters only through the flat-sponge lift of Section B, as the [BDPVA08] indistinguishability term written Lift_c . The TW128-specific steps come from Transcript Injectivity (Lemma 5), the Leaf Tag Collision Bound (Lemma 10), which bounds the bad_{leaf} abort by a birthday on the τ_{leaf} -bit leaf tag space, and the INT-CTXT auxiliary lemmas (Lemmas 14 and 15), with the leaf-freshness and encryption-first-replay steps argued inline.

8 Hash Security of the Root Tag

The tag-level guarantees of this section rest on one construction, isolated below as the Root tag Candidate Sequence lemma (Lemma 2): a chronological candidate sequence of root tag inputs, whose collision or preimage probability the adaptive lemmas of Section A bound, controlling the chance that distinct encryption inputs land on the same τ_{root} -bit root tag projection. We instantiate it in the random-oracle model for collision and preimage resistance of the wrapper H and for the [BH22] CMTDs-4 case; Section B transfers each instance to the public-permutation setting and Section 5.3 records the resulting concrete bounds.

First, the random-oracle CMTDs-4 bound (Theorem 9) is the pure s -way root tag collision case; the headline CMTDs-4 statement (Corollary 1) is its flat-sponge lift, and Section C forwards the remaining committing notions to the same root-collision bound. Second, the random-oracle preimage bound (Theorem 11) runs the same argument with the s -way collision replaced by a preimage to a fixed target tag, underlying the headline preimage statement (Theorem 5). Third, the random-oracle collision bound (Theorem 10) keeps the root tag collision argument intact but, because colliding inputs may use different ciphertext bodies, first rules out the only other way distinct bodies can reach a common root transcript—a collision among the absorbed leaf tags—through the known-key leaf tag collision lemma (Lemma 3); its public-permutation form is the headline Theorem 3.

The committing and discoverability arguments below rest on one structural fact, which we record first: distinct contexts reach distinct final root transcripts before any leaf tag is aggregated, so agreement among leaf tags cannot merge them.

Proposition 1 (Opening Triple Separation). *If two TW128 root computations have distinct (K, N, A) triples, then their bridged final root transcript inputs under $\text{flat}(\cdot)$ are distinct, regardless of whether each computation is an encryption or a decryption check on a common ciphertext.*

Proof. Suppose for contradiction that $\text{flat}(R_i) = \text{flat}(R_j)$. Since the bridge $\text{flat}(\cdot)$ is injective on well-formed transcript prefixes (Lemma 7), the native flattened inputs of the two final-root prefixes are equal. Then Lemma 5 recovers the full duplex-call sequence and reads off the pair $(\sigma, \sigma_{\text{ph}})$ for each call. The seven 4-bit phase suffixes are pairwise distinct, so the σ_{init} , $\sigma_{\text{ad}}^\pm$, $\sigma_{\text{msg}}^\pm$, and (when present) $\sigma_{\text{agg}}^\pm$ calls in the recovered sequence are unambiguously identified. The aggregation phase is present exactly when $n \geq 1$, and $n = \text{leaves}(C)$ is determined by the common ciphertext, so the two recovered sequences either both carry an aggregation phase or both omit it; either way the recovery of (K, N, A) below uses only the σ_{init} and AD calls, which precede any message or aggregation block.

Equality of the recovered sequences forces equality of the σ_{init} call, whose σ is $p_{\text{root}} \| K \| N$ with fixed-width K and N , hence $K_i = K_j$ and $N_i = N_j$. It also forces equality of the recovered AD subsequences. By the AD bullet of Lemma 5 the associated-data phase contributes a σ_{ad}^+ -tagged block exactly when the associated data is nonempty, so the recovered sequences agree on the presence of the AD phase. If exactly one of A_i, A_j were empty the recovered sequences would differ in the presence of a σ_{ad}^+ call, contradicting their equality; hence either both are empty, giving $A_i = A_j = \varepsilon$, or both are nonempty, in which case the phase-recovery sub-claim of Lemma 5 inverts the ρ -byte-block partition map on the AD byte string and equal AD σ -block sequences imply $A_i = A_j$. In all cases $(K_i, N_i, A_i) = (K_j, N_j, A_j)$, contradicting the hypothesis of distinct triples. $\square$

Lemma 2 (Root tag Candidate Sequence). *Consider a random-oracle game of Section 4.2 in which the adversary $\mathcal{B}$ first makes direct RO_{flat} queries and then outputs values on which the challenger runs $m \geq 1$ deterministic encryption or decryption checks, the i -th reaching a final root transcript R_i whose root tag is read by a single RO_{flat} lookup at $\text{flat}(R_i)$. Every execution then admits a chronological sequence of root tag inputs such that*

- 1298 1. each distinct direct query whose input Y decodes under **KeyedTWOut** to a root tag
 1299 output-point class— $\mathcal{R}_{\text{msg}}^+$ (the single-chunk root tag, aggregation elided) or $\mathcal{R}_{\text{tag}}$
 1300 (the multi-chunk root tag)—is appended as a candidate before its RO_{flat} lookup, and
 1301 contributes at most one candidate;
- 1302 2. if the challenger reaches its checks, each $\text{flat}(R_i)$ is in the sequence, appended—if not
 1303 already present—immediately before the i -th root tag answer is sampled;
- 1304 3. no candidate's RO_{flat} value is read before its append step, so the sequence satisfies
 1305 the predictability and unrevealed-value premises of Lemma 8; and
- 1306 4. its length is at most $q_{\text{RO}}(\mathcal{B}) + m$.

1307 *Proof.* The committing and discoverability games are keyless: all keys are adversary-
 1308 supplied, so a direct query to a keyed transcript is one of $\mathcal{B}$'s visible RO_{flat} queries counted
 1309 in $q_{\text{RO}}(\mathcal{B})$, and there is no bad_{key} event. No construction oracle runs during the direct-query
 1310 phase, so each direct-query candidate is first read no earlier than its append step. The
 1311 append predicate depends on Y alone through the exact decoder of Lemma 7, which ignores
 1312 the requested output length, and by Output-Point Separation (Corollary 4) each input
 1313 decodes to at most one output-point class; hence each distinct direct query contributes at
 1314 most one candidate, giving (1).

1315 If the challenger reaches its m checks, append $\text{flat}(R_i)$ immediately before the i -th root
 1316 tag answer is sampled, unless it is already present. The intermediate RO_{flat} lookups of
 1317 check i lie at non-root tag output points, so by Corollary 4 they do not read $\text{flat}(R_i)$. If
 1318 $\text{flat}(R_i)$ was touched earlier—by a direct query or by an earlier check $j < i$ —then Lemma 7
 1319 and Corollary 4 make that earlier access a final-root lookup at the same address, which
 1320 was therefore already appended, so the input is in the sequence and is not appended again.
 1321 Otherwise its value is still unread when appended. Either way no candidate's value is
 1322 read before its append step, giving (2) and (3). At most $q_{\text{RO}}(\mathcal{B})$ direct candidates and m
 1323 challenger candidates are appended, giving (4). $\square$

1324 **Theorem 9** (Random-Oracle CMTDs-4). *For every $s \geq 2$ and every s -way CMTDs-4*
 1325 *adversary $\mathcal{B}$ in the TW128 random-oracle model (Section 4.2),*

$$1326 \quad \text{Adv}_{\text{RO}}^{\text{CMTDs-4}}(\mathcal{B}) \leq \text{RootColl}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B}), s) = \frac{\binom{q_{\text{RO}}(\mathcal{B})+s}{s}}{2^{\tau_{\text{root}}(s-1)}}.$$

1327 *Proof.* Run the random-oracle CMTDs-4 game (Section 4.2). After rejecting on any
 1328 failed syntax, message-length, or pairwise-full-input check, its challenger performs $m = s$
 1329 deterministic decryption checks $\text{Dec}_{K_i}^{\text{RO}}(N_i, A_i, C \parallel T)$ on the one common body $C \parallel T$,
 1330 reaching final root transcripts $R_1, \dots, R_s$. The Root tag Candidate Sequence lemma
 1331 (Lemma 2) yields a sequence of length at most $q_{\text{RO}}(\mathcal{B}) + s$ meeting the premises of Lemma 8
 1332 and containing each $\text{flat}(R_i)$.

1333 On a winning execution the pairwise-full-input check passed, so the tuples
 1334 (K_i, N_i, A_i, M_i) are pairwise distinct. Because all s checks decrypt the common
 1335 body $C \parallel T$, determinism of Dec makes the (K_i, N_i, A_i) triples pairwise distinct as
 1336 well: equal triples would return equal messages, hence equal tuples. By Opening Triple
 1337 Separation (Proposition 1), the bridged final-root inputs $\text{flat}(R_1), \dots, \text{flat}(R_s)$ are therefore
 1338 pairwise distinct; leaf tag collisions cannot merge them. Since every decryption check
 1339 accepts, the τ_{root} -bit projections at these s distinct candidates all equal the supplied tag
 1340 T , so the win event is contained in the s -way candidate-collision event. Lemma 8 with
 1341 $Q = q_{\text{RO}}(\mathcal{B})$ and $\tau = \tau_{\text{root}}$ gives

$$1342 \quad \text{Adv}_{\text{RO}}^{\text{CMTDs-4}}(\mathcal{B}) \leq \binom{q_{\text{RO}}(\mathcal{B})+s}{s} \cdot 2^{-\tau_{\text{root}}(s-1)} = \text{RootColl}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B}), s).$$

1343 $\square$

Lemma 3 (Random-Oracle Known-Key Leaf Collision). *For any TW128 random-oracle-model game with adversary-supplied keys and adversary $\mathcal{B}$, let $\text{bad}_{\text{leaf}}^*$ be the event that two distinct construction-generated final leaf transcripts receive the same τ_{leaf} -bit RF projection. Then*

$$\Pr[\text{bad}_{\text{leaf}}^*] \leq \text{LeafColl}_{\tau_{\text{leaf}}}(q_{\text{RO}}(\mathcal{B}) + n_{\text{leaf}}(\mathcal{B})) = \frac{\binom{q_{\text{RO}}(\mathcal{B}) + n_{\text{leaf}}(\mathcal{B})}{2}}{2^{\tau_{\text{leaf}}}}.$$

Proof. Build a leaf tag candidate sequence. During $\mathcal{B}$'s direct oracle phase, append each distinct direct query input Y before answering it if $\text{KeyedTWOut}(Y)$ decodes to a final leaf tag output-point class $\mathcal{L}_{\text{tag}}[j]$. As the game's construction computations create distinct final leaf transcripts, append the bridged input of each immediately before its leaf tag oracle answer is sampled, unless that input is already in the sequence. If the input was touched earlier by a direct query, then Lemma 7 and Corollary 4 imply that the earlier query was already appended as a leaf tag candidate. If it was touched earlier by a construction computation, then Corollary 4, transcript injectivity (Lemma 5), and bridge injectivity imply that the same final leaf transcript had already been generated; repeated evaluations are not new collision opportunities. Thus every newly appended candidate satisfies the predictability and unrevealed-value premises of the adaptive candidate-collision argument, and the sequence length is at most $q_{\text{RO}}(\mathcal{B}) + n_{\text{leaf}}(\mathcal{B})$.

For any fixed unordered pair of candidate positions, expose the two positions in chronological order. When the later candidate is appended, its τ_{leaf} -bit projection is still unrevealed and uniform independently of the earlier one, so the pair collides with probability $2^{-\tau_{\text{leaf}}}$. A union bound over at most $\binom{q_{\text{RO}}(\mathcal{B}) + n_{\text{leaf}}(\mathcal{B})}{2}$ pairs gives the claim. The event $\text{bad}_{\text{leaf}}^*$ is contained in this candidate collision event because every construction-generated final leaf transcript is either appended when first created or was already appended by a direct query to the same bridged input. $\square$

Theorem 10 (Random-Oracle Collision Resistance of H). *For every $s \geq 2$ and every s -way collision adversary $\mathcal{B}$ in the TW128 random-oracle model,*

$$\text{Adv}_{\text{RO}}^{\text{Coll}}(\mathcal{B}) \leq \text{LeafColl}_{\tau_{\text{leaf}}}(q_{\text{RO}}(\mathcal{B}) + n_{\text{leaf}}(\mathcal{B})) + \text{RootColl}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B}), s).$$

Proof. Run the random-oracle collision game. By Lemma 3, the probability of $\text{bad}_{\text{leaf}}^*$ is at most the stated leaf-collision term, so it remains to bound the probability of the win event under $\neg \text{bad}_{\text{leaf}}^*$.

After rejecting unless the s output inputs are pairwise distinct and in the TW128 domain, the challenger performs $m = s$ deterministic encryptions $\text{Enc}_{K_i}^{\text{RO}}(N_i, A_i, M_i)$, reaching final root transcripts $R_1, \dots, R_s$. The Root tag Candidate Sequence lemma (Lemma 2) yields a sequence of length at most $q_{\text{RO}}(\mathcal{B}) + s$ meeting the premises of Lemma 8 and containing each $\text{flat}(R_i)$.

On a winning execution with $\neg \text{bad}_{\text{leaf}}^*$, the inputs (K_i, N_i, A_i, M_i) are pairwise distinct and all s encryptions yield a common tag T . We first show that the bridged final root inputs $\text{flat}(R_1), \dots, \text{flat}(R_s)$ are pairwise distinct. Suppose instead that checks $i \neq j$ reach the same final root input. The bridge and transcript encodings are injective, so the root transcripts have the same key, nonce, associated data, root ciphertext chunk, root tag output point, and, when leaves are present, the same ordered leaf tag aggregation string. The trailing encoded leaf count gives the same number of leaves. For each leaf position, equality of the aggregated leaf tag values together with $\neg \text{bad}_{\text{leaf}}^*$ implies that the two final leaf transcripts are the same; hence the corresponding leaf chunks are the same. Thus the two encryptions share (K, N, A, M) , so $(K_i, N_i, A_i, M_i) = (K_j, N_j, A_j, M_j)$, contradicting the pairwise distinctness of the colliding inputs. The final root inputs are therefore pairwise distinct.

Since all s encryptions yield the common tag, the τ_{root} -bit projections at these s distinct final-root candidates are all equal. The win event under $\neg \text{bad}_{\text{leaf}}^*$ is contained in the s -way

1393 root candidate-collision event, which Lemma 8 bounds by $\text{RootColl}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B}), s)$. Adding
 1394 the $\text{bad}_{\text{leaf}}^*$ probability gives the theorem. $\square$

1395 **Theorem 11** (Random-Oracle Preimage Resistance of H). *For every query-independent*
 1396 *target tag $T^* \in \{0, 1\}^{\tau_{\text{root}}}$ and every preimage adversary $\mathcal{B}$ in the TW128 random-oracle*
 1397 *model (Section 4.2),*

$$1398 \quad \text{Adv}_{\text{RO}}^{\text{Pre}}(\mathcal{B}) \leq \text{RootPre}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B})) = \frac{q_{\text{RO}}(\mathcal{B}) + 1}{2^{\tau_{\text{root}}}}.$$

1399 *Proof.* Run the random-oracle preimage game (Section 4.2) for the query-independent
 1400 target T^* , which is independent of RO_{flat} . After rejecting unless the output input $X =$
 1401 (K, N, A, M) is in the TW128 domain, the challenger performs $m = 1$ deterministic
 1402 encryption $\text{Enc}_K^{\text{RO}}(N, A, M)$, reaching a final root transcript R . The Root tag Candidate
 1403 Sequence lemma (Lemma 2) yields a sequence of length at most $q_{\text{RO}}(\mathcal{B}) + 1$ meeting the
 1404 premises of Lemma 8 and containing $\text{flat}(R)$; with a single input no pairwise distinctness
 1405 is needed.

1406 On a winning execution $H(X) = T^*$, that is, the τ_{root} -bit projection T' at the final root
 1407 transcript R equals T^* ; in the random-oracle model $T' = \lfloor \text{RO}_{\text{flat}}(\text{flat}(R)) \rfloor_{\tau_{\text{root}}}$. Hence the
 1408 win event is contained in the event that some candidate's τ_{root} -bit projection equals the
 1409 fixed target T^* . Applying Lemma 8 with $Q = q_{\text{RO}}(\mathcal{B})$, $\tau = \tau_{\text{root}}$, and $t = T^*$ gives

$$1410 \quad \text{Adv}_{\text{RO}}^{\text{Pre}}(\mathcal{B}) \leq (q_{\text{RO}}(\mathcal{B}) + 1) \cdot 2^{-\tau_{\text{root}}} = \text{RootPre}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B})).$$

1411 $\square$

1412 **Theorem 12** (Random-Oracle aSec). *For every aSec adversary $\mathcal{B}$ in the TW128 random-*
 1413 *oracle model (Section 4.2),*

$$1414 \quad \text{Adv}_{\text{RO}}^{\text{aSec}}(\mathcal{B}) \leq \text{RootPre}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B})) + \text{LeafColl}_{\tau_{\text{leaf}}}(q_{\text{RO}}(\mathcal{B}) + n_{\text{leaf}}(\mathcal{B})).$$

1415 *Proof.* Run the random-oracle aSec game. The challenger draws the challenge input X ,
 1416 encrypts it to obtain $T = H(X)$ at a final root transcript R_X , and gives X to $\mathcal{B}$, which
 1417 outputs an input $X' \neq X$; the win event is $H(X') = T$. By Lemma 3 the probability of a
 1418 collision $\text{bad}_{\text{leaf}}^*$ among the leaf transcripts of the encryptions of X and X' is at most the
 1419 stated leaf term, so it remains to bound the win under $\neg \text{bad}_{\text{leaf}}^*$.

1420 Here $T = \lfloor \text{RF}(R_X) \rfloor_{\tau_{\text{root}}}$ is the root tag of the challenge transcript R_X . Encrypting
 1421 X' reaches a final root transcript R' with $H(X') = \lfloor \text{RF}(R') \rfloor_{\tau_{\text{root}}}$. If $R' = R_X$, then
 1422 by transcript injectivity (Lemma 5) X' shares the context, leaf count, and aggregated
 1423 leaf tags of X , and under $\neg \text{bad}_{\text{leaf}}^*$ equal leaf tags force equal leaf transcripts by Leaf-
 1424 Transcript Recovery (Lemma 6), hence equal leaf bodies; so $X' = X$ by determinism,
 1425 contradicting $X' \neq X$. Thus $R' \neq R_X$, and the win event $H(X') = T$ is the event that
 1426 R' collides with R_X on its τ_{root} -bit projection. The Root tag Candidate Sequence lemma
 1427 (Lemma 2), applied to $\mathcal{B}$'s direct queries and the single post-output check encrypting
 1428 X' , yields a chronological sequence of at most $q_{\text{RO}}(\mathcal{B}) + 1$ candidates containing $\text{flat}(R')$,
 1429 each appended with unrevealed value; prepending the challenge candidate $\text{flat}(R_X)$ as the
 1430 designated position—whose value is the exposed challenge tag T —the second-preimage
 1431 facet of Lemma 8 bounds the probability that any candidate other than $\text{flat}(R_X)$ collides
 1432 with it by $\text{RootPre}_{\tau_{\text{root}}}(q_{\text{RO}}(\mathcal{B}))$. Adding the $\text{bad}_{\text{leaf}}^*$ probability gives the theorem. $\square$

1433 9 Performance Evaluation

1434 9.1 Optimized Implementations

1435 We evaluate three implementations of TW128 sharing a common structure: a portable
 1436 reference written in Go, an **amd64** implementation, and an **arm64** implementation. The two

architecture-specific implementations replace only the KECCAK- p [1600, 12] permutation and the inner absorb/squeeze loops with hand-written assembly; the framing, domain separation, padding, and tree bookkeeping remain in the shared Go code. The portable reference uses a scalar permutation and a scalar eight-instance loop, and serves both as a correctness oracle for the assembly cores and as the fallback on other architectures.

The tree structure of TW128 exposes two distinct permutation workloads, and both architectures provide a separate core for each. The root duplex—which absorbs the associated data, processes chunk 0, and absorbs the leaf tag aggregation transcript—is inherently sequential, since each of its calls consumes the previous call’s output; it is driven by a *single-duplex* ($\times 1$) core that permutes one 1600-bit state at a time, except for its chunk-0 message phase, which is fused into the first batched leaf call as described below. The leaf duplexes, by contrast, operate on disjoint state and disjoint inputs (Section 3), so the implementation batches eight complete leaf chunks and runs them in lockstep through an *eight-way* ($\times 8$) core. Because every leaf chunk is exactly $\beta = 49\rho$ bytes, the eight instances step through an identical sequence of 49 full ρ -blocks (the first 48 closed with MSG_MORE, the last with MSG_LAST), so a single shared block position drives all eight. The eight-way state is held lane-major—25 lanes each holding the corresponding 64-bit word of all eight instances—so that the batched cores can address the eight instances of a lane with a single vector load.

Messages are decomposed into eight-chunk batches run on the $\times 8$ core, and a leftover run of two to seven complete chunks is drained by a narrower kernel: on **amd64** a register-resident kernel processes the remainder in a single call, reading the active chunks in place, and on **arm64** a 2-wide kernel consumes it two chunks at a time. These remainder kernels read each chunk as a sequential stream, so they prefetch as well on the cold tail of a long message as on a cache-resident short one; on the **amd64** host they outperform both repeated single-duplex calls and padding the remainder to a full eight-chunk batch, at every remainder width. Only a single leftover complete chunk, a partial trailing chunk, and the count-aggregation tail fall back to the single-duplex ($\times 1$) core.

Chunk 0 itself runs on the batched kernels rather than serially, a technique we refer to as *lane-0 fusion*. The root duplex’s chunk-0 message phase has the same kernel-visible block schedule as a leaf chunk—the same 49 ρ -blocks with the same closing flags—and differs from a leaf only in its initial state, to which the kernels are indifferent; chunk 0 is also contiguous in the message with the first leaf chunks. The implementation therefore seeds lane 0 of the first batched call with the root state (after initialization and associated-data processing) and runs the chunk-0 phase alongside up to seven leaves: in the $\times 8$ core when the message has at least seven complete leaf chunks, and in the **amd64** remainder kernel or the **arm64** 2-wide kernel below that. Lane 0’s output state is written back to the root duplex, which then absorbs the leaf tags produced by the same call; no serial pass over chunk 0 precedes the leaf work. On **amd64** the assembly kernels handle only the 48 full MSG_MORE blocks of each chunk; the final MSG_LAST block and the leaf tag extraction are performed in portable Go, shared with the reference path, which keeps the byte-granular tail logic out of assembly. The **arm64** kernels process the complete chunk, extracting the leaf tags and storing the permutation states back in assembly—the writeback that allows the root duplex to occupy lane 0.

Architecture-specific cores. On **amd64** the cores are built from AVX-512 (selected once at startup from the AVX512VL CPUID feature bit) and AVX2, holding the lane-major state in ZMM or YMM registers and permuting it with no cross-lane shuffles. The steady-state $\times 8$ kernel transposes each rate block into the lane-major layout with contiguous, prefetcher-friendly loads and stores, while the register-resident kernel that drains a two-to-seven-chunk remainder reads its active chunks in place by masked gather and scatter. On **arm64** the cores use NEON with the Armv8.2 SHA-3 extension (FEAT_SHA3, available on Apple Silicon

and Neoverse V1/V2 and N2), one instance per 64-bit lane in the single-duplex core and two instances per 128-bit register in the $\times 8$ and 2-wide kernels. Both batched paths store the permutation state back after the closing block—the writeback that lets the root duplex occupy lane 0. Section D gives the per-instruction detail, including the fused permutation instructions and the remainder-kernel strategies on each architecture.

Constant time. All three implementations are constant time with respect to the key, nonce, and plaintext. The permutation and the XOR-based absorb/squeeze contain no secret-dependent branches and no secret-dependent memory or vector indices. The only indexed table is the round-constant array, addressed by the public round number; the AVX-512 chunk transpose uses contiguous loads and stores, and the gather and scatter that remain—for the partial rate lane and the register-resident remainder kernel—are addressed by the fixed public chunk strides under a mask set by the public chunk count, and the AVX2 remainder kernel’s redirection of inactive instances to its dummy block is likewise selected by the public chunk count. None of these depend on secret data.

9.2 Benchmark Methodology

We measure on two hosts, one per architecture. The **amd64** host is a Google Compute Engine **c4-standard-4** instance with an Intel Xeon Platinum 8581C (Emerald Rapids, 2.30 GHz base, AVX-512 including AVX512VL, AVX512_VBMI2, GFNI, and VAES), two physical cores with simultaneous multithreading enabled, 48 KiB L1d and 32 KiB L1i per core, 2 MiB L2 per core, and a 260 MiB shared L3, running Debian 12 (kernel 6.1) under KVM. The guest does not expose a **cpufreq** interface, so the frequency governor and turbo state are not under our control; we mitigate the resulting variance statistically (below). The **arm64** host is an Apple M4 Pro (10 performance cores and 4 efficiency cores; per performance core, 128 KiB L1i, 64 KiB L1d, and a 16 MiB shared L2) running macOS 26.5.1 (Darwin 25.5), with **FEAT_SHA3** present. macOS exposes no userspace frequency control.

Measurements are collected by a standalone harness (**cmd/cpb**) that locks its goroutine to an OS thread and, for each algorithm, operation, and message length, first calibrates an iteration count that fills at least 100 ms, then records 100 samples, from which it reports the median cycles per byte and median wall-clock throughput together with the interquartile range as a dispersion measure (Table 7). Both metrics are read from the same timed loop, so the cycles-per-byte and throughput figures for a given measurement come from one interleaved run rather than two separately scheduled ones. Each sample reuses the same source and destination buffers, so the reported figures are warm-cache, steady-state rates. The single-threaded measurement leaves the SMT sibling of the **amd64** host idle. We report a sweep of seven message lengths from 1 B to 16 MiB.

The cycle counters differ by architecture, and this affects how the cycles-per-byte figures may be read. On **amd64** the harness reads **RDTSC**; on this part the time-stamp counter is invariant and ticks at the 2.30 GHz reference frequency, so the reported figures are *reference* cycles per byte and are unaffected by turbo (and convert directly to wall-clock time). On **arm64** the harness reads **CNTVCT_ELO** and scales it by the ratio of the peak core frequency to **CNTFRQ_ELO**; since Apple exposes no frequency API, the peak is auto-detected by timing a dependent integer-add chain and taking the top observed P-state, yielding *core* cycles per byte. Consequently the cycles-per-byte figures are comparable within an architecture and against the same-host AES-128-GCM baseline, but not directly across architectures; absolute throughput (Table 6) is the cross-platform metric.

The baseline is Go’s AES-128-GCM implementation (**crypto/aes** with **crypto/cipher**). It uses AES-NI and **PCLMULQDQ** on **amd64**, and the AES and **PMULL** instructions on **arm64**. Each timed AES-128-GCM call constructs its cipher, so its measurement includes the key schedule and the GHASH key-power precomputation; this mirrors the TW128 measurement, whose one-shot seal and open perform the root duplex initialization

Table 5: Median cycles per byte (100 samples). The **amd64** figures are RDTSC reference cycles at the 2.30 GHz invariant time-stamp counter; the **arm64** figures are core cycles at the auto-detected peak performance-core frequency. Cycle counts are not directly comparable across architectures (Section 9.2).

	Message length						
	1 B	64 B	8 KiB	32 KiB	64 KiB	1 MiB	16 MiB
<i>Intel Xeon 8581C (Emerald Rapids), AVX-512</i>							
TW128 encrypt	590	9.27	1.89	0.78	0.40	0.39	0.40
TW128 decrypt	615	9.72	1.90	0.75	0.40	0.39	0.39
AES-128-GCM seal	765	13.23	0.38	0.32	0.30	0.30	0.30
AES-128-GCM open	785	12.79	0.37	0.31	0.30	0.29	0.29
<i>Intel Xeon 8581C (Emerald Rapids), AVX2</i>							
TW128 encrypt	656	10.31	2.20	1.10	1.02	1.07	1.08
TW128 decrypt	683	10.70	2.21	1.11	1.08	1.07	1.08
<i>Apple M4 Pro, NEON + FEAT_SHA3</i>							
TW128 encrypt	620	9.77	1.95	0.91	0.88	0.88	0.89
TW128 decrypt	667	10.59	2.00	0.89	0.87	0.87	0.87
AES-128-GCM seal	1044	17.28	0.54	0.45	0.44	0.43	0.44
AES-128-GCM open	1055	17.31	0.52	0.43	0.42	0.41	0.42

(one permutation) inside the timed call. Both directions are measured for each scheme; the two directions track each other to within a few percent across the sweep, with a worst-case divergence of 8% (TW128 on **arm64** at 64 B).

9.3 Throughput

Table 5 reports cycles per byte across the message-length sweep and Table 6 the corresponding wall-clock throughput in the bulk regime. The dominant feature of the TW128 rows is the descent produced by the tree-parallel leaf core: the per-byte cost falls as a message lengthens and its chunks occupy more SIMD lanes. A message of at most one chunk has no complete leaf chunk for chunk 0 to share a kernel with, so it runs entirely on the single-duplex core, and the 8 KiB column sits at that core’s rate. Past one chunk, lane-0 fusion (Section 9.1) keeps every complete chunk on the batched kernels, and the descent tracks lane occupancy: at 32 KiB, chunk 0 and three complete leaves run four-wide in the **amd64** remainder kernels and as two full pairs on **arm64**, and 64 KiB is the first length whose eight complete chunks ($8\beta \approx 64$ KiB) fill the eight-way ($\times 8$) core. On the **amd64** AVX-512 path TW128 encryption falls $1.89 \rightarrow 0.78 \rightarrow 0.40$ across the 8, 32, and 64 KiB columns and is already at its bulk rate at 64 KiB, holding at 0.39–0.40 through 16 MiB. The AVX2 path follows the same shape at lower throughput ($2.20 \rightarrow 1.10$ over the same span, thereafter between 1.02 and 1.08); it runs the eight instances as two groups of four rather than in a single 8-wide register, leaving the AVX-512 core about $2.7\times$ faster in bulk. The **arm64** curve flattens earliest ($1.95 \rightarrow 0.91 \rightarrow 0.88 \rightarrow 0.88 \rightarrow 0.89$ cycles per byte from 8 KiB to 16 MiB): the eight-way core itself processes its batch as four two-instance pairs, so the fused 2-wide kernel runs at essentially the same per-chunk rate, and a 32 KiB message—chunk 0 and three leaves as two full pairs—is already within 3% of the 16 MiB floor. In wall-clock terms TW128 reaches 5.77 GB/s on the **amd64** AVX-512 host and 5.04 GB/s on the M4 Pro for 16 MiB messages.

Table 6: Measured wall-clock throughput (GB/s, GB = 10^9 bytes) from the same `cmd/cpb` run as Table 5, encryption direction; the decryption direction tracks it. The `amd64` AES-128-GCM row is the AVX-512 host and is unaffected by the TW128 core selection.

	8 KiB	32 KiB	64 KiB	1 MiB	16 MiB
<i>Intel Xeon 8581C (Emerald Rapids)</i>					
TW128 (AVX-512)	1.22	2.95	5.78	5.94	5.77
TW128 (AVX2)	1.05	2.09	2.25	2.15	2.14
AES-128-GCM	6.11	7.27	7.57	7.68	7.63
<i>Apple M4 Pro</i>					
TW128 (NEON+SHA3)	2.30	4.92	5.06	5.10	5.04
AES-128-GCM	8.25	9.89	10.18	10.33	10.09

Table 7: Cycles-per-byte measurement dispersion for TW128 across the seven-length sweep (seal and open, 100 samples per point), as the interquartile range relative to the median. The final column is the widest single-point min–max range; its size on the `amd64` guest reflects the turbo and governor states we cannot pin (Section 9.2) and is excluded from the IQR as a tail effect.

Path	Relative IQR		Max
	median	max	range
Xeon 8581C, AVX-512	1.2%	1.6%	16.5%
Xeon 8581C, AVX2	1.4%	2.1%	20.2%
Apple M4 Pro	0.6%	1.0%	4.7%

Dispersion. Each cell of Tables 5 and 6 is the median of 100 samples; Table 7 summarizes their spread as the interquartile range (IQR) relative to the median. The medians are stable: across the sweep the relative IQR of the TW128 cycles-per-byte measurements is at most 1.6% on the `amd64` AVX-512 path, 2.1% on AVX2, and 1.0% on the M4 Pro, with per-path medians of 1.2%, 1.4%, and 0.6%. The full min–max range is wider on the `amd64` guest—up to 16.5% (AVX-512) and 20.2% (AVX2) at isolated lengths—because its turbo and governor states are not under our control (Section 9.2); these are tail excursions that the IQR excludes, and the M4 Pro, whose frequency is steadier, keeps even its full range within 4.7%. We therefore report medians throughout and treat the IQR as the dispersion measure.

9.4 Latency

For short messages the cost is set by the serial root duplex and is independent of the parallel leaf machinery. A message of at most $\rho = 167$ bytes occupies a single rate block and never enters leaf mode, so it costs exactly two permutations—one to initialize the root duplex and one to close the message block and extract the tag. The 1 B and 64 B columns of Table 5 bear this out: per-message latency is nearly flat across them at roughly 590 reference cycles on `amd64` (590 at 1 B versus $9.27 \times 64 \approx 593$ at 64 B) and 620 core cycles on `arm64` (620 versus $9.77 \times 64 \approx 625$), i.e. about 295 and 310 cycles per KECCAK- p [1600, 12] respectively. Because such messages bypass the leaf core entirely, leaf-level parallelism imposes no latency penalty on them.

The latency/throughput trade-off appears instead in the intermediate regime, which lane-0 fusion has narrowed to roughly the one-to-eight-chunk band. The worst per-byte cost in the sweep is the single-chunk regime at 8 KiB (1.9–2.2 cycles per byte across the

three paths), where the message is the chunk-0 phase alone on the single-duplex core. Once the message has complete leaf chunks for chunk 0 to share a kernel with, the cost falls quickly: by 32 KiB TW128 is within a factor of two of its AVX-512 floor and within 3% of its `arm64` floor, and the floor itself is reached once the eight-way core fills at 64 KiB. The root duplex also bounds the tail of a long message: the final tag cannot be produced until chunk 0 has been processed and every leaf tag has been absorbed into the aggregation transcript. That absorption is cheap—each rate block of the root absorbs five 32-byte leaf tags, so a 16 MiB message (≈ 2000 leaves) adds on the order of 400 root permutations against roughly 10^5 permutations of leaf work, under 0.5% overhead—so the serial root does not materially cap bulk throughput.

9.5 Comparison with Other AEADs

We compare against the one baseline measured under the same harness on the same hosts, the Go standard library’s hardware-accelerated AES-128-GCM (Tables 5 and 6). The harness times TW128 and AES-128-GCM back-to-back at each length and reads both metrics from the same loop, so the cycles-per-byte and throughput comparisons hold under identical conditions and agree. In the bulk regime AES-128-GCM is faster on both architectures, as expected for a primitive with dedicated AES and carryless-multiply instructions: at 16 MiB it runs at 0.30 cycles per byte on `amd64` and 0.44 on `arm64`, against 0.40 and 0.89 for TW128—about $1.3\times$ and $2\times$ faster. The wall-clock throughputs show the same margins: TW128 reaches 5.77 and 5.04 GB/s against AES-128-GCM’s 7.63 and 10.09 GB/s. The wider `arm64` gap reflects the strength of Apple’s AES and PMULL units. TW128 attains these rates with a permutation that has no dedicated hardware support, relying only on the SHA-3 extension on `arm64` and on general SIMD on `amd64`.

The ordering reverses for very short messages, where AES-128-GCM’s key schedule and GHASH key-power precomputation dominate: at 1 B AES-128-GCM costs 765 and 1044 cycles on the two hosts against TW128’s 590 and 620. This comparison is setup-bound rather than representative of steady state, since each timed call rebuilds its cipher; it nonetheless reflects the per-message cost an application pays when it does not amortize key setup across messages. In the sub-bulk regime AES-128-GCM is several times faster at one chunk (0.38 versus 1.89 cycles per byte at 8 KiB on `amd64`), but the gap narrows quickly once the fused kernels engage: about $2.4\times$ at 32 KiB, and the bulk ratio from 64 KiB on. TW128’s intended value relative to AES-128-GCM lies in the tree structure and committing-security properties analyzed in Sections 6 to 8 rather than in raw speed.

10 Discussion

10.1 Comparison Table

Table 8 situates TW128 against representative authenticated encryption schemes along the axes that distinguish it: the underlying primitive, whether the mode is parallelizable, the key, nonce, and tag sizes, associated-data support, nonce-misuse resistance, full-input key commitment (CMT-4), and context discoverability (CDY). The comparison is structural; TW128’s own concrete bounds and the regimes in which each term dominates are treated in Section 5.6, and its measured throughput against hardware-accelerated AES-128-GCM in Section 9.5. The CMT-4 column records full-input commitment: TW128 provides it within the mode, as does Ascon [KSW23], a committing transform supplies it for an arbitrary base scheme, and the remaining listed schemes do not provide it. The CDY column records context-discovery resistance in the [MLGR23] sense: TW128 provides it within the mode (Theorem 6), and the remaining entries are marked “?” because, to our knowledge, no discoverability result—attack or proof—has been published for them.

Table 8: Structural comparison of TW128 with representative AEADs. Sizes are in bytes; AES-GCM-SIV also admits a 32-byte key. “Misuse-res.” is nonce-misuse resistance in the sense of [RS06]; the CMT-4 column records full-input commitment in the sense of [BH22], abstracting over its decryption (CMTD) and encryption (CMT) forms, of which TW128’s is the decryption form CMTDs-4; CDY is context discoverability in the sense of [MLGR23]. A dash means the entry is inherited from the base scheme, and “?” that no result is established in the literature. TW128’s concrete bounds appear in Section 5.6.

Scheme	Primitive	Par.	K/N/T	AD	Misuse	CMT-4	CDY
TW128	KECCAK- p [1600, 12]	yes	32/32/32	yes	no	yes	yes
Ascon-128a [DEMS21]	Ascon- p (320 b)	no	16/16/16	yes	no	yes	?
Xoodoo [DHP ⁺ 20]	Xoodoo (384 b)	no	16/16/16	yes	no	no	?
AES-GCM-SIV [GLL17]	AES	yes	16/12/16	yes	yes	no	?
nAE + CTX [CR22]	any nAE	—	—	yes	—	yes	?

Context discoverability is a recent notion [MLGR23], so its absence of entries reflects the state of the literature rather than a negative result; the schemes [MLGR23] do break on discoverability (GCM, CCM, EAX, SIV, OCB3) are not among the rows above. The table does not separately track compact (tag-only) commitment, since that property has not been systematically analyzed for the comparison schemes.

10.2 Comparison with Prior Sponge AEADs

TW128 belongs to the family of single-permutation duplex AEADs initiated by [BDPVA11]. The dedicated lightweight members of that family, Ascon [DEMS21] and Xoodoo [DHP⁺20], target 128-bit security on small permutations (320 and 384 bits) with a strictly serial duplex: each call depends on the previous one, so there is no mode-level parallelism to exploit. TW128 instead pays for a larger permutation, KECCAK- p [1600, 12], and a 256-bit capacity—the same round count as KangarooTwelve [BDP⁺16]—in exchange for a tree that processes leaf chunks in parallel and for the headroom that yields 128-bit security with a comfortable margin. The cost of this choice is visible in Section 9: on short, single-leaf inputs TW128 is slower per byte than a compact serial duplex would be, and its advantage appears only once a message spans enough leaves to fill the vector units.

TW128 reuses KangarooTwelve’s final-node/leaf split but not its Sakura coding, which renders that scheme’s tree hashing sound: the frame bits and coded child count of a Sakura coding make every node input unambiguously decodable, so that any collision in the hash output entails a collision in the inner function. TW128 adopts no such coding and does not need one. Its tree has a single fixed two-level shape—one root and a leaf count fixed by $\|C\|$ through $\text{leaves}(\cdot)$ —so it never distinguishes among a family of admissible topologies, the generality a Sakura coding exists to serve; the leaf count is moreover pinned by absorbing $\langle n \rangle_8$ before the root tag. The unambiguous parsing such a coding would supply is instead furnished by the per-call domain separation of Section 3.4: the prefixes p_{root} , p_{leaf} and the leaf index $\langle j \rangle_8$ fix the duplex instance, and the seven pairwise-distinct phase suffixes of Table 3 fix the phase and the final/non-final role of every call, so distinct transcripts flatten to distinct sponge inputs (Lemma 5 and Corollary 4); binding the index into each leaf is in fact a finer separation than ordering leaves within an aggregation alone. More to the point, the committing and discoverability guarantees of Section 8 do not rest on soundness of a tree coding at all: distinct (K, N, A) triples already diverge in the root initialization and associated-data calls, before any leaf tag is aggregated (Proposition 1), so agreement among leaf tags cannot merge distinct contexts. The leaf encoding enters only the collision bound of Theorem 3, and there only through its explicit leaf tag collision term. A Sakura coding would re-establish parsing facts TW128 already possesses, and would leave these bounds unchanged.

Keyak [BDP⁺15], whose Motorist mode is already parallelizable, is the closest prior duplex AEAD in spirit; Section 1.2 contrasts its wire-visible, encryptor-and-decryptor-shared degree of parallelism with TW128’s run-time leaf choice. Strobe [Ham17] is a serial sponge framework aimed at whole protocols rather than at a standalone AEAD, and like Ascon and Xoodyak it does not parallelize. Committing security is not unique to TW128 in this family: a dedicated analysis of the sponge-based NIST lightweight finalists proves Ascon committing while breaking others [KSW23], and some constructions, such as Strobe, have not been examined in that setting at all. What distinguishes TW128 is that it makes the root tag a secure compact commitment to the full input—collision-, second-preimage-, and preimage-resistant as a hash, which in particular yields the strongest full-input committing notion (CMT-4)—as a proven, designed property of the mode, and additionally resists [MLGR23] context discovery, established without leaving the single-permutation duplex setting; the discoverability guarantee in particular is not known to hold for the other members of the family.

10.3 Comparison with Committing AEAD Constructions

The dominant route to committing AEAD is a generic transform over a non-committing base scheme. [BH22] give the UtC, RtC, and HtE transforms, which add key- or context-commitment to an arbitrary AEAD, and [CR22] give CTX, which makes any nonce-based AE scheme commit to its full context at the cost of a single hash over a short string and with no ciphertext expansion. These transforms are inexpensive and broadly applicable; CTX in particular is nearly free. TW128 differs not by undercutting their cost but by integration: it is committing as the mode itself, with the same permutation and the same tag that already provide confidentiality and integrity, so no separate commitment primitive, key-derivation step, or auxiliary hash is invoked, and the strongest s -way full-input notion follows from a single root tag collision bound (Section 8). More strongly, Theorem 3 shows that the root tag alone is a compact commitment string even when the ciphertext bodies used as openings differ, up to the additional leaf tag birthday term. The same tag, being preimage-resistant, additionally yields context discoverability against that fixed tag, which the context-committing transforms are not known to provide. This places TW128 alongside the dedicated committing primitives—the compactly committing AEAD of [GLR17] and the encryptment of [DGRW18]—which likewise build commitment in rather than bolt it on, but which were designed for message franking rather than as general nonce-based AEADs. The contrast with transformed conventional schemes is sharpened by the attacks of Section 1.2: base schemes such as GCM and OCB are not committing on their own [CR22], and a transform is the only way to make them so.

Closest to TW128 here is the recent work of [DHM⁺24], which builds nonce-based AE directly on the SHA-3 functions SHAKE and TurboSHAKE—the latter using the same round-reduced KECCAK- p permutation as TW128—and likewise achieves CMT-4 natively, from the collision resistance of the underlying function rather than from a transform. The two designs make different structural choices: [DHM⁺24] targets session-based communication, chaining a stream of messages through intermediate tags and generalizing the keyed duplex into a *duplex cipher*, whereas TW128 is a single two-level tree whose independent leaves expose run-time-selectable parallelism at constant memory (Sections 1.2 and 9.1). Because a session chain processes each message serially, TW128’s principal advantage is throughput on large messages (Section 9): its parallel leaves fill vector units a serial duplex leaves idle, at the cost of the session support [DHM⁺24] provides and TW128 does not. Both demonstrate that committing AE needs no add-on transform once it is built on a well-scrutinized KECCAK- p permutation.

10.4 Limitations and Open Problems

Nonce misuse. TW128’s privacy analysis requires a nonce-respecting adversary, and the mode is not misuse-resistant: a repeated nonce reuses leaf keystream and breaks confidentiality, as for any online duplex stream cipher. Schemes such as AES-GCM-SIV [GLL17], in the deterministic/misuse-resistant lineage of [RS06], tolerate nonce repetition at the price of a second pass. A misuse-resistant variant of TW128 is left open.

Release of unverified plaintext. The analysis assumes that plaintext is released only after the tag verifies. TW128 is online and single-pass, so an implementation that streams decrypted leaf output before checking the root tag operates in the release-of-unverified-plaintext setting of [ABL⁺14], which our bounds do not cover; plaintext-awareness and INT-RUP security for TW128 are unstudied.

Bound tightness. Per-term tightness is itemized in Section 5.6; one term is conservative in a way that points to an open problem. The flat-sponge differentiating loss $\text{Lift}_c(N_{\text{tot}}) = N_{\text{tot}}(N_{\text{tot}} + 1)/2^{c+1}$ bounds the indistinguishability loss of [BDPVA08], used here as a generic lift from the random-oracle model. A direct analysis of the keyed duplex is tighter: the modern keyed-duplex bounds synthesized by [Men23], building on the full-state keyed-duplex line, bound a keyed duplex against an ideal permutation without passing through indistinguishability, and recasting TW128’s leaf and root duplexes in that framework is a promising route to a sharper capacity term. This route is not turnkey, however: the keyed duplex bundles squeezing and absorption into a single call, so its authenticated-encryption mode *MonkeySpongeWrap* has the decryptor *overwrite* the rate with each ciphertext block rather than feed back the ciphertext it has just produced. On the final, padded block this overwrite no longer matches the encryptor’s XOR-absorbed padded plaintext outside the message bits, so the decryptor cannot reconstruct the final block of duplex output and recomputes the tag from a divergent state [Men23, Alg. 8]. TW128 sidesteps this by absorbing the ciphertext in both directions (Section 3), so recasting it on the keyed duplex would first require repairing the mode. We retain the indistinguishability lift for its modularity, as the resulting Lift_c already meets the 128-bit target (Section 5.6).

Beyond-birthday and leakage. All bounds are birthday-type on the 256-bit capacity, delivering the 128-bit target but no more; a beyond-birthday analysis is open. The model is also single-stage and leakage-free: side-channel resistance is addressed only at the implementation level, through the constant-time properties of Section 9.1, and is not part of the provable-security claims.

11 Conclusion

TW128 is a two-level tree of keyed duplexes over a single KECCAK- p [1600, 12] permutation that combines mode-level parallelism, constant memory, and commitment security in both its collision and preimage facets. Its concrete public-permutation bounds—for all-in-one AE, multi-user indistinguishability, the secure-hash security of the root-tag wrapper (collision, second-preimage, and preimage resistance) that makes the tag a compact commitment, the s -way full-input committing notion (CMTDs-4) it yields, and [MLGR23] context discoverability—meet a 128-bit target at the implemented parameters, and vectorized *amd64* and *arm64* implementations turn the tree’s leaf parallelism into multi-gigabyte-per-second throughput within a small factor of hardware-accelerated AES-128-GCM.

Several questions remain open (Section 10.4): a nonce-misuse-resistant variant, security under the release of unverified plaintext, and sharper bounds—whether by recasting the leaf and root duplexes on the modern keyed-duplex analysis or through a beyond-birthday

argument. More broadly, TW128 adds to the growing evidence that a single, well-scrutinized KECCAK- p permutation suffices to build authenticated encryption that is at once fast, parallel, and committing.

Acknowledgments

A hearty thank-you to my wife, who remains reasonably mystified at my choice of hobbies.

References

- [ABL⁺14] Elena Andreeva, Andrey Bogdanov, Atul Luykx, Bart Mennink, Nicky Mouha, and Kan Yasuda. How to securely release unverified plaintext in authenticated encryption. In *Advances in Cryptology – ASIACRYPT 2014*, volume 8873 of *Lecture Notes in Computer Science*, pages 105–125. Springer, 2014.
- [ADG⁺22] Ange Albertini, Thai Duong, Shay Gueron, Stefan Kölbl, Atul Luykx, and Sophie Schmieg. How to abuse and fix authenticated encryption without key commitment. In *31st USENIX Security Symposium (USENIX Security 22)*, pages 3291–3308. USENIX Association, 2022.
- [BDP⁺15] Guido Bertoni, Joan Daemen, Michaël Peeters, Gilles Van Assche, and Ronny Van Keer. CAESAR submission: Keyak v2. CAESAR Competition, Round 3 Candidate, 2015.
- [BDP⁺16] Guido Bertoni, Joan Daemen, Michaël Peeters, Gilles Van Assche, Ronny Van Keer, and Benoît Viguier. KangarooTwelve: Fast hashing based on Keccak-p. *Cryptology ePrint Archive*, Paper 2016/770, 2016.
- [BDPVA08] Guido Bertoni, Joan Daemen, Michaël Peeters, and Gilles Van Assche. On the indifferentiability of the sponge construction. In *Advances in Cryptology – EUROCRYPT 2008*, volume 4965 of *Lecture Notes in Computer Science*, pages 181–197. Springer, 2008.
- [BDPVA11] Guido Bertoni, Joan Daemen, Michaël Peeters, and Gilles Van Assche. Duplexing the sponge: Single-pass authenticated encryption and other applications. In *Selected Areas in Cryptography – SAC 2011*, volume 7118 of *Lecture Notes in Computer Science*, pages 320–337. Springer, 2011.
- [BH22] Mihir Bellare and Viet Tung Hoang. Efficient schemes for committing authenticated encryption. In *Advances in Cryptology – EUROCRYPT 2022*, volume 13276 of *Lecture Notes in Computer Science*, pages 845–875. Springer, 2022.
- [BN00] Mihir Bellare and Chanathip Namprempre. Authenticated encryption: Relations among notions and analysis of the generic composition paradigm. In *Advances in Cryptology – ASIACRYPT 2000*, volume 1976 of *Lecture Notes in Computer Science*, pages 531–545. Springer, 2000.
- [BT16] Mihir Bellare and Björn Tackmann. The multi-user security of authenticated encryption: AES-GCM in TLS 1.3. In *Advances in Cryptology – CRYPTO 2016*, volume 9814 of *Lecture Notes in Computer Science*, pages 247–276. Springer, 2016.
- [CR22] John Chan and Phillip Rogaway. On committing authenticated encryption. In *Computer Security – ESORICS 2022*, *Lecture Notes in Computer Science*. Springer, 2022.

- [DEMS21] Christoph Dobraunig, Maria Eichlseder, Florian Mendel, and Martin Schl  ffer. Ascon v1.2: Lightweight authenticated encryption and hashing. *Journal of Cryptology*, 34(3):33, 2021.
- [DGRW18] Yevgeniy Dodis, Paul Grubbs, Thomas Ristenpart, and Joanne Woodage. Fast message franking: From invisible salamanders to encryptment. In *Advances in Cryptology – CRYPTO 2018*, volume 10991 of *Lecture Notes in Computer Science*, pages 155–186. Springer, 2018.
- [DHM⁺24] Joan Daemen, Seth Hoffert, Silvia Mella, Gilles Van Assche, and Ronny Van Keer. Shaking up authenticated encryption. Cryptology ePrint Archive, Paper 2024/1618, 2024.
- [DHP⁺20] Joan Daemen, Seth Hoffert, Micha  l Peeters, Gilles Van Assche, and Ronny Van Keer. Xoodooak, a lightweight cryptographic scheme. *IACR Transactions on Symmetric Cryptology*, 2020(S1):60–87, 2020.
- [GLL17] Shay Gueron, Adam Langley, and Yehuda Lindell. AES-GCM-SIV: Specification and analysis. Cryptology ePrint Archive, Paper 2017/168, 2017.
- [GLR17] Paul Grubbs, Jiahui Lu, and Thomas Ristenpart. Message franking via committing authenticated encryption. In *Advances in Cryptology – CRYPTO 2017*, volume 10403 of *Lecture Notes in Computer Science*, pages 66–97. Springer, 2017.
- [Ham17] Mike Hamburg. The STROBE protocol framework. Cryptology ePrint Archive, Paper 2017/003, 2017.
- [IR23] Takanori Isobe and Mostafizar Rahman. Key committing security analysis of AEGIS. Cryptology ePrint Archive, Paper 2023/1495, 2023.
- [KSW23] Juliane Kr  mer, Patrick Struck, and Maximiliane Weish  upl. Committing AE from sponges: Security analysis of the NIST LWC finalists. Cryptology ePrint Archive, Paper 2023/1525, 2023.
- [LGR21] Julia Len, Paul Grubbs, and Thomas Ristenpart. Partitioning oracle attacks. In *30th USENIX Security Symposium (USENIX Security 21)*, pages 195–212. USENIX Association, 2021.
- [Men23] Bart Mennink. Understanding the duplex and its security. *IACR Transactions on Symmetric Cryptology*, 2023(2):1–46, 2023.
- [MLGR23] Sanketh Menda, Julia Len, Paul Grubbs, and Thomas Ristenpart. Context discovery and commitment attacks: How to break CCM, EAX, SIV, and more. In *Advances in Cryptology – EUROCRYPT 2023*, volume 14007 of *Lecture Notes in Computer Science*, pages 379–407. Springer, 2023.
- [Nat15] National Institute of Standards and Technology. SHA-3 standard: Permutation-based hash and extendable-output functions. Federal Information Processing Standards Publication FIPS PUB 202, U.S. Department of Commerce, August 2015.
- [RS04] Phillip Rogaway and Thomas Shrimpton. Cryptographic hash-function basics: Definitions, implications, and separations for preimage resistance, second-preimage resistance, and collision resistance. In *Fast Software Encryption – FSE 2004*, volume 3017 of *Lecture Notes in Computer Science*, pages 371–388. Springer, 2004.




Figure 2: Dependency graph of the supporting lemmas in this appendix and their consumers. Solid boxes are lemmas; dashed boxes are the proof sections that consume them. The edge from Lemma 5 into the committing proofs of Sections C and 8 is mediated by Proposition 1 for final-root distinctness and Corollary 4 for candidate-sequence filtering; the edge from Lemma 8 records the collision accounting used by the CMTDs-4 and CMTs proofs. The edge from Lemma 5 into Lemma 11 uses Corollary 4; the verification-first root tag guessing accounting reached through the same separation is carried out in Section A.10 (Lemma 15) and consumed by Section 7. The Lemma 9 edge records the shared bad_{key} accounting used by privacy and INT-CTXT.

- [RS06] Phillip Rogaway and Thomas Shrimpton. A provable-security treatment of the key-wrap problem. In *Advances in Cryptology – EUROCRYPT 2006*, volume 4004 of *Lecture Notes in Computer Science*, pages 373–390. Springer, 2006.
- [WP14] Hongjun Wu and Bart Preneel. AEGIS: A fast authenticated encryption algorithm. In *Selected Areas in Cryptography – SAC 2013*, volume 8282 of *Lecture Notes in Computer Science*, pages 185–201. Springer, 2014.

A Supporting Lemmas

The proof core separates structural decoding from probabilistic accounting. The well-formed transcript language of Definition 1 fixes which flattened queries are valid TW128 construction prefixes. Lemmas 4, 5 and 7 then show how such a query is flattened, parsed as a typed transcript, assigned an output point, and decoded to a candidate key, when any. Lemma 9 turns those decoded keys into an adaptive key-test bound. The remaining proof interfaces expose the events and stopped-game equalities their consumers must control: privacy freshness and hybrid replacement, INT-CTXT hidden-key exposure and root tag guessing, leaf tag collisions, and the committing candidate-sequence collision event. Thus the privacy, INT-CTXT, and committing proofs only have to derive the relevant local event premise before applying the corresponding accounting argument.

A.1 Duplex Flattening

Lemma 4 (Duplex Flattening). *Every TW128 root or leaf duplex output is equal to a [BDPVA11] sponge output on the corresponding flattened duplex-call transcript, and the ciphertext-absorbing message phase admits a flattened duplex transcript that is well defined for both encryption and decryption.*

Proof. Let D be a duplex object using permutation π , rate r , and padding pad10^*1 . For a sequence of duplex calls $Z_i = D.\text{duplexing}(\sigma_i, \ell_i)$ with each σ_i short enough to fit in one duplex block after padding, [BDPVA11, Lemma 3] gives

$$Z_i = \text{Sponge}[\pi, \text{pad10}^*1, r](\sigma_0 \parallel \text{pad}_0 \parallel \sigma_1 \parallel \text{pad}_1 \parallel \cdots \parallel \sigma_i, \ell_i),$$

where $\text{pad}_j = \text{pad10}^*1[r](|\sigma_j|)$, and Lemma 4 says that, for fixed pad10^*1 and r , the map from the duplex-call sequence to the flattened sponge input is injective.

In TW128, each duplex call absorbs a byte-aligned block σ followed by a 4-bit phase suffix $\sigma_{\text{ph}} \in \{\sigma_{\text{init}}, \sigma_{\text{ad}}^-, \dots, \sigma_{\text{agg}}^+\}$ (Section 3.4), so the duplex-call input is $\sigma \parallel \sigma_{\text{ph}}$ followed by pad10^*1 . With $r = 1344$ and $\rho_{\text{max}}(\text{pad10}^*1, r) = r - 2 = 1342$ bits, the maximum byte-aligned input is $\rho = 167$ bytes (Section 3.2), giving a worst-case duplex-call input of $8 \cdot 167 + 4 = 1340 \leq 1342$ bits. The two initialization calls are shorter still: $|p_{\text{root}} \parallel K \parallel N| + 4 = 8 \cdot (6 + 32 + 32) + 4 = 564$ bits and $|p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8| + 4 = 8 \cdot (6 + 32 + 32 + 8) + 4 = 628$ bits. [BDPVA11, Lemmas 3 and 4] therefore apply independently to every TW128 duplex object.

The root duplex is initialized by absorbing $p_{\text{root}} \parallel K \parallel N$ under σ_{init} (Algorithm 2), then absorbs the associated-data blocks under $\sigma_{\text{ad}}^- / \sigma_{\text{ad}}^+$, the root ciphertext blocks in the message phase under $\sigma_{\text{msg}}^- / \sigma_{\text{msg}}^+$, and the leaf tag aggregation blocks under $\sigma_{\text{agg}}^- / \sigma_{\text{agg}}^+$. By the duplex-to-sponge equality, every root duplex output is the sponge function evaluated on the root transcript prefix accumulated up to the relevant output point. The same holds for each leaf duplex, initialized by $p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8$ and absorbing only its own ciphertext blocks in the message phase. In decryption and verification, Algorithm 3 absorbs the submitted ciphertext blocks before the root tag comparison, so the same flattened message-phase transcript is defined whether the comparison accepts or rejects. $\square$

A.2 Well-formed Transcript Prefixes

For a duplex-call prefix $((\sigma_0, \sigma_{\text{ph},0}), \dots, (\sigma_i, \sigma_{\text{ph},i}))$, write

$$\text{Flat}((\sigma_0, \sigma_{\text{ph},0}), \dots, (\sigma_i, \sigma_{\text{ph},i})) = \bigg\|_{j=0}^{i-1} (\sigma_j \parallel \sigma_{\text{ph},j} \parallel \text{pad}_j) \parallel \sigma_i \parallel \sigma_{\text{ph},i}.$$

The current call's padding pad_i is not part of Flat ; it is applied internally by the sponge function. Equivalently, after the i -th call the duplex state is the sponge state after absorbing $\text{Flat}(\cdot) \parallel \text{pad}_i$.

Definition 1 (Well-Formed TW128 Transcript Prefixes). A typed TW128 transcript prefix is *well formed* if it is a prefix, ending at a construction transcript lookup point, of one of the following two call languages.

- A root transcript starts with $(p_{\text{root}} \parallel K \parallel N, \sigma_{\text{init}})$, with fixed-width fields $K \in \{0, 1\}^k$ and $N \in \{0, 1\}^\nu$. It then absorbs the associated-data byte string (only when the associated data is nonempty; the phase is otherwise elided, Section 3.5), the root ciphertext byte string, and the aggregation byte string (only when $n \geq 1$; when $n = 0$ the aggregation phase is elided, Section 3.5, and the root tag is emitted by the final σ_{msg}^+ message call), in that order. Each present phase byte string is partitioned

by the block rule of Algorithm 1: the empty string gives one empty final block, and a nonempty string gives zero or more ρ -byte non-final blocks followed by one final block. The phases use respectively $\sigma_{\text{ad}}^-/\sigma_{\text{ad}}^+$, $\sigma_{\text{msg}}^-/\sigma_{\text{msg}}^+$, and $\sigma_{\text{agg}}^-/\sigma_{\text{agg}}^+$.

- A leaf- j transcript starts with $(p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8, \sigma_{\text{init}})$, where $1 \leq j < 2^{64}$ and the fields have fixed width. It then absorbs the leaf ciphertext byte string under $\sigma_{\text{msg}}^-/\sigma_{\text{msg}}^+$, using the same block rule.

The message byte string in this language is always the ciphertext byte string absorbed by the construction: encryption obtains it by XORing the plaintext with the current keystream, while decryption and verification use the submitted ciphertext. Thus a verification transcript is well formed for every in-domain ciphertext before the tag comparison is made; acceptance is not part of the transcript language.

The root aggregation byte string has the form $T_1 \parallel \dots \parallel T_n \parallel \langle n \rangle_8$, where each T_j has fixed byte length $\tau_{\text{leaf}}/8$. The trailing fixed-width field therefore gives a unique parse of the leaf tag sequence. The output-point class of a well-formed counted prefix is the class in Table 9 determined by its duplex instance and final-call suffix.

Name the tag-emitting transcript families:

$$\begin{aligned} \mathcal{R}_{\text{tag}} &= \text{root transcript prefix whose sponge output gives the final root tag,} \\ \mathcal{L}_{\text{tag}}[j] &= \text{leaf-}j \text{ transcript prefix whose sponge output gives the leaf tag.} \end{aligned}$$

The final root tag is emitted by the σ_{agg}^+ aggregation call (the $\mathcal{R}_{\text{tag}}$ family) when $n \geq 1$, and by the closing σ_{msg}^+ message call (an $\mathcal{R}_{\text{msg}}^+$ prefix, in the notation of Corollary 4) when $n = 0$ and the aggregation phase is elided. Since $n = \text{leaves}(C)$ is fixed by $\|C\|$, every computation on a given ciphertext emits its tag at the one of these two output points selected by $\|C\|$. Intermediate construction transcript lookup points (init, non-final AD, non-final message, and non-final aggregation) are also typed prefixes covered by Lemma 7; the exact keyed direct-query decoder names them in Table 9.

A.3 Transcript Injectivity

Lemma 5 (Transcript Injectivity). *Well-formed TW128 flattened duplex-call transcript prefixes are injectively encoded and separated by duplex instance (root vs leaf), leaf index j , phase suffix, and duplex-call order. For final-root prefixes, equality of flattened inputs recovers the same root initialization, AD blocks, root ciphertext blocks, aggregation input, and leaf tag sequence.*

Proof. By Lemma 4, every well-formed output point can be written as a [BDPVA11] flattened sponge input for the corresponding duplex-call prefix, namely Flat as defined above. The deterministic current-call `pad10*1` is applied internally by the sponge function and is not part of the input to which [BDPVA11, Lemma 4] is applied. That lemma recovers the duplex-call sequence from the flattened sponge input; in TW128, each call input is $\sigma \parallel \sigma_{\text{ph}}$ with byte-aligned σ and fixed 4-bit suffix σ_{ph} , so recovering the call input recovers the pair $(\sigma, \sigma_{\text{ph}})$.

Definition 1 fixes the root and leaf initialization fields, the admissible phase order, and the final-call suffixes. The distinct prefixes p_{root} and p_{leaf} separate root from leaf transcripts; the fixed-width leaf field $\langle j \rangle_8$ separates leaves; and the seven suffix values of Table 3 separate phases and non-final/final calls. Thus equality of flattened inputs forces equality of the recovered instance type, key, nonce, leaf index when present, phase suffixes, and duplex-call order.

Phase-recovery sub-claim. For each present phase $P \in \{\text{ad}, \text{msg}, \text{agg}\}$ (the ad phase is present exactly when the associated data is nonempty; see Section 3.5), TW128 absorbs the phase’s input byte string s_P by partitioning into ρ -byte blocks (with the empty case yielding a single empty block, per Section 3.5) and feeding each block to the duplex with suffix σ_P^- (non-final) or σ_P^+ (final). Lemma 4 and [BDPVA11, Lemma 4] recover the corresponding $(\sigma, \sigma_{\text{ph}})$ sequence from the flattened input. Because the partition map is deterministic and uniquely invertible on its image (the empty case yielding the single empty block carrying σ_P^+), concatenating the recovered σ blocks reconstructs s_P exactly. The map from s_P to the phase’s $(\sigma, \sigma_{\text{ph}})$ sequence is therefore injective.

Applied phase by phase to a well-formed final-root transcript:

- **AD.** The associated-data phase contributes a σ_{ad}^+ -tagged block exactly when the associated data is nonempty; an empty associated data elides the phase and contributes no block. When the phase is present the sub-claim recovers the AD byte string. Thus distinct associated-data strings $A_i \neq A_j$ are separated either by the presence versus absence of the AD phase (when exactly one is empty) or, when both are nonempty, by their distinct AD σ -block sequences.
- **MSG.** Distinct absorbed root or leaf ciphertext byte strings produce distinct MSG σ -block sequences; the message language of Definition 1 is ciphertext-absorbing for encryption and decryption alike.
- **AGG.** The aggregation phase is present exactly when $n \geq 1$ (Section 3.5). When it is present, the sub-claim applied to the aggregation byte string $T_1 \parallel \dots \parallel T_n \parallel \langle n \rangle_8$ recovers that byte string. The final eight bytes give $\langle n \rangle_8$, and each leaf tag has fixed byte length $\tau_{\text{leaf}}/8$, so the byte string has a unique parse as a leaf tag sequence. Two root aggregation encodings are therefore equal exactly when their leaf tag sequences are equal. When $n = 0$ the aggregation phase is absent and the final-root transcript ends at the recovered σ_{msg}^+ root message call; the MSG bullet recovers the root ciphertext byte string, and the absence of any $\sigma_{\text{agg}}^-/\sigma_{\text{agg}}^+$ call distinguishes such a prefix from every $n \geq 1$ final-root prefix.

Therefore the recovered final-root transcript determines the root initialization, AD blocks, root ciphertext blocks, and, when $n \geq 1$, the aggregation byte string and leaf tag sequence. $\square$

Lemma 6 (Leaf-Transcript Recovery). *Let two construction-generated final-root prefixes have equal flattened inputs, and suppose that no two distinct construction-generated final leaf transcripts produce the same leaf tag. Then equality of flattened inputs recovers the same leaf transcript sequence, and therefore the same full absorbed ciphertext.*

Proof. By Transcript Injectivity (Lemma 5), the two equal flattened final-root inputs recover the same root initialization, AD blocks, root ciphertext blocks, and, when $n \geq 1$, the same aggregation byte string and leaf tag sequence; the trailing $\langle n \rangle_8$ field fixes the common leaf count n . When $n = 0$ no leaf is present and the recovered root ciphertext blocks already constitute the full absorbed ciphertext. When $n \geq 1$, the aggregation byte string parses uniquely as the leaf tag sequence $T_1 \parallel \dots \parallel T_n$; under the hypothesis that distinct construction-generated final leaf transcripts receive distinct leaf tags, equality of the two leaf tag sequences forces, position by position, equality of the corresponding final leaf transcripts, hence of their absorbed leaf ciphertext bodies. Together with the common root ciphertext blocks this recovers the same full absorbed ciphertext. $\square$

A.4 Bridge and Typed Decoding

Lemma 7 (Bridge and Typed Decoding). *The random-oracle games used in Sections C and 6 to 8 are ordinary random-oracle games on a single random oracle $\text{RO}_{\text{flat}} : \{0, 1\}^* \rightarrow$*

$\{0,1\}^\infty$ over the unpadded [BDPVA08] H-input domain (Section 4.2), with TW128 root and leaf duplex outputs answered by the typed restriction

$$\text{RF}(X) = \text{RO}_{\text{flat}}(\text{flat}(X)), \quad \text{flat}(X) = I[r, r_{\max}](\text{raw_flat}(X)),$$

for $r = r_{\max} = 1344$. Here $\text{raw_flat}(X)$ is the native flattened input $\text{Flat}(\cdot)$ of Section A.2 applied to the duplex-call sequence of X , and $I[r, r_{\max}]$ is the [BDPVA11] Theorem 3 preprocessing map. The induced map $X \mapsto \text{flat}(X)$ is injective on well-formed typed TW128 duplex transcript prefixes. The exact decoder KeyedTWOut of Definition 2 then maps any direct-query input to either $\perp$ or a unique candidate key and counted output-point class.

Proof. The bridge $I[r, r_{\max}]$ is described by the proof of [BDPVA11, Theorem 3] in three steps: (1) pad the input with $\text{pad}10^*1[r]$; (2) for each r -bit block, append $r_{\max} - r$ zero bits; (3) strip the trailing $\text{pad}10^*$ from the result. The $\text{pad}10^*1$ padding in step (1) appends a 1, then $q = (-|\text{raw_flat}(X)| - 2) \bmod r$ zero bits, then a closing 1; the $\text{pad}10^*$ -unpadding in step (3) strips the $r_{\max} - r$ trailing zero bits introduced by step (2) together with the closing 1 of step (1). For TW128 with $r = r_{\max}$, step (2) appends an empty string and step (3) strips zero trailing zeros and the closing 1, so the net effect of steps (1) and (3) is to map a native flattened input $U = \text{raw_flat}(X)$ to $U \parallel 1 \parallel 0^q$. Any string in this image has a unique inverse: q is the number of trailing zero bits, the preceding bit is the inserted 1, and deleting this suffix recovers U .

Injectivity of flat on well-formed typed TW128 prefixes then follows from Lemma 5: distinct well-formed typed prefixes have distinct $\text{raw_flat}(\cdot)$ images, and the bridge is injective on that image. Direct adversary queries on inputs outside the bridged TW128 well-formed transcript language still count in $q_{\text{RO}}(\mathcal{B})$ (Section 4.3) but cannot trigger bad_{key} .

Counted transcript lookup points are the well-formed prefixes of Definition 1 whose classes are listed in Table 9: root or leaf initialization, root AD blocks, root and leaf message blocks, root aggregation blocks, and the final root tag point. An input accepted by KeyedTWOut therefore fixes a unique candidate key—by the injectivity just shown and the fixed-width key field of Lemma 5—and a unique output-point class, by Output-Point Separation (Corollary 4); inputs outside this well-formed transcript language decode to none. $\square$

The bridge injectivity established here underlies Opening Triple Separation (Proposition 1, Section 8): distinct (K, N, A) triples yield distinct bridged final root transcripts.

Corollary 4 (Output-Point Separation). *Every well-formed TW128 typed transcript prefix at a counted construction transcript lookup point belongs to exactly one of the following output-point classes, identified by the recovered duplex instance and the 4-bit suffix of its final call:*

- $\mathcal{R}_{\text{init}}(\text{root duplex, suffix } \sigma_{\text{init}})$,
- $\mathcal{L}_{\text{init}}(j)$ (leaf- j duplex, suffix σ_{init}),
- $\mathcal{R}_{\text{ad}}^- / \mathcal{R}_{\text{ad}}^+$ (root duplex, suffix σ_{ad}^- or σ_{ad}^+),
- $\mathcal{R}_{\text{msg}}^- / \mathcal{R}_{\text{msg}}^+$ (root duplex, suffix σ_{msg}^- or σ_{msg}^+),
- $\mathcal{L}_{\text{msg}}^-(j)$ (leaf- j duplex, suffix σ_{msg}^-),
- $\mathcal{L}_{\text{tag}}[j]$ (leaf- j duplex, suffix σ_{msg}^+),
- $\mathcal{R}_{\text{agg}}(\text{suffix } \sigma_{\text{agg}}^-)$,
- $\mathcal{R}_{\text{tag}}$ (root duplex, suffix σ_{agg}^+).

For any two such prefixes whose bridged flattened inputs are equal, the separation of Lemma 5 recovers the same duplex instance, leaf index j when present, (K, N) pair, output-point class, and duplex-call sequence. Equivalently, any two distinct counted transcript prefixes already differ in one of these recovered fields, and hence in their flattened inputs.

Proof. Lemma 7 recovers equality of native flattened inputs from equality of bridged inputs, after which Lemma 5 recovers the duplex-call sequence and its per-call $(\sigma, \sigma_{\text{ph}})$ pairs. The first call's σ is $p_{\text{root}} \parallel K \parallel N$ for root instances and $p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8$ for leaf instances, with fixed-width fields, so it fixes the instance type (by p_{root} vs p_{leaf}), the (K, N) pair, and the leaf index j ; the seven phase suffixes are pairwise distinct, so the final-call suffix fixes the output-point class, and each prefix therefore lies in exactly one class. Conversely, two distinct well-formed prefixes in the same class on the same instance differ in some recovered call's σ or in the sequence length, hence in their flattened inputs. $\square$

Definition 2 (Exact Keyed Decoder). For a direct query to RO_{flat} with input Y and finite length ℓ , define $\text{KeyedTWOOut}(Y)$ as a partial map from $\{0, 1\}^*$ to $\{0, 1\}^k \times \mathcal{C}_{\text{out}}$. The map ignores ℓ . It returns $(K, \mathcal{C})$ iff there exists a typed TW128 duplex-call prefix X such that $Y = \text{flat}(X)$, the raw flattened prefix of X parses as a well-formed TW128 transcript prefix in the class $\mathcal{C}$ listed in Table 9, and the first call of X contains the candidate key K in the fixed-width root field $p_{\text{root}} \parallel K \parallel N$ or leaf field $p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8$. If no such prefix exists, $\text{KeyedTWOOut}(Y) = \perp$. In particular, inputs with the right final suffix but a malformed phase order, noncanonical block partition, malformed aggregation string, or out-of-range leaf index are outside the well-formed language and decode to $\perp$. A non- $\perp$ decoding fixes not only the candidate key K but the candidate context components present in the decoded prefix: the nonce N occupies the remaining fixed-width init-field slot, and the associated data A is read off the recovered associated-data blocks. We use the key projection $(K, \mathcal{C})$ throughout; when a game hides a single context component $Z \in \{K, N, A\}$, the same decoding returns that component's candidate value, which we denote $\text{KeyedTWOOut}_Z(Y)$.

Table 9: Counted keyed transcript classes for KeyedTWOOut.

Class $\mathcal{C}$	Instance	Final call / role
$\mathcal{R}_{\text{init}}$	root	σ_{init} , root initialization
$\mathcal{R}_{\text{ad}}^-$	root	σ_{ad}^- , non-final AD block
$\mathcal{R}_{\text{ad}}^+$	root	σ_{ad}^+ , final AD block
$\mathcal{R}_{\text{msg}}^-$	root	σ_{msg}^- , non-final root message block
$\mathcal{R}_{\text{msg}}^+$	root	σ_{msg}^+ , final root message block
$\mathcal{R}_{\text{agg}}^-$	root	σ_{agg}^- , non-final aggregation block
$\mathcal{R}_{\text{tag}}$	root	σ_{agg}^+ , final aggregation / root tag
$\mathcal{L}_{\text{init}}(j)$	leaf j	σ_{init} , leaf initialization
$\mathcal{L}_{\text{msg}}^-(j)$	leaf j	σ_{msg}^- , non-final leaf message block
$\mathcal{L}_{\text{tag}}[j]$	leaf j	σ_{msg}^+ , final leaf message block / leaf tag

The table is a transcript-lookup table, not an observation-length table. A class is counted even when the construction's requested output length at that call is zero, including root initialization, non-final AD and aggregation calls, a final AD call whose following root chunk requests no keystream bytes, and the final root message call. A direct query triggers the same decoder regardless of ℓ : short finite-output queries and zero-length queries $(Y, 0)$ still count as direct queries to the address Y . Leaves have no AD or aggregation classes; a leaf transcript enters the table only through leaf initialization, non-final leaf message blocks, or the final leaf tag point. When the associated data is empty the root transcript likewise has no $\mathcal{R}_{\text{ad}}^-$ or $\mathcal{R}_{\text{ad}}^+$ class (Section 3.5); the $\mathcal{R}_{\text{init}}$ class then supplies the first root keystream block, exactly as $\mathcal{L}_{\text{init}}(j)$ supplies the first leaf keystream block, and the decoder

still ignores ℓ . Symmetrically, when $n = 0$ the root transcript has no $\mathcal{R}_{\text{agg}}$ or $\mathcal{R}_{\text{tag}}$ class (Section 3.5); the final root message call $\mathcal{R}_{\text{msg}}^+$ then supplies the root tag, exactly as $\mathcal{L}_{\text{tag}}[j]$ supplies a leaf tag, and the decoder again ignores ℓ . An $n \geq 1$ computation also reaches an $\mathcal{R}_{\text{msg}}^+$ point when closing chunk 0, but there the construction requests zero output and continues into the aggregation phase, so the $\mathcal{R}_{\text{msg}}^+$ value is exposed as a tag only on the $n = 0$ path; since $n = \text{leaves}(C')$ is fixed by $\|C\|$, the two uses never coincide on a single ciphertext.

A.5 Adaptive Candidate Bounds

Lemma 8 (Adaptive Candidate Collision and Preimage). *Consider any interaction with a lazy random oracle $\text{RO}_{\text{flat}} : \{0, 1\}^* \rightarrow \{0, 1\}^\infty$ that builds a sequence of distinct candidate inputs $Y_1, \dots, Y_m$. The process may make arbitrary non-candidate oracle queries and may choose each candidate adaptively from the full prior transcript. Whenever a new candidate Y_j is appended, two premises hold: predictability—both the decision to append and the string Y_j are determined by the transcript preceding the append step—and unrevealed value—no oracle lookup before the append step has requested a positive number of bits of $\text{RO}_{\text{flat}}(Y_j)$; zero-length lookups at Y_j are permitted. Fix a projection length τ and a cap Q .*

1. Collision. For every $s \geq 2$, if $m \leq Q + s$ then the probability $\Pr[\text{coll}_{s,\tau}]$ that some s distinct candidates have equal τ -bit projections,

$$[\text{RO}_{\text{flat}}(Y_{i_1})]_\tau = \dots = [\text{RO}_{\text{flat}}(Y_{i_s})]_\tau \quad \text{for some } 1 \leq i_1 < \dots < i_s \leq m,$$

satisfies $\Pr[\text{coll}_{s,\tau}] \leq \binom{Q+s}{s} \cdot 2^{-\tau(s-1)}$.

2. Preimage. For every target $t \in \{0, 1\}^\tau$ chosen independently of RO_{flat} , if $m \leq Q + 1$ then the probability $\Pr[\text{pre}_{\tau,t}]$ that some candidate's τ -bit projection equals t , i.e. $[\text{RO}_{\text{flat}}(Y_j)]_\tau = t$ for some $1 \leq j \leq m$, satisfies $\Pr[\text{pre}_{\tau,t}] \leq (Q + 1) \cdot 2^{-\tau}$.

3. Second-preimage. Fix a designated candidate position j_0 . If $m \leq Q + 2$, then the probability $\Pr[\text{sec}_{\tau,j_0}]$ that some candidate $j \neq j_0$ has $[\text{RO}_{\text{flat}}(Y_j)]_\tau = [\text{RO}_{\text{flat}}(Y_{j_0})]_\tau$, i.e. collides with the designated candidate on its τ -bit projection, satisfies $\Pr[\text{sec}_{\tau,j_0}] \leq (Q + 1) \cdot 2^{-\tau}$.

Proof. Both parts expose the interaction in chronological order and sample each candidate's RO_{flat} value lazily at its append step, which the premises license: when Y_j is appended its string is fixed by the prior transcript (predictability) and no bit of $\text{RO}_{\text{flat}}(Y_j)$ has yet been revealed (unrevealed value), so $\text{RO}_{\text{flat}}(Y_j)$ may be drawn then, uniform and independent of everything so far.

Collision. For a fixed position set $I = \{i_1 < \dots < i_s\} \subseteq \{1, \dots, Q + s\}$, let E_I be the event that these candidate positions exist and their τ -bit projections are all equal. Condition on any positive-probability prefix immediately before position i_r is appended, for $r \geq 2$, and on the values sampled at the earlier positions in I . By the above, $\text{RO}_{\text{flat}}(Y_{i_r})$ is then uniform and independent of the conditioning, so its τ -bit projection equals the already fixed projection of Y_{i_1} with probability $2^{-\tau}$. Multiplying over $r = 2, \dots, s$ gives $\Pr[E_I] \leq 2^{-\tau(s-1)}$; if some position in I is never appended then E_I is false and the bound still holds. A union bound over the $\binom{Q+s}{s}$ position sets gives the claim.

Preimage. For a fixed position $j \in \{1, \dots, Q + 1\}$, let E_j be the event that position j exists and $[\text{RO}_{\text{flat}}(Y_j)]_\tau = t$. Condition on any positive-probability prefix immediately before Y_j is appended; the target t is a constant. By the above, $\text{RO}_{\text{flat}}(Y_j)$ is uniform and independent of the conditioning, so its τ -bit projection equals t with probability $2^{-\tau}$. If position j is never appended, E_j is false. A union bound over the $Q + 1$ positions gives the claim.

2128 *Second-preimage.* Expose $\text{RO}_{\text{flat}}(Y_{j_0})$ at the append step of the designated candidate Y_{j_0} ,
 2129 which predictability and unrevealed value license; this fixes the target $t = \lfloor \text{RO}_{\text{flat}}(Y_{j_0}) \rfloor_\tau$
 2130 as a constant for the rest of the interaction. Each of the at most $Q + 1$ candidates Y_j
 2131 with $j \neq j_0$ is still unrevealed when appended, so the preimage argument applied with
 2132 this t gives that its projection equals t with probability $2^{-\tau}$; a union bound over those
 2133 positions gives $\Pr[\text{sec}_{\tau, j_0}] \leq (Q + 1) \cdot 2^{-\tau}$. The designated candidate Y_{j_0} is excluded, so its
 2134 trivially-equal projection does not enter the count. $\square$

2135 A.6 Adaptive Key Tests

2136 **Lemma 9** (Adaptive Key-Test Bound). *Consider a TW128 random-oracle-model game*
 2137 *with a single hidden context component Z sampled uniformly from $\{0, 1\}^w$ for some $w \geq k$ —*
 2138 *the standard case being the hidden key, $Z = K$ and $w = k$, used in Sections 6 and 7—direct*
 2139 *adversary access to RO_{flat} , and an immediate abort event bad_{key} that fires on a direct query*
 2140 *(Y, ℓ) exactly when $\text{KeyedTWO}_{\text{out}}(Y) = (Z, \mathcal{C})$ for some counted output-point class $\mathcal{C}$ of*
 2141 *Table 9. Suppose that, before the abort, the following invariant holds for every direct*
 2142 *query position i : after conditioning on the full visible execution prefix and on the set S_i of*
 2143 *distinct decoded candidate Z -values from earlier direct queries, the hidden Z is uniform on*
 2144 *$\{0, 1\}^w \setminus S_i$. Then*

$$2145 \Pr[\text{bad}_{\text{key}}] \leq q_{\text{RO}}/2^w \leq \text{KeyGuess}_k(q_{\text{RO}}) = q_{\text{RO}}/2^k,$$

2146 where q_{RO} is the execution-uniform count of direct RO_{flat} queries.

2147 *Proof.* If $q_{\text{RO}} \geq 2^w$ the right-hand side $q_{\text{RO}}/2^w$ is at least one, so the claim is trivial.
 2148 Assume $q_{\text{RO}} < 2^w$.

2149 Order the direct RO_{flat} queries. By the definition of $\text{KeyedTWO}_{\text{out}}$ and Lemma 7, each
 2150 query input either decodes to $\perp$ or decodes to a unique candidate Z -value and counted
 2151 output-point class. Queries that decode to $\perp$, and repeated queries whose decoded Z -value
 2152 already lies in the current set S_i , do not change the set of possible first successful tests.
 2153 Removing them can only shorten the sequence, so it suffices to analyze the subsequence of
 2154 distinct fresh decoded candidate Z -values $Z'_1, \dots, Z'_m$, where $m \leq q_{\text{RO}}$.

2155 Let F_i be the event that the first i fresh decoded candidate values all miss the hidden
 2156 Z . The invariant says that, conditioned on the visible prefix before the $(i + 1)$ -st fresh test
 2157 and on F_i , the hidden Z is uniform over the $2^w - i$ values not yet tested. The next fresh
 2158 candidate value Z'_{i+1} is one of those remaining values and is determined by the adversary's
 2159 next direct query, so

$$2160 \Pr[Z = Z'_{i+1} \mid F_i] = \frac{1}{2^w - i}, \quad \Pr[F_{i+1} \mid F_i] = 1 - \frac{1}{2^w - i}.$$

2161 Multiplying the miss probabilities gives

$$2162 \Pr[F_m] = \prod_{i=0}^{m-1} \left(1 - \frac{1}{2^w - i}\right) = \prod_{i=0}^{m-1} \frac{2^w - i - 1}{2^w - i} = \frac{2^w - m}{2^w}.$$

2163 Thus the probability that some fresh decoded candidate value equals the hidden Z is
 2164 $m/2^w \leq q_{\text{RO}}/2^w \leq q_{\text{RO}}/2^k$, the last step by $w \geq k$. This event is exactly the first bad_{key}
 2165 abort, because $\text{KeyedTWO}_{\text{out}}$ returns either $\perp$ or a unique candidate Z -value. $\square$

2166 A.7 Leaf Tag Collision Bound

2167 **Lemma 10** (Leaf Tag Collision Bound). *Consider any TW128 random-oracle-model*
 2168 *game with a hidden key, an adversary $\mathcal{B}$ with direct access to RO_{flat} , and construction*
 2169 *computations that may generate final leaf transcripts; $n_{\text{leaf}}(\mathcal{B})$ denotes the execution-uniform*

count of distinct construction-generated final leaf transcripts of Section 4.3. Let hit_{leaf} be the event that, before some construction-generated keyed final leaf transcript is first created, a direct adversary query to RO_{flat} has already hit the bridged input of that hidden-key leaf transcript. Let bad_{leaf} be the event that two distinct construction-generated keyed final leaf transcript prefixes $X \neq X'$ in leaf tag output-point classes receive the same τ_{leaf} -bit projection from $\text{RF}(\cdot)$. Then the probability that bad_{leaf} occurs before hit_{leaf} is bounded by

$$\Pr[\text{bad}_{\text{leaf}} \text{ before } \text{hit}_{\text{leaf}}] \leq \binom{n_{\text{leaf}}(\mathcal{B})}{2} \cdot 2^{-\tau_{\text{leaf}}} = \frac{n_{\text{leaf}}(\mathcal{B})(n_{\text{leaf}}(\mathcal{B}) - 1)}{2^{\tau_{\text{leaf}} + 1}}.$$

Proof. Construction-generated means generated by encryption computations or by INT-CTXT verification computations (whether they accept or reject). Repeated evaluations of the same final leaf transcript are not new collision opportunities, since the lazy-sampled RO_{flat} value is reused.

Run the relevant game and stop the leaf-collision accounting if hit_{leaf} occurs. The execution-uniform resource $n_{\text{leaf}}(\mathcal{B})$ of Section 4.3 bounds the number of distinct final leaf transcripts. Order those transcripts by first creation. At the moment such a transcript is first created by a construction computation before the stop, no earlier direct RO_{flat} query has hit the bridge image of that hidden-key transcript by definition of hit_{leaf} . Nor has an earlier construction computation queried the same RO_{flat} input under a different well-formed transcript: Lemma 5 separates distinct final leaf transcript encodings, and the [BDPVA11, Theorem 3] bridge is injective. The τ_{leaf} -bit leaf tag projection of $\text{RF}(X)$ for that transcript sampled at that moment is therefore uniform and independent of the entire prior game view, including the prior RO_{flat} table on other inputs, prior ciphertext and tag outputs, and the leaf tag projections assigned to all distinct prior final leaf transcripts.

For any fixed unordered pair of distinct final leaf transcripts created before this stop, the probability that their leaf tags are equal is $2^{-\tau_{\text{leaf}}}$. There are at most $\binom{n_{\text{leaf}}(\mathcal{B})}{2}$ such pairs, and a union bound gives the claim. By Leaf-Transcript Recovery (Lemma 6), conditioned on no leaf tag collision, equal root aggregation inputs identify the same leaf transcript sequence. $\square$

A.8 Transcript Freshness

Lemma 11 (Transcript Freshness). *For any fixed nonce-respecting encryption query in the TW128 random-oracle experiment, let $\text{hit}_{\text{fresh}}$ be the event that, before this query reaches some counted transcript point, a prior direct adversary query to RO_{flat} has already hit the bridged input of that hidden-key point. On $\neg\text{hit}_{\text{fresh}}$, every transcript output of the query that contributes to a returned ciphertext block, to an internal leaf tag, or to the final root tag is fresh at the moment its RO_{flat} value is sampled.*

Proof. Work on an execution outside $\text{hit}_{\text{fresh}}$ for the fixed query. This rules out prior adversary reads of the hidden-key construction inputs considered below. It remains to rule out repeats from previous construction-interface outputs and from the current encryption query.

First root keystream block. The first root keystream block, when present, is produced by the root duplex after the initialization call $p_{\text{root}} \parallel K \parallel N$ and any AD absorption (elided when $A = \varepsilon$, in which case the σ_{init} call itself emits the first root keystream block). Since the privacy adversary never repeats a nonce, no previous encryption query can have used the same root initialization transcript. Within the current query, Lemma 5 separates initialization, AD, message, and aggregation calls by their suffixes and by the duplex-call encoding, so the first root keystream transcript is fresh. If the requested keystream length is zero, no ciphertext block is returned at that point and there is nothing to prove for that output.

2217 **First leaf keystream block.** For each leaf chunk $j \geq 1$, the first leaf keystream block is
 2218 produced after the initialization call $p_{\text{leaf}} \parallel K \parallel N \parallel \langle j \rangle_8$. The prefix separates leaves from
 2219 the root, the nonce separates this encryption query from all previous encryption queries,
 2220 and $\langle j \rangle_8$ separates leaves within this query. Hence every first leaf keystream transcript is
 2221 fresh.

2222 **Later message outputs.** Argue inductively within each root or leaf message stream.
 2223 Suppose the current message-output transcript is fresh. If its output is used as a keystream
 2224 block, its RO_{flat} value Z_i is, by freshness of the lazy sample, uniform conditioned on the
 2225 full prior view; since the adaptive plaintext block M_i is a deterministic function of that
 2226 prior view,

$$C_i = M_i \oplus Z_i$$

2227
 2228 is uniform conditioned on the prior view. TW128 then absorbs C_i with the appropriate
 2229 message-phase suffix (σ_{msg}^- or σ_{msg}^+) before requesting the next keystream block. Once C_i is
 2230 sampled, the next transcript is fixed; Lemma 5's injectivity and domain separation imply
 2231 it has not appeared earlier unless the same duplex-call prefix has appeared earlier. Nonce
 2232 uniqueness excludes this across encryption queries. By Corollary 4, the next message-
 2233 keystream output point can coincide with a within-query earlier output point only if both
 2234 belong to the same output-point class on the same duplex instance (root or leaf- j with
 2235 matching j) and have the same duplex-call sequence; the current message-stream prefix
 2236 is strictly longer than every earlier prefix in that stream, so this is excluded. Across
 2237 distinct instances within the same query (root vs leaf, or two leaves with distinct j), the
 2238 prefixes already differ in the first call's σ by $p_{\text{root}}/p_{\text{leaf}}$ or $\langle j \rangle_8$ respectively. Each later
 2239 message-output transcript that emits keystream is therefore fresh when sampled. The
 2240 terminal message-output transcript of a leaf emits the leaf tag rather than a following
 2241 keystream block; the same separation argument applies to that transcript, so each internal
 2242 leaf tag is sampled at a fresh point. Empty inputs still induce a duplex call, but with zero
 2243 keystream output they contribute no ciphertext block.

2244 **Final root tag transcript.** The final root tag is sampled at the root tag output point
 2245 selected by $\|C\|$: the $\mathcal{R}_{\text{tag}}$ point after the root duplex absorbs the aggregation transcript
 2246 built from the leaf tags and $\langle n \rangle_8$ when $n \geq 1$, and the $\mathcal{R}_{\text{msg}}^+$ point closing the root
 2247 message phase when $n = 0$ (Section 3.5). When $n \geq 1$, the leaf tags are themselves
 2248 RO_{flat} outputs on final leaf transcripts; condition on their sampled values, on the sampled
 2249 ciphertext, and on the adversary-visible prior view and RO_{flat} table state, so that the root
 2250 aggregation transcript is fixed. When $n = 0$ there is no aggregation transcript; condition
 2251 on the sampled ciphertext and the adversary-visible prior view alone. By Corollary 4,
 2252 the selected root tag output-point class is separated from every other output-point class
 2253 in the same query — including root initialization (suffix σ_{init}), AD-phase outputs, the
 2254 remaining message-phase outputs, leaf-side output points (separated by p_{leaf}), and, in the
 2255 $n \geq 1$ case, earlier $\mathcal{R}_{\text{agg}}$ -prefix output points (separated by the σ_{agg}^- vs σ_{agg}^+ suffix). Even if
 2256 two encryption queries realize the same aggregation transcript (or, for $n = 0$, the same
 2257 root ciphertext), the full root transcript also contains the root initialization $p_{\text{root}} \parallel K \parallel N$,
 2258 and nonce uniqueness separates that initialization from all previous encryption queries.
 2259 The final root tag transcript is therefore fresh, and its τ_{root} -bit RO_{flat} output is uniform
 2260 independently of the conditioned information. $\square$

2261 A.9 Privacy Accounting Lemmas

2262 The random-oracle privacy proof of Theorem 7 uses Transcript Freshness and the Adaptive
 2263 Key-Test Bound through the privacy-specific interfaces below. These interfaces track
 2264 the hidden key through the set of key values still viable after the visible stopped-game

prefix. The stopped privacy games use the event bad_{key} from Theorem 7: a direct query (Y, ℓ) aborts when $\text{KeyedTWOOut}(Y) = (K, \mathcal{C})$ for the hidden or auxiliary key K and a counted output-point class $\mathcal{C}$. The stopped games inspect this predicate before returning the direct-oracle answer for the offending query; if it holds, no answer for that query is included in the adversary's view.

Lemma 12 (Privacy One-Query Replacement). *Fix a nonce-respecting privacy adversary and an index $i \geq 0$. Let H_i be the stopped privacy hybrid that samples $K \leftarrow \$ \{0, 1\}^k$, answers the first i accepted encryption queries by Rand , answers all later accepted encryption queries by Enc_K^{RO} , answers direct RO_{flat} queries by the lazy table, and aborts on bad_{key} . On executions with fewer than $i + 1$ accepted encryption queries, the two hybrids coincide. Then H_i and H_{i+1} can be coupled so that the adversary's visible transcript and the abort indicator are identical. In particular, they have identical joint distributions of the adversary's view and the abort indicator.*

Proof. Use the same adversary coins, the same key K , and the same answers to all direct queries and encryption queries before the $(i + 1)$ -st accepted encryption query. If the adversary never makes that query, the coupling is immediate. Otherwise condition on any common positive-probability visible prefix that includes the submitted query but not its oracle answer, and on no earlier abort. Let the query be (N, A, M) .

Viable-key prefix. Let S be the set of distinct keys K' for which some prior direct query input Y satisfies $\text{KeyedTWOOut}(Y) = (K', \mathcal{C})$ for a counted output-point class $\mathcal{C}$, and let $\mathcal{V} = \{0, 1\}^k \setminus S$. Before the $(i + 1)$ -st accepted encryption query in H_i , the accepted construction-interface queries were answered by Rand , so the visible encryption answers and the lazy direct-query answers are independent of the hidden key except through the immediate-abort rule, which removes exactly the keys in S ; hence the hidden key is uniform on $\mathcal{V}$ under this conditioning. For every $K' \in \mathcal{V}$, running the online execution of $\text{Enc}_{K'}^{\text{RO}}$ on the pending query reaches no counted transcript point whose bridged input was previously queried directly: such a point Y would give $\text{KeyedTWOOut}(Y) = (K', \mathcal{C})$ by Lemma 7, placing K' in S . The bridged transcript inputs reached for two distinct keys in $\mathcal{V}$ are disjoint, since equal inputs would, by bridge injectivity and Lemma 5, recover the same first duplex call and hence the same fixed-width key field.

For the actual key in H_i , the no-hit condition is precisely the event $\neg \text{hit}_{\text{fresh}}$ of Lemma 11 for the pending computation: any prior direct query that hit a counted transcript point reached by the computation would, by Lemma 7, be decoded by KeyedTWOOut to the hidden key K and would already have triggered bad_{key} . Applying Lemma 11 gives freshness for every construction output of the query that contributes to the returned ciphertext, to an internal leaf tag, or to the final root tag. Applying the same transcript freshness argument to each $K' \in \mathcal{V}$, and using the disjointness of key-indexed transcript inputs established above, enumerate all such outputs in the order taken by the encryption computation.

Thus, to describe the conditional law, introduce an auxiliary online family of uniform coins indexed by a viable key and by the output position reached in that key's encryption computation. These auxiliary coins are sampled independently of the hidden key. If the hidden key is K' , the H_i computation reads the K' -row and installs only those row entries in the lazy table, at the transcript addresses actually reached by $\text{Enc}_{K'}^{\text{RO}}$. The coins for other viable keys are not lazy-table entries; they only witness that every possible hidden-key row induces the same distribution on the returned string. A later direct query to a nonactual viable-key address is therefore answered by the ordinary shared lazy table in both hybrids, not by a coin sampled during this replacement coupling.

Each plaintext block is fixed before the corresponding keystream coin is drawn, so XOR with that coin makes the ciphertext block uniform. Once a ciphertext block is fixed, the next message transcript is fixed and fresh at its sampling time. When $n \geq 1$, leaf tags are sampled from fresh coins as well; after these tags and the ciphertext are fixed, the aggregation transcript is fixed and the final root tag is sampled from another fresh coin

at the $\mathcal{R}_{\text{tag}}$ point. When $n = 0$ the aggregation phase is elided and the final root tag is instead the fresh coin at the closing $\mathcal{R}_{\text{msg}}^+$ root message point. Hence the returned string (C, T) is jointly uniform of length $\|M\| + \tau_{\text{root}}/8$ and independent of K conditioned on the prefix. In the coupling, the Rand answer in H_{i+1} is sampled as this same independent string.

It remains to compare the lazy-table state exposed after this query. The entries that may be written in H_i but not in H_{i+1} are construction-internal entries at hidden-key counted transcript inputs for nonce N . A later direct adversary query to any such input would be decoded by KeyedTWOut to K and would trigger bad_{key} before returning an oracle answer, so the possibly different table entry is never exposed. Later real encryption queries use nonces different from N by nonce-respectingness, and their typed construction inputs are therefore disjoint from this query's inputs by Corollary 4. Thus the extra lazy-table entries are unobservable before the abort. Continuing the coupling with shared answers on all exposed direct-oracle inputs and all later real construction inputs gives identical visible transcripts and identical abort indicators. $\square$

Lemma 13 (Privacy Stopped-Game Advantage Bound). *Let P_0 and P_1 be the unstopped real and ideal privacy games of Theorem 7, with P_1 carrying the auxiliary key used only for the abort predicate, and let P_0^{stop} and P_1^{stop} be their immediate-abort variants. Assume the adversary $\mathcal{B}$ has an execution-uniform cap q_e on accepted encryption queries. Then for any event E determined by the adversary's final output in the unstopped games,*

$$|\Pr[E \text{ in } P_0] - \Pr[E \text{ in } P_1]| \leq \text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})).$$

Proof. Stopped-game equality. Define hybrids $H_0, \dots, H_{q_e}$ as in Lemma 12. Then $H_0 = P_0^{\text{stop}}$. Since every accepted encryption query is among the first q_e such queries, H_{q_e} is P_1^{stop} . Applying Lemma 12 for $i = 0, \dots, q_e - 1$ gives the same joint distribution of the adversary's view and the abort indicator in adjacent hybrids, and telescoping gives the same joint distribution in the two stopped games. Write

$$p = \Pr[\text{bad}_{\text{key}} \text{ in } P_1^{\text{stop}}];$$

by the stopped-game equality the abort probability is also p in P_0^{stop} . For each side $b \in \{0, 1\}$, the unstopped game P_b and its stopped variant P_b^{stop} agree exactly until the first bad_{key} direct query and have the same occurrence probability for that event. Hence, for the final-output event E ,

$$\Pr[E \text{ in } P_b] = \Pr[E \wedge \neg \text{bad}_{\text{key}} \text{ in } P_b^{\text{stop}}] + x_b$$

for some $0 \leq x_b \leq p$. The first terms are equal for $b = 0$ and $b = 1$ by stopped-game equality, while $x_0, x_1 \in [0, p]$, so

$$|\Pr[E \text{ in } P_0] - \Pr[E \text{ in } P_1]| \leq p.$$

Abort bound. It remains to show $p \leq \text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B}))$. Let P_1^{aux} be the non-aborting version of the ideal privacy game: it samples the auxiliary key $K \leftarrow \$ \{0, 1\}^k$, answers construction queries by fresh random strings exactly as Rand does, answers direct RO_{flat} queries by the ordinary lazy table, and never aborts. For each direct query input Y_i , Lemma 7 either rejects Y_i as outside the bridged well-formed TW128 transcript language or recovers a unique candidate key from the decoded keyed transcript prefix.

The visible-prefix uniformity invariant required by Lemma 9 holds in P_1^{aux} . Condition on any positive-probability visible execution prefix immediately before a direct query, on no earlier bad_{key} , and on the set S_i of distinct candidate keys decoded from prior direct-query inputs. Construction responses are fresh random strings, direct RO_{flat} answers are lazy

random-oracle values, and both are independent of the auxiliary key K ; the no-earlier-abort condition removes exactly the keys in S_i . Thus K remains uniform on $\{0, 1\}^k \setminus S_i$.

The first bad_{key} event in $\mathcal{P}_1^{\text{stop}}$ has the same probability as the first successful adaptive key test in $\mathcal{P}_1^{\text{aux}}$, because the two games are identical up to that query. Applying Lemma 9 with $q_{\text{RO}} = q_{\text{RO}}(\mathcal{B})$ gives $p \leq \text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B}))$. Combining with the stopped-game bound proves the claim. $\square$

A.10 INT-CTXT Accounting Lemmas

The INT-CTXT proof of Theorem 8 uses the generic key-test and leaf-collision accounting lemmas together with the INT-specific facts below. The *root tag output point* of a computation is the output point that emits its root tag: $\mathcal{R}_{\text{tag}}$ (suffix σ_{agg}^+) when $n \geq 1$, and the closing root message point $\mathcal{R}_{\text{msg}}^+$ (suffix σ_{msg}^+) when $n = 0$ and the aggregation phase is elided (Section 3.5). Because $n = \text{leaves}(C)$ is fixed by $\|C\|$, all computations on a common ciphertext share the same root tag output point. A *final root transcript class* is the set of construction computations whose encryption or verification computation realizes the same bridged final root input at this root tag output point. Such a class is *encryption-first* if its first construction generation is by an encryption query, and *verification-first* if its first construction generation is by a non-replay verification query.

Lemma 14 (INT Visible-Prefix Key Uniformity). *In the random-oracle INT-CTXT game stopped at bad_{key} as in Theorem 8, order the direct RO_{flat} queries. For a direct query position i , let S_i be the set of distinct candidate keys decoded by KeyedTWOOut from earlier direct-query inputs. Condition on any positive-probability visible execution prefix immediately before query i , on no earlier bad_{key} , and on S_i . Then the hidden key K is uniform on $\{0, 1\}^k \setminus S_i$. Consequently the uniformity invariant required by Lemma 9 holds in the stopped INT-CTXT game.*

Proof. The visible prefix contains the adversary’s oracle queries and replies: direct RO_{flat} outputs, encryption outputs and the resulting replay table, verification bits, and the adversary state determined by these values. Fix such a prefix and two keys $K_0, K_1 \notin S_i$.

Define a transcript-renaming map $\Phi_{0 \rightarrow 1}$ on typed construction prefixes by replacing the first-call key field K_0 by K_1 and leaving every other recovered field unchanged: the nonce, leaf index, phase sequence, AD blocks, ciphertext blocks, leaf tag bytes appearing in root aggregation, and the root/leaf instance identifier are preserved. Let $\Phi_{1 \rightarrow 0}$ be the inverse map. By Lemma 7 and Corollary 4, $\text{flat} \circ \Phi_{0 \rightarrow 1} \circ \text{flat}^{-1}$ is a bijection between the bridged construction-addresses whose decoded key is K_0 and those whose decoded key is K_1 ; it preserves output-point classes and equality relations among addresses.

This bijection is applied online, not to a pre-existing fixed address set. Whenever a construction computation under K_0 would first query a hidden-key address Y , the coupled computation under K_1 queries $\Phi_{0 \rightarrow 1}(Y)$ and receives the same lazy-table value; repeated queries are coupled consistently through the same map. If the queried address is a root aggregation address containing leaf tag bytes, those bytes are already coupled equal because the corresponding leaf tag lookups were either repeated or first sampled earlier under the same renaming rule. Thus adaptively generated message transcripts and root aggregation transcripts are renamed step by step with the same visible ciphertext, leaf tag, and root tag bytes.

Prior direct-query inputs are not renamed: they are adversary-chosen visible strings. None lies in either hidden-key construction-address set for K_0 or K_1 , because any prior direct query to such an address would be decoded by KeyedTWOOut to K_0 or K_1 and would put that key in S_i . Direct-query lazy-table values are therefore coupled identically and remain disjoint from the renamed hidden construction addresses.

Use the same adversary coins, the same direct-query lazy-table values, and the online renamed construction-internal lazy-table values. Encryption outputs have the same distri-

bution under the coupling, because every construction lookup that determines ciphertext, leaf tags, or the final root tag is paired with a distinct renamed lookup carrying the same sampled value. Replay verification decisions depend only on the visible replay table. Non-replay verification computations are renamed in the same online way as encryption computations, and the final root tag comparison therefore gives the same accept/reject bit. Verification does not reveal plaintext on rejection or acceptance; it reveals only that bit.

Thus every visible prefix with hidden key $K_0 \notin S_i$ has the same conditional probability as the corresponding execution with hidden key $K_1 \notin S_i$. Since K is initially uniform and the condition “no earlier bad_{key} ” removes exactly the keys in S_i , all keys in $\{0, 1\}^k \setminus S_i$ remain equally likely. $\square$

Lemma 15 (INT Verification-First Root Guessing). *In the random-oracle INT-CTXT game stopped before $\text{bad}_{\text{key}} \cup \text{bad}_{\text{leaf}}$, let win_{vf} be the event that some accepting non-replay verification submission belongs to a verification-first final root transcript class. Then*

$$\Pr[\text{win}_{\text{vf}}] \leq q_v(\mathcal{B})/2^{\tau_{\text{root}}}.$$

Proof. Throughout, a *non-replay verification submission* means a valid non-replay verification query; by the validity convention, an invalid verification query returns 0 and performs no construction computation, so it realizes no bridged final root input, belongs to no final root transcript class, and contributes to no $G_{\mathcal{C}}$.

Work in the game stopped at the first occurrence of bad_{key} or bad_{leaf} . For accounting, define an all-reject continuation: encryption queries are answered normally, replay verification queries accept normally, and every non-replay verification submission performs the same construction computation but returns reject to the adversary. Lazy sampling is deferred for each verification-first class’s final root tag value: the continuation records the class address and the submitted tag, but while the class remains verification-first it does not expose that root tag value to the adversary. The execution-uniform count $q_v(\mathcal{B})$ applies to this continuation.

Fix a verification-first final root transcript class $\mathcal{C}$ and follow the all-reject path until the first later encryption query generating the same class, if any. Let $G_{\mathcal{C}}$ be the set of distinct candidate tags submitted by non-replay verification queries in class $\mathcal{C}$ before that cutoff. Repeated tags only shrink this set. The class’s correct root tag $U_{\mathcal{C}}$ is the τ_{root} -bit projection of RO_{flat} at the class’s bridged root tag input. Before the stop, no direct query has hit this hidden-key input: such a query would be decoded by KeyedTWOut to the hidden key and would trigger bad_{key} . Before the cutoff, no encryption query has revealed $U_{\mathcal{C}}$ as an encryption tag. (When the class’s root tag point is $\mathcal{R}_{\text{msg}}^+$, i.e. $n = 0$, an encryption query on a longer message that shares chunk 0 may touch this same address while closing its chunk-0 message phase, but it requests zero output there and continues into its aggregation phase, so it does not reveal $U_{\mathcal{C}}$; its own tag is emitted at a later $\mathcal{R}_{\text{tag}}$ point.) The all-reject path and the set $G_{\mathcal{C}}$ are therefore functions only of the adversary’s coins, visible oracle replies, and lazy-table values at inputs other than this class’s root tag address. By lazy sampling, conditioned on those values and on the fixed path, $U_{\mathcal{C}}$ may be sampled after $G_{\mathcal{C}}$ is fixed and is uniform independently of $G_{\mathcal{C}}$.

After the cutoff, if it exists, class $\mathcal{C}$ contributes no accepting non-replay submission. Let the cutoff encryption query return (N_e, A_e, C_e, T_e) . Any later verification submission in the same final root transcript class has, by the final-root determinacy of Lemma 5 and Leaf-Transcript Recovery (Lemma 6) under the absence of bad_{leaf} , the same (N, A, C) as that encryption computation. If the submitted tag is T_e , the tuple is a recorded encryption tuple and the verification is a replay; if the submitted tag is not T_e , the final tag comparison fails.

Consider the event that the first accepting non-replay verification submission in the stopped game belongs to class $\mathcal{C}$. Up to that global first accept, the adversary’s visible answers match the all-reject continuation: every earlier non-replay submission rejects,

replay queries accept in both executions, and encryption answers are unchanged. The construction computations also agree at every address except that the all-reject continuation defers the final root tag value for class $\mathcal{C}$ until the comparison is needed. Therefore the first accepting non-replay submission can belong to class $\mathcal{C}$ only before the cutoff, and only if $U_{\mathcal{C}} \in G_{\mathcal{C}}$, which has probability at most $|G_{\mathcal{C}}|/2^{\tau_{\text{root}}}$.

Each non-replay verification submission deterministically reconstructs one final root transcript at the root tag output point. If the class is verification-first and the submission occurs before that class's encryption cutoff, the submitted tag contributes to at most one set $G_{\mathcal{C}}$; otherwise it contributes to none. Thus $\sum_{\mathcal{C}} |G_{\mathcal{C}}| \leq q_v(\mathcal{B})$, and a union bound over the verification-first classes gives the claim. $\square$

A.11 Multi-User Hybrid Lemma

The multi-user indistinguishability theorem (Theorem 2) telescopes a hybrid over the D users, replacing one real user by its ideal (Rand, Replay) interface at each step. The following lemma bounds one such step, reusing the privacy accounting of Lemma 12 and the INT-CTXT accounting of Theorem 8 within a shared random-oracle environment.

Lemma 16 (Mu-Ind Adjacent-Hybrid Bound). *Let $\mathcal{B}$ be a flat-RO mu-ind adversary in the pre-sampled-key formulation of Section 4.4, with keys $K_1, \dots, K_D$ sampled at the start of the experiment. Fix $d \in \{1, \dots, D\}$. Let H_{d-1}^* and H_d^* be the adjacent stopped hybrids that output a fixed bit if any two sampled keys collide, and otherwise run $\mathcal{B}$ with one shared lazy RO_{flat} table as follows: users $e < d$ are answered by (Rand, Replay), users $e > d$ are answered by $(\text{Enc}_{K_e}^{\text{RO}}, \text{Ver}_{K_e}^{\text{RO}})$, and user d is answered by $(\text{Enc}_{K_d}^{\text{RO}}, \text{Ver}_{K_d}^{\text{RO}})$ in H_{d-1}^* and by (Rand, Replay) in H_d^* . If $n_{\text{leaf}}^{(d)}$ and $q_v^{(d)}$ are the user- d resource caps, then*

$$|\Pr[\mathcal{B}^{H_{d-1}^*} \Rightarrow 1] - \Pr[\mathcal{B}^{H_d^*} \Rightarrow 1]| \leq 2\text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})) + \frac{n_{\text{leaf}}^{(d)}(n_{\text{leaf}}^{(d)} - 1)}{2^{\tau_{\text{leaf}}+1}} + \frac{q_v^{(d)}}{2^{\tau_{\text{root}}}}.$$

Proof. The fixed-output branch on a key collision is identical in H_{d-1}^* and H_d^* , so only the branch with pairwise distinct keys contributes. On that branch, the two hybrids differ only in user d : users $e < d$ are ideal in both hybrids, and users $e > d$ are real in both hybrids.

Let $\mathcal{E}_d$ denote the common surrounding environment. It runs $\mathcal{B}$, answers users $e < d$ by their (Rand, Replay) interfaces, answers users $e > d$ by $\text{Enc}_{K_e}^{\text{RO}}, \text{Ver}_{K_e}^{\text{RO}}$, forwards $\mathcal{B}$'s direct RO_{flat} queries unchanged, and shares the same lazy RO_{flat} table with user d . The Bellare–Namprep insertion is pathwise in this environment. Insert the interface in which user d 's encryption oracle is still real but user d 's verification oracle is replaced by its replay table. The first hop is the user- d INT-CTXT event; the second hop is the user- d privacy replacement with the same environment and replay table. The replay table is determined by user d 's encryption answers and adds no direct RO_{flat} queries or construction-generated transcripts.

The privacy and INT-CTXT accounting used in these two hops is local to user d 's keyed transcript language. In the privacy hop, the one-query replacement of Lemma 12 only requires that no direct query has read a user- d counted transcript before $\text{bad}_{\text{key}}^{(d)}$, the bad_{key} event of Sections 6 and 7 instantiated at user d 's key K_d ; any extra lazy-table entries written by the real user- d encryption computation are unobservable before that abort. The accepted user- d encryption queries are nonce-respecting because the mu-ind interface enforces nonce uniqueness per user. In the INT-CTXT hop, the analysis of Theorem 8—its visible-prefix key uniformity (Lemma 14), its leaf-freshness and encryption-first-replay steps, and the verification-first root-guessing bound (Lemma 15)—refers only to user- d hidden-key transcript points, user- d final leaf transcripts, and user- d non-replay verification submissions.

It remains to justify that the same-RO environment does not enlarge the direct-query term. The real users $e > d$ may perform construction-internal RO_{flat} lookups while

simulating $\text{Enc}_{K_e}^{\text{RO}}$ and $\text{Ver}_{K_e}^{\text{RO}}$. Whenever such a lookup lies in a counted keyed transcript class, Lemma 7 decodes its candidate key as K_e ; on the non-collision branch this is different from K_d . If the lookup is outside the counted keyed language, it is irrelevant to $\text{bad}_{\text{key}}^{(d)}$. Thus foreign-user construction lookups neither trigger user d 's key-test event nor pre-read a user- d hidden transcript point. They also do not create user- d leaf tag collisions or user- d verification attempts, which are counted by $n_{\text{leaf}}^{(d)}$ and $q_v^{(d)}$.

The key-test contribution is taken in the original pre-sampled-key experiment, not in a renormalized experiment conditioned on the non-collision branch. Fix the foreign keys and run the visible-prefix coupling used in the user- d privacy and INT-CTXT proofs, with foreign-key transcript addresses left unchanged. Before the first user- d key hit, the visible prefix is invariant under renaming K_d among keys not already tested and not equal to any fixed foreign key. For each fresh candidate key tested by one of $\mathcal{B}$'s original direct RO_{flat} queries, the event contributing on the stopped branch is contained in $\{K_d \text{ equals that candidate}\}$; if the candidate is a foreign key, it contributes nothing on the non-collision branch. Hence each fresh original direct test costs at most 2^{-k} in the unconditioned key experiment, and at most $q_{\text{RO}}(\mathcal{B})$ such tests occur.

The proofs of Theorems 7 and 8 therefore apply to the two user- d hops with the same direct-query cap $q_{\text{RO}}(\mathcal{B})$ and the same user- d construction resources $n_{\text{leaf}}^{(d)}, q_v^{(d)}$. The surrounding environment affects oracle scheduling and foreign construction-internal table entries, but not the counted user- d events. The privacy hop contributes $\text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B}))$, and the INT-CTXT hop contributes

$$\text{KeyGuess}_k(q_{\text{RO}}(\mathcal{B})) + \frac{n_{\text{leaf}}^{(d)}(n_{\text{leaf}}^{(d)} - 1)}{2^{\tau_{\text{leaf}} + 1}} + \frac{q_v^{(d)}}{2^{\tau_{\text{root}}}}.$$

Combining the two hops gives the stated bound. $\square$

B The Flat-Sponge Lift

This appendix expands the sketch of Section 5.2 into the full argument: it supplies the flat-sponge lift machinery (Lemmas 18 and 19 and Corollary 5) invoked by the headline theorems of Section 5.3 and by Section C.

B.1 Simulator Convention

Throughout this appendix, $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$ denotes the public-primitive simulator supplied by [BDPVA08, Theorem 2] — the indistinguishability theorem for the simple padded sponge over a random permutation — after applying the [BDPVA11, Theorem 3] bridge of Lemma 7 to TW128's native `pad10*1` transcript inputs. The superscript records that both simulator directions share the same internal lazy RO_{flat} table. This is the simulator referenced by the Sections 4.1 and 4.4 definitions of $\text{Adv}_{\text{TW128}}^{\text{priv}}$, $\text{Adv}_{\text{TW128}}^{\text{ae}}$, and $\text{Adv}_{\text{TW128}}^{\text{mu-ind}}$: the ideal side of each AE-style experiment exposes the construction interface specified by the game (either `Rand` or `(Rand, Replay)`), instantiated per user in `mu-ind`) together with $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$ as the public-primitive interface. The RO_{flat} table in this notation is internal to the ideal system and is not an extra interface exposed to the application adversary; the INT-CTXT and committing-security advantages remain the real public-permutation success probabilities of Section 4.1, with the simulator appearing only inside the reduction to the corresponding random-oracle-model adversary.

Lemma 17 (Simulator RO-Call Filter). *For the simulator $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$, every inverse primitive-interface query and every forward primitive-interface query violating one of the following conditions induces no simulator RO_{flat} call. The symbols s , p , $\mathcal{R}$, $\mathcal{O}$, and $\mathcal{C}$ are the local internal notation of the BDPV simple-padded-sponge simulator, not TW128 resource notation:*

2557 **(C1) New edge.** *The simulator's internal graph has no outgoing edge from the input node*
 2558 *s .*

2559 **(C2) Unsaturated.** $\mathcal{R} \cup \mathcal{O} \neq \mathcal{C}$.

2560 **(C3) Rooted input.** *The input node is rooted.*

2561 **(C4) Paddable path.** *The constructed path p decomposes uniquely as $p = p' \parallel 0^{r^j}$ with*
 2562 *p' not ending in 0^r , and the prefix p' is a valid padded sponge input: equivalently,*
 2563 *$p' = x \parallel \text{pad10}^*[r](|x|)$ for an unpadded BDPV08 random-oracle input x .*

2564 *When all four conditions hold, the forward primitive-interface query induces one simulator*
 2565 *RO_{flat} call. Consequently, each primitive-interface query induces at most one simulator-side*
 2566 *RO_{flat} call.*

2567 *Proof.* This is the branch structure of the [BDPVA08] simple-padded permutation simulator.
 2568 The simulator invokes the random oracle only on the forward-query branch where the input
 2569 node is rooted, unsaturated, paddable to an unpadded random-oracle input x , and not
 2570 already extended by an outgoing edge in the simulator graph. Forward queries violating
 2571 any of these conditions and all inverse queries return outputs sampled or read from the
 2572 simulator's internal graph without invoking the random oracle. Under the [BDPVA11,
 2573 Theorem 3] bridge fixed in Section B.1, that simulator random-oracle invocation is the
 2574 simulator-side RO_{flat} call used throughout this appendix. $\square$

2575 **Lemma 18** (Flat-Sponge Lift Bound). *Let G be any of the single-stage TW128 games*
 2576 *of Sections 4.1 and 4.4: privacy, INT-CTXT, all-in-one AE, mu-ind, CMTDs-4, the H*
 2577 *collision, second-preimage, and preimage games, $\text{CDY}^*[\text{ts}]$, or CMTs- ℓ for $\ell \in \{1, 3, 4\}$*
 2578 *(the $\text{CDY}^*[\text{ts}]$ selector encryption is construction-internal, counted in N like a challenger*
 2579 *check). Let $\mathcal{A}$ be a public-permutation G adversary with construction-interface cost at most*
 2580 *N and at most N_{prim} direct primitive-interface queries. In the [BDPVA08] single-stage*
 2581 *replacement, the combined construction-and-primitive transcript has length at most*

$$2582 \quad N_{\text{tot}} = N + N_{\text{prim}}.$$

2583 *Consequently replacing the real public permutation and TW128 construction by the*
 2584 *simulator-world primitive interface $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$ and the corresponding flat-RO*
 2585 *construction interface costs at most $\text{Lift}_c(N_{\text{tot}})$.*

2586 *Proof.* The [BDPVA08] replacement is applied before the derived-adversary construction,
 2587 so its transcript contains two kinds of public-primitive activity. First, each construction-
 2588 interface computation contributes the TW128 duplex calls it performs. By Lemmas 4
 2589 and 7, each such root or leaf output point is a typed restriction of the bridged flat-sponge
 2590 construction, and by the definition of N in Section 4.3 these calls are counted at the
 2591 same per-block granularity as the underlying KECCAK- $p[1600, 12]$ calls. This includes
 2592 verification computations whether they accept or reject, the per-user sum of construction
 2593 calls in mu-ind, and the deterministic challenger decryption or encryption checks actually
 2594 performed in the committing and discoverability games.

2595 Second, each direct adversary query to (π, π^{-1}) contributes one primitive-interface
 2596 query and is counted in N_{prim} . These two counts are disjoint in the public-permutation
 2597 experiment: N counts construction-internal use of the primitive, while N_{prim} counts only
 2598 the adversary's public-primitive interface queries. The execution-uniform caps ensure
 2599 that every adaptive transcript seen by the single-stage replacement has length at most
 2600 $N + N_{\text{prim}} = N_{\text{tot}}$. If $N_{\text{tot}} \geq 2^c$ then $\text{Lift}_c(N_{\text{tot}}) \geq 1$ and the claimed bound holds trivially, so
 2601 assume $N_{\text{tot}} < 2^c$, satisfying the hypothesis of [BDPVA08, Theorem 2]. That theorem gives
 2602 distinguishing or success-probability cost at most the random-permutation differentiating
 2603 bound $f_P(N_{\text{tot}})$ of [BDPVA08, Lemma 5]. The [BDPVA08, Lemmas 4 and 5] product

bounds give the random-transformation bound $f_T(N_{\text{tot}}) = 1 - \prod_{i=1}^{N_{\text{tot}}} (1 - i/2^c)$, and the factor of $f_P(N_{\text{tot}})$ corresponding to the f_T factor at index i is that factor divided by a quantity $1 - (i - 1)/2^{r+c} \in (0, 1]$, hence at least as large, so $f_P(N_{\text{tot}}) \leq f_T(N_{\text{tot}})$. With $N_{\text{tot}} < 2^c$ every factor lies in $[0, 1]$ and

$$f_P(N_{\text{tot}}) \leq f_T(N_{\text{tot}}) = 1 - \prod_{i=1}^{N_{\text{tot}}} \left(1 - \frac{i}{2^c}\right) \leq \sum_{i=1}^{N_{\text{tot}}} \frac{i}{2^c} = \frac{N_{\text{tot}}(N_{\text{tot}} + 1)}{2^{c+1}} = \text{Lift}_c(N_{\text{tot}}),$$

the second inequality by the Weierstrass product inequality $\prod_i (1 - x_i) \geq 1 - \sum_i x_i$ for $x_i \in [0, 1]$. $\square$

Lemma 19 (Derived-Adversary Execution Contract). *Let G be any of the single-stage TW128 games of Sections 4.1 and 4.4: privacy, INT-CTXT, all-in-one AE, mu-ind, CMTDs-4, the H collision, second-preimage, and preimage games, $\text{CDY}^*[\text{ts}]$, or CMTs- ℓ for $\ell \in \{1, 3, 4\}$ (the $\text{CDY}^*[\text{ts}]$ selector encryption is construction-internal, counted in N like a challenger check). Let $\mathcal{A}$ be a simulator-world G adversary whose public-primitive interface is answered by $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$, with at most N_{prim} direct primitive-interface queries. Define $\mathcal{B}_{\text{derived}}(\mathcal{A})$ to run $\mathcal{A}$ internally, answer each primitive-interface query by running the same simulator against direct finite-output queries to its own RO_{flat} oracle, and forward construction-interface queries (or, in the committing and discoverability games, the final structured output) unchanged to the corresponding random-oracle experiment. Then the simulator-world execution of $\mathcal{A}$ and the random-oracle execution of $\mathcal{B}_{\text{derived}}(\mathcal{A})$ have identical joint distributions, and*

$$q_{\text{RO}}(\mathcal{B}_{\text{derived}}) \leq N_{\text{prim}}.$$

In this coupling, simulator-induced RO_{flat} calls and construction-internal RF lookups use the same lazy table. Therefore, if a simulator-induced query is the bridged input $\text{flat}(X)$ of a well-formed TW128 transcript prefix X and a forwarded construction computation later reaches the same prefix X , both interfaces read the same $\text{RO}_{\text{flat}}(\text{flat}(X))$ value, projected to the requested output length. Moreover, $\mathcal{B}_{\text{derived}}$ inherits the construction-side caps of $\mathcal{A}$:

$$\begin{aligned} q_v(\mathcal{B}_{\text{derived}}) &= q_v(\mathcal{A}) \quad (\text{INT-CTXT, AE, mu-ind}), \\ n_{\text{leaf}}(\mathcal{B}_{\text{derived}}) &\leq n_{\text{leaf}}(\mathcal{A}) \quad (\text{all games above}). \end{aligned}$$

In the mu-ind game these resource inheritances hold per user, and the New-query transcript is unchanged.

Proof. Couple the two executions by using the same lazy RO_{flat} table for the simulator and for all construction-internal $\text{RF}(\cdot)$ lookups. In the simulator-world execution, $\mathcal{A}$ sees construction answers from the selected game interface and public-primitive answers from $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$. In the derived random-oracle execution, $\mathcal{B}_{\text{derived}}$ runs the same $\mathcal{A}$, forwards construction-interface queries (or the final committing- or discoverability-game output) unchanged, and answers primitive-interface queries by invoking the same simulator code with the same lazy RO_{flat} table. The construction interface or committing challenger therefore receives the same forwarded inputs, the simulator receives the same primitive queries in the same order, and the lazy table supplies the same values. The full views of $\mathcal{A}$ in the simulator-world execution and of $\mathcal{B}_{\text{derived}}$ in the random-oracle execution are identically distributed.

The simulator's random-oracle calls may be on arbitrary [BDPVA08] H -input strings, not only bridged TW128 transcript inputs. These calls are the direct RO_{flat} queries of $\mathcal{B}_{\text{derived}}$ and are counted in $q_{\text{RO}}(\mathcal{B}_{\text{derived}})$. Construction-internal $\text{RF}(\cdot)$ lookups made by Enc_K^{RO} , Dec_K^{RO} , Ver_K^{RO} , or a committing or discoverability challenger are forwarded to the same RO_{flat} table but are not counted in q_{RO} , exactly as in Section 4.3.

By Lemma 17, each primitive-interface query induces at most one direct RO_{flat} query by $\mathcal{B}_{\text{derived}}$, and inverse queries or non-RO-touching forward queries induce none. Since $\mathcal{A}$ makes at most N_{prim} direct primitive-interface queries, this gives $q_{\text{RO}}(\mathcal{B}_{\text{derived}}) \leq N_{\text{prim}}$.

Lemma 7’s bridge places TW128 construction restrictions and simulator-induced RO_{flat} calls in a single lazy table. If the simulator invokes RO_{flat} on $\text{flat}(X)$ for a well-formed TW128 transcript prefix X , and a forwarded construction computation later reaches X , the construction lookup $\text{RF}(X) = \text{RO}_{\text{flat}}(\text{flat}(X))$ reads the same table entry and returns the requested projection. Since TW128 uses $r = r_{\text{max}}$, the [BDPVA11, Theorem 3] output post-processing does not alter TW128 output bits. Thus simulator-induced direct queries and construction-internal lookups at the same bridged input are transcript-consistent. In the AE games, a simulator call whose input is accepted by **KeyedTWOut** for the hidden key is still a direct RO_{flat} query and is covered by the same bad_{key} accounting used by the random-oracle privacy and INT-CTXT theorems. The derivation step itself does not prove a key-guessing statement; it only supplies the derived adversary and the query bound at which the random-oracle envelopes of Section 5.2 are instantiated.

Finally, the execution-uniform caps of Section 4.3 hold along every oracle-answer trace of $\mathcal{A}$, including traces generated by the simulator on the ideal public-primitive interface. The derived-adversary construction does not add construction-interface encryption or verification queries and forwards $\mathcal{A}$ ’s construction-interface queries unchanged along each trace. $\mathcal{B}_{\text{derived}}$ therefore inherits the relevant construction resources: $q_v(\mathcal{B}_{\text{derived}}) = q_v(\mathcal{A})$ in the INT-CTXT, AE, and mu-ind games, and $n_{\text{leaf}}(\mathcal{B}_{\text{derived}}) \leq n_{\text{leaf}}(\mathcal{A})$ for the distinct construction-generated final-leaf-transcript cap. In mu-ind, construction-interface forwarding preserves the New calls and these caps user by user. $\square$

B.2 Lift Application

The lift bound of Lemma 18 and the derived-adversary construction of Lemma 19 combine into a single template, stated once and then instantiated by the headline theorems of Section 5.3 and the committing-notion bounds of Section C.

Corollary 5 (Lift Application). *Let G be any of the games of Lemma 18. For every public-permutation G -adversary $\mathcal{A}$ against TW128 with the resources of Section 4.3, the derived adversary $\mathcal{B} = \mathcal{B}_{\text{derived}}(\mathcal{A})$ of Lemma 19 is a random-oracle G -adversary with $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$ and the construction-side caps of Lemma 19—in particular $q_v(\mathcal{B}) \leq Q_v$ and $n_{\text{leaf}}(\mathcal{B}) \leq N_{\text{leaf}}$, where these apply—such that*

$$\text{Adv}_{\text{TW128}}^{\mathsf{G}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{Adv}_{\text{RO}}^{\mathsf{G}}(\mathcal{B}).$$

If moreover $\text{Adv}_{\text{RO}}^{\mathsf{G}}(\mathcal{B}) \leq \varepsilon_{\mathsf{G}}(q_{\text{RO}}(\mathcal{B}), n_{\text{leaf}}(\mathcal{B}))$ for some ε_{G} nondecreasing in each argument, then

$$\text{Adv}_{\text{TW128}}^{\mathsf{G}}(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \varepsilon_{\mathsf{G}}(N_{\text{prim}}, N_{\text{leaf}}).$$

Proof. By the flat-sponge lift bound (Lemma 18), replacing the real public permutation and TW128 construction by $(\mathcal{S}^{\text{RO}_{\text{flat}}}, \mathcal{S}^{-1, \text{RO}_{\text{flat}}})$ and the flat-RO construction interface costs at most $\text{Lift}_c(N_{\text{tot}})$, where $N_{\text{tot}} = N + N_{\text{prim}}$ counts both the construction calls of N —including any construction oracle exposed during $\mathcal{A}$ ’s run and, in the win-event games, the challenger’s post-output decryption or encryption checks—and the N_{prim} direct primitive queries. The derived-adversary contract (Lemma 19) expresses the resulting simulator-world execution as the identically distributed random-oracle execution of $\mathcal{B} = \mathcal{B}_{\text{derived}}(\mathcal{A})$, with $q_{\text{RO}}(\mathcal{B}) \leq N_{\text{prim}}$ and the stated construction-side inheritances, giving the first bound. The second follows by the monotonicity of ε_{G} . When G is parameterized by a target fixed before $\mathcal{A}$ runs—the discoverability target T^* —the coupling holds for each fixed target and the target-independent bound holds for the maximum defining $\text{Adv}_{\text{TW128}}^{\mathsf{G}}(\mathcal{A})$. $\square$

The public-permutation privacy and INT-CTXT advantages are not stated as separate corollaries: the all-in-one AE theorem (Theorem 1) applies the lift once to the all-in-one AE adversary and then splits the resulting random-oracle advantage into the privacy and INT-CTXT envelopes of Section 5.2, adding $\text{Lift}_c(N_{\text{tot}})$ a single time rather than the two copies that lifting privacy and INT-CTXT separately would incur.

C Committing-Notion Bounds

The headline results bound full-input CMTDs-4 (Corollary 1) as a corollary of the collision resistance of the root-tag wrapper (Theorem 3). The remaining [BH22] committing notions—CMTDs-1, CMTDs-3, and the CMTs- ℓ source games for $\ell \in \{1, 3, 4\}$ —all reduce to the same root-collision bound, so we record the two reduction patterns once rather than accounting for each notion separately.

Lemma 20 (Forwarding Reductions for the D-Notions). *Fix $s \geq 2$ and $X \in \{\text{CMTDs-1}, \text{CMTDs-3}\}$. The identity reduction $\mathcal{A}^* = \mathcal{A}$ —preceded, for $X = \text{CMTDs-1}$, by the source-game syntax, length, and pairwise- WiC_1 prechecks—turns every s -way X -adversary against TW128 into an s -way CMTDs-4 adversary with*

$$\text{Adv}_{\text{TW128}}^X(\mathcal{A}) \leq \text{Adv}_{\text{TW128}}^{\text{CMTDs-4}}(\mathcal{A}^*), \quad N_{\text{prim}}(\mathcal{A}^*) = N_{\text{prim}}(\mathcal{A}), \quad N_{\text{tot}}(\mathcal{A}^*) \leq N_{\text{tot}}(\mathcal{A}).$$

Proof. A CMTDs-3 winner has pairwise distinct (K_i, N_i, A_i) triples, which are *a fortiori* pairwise distinct full tuples (K_i, N_i, A_i, M_i) , so the winner is a CMTDs-4 winner on the same output. For CMTDs-1, pairwise WiC_1 -distinctness makes the keys K_i —hence the triples, hence the full tuples—pairwise distinct; the prechecks are source-game rejections, and the eager length precheck is success preserving because TW128 decryption returns $\perp$ or a message of length $\|C\|$, so no winning transcript is discarded. Either reduction makes no primitive-interface query and performs at most the source-game decryption checks, so neither cost increases. $\square$

Corollary 6 (Committing-Notion Root-Collision Bound). *For every $s \geq 2$, every*

$$X \in \{\text{CMTDs-1}, \text{CMTDs-3}, \text{CMTDs-4}, \text{CMTs-1}, \text{CMTs-3}, \text{CMTs-4}\},$$

and every s -way X -adversary $\mathcal{A}$ against TW128,

$$\text{Adv}_{\text{TW128}}^X(\mathcal{A}) \leq \text{Lift}_c(N_{\text{tot}}) + \text{RootColl}_{\tau_{\text{root}}}(N_{\text{prim}}, s) = \text{Lift}_c(N_{\text{tot}}) + \frac{\binom{N_{\text{prim}} + s}{s}}{2^{\tau_{\text{root}}(s-1)}}.$$

Proof. CMTDs-4 is bounded directly by Corollary 1. CMTDs-1 and CMTDs-3 reduce to CMTDs-4 by Lemma 20, whose public-permutation bound is again Corollary 1; monotonicity of Lift_c absorbs $N_{\text{tot}}(\mathcal{A}^*) \leq N_{\text{tot}}(\mathcal{A})$.

The E-notions are bounded directly by the final-root candidate-collision argument of Theorem 9, with the challenger’s s deterministic *encryption* checks supplying the candidate final-root transcripts: Lemma 2 builds the candidate sequence for encryption or decryption checks alike. On a winning execution all s encryptions are equal, hence of equal length and with one common root tag T ; pairwise WiC_ℓ -distinctness forces pairwise distinct triples—for $\ell = 4$ via determinism, since equal triples with equal ciphertexts would decrypt to equal messages—so Proposition 1 makes the s final-root candidates distinct while their τ_{root} -bit projections all equal T . The win is contained in the s -way candidate-collision event of Lemma 8, and the flat-sponge lift (Corollary 5) transfers the bound to the public-permutation setting at N_{prim} ; the encryption checks are construction-internal work counted in N , not in N_{prim} . $\square$

D Vectorized Kernel Details

This appendix details the architecture-specific cores summarized in Section 9.1: the instruction selection, register layout, and remainder handling of the `amd64` and `arm64` kernels.

amd64. The `amd64` implementation provides AVX-512 and AVX2 cores and selects between them once at startup from the AVX512VL CPUID feature bit. The single-duplex permutation has two variants: a general-purpose-register core adapted from the standard library’s KECCAK- p permutation (using the lane-complement trick so that χ requires no separate negation), and an AVX-512 variant; the root duplex uses whichever matches the selected core. The eight-way AVX-512 core packs the lane-major state into 25 ZMM registers, one per lane with all eight instances in the register’s eight 64-bit slots, and performs the permutation with no cross-lane shuffles: rotations use `VPROLQ`, and `VPTERNLOGQ` fuses the θ D -term formation and the χ and-not into single three-input logic instructions. The eight-way AVX2 core, lacking 512-bit registers, runs the eight instances as two groups of four (four 64-bit lanes per YMM register), rotating by shift-or and computing χ with `VPANDN`. The fused chunk kernels combine absorption with the permutation. The AVX-512 steady-state kernel reads the eight chunks with contiguous loads, transposes each rate block into the lane-major layout in registers (`VPUNPCKLQDQ`/`VPUNPCKHQDQ` and `VSHUFI64X2`), absorbs on the lane-major state, and transposes each output block back for a contiguous store, leaving only the 7-byte partial rate lane to a masked gather; these sequential accesses are prefetcher-friendly, whereas per-lane gathers and scatters at the chunk stride β (`VPGATHERQQ`/`VPSCATTERQQ`) would stall on cold memory and cap the long-message rate. The register-resident kernel that drains a two-to-seven-chunk remainder instead uses that per-lane gather/scatter form under a mask, reading the active chunks in place: the transpose’s shuffle work is constant regardless of the chunk count and would be spent partly on inactive lanes, whereas the gathers scale with the active element count. The AVX2 path drains the same remainders with a variant of its grouped-by-four kernels that aims each inactive instance’s loads and stores at a dummy block inside the kernel frame with a zero advance stride, so inactive instances touch no memory beyond the remainder and the hot loop stays branch-free.

arm64. The `arm64` path uses NEON plus the Armv8.2 SHA-3 extension (`FEAT_SHA3`), available on Apple Silicon and on Neoverse V1/V2 and N2. The permutation is expressed with the extension’s fused instructions: `EOR3` (three-input XOR) for the θ column parities, `RAX1` (rotate-by-one and XOR) for the θ D -terms, `XAR` (XOR then rotate) to fuse the θ accumulation with the ρ rotation, and `BCAX` (bit-clear and XOR) for χ . The single-duplex core places one instance per 64-bit D lane across the 25 vector registers; the eight-way core packs two instances per 128-bit register and processes the batch of eight as four such pairs, using `ZIP1` and duplicating moves to interleave and extract the two instances of each lane in the fused chunk kernel. The same pair machinery backs a 2-wide kernel that drains a leaf-chunk remainder two chunks at a time—one instance per 64-bit half of a 128-bit register—at roughly twice the single-duplex per-chunk rate. Both batched kernels store the permutation state back into the batch after the closing block—the $\times 8$ kernel for its first pair, the 2-wide kernel for both instances—which is the writeback that permits the root duplex to occupy lane 0.

E Test Vectors

The following test vectors cover the corner cases of TW128 encryption, as specified in § 3.

2784 All byte strings are written in hexadecimal. For each vector we list the key K , nonce N ,
 2785 associated data A , message M , ciphertext C , and tag T ; the sealed output of encryption
 2786 is $C \parallel T$. The empty string is written ε . The leaf index is encoded as a little-endian 64-bit
 2787 integer and the phase suffixes are appended least-significant-bit first.

2788 To keep the longer vectors compact, any value exceeding 32 bytes is given by its
 2789 length in bytes together with its SHA-256 digest rather than in full. Every message and
 2790 associated-data byte is defined by $m_i = (17i + 31) \bmod 256$ for $i = 0, 1, \dots$, so each such
 2791 input is determined by its length alone and can be reconstructed and checked against
 2792 the stated digest; a ciphertext given by its length and digest can likewise be checked by
 2793 encrypting the corresponding message and hashing the result.

Vector 1. Empty associated data and empty message: the associated-data and aggregation phases are both elided, and the root tag is emitted by the single closing message call with no leaves.

2794 K 000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f
 N 202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f
 A ε
 M ε
 C ε
 T da65bbda0b20b1e936f5326458166633d1e5a3f7aebc0b318d24b051a4efa697

Vector 2. Multi-block associated data with an empty message: the associated data spans two rate blocks and no message bytes are processed.

2795 K 000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f
 N 202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f
 A 168 bytes, SHA-256
 4c7d125a3488a7603e2f403f0010a6060b8321b60b0fd2471120ae627bbe759a
 M ε
 C ε
 T 2093878418f3fca96ad3a8d1748a9be4d2a8b518e917d988fd703dcb7bf72173

Vector 3. Empty associated data and a single-block message: the root message phase only, no leaves.

2796 K 000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f
 N 202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f
 A ε
 M 1f30415263748596a7b8c9daebfc0d1e2f405162738495a6b7c8d9eafb0c1d2e
 C 676a1441e20daea0f1ee4571ee4543842c946d59e0d3df6f1dd2f92dc4f876aa
 T 1873332d359ff2fe5197488224af7bf6ad821875fdbd964100de424aa77342be

Vector 4. Empty associated data and a two-block message: the root keystream is chained across two rate blocks.

2797 K 000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f
 N 202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f
 A ε
 M 168 bytes, SHA-256
 4c7d125a3488a7603e2f403f0010a6060b8321b60b0fd2471120ae627bbe759a
 C 168 bytes, SHA-256
 df3f0a98a91a69ed474edbc52e0dc1d8e54bfd6fc514966ce7b878d48be0bf9a
 T aab2413074a202cfadd5eb784663b1831eb330025972d163d03e9ed5a964b765

Vector 5. A message of exactly one chunk: the root is full, there is still no leaf, and the aggregation phase is elided so the closing root message call emits the tag.

2798 K 000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f
 N 202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f
 A ε
 M 8183 bytes, SHA-256
 6532a370a4ab6b5f4094dd8a6016512ab8e8416abe910bc1a0b532979224151d
 C 8183 bytes, SHA-256
 8d58f8aa3413ea0ba1b8cc3ed4e9a334521d8dfe9694a0661fb8251049907e9
 T c2201637f1116c1303b8982622756770d23acb85384f4658fcb63c37e4b629dd

Vector 6. A message of one chunk and one further byte: one root chunk and one leaf, exercising leaf tag aggregation.

2799 *K* 000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f
N 202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f
A ε
M 8184 bytes, SHA-256
c4c383bca0808e2ce44d481ddfe56efdcd7a147dcd5a14c898ef5423f2604cd7
C 8184 bytes, SHA-256
ef1b2f7607ade503ab497fc61e62cef2b44c6328fa06e499718eb7da5fdd04d3
T c96bea48e07a8431fd19721ffbe8afe6a73047f96d953e3281f10126eeca06a1

Vector 7. A multi-leaf message of two chunks and one further byte: the full tree path with two leaves.

2800 *K* 000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f
N 202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f
A ε
M 16367 bytes, SHA-256
17e31f3700d0602aab8a686024ecc05b8192e80a531483c67dd90d5a26557c5e
C 16367 bytes, SHA-256
6d83d8fbdca7c2ef590d29a36527a45019e50d1f8c8db037959081685a46908
T cdc2e50ac5380419f06772a2f3af2146050bd0340b35f61b67f839351767804e

Vector 8. Maximum associated data with a short message: the associated-data blocks dominate the cost.

2801 *K* 000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f
N 202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f
A 337 bytes, SHA-256
04ca7b24930bc6b5fe8b95ff1eb0933907657c1283cc3a7e69c5f7f02220f281
M 1f30415263748596a7b8c9daebfc0d1e
C 0dd615a0a05ed82a78c3999b9e80cbed
T 22e4e6725f548ad0660041d66cf2f18dc45c69b447cdaae1f147d33a3b6aa1a9

Vector 9. An all-ones key and nonce with a multi-chunk message.

2802 *K* ff
N ff
A 168 bytes, SHA-256
4c7d125a3488a7603e2f403f0010a6060b8321b60b0fd2471120ae627bbe759a
M 8184 bytes, SHA-256
c4c383bca0808e2ce44d481ddfe56efdcd7a147dcd5a14c898ef5423f2604cd7
C 8184 bytes, SHA-256
49818c320ab282296639798d840cbd60751e1623f449dcbf9423371d44145dfb
T 310c9fff20e9651f8ed47eed9bb182a086ed1af1b3f1799e35307a4139865fc7
