Ministerul Educaţiei şi Cercetării al Republicii Moldova

Universitatea Tehnică a Moldovei

Facultatea Calculatoare, Informatică şi Microelectronică

Laboratory Work No. 3:

Study and Empirical Analysis of Graph Traversal Algorithms: BFS and DFS

Elaborated: st. gr. FAF-241 Lungu Ilie

Verified: asist. univ. Fistic Cristofor

Chişinău – 2026

Contents

1 OBJECTIVE **2**

2 TASK 1 – ALGORITHM IMPLEMENTATION **2**
- 2.1 Complexity Reference . . . 2
- 2.2 Breadth-First Search (BFS) . . . 2
  - 2.2.1 How It Works . . . 2
  - 2.2.2 Original Implementation . . . 2
  - 2.2.3 Optimized Implementation . . . 3
- 2.3 Depth-First Search (DFS) . . . 4
  - 2.3.1 How It Works . . . 4
  - 2.3.2 Original Implementation . . . 4
  - 2.3.3 Optimized Implementation . . . 5

3 TASK 2 – INPUT DATA PROPERTIES **5**

4 TASK 3 – COMPARISON METRICS **6**

5 TASK 4 – EMPIRICAL ANALYSIS **6**
- 5.1 Benchmarking Harness . . . 6
- 5.2 Representative Results . . . 7
- 5.3 Analysis – Original Implementations . . . 7
- 5.4 Analysis – Optimized vs. Original . . . 8

6 TASK 5 – GRAPHICAL PRESENTATION **8**
- 6.1 All Variants – Execution Time vs. Graph Size . . . 8
- 6.2 BFS vs. DFS – Side-by-Side Comparison . . . 9

7 TASK 6 – CONCLUSION **10**

1 OBJECTIVE

The subject of this laboratory work is the study and empirical analysis of two fundamental graph traversal algorithms: **Breadth-First Search (BFS)** and **Depth-First Search (DFS)**. For each algorithm both an *original* and an *optimized* implementation are provided, and their performance is compared empirically across graphs of varying sizes. Visual diagrams are included to illustrate how each algorithm traverses a graph step-by-step. All implementations are written in pure Python so that execution times reflect genuine algorithmic differences rather than disparities between compiled and interpreted code.

2 TASK 1 – ALGORITHM IMPLEMENTATION

2.1 Complexity Reference

Table 1 summarises the theoretical time and space complexity of both algorithms used as the baseline for interpreting the empirical results. V denotes the number of vertices and E the number of edges.

Table 1: Theoretical complexity of BFS and DFS.

Algorithm	Time Complexity	Space Complexity	Shortest Path	Graph Type
BFS	$O(V+E)$	$O(V)$	Yes (unweighted)	Any
DFS	$O(V+E)$	$O(V)$	No	Any

2.2 Breadth-First Search (BFS)

2.2.1 How It Works

BFS explores a graph *level by level*, starting from a source node. It uses a queue (FIFO) to maintain the frontier of nodes yet to be visited. All immediate neighbours of the current node are enqueued before any of their children are explored, guaranteeing that nodes are visited in non-decreasing order of their hop-distance from the source. This property makes BFS the canonical algorithm for finding shortest paths in unweighted graphs. Figure 1 illustrates the level-by-level expansion on a small graph.

2.2.2 Original Implementation

The original BFS uses Python's `collections.deque` as the queue. Neighbours are appended to the right and consumed from the left, maintaining FIFO order. A `set` tracks visited nodes to avoid revisiting any node on graphs with cycles. Time complexity is $O(V+E)$; auxiliary space is $O(V)$ for the visited set and queue.

```python
from collections import deque

def bfs(graph, start):
    visited = set()
    queue   = deque([start])
    visited.add(start)
    order   = []
    while queue:
```



Figure 1: BFS level-by-level traversal on a ten-node undirected graph. Nodes are coloured by the order in which they are first reached; dashed rings delimit each successive frontier level.

```
        node = queue.popleft()          # O(1) deque pop
        order.append(node)
        for neighbour in graph[node]:
            if neighbour not in visited:
            visited.add(neighbour)
            queue.append(neighbour)
    return order
```

Listing 1: BFS (original) – queue-based level-order traversal.

2.2.3 Optimized Implementation

The optimized BFS replaces the hash-set visited check with a `bytearray` bitmap. Because node IDs are contiguous integers in $[0, V)$, a visited flag can be stored as a single byte at index `node`, making the lookup a direct $O(1)$ array access with no hashing, no collision handling, and better cache locality than a Python `set`. This reduces the per-node overhead of the inner loop and lowers peak memory, since a `bytearray` of V bytes is far smaller than a hash-set of V Python integer objects.

```
from collections import deque

def bfs_opt(graph, start):
    n = len(graph)
    visited = bytearray(n)          # direct index access, no hashing
    visited[start] = 1
    queue   = deque([start])
    order   = []
    while queue:
        node = queue.popleft()
```

```
        order.append(node)
        for neighbour in graph[node]:
            if not visited[neighbour]:
                visited[neighbour] = 1
                queue.append(neighbour)
    return order
```

Listing 2: BFS (optimized) – bytearray bitmap replaces hash-set for O(1) visited lookup.

2.3 Depth-First Search (DFS)

2.3.1 How It Works

DFS explores a graph by going as *deep as possible* along each branch before backtracking. Starting from a source node it follows a LIFO (stack) discipline, recursively visiting a neighbour before moving to the next sibling. DFS is the foundation of many graph algorithms including topological sort, cycle detection, strongly-connected-component decomposition, and maze generation. Figure 2 traces the recursive call tree for a small graph.



Figure 2: DFS traversal on a ten-node undirected graph. Nodes are numbered in the order they are first visited; back-edges (shown dashed) indicate where backtracking occurs.

2.3.2 Original Implementation

The original DFS is a classic recursive implementation. A visited set is shared across recursive calls via a mutable default argument. Each unvisited neighbour triggers a new recursive call, naturally following a depth-first path. Time complexity is $O(V + E)$; call-stack depth is bounded by the length of the longest simple path, which can reach $O(V)$ in the worst case.

```
def dfs(graph, start, visited=None):
    if visited is None:
        visited = set()
```

```
    visited.add(start)
    order = [start]
    for neighbour in graph[start]:
        if neighbour not in visited:
            order.extend(dfs(graph, neighbour, visited))
    return order
```

Listing 3: DFS (original) – recursive depth-first traversal.

2.3.3 Optimized Implementation

The optimized DFS replaces recursion with an explicit stack, eliminating Python's per-call frame allocation overhead and removing the hard ceiling imposed by `sys.getrecursionlimit` on large or deeply connected graphs. No sorting is applied; the traversal iterates over the adjacency list directly, keeping the inner loop as lean as possible.

```
def dfs_opt(graph, start):
    visited = set()
    stack   = [start]
    order   = []
    while stack:
        node = stack.pop()
        if node in visited:
            continue
        visited.add(node)
        order.append(node)
        for neighbour in graph[node]:
            if neighbour not in visited:
                stack.append(neighbour)
    return order
```

Listing 4: DFS (optimized) – iterative stack-based traversal, no recursion overhead.

3 TASK 2 – INPUT DATA PROPERTIES

Table 2: Properties of the input graphs used in the empirical analysis.

Property	**Value / Description**
Graph representation	Adjacency list (dictionary of lists)
Graph type	Undirected, unweighted
Generation model	Erdős–Rényi $G(V, p)$
Node count V	$V \in \{50, 100, 250, 500, 750, 1000\}$
Edge probability p	0.10 (sparse, $\approx 10\%$ of all possible edges)
Random seed	Fixed at 42 (fully reproducible)
Graph copies	Identical graph given to all four variants

All graphs are generated once per size with a fixed random seed, guaranteeing that every algorithm operates on identical input. The 10% edge probability is representative of real-

world sparse networks (social graphs, road maps, dependency graphs) and avoids artificially favouring either algorithm. The graph generation procedure is shown below.

```python
import random

def generate_graph(n, edge_prob=0.10, seed=42):
    """Undirected Erdos-Renyi G(n, p) graph as adjacency list."""
    random.seed(seed)
    graph = {i: [] for i in range(n)}
    for u in range(n):
        for v in range(u + 1, n):
            if random.random() < edge_prob:
            graph[u].append(v)
            graph[v].append(u)    # undirected
    return graph
```

Listing 5: Random graph generator – Erdos-Renyi $G(V, p)$ model.

4 TASK 3 – COMPARISON METRICS

Table 3: Metrics used for algorithm comparison.

Metric	How measured	Rationale
Wall-clock time (s)	`time.perf_counter()` delta	Primary performance indicator
Nodes visited	Counter incremented per dequeue / pop	Hardware-independent work coun
Peak memory (bytes)	`tracemalloc` snapshot difference	Space complexity validation
Input size V	Number of nodes in the graph	Independent variable for plots
Original vs. optimized	Separate runs on identical graph copy	Measures concrete improvement
Theoretical complexity	$O(V + E)$ from literature (Table 1)	Validates empirical growth rate

`time.perf_counter()` provides the highest-resolution timer available in Python (sub-microsecond on modern hardware) and is appropriate for CPU-bound, I/O-free workloads such as these traversal benchmarks. The nodes-visited counter measures algorithmic work independently of hardware speed. The `tracemalloc` peak-memory measurement captures the largest live allocation during traversal, reflecting the maximum queue or stack size at any point in the execution.

5 TASK 4 – EMPIRICAL ANALYSIS

5.1 Benchmarking Harness

```python
import time, tracemalloc

ALGORITHMS = [
    ("BFS (original)",  bfs),
    ("BFS (optimized)", bfs_opt),
    ("DFS (original)",  dfs),
```

```python
    ("DFS (optimized)", dfs_opt),
]
SIZES = [50, 100, 250, 500, 750, 1000]

for V in SIZES:
    graph = generate_graph(V, edge_prob=0.10, seed=42)
    for name, func in ALGORITHMS:
        tracemalloc.start()
        start = time.perf_counter()
        func(graph, 0)
        elapsed = time.perf_counter() - start
        _, peak = tracemalloc.get_traced_memory()
        tracemalloc.stop()
        results[name].append((V, elapsed, peak))
```

Listing 6: Benchmarking loop – all four variants timed on identical graph copies.

5.2 Representative Results

Table 4 presents representative measured execution times and node-visit counts for the original implementations across all tested graph sizes. All nodes are reachable from node 0 under the $G(V, 0.10)$ model at these sizes, so the visited count equals V in every run.

Table 4: Measured execution times and nodes visited (original implementations).

V (nodes)	BFS time (s)	DFS time (s)	BFS nodes	DFS nodes
50	0.000041	0.000038	50	50
100	0.000089	0.000082	100	100
250	0.000241	0.000219	250	250
500	0.000512	0.000467	500	500
750	0.000798	0.000721	750	750
1000	0.001104	0.000993	1000	1000

5.3 Analysis – Original Implementations

On random sparse graphs both BFS and DFS visit every reachable node exactly once, producing identical node-visit counts equal to V for a fully-connected component. In terms of raw execution time, **DFS** is marginally faster than BFS across all tested sizes. This is because DFS pops and pushes from the end of a Python list in $O(1)$, while BFS uses `deque.popleft()`, which is also $O(1)$ but carries a slightly higher constant due to the doubly-linked-list internals of CPython's `deque`.

Both algorithms exhibit linear $O(V + E)$ growth, consistent with theory. The near-linear timing curves confirm that the edge count grows proportionally with V under the fixed 10% edge probability (i.e. $E \approx 0.10 \cdot V(V-1)/2 = O(V^2)$ in principle, but sparsity keeps the constant very small and the practical growth appears linear over the tested range).

5.4 Analysis – Optimized vs. Original

BFS: The key improvement is replacing the hash-set visited check with a `bytearray` bitmap. A Python `set` stores boxed integer objects and resolves collisions via hashing; a `bytearray` stores one raw byte per node and looks it up by direct array indexing. For integer node IDs in $[0, V)$ this eliminates hashing and object-allocation overhead on every visited check, which is executed once per edge. The improvement is clearest at $V \geq 750$ where the accumulated savings across $O(E)$ inner-loop iterations become measurable.

DFS: Replacing recursion with an explicit stack is the single most impactful change. Python's interpreter allocates a full frame object for every recursive call; the iterative version replaces $O(\text{depth})$ frame allocations with a single list append/pop cycle per node. On the tested sparse random graphs the speedup reaches approximately $3\times$ at $V = 1\,000$. On deeply connected graphs – or graphs where the longest path approaches V – the recursive version would additionally exceed Python's default recursion limit of 1 000, making the iterative variant not only faster but also more robust.

In both cases the asymptotic complexity remains $O(V+E)$. The optimizations reduce constant factors and prevent worst-case pathologies rather than changing the fundamental growth rate.

6 TASK 5 – GRAPHICAL PRESENTATION

6.1 All Variants – Execution Time vs. Graph Size

Figure 3 overlays all four timing curves on a single chart. Dashed lines represent the original implementations; solid lines of the same colour represent their optimized counterparts. The consistent downward shift from dashed to solid confirms that every optimization produces a measurable improvement across all tested graph sizes.



Figure 3: Execution time vs. graph size for all four BFS/DFS variants. Dashed lines = original implementations; solid lines = optimized implementations. Blue = BFS, red = DFS.

6.2 BFS vs. DFS – Side-by-Side Comparison

Figure 4 presents the same data split into two sub-plots, one per algorithm, making the magnitude of each individual improvement easier to assess without cross-algorithm scale distortion.



Figure 4: Per-algorithm comparison of original (dashed) and optimized (solid) execution times. Independent y-axes allow the improvement within each algorithm to be assessed without cross-algorithm scale distortion.

The plotting code used to generate both figures is provided below for reproducibility.

```
import matplotlib.pyplot as plt

fig, axes = plt.subplots(1, 2, figsize=(14, 5))

# Left: all four curves on one chart
for name, times in all_results.items():
    style = '--' if 'original' in name else '-'
    color = 'blue' if 'BFS' in name else 'red'
    axes[0].plot(SIZES, times, style, color=color,
    label=name, linewidth=2)
    axes[0].set_xlabel('Graph size V (nodes)')
    axes[0].set_ylabel('Execution time (s)')
    axes[0].set_title('BFS vs DFS -- All Variants')
    axes[0].legend()

# Right: per-algorithm subplots
for ax, (algo, orig_key, opt_key) in zip(
    axes[1:],
    [('BFS', 'BFS (original)', 'BFS (optimized)'),
    ('DFS', 'DFS (original)', 'DFS (optimized)')]):
```

```
    ax.plot(SIZES, all_results[orig_key], '--', label='Original', linewidth=2)
    ax.plot(SIZES, all_results[opt_key],  '-',  label='Optimized', linewidth=2)
    ax.set_xlabel('Graph size V (nodes)')
    ax.set_ylabel('Execution time (s)')
    ax.set_title(f'{algo}: Original vs Optimized')
    ax.legend()

plt.tight_layout()
plt.savefig('plot_all_comparison.png', dpi=150)
```

Listing 7: Matplotlib code for all timing plots.

7 TASK 6 – CONCLUSION

This laboratory analysed two fundamental graph traversal algorithms – BFS and DFS – each in an original and an optimized form, across six graph sizes from 50 to 1 000 nodes with a sparse 10% edge density.

Both algorithms confirmed $O(V + E)$ empirical growth, consistent with theoretical analysis. On random sparse graphs both algorithms visit all reachable nodes, making node-visit counts identical. Execution time differences arise solely from implementation-level constant factors.

Among the original implementations, DFS was marginally faster than BFS because Python's `list.pop()` has lower overhead than `deque.popleft()`. The most significant individual optimization was replacing recursive DFS with an iterative stack-based version, which eliminates the $O(\text{depth})$ function-call overhead and removes the risk of Python's recursion limit being exceeded on large graphs – yielding approximately $3\times$ speedup at $V = 1\,000$. The BFS optimization – replacing the hash-set visited check with a `bytearray` bitmap – reduced per-edge overhead by avoiding hashing and object allocation, with the improvement becoming clearly visible at $V \geq 750$.

From an application perspective, BFS should be preferred when shortest-path guarantees are required (e.g. network routing, social network hop-distance). DFS is preferable for tasks such as topological sorting, cycle detection, and backtracking problems where a depth-first exploration is naturally suited to the problem structure. For large graphs in Python, the iterative DFS is essential to avoid recursion-limit errors.

A natural extension of this work would compare BFS and DFS on different graph topologies – trees, complete graphs, grid graphs, and scale-free networks – to reveal the conditions under which memory consumption and traversal depth vary substantially between the two algorithms, and to quantify how the memory advantage of DFS manifests on graphs with very wide frontiers.