

Communication and Synchronisation

Assignment Project Exam Help

Files <https://tutorcs.com>

Signals (UNIX)

Events, exceptions (Windows) [WeChat: cstutorcs](#)

Pipes

Message Queues (UNIX)

Mailslots (Windows)


Sockets – in NDS course

Shared memory

Semaphores, Locks, Monitors

Types of Process Interaction

Sharing



Require **mutually exclusive** access to prevent interference

Assignment Project Exam Help


<https://tutores.com>

Synchronisation



P1 informs P2 that some event has happened. P2 waits for it

Communication



P1 sends P2 data. P1 blocks when buffer is full, P2 blocks when buffer is empty.

Mutual Exclusion, Synchronisation and Communication are closely related.

UNIX Signals

Inter-Process Communication (IPC) mechanism

Signal delivery similar to delivery of hardware interrupts

Used to notify processes when an event occurs

A process can send a signal to another process if it has permission

- *"the real or effective user ID of the receiving process must match that of the sending process or the user must have appropriate privileges (such as given by a set-user-ID program or the user is the super-user)." (man page)*
- The kernel can send signals to any process

When Are Signals Generated?

When an exception occurs

- e.g., division by zero => **SIGFPE**,
segment violation => **SIGSEGV**

When the kernel wants to notify the process of an event

- e.g., if process writes to a closed pipe => **SIGPIPE**

When certain key combinations are typed in a terminal

- e.g., Ctrl-C => **SIGINT**

Explicitly using the **kill()** system call

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

UNIX Signals – Examples

SIGINT	Interrupt from keyboard
SIGABRT	Abort signal from abort
SIGFPE	Floating point exception
SIGKILL	Kill signal
SIGSEGV	Invalid memory reference
SIGPIPE	Broken pipe: write to pipe with no readers
SIGALRM	Timer signal from alarm
SIGTERM	Termination signal

UNIX Signals

The default action for most signals is to terminate the process

But the receiving process may choose to

- Ignore it
- Handle it by installing a signal handler
- Two signals cannot be ignored/handled: **SIGKILL** and **SIGSTOP**

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
signal(SIGINT, my_handler);

void my_handler(int sig) {
    printf("Received SIGINT. Ignoring...\n")
}
```

Signal Handlers – Example

```
#include <signal.h>
#include <stdio.h>
```

```
void my_handler(int sig) {
    fprintf(stderr, "SIGINT caught!");
}
```

```
int main(int argc, char *argv[])
{
    signal(SIGINT, my_handler);
    while (1) {}
}
```

```
$ ./a.out
```

```
[ctrl-C]
```

```
SIGINT caught
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Sockets

Allow bidirectional communication

Can be used to exchange information both locally and across a network

- Unlike pipes which are identified by machine specific file descriptors

Two types of sockets:

- TCP (stream sockets)
- UDP (datagram sockets)

Covered in Networks and Distributed Systems course

Shared Memory

Processes can set up shared memory areas


- Implicitly or explicitly mapped to files on disk

After shared memory is established, no need for kernel involvement

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: estutorcs



Shared Memory – System V API

shmget	Allocates a shared memory segment
shmat	Attaches a shared memory segment to the address space of a process
shmctl	Changes the properties associate with a shared memory segment
shmdt	Detaches a shared memory segment from a process

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutores

Assignment Project Exam Help

<https://tutorcs.com>
Synchronisation

WeChat: cstutorcs

Process Synchronization

How do processes synchronize their operation to perform a task?

Key concepts: [Assignment Project Exam Help](https://tutorcs.com)

- Critical sections <https://tutorcs.com>
- Mutual exclusion
- Atomic operations [WeChat: cstutorcs](#)
- Race conditions
- Synchronization mechanisms
 - ✦ Locks, semaphores, monitors, etc.
- Deadlock
- Starvation

Concepts relevant to both **processes** and **threads**

Shared Data Example

Assignment Project Exam Help

Account #1234: £10,000

<https://tutorcs.com>

WeChat: cstutorcs



Extract £1000
from account 1234



Extract £1000
from account 1234

Shared Data Example

```
void Extract(int acc_no, int sum)
{
    int B = Acc[acc_no];
    Acc[acc_no] = B - sum;
}
```

<https://tutorcs.com>

WeChat: cstutorcs

Acc[1234] = 10,000

B = 10,000
Acc[1234] = 9000



`Extract(1234, 1000)`

B = 9,000
Acc[1234] = 8000



`Extract(1234, 1000)`

Shared Data Example

```
void Extract(int acc_no, int sum)
{
    int B = Acc[acc_no];
    Acc[acc_no] = B - sum;
}
```

Critical section!
Need mutual exclusion

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Acc[1234] = 10,000

B = 10,000

Acc[1234] = 9000

B = 10,000

Acc[1234] = 9000



Extract(1234, 1000)

Extract(1234, 1000)

Critical Sections and Mutual Exclusion

Critical section/region: section of code in which processes access a shared resource – executed by only one process at a time.

A code section is critical if it:

1. Reads a memory location which is shared with another process
2. Updates a shared memory location with a value which depends on what it read

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Mutual exclusion ensures that if a process is executing its critical section, no other process can be executing it

- Processes must request **permission** to enter critical sections

A **synchronisation mechanism** is required at the entry and exit of the critical section

Requirements for Mutual Exclusion


- No two processes may be simultaneously inside a critical section
- No process running outside the critical section may prevent other processes from entering the critical section
 - When no process is inside a critical section, any process requesting permission to enter must be allowed to do so immediately
- No process requiring access to its critical section can be delayed forever
- No assumptions are made about relative the speed of processes

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Critical Sections and Mutual Exclusion



Disabling Interrupts

```
void Extract(int acc_no, int sum)
{
    CLI ();
    int B = Acc[acc_no];
    Acc[acc_no] = B - sum;
    STI ();
}
```

Assignment Project Exam Help
<https://tutorcs.com>
WeChat: cstutorcs

Works only on single-processor systems, but not with user level threads.

Misbehaving/buggy processes may never release CPU

- Mechanism usually only used by kernel code

Software Solution – Strict Alternation

P₀

turn **0**

P₁

```
while (true) {  
    while (turn != 0)  
        /* loop */ ;  
    critical_section()  
    turn = 1;  
    noncritical_section0();  
}
```

```
while (true) {  
    while (turn != 1)  
        /* loop */ ;  
    critical_section()  
    turn = 0;  
    noncritical_section1();  
}
```

What happens if P₀ takes a long time in its non-critical section?

- Remember: No process running outside its critical section may prevent other processes from entering the critical section

Can we have P₁ execute its loop twice in a row (w/o P₀ executing in-between)?

Busy Waiting

Strict alternation solution requires continuously testing the value of a variable

Called **busy waiting**

- Wastes CPU time
- Should only be used when the wait is expected to be short

WeChat: cstutorcs

Atomic Operations

```
void Extract(int acc_no,  
             int sum)  
{  
    int B = Acc[acc_no];  
    Acc[acc_no] = B - sum;  
}
```

```
void Extract(int acc_no,  
             int sum)  
{  
    Acc[acc_no] -= sum;  
}
```

Assignment Project Exam Help
<https://tutorcs.com>

WeChat: cstutorcs

Does this work?

- Not atomic!

Atomic operation: a sequence of one or more statements that is/appears to be indivisible

Lock Variables

L= 0 lock open/free
L=1 locked

```
void Extract(int acc_no, int sum)
{
    lock(L);
    int B = Acc[acc_no];
    Acc[acc_no] = B - sum;
    unlock(L);
}
```

```
void lock(int L)
{
    while (L != 0)
        /* wait */ ;
    L = 1;
}
```

```
void unlock(int L)
{
    L = 0;
}
```

- Does this work?

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

TSL (Test and Set Lock) Instruction

Atomic instruction provided by most CPUs

TSL (LOCK)

- Atomically sets memory location **LOCK** to 1 and returns old value

Pseudocode

```
void lock(int L)
{
    while (TSL(L) != 0)
        /* wait */ ;
}
```

Assembler

```
TSL L    Read L and set
          condition code if L=0
BNZ      jumps if Z is not set.
MOV #n,L sets L to constant n
```

```
LOCK:    TSL L
          BNZ LOCK
```

```
UNLOCK:  MOV #0, L
```


Spin Locks

Locks using busy waiting are called **spin locks**

Waste CPU

- Should only be used when the wait is expected to be short

May run into *priority inversion problem*

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Priority Inversion Problem and Spin Locks

Two processes:

- H with high priority
- L with low priority
- H should always be scheduled if runnable

Assignment Project Exam Help

Assume the following scenario:

<https://tutorcs.com>

- H is waiting for I/O
- L acquires lock A and enters critical section
- I/O arrives and H is scheduled
- H tries to acquire lock A that L is holding

WeChat: cstutorcs

What happens?

Lock Granularity

```
void Extract(int acc_no, int sum)
{
    lock(L);
    int B = Acc[acc_no];
    Acc[acc_no] = B - sum;
    unlock(L);
}
```

T1: Extract(1, 40);

T2: Extract(2, 40);

What happens if there are concurrent accesses to *different* accounts?

Lock Granularity

```
void Extract(int acc_no, int sum)
{
    lock(L[acc_no]);
    int B = Acc[acc_no];
    Acc[acc_no] = B - sum;
    unlock(L[acc_no]);
}
```

T1: Extract(1, 40);

T2: Extract(2, 40);

Lock granularity: the amount of data a lock is protecting

Is finer granularity always better?

Lock Overhead and Lock Contention

Lock overhead: a measure of the cost associated with using locks

- Memory space
- Initialization
- ***Time required to acquire and release locks***

Lock contention: a measure of the number of processes waiting for a lock

- More contention, less parallelism

• Coarser granularity:

- Lower overhead
- More contention
- Lower complexity

• Finer granularity:

- Higher lock overhead
- Less contention
- Higher complexity

Minimizing Lock Contention/Maximizing Concurrency

Choose finer lock granularity

- But understand tradeoffs


Release a lock as soon as it is not needed

- Make critical sections small!

<https://tutorcs.com>
WeChat: cstutorcs

```
void AddAccount(int acc_no, int balance)
{
    lock(L_Acc);
    CreateAccount(acc_no);
    lock(L[acc_no]);
    Acc[acc_no] = balance;
    unlock(L[acc_no]);
    unlock(L_Acc);
}
```

?



Read/Write Locks

```
void ViewHistory(int acc_no)
{
    print_transactions(acc_no);
}
```

P1: ViewHistory(1234) ;

P2: ViewHistory(1234) ;

P3: ViewHistory(1234) ;

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Any locks needed?

Race Condition

Occurs when multiple threads or processes read and write **shared data** and the final result depends on the relative timing of their execution

- i.e. on the exact process or thread **interleaving**
- Assignment Project Exam Help

E.g., the **Extract** example → final value of account 8,000 or 9,000

<https://tutorcs.com>
WeChat: cstutorcs

Thread Interleavings

```

int a, b; // shared
void P1 ()
{
    a = 1;
    b = 1;
}

void P2 ()
{
    b = 2;
    a = 2;
}
    
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

a = 1	a = 1	a = 1	b = 2	b = 2	b = 2
b = 1	b = 2	b = 2	a = 2	a = 1	a = 1
b = 2	b = 1	a = 2	a = 1	a = 2	b = 1
a = 2	a = 2	b = 1	b = 1	b = 1	a = 2
(2, 2)	(2, 1)	(2, 1)	(1, 1)	(2, 1)	(2, 1)

Thread Interleaving

Menti.com Q1-3 76 84 50

Consider the following three threads:

T1: {a=1; b=2;} T2: {b =1;} T3: {a=2;}

1. How many different thread interleavings are there?

Assignment Project Exam Help

2. If all thread interleavings are as likely to occur, what is the probability to have a=1 and b=1 after all threads complete execution?

<https://tutorcs.com>
WeChat: cstutorcs

3. What about a=2 and b=2?

Semaphores

Blocking synchronization mechanism invented by Dijkstra in 1965

Idea: Processes will cooperate by means of *signals*

- A process will block, waiting for a specific signal
- A process will continue if it has received a specific signal

Semaphores are *special variables*, accessible via the following *atomic* operations:

- **down(s)** : receive a signal via semaphore **s**
- **up(s)** : transmit a signal via semaphore **s**
- **init(s, i)** : initialise semaphore **s** with value **i**

down() also called **P()** (*probeer te verlagen*)

up() also called **V()** (*verhogen*)

Semaphores


Semaphores have two private components:

- A counter (non-negative integer)
- A queue of processes currently waiting for that semaphore

Queue is typically first in first out (FIFO)

<https://tutorcs.com>

WeChat: cstutores



Semaphore
Data Structure

Queue of processes waiting on Semaphore

Semaphore Operations

```
init(s, i) ::= counter(s) = i  
             queue(s) = {}
```

Assignment Project Exam Help

```
down(s) ::= if counter(s) > 0  
             counter(s) = counter(s) - 1  
             else  
               add P to queue(s)  
               suspend current process P
```

```
up(s) ::= if queue(s) not empty  
           resume one process in queue(s)  
           else  
             counter(s) = counter(s) + 1
```

Semaphores for Mutual Exclusion

Binary semaphore: counter is initialized to 1

Similar to a lock/mutex

```
process A                                process B
...                                     ...
down(s)                                down(s)
    critical section                    critical section
up(s)                                  up(s)
end                                    end

main() {
    var s:Semaphore
    ...
    init(s, 1) /* initialise semaphore */
    ...
    start processes A and B in random order
    ...
}
```

Note: for binary semaphore if $s = 1$, $\text{up}(s)$ leaves $s = 1$

General Semaphores

The initial value of a semaphore counter indicates how many processes can access shared data at the same time

counter(s) >= 0:

Initial value defines how many processes can execute down without being blocked


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Menti.com Q4, 5 threads & semaphore 76 84 50

Producer / Consumer



There can be multiple producers and consumers

Producer / Consumer

Buffer constraints:

- Buffer can hold between **0** and **N** items

Producer constraints:

- Items can only be deposited in buffer if there is space (items in buffer $< N$)
- Items can only be deposited in buffer if mutual exclusion is ensured

Consumer constraints:

- Items can only be fetched from buffer if it is not empty (items in buffer > 0)
- Items can only be fetched from buffer if mutual exclusion is ensured

Producer/Consumer?

```
var item, space, mutex: semaphore
init (item, 0)      /* Semaphore to ensure buffer is not empty */
init (space, N)     /* Semaphore to ensure buffer is not full */
init (mutex, 1)     /* Semaphore to ensure mutual exclusion */
```

```
process Producer
loop
  produce item
  down (mutex)
  down (space)
  deposit item
  up (item)
  up (mutex)
end loop
end Producer

process Consumer
loop
  down (mutex)
  down (item)
  fetch item
  up (space)
  up (mutex)
  consume item
end loop
end Consumer
```

What is wrong with this?

Producer/Consumer

```
var item, space, mutex: semaphore
init (item, 0)      /* Semaphore to ensure buffer is not empty */
init (space, N)     /* Semaphore to ensure buffer is not full */
init (mutex, 1)     /* Semaphore to ensure mutual exclusion */
```

```
process Producer
loop
  produce item
  down (space)
  down (mutex)
  deposit item
  up (mutex)
  up (item)
end loop
end Producer


process Consumer
loop
  down (item)
  down (mutex)
  fetch item
  up (mutex)
  up (space)
  consume item
end loop
end Consumer
```

Works for multiple producers & consumers

What happens when space = 0 or items = 0?

Animation: <https://www.youtube.com/watch?v=NuvAjMk9bZ8>

Readers/Writers



Assignment Project Exam Help

- Writers constraints:
 - items can only be written if no other process is writing;
 - items can only be written if no other process is reading.
-
- Readers constraints:
 - items can only be read if no other process is writing;
 - items can be read if there are other processes reading.
-
- File can hold an arbitrary number of items.

Readers/Writers With Semaphores

```
semaphore mutex, wrt;  
int read_cnt = 0;  
init(mutex, 1);  
init(wrt, 1);
```

```
process writer()  
  loop  
    produce item  
    down(wrt);  
    write item  
    up(wrt);  
  end loop  
end writer
```

Does this work?

```
process reader()  
  loop  
    if(read_cnt == 0)  
      //1st reader  
      down(wrt);  
      down(mutex)  
      read_cnt += 1;  
      up(mutex);  
      read item  
      down(mutex);  
      read_cnt -= 1  
      up(mutex);  
      If (read_cnt == 0)  
        up(wrt);  
      consume item  
    end loop  
  end reader
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Readers/Writers With Semaphores

```
semaphore mutex, wrt;  
int read_cnt = 0;  
init(mutex, 1);  
init(wrt, 1);  
  
process writer()  
    loop  
        produce item  
        down(wrt);  
        write item  
        up(wrt);  
    end loop  
end writer  
  
process reader()  
    loop  
        down(mutex)  
        read_cnt += 1;  
        if(read_cnt == 1)  
            // 1st reader  
            down(wrt);  
        up(mutex);  
        read item  
        down(mutex);  
        read_cnt -= 1  
        If (read_cnt == 0)  
            up(wrt);  
        up(mutex);  
        consume item  
    end loop  
end reader
```

Assignment Project Exam Help
<https://tutorcs.com>
WeChat: cstutorcs

Is this fair?

Semaphore Question

The following program consists of 3 concurrent processes and 3 binary semaphores. The semaphores are initialized as $S0 = 1$, $S1 = 0$, $S2 = 0$.

Process P0	Process P1	Process P2
<code>while true</code>	<code>down(S1);</code>	<code>down(S2);</code>
<code>{ down(S0);</code>	<code>up(S0);</code>	<code>up(S0);</code>
<code> print '0';</code>		
<code> up(S1);</code>		
<code> up(S2); }</code>		

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

How many times will P0 print '0'?

Menti.com Q6 76 84 50

General Semaphore Using Binary Semaphores

Describe a suitable data structure for a general semaphore and give a pseudocode outline for the following operations in terms of the operations down(s) and up(s) on a binary semaphore s.

Assignment Project Exam Help

init (value, gs)	https://tutorcs.com initialises the general semaphore gs to value
gen_down (var gs)	WeChat: cstutorcs the down operation on a general semaphore gs
gen_up (var gs)	the up operation on a general semaphore gs

Monitors

Higher-level synchronization primitive

Introduced by Hansen (1973) and Hoare (1974)

Refined by Lampson (1980)

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Monitors

Ensure mutual exclusion for shared resource (data)

Entry procedures

- Can be called from outside the monitor

Internal procedures

- Can be called only from monitor procedures

An (implicit) monitor lock

One or more condition variables

Processes can only call entry procedures

- cannot directly access internal data

Only one process can be in the monitor at one time

Condition Variables

Associated with high-level conditions

- “some space has become available in the buffer”
- “some data has arrived in the buffer”

Operations: [Assignment Project Exam Help](https://tutorcs.com)

- **wait(c)**: releases monitor lock and waits for **c** to be signalled <https://tutorcs.com>
- **signal(c)**: [WeChat: cstutorcs](https://tutorcs.com) wakes up one process waiting for **c**
- **broadcast(c)**: wakes up all processes waiting for **c**

Signals do not accumulate i.e c is not a counter.

- If a condition variable is signalled with no one waiting for it, the signal is lost

What happens on signal?

[Hoare] A process waiting for signal is immediately scheduled

- + Easy to reason about

- Inefficient: the process that signals is switched out, even if it has not finished yet with the monitor

- Places extra constraints on the scheduler

[Lampson] Sending signal and waking up from a wait are not atomic

- More difficult to understand, need to take extra care when waking up from a wait()

- + More efficient, no constraints on the scheduler

- + More tolerant of errors: if the condition being notified is wrong, it is simply discarded when rechecked (see next slides)

*Usually [**Lampson**] is used*

Hoare Monitor Implementation Using Semaphores

Variables

```
semaphore mutex;    // (initially = 1)
semaphore next;     // (initially = 0)
int next_count = 0;
```

Each access procedure **F** will be replaced by

```
wait(mutex);
...
body of access procedure F;
...
if (next_count > 0)
    up(next)
else
    up(mutex);
```

Mutual exclusion within a monitor is ensured

Note: this code is generated by a compiler and is not seen by the programmer who writes the access procedures.

Monitor Implementation – Condition Variables

For each condition variable **c**, we have:

```
semaphore c_sem; // (initially = 0)
int c_count = 0;
```

The operation **wait (c)** can be implemented as:

```
c_count++;
if (next_count > 0) up(next);
else up(mutex);
down(c_sem);
c_count--;
```

The operation **signal (c)** can be implemented as:

```
if (c_count > 0) {
    next_count++; up(c_sem);
    down(next); next_count--;
}
```

Producer/Consumer with Monitors

```
monitor ProducerConsumer
```

```
    condition not_full, not_empty;
```

```
    integer count = 0;
```

```
entry procedure insert(item)
```

```
    if (count == N) wait(not_full);
```

```
    insert_item(item); count++;
```

```
    signal(not_empty);
```

```
entry procedure remove(item)
```

```
    if (count == 0) wait(not_empty);
```

```
    remove_item(item); count--;
```

```
    signal(not_full);
```

```
end monitor
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Does this work?

Producer/Consumer with Lampson Monitors

```
monitor ProducerConsumer
    condition not_full, not_empty;
    integer count = 0;

    entry procedure insert(item)
        while (count == N) wait(not_full);
        insert_item(item); count++;
        signal(not_empty);

    entry procedure remove(item)
        while (count == 0) wait(not_empty);
        remove_item(item); count--;
        signal(not_full);
end monitor
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Readers/Writers Revisited

Correctness Constraints:

- Readers can access file when no writers
- Writers can access file when no readers or writers
- Only one thread manipulates state variables at a time

Assignment Project Exam Help

Basic structure of a solution:

<https://tutorcs.com>

- Reader()
 - Wait until no writers
 - Access file
 - Check out – wake up a waiting writer
- Writer()
 - Wait until no active readers or writers
 - Access file
 - Check out – wake up waiting readers or writer

WeChat: cstutorcs

Readers/Writers: Fairness?

Problem statement clarification

- Suppose that a writer is active and a mixture of readers and writers now shows up. Who should get in next?
- If a writer is waiting and an endless stream of readers keeps showing up. Is it fair for them to become active?

Alternation is a possible fair solution:

- Once a reader is waiting, readers will get in next.
- If a writer is waiting, one writer will get in next.

State variables needed (Protected by a lock called "lock"):

- int NReaders: Number of active readers; initially = 0
- int WaitReaders: Number of waiting readers; initially = 0
- int N Writers: Number of active writers; initially = 0
- int WaitWriters: Number of waiting writers; initially = 0
- Condition CanRead = NIL, CanWrite = NIL

Readers/Writers with Monitors

```
monitor ReadersNriters
  integer WaitWriters, WaitReaders,
           NReaders, N Writers;
  condition CanRead, CanWrite;

  entry procedure StartRead()
    if (N Writers == 1 or WaitWriters > 0)
    {
      ++WaitReaders; Wait (CanRead); --WaitReaders;
    }
    ++Nreaders;
    Signal (CanRead);
  end StartRead

  entry procedure EndRead()
    If (--Nreaders == 0) Signal (CanWrite);
  end EndRead
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Reader/Writer contd

```
entry procedure StartWrite()  
  if(NWriters == 1 or NReaders > 0)  
  {  
    ++WaitWriters; wait(CanWrite); --WaitWriters;  
  }  
  NWriters = 1;  
end StartWrite;
```

Assignment Project Exam Help

<https://tutorcs.com>

```
entry procedure EndWrite()  
  NWriters = 0;  
  if(WaitReaders > 0) Signal(CanRead);  
  else Signal(CanWrite);  
end EndWrite;
```

```
end monitor
```

Monitors

Monitors are a language construct

Not supported by C

Java

- synchronized methods
- no condition variables
 - ✦ wait() and notify()

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Synchronization within Monitors

Synchronization within monitors uses condition variables and two special operations, **wait** and **signal**. A more general form of synchronization would be to have a single primitive, **waituntil**, that had an arbitrary Boolean predicate as parameter. Thus, one could say, for example,

waituntil $(x < 0 \text{ or } y + z < n)$

The signal primitive would be no longer needed. This scheme is clearly more general than that of Hoare, but it is not used. Why not?
(Hint: think about the implementation.)

Bohr and Heisen bugs

Bohrbugs:

- Deterministic, reproducible bugs
- Behave similar to Bohr's atom model where electrons deterministically orbit the nucleus

Heisenbugs

- Non-deterministic, hard to reproduce bugs
 - ✦ Often caused by race conditions
- Suffer from the observer effect (Heisenberg Uncertainty Principle): attempts to observe them (i.e., printf's) make them disappear!

Which bug would you rather have?

- During development/testing: _____
- During deployment: _____

Communication & Synchronization Summary

Signals: really interaction with kernel, to wake a waiting process or indicate a problem.

Pipes: simple read, write type communication

Shared memory: requires synchronisation to prevent corruption

Critical section: code in which process accesses shared resource

Mutual exclusion: only 1 process at a time within CS

Disabling interrupts: may not be effective

Locks: low level, busy wait, very difficult to program correctly

Semaphores: blocks waiting program, but difficult to program

Monitors: easier to program, but signal semantics can be tricky

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs