

程序代写代做 CS编程辅导



CMT10 Visual Computing

WeChat: cstutorcs

Image Filtering
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>
School of Computer Science and Informatics
Cardiff University

Overview

- Linear filtering
- Convolution
- Box filtering
- Gaussian filtering
- Separable kernel
- Median filter
- Sharpening

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Acknowledgement

The majority of the slides in this section are from Svetlana Lazebnik at University of Illinois at Urbana-Champaign

Image Filtering

- Filtering is a technique for modifying or enhancing an image

- Emphasise certain features over other feature

- Filtering is a neighbourhood operation



- The output value of any given pixel is determined by the values of the pixels in the neighbourhood of the corresponding input pixel

- Linear filtering is filtering in which the value of an output pixel is a linear combination (weighted average) of the values of the pixels in the input pixel's neighbourhood


- Linear filtering can be represented by convolution

WeChat: cstutorcs
Assignment Projects Exam Help
Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>

Linear Filtering

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Motivation: Image Denoising

- How can we reduce noise in a photograph?



Moving Average

- Let's replace each pixel with a weighted average of its neighbourhood
- The weights are called the filter



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Moving Average

- Let's replace each pixel with a weighted average of its neighbourhood
- The weights are called the filter
- What are the weights for the centre of a 3x3 neighbourhood?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Moving Average

- Let's replace each pixel with a weighted average of its neighbourhood
- The weights are called the filter kernel
- What are the weights for the centre of a 3x3 neighbourhood?



WeChat: cstutorcs		
1	1	1
Assignment Project Exam Help		
$\frac{1}{9}$	1	1
Email: tutorcs@163.com		
QQ: 749389476		
1	1	1
https://tutorcs.com		

“box filter”

Moving Average

- Let's replace each pixel with a weighted average of its neighbourhood
- The weights are called the filter kernel
- What are the weights for the centre of a 3x3 neighbourhood?



1	1	1
1	10	1
1	1	1

$$\begin{matrix} & \begin{matrix} \text{WeChat: cstutorcs} \\ 1 & 1 & 1 \\ \text{Assignment Project Exam Help} \\ \frac{1}{9} \text{ Email: tutorcs@163.com} \\ \text{QQ: 749389476} \\ \text{https://tutorcs.com} \end{matrix} & = \end{matrix}$$

	?	

“box filter”

Moving Average

- Let's replace each pixel with a weighted average of its neighbourhood
- The weights are called the filter kernel
- What are the weights for the centre of a 3x3 neighbourhood?



1	1	1
1	10	1
1	1	1

$$\begin{matrix} & \begin{matrix} \text{WeChat: cstutorcs} \\ 1 & 1 & 1 \\ \text{Assignment Project Exam Help} \\ \frac{1}{9} & \text{Email: tutorcs@163.com} \\ \text{QQ: 749389476} \\ 1 & 1 & 1 \\ \text{https://tutorcs.com} \end{matrix} & = \end{matrix}$$

	2	

“box filter”

Convolution

- Let f be the image and g be the kernel. The output of convolving f with g is denoted $f * g$



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Convolution

- Let f be the image and g be the kernel. The output of convolving f with g is denoted $f * g$



WeChat: cstutorcs



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749f89476

<https://tutorcs.com>

Convolution

- Let f be the image and g be the kernel. The output of convolving f with g is denoted $f * g$



WeChat: cstutorcs



Convention: kernel is
flipped for convolution

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

Convolution

- Let f be the image and g be the kernel. The output of convolving f with g is denoted $f * g$



WeChat: cstutorcs



Convention: kernel is
flipped for convolution

Convolution

- Let f be the image and g be the kernel. The output of convolving f with g is denoted $f * g$


$$(f * g)[x, y]$$



$$\sum_{i=-k}^l \sum_{j=-l}^l f[x - i, y - j]g[i, j]$$

WeChat: cstutorcs

Convention: kernel is flipped for convolution



Linear Filter: Key Properties

- **Linearity:** $\text{filter}(f_1 + f_2) = \text{filter}(f_1) + \text{filter}(f_2)$
- **Shift invariance:** same behavior regardless of pixel location
 $\text{filter}(\text{shift}(f)) = \text{shift}(\text{filter}(f))$
- Theoretical result: any linear shift-invariant operator can be represented as a convolution



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Linear Filter: More Properties

- Commutative: $a * b = b * a$ 程序代写代做 CS 编程辅导

- Conceptually no difference between filter and signal

- Associative: $a * (b * c) = (a * b) * c$

- Often apply several filters one after another: $((a * b_1) * b_2) * b_3$
 - This is equivalent to applying one filter: $a * (b_1 * b_2 * b_3)$

- Distributive over addition: $a * (b + c) = (a * b) + (a * c)$

- Scalars factor out: $ka * b = a * kb = k(a * b)$

- Identity: unit pulse $e = [\dots, 0, 0, 1, 0, 0, \dots]$, $a * e = a$

QQ: 749389476

<https://tutorcs.com>



Tutor CS


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

Size of the Output

- “full”: output size is the sum of sizes of f and g minus 1
- “same”: output size is the same as the size of f
- “valid”: output size is the difference of the sizes of f and g




WeChat: same

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Boundary Pixels

- What about near the edge? 程序代写代做 CS编程辅导

- The filter window falls off the image
- Need to extrapolate
- Method
 - Clip filter (black)
 - Wrap around
 - Copy edge
 - Reflect across edge



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Boundary Pixels

- Clip filter (black)



程序代写代做 CS编程辅导




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Boundary Pixels

- Wrap around



程序代写代做 CS编程辅导




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Boundary Pixels

- Copy edge



程序代写代做 CS编程辅导




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Boundary Pixels

- Reflect across edge



程序代写代做 CS编程辅导




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Practice with Linear Filter

程序代写代做 CS编程辅导



Original



WeChat: cstutorcs

*Assignment Project Exam Help

0	0	0
0	1	0
0	0	0

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

?

Practice with Linear Filter

程序代写代做 CS编程辅导



Original



WeChat: cstutorcs

*Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Filtered
(no change)

Practice with Linear Filter

程序代写代做 CS编程辅导



Original



WeChat: cstutorcs

*Assignment Project Exam Help

0	0	0
1	0	0
0	0	0

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

?

Practice with Linear Filter

程序代写代做 CS编程辅导



Original



WeChat: cstutorcs
 $\begin{matrix} 0 & 0 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{matrix}$
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Shifted left
by 1 pixel

Practice with Linear Filter

程序代写代做 CS编程辅导



Original



WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com

1	1	1
1	1	1
9	1	1

QQ: 749389476

<https://tutorcs.com>

?

Practice with Linear Filter

程序代写代做 CS编程辅导




Original



WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Blur
(with a box filter)

Practice with Linear Filter

程序代写代做 CS编程辅导



Original



$$\text{Original} * \left(\begin{array}{ccc|ccc} 0 & 0 & 0 & 1 & 1 & 1 \\ 0 & 2 & 0 & -1 & 1 & 1 \\ 0 & 0 & 0 & 9 & 1 & 1 \end{array} \right) = ?$$

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476
(Note that filter weights sum to 1)

<https://tutorcs.com>

Practice with Linear Filter

程序代写代做 CS编程辅导



QR code: 

$\ast \left(\begin{array}{ccc|ccc} 0 & 0 & 0 & 1 & 1 & 1 \\ 0 & 2 & 0 & 1 & 1 & 1 \\ 0 & 0 & 0 & 1 & 1 & 1 \end{array} \right) =$

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476
(Note that filter weights sum to 1)
<https://tutorcs.com>



Sharpening filter:
Accentuates differences
with local average

Smoothing with Box Filter revisited

- What's wrong with this picture?
- What's the solution?



WeChat: cstutorcs

Assignment Project Exam Help

*




=

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Smoothing with Box Filter revisited

- What's wrong with this picture? 程序代写代做 CS编程辅导
- What's the solution?
 - To eliminate edge effect, we distribute the distribution of neighbourhood pixels according to their closeness to the centre.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>
"fuzzy blob"

Gaussian Kernel

程序代写代做 CS编程辅导

$$G(x, y) = \frac{1}{\sigma^2} e^{-\frac{(x^2+y^2)}{2\sigma^2}}$$



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

$5 \times 5, \sigma = 1$




0.003	0.013	0.022	0.013	0.003
0.013	0.059	0.097	0.059	0.013
0.022	0.097	0.159	0.097	0.022
0.013	0.059	0.097	0.059	0.013
0.003	0.013	0.022	0.013	0.003

- Constant factor at front makes volume sum to 1 (can be ignored when computing the filter values, as we should renormalize weights to sum to 1 in any case)

Gaussian Kernel

程序代写代做 CS 编程辅导

$$C \frac{1}{\sigma^2} e^{-\frac{(x^2+y^2)}{2\sigma^2}}$$



$\sigma = 2$ with 30×30 kernel


QQ: 749389476

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com




$\sigma = 5$ with 30×30 kernel

- Standard deviation σ determines the extent of smoothing


Choosing Kernel Width

- The Gaussian function has infinite support, but discrete filters use finite kernels



Choosing Kernel Width

- Rule of thumb: set filter half width to about 50



Gaussian vs. Box Filtering

程序代写代做 CS编程辅导




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Gaussian Filters

- Remove “high frequency” component from the image (low-pass filter)
- Convolution with self is another Gaussian
 - So can smooth with small- σ kernel, repeat, and get same result as large- σ kernel would have
 - Convolving two times with Gaussian kernel with standard deviation σ is the same as convolving one with Gaussian kernel with standard deviation $\sigma\sqrt{2}$

Separable kernel

- Factors into product of two 1D Gaussians

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Separability of the Gaussian Filter

程序代写代做 CS 编程辅导

$$G_{\sigma}(x, y) = \frac{1}{2\pi\sigma^2} e^{-(\frac{x^2+y^2}{2\sigma^2})}$$

$$= \left(\frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{x^2}{2\sigma^2}} \right) \left(\frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{y^2}{2\sigma^2}} \right)$$

- The 2D Gaussian can be expressed as the product of two 1D functions: one is a function of x , and the other is a function of y .
[WeChat: estutors](#)
[Assignment Project Exam Help](#)
[Email: tutorcs@163.com](#)
- In this case, the two functions are the identical 1D Gaussian.

QQ: 749389476

<https://tutorcs.com>

Separability Example

2D convolution
(centre location only)

程序代写 代做CS编程辅导

1	2	3
4	5	6
7	8	9

*

3	5	5
4	4	6

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Separability Example

2D convolution
(centre location only)


$$\begin{array}{|c|c|c|} \hline \text{程序代写} & \text{代做CS编程} & \text{辅导} \\ \hline 1 & 2 & 3 \\ \hline 3 & 4 & 5 \\ \hline \end{array} * \begin{array}{|c|c|c|} \hline 2 & 3 & 3 \\ \hline 3 & 5 & 5 \\ \hline 4 & 4 & 6 \\ \hline \end{array}$$
$$1 \times 2 + 2 \times 3 + 1 \times 3 = 11$$
$$= 2 \times 3 + 4 \times 5 + 2 \times 5 = 36$$
$$= 1 \times 4 + 2 \times 4 + 1 \times 6 = 18$$

$$65$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Separability Example

2D convolution
(centre location only)

The filter factors into a product of 1D filters

程序代写 * 代做CS编程辅导

$$\begin{matrix} 1 & 2 & 3 \\ 2 & 3 & 4 \\ 3 & 4 & 5 \end{matrix} * \begin{matrix} 2 & 3 & 3 \\ 3 & 5 & 5 \\ 4 & 4 & 6 \end{matrix}$$
$$= 1 \times 2 + 2 \times 3 + 1 \times 3 = 11$$
$$= 2 \times 3 + 4 \times 5 + 2 \times 5 = 36$$
$$= 1 \times 4 + 2 \times 4 + 1 \times 6 = 18$$

$$65$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Separability Example

2D convolution
(centre location only)


The filter factors into a product of 1D filters


Perform convolution along rows

$$\begin{array}{c} \text{程序代写} \\ \text{代做CS编程辅导} \\ \hline \end{array} \times \begin{array}{c} 2 \\ 3 \\ 5 \\ 5 \\ 4 \\ 4 \\ 6 \end{array} = 1 \times 2 + 2 \times 3 + 1 \times 3 = 11$$
$$= 2 \times 3 + 4 \times 5 + 2 \times 5 = 36$$
$$= 1 \times 4 + 2 \times 4 + 1 \times 6 = 18$$


$$65$$

 * 

 * 

 = 

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476



<https://tutorcs.com>

Separability Example

2D convolution
(centre location only)

The filter factors into a product of 1D filters

Perform convolution along rows

$$\begin{array}{c} \text{程序代写} \\ \text{代做CS编程辅导} \\ \hline \begin{matrix} 1 & 2 & 2 \\ 3 & 4 & 3 \\ 4 & 4 & 6 \end{matrix} * \begin{matrix} 2 & 3 & 3 \\ 3 & 5 & 5 \\ 4 & 4 & 6 \end{matrix} = 1 \times 2 + 2 \times 3 + 1 \times 3 = 11 \\ = 2 \times 3 + 4 \times 5 + 2 \times 5 = 36 \\ = 1 \times 4 + 2 \times 4 + 1 \times 6 = 18 \\ \hline \end{array}$$

WeChat: cstutorcs

Email: tutorcs@163.com

QQ: 749389476

$$\begin{matrix} 1 & 2 & 1 \end{matrix} \times \begin{matrix} 1 & 2 & 1 \end{matrix} = 11$$
$$\begin{matrix} 2 & 3 & 3 \\ 3 & 5 & 5 \\ 4 & 4 & 6 \end{matrix} = \begin{matrix} 11 \\ 18 \\ 18 \end{matrix}$$

<https://tutorcs.com>

Separability Example

2D convolution
(centre location only)

The filter factors into a product of 1D filters

Perform convolution along rows

Followed by convolution along the remaining column

程序代写 代做CS编程辅导

$$\begin{matrix} 1 & 2 & 3 \\ 2 & 3 & 1 \\ 3 & 1 & 2 \end{matrix} * \begin{matrix} 1 & 2 & 3 \\ 2 & 3 & 1 \\ 3 & 1 & 2 \end{matrix} = \begin{matrix} 1 & 2 & 1 \\ 2 & 1 & 1 \\ 1 & 1 & 1 \end{matrix}$$

$1 \times 2 + 2 \times 3 + 1 \times 3 = 11$
 $= 2 \times 3 + 4 \times 5 + 2 \times 5 = 36$
 $= 1 \times 4 + 2 \times 4 + 1 \times 6 = 18$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

CMT107 Visual Computing

65

Separability Example

2D convolution
(centre location only)

The filter factors into a product of 1D filters

Perform convolution along rows

Followed by convolution along the remaining column

程序代写 代做CS编程辅导

$$\begin{matrix} 1 & 2 & 3 \\ 3 & 4 & 2 \\ 4 & 1 & 2 \end{matrix} * \begin{matrix} 2 & 3 & 3 \\ 3 & 5 & 5 \\ 4 & 4 & 6 \end{matrix} = \begin{matrix} 1 \times 2 + 2 \times 3 + 1 \times 3 = 11 \\ 2 \times 3 + 4 \times 5 + 2 \times 5 = 36 \\ 1 \times 4 + 2 \times 4 + 1 \times 6 = 18 \end{matrix}$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{matrix} 1 & 2 & 1 \end{matrix} \times \begin{matrix} 1 & 2 & 1 \end{matrix} = 65$$
$$\begin{matrix} 1 & 2 & 1 \end{matrix} * \begin{matrix} 2 & 3 & 3 \\ 3 & 5 & 5 \\ 4 & 4 & 6 \end{matrix} = \begin{matrix} 11 \\ 18 \\ 18 \end{matrix}$$
$$\begin{matrix} 1 \\ 2 \\ 1 \end{matrix} * \begin{matrix} 11 \\ 18 \\ 18 \end{matrix} = 1 \times 11 + 2 \times 18 + 1 \times 18 = 65$$

CMT107 Visual Computing

Why is Separability Useful

- What is the complexity of filtering an $n \times n$ image with an $m \times m$ kernel?
 - $O(n^2 \times m^2)$
- What if the kernel separable?
 - $O(n^2 \times m)$



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Noise

- **Salt and pepper noise:** contains random occurrences of black and white pixels
- **Impulse noise:** contains random occurrences of white pixels
- **Gaussian noise:** variations in intensity drawn from a gaussian normal distribution



Original



Salt and pepper noise



CMT107 Visual Computing

Impulse noise



Gaussian noise

49

Source: S. Seitz

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
<https://tutorcs.com>

Gaussian Noise

- Mathematical model: sum of many independent factors
- Good for small standard deviations
- Assumption: independent, zero-mean noise

程序代写代做CS编程辅导

Image



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

$$f(x, y) = \overbrace{\hat{f}(x, y)}^{\text{Ideal Image}} + \overbrace{\eta(x, y)}^{\text{Noise process}}$$


Gaussian i.i.d. ("white") noise:
 $\eta(x, y) \sim \mathcal{N}(\mu, \sigma)$

Reducing Gaussian Noise


$\sigma=0.05$



$\sigma=0.1$





程序代写代做 CS 编程辅导




10
smoothing



Noise
supressed



WeChat: cstutorcs



Assignment Project Exam Help

$\sigma=1$ pixel

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$\sigma=2$ pixels



Image
blurred



Reducing Salt and Pepper Noise

程序代写代做 CS编程辅导

3x3



5x5



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

7x7




QQ: 749389476

- What's wrong with the results?

<https://tutorcs.com>

Alternative Idea: Median Filtering


- A median filter operates over a window by selecting the median intensity in the window



- Is median filtering linear?

Median Filter


- What advantage does median filtering have over Gaussian filtering?
 - Robustness to outliers



Median Filter

程序代写代做 CS编程辅导

Salt-and-pepper noise




Median filtered



WeChat: cstutores


Assignment Project Exam Help

Email: tutorcs@163.com



QQ: 749389476

<https://tutorcs.com>



Gaussian vs. Median Filter

3x3

程序代写代做CS编程辅导

7x7

Gaussian




Median



Sharpening revisited

程序代写代做 CS编程辅导




WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

before <https://tutorcs.com>



after

Sharpening revisited

- What does blurring take away?



程序代写代做 CS编程辅导
WeChat: cstutorcs
smoothed (5x5)
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Sharpening revisited

- What does blurring take away?



程序代写代做 CS编程辅导
WeChat: cstutorcs
smoothed (5x5)
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Sharpening revisited

- What does blurring take away?



- Let's add it back



Sharpening revisited

- What does blurring take away?



- Let's add it back



Unsharp Mask Filter

$$f + \alpha(f - f * g) = (1 + \alpha)f - \alpha f * g = f * ((1 + \alpha)e - \alpha g)$$

↑ ↑ ↑
image blurred unit impulse
 image (identity)



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>


Unsharp Mask Filter

$$f + \alpha(f - f * g) = (1 + \alpha)f - \alpha f * g = f * ((1 + \alpha)e - \alpha g)$$

↑ ↑ ↑

image blurred image unit impulse
(identity)





WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

Gaussian
CMT107 Visual Computing



unit impulse
(identity)



Laplacian of Gaussian

Image Filtering with Java

- Use filter() in BufferedImageOp
- Implement filtering without BufferedImageOp function



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Use filter() Function

- Define a filter kernel

```
float[] km = { // low-pass filter kernel  
    0.1f, 0.1f, 0.1f, // Suppose matrix has been flipped  
    0.1f, 0.2f, 0.1f,  
    0.1f, 0.1f, 0.1f
```

```
};
```

```
Kernel kernel = new Kernel(3, 3, km);
```

- Define an operator

```
BufferedImageOp op = null;  
op = new ConvolveOp(kernel, ConvolveOp.EDGE_NO_OP, null);
```

- Call the filter() function

```
out = new BufferedImage(width, height, BufferedImage.TYPE_INT_RGB);  
op.filter(in, out);
```

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

ConvolveOp(Kernel kernel, int edgeCondition,
RenderingHints hints)

• edgeCondition: ConvolveOp.EDGE_NO_OP or
ConvolveOp.EDGE_ZERO_FILL

<https://tutorcs.com>

Not Use filter() Function

- Define a filter kernel matrix 程序代写代做 CS编程辅导

```
float[] km = {          // low-pass filter kernel
    0.1f, 0.1f, 0.1f,   // Suppose the matrix has been flipped
    0.1f, 0.2f, 0.1f,
    0.1f, 0.1f, 0.1f
};
```



WeChat: cstutorcs

- Calculate convolution on each pixel Assignment Project Exam Help

```
int[] rArray = new int[width*height]; //
for each pixel {
    get the neighbourhood colour
    calculate the colour according to the convolution formula
    set the pixel colour in the output image
}
```

- More details in Lab session 6

Summary

- What is filtering? What is linear filtering? 程序代写代做 CS 编程辅导
- What is convolution?
- How to do sharpening of images?
- What is box filtering, Gaussian filtering, and median filtering?
- What is separable kernel? Why use separable kernel? WeChat: cstutorcs



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>