

Assignment Project Exam Help

SQL: A Language for Database Applications

<https://tutorcs.com>

P.J. McBrien

Imperial College London

WeChat: cstutorcs

Bank Branch Database

branch		
sortcode	branch	cash
56	'Wimbledon'	94340.45
34	'Goodge St'	8900.67
67	'Strand'	34005.00

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	101	4000.00	5/1/1999
1002	100	-223.45	8/1/1999
1004	107	-100.00	11/1/1999
1005	103	45.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999

account			
no	type	name	rate
100	'current'	'McBrien, P.'	NULL
101	'deposit'	'McBrien, P.'	5.25
103	'current'	'Boyd, M.'	NULL
107	'current'	'Poulovassilis, A.'	NULL
119	'deposit'	'Poulovassilis, A.'	5.50
125	'current'	'Bailey, J.'	NULL

key branch(sortcode)

key branch(bname)

key movement(mid)

key account(no)

movement(no) \xRightarrow{fk} account(no)account(sortcode) \xRightarrow{fk} branch(sortcode)

SQL WHERE expressions in more detail

Testing Strings against a Pattern

`WHERE column LIKE pattern ESCAPE escape_char`

Will return TRUE where pattern matches column. The escape_char may be used before any of the special characters below to allow them to be treated as normal text.

- `_` to match a single character
- `%` to match any number (including zero) of characters
- TransactSQL Only: `[A-Z]` to match a character between A and Z
- TransactSQL Only: `[ABC]` to match a characters A, B and C

WeChat: cstutorcs

List customers whose first initial is P, and have one more initial

```
SELECT DISTINCT cname
FROM   account
WHERE  cname LIKE '%, P. _ '
```

SQL WHERE expressions in more detail

Testing Strings against a Pattern

`WHERE column LIKE pattern ESCAPE escape_char`

Will return TRUE where pattern matches column. The escape_char may be used before any of the special characters below to allow them to be treated as normal text.

- `_` to match a single character
- `%` to match any number (including zero) of characters
- TransactSQL Only: `[A-Z]` to match a character between A and Z
- TransactSQL Only: `[ABC]` to match a characters A, B and C

<https://tutorcs.com>

WeChat: cstutorcs

List customers whose first initial is between A and L

```
SELECT DISTINCT cname
FROM   account
WHERE  cname LIKE '%, [A-L].%'
```

Processing the result of project

Modifications to data

Any processing of data to appear in a result set must be placed in the **SELECT** clause

- Many functions proposed in ANSI SQL, e.g.
 - **ABS**(number) returns the absolute value of any number
 - **ROUND**(value,dp) rounds a numeric value to dp decimal places
 - **UPPER**(str) returns the string converted to all capitals
- Tends to be an aspect of SQL implementations that is not ANSI SQL compliant, e.g.
 - Postgres: **LENGTH**(object) returns the length of any object (including strings)
 - TransactSQL: **LEN**(str) returns the length of any string type column

Display accounts with just surnames and rounded rates

PostgreSQL

```
SELECT no,
       ROUND(rate,1) AS rate_1dp,
       SUBSTRING(cname FROM 1 FOR POSITION(' ' IN cname)-1) AS surname
FROM   account
```

Quiz 1: SQL extensions to RA select and project

customer				
cname	phone	address	joined	salary
'McBrien, P.'	'02077651234'	'123 Strand, London WC1A'	1999-01-03	30000
'Boyd, M.'	'02077656666'	'33 Aldwych, London'	1999-01-05	NULL
'Poulovassilis, A.'	'02089474321'	'13 Haydons Rd, London SW19'	1999-01-05	40000
'Bailey, J.'	'02089461111'	'22 Queens Rd, London SW19'	1999-01-07	45000

```

SELECT cname,
SUBSTRING(address, CHARINDEX(' ', address)+2, LEN(address)) AS area
FROM customer
WHERE phone LIKE '02089[4-7]%' ;

```

<https://tutorcs.com>

What is the result of the TransactSQL query?

A

cname	area
Bailey, J.	London SW19
Poulovassilis, A.	London SW19

B

cname	area
Bailey, J.	22 Queens Rd
Poulovassilis, A.	13 Haydons Rd

C

cname	area
Poulovassilis, A.	London SW19

D

cname	area
Poulovassilis, A.	13 Haydons Rd

WeChat: cstutorcs

Processing the result of project: CASE statements

CASE statements

A CASE statement may be put in the SELECT clause to process the values being returned.

Display account interest rates

```
SELECT no,
       COALESCE(rate,0.00) AS rate,
       CASE
         WHEN rate > 0 AND rate < 5.5
           THEN 'low rate'
         WHEN rate >= 5.5
           THEN 'high rate'
         ELSE 'zero rate'
       END AS interest_class
FROM account
```

no	rate	interest_class
100	0.00	zero rate
101	5.25	low rate
103	0.00	zero rate
107	0.00	zero rate
119	5.50	high rate
125	0.00	zero rate

Need for yet another type of Join?

account				
no	type	cname	rate	sortcode
100	'current'	'McBrien, P.'	NULL	57
101	'deposit'	'McBrien, P.'	5.25	67
103	'current'	'Boyd, M.'	NULL	34
107	'current'	'Poulovassilis, A.'	NULL	56
119	'deposit'	'Poulovassilis, A.'	5.50	56
125	'current'	'Bailey, J.'	NULL	56

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	101	4000.00	1/1/1999
1002	100	233.45	1/1/1999
1004	103	110.00	1/1/1999
1005	103	145.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999

Assignment Project Exam Help

<https://tutorcs.com>

Listing of movement mid for all customers with movements

```
SELECT cname,
        mid
FROM   account NATURAL JOIN
        movement
```



cname	mid
McBrien, P.	1000
McBrien, P.	1001
McBrien, P.	1002
Poulovassilis, A.	1004
Boyd, M.	1005
McBrien, P.	1006
Poulovassilis, A.	1007
McBrien, P.	1008
Poulovassilis, A.	1009

Need for yet another type of Join?

account				
no	type	cname	rate	sortcode
100	'current'	'McBrien, P.'	NULL	56
101	'deposit'	'McBrien, P.'	5.25	67
103	'current'	'Boyd, M.'	NULL	34
107	'current'	'Poulovassilis, A.'	NULL	56
119	'deposit'	'Poulovassilis, A.'	5.50	56
125	'current'	'Bailey, J.'	NULL	56

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	101	4000.00	15/1/1999
1002	100	233.45	15/1/1999
1003	101	110.00	15/1/1999
1005	103	145.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999

Assignment Project Exam Help

<https://tutorcs.com>

Listing any movements for all customers

```
SELECT cname,
       mid
FROM   account NATURAL LEFT JOIN
       movement
```



cname	mid
McBrien, P.	1000
McBrien, P.	1001
McBrien, P.	1002
Poulovassilis, A.	1004
Boyd, M.	1005
McBrien, P.	1006
Poulovassilis, A.	1007
McBrien, P.	1008
Poulovassilis, A.	1009
Bailey, J.	NULL

Left and Right Joins

Left Join

A left join $R \overset{L}{\bowtie} S$ returns every row in R , even if no rows in S match. In such cases where no row in S matches a row from R , the columns of S are filled with NULL values.

Right Join

A right join $R \overset{R}{\bowtie} S$ returns every row in S , even if no rows in R match. In such cases where no row in R matches a row from S , the columns of R are filled with NULL values.

Outer Join

An outer join $R \overset{O}{\bowtie} S$ returns every row in R , even if no rows in S match, and also returns every row in S even if no row in R matches.

$$R \overset{O}{\bowtie} S \equiv (R \overset{L}{\bowtie} S) \cup (R \overset{R}{\bowtie} S)$$

RA equivalent of LEFT JOIN

Assignment Project Exam Help

```

SELECT A1, ..., Am
FROM R1 LEFT JOIN R2 ON O1 AND ... AND Oi
WHERE P1
AND ...
AND Pk

```

<https://tutorcs.com>



$$\pi_{A_1, \dots, A_m} \sigma_{P_1 \wedge \dots \wedge P_k} (\sigma_{O_1 \wedge \dots \wedge O_i} (R_1 \times R_2) \cup (R_1 - \sigma_{O_1 \wedge \dots \wedge O_i} (R_1 \times R_2)) \times \omega(R_2))$$

WeChat: cstutorcs

- $\omega(R_2)$ returns a row of NULLs with the same number of columns as R_2

Quiz 2: SQL LEFT JOIN ... ON (1)

```

SELECT account.no,
       movement.amount
FROM account LEFT JOIN movement
ON account.no=movement.no
AND movement.amount<0

```

What is the result of the above query?

<https://tutorcs.com>

A

no	amount
100	-223.45
107	-100.00

B

no	amount
100	-223.45
107	-100.00

C

no	amount
100	-223.45
101	NULL
103	NULL
107	-100.00
119	NULL
125	NULL

D

no	amount
100	-223.45
101	0.00
103	0.00
107	-100.00
119	0.00
125	0.00

Quiz 3: SQL LEFT JOIN ... ON (2)

```

SELECT account.no,
       movement.amount
FROM account LEFT JOIN movement
ON account.no=movement.no
WHERE movement.amount<0

```

What is the result of the above query?

<https://tutorcs.com>

A

no	amount
100	-223.45
107	-100.00

B

no	amount
100	-223.45
107	-100.00

C

no	amount
100	-223.45
101	NULL
103	NULL
107	-100.00
119	NULL
125	NULL

D

no	amount
100	-223.45
101	0.00
103	0.00
107	-100.00
119	0.00
125	0.00

Worksheet: Left, Right and Outer Joins

worksheet_null database

movement			
mid	no	amount	tdate
0999	119	45.00	null
1000	100	2300.00	5/1/1999
1001	101	4000.00	5/1/1999
1002	100	223.45	8/1/1999
1004	107	-100.00	11/1/1999
1005	103	145.50	12/1/1999
1006	100	10.23	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5500.00	16/1/1999
1010	100	null	20/1/1999
1011	null	null	20/1/1999
1012	null	600.00	20/1/1999
1013	null	-46.00	20/1/1999

account				
no	type	cname	rate	sortcode
100	'current'	'McBrien, P.'	null	67
101	'deposit'	'McBrien, P.'	5.25	67
119	'deposit'	'Poulovassilis, A.'	5.50	56
125	'current'	'Bailey, J.'	null	56

OLTP and OLAP

OLTP

- online transactional processing
- reads and writes to a few rows
- 'standard' data processing

```
BEGIN TRANSACTION T1
UPDATE branch
SET cash=cash-10000.00
WHERE sortcode=56

UPDATE branch
SET cash=cash+10000.00
WHERE sortcode=34
COMMIT TRANSACTION T1
```

OLAP

- online analytical processing
- reads many rows
- management information

```
BEGIN TRANSACTION T4
SELECT SUM(cash)
FROM branch
COMMIT TRANSACTION T4
```

SQL OLAP features: GROUP BY

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	101	4000.00	5/1/1999
1002	100	-223.45	8/1/1999
1004	101	-100.00	11/1/1999
1005	103	145.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999

FROM movement

GROUP BY no

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1002		-223.45	8/1/1999
1006		10.23	15/1/1999
1001	101	4000.00	5/1/1999
1008		1230.00	15/1/1999
1004	107	-100.00	11/1/1999
1007		345.56	15/1/1999
1005	103	145.50	12/1/1999
1009	119	5600.00	18/1/1999

Aggregate Functions

Aggregate	Semantics
SUM	Sum the values of all rows in the group
COUNT	Count the number of non-NULL rows in the group
AVG	Average of the non-NULL values in the group
MIN	Minimum value in the group
MAX	Maximum value in the group
...	...

GROUP BY rules

- Only one row output per group
- ANSI SQL says must apply aggregate function to non grouped columns*

SQL OLAP features: GROUP BY

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	101	4000.00	5/1/1999
1002	100	-223.45	8/1/1999
1004	101	-100.00	11/1/1999
1005	103	145.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999

FROM movement

GROUP BY no

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1002		-223.45	8/1/1999
1006		10.23	15/1/1999
1001	101	4000.00	5/1/1999
1008		1230.00	15/1/1999
1004	107	-100.00	11/1/1999
1007		345.56	15/1/1999
1005	103	145.50	12/1/1999
1009	119	5600.00	18/1/1999

Example of Aggregate Functions

```

SELECT no,
       SUM(amount) AS balance,
       COUNT(amount) AS no_trans
FROM movement
GROUP BY no

```

no	balance	no_trans
100	2086.78	3
101	5230.00	2
103	145.50	1
107	245.56	2
119	5600.00	1

GROUP BY rules

- Only one row output per group
- ANSI SQL says must apply aggregate function to non grouped columns*

Quiz 4: GROUP BY in ANSI SQL

account				
<u>no</u>	type	cname	rate	sortcode
100	'current'	'McBrien, P.'	NULL	67
101	'deposit'	'McBrien, P.'	5.25	67
103	'current'	'Boyd, M.'	NULL	34
107	'current'	'Poulouvassilis, A.'	NULL	56
119	'deposit'	'Poulouvassilis, A.'	5.50	56
125	'current'	'Bailey, J.'	NULL	56

Assignment Project Exam Help

<https://tutorcs.com>

Which SQL query is not permitted in ANSI SQL?

A

```
SELECT no,
       cname,
       AVG(rate)
FROM account
GROUP BY no
```

B

```
SELECT no,
       MIN(cname),
       AVG(rate)
FROM account
GROUP BY no
```

C

```
SELECT no,
       MIN(rate),
       MAX(rate)
FROM account
GROUP BY no
```

D


```
SELECT AVG(rate)
FROM account
```

WeChat: cstutorcs

SQL OLAP features: Aggregate operators

- Normally use GROUP BY on all non-aggregated attributes.


```
SELECT no,
       SUM(amount) AS total,
       COUNT(amount) AS trans
FROM   movement
GROUP BY no
```



no	total	trans
119	5600.00	1
107	245.56	2
103	145.50	1
101	5230.00	2
100	2086.75	3

- Don't forget to choose bag or set semantics for COUNT

```
SELECT COUNT(DISTINCT no) AS active_accounts
FROM   movement
```



active_accounts
5

- NULL attributes don't count!

```
SELECT COUNT(rate) AS no_rates
FROM   account
```



no_rates
2

Quiz 5: GROUP BY over NULL values (1)

movement			
mid	no	amount	tdate
0999	119	45.00	NULL
1000	100	2300.00	5/1/1999
1001	101	1230.00	5/1/1999
1002	100	-223.45	8/1/1999
1006	100	10.23	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999
1010	100	NULL	20/1/1999
1011	NULL	NULL	20/1/1999
1012	NULL	600.00	20/1/1999
1013	NULL	-46.00	20/1/1999

account				
no	type	cname	rate	sortcode
100	'current'	'McBrien, P.'	NULL	67
101	'deposit'	'McBrien, P.'	5.25	67
102	'deposit'	'Poulouvasilis, A.'	5.50	56
125	'current'	'Bailey, J.'	NULL	56

```

SELECT movement.no,
       COUNT(movement.amount) AS no_trans,
       MIN(movement.amount) AS min_value
FROM   movement NATURAL JOIN account
GROUP BY movement.no

```

What is the result of the above query?

A

no	no_trans	min_value
119	2	45.00
101	2	1230.00
107	1	-100.00
100	3	-223.45
103	1	145.00

B

no	no_trans	min_value
101	2	1230.00
100	4	-223.45
119	2	45.00

C

no	no_trans	min_value
101	2	1230.00
100	4	NULL
119	2	45.00

D

no	no_trans	min_value
101	2	1230.00
100	3	-223.45
119	2	45.00

Quiz 6: GROUP BY over NULL values (2)

movement			
mid	no	amount	tdate
0999	119	45.00	NULL
1000	100	2300.00	5/1/1999
1001	101	4000.00	5/1/1999
1002	100	223.45	8/1/1999
1006	100	10.23	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999
1010	100	NULL	20/1/1999
1011	NULL	NULL	20/1/1999
1012	NULL	600.00	20/1/1999
1013	NULL	-46.00	20/1/1999

account				
no	type	cname	rate	sortcode
100	'current'	'McBrien, P.'	NULL	67
101	'deposit'	'McBrien, P.'	5.25	67
119	'deposit'	'Pourovassilis, A.'	5.50	56
125	'current'	'Bailey, J.'	NULL	56

```
SELECT movement.no,
       SUM(movement.amount) AS balance
FROM   movement
GROUP BY movement.no
```

<https://tutorcs.com>

What is the result of the above query?

WeChat: cstutorcs

A

no	balance
NULL	NULL
NULL	600.00
NULL	-46.00
119	5645.00
101	5230.00
100	2086.78

B

no	balance
NULL	600.00
NULL	-46.00
119	5645.00
101	5230.00
100	2086.78

C

no	balance
NULL	554.00
119	5645.00
101	5230.00
100	2086.78

D

no	balance
119	5645.00
101	5230.00
100	2086.78

Selecting results from aggregates: HAVING

GROUP BY in the RA

- An extension to the RA includes a group by operator
- In SQL, the GROUP BY operator is applied *outside* the $\sigma_P(\dots \times \dots)$
- To execute a σ_P *outside* the GROUP BY you must place the predicates P in a HAVING clause

```
SELECT
  SUM(amount) AS balance
  COUNT(amount) AS no_trans
FROM
  movement
GROUP BY
  no
HAVING
  SUM(amount) > 2000
```

no	balance	no_trans
100	2086.18	3
101	5230.00	2
119	5600.00	1



<https://tutorcs.com>

WeChat: cstutorcs

Ordering of SQL clauses

- HAVING is executed after GROUP BY, but before SELECT
- Can be used to avoid divide by zero errors

```
SELECT
  no,
  MAX(amount)/MIN(amount) AS variance_ratio
FROM
  movement
GROUP BY
  movement.no
HAVING
  MIN(amount) < 1
```

Quiz 7: HAVING

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	101	4000.00	5/1/1999
1002	100	-223.45	8/1/1999
1004	107	-100.00	15/1/1999
1005	103	-145.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999

account				
no	type	cname	date	code
100	'current'	'McBrien, P.'	NULL	67
101	'deposit'	'McBrien, P.'	5.25	67
103	'current'	'Boyd, M.'	NULL	34
107	'current'	'Poulovassilis, A.'	NULL	56
119	'deposit'	'Poulovassilis, A.'	5.50	56
125	'current'	'Bailey, J.'	NULL	56

```

SELECT account.no,
       account.cname,
       SUM(movement.amount) AS balance
FROM   account NATURAL JOIN movement
WHERE  movement.amount > 200
GROUP BY account.no,
          account.cname
HAVING COUNT(movement.no) > 1
AND     SUM(movement.amount) > 1000

```

<https://tutorcs.com>
WeChat: cstutorcs

What is the result of the above query?

A

no	cname	balance
101	McBrien, P.	5230.00

B

no	cname	balance
101	McBrien, P.	5230.00
119	Poulovassilis, A.	5600.00

C

no	cname	balance
100	McBrien, P.	2086.78
101	McBrien, P.	5230.00

D

no	cname	balance
100	McBrien, P.	2086.78
101	McBrien, P.	5230.00
119	Poulovassilis, A.	5600.00

SQL OLAP features: PARTITION

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	101	4000.00	5/1/1999
1002	100	-223.45	8/1/1999
1004	107	-100.00	11/1/1999
1005	103	145.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1230.00	15/1/1999
1009	119	5600.00	18/1/1999

OVER (PARTITION BY no)
FROM movement

movement			
mid	no	amount	tdate
1000	100	2300.00	5/1/1999
1002	100	-223.45	8/1/1999
1006	100	10.23	15/1/1999
1001	101	4000.00	5/1/1999
1008	101	1230.00	15/1/1999
1004	107	-100.00	11/1/1999
1007	107	345.56	15/1/1999
1005	103	145.50	12/1/1999
1009	119	5600.00	18/1/1999

<https://tutorcs.com>

```
SELECT mid,
       no,
       amount,
       SUM(amount) OVER (PARTITION BY no) AS balance
FROM movement
```

mid	no	amount	balance
1000	100	2300.00	2086.78
1002	100	-223.45	2086.78
1006	100	10.23	2086.78
1001	101	4000.00	5230.00
1008	101	1230.00	5230.00
1004	107	-100.00	245.56
1007	107	345.56	245.56
1005	103	145.50	145.50
1009	119	5600.00	5600.00

PARTITION BY

- One row output per input row
- Aggregates apply to partition

Relationally Complete SQL

Relational Completeness

- Relational completeness in SQL means being able to fully support the RA in SQL
- 'pure' RA can be fully supported by SQL
- Aggregates require 'relationally complete' SQL
 - Temporary tables
 - SELECT statements in FROM clause

```
SELECT SUM(amount) AS total
INTO #total_balance
FROM movement
```



#total_balance
total
13307.84

```
SELECT movement.no,
SUM(movement.amount) AS balance,
ROUND(100*SUM(movement.amount)/
#total_balance.total,1) AS pc
FROM movement,
#total_balance
GROUP BY movement.no,#total_balance.total
ORDER BY movement.no
```



no	balance	pc
100	2086.78	15.7
101	5230.00	39.3
103	145.50	1.1
107	245.56	1.8
119	5600.00	42.1

Relationally Complete SQL

Relational Completeness

- Relational completeness in SQL means being able to fully support the RA in SQL
- 'pure' RA can be fully supported by SQL
- Aggregates require 'relationally complete' SQL
 - Temporary tables
 - SELECT statements in FROM clause

```
SELECT movement.no,
       SUM(movement.amount) AS balance,
       ROUND(100*SUM(movement.amount)/total_balance.total,1) AS pc
FROM   movement,
       (SELECT SUM(amount) AS total FROM movement) total_balance
GROUP BY movement.no, total_balance.total
ORDER BY movement.no
```

<https://tutorcs.com>

WeChat: cstutorcs



no	balance	pc
100	2086.78	15.7
101	5230.00	39.3
103	145.50	1.1
107	245.56	1.8
119	5600.00	42.1

SQL OLAP features: Ordering Rows

movement			
<u>mid</u>	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	100	4000.00	5/1/1999
1002	100	-223.45	8/1/1999
1004	107	-100.00	11/1/1999
1005	103	145.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1230.00	15/1/1999
1009	110	5600.00	18/1/1999

Assignment Project Exam Help

<https://tutoroics.com>

WeChat: cstutoroics

```
SELECT mid,
       tdate,
       amount
FROM movement
ORDER BY mid
```



mid	tdate	amount
1000	1999-01-05	2300.00
1001	1999-01-05	4000.00
1002	1999-01-08	-223.45
1004	1999-01-11	-100.00
1005	1999-01-12	145.50
1006	1999-01-15	10.23
1007	1999-01-15	345.56
1008	1999-01-15	1230.00
1009	1999-01-18	5600.00

SQL OLAP features: Ranking Rows

Assignment Project Exam Help

```

SELECT mid,
       tdate,
       amount,
       RANK() OVER
         (ORDER BY amount DESC) AS rank
FROM   movement

```



mid	tdate	amount	rank
1009	1999-01-18	5600.00	1
1001	1999-01-05	4000.00	2
1000	1999-01-05	2300.00	3
1008	1999-01-15	1230.00	4
1007	1999-01-15	345.56	5
1005	1999-01-12	145.50	6
1006	1999-01-15	10.23	7
1004	1999-01-11	-100.00	8
1002	1999-01-08	-223.45	9

- RANK function provides normal concept of ranking values in order
- DENSE RANK function will not skip numbers where previous values are identical
- Only in Postgres since version 9.0

<https://tutorcs.com>

WeChat: cstutors

Quiz 8: Execution of SQL clauses

SELECT
FROM
WHERE
GROUP BY
HAVING
ORDER BY

Assignment Project Exam Help

<https://tutorcs.com>

What order are the SQL clauses executed in?

A

SELECT
FROM
WHERE
GROUP BY
HAVING
ORDER BY

B

FROM
WHERE
SELECT
GROUP BY
HAVING
ORDER BY

C

FROM
WHERE
GROUP BY
HAVING
SELECT
ORDER BY

D

ORDER BY
HAVING
GROUP BY
WHERE
FROM
SELECT

WeChat: cstutorcs

OLAP: Pivot


Assignment Project Exam Help

- for presentation purposes useful to change layout of table
- information spread over rows is instead spread over columns

```

SELECT  branch.sortcode,
        branch.bname,
        account.type,
        COUNT(no) AS qty
FROM    account JOIN branch
ON      account.sortcode=
        branch.sortcode
GROUP BY branch.sortcode,
        branch.bname,
        account.type
ORDER BY branch.sortcode,
        branch.bname

```



sortcode	bname	type	qty
34	Goode St	current	1
56	Wimbledon	current	2
56	Wimbledon	deposit	1
67	Strand	current	1
67	Strand	deposit	1

SQL OLAP: Pivot using CASE statements

```

SELECT  branch.sortcode,
        branch.bname,
        COUNT(CASE WHEN type='current' THEN no ELSE NULL END) AS current,
        COUNT(CASE WHEN type='deposit' THEN no ELSE NULL END) AS deposit,
        COUNT(CASE WHEN type NOT IN ('current','deposit') THEN no
        ELSE NULL END) AS other
FROM    account JOIN branch ON account.sortcode=branch.sortcode
GROUP BY branch.sortcode, branch.bname
ORDER BY branch.sortcode, branch.bname

```

<https://tutorcs.com>



WeChat: cstutores

sortcode	branch name	current	deposit	other
34	Goodge St	1	0	0
56	Wimbledon	2	1	0
67	Strand	1	1	0

- use CASE statements to filter values from column being pivoted
- one case for each value
- wise to have a default case

Worksheet: OLAP Queries in SQL

Assignment Project Exam Help

movement			
<u>mid</u>	no	amount	tdate
1000	100	2300.00	5/1/1999
1001	101	4000.00	5/1/1999
1002	100	-123.45	8/1/1999
1004	107	-100.00	11/1/1999
1005	103	145.50	12/1/1999
1006	100	10.23	15/1/1999
1007	107	345.56	15/1/1999
1008	101	1238.00	15/1/1999
1009	119	5600.00	18/1/1999

account				
<u>no</u>	type	cname	rate	sortcode
100	'current'	'McBrien, P.'	NULL	67
101	'deposit'	'McBrien, P.'	5.25	67
103	'current'	'Boyd, M.'	NULL	34
107	'current'	'Poulovassilis, A.'	NULL	56
119	'deposit'	'Poulovassilis, A.'	5.50	56
125	'current'	'Bailey, J.'	NULL	56

<https://tutorcs.com>

WeChat: cstutorcs

Worksheet: OLAP Queries Questions 3 & 4

- 3 Write an SQL query returning the scheme

(*cname*, *current*, *balance*, *deposit*, *balance*) that lists one row for each customer (i.e. each distinct *cname*) with a column for the net balance of all current accounts held by the customer, and a column for the net balance of all deposit accounts held by the customer.

- 4 Write an SQL query returning the scheme

(*no*, *cname*, *type*, *pc_cust_funds*, *pc_type_funds*) that lists one row for each account, and for each account, lists the *no*, *cname* and *type* of the account, and in *pc_cust_funds* the percentage of the customer funds held in the account, and in *pc_type_funds* the percentage of the total funds in this particular type of account. For the current data this should result in:

no	cname	type	pc_cust_funds	pc_type_funds
100	McBrien, P.	current	28.52	84.22
101	McBrien, P.	deposit	71.48	48.29
103	Boyd, M.	current	100.00	5.87
107	Poulovassilis, A.	current	4.20	9.91
119	Poulovassilis, A.	deposit	95.80	51.71
125	Bailey, J.	current	NULL	0.00

Worksheet: OLAP Queries in SQL (3)

Assignment Project Exam Help

```
SELECT    account.cname ,
          COALESCE(SUM(CASE account.type
                        WHEN 'current' THEN movement.amount
                        ELSE null END),0.0) AS current_balance ,
          COALESCE(SUM(CASE account.type
                        WHEN 'deposit' THEN movement.amount
                        ELSE null END),0.0) AS deposit_balance
FROM      account LEFT JOIN movement ON account.no=movement.no
GROUP BY  account.cname
```

<https://tutorcs.com>

WeChat: cstutorcs

Worksheet: OLAP Queries in SQL (4)

Assignment Project Exam Help

```
SELECT DISTINCT account.no ,
               account.cname ,
               account.type ,
               ROUND(COALESCE(100.0*SUM(movement.amount) OVER (PARTITION BY account.no),0.0)/
                    SUM(movement.amount) OVER (PARTITION BY account.cname),2)
               AS pc_type.funds,
               ROUND(COALESCE(100.0*SUM(movement.amount) OVER (PARTITION BY account.no),0.0)/
                    SUM(movement.amount) OVER (PARTITION BY account.type),2)
               AS pc_type.funds
FROM   account LEFT JOIN movement ON account.no=movement.no
```

<https://tutorcs.com>
WeChat: cstutorcs

SQL OLAP: Un-pivot using UNION statements

Un-pivot the account table to triple format

```

SELECT no,
       'cname' AS col,
       cname AS value
FROM account
UNION
SELECT no,
       'type' AS col,
       type AS value
FROM account
UNION
SELECT no,
       'rate' AS col,
       CAST(rate AS VARCHAR) AS value
FROM account
WHERE rate IS NOT NULL
UNION
SELECT no,
       'sortcode' AS col,
       CAST(sortcode AS VARCHAR) AS value
FROM account

```



no	col	value
100	cname	McBrien, P.
100	sortcode	67
100	type	current
101	cname	McBrien, P.
101	rate	5.25
101	sortcode	67
101	type	deposit
103	cname	Floyd, M.
103	sortcode	34
103	type	current
107	cname	Poulovassilis, A.
107	sortcode	56
107	type	current
119	cname	Poulovassilis, A.
119	rate	5.50
119	sortcode	56
119	type	deposit
125	cname	Bailey, J.
125	sortcode	56
125	type	current

SQL Functions

FUNCTION

- Most SQL implementations support some variant of ANSI SQL FUNCTION
- Details vary ...

TransactSQL function to return cnames reformatted

```
CREATE FUNCTION cname_to_initial_first (@cname VARCHAR(20))
RETURNS VARCHAR(20) AS
BEGIN
    DECLARE @ifcname VARCHAR(20)
    SELECT @ifcname=
        SUBSTRING(@cname, CHARINDEX(' ', @cname)+2, LEN(@cname)) +
        SUBSTRING(@cname, 1, CHARINDEX(' ', @cname)-1)
    RETURN @ifcname
END
```

```
SELECT no,
       dbo.cname_to_initial_first(
           account.cname) AS cname
FROM   account
```



no	cname
100	P.McBrien
101	P.McBrien
103	M.Boyd
107	A.Poulovassilis
119	A.Poulovassilis
125	J.Bailey

SQL Procedures

PROCEDURE

- No specific PROCEDURE construct in Postgres
- TransactSQL supports PROCEDURE definition, and generally refers to them as stored procedure

TransactSQL Procedure to move cash between branches

```
CREATE PROCEDURE move_cash
(
  @from_branch INTEGER,
  @to_branch INTEGER,
  @total DECIMAL(10,2)
) AS
BEGIN
  UPDATE branch
  SET cash=cash-@total
  WHERE sortcode=@from_branch

  UPDATE branch
  SET cash=cash+@total
  WHERE sortcode=@to_branch
END
```

SQL Constraints

$$\forall \text{No, Rate. account}(\text{No}, _, _, \text{Rate}, _) \rightarrow \text{Rate} \geq 0.00$$

```
ALTER TABLE account
ADD CONSTRAINT check_account_rate
CHECK (rate >= 0.00)
```

```
IF account(No, CN, 'current', _, SC) THEN current_account(No, CN, SC)
```

```
CREATE FUNCTION is_in_current_account(@NO INT, @CN VARCHAR(20), @SC INT)
RETURNS BIT AS
BEGIN
```

```
    IF EXISTS (SELECT *
               FROM current_account
               WHERE no=@NO
               AND   cn=cn
               AND   sortcode=@SC)
```

```
    RETURN 1
```

```
    RETURN 0
```

```
END;
```

```
ALTER TABLE account
ADD CONSTRAINT check_current_account
CHECK (type <> 'current' OR dbo.is_in_current_account(no, cname, sortcode)=1);
```