

580: Algorithms  
Tutorial: Dynamic Programming

1. The array  $A = [A_1, \dots, A_N]$  contains  $N$  integers.
- (a) A *prefix subarray* of  $A$  is any continuous subarray that starts with  $A[1]$ . Write a  $\Theta(N)$ -time algorithm to find the greatest sum of any prefix subarray of  $A$ .
  - (b) The greatest sum of *any* continuous subarray of  $A$  can be found as follows. For each position  $i$  in the array, find  $s_i$ , the maximum sum of any continuous subarray starting at  $i$ . The solution is then the maximum of those  $s_i$  values. There are  $N$  such values, so this method will take  $\Theta(N^2)$  time using your answer for (1a). This is referred to as a *naïve* solution.

By considering the structure of the naive solution, design a  $\Theta(N)$ -time solution to the problem.

**Answer:**

- (a) The algorithm needs to loop through the array maintaining two variables: the sum of all the elements seen so far, and the greatest prefix sum found so far. Each time you see a new element, the new total for all elements gives you a possible value for the max prefix sum.

```
1: procedure MAXPREFIX( $A = [A_1, \dots, A_N]$ )
2:    $Total = A[1]$                                 ▷ empty prefix not allowed
3:    $Max = A[1]$ 
4:   for  $i = 2$  to  $N$  do
5:      $Total = Total + A[i]$ 
6:     if  $Total > Max$  then
7:        $Max = Total$ 
8:     end if
9:   end for
10:  return  $Max$ 
11: end procedure
```

The values of  $Total$  for each prefix could be stored in another array of size  $N$ , and this could be searched for  $Max$  when it is full. However, it is only ever the

value of the previous total that is needed to calculate the next one, so keeping them all is unnecessary. In this situation it is simpler and cleaner to just update a single variable, although it will not affect the time complexity if you do use auxiliary arrays.

- (b) The key to the  $\Theta(N)$  solution is to define  $s_i$  in terms of a subproblem. This works as follows. The first subarray starting at  $i$  is just  $A[i]$ . All others are  $A[i]$  and some subarray starting at  $i+1$ . So, value of  $s_i$  is either  $A[i]$  or  $A[i] + s_{i+1}$ . So, by working backwards through the array, each  $s_i$  can be calculated from the previous one in constant time, and the following algorithm calculates the maximum sum.

```

1: procedure MAXSUM( $A = [A_1, \dots, A_N]$ )
2:    $Max = A[N]$ 
3:    $S = A[N]$  ▷ max sum starting at  $i$ 
4:   for  $i = N - 1$  to  $1$  do
5:     if  $S > 0$  then
6:        $S = S + A[i]$ 
7:     else
8:        $S = A[i]$ 
9:     end if
10:    if  $S > Max$  then
11:       $Max = S$ 
12:    end if
13:  end for
14:  return  $Max$ 
15: end procedure

```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

As before, there is no need to fill another array with the  $s_i$  values, although it will not affect the time complexity if you do.