

COMP1511 PROGRAMMING FUNDAMENTALS

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

LECTURE 8

Recap 2D arrays and Strings

ON MONDAY...

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

LAST LECTURE...

- Went back to reinforce 1D arrays
- Looked at 2D arrays (which make up a grid and allow us to do some pretty cool stuff)

THIS LECTURE...

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

TODAY

- Revisiting scanf() and EOF
- Recap of 2D arrays
- Strings!
- Command line arguments if there is time

“

WHERE IS THE CODE?

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Live lecture code can be found here:



[HTTPS://CGI.CSE.UNSW.EDU.AU/~CS1511/23T1/LIVE/WEEK04/](https://cgi.cse.unsw.edu.au/~cs1511/23T1/LIVE/WEEK04/)

ARRAY OF ARRAYS

A RECAP

For example, let's say we declare an array of arrays:

```
int array[3][4];
```

Visually it looks like this and showing how to access each of the grid elements:

Assignment Project Exam Help

	col 0	col 1	col 2	col 3
row 0	array[0][0]	array[0][1]	array[0][2]	array[0][3]
row 1	array[1][0]	array[1][1]	array[1][2]	array[1][3]
row 2	array[2][0]	array[2][1]	array[2][2]	array[2][3]

PROBLEM TIME

Going back to the question we finished with on Monday, let's go back and move things out into functions...

2D_arrays.c

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

PROBLEM TIME

Write a program in C to find the sum of the right diagonals of a 2D array of numbers. (Assume 2D array will always be square)

diagonals.c

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

	col 0	col 1	col 2
row 0	array[0][0]	array[0][1]	array[0][2]
row 1	array[1][0]	array[1][1]	array[1][2]
row 2	array[2][0]	array[2][1]	array[2][2]

PROBLEM TIME

Now a bit harder, what about the left diagonals?

diagonals.c

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

	col 0	col 1	col 2
row 0	array[0][0]	array[0][1]	array[0][2]
row 1	array[1][0]	array[1][1]	array[1][2]
row 2	array[2][0]	array[2][1]	array[2][2]

BREAK TIME

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs




BACK AND FORTH

You're a very lazy person ...

In the cellar of your house, there are three power switches in the off position, but only one of these switches controls the lightbulb in the attic.

You can't see the lightbulb in the attic from the cellar, and yet you want be able to work out which switch is the one that's connected to this bulb from just making one trip up to the attic.

How will you go about it?



STRINGS

WHAT ARE THEY?

- Strings are a collection of characters that are joined together
 - an array of characters!
- There is one very special thing about strings in C - it is an array of characters that finishes with a
 - This symbol is called a null terminating character
- It is always located at the end of an array, therefore an array has to always be able to accomodate this character
- It is not displayed as part of the string
- It is a placeholder to indicate that this array of characters is a string
- It is very useful to know when our string has come to an end, when we loop through the array of characters

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

HOW DO WE DECLARE A STRING?

WHAT DOES IT LOOK LIKE VISUALLY?


- Because strings are an array of characters, the array type is char.
- To declare and initialise a string, you can use two methods:

//the more convenient way

`char word[] = "hello";`

//this is the same as '\0':

`char word[] = {'h', 'e', 'l', 'l', 'o', '\0'};`



HELPFUL LIBRARY FUNCTIONS FOR STRINGS

FGETS()

There is a useful function for reading strings:

fgets(array[], length, stream)

The function needs three inputs:

- array[] - the array that the string will be stored into
- length - the number of characters that will be read in

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- stream - this is where this string is coming from - you don't have to worry about this one, in your case, it will always be stdin (the input will always be from terminal)

// Declare an array where you will place the string that you read from somewhere

```
char array[MAX_LENGTH];
```

// Read in the string into array of length MAX_LENGTH from terminal input

```
fgets(array, MAX_LENGTH, stdin)
```

HOW DO I KEEP READING STUFF IN OVER AND OVER AGAIN?

Using the **NULL** keyword, you can continuously get string input from terminal until Ctrl+D is pressed


- `fgets()` stops reading when either length-1 characters are read, newline character is read or an end of file is reached, whichever comes first

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
1 #include <stdio.h>
2
3 #define MAX_LENGTH 15
4
5 int main(void) {
6     // Declare an array where you will place the string
7     char array[MAX_LENGTH];
8
9     printf("Type in a string to echo: ");
10    // Read in the string into the array until Ctrl+D is
11    // pressed, which is indicated by the NULL keyword
12    while (fgets(array, MAX_LENGTH, stdin) != NULL) {
13        printf("The string is: \n");
14        printf("%s", array);
15        printf("Type in a string to echo: ");
16    }
17    return 0;
18 }
```



HELPFUL LIBRARY FUNCTIONS FOR STRINGS

FPUTS()

Another useful function to output strings:

fputs(array[], stream)

The function needs two inputs:

- array[] - the array that the string is be stored in
- stream - this is where this string will be output to, you

don't have to worry about this one, in your case, it will always be stdout (the output will always be in terminal)

// Declare an array where you will place the string that you read from somewhere

char array[MAX_LENGTH];

// Read in the string into array of length MAX_LENGTH from terminal input

fgets(array, MAX_LENGTH, stdin)

//Output the array now

fputs(array, stdout)

SOME OTHER INTERESTING STRING FUNCTIONS

<STRING.H> STANDARD LIBRARY

CHECK OUT THE REST OF THE FUNCTIONS:
[HTTPS://WWW.TUTORIALSPOINT.COM/
C_STANDARD_LIBRARY/STRING_H.HTM](https://www.tutorialspoint.com/C_standard_library/string_h.htm)



Some other useful functions for strings:

- **strlen()** gives us the length of the string (excluding the '\0')
- **strcpy()** copy the contents of one string to another
- **strcat()** attach one string to the end of another (concatenate)

<https://tutorcs.com>

- **strcmp()** compare two strings

WeChat: cstutorcs

- **strchr()** find the first or last occurrence of a character

USING SOME OF THESE FUNCTIONS ON STRINGS

```
1 #include <stdio.h>
2 #include <string.h>
3
4 #define MAX_LENGTH 15
5
6 int main(void) {
7     // Declare an array
8     char word_array[MAX_LENGTH];
9
10    // Example using strcpy to copy from one string
11    // to another (destination, source)
12    strcpy(word_array, "Jax");
13    printf("%s\n", word_array);
14
15    // Example using strlen to find string length
16    // returns the int length NOT including '\0'
17    int length = strlen("Sasha");\n
18    printf("The size of string 'Sasha' is %d chars\n", length);
19
20    // Example using strcmp to compare two strings character
21    // by character - function will return:
22    // 0 = two strings are equal
23    // other int if not the same
24
25    int compare_string = strcmp("Jax", "Juno");
26    printf("The two strings are the same: %d\n", compare_string);
27
28    compare_string = strcmp(word_array, "Jax");
29    printf("The two strings are the same: %d\n", compare_string);
30    return 0;
31 };
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: pstutorcs

COMMAND LINE ARGUMENTS

WHAT ARE THEY?

- So far, we have only given input to our program after we have started running that program (using scanf())
- This means our `int main(void) {}` function has always been void as input
- Command line arguments allow us to give inputs to our

Assignment Project Exam Help

<https://tutorcs.com>

example:

WeChat: cstutores

```
avas605@vx5:~$ gcc test6.c -o test6
avas605@vx5:~$ ./test6 argument2 argument3 argument4
```

TIME TO CHANGE THAT VOID

LET'S GET OUR MAIN FUNCTION TO ACCEPT SOME INPUT PARAMETERS

- In order to change your main function to accept command line arguments on first running, you need to change the void input:

```
int main(int argc, char *argv[]) {}
```

Assignment Project Exam Help

- <https://tutorcs.com>
[WeChat: cstutorcs](#)
int argc = is a counter for how many command line arguments you have (including the program name)
- char *argv[] = is an array of the different command line arguments (separated by a spaces). Each command line argument is a string (an array of char)

AN EXAMPLE

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
1 #include <stdio.h>
2
3 int main (int argc, char *argv[]) {
4     printf("There are %d command line arguments in this program\n", argc);
5
6     //argv[0] is always the program name
7     printf("The program name is %s (argv[0])\n", argv[0]);
8
9     // What about the other command line arguments? Let's loop through
10    // the array and print them all out!
11    for (int i = 0; i < argc; i++) {
12        printf("The command line argument at index %d"
13              "argv[%d] is %s\n", i, i, argv[i]);
14    }
15
16    return 0;
17 }
```

```
avas605@vx02:~$ gcc argv_demo.c -o argv_demo
avas605@vx02:~$ ./argv_demo We are almost half way through this term!
There are 9 command line arguments in this program
The program name is ./argv_demo (argv[0])
The command line argument at index 0argv[0] is ./argv_demo
The command line argument at index 1argv[1] is We
The command line argument at index 2argv[2] is are
The command line argument at index 3argv[3] is almost
The command line argument at index 4argv[4] is half
The command line argument at index 5argv[5] is way
The command line argument at index 6argv[6] is through
The command line argument at index 7argv[7] is this
The command line argument at index 8argv[8] is term!
```

WHAT IF YOU WANT NUMBERS AND NOT STRINGS?

REMEMBER THAT
EACH COMMAND
LINE ARGUMENT
IS A STRING

- You want numbers, if you want to use your command line arguments to perform calculations
- There is a useful function that converts your strings to numbers:

atoi() in the standard library: <stdlib.h>

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

WHAT IF YOU WANT NUMBERS AND NOT STRINGS?

REMEMBER THAT
EACH COMMAND
LINE ARGUMENT
IS A STRING

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 int main (int argc, char *argv[]) {
5     // Remember that the command line arguments are all strings, so if you
6     // need to do mathematical operations, you will need to convert them
7     // to numbers
8     // You can do this with a really handy function atoi() in the stdlib.h library!
9
10    // Let's print out all the command line arguments given and then add
11    // them together to give the sum of the command line arguments
12
13    int sum = 0;
14    for (int i = 1; i < argc; i++) {
15        printf("The command line argument at index %d (argv[%d]) is %d\n",
16              i, i, atoi(argv[i]));
17        sum = sum + atoi(argv[i]);
18    }
19    printf("The sum of the arguments is %d\n", sum);
20    return 0;
21 }
22 }
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
avas605@vx02:~$ gcc atoi_demo.c -o atoi_demo
```

```
avas605@vx02:~$ ./atoi_demo 3 4 5 6 7
```

```
The command line argument at index 1 (argv[1]) is 3
```

```
The command line argument at index 2 (argv[2]) is 4
```

```
The command line argument at index 3 (argv[3]) is 5
```

```
The command line argument at index 4 (argv[4]) is 6
```

```
The command line argument at index 5 (argv[5]) is 7
```

```
The sum of the arguments is 25
```

CODE TIME

:)

- Read in two numbers from the command line arguments and state whether the two numbers are the same or not

compare_numbers.c

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: [cstutorcs](#)

- Let's make it a bit more interesting, read in two strings from the command line arguments and compare the strings to say whether they are the same or not!

compare_strings.c



Assignment Project Exam Help

<https://tutores.com>
WeChat: cstutores

Feedback please!

I value your feedback and use to pace the lectures and improve your overall learning experience. If you have any feedback from today's lecture, please follow the link below. Please remember to keep your feedback constructive, so I can action it and improve the learning experience.

<https://www.menti.com/alafjm9rxpmy>

WHAT DID WE LEARN TODAY?

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: [tutorcs](#)

2D ARRAY RECAP

2D_array.c
diagonals.c

STRINGS

echo.c
string.c

COMMAND LINE ARGUMENTS

argv_demo.c
atoi_demo.c
compare_numbers.c
compare_strings.c

REACH OUT



CONTENT RELATED QUESTIONS

Check out the forum

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



ADMIN QUESTIONS

cs1511@unsw.edu.au