

程序代写代做 CS编程辅导



Normalisation – Part 3

WeChat: cstutorcs
Summary and Discussion
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导 Summary of Normal Forms



- 1NF, 3NF and BCNF are used in practice. Other normal forms are rarely used.

1NF: only atomic values for attributes
(part of the definition for the relational data model);

2NF: an intermediate result in the history of database design theory;

3NF: lossless and dependencies can be preserved;

BCNF: lossless but dependencies may not be preserved.

- 3NF can only **minimise (not necessarily eliminate) redundancy**. So a relation schema in 3NF may still have update anomalies.
- A relation schema in BCNF **eliminates redundancy**.

程序代写代做 CS编程辅导 Why Denormalisation?



- **Do we need to normalise relation schemas in all cases** when designing a relational database?
- The normalisation process **may degrade performance** when data are frequently queried. **WeChat: cstutorcs**
- Since relation schemas are decomposed into many smaller ones after normalisation, queries need to **join many relations together** in order to return the results. **Email: tutorcs@163.com**
- Unfortunately, **join operation is very expensive**. **QQ: 749389476**
- When data is **more frequently queried rather than being updated** (e.g., data warehousing system), a weaker normal form is desired (i.e., **denormalisation**). **https://tutorcs.com**

程序代写代做 CS编程辅导 Denormalisation



- **Denormalisation** is a process that
 - happens after the normalisation process,
 - is often performed during the physical design stage, and
 - reduces the number of relations that need to be joined for certain queries.

Assignment Project Exam Help

- We need to distinguish:
 - **Unnormalised** – there is no systematic design.
 - **Normalised** – redundancy is reduced after a systematic design (to minimise data inconsistencies).
 - **Denormalised** – redundancy is introduced after analysing the normalised design (to improve efficiency of queries)

程序代写代做 CS编程辅导
Trade-offs



WeChat: cstutores

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

- A good database design is to **find a balance** between desired properties, then normalise/denormalise relations to a desired degree.

程序代写代做 CS编程辅导

Trade-offs – Data Redundancy vs. Query Efficiency

- Normalisation: **No Data Redundancy but No Efficient Query Processing**
- Data redundancies are introduced in the following relations.



STUDENT		
Name	<u>StudentID</u>	DoB
Tom	123456	25/01/1988
Michael	123458	21/04/1985

COURSE	
<u>CourseNo</u>	Unit
COMP2400	6
COMP8740	12

Assignment Project Exam Help

ENROL		
<u>StudentID</u>	<u>CourseNo</u>	<u>Semester</u>
123456	COMP2400	2010 S2
123456	COMP8740	2011 S2
123458	COMP2400	2009 S2

- However, the query for “list the names of students who enrolled in a course with 6 units” requires 2 join operations.

```
SELECT Name, CourseNo FROM ENROL e, COURSE c, STUDENT s WHERE
e.StudentID=s.StudentID and e.CourseNo=c.CourseNo and c.Unit=6;
```


程序代写代做 CS编程辅导

Trade-offs – Data Redundancy vs. Query Efficiency



- Denormalisation: **Data Redundancy but Efficient Query Processing**
- If a student enrolled in a course, then the name and DoB of this student need to be stored repeatedly 15 times in ENROLMENT.

WeChat: cstutorcs

ENROLMENT					
Name	StudentID	DoB	CourseNo	Semester	Unit
Tom	123456	25/01/1988	COMP2400	2010 S2	6
Tom	123456	25/01/1988	COMP8740	2011 S2	12
Michael	123458	21/04/1985	COMP2400	2009 S2	6

QQ: 749389476

- However, the query for “list the names of students who enrolled a course with 6 units” can be processed efficiently (no join needed).

https://tutorcs.com

```
SELECT Name, CourseNo FROM ENROLMENT WHERE Unit=6;
```

程序代写代做 CS编程辅导 Discussion



- Both normalisation and denormalisation are useful in database design.
- Normalisation**: obtain database schema avoiding redundancies and data inconsistencies.
- Denormalisation**: join normalized relation schemata for the sake of better query processing.
- Some problems of (de-)normalisation:
 - FDs **cannot handle null values**.
 - To apply normalisation, FDs must be **fully specified**.
 - The algorithms for normalisation **are not deterministic**, leading to different decompositions.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>