



Australian
National
University

程序代写代做 CS编程辅导



— Part 3

WeChat: cstutorcs
Data Manipulation Language
(Simple SQL Queries)
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



程序代写代做 CS编程辅导

Simple SQL Queries



- SQL provides the **SELECT** statement for retrieving data from a database.
- The **SELECT** statement has the following basic form:

```
SELECT attribute_list
FROM table_list
[WHERE condition]
[GROUP BY attribute_list [HAVING group_condition]]
[ORDER BY attribute_list];
```

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

Note:

- Only **SELECT** and **FROM** are mandatory.
- The symbol ***** means all the attributes.
- Attribute names may be qualified with the table name (required, if attribute-names are not unique).
- Attribute and table names can be given an alias.
- **DISTINCT** is used for removing duplicate tuples in the query result.

QQ: 749389476

http://tutorcs.com



程序代写代做 CS编程辅导 SQL Queries – Select Clause



ENROL				
StudentID	CourseNo	Semester	Status	EnrolDate
456	COMP2600	2016 S2	active	25/02/2016
458	COMP1130	2016 S1	active	25/02/2016
456	COMP2400	2016 S2	active	09/03/2016

SELECT * FROM ENROL

StudentID	CourseNo	Semester	Status	EnrolDate
456	COMP2600	2016 S2	active	25/02/2016
458	COMP1130	2016 S1	active	25/02/2016
456	COMP2400	2016 S2	active	09/03/2016

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

https://tutorcs.com



SQL Queries – Select Clause



ENROL				
StudentID		Semester	Status	EnrolDate
456	C	2016 S2	active	25/02/2016
458	COMP1130	2016 S1	active	25/02/2016
456	COMP2100	2016 S2	active	09/03/2016

WEChat: cstutores

Assignment Project Exam Help

```
SELECT ENROL.StudentID, Semester FROM ENROL;
```

Email: tutores@163.com

```
SELECT e.StudentID as SID, e.Semester FROM ENROL e;
```

QQ: 749389476

```
SELECT DISTINCT StudentID, Semester FROM ENROL;
```

<https://tutores.com>

StudentID	Semester
456	2016 S2
458	2016 S1
456	2016 S2

SID	Semester
456	2016 S2
458	2016 S1
456	2016 S2

StudentID	Semester
456	2016 S2
458	2016 S1



SQL Queries – Where Clause



- Unspecified WHERE-clause has no condition.
 - all tuples of a relation in the FROM-clause are selected.
 - if multiple relations are specified in the FROM-clause without join conditions, the Cartesian product of relations is selected (**be careful**).

WeChat: cstutorcs

- The condition in the WHERE-clause can be simple or complicated.

Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
SELECT * FROM STUDENT;
SELECT * FROM STUDENT, COURSE;
SELECT * FROM STUDENT WHERE StudentID BETWEEN 100 AND 500;
SELECT * FROM STUDENT WHERE Email is NOT NULL;
SELECT * FROM STUDENT WHERE Email like '%@gmail.com';

- **Question:** Assume that we have 1000 tuples in STUDENT and 100 tuples in COURSE. How many tuples we will have in the results of the first two queries?
- **Answer:** 1st query result: 1000 tuples; 2nd query result: 100000 tuples.



SQL Queries – Group By Clause



- **GROUP BY** *attribute_list* Examples for each value combination in the *attribute_list*.
- Aggregate functions can be applied to aggregate a group of attribute values into a single value, e.g.,
 - **COUNT** returns the total number of argument values
 - **AVG** returns the average of argument values
 - **MIN** returns the minimum value of the arguments
 - **MAX** returns the maximum value of the arguments
 - **SUM** returns the sum of the argument values
- We can use **HAVING** *condition* to add the condition on the groups.

程序代写代做 CS编程辅导

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

https://tutorcs.com



SQL Queries – Group By Clause



- List the total number of courses, the sum of the units of courses, the minimum unit in COURSE

COURSE		
<u>No</u>	Cname	Unit
COMP1130	Introduction to Advanced Computing I	6
COMP2400	Relational Databases	6
COMP3600	Algorithms	4

SELECT COUNT(*), SUM(unit), MIN(unit)
FROM COURSE;

- The query result may look like:

COUNT	SUM	MIN
3	16	4



SQL Queries – Group By Clause



- List each course offered in semester 2 2016 together with the number of students who have enrolled in the course

```
SELECT e.CourseNo, COUNT(*) AS NumberOfStudents
FROM ENROL e
```

```
WHERE e.Semester = '2016 S2'
```

```
GROUP BY e.CourseNo;
```

Email: tutorcs@163.com

ENROL				
StudentID	CourseNo	Semester	Status	EnrolDate
458	COMP2400	2016 S2	active	25/02/2016
458	COMP1130	2016 S1	active	25/02/2016
456	COMP2400	2016 S2	active	25/02/2016
...



SQL Queries – Group By Clause



- List each course offered in semester 2 2016 together with the number of students who have enrolled in the course

```
SELECT e.CourseNo, COUNT(*) AS NumberOfStudents
FROM ENROL e
WHERE e.Semester = '2016 S2'
GROUP BY e.CourseNo;
```

- The query result may look like:

CourseNo	NumberOfStudents
COMP2400	120
COMP2000	100
COMP1130	150
...	...



SQL Queries – Having Clause



- List each course offered in semester 2 2016 together with the number of students that is at least 120

```
SELECT e.CourseNo, COUNT(*) AS NumberOfStudents
FROM ENROLL e
WHERE e.Semester = '2016 S2'
GROUP BY e.CourseNo
HAVING COUNT(*) >= 120 ;
```

- The query result may look like:

CourseNo	NumberOfStudents
COMP2100	120
COMP1130	150
...	...



SQL Queries – Order By Clause

程序代写代做 CS编程辅导

- The **ORDER BY** clause is used to sort the tuples in a query result.
 - ASC indicates ascending order (default).
 - DESC indicates descending order.
- We can sort the previous result by



```
SELECT e.CourseNo, COUNT(*) AS NumberOfStudents
FROM ENROL e
WHERE e.Semester = '2016 S2'
GROUP BY e.CourseNo
ORDER BY NumberOfStudents DESC
```

WeChat: cstutores

Assignment Project Exam Help

Email: tutores@163.com

- This would return all tuples sorted by the number of enrolled students in descending order.

QQ: 749389476

<https://tutores.com>

CourseNo	NumberOfStudents
COMP1130	150
COMP2400	120
COMP2600	100
...	...