



程序代写代做 CS编程辅导



## Relational Algebra (Part 2)

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



## 程序代写代做 CS 编程辅导

# Summary of Relational Operators

Operator	QR Code	Meaning
Selection		choose rows
Projection	$\pi_{A_1, \dots, A_n}(R)$	choose columns
Union	$R_1 \cup R_2$	
Intersection	$R_1 \cap R_2$	set operations
Difference	$R_1 - R_2$	Assignment Project Exam Help Email: tutorcs@163.com
Cartesian product	$R_1 \times R_2$	
Join	QQ: 749389476	combine tables
Natural-join	$R_1 \bowtie R_2$	<a href="https://tutorcs.com">https://tutorcs.com</a>
Renaming	$\rho_{R'}(A_1, \dots, A_n)(R)$ $\rho_{R'}(R)$ $\rho_{(A_1, \dots, A_n)}(R)$	rename relation and attributes



程序代写代做 CS 编程辅导

## A Complete Set of Relational Operators



- The following six operators constitute **a complete set**:

- **selection**  $\sigma$ ;

WeChat: cstutorcs

- **projection**  $\pi$ ;

Assignment Project Exam Help

- **renaming**  $\rho$ ;

Email: tutorcs@163.com

- **union**  $\cup$ ;

QQ: 749389476

- **difference**  $-$ ;

<https://tutorcs.com>

- **Cartesian product**



程序代写代做 CS 编程辅导

## A Complete Set of Relational Operators



- Six operators (i.e., selection  $\sigma$ , projection  $\pi$ , renaming  $\rho$ , union  $\cup$ , difference  $-$  and Cartesian product  $\times$ ) constitute **a complete set**.
- It means that the other RA operators like **intersection** and **join** are **not necessary** and can be expressed by these six operators.

WeChat: cstutorcs  
Assignment Project Exam Help

- **join:**  $R_1 \bowtie_{\varphi} R_2 = \sigma_{\varphi}(R_1 \times R_2)$
- **intersection:**  $R_1 \cap R_2 = R_1 - (R_1 - R_2)$

Email: tutorcs@163.com  
QQ: 749389476

- Hence, **intersection** and **join** do not increase the expressive power of RA.
- Nonetheless it is important to include **intersection** and **join** because they are convenient to use and commonly applied in database applications.

<https://tutorcs.com>



## 程序代写代做 CS 编程辅导 Relational Algebra Queries



- The output of each RA operation is a relation, which can be used again as the input for another operation.
- RA operations **can be nested to arbitrary depth** for expressing complex queries, as in arithmetic.

WeChat: cstutorcs

- Parentheses and precedence rules define the order of evaluation: from highest to lowest: { $\sigma$ ,  $\pi$ ,  $\rho$ }, { $\times$ ,  $\bowtie$ }, { $\cap$ }, { $\cup$ ,  $\Delta$ }, { $\setminus$ ,  $\Theta$ }
  - Operators with the same precedence are evaluated from left to right.
  - Use brackets if you are not sure.
- Assignment Project Exam Help
- Email: [tutorcs@163.com](mailto:tutorcs@163.com)
- QQ: 749389476
- <https://tutorcs.com>
- A **query** in RA is a sequence of RA operations and each RA operation takes one or two relations as its input and produces one relation as its output.
  - Different from SQL, RA considers **relations as sets** (not **multisets** as in SQL). Hence, relations produced by an RA operation **have no duplicate tuples**.



## 程序代写代做 CS 编程辅导 Hints for Writing RA Queries



- ① Firstly, identify which relations need to be involved, while ignoring the rest.
- ② Then break the answer into steps, considering intermediate relations, i.e., queries may be expressed as **a sequence of assignment statements**.

**Example:**  $R := \pi_{HTeam, GTeam}(\sigma_{HScore = 10}(I(HTeam, HScore, GScore, GTeam)) \text{ (SOCCER)})$

- Use good names for intermediate relations:
- Keep track of attributes you have at each step.

- ③ When combining relations, check attribute names and make sure that:

- attributes that should match are to match.
- attributes that shouldn't match are not to match.

<https://tutorcs.com>

- ④ When using set operations, make sure that two relations of an operation have the same type (i.e., **type compatibility**).



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Self Join)

- Given the following relations:



STUDENT { StudentID, Name, DoB }

- Query 1:** Find **pairs of** students who have the same birthday. Show their names.

WeChat: cstutorcs

Assignment Project Exam Help

STUDENT		
StudentID	Name	DoB
457	Lisa	18-Oct-1993
458	Mike	16-May-1990
459	Peter	18-Oct-1993

Email: tutorcs@163.com  
QQ: 749389476  
<https://tutorcs.com>



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Self Join)

- Given the following relations, answer the following questions:



StudentID, Name, DoB}

- Query 1:** Find **pairs of** students who have the same birthday. Show their names.

WeChat: cstutorcs

$\pi_{R_1.\text{Name}, R_2.\text{Name}}(\sigma_{R_1.\text{StudentID} < R_2.\text{StudentID}}(\rho_{R_1 \times R_2}(R_1 \sqcap R_2)))$

Email: tutorcs@163.com

SELECT  $R_1.\text{name}$ ,  $R_2.\text{name}$

FROM Student AS  $R_1$ , Student AS  $R_2$

WHERE  $R_1.\text{DoB} = R_2.\text{DoB}$  AND  $R_1.\text{StudentID} < R_2.\text{StudentID}$ ;

<https://tutorcs.com>

- Why do we need  $\sigma_{R_1.\text{StudentID} < R_2.\text{StudentID}}$  in the above query?
- Why do we need to use renaming in the above query?



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Self Join)



- Given the following relations schema:

$\text{STUDENT} = \{\text{StudentID}, \text{Name}, \text{DoB}\}$

- Query 1:** Find pairs of students who have the same birthday. Show their names.

Assignment Project Exam Help

Two different solutions:

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

(1).  $\pi_{R_1.\text{Name}, R_2.\text{Name}}(\sigma_{R_1.\text{StudentID} < R_2.\text{StudentID}}(\sigma_{R_1.\text{DoB} = R_2.\text{DoB}}(\rho_{R_1}(\text{STUDENT}) \times \rho_{R_2}(\text{STUDENT}))))$

(2).  $\pi_{\text{Name}, \text{Name}'}(\sigma_{\text{StudentID} < \text{StudentID}'}(\text{STUDENT} \bowtie \rho_S(\text{StudentID}', \text{Name}', \text{DoB})(\text{STUDENT})))$

<https://tutorcs.com>



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Self Join)



- **Query 1:** Find **pairs** who have the same birthday. Show their names.

(1).  $\pi_{R_1.Name, R_2.Name}(\sigma_{R_1.StudentID < R_2.StudentID}(\sigma_{R_1.DoB = R_2.DoB}(\rho_{R_1}(\text{STUDENT}) \bowtie \rho_{R_2}(\text{STUDENT})))$

(2).  $\pi_{Name, Name'}(\sigma_{StudentID < StudentID'}(\text{STUDENT} \bowtie \rho_S(StudentID', Name', DoB)(\text{STUDENT}))$

- If evaluating our queries over the following relation, what will be the result?

STUDENT		
StudentID	Name	DoB
457	isa	18-Oct-1993
458	Mike	16-May-1990
459	Peter	18-Oct-1993



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Self Join)

### ● Query 1 (solution 1)

$\rho_{R_1}(\text{STUDENT}) \times \rho_{R_2}(\text{STUDENT}) \rightarrow \sigma_{R_1.\text{StudentID} < R_2.\text{StudentID}}(\sigma_{R_1.\text{DoB} = R_2.\text{DoB}}(R_1 \times R_2).\text{Name})$ .



STUDENT		
StudentID	Name	DoB
457	Lisa	18-Oct-1993
458	Mike	16-May-1990
459	Peter	18-Oct-1993

Assignment Project Exam Help

$\rho_{R_1}(\text{STUDENT}) \times \rho_{R_2}(\text{STUDENT})$

$R_1.\text{StudentID}$	$R_1.\text{Name}$	$R_1.\text{DoB}$	$R_2.\text{StudentID}$	$R_2.\text{Name}$	$R_2.\text{DoB}$
457	Lisa	18-Oct-1993	457	Lisa	18-Oct-1993
457	Lisa	18-Oct-1993	458	Mike	16-May-1990
457	Lisa	18-Oct-1993	458	Peter	18-Oct-1993
458	Mike	16-May-1990	457	Lisa	18-Oct-1993
458	Mike	16-May-1990	458	Mike	16-May-1990
458	Mike	16-May-1990	458	Peter	18-Oct-1993
458	Peter	18-Oct-1993	457	Lisa	18-Oct-1993
458	Peter	18-Oct-1993	458	Mike	16-May-1990
458	Peter	18-Oct-1993	458	Peter	18-Oct-1993

QQ: 749389476

<https://tutorcs.com>



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Self Join)

### ● Query 1 (solution 1)

$\rho_{R_1}(\text{STUDENT}) \times \rho_{R_2}(\text{STUDENT}) \rightarrow \pi_{R_1.\text{Name}, R_2.\text{Name}}(\sigma_{R_1.\text{StudentID} < R_2.\text{StudentID}}(\sigma_{R_1.\text{DoB} = R_2.\text{DoB}}(R_1 \times R_2)))$ .



STUDENT		
StudentID	Name	DoB
457	Lisa	18-Oct-1993
458	Mike	16-May-1990
459	Peter	18-Oct-1993

WeChat: cstutorcs  
Assignment Project Exam Help

$$R' = \sigma_{R_1.\text{DoB} = R_2.\text{DoB}}(\rho_{R_1}(\text{STUDENT}) \times \rho_{R_2}(\text{STUDENT}))$$

$R_1.\text{StudentID}$	$R_1.\text{Name}$	$R_1.\text{DoB}$	$R_2.\text{StudentID}$	$R_2.\text{Name}$	$R_2.\text{DoB}$
457	Lisa	18-Oct-1993	457	Lisa	18-Oct-1993
457	Lisa	18-Oct-1993	459	Peter	18-Oct-1993
458	Mike	16-May-1990	458	Mike	16-May-1990
459	Peter	18-Oct-1993	457	Lisa	18-Oct-1993
459	Peter	18-Oct-1993	459	Peter	18-Oct-1993

<https://tutorcs.com>

$$\pi_{R_1.\text{Name}, R_2.\text{Name}}(\sigma_{R_1.\text{StudentID} < R_2.\text{StudentID}}(R'))$$

$R_1.\text{Name}$	$R_2.\text{Name}$
Lisa	Peter



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Self Join)

- Query 1 (solution 2)

$\text{STUDENT} \bowtie \rho_S(\text{StudentID}', \text{Name}', \text{DoB})$



$e' (\sigma_{\text{StudentID} < \text{StudentID}'} ($   
 $, \text{DoB}) (\text{STUDENT}))$ .

STUDENT		
StudentID	Name	DoB
457	Lisa	18-Oct-1993
458	Mike	16-May-1990
459	Peter	18-Oct-1993

WeChat: cstutorcs  
Assignment Project Exam Help

$R' = \text{STUDENT} \bowtie \rho_S(\text{StudentID}', \text{Name}', \text{DoB}) (\text{STUDENT})$

StudentID	Name	DoB	StudentID'	Name'
457	Lisa	18-Oct-1993	459	Peter
459	Peter	18-Oct-1993	457	Lisa
451	Peter	18-Oct-1993	459	Peter
457	Lisa	18-Oct-1993	457	Lisa
458	Mike	16-May-1990	458	Mike

QQ: 749389476  
<https://tutorcs.com>

$\pi_{\text{Name}, \text{Name}'} (\sigma_{\text{StudentID} < \text{StudentID}'} (R'))$

Name	Name'
Lisa	Peter



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Difference 1)

- Given the following relations:



STUDENT { StudentID, Name, DoB }

ENROL = { ENROLID, StudentID, CourseNo, Semester, EnrolDate }

- Query 2:** Which students have **never** enrolled in any course? Show their IDs and names.

WeChat: cstutorcs

STUDENT		
StudentID	Name	DoB
456	Tom	02-Jan-1991
457	Lisa	18-Oct-1993
458	Mike	16-May-1990

Email: tutordes@163.com

QQ: 749389476

Assignment Project Exam Help

ENROL			
StudentID	CourseNo	Semester	EnrolDate
456	COMP2400	2010 S2	02-Jul-2010
458	COMP2400	2010 S2	23-Jun-2010
458	COMP2600	2010 S2	05-Aug-2010

<https://tutorcs.com>



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Difference 1)

- Given the following relations:



Tutor CS

STUDENT = {StudentID, Name, DoB}

ENROL = {CourseNo, Semester, EnrolDate}

- Query 2:** Which students have **never** enrolled in any course? Show their IDs and names.

WeChat: cstutorcs

Assignment Project Exam Help

**Hints:**

Email: tutorcs@163.com

(1) All the students

(2) Students who have **never** enrolled in at least one course

<https://tutorcs.com>

**Answer:** Students in **the result (1) but not in the result (2).**



程序代写代做 CS 编程辅导

## RA Queries – Exercises (Difference 1)

- Given the following relations:



STUDENT = {StudentID, Name, DoB}

ENROL = {CourseNo, Semester, EnrolDate}

- Query 2:** Which students have **never** enrolled in any course? Show their IDs and names.

WeChat: cstutorcs

- All the students

Assignment Project Exam Help

$R_1 := \pi_{StudentID}(\text{STUDENT})$

- Students who have enrolled in at least one course

QQ: 749389476

**Answer:** Students in the result (1) but not in the result (2)

$\pi_{StudentID, Name}((R_1 - R_2) \bowtie \text{STUDENT})$



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Difference 1)

- **Query 2:** Which students **never** enrolled in any course? Show their IDs and names.
- If evaluating our query over the following relations, what will be the result?



- $R_1 := \pi_{StudentID}(\text{STUDENT})$
- $R_2 := \pi_{StudentID}(\text{ENROL})$
- $\pi_{StudentID, Name}((R_1 - R_2) \bowtie \text{STUDENT})$

Assignment Project Exam Help

STUDENT		
StudentID	Name	DoB
456	Tom	02-Jan-1991
457	Lisa	18-Oct-1993
458	Mike	16-May-1990

<https://tutores.com>

StudentID	CourseNo	Semester	EnrolDate
456	COMP2400	2010 S2	02-Jul-2010
458	COMP2400	2010 S2	23-Jun-2010
458	COMP2600	2010 S2	05-Aug-2010



程序代写代做 CS 编程辅导

## RA Queries – Exercises (Difference 1)

- **Query 2:** Which students **never** enrolled in any course? Show their IDs and names.
- If evaluating our query over the following relations, what will be the result?



- $R_1 := \pi_{StudentID}(\text{STUDENT})$
- $R_2 := \pi_{StudentID}(\text{ENROL})$
- $\pi_{StudentID, Name}((R_1 - R_2) \bowtie \text{STUDENT})$

Assignment Project Exam Help

$R_1$	$R_2$
StudentID	StudentID
456	456
457	458
458	

Email: [tutores@163.com](mailto:tutores@163.com)

QQ: 749389476

$\pi_{StudentID, Name}((R_1 - R_2) \bowtie \text{STUDENT})$

StudentID	Name
457	Lisa

<https://tutorcs.com>



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Difference 2)

- Given the following relations:



Tutor CS

STUDENT = {StudentID, Name, DoB}

ENROL = {CourseNo, Semester, EnrolDate}

- Query 3:** Which students have **only** enrolled in the course COMP2400?  
Show their IDs and names.

WeChat: cstutorcs

Assignment Project Exam Help

StudentID	Name	DoB
456	Tom	02-Jan-1991
457	Lisa	18-Oct-1993
458	Mike	16-May-1990

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

ENROL

StudentID	CourseNo	Semester	EnrolDate
456	COMP2400	2010 S2	02-Jul-2010
457	COMP2400	2010 S2	08-Jul-2010
458	COMP2400	2010 S2	23-Jun-2010
458	COMP2600	2010 S2	05-Aug-2010

<https://tutorcs.com>



## 程序代写代做 CS 编程辅导 RA Queries – Exercises (Difference 2)

- Given the following relations:  
  
STUDENT = {StudentID, Name, DoB}  
ENROL = {CourseNo, Semester, EnrolDate}
- Query 3:** Which students have **only** enrolled in the course COMP2400?  
Show their IDs and names.  
**WeChat: cstutorcs**

Assignment Project Exam Help

**Hints:**

- (1) Students who have enrolled in the course COMP2400.
- (2) Students who have enrolled in a course but not COMP2400.
- Email: tutorcs@163.com**  
**QQ: 749389476**

<https://tutorcs.com>

**Answer:** Students in **the result (1) but not in the result (2).**



程序代写代做 CS 编程辅导

## RA Queries – Exercises (Difference 2)

- Given the following relations:



STUDENT = {StudentID, Name, DoB}

ENROL = {CourseNo, Semester, EnrolDate}

- Query 3:** Which students have **only** enrolled in the course COMP2400?  
Show their IDs and names.

(1) Students who have enrolled in the course COMP2400.

Assignment Project Exam Help

$R_1 := \pi_{StudentID}(\sigma_{CourseNo='COMP2400'}(ENROL))$

(2) Students who have enrolled in a course but not COMP2400.

$R_2 := \pi_{StudentID}(\sigma_{CourseNo \neq 'COMP2400'}(ENROL))$

**Answer:** Students in the result (1) but not in the result (2).

$\pi_{StudentID, Name}((R_1 - R_2) \bowtie STUDENT) =$

$\pi_{StudentID, Name}((\pi_{StudentID}(\sigma_{CourseNo='COMP2400'}(ENROL)))$

$- \pi_{StudentID}(\sigma_{CourseNo \neq 'COMP2400'}(ENROL))) \bowtie STUDENT)$



程序代写代做 CS 编程辅导

## RA Queries – Exercises (Difference 2)

- **Query 3:** Which student **only** enrolled in the course COMP2400?  
Show their IDs and names.
- If evaluating our query over the following relations, what will be the result?
  - $R_1 := \pi_{StudentID}(\sigma_{CourseNo='COMP2400'}(ENROL))$
  - $R_2 := \pi_{StudentID}(\sigma_{CourseNo \neq 'COMP2400'}(ENROL))$
  - $\pi_{StudentID, Name}((R_1 - R_2) \bowtie STUDENT)$

WeChat: estutorcs

STUDENT		
StudentID	Name	DOB
456	Tom	02-Jan-1991
457	Lisa	18-Oct-1993
458	Mike	16-May-1990

QQ: 749389476

Email: tutorcs@163.com

ENROL			
StudentID	CourseNo	Semester	EnrolDate
456	COMP2400	2010 S2	02-Jul-2010
457	COMP2400	2010 S2	08-Jul-2010
458	COMP2400	2010 S2	23-Jun-2010
458	COMP2600	2010 S2	05-Aug-2010



程序代写代做 CS 编程辅导

## RA Queries – Exercises (Difference 2)

- **Query 3:** Which student **only** enrolled in the course COMP2400?  
Show their IDs and names.
- If evaluating our query on the following relations, what will be the result?
  - $R_1 := \pi_{StudentID}(\sigma_{CourseNo = 'COMP2400'}(ENROL))$
  - $R_2 := \pi_{StudentID}(\sigma_{CourseNo \neq 'COMP2400'}(ENROL))$
  - $\pi_{StudentID, Name}((R_1 - R_2) \bowtie STUDENT)$

Assignment Project Exam Help

StudentID
456
457
458

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

$\pi_{StudentID, Name}((R_1 - R_2) \bowtie STUDENT)$

StudentID	Name
456	Tom
457	Lisa

<https://tutorcs.com>



## 程序代写代做 CS 编程辅导 More Hints for Writing RA Queries



- Pay attention to keywords like **not, never, only, always, exactly**, etc. which often indicates the usage of **difference** in the corresponding RA queries.

- To show “never”: **WeChat: cstutorcs**

- Find all the (combinations of) tuples that are involved.

**Assignment Project Exam Help**

- Use difference to subtract those that have occurred.

**Email: tutorcs@163.com**

- To show “only” and “always”:

**QQ: 749389476**

- Find all the (combinations of) tuples that are involved.

**https://tutorcs.com**

- Use difference to subtract those that didn't always occur.



程序代写代做 CS 编程辅导

## Equivalence of RA and SQL Queries (1)



- Each RA query can be written in SQL, or vice versa.

- Selection:**  $\sigma_{\varphi}(R)$  corresponds to

SELECT DISTINCT \* FROM R WHERE  $\varphi$ ;

Assignment Project Exam Help

- Projection:**  $\pi_{A_1, \dots, A_n}(R)$  corresponds to

SELECT DISTINCT  $A_1, \dots, A_n$  FROM R;

- Renaming:**  $\rho_{S(B_1, \dots, B_n)}(R)$  (With attributes  $A_1, \dots, A_n$  in  $R$ ) corresponds to

<https://tutorcs.com>

SELECT  $A_1$  AS  $B_1, \dots, A_n$  AS  $B_n$  FROM  $R$  AS  $S$ ;



程序代写代做 CS 编程辅导

## Equivalence of RA and SQL Queries (2)



- **Union:**  $R_1 \cup R_2$  corresponds to

```
SELECT * FROM R1 UNION SELECT * FROM R2
```

- **Intersection:**  $R_1 \cap R_2$  corresponds to

WeChat: cstutorcs

```
SELECT * FROM R1 INTERSECT SELECT * FROM R2
```

- **Difference:**  $R_1 - R_2$  (with attributes  $A_1, \dots, A_n$ ) corresponds to

```
SELECT * FROM R1 EXCEPT SELECT * FROM R2
```

Email: tutorcs@163.com

```
SELECT DISTINCT * FROM R1 WHERE NOT EXISTS
```

QQ: 749389476

```
(SELECT * FROM R2
```

WHERE  $R_1.A_1=R_2.A_1$  AND ... AND  $R_1.A_n=R_2.A_n$ )

SQL eliminates duplicate tuples in the resulting relations of set operations UNION, INTERSECT and EXCEPT.



程序代写代做 CS 编程辅导

## Equivalence of RA and SQL Queries (3)



- **Cartesian Product:**  $R_1 \times R_2$  corresponds to

SELECT \* FROM  $R_1$ ,  $R_2$ ;

WeChat: cstutorcs

- **Join:**  $R_1 \bowtie_{\varphi} R_2$  corresponds to

Assignment Project Exam Help  
SELECT DISTINCT \* FROM  $R_1$  INNER JOIN  $R_2$  ON  $\varphi$ ;

( $\varphi$  may contain  $=, <, \leq, >, \geq, \neq$ )

- **Natural-Join:**  $R_1 \bowtie R_2$  corresponds to

QQ: 749389476

SELECT DISTINCT \* FROM  $R_1$  NATURAL JOIN  $R_2$ ;

<https://tutorcs.com>

Outer joins are not considered in the traditional relational algebra, as well as aggregation.



# 程序代写代做 CS编程辅导

## Summary



- RA is a **procedural language** defined in the relational model.

An RA query itself suggests a procedure for constructing the result (i.e., implement the query)

WeChat: cstutorcs

- RA is **not used as a query language by users**

Assignment Project Exam Help

- RA is **used for the internal representation and processing of SQL queries** in relational DBMSs, which is a basis of query optimisation techniques.

Email: [tutors@163.com](mailto:tutors@163.com)  
QQ: 749389476

- Thus, to understand how SQL queries are processed and how they can be optimised, we **first need to understand relational algebra**.

<https://tutorcs.com>