



程序代写
作业
CS编程辅导



COMP4121 Advanced Algorithms

WeChat: [estudious](#)

Assignment Project Exam Help
Aleks Ignjatović
Email: tutorcs@163.com

School of Computer Science and Engineering
University of New South Wales Sydney

The Hidden Markov Models and the Viterbi Algorithm and its applications
<https://tutorcs.com>

The Problem of Speech Recognition

程序代写代做 CS编程辅导

We start with an example, the problem of speech recognition.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

程序代写代做 CS编程辅导

We start with an example, the problem of speech recognition.

- A **phoneme** is an “element” or “article” of human speech, so to speak.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

程序代写代做 CS编程辅导

We start with an example, the problem of speech recognition.

- A **phoneme** is an “elementary article” of human speech, so to speak.
- Spoken words of a particular language are understood by a listener by parsing them into a sequence of phonemes.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

程序代写代做 CS编程辅导

We start with an example, the problem of speech recognition.

- A **phoneme** is an “elementary article” of human speech, so to speak.
- Spoken words of a particular language are understood by a listener by parsing them into a sequence of phonemes.
- There is no general consensus what exactly the phonemes are, even for a specific language such as English.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

程序代写代做 CS编程辅导

We start with an example, the problem of speech recognition.

- A **phoneme** is an “elementary article” of human speech, so to speak.
- Spoken words of a particular language are understood by a listener by parsing them into a sequence of phonemes.
- There is no general consensus what exactly the phonemes are, even for a specific language such as English.
- We can think of them as the basic sounds of a language, which have the property that replacing one phoneme in a word with a different phoneme would change the meaning of the word.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

程序代写代做 CS编程辅导

We start with an example, the problem of speech recognition.

- A **phoneme** is an “elementary article” of human speech, so to speak.
- Spoken words of a particular language are understood by a listener by parsing them into a sequence of phonemes.
- There is no general consensus what exactly the phonemes are, even for a specific language such as English.
- We can think of them as the basic sounds of a language, which have the property that replacing one phoneme in a word with a different phoneme would change the meaning of the word.
- For example, if you replace the last phoneme /s/ in ‘kiss’ with phoneme /l/ you obtain a different word, ‘kill’.

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

程序代写代做 CS编程辅导

We start with an example, the problem of speech recognition.

- A **phoneme** is an “elementary article” of human speech, so to speak.
- Spoken words of a particular language are understood by a listener by parsing them into a sequence of phonemes.
- There is no general consensus what exactly the phonemes are, even for a specific language such as English.
- We can think of them as the basic sounds of a language, which have the property that replacing one phoneme in a word with a different phoneme would change the meaning of the word.
- For example, if you replace the phoneme /s/ in ‘kiss’ with phoneme /l/ you obtain a different word, ‘kill’.
- However, we identify variants of the same sound as a single phoneme, for example the “k” sound in words “cat”, “kit” and “skill” are considered all to be slight variants of a single basic phoneme /k/, and replacing one such variant with another would not cause the listener to mistakenly understand the word being pronounced.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutors@163.com

QQ: 749389476
<https://tutors.com>

The Problem of Speech Recognition

- Humans are very good at understanding speech, but machines got good at that only quite recently.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- Humans are very good at understanding speech, but machines got good at that only quite recently.
- So let us now consider being spoken, for example “I love algorithms”.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- Humans are very good at understanding speech, but machines got good at that only quite recently.
- So let us now consider what is being spoken, for example “I love algorithms”.
- We understand this sentence by breaking the speech into constituent phonemes.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- Humans are very good at understanding speech, but machines got good at that only quite recently.
- So let us now consider being spoken, for example “I love algorithms”.
- We understand this sentence by breaking the speech into constituent phonemes.
- I tried to reproduce the International Phonetic Alphabet (IPA) transcription in LaTeX, but could only get an approximation; so the utterance of “I love algorithms” would look approximately like this:



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- 程序代写代做 CS编程辅导
- Humans are very good at understanding speech, but machines got good at that only quite recently.
 - So let us now consider being spoken, for example “I love algorithms”.
 - We understand this sentence by breaking the speech into constituent phonemes.
 - I tried to reproduce the International Phonetic Alphabet (IPA) transcription in LaTeX, but could only get an approximation; so the utterance of “I love algorithms” would look approximately like this:



WeChat: cstutorcs

Assignment Project Exam Help

- Neither humans nor machines have a direct access to the sequence of the phonemes spoken.

Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- 程序代写代做 CS编程辅导
- Humans are very good at understanding speech, but machines got good at that only quite recently.
 - So let us now consider being spoken, for example “I love algorithms”.
 - We understand this sentence by breaking the speech into constituent phonemes.
 - I tried to reproduce the International Phonetic Alphabet (IPA) transcription in LaTeX, but could only get an approximation; so the utterance of “I love algorithms” would look approximately like this:



WeChat: cstutorcs

Assignment Project Exam Help

- Neither humans nor machines have a direct access to the sequence of the phonemes spoken.
- Humans have access only to the resulting acoustic waves produced, as detected by the hearing organs.

<https://tutorcs.com>

Email: tutorcs@163.com

QQ: 749389476

The Problem of Speech Recognition

- 程序代写代做 CS编程辅导
- Humans are very good at understanding speech, but machines got good at that only quite recently.
 - So let us now consider being spoken, for example “I love algorithms”.
 - We understand this sentence by breaking the speech into constituent phonemes.
 - I tried to reproduce the International Phonetic Alphabet (IPA) transcription in LaTeX, but could only get an approximation; so the utterance of “I love algorithms” would look approximately like this:



WeChat: cstutorcs

Assignment Project Exam Help

- Email: tutorcs@163.com
- QQ: 749389476
- <https://tutorcs.com>
- Neither humans nor machines have a direct access to the sequence of the phonemes spoken.
 - Humans have access only to the resulting acoustic waves produced, as detected by the hearing organs.
 - Machines only have access to the resulting digitally sampled acoustic waveforms.

The Problem of Speech Recognition

- 程序代写代做 CS编程辅导
- Humans are very good at understanding speech, but machines got good at that only quite recently.
 - So let us now consider being spoken, for example “I love algorithms”.
 - We understand this sentence by breaking the speech into constituent phonemes.
 - I tried to reproduce the International Phonetic Alphabet (IPA) transcription in LaTeX, but could only get an approximation; so the utterance of “I love algorithms” would look approximately like this:



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

- Neither humans nor machines have a direct access to the sequence of the phonemes spoken.
- Humans have access only to the resulting acoustic waves produced, as detected by the hearing organs.
- Machines only have access to the resulting digitally sampled acoustic waveforms.
- From such waveforms they have to “decide” what phonemes were spoken.

The Problem of Speech Recognition

- In order to recognise a spoken sentence a machine has to:



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- In order to recognise a spoken sentence a machine has to:
① partition the waveform into disjoint pieces, so that each piece should correspond to a single phoneme



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- In order to recognise a spoken sentence a machine has to:
① partition the waveform into disjoint pieces, so that each piece
should correspond to a single phoneme
(this is tricky in determining where the boundaries between
the waveforms defining the phonemes are)



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- In order to recognise a spoken sentence a machine has to:
① partition the waveform into disjoint pieces, so that each piece should correspond to a single phoneme
(this is tricky in determining where the boundaries between the waveforms defining phonemes are)
② then it has to do feature extraction from each piece, thus producing feature vectors $\vec{f}[1], \vec{f}[2], \dots$
(this is usually done in the frequency domain, by applying a transform of the kind of the Discrete Fourier Transform);

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- In order to recognise a spoken sentence a machine has to:
 - ① partition the waveform into disjoint pieces, so that each piece should correspond to a single phoneme
(this is tricky in determining where the boundaries between the waveforms defining phonemes are)
 - ② then it has to do feature extraction from each piece, thus producing feature vectors $\vec{f}[1], \vec{f}[2], \dots$
(this is usually done in the frequency domain, by applying a transform of the kind of the Discrete Fourier Transform);
 - ③ finally, it has to decide for each feature vector $\vec{f}[i]$ to which phoneme it corresponds, i.e., it has to decide what phonemes would produce as their signatures each of the feature vectors $\vec{f}[i]$.

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- In order to recognise a spoken sentence a machine has to:
 - ① partition the waveform into disjoint pieces, so that each piece should correspond to a single phoneme
(this is tricky in determining where the boundaries between the waveforms defining phonemes are)
 - ② then it has to do feature extraction from each piece, thus producing feature vectors $\vec{f}[1], \vec{f}[2], \dots$
(this is usually done in the frequency domain, by applying a transform of the kind of the Discrete Fourier Transform);
 - ③ finally, it has to decide for each feature vector $\vec{f}[i]$ to which phoneme it corresponds, i.e., it has to decide what phonemes would produce as their signatures each of the feature vectors $\vec{f}[i]$.

QQ: 749389476

- Note that some phonemes are only slightly different from one another and the phonemes also vary a lot from speaker to speaker;

<https://tutorcs.com>

The Problem of Speech Recognition

- In order to recognise a spoken sentence a machine has to:
 - ① partition the waveform into disjoint pieces, so that each piece should correspond to a single phoneme
(this is tricky in determining where the boundaries between the waveforms defining phonemes are)
 - ② then it has to do feature extraction from each piece, thus producing feature vectors $\vec{f}[1], \vec{f}[2], \dots$
(this is usually done in the frequency domain, by applying a transform of the kind of the Discrete Fourier Transform);
 - ③ finally, it has to decide for each feature vector $\vec{f}[i]$ to which phoneme it corresponds, i.e., it has to decide what phonemes would produce as their signatures each of the feature vectors $\vec{f}[i]$.

QQ: 749389476

- Note that some phonemes are only slightly different from one another and the phonemes also vary a lot from speaker to speaker;
- It is hard to determine with absolute certainty from a feature vector $\vec{f}[i]$ what phoneme “caused” a waveform that resulted in that particular feature vector.

The Problem of Speech Recognition



The Problem of Speech Recognition

- One can model human speech as a Markov chain, whose states are the phonemes.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- One can model human speech as a Markov chain, whose states are the phonemes.
- An utterance is an evolution of a Markov chain through such states, i.e., phonemes.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- One can model human speech as a Markov chain, whose states are the phonemes.
- An utterance is an evolution of a Markov chain through such states, i.e., phonemes.
- This Markov chain is  understood from the listener (in our case a machine)



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- One can model human speech as a Markov chain, whose states are the phonemes.
- An utterance is an evolution of a Markov chain through such states, i.e., phonemes.
- This Markov chain is observed by the listener (in our case a machine)
- The machine has access to a corresponding sequence of manifestations caused by pronouncing these phonemes, namely the corresponding waveforms.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- One can model human speech as a Markov chain, whose states are the phonemes.
- An utterance is an evolution of a Markov chain through such states, i.e., phonemes.
- This Markov chain is observed by the listener (in our case a machine)
- The machine has access to a corresponding sequence of manifestations caused by pronouncing these phonemes, namely the corresponding waveforms.
- These waveforms are processed into feature vectors $\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10]$.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- One can model human speech as a Markov chain, whose states are the phonemes.
- An utterance is an evolution of a Markov chain through such states, i.e., phonemes.
- This Markov chain is observed by the listener (in our case a machine)
- The machine has access to a corresponding sequence of manifestations caused by pronouncing these phonemes, namely the corresponding waveforms.
- These waveforms are processed into feature vectors $\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10]$.
- Given a sequence of manifestations $\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10]$ how can we decide what sequence of phonemes caused it?


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Problem of Speech Recognition

- One can model human speech as a Markov chain, whose states are the phonemes.
- An utterance is an evolution of a Markov chain through such states, i.e., phonemes.
- This Markov chain is observed by the listener (in our case a machine)
- The machine has access to a corresponding sequence of manifestations caused by pronouncing these phonemes, namely the corresponding waveforms.
- These waveforms are processed into feature vectors $\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10]$.
- Given a sequence of manifestations $\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10]$ how can we decide what sequence of phonemes caused it?



The Viterbi Algorithm

程序代写代做 CS编程辅导

- Main idea: we should do it in a way that maximises the likelihood that we are correct!



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

程序代写代做 CS编程辅导

- Main idea: we should find a way that maximises the likelihood that we are correct!
- This is what the Viterbi algorithm does.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

程序代写代做 CS编程辅导

- Main idea: we should find a way that maximises the likelihood that we are correct!
- This is what the Viterbi algorithm does.
- It is a dynamic programming algorithm which produces a sequence of states that are most likely to have as a consequence the sequence of “observations” $\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10]$.



WeChat: **tutorcs**

Assignment Project Exam Help

Email: **tutorcs@163.com**

QQ: **749389476**

<https://tutorcs.com>

The Viterbi Algorithm

程序代写代做 CS编程辅导



- Main idea: we should find a way that maximises the likelihood that we are correct!
- This is what the Viterbi algorithm does.
- It is a dynamic programming algorithm which produces a sequence of states that are most likely to have as a consequence the sequence of “observations” $\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10]$.
- The Viterbi algorithm has a huge range of applications, besides speech recognition, for example, for decoding the transmitted convolutional codes in presence of noise in communication channels, which is used in digital telecommunications such as the CDMA mobile phone network and 802.11 wireless LANs; it is also used in many other fields such as bioinformatics and computational linguistics.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: [749389476](https://tutorcs.com)

<https://tutorcs.com>

Hidden Markov Models: the general setup

- We are given a finite Markov chain, consisting of a set of its states
 $S = \{s_1, s_2, \dots, s_K\}$



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Hidden Markov Models: the general setup

- We are given a finite Markov chain, consisting of a set of its states
 $S = \{s_1, s_2, \dots, s_K\}$
- We are also given the initial probabilities $\pi_1, \pi_2, \dots, \pi_K$ of states,



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Hidden Markov Models: the general setup

- We are given a finite Markov chain, consisting of a set of its states $S = \{s_1, s_2, \dots, s_K\}$
- We are also given the initial probabilities $\pi_1, \pi_2, \dots, \pi_K$ of states,
- π_i is the probability that the chain starts in state s_i .



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Hidden Markov Models: the general setup

- We are given a finite Markov chain, consisting of a set of its states $S = \{s_1, s_2, \dots, s_K\}$
 - We are also given the initial probabilities $\pi_1, \pi_2, \dots, \pi_K$ of states,
 - π_i is the probability that the chain starts in state s_i .
 - We are also given a matrix $p(i, j) : 1 \leq i, j \leq K$ of size $K \times K$ of transition probabilities p_{ij} ($s_i \rightarrow s_j$).

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Hidden Markov Models: the general setup

- We are given a finite Markov chain, consisting of a set of its states $S = \{s_1, s_2, \dots, s_K\}$
- We are also given the initial probabilities $\pi_1, \pi_2, \dots, \pi_K$ of states,
- π_i is the probability the chain starts in state s_i .
- We are also given a matrix $p(i, j) : 1 \leq i, j \leq K$ of size $K \times K$ of transition probabilities $p(i, j)$ ($s_i \rightarrow s_j$).
- So if at an instant t the chain is in a state s_i , then $p(i, j)$ is the probability that at the next instant $t + 1$ the chain will be in state s_j .

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Hidden Markov Models: the general setup

- We are given a finite Markov chain, consisting of a set of its states $S = \{s_1, s_2, \dots, s_K\}$
- We are also given the initial probabilities $\pi_1, \pi_2, \dots, \pi_K$ of states,
- π_i is the probability that the chain starts in state s_i .
- We are also given a matrix $p(i, j) : 1 \leq i, j \leq K$ of size $K \times K$ of transition probabilities $p(i, j)$ ($s_i \rightarrow s_j$).
- So if at an instant t the chain is in a state s_i , then $p(i, j)$ is the probability that at the next instant $t + 1$ the chain will be in state s_j .
- We have no direct access to the states of such a Markov chain.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Hidden Markov Models: the general setup

- We are given a finite Markov chain, consisting of a set of its states $S = \{s_1, s_2, \dots, s_K\}$
- We are also given the initial probabilities $\pi_1, \pi_2, \dots, \pi_K$ of states,
- π_i is the probability the chain starts in state s_i .
- We are also given a matrix $p = (p(i, j) : 1 \leq i, j \leq K)$ of size $K \times K$ of transition probabilities ($s_i \rightarrow s_j$).
- So if at an instant t the chain is in a state s_i , then $p(i, j)$ is the probability that at the next instant $t + 1$ the chain will be in state s_j .
- We have no direct access to the states of such a Markov chain.
- Instead we have a set of observables $O = \{o_1, o_2, \dots, o_N\}$ which are the possible manifestations of the states $S = \{s_1, s_2, \dots, s_K\}$

WeChat:  [tutorcs](#)

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Hidden Markov Models: the general setup


- We are given a finite Markov chain, consisting of a set of its states $S = \{s_1, s_2, \dots, s_K\}$
- We are also given the initial probabilities $\pi_1, \pi_2, \dots, \pi_K$ of states,
- π_i is the probability that the chain starts in state s_i .
- We are also given a matrix $p = (p(i, j) : 1 \leq i, j \leq K)$ of size $K \times K$ of transition probabilities $p(i, j)$ ($s_i \rightarrow s_j$).
- So if at an instant t the chain is in a state s_i , then $p(i, j)$ is the probability that at the next instant $t + 1$ the chain will be in state s_j .
- We have no direct access to the states of such a Markov chain.
- Instead we have a set of observables $O = \{o_1, o_2, \dots, o_N\}$ which are the possible manifestations of the states $S = \{s_1, s_2, \dots, s_K\}$
- We are also given the emission matrix E of size $K \times N$ where entry $e(i, k)$ represents the probability that when the chain is in state s_i the observable outcome will be o_k .

QQ: 749389476

<https://tutorcs.com>

Hidden Markov Models: the general setup

- We are given a finite Markov chain, consisting of a set of its states $S = \{s_1, s_2, \dots, s_K\}$
- We are also given the initial probabilities $\pi_1, \pi_2, \dots, \pi_K$ of states, π_i is the probability that the chain starts in state s_i .
- We are also given a matrix $p = (p(i, j) : 1 \leq i, j \leq K)$ of size $K \times K$ of transition probabilities $p(i, j)$ ($s_i \rightarrow s_j$).
- So if at an instant t the chain is in a state s_i , then $p(i, j)$ is the probability that at the next instant $t + 1$ the chain will be in state s_j .
- We have no direct access to the states of such a Markov chain.
- Instead we have a set of observables $O = \{o_1, o_2, \dots, o_N\}$ which are the possible manifestations of the states $S = \{s_1, s_2, \dots, s_K\}$.
- We are also given the emission matrix E of size $K \times N$ where entry $e(i, k)$ represents the probability that when the chain is in state s_i the observable outcome will be o_k .



A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .
- Thus, the probability of a head is $1 - p$.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .
- Thus, the probability of getting a head is $1 - p$.
- The probability of getting the sequence $TTHTTH$ is equal to $p \cdot p \cdot (1 - p) \cdot p \cdot p \cdot (1 - p)^2$.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .
- Thus, the probability of getting a tail is $1 - p$.
- The probability of getting the sequence $TTHTTH$ is equal to $p \cdot p \cdot (1 - p) \cdot p \cdot p \cdot (1 - p)^2$.
- But now we can invert the question: assume we have a coin with an unknown probability p of getting a tail.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .
- Thus, the probability of getting a head is $1 - p$.
- The probability of getting the outcome $TTHTTH$ is equal to $p \cdot p \cdot (1 - p) \cdot p \cdot p \cdot (1 - p)^2$.
- But now we can invert the question: assume we have a coin with an unknown probability p of getting a tail.
- Assume we have tossed it 6 times and got the outcome $TTHTTH$.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .
- Thus, the probability of getting a head is $1 - p$.
- The probability of getting the outcome $TTHTTH$ is equal to $p \cdot p \cdot (1 - p) \cdot p \cdot p \cdot (1 - p)^2$.
- But now we can invert the question: assume we have a coin with an unknown probability p of getting a tail.
- Assume we have tossed it 6 times and got the outcome $TTHTTH$.
- We can now ask for what value of p is such an outcome MOST LIKELY?

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .
- Thus, the probability of getting a head is $1 - p$.
- The probability of getting the outcome $TTHTTH$ is equal to $p \cdot p \cdot (1 - p) \cdot p \cdot p \cdot (1 - p)^2 = p^4(1 - p)^2$.
- But now we can invert the question: assume we have a coin with an unknown probability p of getting a tail.
- Assume we have tossed it 6 times and got the outcome $TTHTTH$.
- We can now ask for what value of p is such an outcome MOST LIKELY?
- This boils down to finding p for which $f(p) = p^4(1 - p)^2$ attains maximal value.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .
- Thus, the probability of getting a head is $1 - p$.
- The probability of getting the outcome $TTHTTH$ is equal to $p \cdot p \cdot (1 - p) \cdot p \cdot p \cdot (1 - p)^2 = p^4(1 - p)^2$.
- But now we can invert the question: assume we have a coin with an unknown probability p of getting a tail.
- Assume we have tossed it 6 times and got the outcome $TTHTTH$.
- We can now ask for what value of p is such an outcome MOST LIKELY?
- This boils down to finding p for which $f(p) = p^4(1 - p)^2$ attains maximal value.
- Differentiating $f(p)$ and setting its first derivative to zero we obtain

$$QQ: 749389476 \quad 4p^3(1 - p)^2 + 2p^4(1 - p) = 0$$

<https://tutorcs.com>

A quick digression: what is likelihood?

- Likelihood is, in a sense, an inverse of probability.
- Assume you have a (possibly biased) coin, so that the probability of a tail is p .
- Thus, the probability of getting a head is $1 - p$.
- The probability of getting the outcome $TTHTTH$ is equal to $p \cdot p \cdot (1 - p) \cdot p \cdot p \cdot (1 - p)^2 = p^4(1 - p)^2$.
- But now we can invert the question: assume we have a coin with an unknown probability p of getting a tail.
- Assume we have tossed it 6 times and got the outcome $TTHTTH$.
- We can now ask for what value of p is such an outcome MOST LIKELY?
- This boils down to finding p for which $f(p) = p^4(1 - p)^2$ attains maximal value.
- Differentiating $f(p)$ and setting its first derivative to zero we obtain

$$QQ: 749389476 \quad 4p^3(1 - p)^2 + 2p^4(1 - p) = 0$$

<https://tutorcs.com>

- Since we can rule out values $p = 0$ and $p = 1$, this implies $4(1 - p) - 2p = 0$ which yields $p = 2/3$ and $1 - p = 1/3$ which sounds right: the probability of getting a tail is twice as high as the probability of getting a head, and indeed, we have twice as many tails than heads in the observed outcome.

Maximum likelihood estimation

程序代写代做 CS编程辅导

- So assume we have an observed outcome, such as $TTHTTH$ in the previous example, generated by a process with unknown parameters, such as p in the previous example. Maximum Likelihood estimation finds the unknown parameters so that the probability of getting the outcome is the largest.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Maximum likelihood estimation

程序代写代做 CS编程辅导

- So assume we have an observed outcome, such as $TTHTTH$ in the previous example, generated by a process with unknown parameters, such as in the previous example. Maximum Likelihood estimation finds the unknown parameters so that the probability of getting the outcome is the largest.
- Maximum likelihood often produces very good estimates of the unknown parameters, but sometimes, if the sample is small, it can produce a very bad estimate.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Maximum likelihood estimation

程序代写代做 CS编程辅导

- So assume we have an observed outcome, such as $TTHTTH$ in the previous example, generated by a process with unknown parameters, such as in the previous example. Maximum Likelihood estimation finds the unknown parameters so that the probability of getting the outcome is the largest.
- Maximum likelihood often produces very good estimates of the unknown parameters, but sometimes, if the sample is small, it can produce a very bad estimate.
- As an example, consider the following problem.

WeChat: cstutors

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Maximum likelihood estimation

程序代写代做 CS编程辅导

- So assume we have an observed outcome, such as $TTHTTH$ in the previous example, generated by a process with unknown parameters, such as the probability p of getting heads in the previous example. Maximum Likelihood estimation finds the unknown parameters so that the probability of getting the outcome is the largest.
- Maximum likelihood often produces very good estimates of the unknown parameters, but sometimes, if the sample is small, it can produce a very bad estimate.
- As an example, consider the following problem.
- Assume that I have given you a box which contains n balls which are numbered consecutively 1 to n , but I do not tell you what n is, i.e., how many balls there are inside.

Assignment Project Exam Help

Email: tutorcs@163.com

WeChat: cstutors

QQ: 749389476

<https://tutorcs.com>

Maximum likelihood estimation

程序代写代做 CS编程辅导

- So assume we have an observed outcome, such as $TTHTTH$ in the previous example, generated by a process with unknown parameters, such as the probability p of getting a head in the previous example. Maximum Likelihood estimation finds the unknown parameters so that the probability of getting the outcome is the largest.
- Maximum likelihood often produces very good estimates of the unknown parameters, but sometimes, if the sample is small, it can produce a very bad estimate.
- As an example, consider the following problem.
- Assume that I have given you a box which contains n balls which are numbered consecutively 1 to n , but I do not tell you what n is, i.e., how many balls there are inside.
- You are allowed to draw one single ball and look at its number, and then you have to estimate how many balls there are inside.

<https://tutorcs.com>

Maximum likelihood estimation

程序代写代做 CS编程辅导

- So assume we have an observed outcome, such as $TTHTTH$ in the previous example, generated by a process with unknown parameters, such as the probability p of getting a head in the previous example. Maximum Likelihood estimation finds the unknown parameters so that the probability of getting the outcome is the largest.



- Maximum likelihood often produces very good estimates of the unknown parameters, but sometimes, if the sample is small, it can produce a very bad estimate.

- As an example, consider the following problem:

Assignment Project Exam Help

- Assume that I have given you a box which contains n balls which are numbered consecutively 1 to n , but I do not tell you what n is, i.e., how many balls there are inside.

- You are allowed to draw one single ball and look at its number, and then you have to estimate how many balls there are inside.

- Assume that you drew the ball numbered 1. Since all balls are equally likely, if there are n balls inside, then the probability of drawing any particular ball is $1/n$.

Maximum likelihood estimation

- Thus, the event that you drew ball K has the highest possible probability if $1/n$ is as large as possible, i.e., when n is as small as possible.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Maximum likelihood estimation

- Thus, the event that you drew ball k has the highest possible probability if $1/n$ is as large as possible, i.e., when n is as small as possible.
- Since you know that there are at least k balls inside, the MLE estimate for the number of balls in the urn is k , i.e., the MLE estimator in this case is $N(X) = X$, or simply



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Maximum likelihood estimation

- Thus, the event that you drew ball k has the highest possible probability if $1/n$ is as large as possible, i.e., when n is as small as possible.
- Since you know that there are at least k balls inside, the MLE estimate for the number of balls in the box is $N(X) = X$, i.e., the MLE estimator in this case is $N(X) = X$, or simply X , of the sample.
- What is the mean of the estimator? The expected value of X , i.e., $\mu = E(X)$ is then given by

$$\mu = \sum_{i=1}^n \left(i \times \frac{1}{n} \right) = \frac{n(n+1)}{2n} = \frac{n+1}{2}.$$

Assignment Project Exam Help

Thus, in this case the MLE estimator is extremely biased, because its expected value is only about one half of the true value n of the number of balls inside the box!

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Maximum likelihood estimation

- Thus, the event that you drew ball X has the highest possible probability if $1/n$ is as large as possible, i.e., when n is as small as possible.
- Since you know that there are at least k balls inside, the MLE estimate for the number of balls in the box is $N(X) = X$, i.e., the MLE estimator in this case is $N(X) = X$, or simply X , of the sample.
- What is the mean of the estimator? The expected value of X , i.e., $\mu = E(X)$ is then given by

$$\mu = \sum_{i=1}^n \left(i \times \frac{1}{n} \right) = \frac{n(n+1)}{2n} = \frac{n+1}{2}.$$

Assignment Project Exam Help

Thus, in this case the MLE estimator is extremely biased, because its expected value is only about one half of the true value n of the number of balls inside the box!

Email: tutorcs@163.com

- If you instead use the estimator $Y(X) = 2X - 1$, then the expected value of Y is

$$\sum_{i=1}^n \frac{2i-1}{n} = \frac{2 \sum_{i=1}^n i}{n} - \frac{\sum_{i=1}^n 1}{n} = \frac{2n(n+1)}{2n} - 1 = n$$

QQ: 749389476

<https://tutorcs.com>

and so this estimator is unbiased – much better than the MLE.

Maximum likelihood estimation

- Thus, the event that you drew ball X has the highest possible probability if $1/n$ is as large as possible, i.e., when n is as small as possible.
- Since you know that there are at least k balls inside, the MLE estimate for the number of balls in the box is $N(X) = X$, i.e., the MLE estimator in this case is $N(X) = X$, or simply X , of the sample.
- What is the mean of the estimator? The expected value of X , i.e., $\mu = E(X)$ is then given by

$$\mu = \sum_{i=1}^n \left(i \times \frac{1}{n} \right) = \frac{n(n+1)}{2n} = \frac{n+1}{2}.$$

Assignment Project Exam Help

Thus, in this case the MLE estimator is extremely biased, because its expected value is only about one half of the true value n of the number of balls inside the box!

Email: tutorcs@163.com

- If you instead use the estimator $Y(X) = 2X - 1$, then the expected value of Y is

$$\sum_{i=1}^n \frac{2i-1}{n} = \frac{2 \sum_{i=1}^n i}{n} - \frac{\sum_{i=1}^n 1}{n} = \frac{2n(n+1)}{2n} - 1 = n$$

and so this estimator is unbiased – much better than the MLE.

- This does not happen for large samples; it can be shown that as the size of the sample increases, ML estimate approaches the best possible estimate.

程序代写代做 CS编程辅导

- Assume now that we are given a sequence of observable outcomes (y_1, y_2, \dots, y_T) .



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Assume now that we are given a sequence of observable outcomes (y_1, y_2, \dots, y_T) .
- The goal is to find the sequence (x_1, x_2, \dots, x_T) of states of the Markov chain for which the likelihood that such a sequence is the cause of the observed sequence of outcomes (y_1, y_2, \dots, y_T) is the highest.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Assume now that we are given a sequence of observable outcomes (y_1, y_2, \dots, y_T) .
- The goal is to find the sequence (x_1, x_2, \dots, x_T) of states of the Markov chain for which the likelihood that such a sequence is the cause of the observed sequence of outcomes (y_1, y_2, \dots, y_T) is the highest.
- In other words, we are looking for the most likely cause of the sequence of observations (y_1, y_2, \dots, y_T) .


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Assume now that we are given a sequence of observable outcomes (y_1, y_2, \dots, y_T) .
- The goal is to find the sequence (x_1, x_2, \dots, x_T) of states of the Markov chain for which the likelihood that such a sequence is the cause of the observed sequence of outcomes (y_1, y_2, \dots, y_T) is the highest.
- In other words, we are looking for the most likely cause of the sequence of observations (y_1, y_2, \dots, y_T) .
- In our speech recognition example we are given a sequence of feature vectors $(\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10])$ extracted from the sound waveform and we have to find what sequence of phonemes $(\phi_1, \phi_2, \dots, \phi_{10})$ is the most likely cause of the sequence of the feature vectors $(\vec{f}[1], \vec{f}[2], \dots, \vec{f}[10])$.



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

- Theoretically, we could solve this problem by brute force:



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

- Theoretically, we could solve this problem by brute force:
- we could go through all possible sequences of states $\vec{x} = (x_1, x_2, \dots, x_T)$ of the same length as the sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and compute the corresponding probability that each of such sequences might be the cause for the given sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and then select the sequence \vec{x} for which such probability is the largest.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

- Theoretically, we could solve this problem by brute force:
WeChat: cstutorcs
- we could go through all possible sequences of states $\vec{x} = (x_1, x_2, \dots, x_T)$ of the same length as the sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and compute the corresponding probability that each of such sequences might be the cause for the given sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and then select the sequence \vec{x} for which such probability is the largest.
- This could, theoretically, be done as follows. We first find the probability $P(\vec{x})$ that a sequence \vec{x} occurred at all, as the following product:

$$P(\vec{x}) = \pi(x_1) \cdot p(x_1 \rightarrow x_2) \cdot p(x_2 \rightarrow x_3) \dots p(x_{T-1} \rightarrow x_T)$$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

- Theoretically, we could solve this problem by brute force:
程序化与代数CS编程辅导
- we could go through all possible sequences of states $\vec{x} = (x_1, x_2, \dots, x_T)$ of the same length as the sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and compute the corresponding probability that each of such sequences might be the cause for the given sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and then select the sequence \vec{x} for which the probability is the largest.
- This could, theoretically, be done as follows. We first find the probability $P(\vec{x})$ that a sequence \vec{x} occurred at all, as the following product:

$$P(\vec{x}) = \pi(x_1) \cdot p(x_1 \rightarrow x_2) \cdot p(x_2 \rightarrow x_3) \dots p(x_{T-1} \rightarrow x_T)$$

- WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com
- This is because $\pi(x_1)$ is the probability that the starting state (phoneme in our example) is x_1 , times the probability $p(x_1 \rightarrow x_2)$ that system transitions from state x_1 into state x_2 and so forth.

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

- Theoretically, we could solve this problem by brute force:
程序化与代数CS编程辅导
- we could go through all possible sequences of states $\vec{x} = (x_1, x_2, \dots, x_T)$ of the same length as the sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and compute the corresponding probability that each of such sequences might be the cause for the given sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and then select the sequence \vec{x} for which the probability is the largest.
- This could, theoretically, be done as follows. We first find the probability $P(\vec{x})$ that a sequence \vec{x} occurred at all, as the following product:

$$P(\vec{x}) = \pi(x_1) \cdot p(x_1 \rightarrow x_2) \cdot p(x_2 \rightarrow x_3) \dots p(x_{T-1} \rightarrow x_T)$$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

- This is because $\pi(x_1)$ is the probability that the starting state (phoneme in our example) is x_1 , times the probability $p(x_1 \rightarrow x_2)$ that system transitions from state x_1 into state x_2 and so forth.
- Next, we compute the probability $P^*(\vec{x}, \vec{y})$ that this particular sequence of states $\vec{x} = (x_1, \dots, x_T)$ will cause the sequence of observable outcomes $\vec{y} = (y_1, \dots, y_T)$, as the product of the probabilities $e(x_1, y_1) \cdot \dots \cdot e(x_T, y_T)$ where each $e(x_i, y_i)$ is the “emission” probability that state x_i produces the observable manifestation y_i .

The Viterbi Algorithm

- Theoretically, we could solve this problem by brute force:
程序化与代数CS编程辅导
- we could go through all possible sequences of states $\vec{x} = (x_1, x_2, \dots, x_T)$ of the same length as the sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and compute the corresponding probability that each of such sequences might be the cause for the given sequence of observables $\vec{y} = (y_1, y_2, \dots, y_T)$ and then select the sequence \vec{x} for which such probability is the largest.
- This could, theoretically, work as follows. We first find the probability $P(\vec{x})$ that a sequence \vec{x} occurred at all, as the following product:

$$P(\vec{x}) = \pi(x_1) \cdot p(x_1 \rightarrow x_2) \cdot p(x_2 \rightarrow x_3) \dots p(x_{T-1} \rightarrow x_T)$$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

- This is because $\pi(x_1)$ is the probability that the starting state (phoneme in our example) is x_1 , times the probability $p(x_1 \rightarrow x_2)$ that system transitions from state x_1 into state x_2 and so fourth.
- Next, we compute the probability $P^*(\vec{x}, \vec{y})$ that this particular sequence of states $\vec{x} = (x_1, \dots, x_T)$ will cause the sequence of observable outcomes $\vec{y} = (y_1, \dots, y_T)$, as the product of the probabilities $e(x_1, y_1) \cdot \dots \cdot e(x_T, y_T)$ where each $e(x_i, y_i)$ is the “emission” probability that state x_i produces the observable manifestation y_i .
- Finally, the probability $\mathcal{P}(\vec{x}, \vec{y})$ that sequence \vec{x} is the cause of the sequence of observable outcomes \vec{y} is the product of the probabilities $P(\vec{x})$ that sequence \vec{x} occurred at all and the probability $P^*(\vec{x}, \vec{y})$ that, if it did occur, it also caused the right observable outcome \vec{y} , so in total $\mathcal{P}(\vec{x}, \vec{y}) = P(\vec{x}) \cdot P^*(\vec{x}, \vec{y})$.

The Viterbi Algorithm

程序代写代做 CS编程辅导

- So given the sequence $\vec{y} = (y_1, y_2, \dots, y_T)$ observed, we could now simply pick the sequence $\vec{x} = (x_1, x_2, \dots, x_T)$ for which the value of $\mathcal{P}(\vec{x}, \vec{y})$ is the largest.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

程序代写代做 CS编程辅导

- So given the sequence $\vec{y} = (y_1, y_2, \dots, y_T)$ observed, we could now simply pick the sequence $\vec{x} = (x_1, x_2, \dots, x_T)$ for which the value of $\mathcal{P}(\vec{x}, \vec{y})$ is the largest.
- However, this is not a feasible algorithm: if the total number of states is K and the observed sequence is of length T then there would be in total K^T many sequences to try, i.e., exponentially many.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



The Viterbi Algorithm

程序代写代做 CS编程辅导

- So given the sequence $\vec{y} = (y_1, y_2, \dots, y_T)$ observed, we could now simply pick the sequence $\vec{x} = (x_1, x_2, \dots, x_T)$ for which the value of $\mathcal{P}(\vec{x}, \vec{y})$ is the largest.



- However, this is not a feasible algorithm: if the total number of states is K and the observed sequence is of length T then there would be in total K^T many sequences to try, i.e., exponentially many.
- This is no good for real time (or almost real time) algorithms such as speech recognition or decoding the convolutional codes used in mobile telephony.

WeChat: cstuorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

程序代写代做 CS编程辅导

- So given the sequence $\vec{y} = (y_1, y_2, \dots, y_T)$ observed, we could now simply pick the sequence $\vec{x} = (x_1, x_2, \dots, x_T)$ for which the value of $\mathcal{P}(\vec{x}, \vec{y})$ is the largest.



- However, this is not a feasible algorithm: if the total number of states is K and the observed sequence is of length T then there would be in total K^T many sequences to try, i.e., exponentially many.

WeChat: cstutorcs
Assignment Project Exam Help

- This is no good for real time (or almost real time) algorithms such as speech recognition or decoding the convolutional codes used in mobile telephony.

- Instead, the Viterbi algorithm solves this problem in time $O(T \times K^2)$ using dynamic programming.

QQ: 749389476
<https://tutorcs.com>

The Viterbi Algorithm

- **The Viterbi Algorithm**: We solve all subproblems $S(i, k)$ for every $1 \leq i \leq T$ and every $1 \leq k \leq K$:

Subproblem $S(i, k)$:
and such that the prob



sequence of states (x_1, \dots, x_i) such that $x_i = s_k$
serving the outcome (y_1, \dots, y_i) is maximal.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

- **The Viterbi Algorithm**: We solve all subproblems $\mathcal{S}(i, k)$ for every $1 \leq i \leq T$ and every $1 \leq k \leq K$:

Subproblem $\mathcal{S}(i, k)$:



sequence of states (x_1, \dots, x_i) such that $x_i = s_k$ and such that the probability of observing the outcome (y_1, \dots, y_i) is maximal.

- Thus, we solve subproblems for all truncations (x_1, \dots, x_i) , $1 \leq i \leq T$, but also insisting that the last state x_i of such a truncated subsequence be state s_k .

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm

- **The Viterbi Algorithm**: We solve all subproblems $S(i, k)$ for every $1 \leq i \leq T$ and every $1 \leq k \leq K$:

Subproblem $S(i, k)$:



sequence of states (x_1, \dots, x_i) such that $x_i = s_k$ and such that the probability of observing the outcome (y_1, \dots, y_i) is maximal.

- Thus, we solve subproblems for all truncations (x_1, \dots, x_i) , $1 \leq i \leq T$, but also insisting that the last state x_i of such a truncated subsequence be state s_k .

WeChat: cstutorcs

- Let us denote by $L(i, k)$ the largest possible probability for which there exists a sequence (x_1, x_2, \dots, x_i) ending with $x_i = s_k$ causing the subsequence of observable outcomes (y_1, y_2, \dots, y_i) ; such probabilities must satisfy the following recursion:

Email: tutorcs@163.com

$$L(1, k) = \pi_k \cdot e(s_k, y_1)$$

$$L(i, k) = \max_{m \in S} (L(i-1, m) p(s_m \rightarrow s_k) e(s_k, y_i));$$

$$\sigma(i, k) = \arg \max_{m \in S} (L(i-1, m) p(s_m \rightarrow s_k) e(s_k, y_i)).$$

The Viterbi Algorithm

- **The Viterbi Algorithm:** We solve all subproblems $S(i, k)$ for every $1 \leq i \leq T$ and every $1 \leq k \leq K$:

Subproblem $S(i, k)$: sequence of states (x_1, \dots, x_i) such that $x_i = s_k$ and such that the probability of observing the outcome (y_1, \dots, y_i) is maximal.

- Thus, we solve subproblems for all truncations (x_1, \dots, x_i) , $1 \leq i \leq T$, but also insisting that the last state x_i of such a truncated subsequence be state s_k .

WeChat: cstutorcs

- Let us denote by $L(i, k)$ the largest possible probability for which there exists a sequence (x_1, x_2, \dots, x_i) ending with $x_i = s_k$ causing the subsequence of observable outcomes (y_1, y_2, \dots, y_i) ; such probabilities must satisfy the following recursion:

Email: tutorcs@163.com

$$L(1, k) = \pi_k \cdot e(s_k, y_1)$$

$$L(i, k) = \max_{m \in S} (L(i-1, m) p(s_m \rightarrow s_k) e(s_k, y_i));$$

$$\sigma(i, k) = \arg \max_{m \in S} (L(i-1, m) p(s_m \rightarrow s_k) e(s_k, y_i)).$$

- Here $\sigma(i, k)$ stores the value of m for which $L(i-1, m) p(s_m \rightarrow s_k) e(s_k, y_i)$ is the largest which allows us to reconstruct the sequence of states which maximize the probabilities we are tracking.

The Viterbi Algorithm

程序代写代做 CS编程辅导



$$L(1, k) = \pi_k$$

$$L(i, k) = \max_{m \in S} L(i-1, m) p(s_m \rightarrow s_k) e(s_k, y_i);$$

$$\sigma(i, k) = \arg \max_{m \in S} (L(i-1, m) p(s_m \rightarrow s_k) e(s_k, y_i)).$$

Assignment Project Exam Help

- We can now obtain the sequence of states which is most likely cause of the given sequence of observations by backtracking:

Email: tutorcs@163.com

$$x_T = \arg \max_m (L(T, m))$$

QQ: 749389476
 $x_{i-1} = \sigma(i, x_i), \quad i = T, T-1, \dots, 2.$

<https://tutorcs.com>

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probability of what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
- probabilities of initial states:

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
WeChat: estatutes
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
- probabilities of initial states: $\pi(R) = \frac{2}{3}$;

<https://tutorcs.com>

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
WeChat: estatotors
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
- probabilities of initial states: $\pi(R) = 2/3$; $\pi(P) = 1/3$.

<https://tutorcs.com>

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
• probabilities of initial states: $\pi(R) = 2/3$; $\pi(P) = 1/3$.
• transition probabilities:
 $p(R \rightarrow R) = 4/5$;

<https://tutorcs.com>

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probability of what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
WeChat: estatotors
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
<https://tutorcs.com>
- probabilities of initial states: $\pi(R) = \frac{2}{3}; \pi(P) = \frac{1}{3}$.
- transition probabilities:
 $p(R \rightarrow R) = \frac{4}{5}; p(R \rightarrow P) = \frac{1}{5}$;

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in pairs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probability of what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
• probabilities of initial states: $\pi(R) = \frac{2}{3}; \pi(P) = \frac{1}{3}$.
• transition probabilities:
 $p(R \rightarrow R) = \frac{4}{5}; p(R \rightarrow P) = \frac{1}{5}; p(P \rightarrow P) = \frac{1}{3};$

QQ: 749389476

<https://tutorcs.com>

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
• probabilities of initial states: $\pi(R) = \frac{2}{3}; \pi(P) = \frac{1}{3}$.
• transition probabilities:
 $p(R \rightarrow R) = \frac{4}{5}; p(R \rightarrow P) = \frac{1}{5}; p(P \rightarrow P) = \frac{1}{3}; p(P \rightarrow R) = \frac{2}{3}.$

QQ: 749389476

<https://tutorcs.com>


The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $O(r|P)$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $1/4$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $4/5$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
WeChat: estatotors
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
- probabilities of initial states: $\pi(R) = 2/3$; $\pi(P) = 1/3$.
- transition probabilities:
 $p(R \rightarrow R) = 4/5$; $p(R \rightarrow P) = 1/5$; $p(P \rightarrow P) = 1/3$; $p(P \rightarrow R) = 2/3$.
- emission probabilities: <https://tutorcs.com>
 $O(r|R) = 1/3$;

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
WeChat: estatotors
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
- probabilities of initial states: $\pi(R) = \frac{2}{3}; \pi(P) = \frac{1}{3}$.
- transition probabilities:
 $p(R \rightarrow R) = \frac{4}{5}; p(R \rightarrow P) = \frac{1}{5}; p(P \rightarrow P) = \frac{1}{3}; p(P \rightarrow R) = \frac{2}{3}$.
- emission probabilities: <https://tutorcs.com>
 $O(r|P) = \frac{1}{3}; O(p|P) = \frac{2}{3}$;


The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?

- probabilities of initial states: $\pi(R) = \frac{2}{3}; \pi(P) = \frac{1}{3}$.
- transition probabilities:
 $p(R \rightarrow R) = \frac{4}{5}; p(R \rightarrow P) = \frac{1}{5}; p(P \rightarrow P) = \frac{1}{3}; p(P \rightarrow R) = \frac{2}{3}$.
- emission probabilities: <https://tutorcs.com>
 $O(r|P) = \frac{1}{3}; O(p|P) = \frac{2}{3}; O(p|R) = \frac{1}{4};$

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $1/4$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $1/4$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $4/5$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?
WeChat: estatotors
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
- probabilities of initial states: $\pi(R) = 2/3; \pi(P) = 1/3$.
- transition probabilities: $p(R \rightarrow R) = 4/5; p(R \rightarrow P) = 1/5; p(P \rightarrow P) = 1/3; p(P \rightarrow R) = 2/3$.
- emission probabilities: <https://tutorcs.com>
 $O(r|P) = 1/3; O(p|P) = 2/3; O(p|R) = 1/4; O(r|R) = 3/4$.

The Viterbi Algorithm Example

- In California there are twice as many raccoons as possums. Having gotten a job with Google, you are in California observing a back yard. It is dusk, so the probability that you think you saw a raccoon when you are actually looking at a possum at a distance is $\frac{1}{4}$. The probability that you think you saw a possum while you are actually looking at a raccoon at a distance is $\frac{1}{4}$. Raccoons move in packs, so if a raccoon comes to your back yard the probability that the next animal to follow will also be a raccoon is $\frac{4}{5}$. Possums are solitary animals, so if a possum comes to your back yard, this does not impact the probabilities what the next animal to come will be (a possum or a raccoon, but recall in California there are twice as many raccoons as possums!) You believe that you saw four animals coming in the following order: a raccoon, a possum, a possum, a raccoon ($rppr$). Given such a sequence of observations, what actual sequence of animals is most likely to cause such a sequence of your observations?

- probabilities of initial states: $\pi(R) = \frac{2}{3}; \pi(P) = \frac{1}{3}$.
- transition probabilities:
 $p(R \rightarrow R) = \frac{4}{5}; p(R \rightarrow P) = \frac{1}{5}; p(P \rightarrow P) = \frac{1}{3}; p(P \rightarrow R) = \frac{2}{3}$.
- emission probabilities: <https://tutorcs.com>
 $O(r|P) = \frac{1}{3}; O(p|P) = \frac{2}{3}; O(p|R) = \frac{1}{4}; O(r|R) = \frac{3}{4}$.
- Homework:** Execute the Viterbi algorithm by hand (using a calculator) to see what actual sequence of animals is most likely to cause the sequence of observations $rppr$.