



程序代写
CS编程辅导

Advanced Algorithms
WeChat: cstutorcs
COMP4121

Assignment Project Exam Help

Email: AleksLjovic@163.com

QQ: 749389476

School of Computer Science and Engineering
University of New South Wales
<https://tutorcs.com>

Introduction to Randomised Algorithms:
Randomised Hashing

Hash Functions

程序代写代做 CS编程辅导

Scenario:

- You are given an algorithm to implement hashing.
- You will self-grade in pairs, testing and grading your partners implementation; **WeChat: cstutorcs**
- Your partner plays dirty:
 - he analyses your hash function;
 - picks a sequence of the worst-case keys, causing your implementation to take $O(n)$ time to search.
- What would you do?
Email: tutorcs@163.com
QQ: 749389476



Hash Functions

程序代写代做 CS编程辅导

Scenario:

- You are given an algorithm to implement hashing.
- You will self-grade in pairs, testing and grading your partners implementation; WeChat: cstutorcs
- Your partner plays dirty:
 - he analyses your hash function;
 - picks a sequence of the worst-case keys, causing your implementation to take $O(n)$ time to search.
- What would you do?
<https://tutorcs.com>



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Hash Functions

程序代写代做 CS编程辅导

Scenario:

- You are given an algorithm to implement hashing.
- You will self-grade in pairs, testing and grading your partners implementation; WeChat: cstutorcs
- Your partner plays dirty:
 - he analyses your hash function;
 - picks a sequence of the worst-case keys, causing your implementation to take $O(n)$ time to search.
- What would you do?
<https://tutorcs.com>



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Hash Functions

程序代写代做 CS编程辅导

Scenario:

- You are given an algorithm to implement hashing.
- You will self-grade in pairs, testing and grading your partners implementation; WeChat: cstutorcs
- Your partner plays dirty:

Assignment Project Exam Help

- he analyses your hash function;
- picks a sequence of the worst-case keys, causing your implementation to take $O(n)$ time to search.

QQ: 749389476

- What would you do?
<https://tutorcs.com>



Hash Functions

程序代写代做 CS编程辅导

Scenario:

- You are given an assignment to implement hashing.
- You will self-grade in pairs, testing and grading your partners implementation; **WeChat: cstutorcs**
- Your partner plays dirty:
 - he analyses your hash function;
 - picks a sequence of the worst-case keys, causing your implementation to take $O(n)$ time to search.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

- What would you do?
<https://tutorcs.com>



Hash Functions

程序代写代做 CS编程辅导

Scenario:

- You are given an assignment to implement hashing.
- You will self-grade in pairs, testing and grading your partners implementation; **WeChat: cstutorcs**
- Your partner plays dirty:
 - he analyses your hash function;
 - picks a sequence of the worst-case keys, causing your implementation to take $O(n)$ time to search.
- What would you do?
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
<https://tutorcs.com>



Hash functions: randomised hashing

程序代写代做 CS编程辅导

Solution:

- Randomise your hash function randomly in a way that is independent of the keys that are actually going to be stored.



WeChat: cstutorcs

Assignment Project Exam Help

- In this way no single input always invokes worst case performance!
- Guarantees good performance on average over many runs of your program, no matter what keys adversary chooses.

QQ: 749389476

<https://tutorcs.com>

Hash functions: randomised hashing

程序代写代做 CS编程辅导

Solution:

- Randomise your hash function randomly in a way that is independent of the keys that are actually going to be stored.



WeChat: cstutorcs

Assignment Project Exam Help

- In this way no single input always invokes worst case performance!
- Guarantees good performance on average over many runs of your program, no matter what keys adversary chooses.

QQ: 749389476

<https://tutorcs.com>

Hash functions: randomised hashing

程序代写代做 CS编程辅导

Solution:

- Randomise your hash function
- Pick a hash function randomly in a way that is independent of the keys that are actually going to be stored.



WeChat: **tutorcs**

Assignment Project Exam Help

- In this way no single input always invokes worst case performance!
- Guarantees good performance on average over many runs of your program, no matter what keys adversary chooses.

QQ: 749389476

<https://tutorcs.com>

Hash functions: randomised hashing

程序代写代做 CS编程辅导

Solution:

- Randomise your hash function
- Pick a hash function randomly in a way that is independent of the keys that are actually going to be stored.



WeChat: **tutorcs**

Assignment Project Exam Help

- In this way no single input always evokes worst case performance!
- Guarantees good performance on average over many runs of your program, no matter what keys adversary chooses.

QQ: 749389476

<https://tutorcs.com>

Hash functions: randomised hashing

程序代写代做 CS编程辅导

Solution:

- Randomise your hash function
- Pick a hash function randomly in a way that is independent of the keys that are actually going to be stored.



WeChat: **tutorcs**

Assignment Project Exam Help

- In this way no single input always evokes worst case performance!
- Guarantees good performance on average over many runs of your program, no matter what keys adversary chooses.

QQ: 749389476

<https://tutorcs.com>

Towards randomised hashing: universal families of hash functions

程序代写代做 CS编程辅导



- Let H be a (finite) collection of hash functions that map a given universe U of keys into the (much smaller) range $\{0, 1, \dots, m - 1\}$;

WeChat: cstutorcs

- H is said to be universal if:

Assignment Project Exam Help

- for each pair of distinct keys $x, y \in U$, the number of hash functions $h \in H$ for which $h(x) = h(y)$ is $\frac{1}{m}$.

Email: tutorcs@163.com

- In other words: if you take any two keys x and y and if you randomly pick a hash function from H , the chance of a collision between x and y is $\frac{1}{m}$ and it is equal to $1/m$.

QQ: 749389476

<https://tutorcs.com>

Towards randomised hashing: universal families of hash functions

程序代写代做 CS编程辅导



- Let H be a (finite) collection of hash functions that map a given universe U of keys into the (much smaller) range $\{0, 1, \dots, m - 1\}$;

WeChat: cstutorcs

- H is said to be **universal** if:

Assignment Project Exam Help

- for each pair of distinct keys $x, y \in U$, the number of hash functions $h \in H$ for which $h(x) = h(y)$ is $\frac{1}{m}$.

Email: tutorcs@163.com

- In other words: if you take any two keys x and y and if you randomly pick a hash function from H , the chance of a collision between x and y is $\frac{1}{m}$ and it is equal to $1/m$.

QQ: 749389476

<https://tutorcs.com>

Towards randomised hashing: universal families of hash functions

程序代写代做 CS编程辅导



- Let H be a (finite) family of hash functions that map a given universe U of keys into the (much smaller) range $\{0, 1, \dots, m - 1\}$;

WeChat: cstutorcs

- H is said to be **universal** if:

Assignment Project Exam Help

- for each pair of distinct keys $x, y \in U$, the number of hash functions $h \in H$ for which $h(x) = h(y)$ is $|H|/m$.
- In other words: if you take any two keys x and y and if you randomly pick a hash function from H , the chance of a collision between x and y is <https://tutorcs.com> and it is equal to $1/m$.

Towards randomised hashing: universal families of hash functions

程序代写代做 CS编程辅导



- Let H be a (finite) family of hash functions that map a given universe U of keys into the (much smaller) range $\{0, 1, \dots, m - 1\}$;

WeChat: cstutorcs

- H is said to be **universal** if:

Assignment Project Exam Help

- for each pair of distinct keys $x, y \in U$, the number of hash functions $h \in H$ for which $h(x) = h(y)$ is $|H|/m$.
- In other words: if you take any two keys x and y and if you randomly pick a hash function from H , the chance of a collision between x and y is the same for all x and y and it is equal to $1/m$.

QQ: 749389476

<https://tutorgs.com>

Universal hashing

程序代写代做 CS编程辅导

- Assume a family of hash functions H is universal.

- Let $x, y \in U$ be keys. For a randomly chosen $h \in H$ let the random variable c_{xy} be defined by $c_{xy} = 1$ if the keys x and y collide under h , $c_{xy} = h(y) - h(x)$, and $c_{xy} = 0$ otherwise.



- Fix x ; then, by universal family, the expected value $E[c_{xy}]$ satisfies

Assignment Project Exam Help

$$E[c_{xy}] = P(h(y) = h(x)) \cdot 1 + P(h(y) \neq h(x)) \cdot 0$$

Email: tutorcs@163.com

$$= \frac{1}{|H|} \cdot 1 + \left(1 - \frac{1}{|H|}\right) \cdot 0$$

QQ: 749389476

$$= \frac{1}{m} \cdot 1 + \left(1 - \frac{1}{m}\right) \cdot 0$$

<https://tutorcs.com>

$$= \frac{1}{m}$$

Universal hashing

程序代写代做 CS编程辅导

- Assume a family of hash functions H is universal.

- Let $x, y \in U$ be keys. For a randomly chosen $h \in H$ let the random variable c_{xy} be defined by $c_{xy} = 1$ if the keys x and y collide under h , $c_{xy} = h(y) - h(x)$, and $c_{xy} = 0$ otherwise.

- Fix x ; then, by universality, the expected value $E[c_{xy}]$ satisfies

Assignment Project Exam Help

$$E[c_{xy}] = P(h(y) = h(x)) \cdot 1 + P(h(y) \neq h(x)) \cdot 0$$

Email: tutorcs@163.com

$$= \frac{|H|/m}{|H|} \cdot 1 + \left(1 - \frac{|H|/m}{|H|}\right) \cdot 0$$

QQ: 749389476

$$= \frac{1}{m} \cdot 1 + \left(1 - \frac{1}{m}\right) \cdot 0$$

<https://tutorcs.com>

$$= \frac{1}{m}$$

Universal hashing

程序代写代做 CS编程辅导

- Assume a family of hash functions H is universal.

- Let $x, y \in U$ be keys. For a randomly chosen $h \in H$ let the random variable c_{xy} be defined by $c_{xy} = 1$ if the keys x and y collide under h , $c_{xy} = h(y) - h(x)$, and $c_{xy} = 0$ otherwise.

- Fix x ; then, by definition of a universal family, the expected value $E[c_{xy}]$ satisfies

Assignment Project Exam Help

$$E[c_{xy}] = P(h(y) = h(x)) \cdot 1 + P(h(y) \neq h(x)) \cdot 0$$

Email: tutorcs@163.com

$$= \frac{|H|/m}{|H|} \cdot 1 + \left(1 - \frac{|H|/m}{|H|}\right) \cdot 0$$

QQ: 749389476

$$= \frac{1}{m} \cdot 1 + \left(1 - \frac{1}{m}\right) \cdot 0$$

<https://tutorcs.com>

$$= \frac{1}{m}$$

Universal hashing

程序代写代做 CS编程辅导

- Assume a family of hash functions H is universal.

- Let $x, y \in U$ be keys. For a randomly chosen $h \in H$ let the random variable c_{xy} be defined by $c_{xy} = 1$ if the keys x and y collide under h , $c_{xy} = h(y) - h(x)$, and $c_{xy} = 0$ otherwise.

- Fix x ; then, by definition of a universal family, the expected value $E[c_{xy}]$ satisfies

Assignment Project Exam Help

$$E[c_{xy}] = P(h(y) = h(x)) \cdot 1 + P(h(y) \neq h(x)) \cdot 0$$

$$= \frac{|H|/m}{|H|} \cdot 1 + \left(1 - \frac{|H|/m}{|H|}\right) \cdot 0$$

Email: tutorcs@163.com

QQ: 749389476

$$= \frac{1}{m} \cdot 1 + \left(1 - \frac{1}{m}\right) \cdot 0$$

<https://tutorcs.com>

$$= \frac{1}{m}$$

Universal hashing

- Assume that a family of hash functions H is universal, and assume that we are hashing n keys into a hash table of size m .



- Let C_x be total number of collisions involving key x , i.e., let

$$C_x = \sum_{y \neq x} c_{yx}$$

WeChat: cstutorcs

- Then the expected value $E[C_x]$ satisfies

Assignment Project Exam Help

$$E[C_x] = \sum_{y \neq x} P_{xy} = \frac{n-1}{m} \quad (1)$$

Email: tutorcs@163.com

QQ: 749389476

- Consequently, if $n \leq m$ then the expected total number of collisions involving any particular key x is less than 1.
- By the Markov inequality the probability that any particular slot of the hash table has lots of elements in it is small!

Universal hashing

- Assume that a family of hash functions H is universal, and assume that we are hashing n keys into a hash table of size m .



- Let C_x be total number of collisions involving key x , i.e., let

$$C_x = \sum_{y \neq x} c_{yx}$$

WeChat: cstutorcs

- Then the expected value $E[C_x]$ satisfies

Assignment Project Exam Help

$$E[C_x] = \sum_{y \neq x} P[y \text{ collides with } x] = \frac{n-1}{m} \quad (1)$$

Email: tutorcs@163.com

QQ: 749389476

- Consequently, if $n \leq m$ then the expected total number of collisions involving any particular key x is less than 1.

- By the Markov inequality the probability that any particular slot of the hash table has lots of elements in it is small!

Universal hashing

- Assume that a family of hash functions H is universal, and assume that we are hashing n keys into a hash table of size m .



- Let C_x be total number of collisions involving key x , i.e., let

$$C_x = \sum_{y \neq x} c_{yx}$$

WeChat: cstutorcs

- Then the expected value $E[C_x]$ satisfies

Assignment Project Exam Help

$$\text{Email: tutorcs@163.com} \quad \sum_{y \neq x} \Pr[y \rightarrow x] = \frac{n-1}{m} \quad (1)$$

QQ: 749389476

- Consequently, if $n \leq m$ then the expected total number of collisions involving any particular key x is less than 1.

- By the Markov inequality the probability that any particular slot of the hash table has lots of elements in it is small!

Universal hashing

- Assume that a family of hash functions H is universal, and assume that we are hashing n keys into a hash table of size m .



- Let C_x be total number of collisions involving key x , i.e., let

$$C_x = \sum_{y \neq x} c_{yx}$$

WeChat: cstutorcs

- Then the expected value $E[C_x]$ satisfies

Assignment Project Exam Help

$$E[C_x] = \sum_{y \neq x} E[c_{yx}] = \frac{n-1}{m} \quad (1)$$

Email: tutorcs@163.com

QQ: 749389476

- Consequently, if $n \leq m$ then the expected total number of collisions involving any particular key x is less than 1.
- By the Markov inequality the probability that any particular slot of the hash table has lots of elements in it is small!

Universal hashing

- Assume that a family of hash functions H is universal, and assume that we are hashing n keys into a hash table of size m .



- Let C_x be total number of collisions involving key x , i.e., let

$$C_x = \sum_{y \neq x} c_{yx}$$

WeChat: cstutorcs

- Then the expected value $E[C_x]$ satisfies

Assignment Project Exam Help

$$E[C_x] = \sum_{y \neq x} E[c_{yx}] = \frac{n-1}{m} \quad (1)$$

Email: tutorcs@163.com

QQ: 749389476

- Consequently, if $n \leq m$ then the expected total number of collisions involving any particular key x is less than 1.

- By the Markov inequality the probability that any particular slot of the hash table has lots of elements in it is small!

Designing a universal family of hash Functions

- Choose the size m of the hash table to be a prime number.



- Let r be such that $m^r \leq |U| < m^{r+1}$, i.e. $r = \lfloor \log_m |U| \rfloor$.
- Represent each key U as a vector of m , i.e., let $\vec{x} = (x_0, x_1, \dots, x_r)$ be such that $0 \leq x_i < m$ for all i such that $0 \leq i \leq r$ and such that

WeChat: cstutorcs

Assignment Project Exam Help
$$x = \sum_{i=0}^r x_i m^i$$

Email: tutorcs@163.com

- Let $\vec{a} = (a_0, a_1, \dots, a_r)$ be a vector of $r + 1$ randomly chosen elements from the set $\{0, 1, 2, \dots, m - 1\}$

https://tutorcs.com $h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m$

- Define a corresponding hash function $h_{\vec{a}}(x) = \langle \vec{x}, \vec{a} \rangle \bmod m$, where $\langle \vec{x}, \vec{a} \rangle$ denotes the dot product of vectors \vec{x} and \vec{a} (also called the scalar product).

Designing a universal family of hash Functions

- Choose the size m of the hash table to be a prime number.

- Let r be such that $|U|$ of the universe U of all keys satisfies $m^r \leq |U| < m^{r+1}$, i.e. $r = \lfloor \log_m |U| \rfloor$.
- Represent each key $x \in U$ as a vector of length m , i.e., let $\vec{x} = (x_0, x_1, \dots, x_r)$ be such that $0 \leq x_i < m$ for all i such that $0 \leq i \leq r$ and such that



WeChat: cstutorcs

Assignment Project Exam Help
$$x = \sum_{i=0}^r x_i m^i$$

Email: tutorcs@163.com

- Let $\vec{a} = (a_0, a_1, \dots, a_r)$ be a vector of $r + 1$ randomly chosen elements from the set $\{0, 1, 2, \dots, m - 1\}$

- Define a corresponding hash function $h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m$
- Note that $h_{\vec{a}}(x) = \langle \vec{x}, \vec{a} \rangle \bmod m$, where $\langle \vec{x}, \vec{a} \rangle$ denotes the dot product of vectors \vec{x} and \vec{a} (also called the scalar product).

Designing a universal family of hash Functions

- Choose the size m of the hash table to be a prime number.
- Let r be such that $|U|$ of the universe U of all keys satisfies $m^r \leq |U| < m^{r+1}$, i.e. $r = \lfloor \log_m |U| \rfloor$.
- Represent each key $x \in U$ as a vector of length m , i.e., let $\vec{x} = (x_0, x_1, \dots, x_r)$ be such that $0 \leq x_i < m$ for all i such that $0 \leq i \leq r$ and such that



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

- Let $\vec{a} = (a_0, a_1, \dots, a_r)$ be a vector of $r + 1$ randomly chosen elements from the set $\{0, 1, 2, \dots, m - 1\}$
- Define a corresponding hash function $h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m$
- Note that $h_{\vec{a}}(x) = \langle \vec{x}, \vec{a} \rangle \bmod m$, where $\langle \vec{x}, \vec{a} \rangle$ denotes the dot product of vectors \vec{x} and \vec{a} (also called the scalar product).

Designing a universal family of hash Functions

- Choose the size m of the hash table to be a prime number.
- Let r be such that $|U|$ of the universe U of all keys satisfies $m^r \leq |U| < m^{r+1}$, i.e. $r = \lfloor \log_m |U| \rfloor$.
- Represent each key $x \in U$ as a vector of length m , i.e., let $\vec{x} = (x_0, x_1, \dots, x_r)$ be such that $0 \leq x_i < m$ for all i such that $0 \leq i \leq r$ and such that



WeChat: cstutorcs

$$x = \sum_{i=0}^r x_i m^i$$

Email: tutorcs@163.com

- Let $\vec{a} = (a_0, a_1, \dots, a_r)$ be a vector of $r + 1$ randomly chosen elements from the set $\{0, 1, 2, \dots, m - 1\}$

- Define a corresponding hash function $h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m$
- Note that $h_{\vec{a}}(x) = \langle \vec{x}, \vec{a} \rangle \bmod m$, where $\langle \vec{x}, \vec{a} \rangle$ denotes the dot product of vectors \vec{x} and \vec{a} (also called the scalar product).

Designing a universal family of hash Functions

- Choose the size m of the hash table to be a prime number.
- Let r be such that $m^r \leq |U| < m^{r+1}$, i.e. $r = \lfloor \log_m |U| \rfloor$.
- Represent each key $x \in U$ as a vector of length $r+1$, i.e., let $\vec{x} = (x_0, x_1, \dots, x_r)$ be such that $0 \leq x_i < m$ for all i such that $0 \leq i \leq r$ and such that
WeChat: cstutorcs
$$x = \sum_{i=0}^r x_i m^i$$
- Let $\vec{a} = (a_0, a_1, \dots, a_r)$ be a vector of $r+1$ randomly chosen elements from the set $\{0, 1, \dots, m-1\}$
QQ: 749389476
- Define a corresponding hash function $h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m$
- Note that $h_{\vec{a}}(x) = \langle \vec{x}, \vec{a} \rangle \bmod m$, where $\langle \vec{x}, \vec{a} \rangle$ denotes the dot product of vectors \vec{x} and \vec{a} (also called the scalar product).

Designing a universal family of hash Functions

- Choose the size m of the hash table to be a prime number.
- Let r be such that $|U|$ of the universe U of all keys satisfies $m^r \leq |U| < m^{r+1}$, i.e. $r = \lfloor \log_m |U| \rfloor$.
- Represent each key $x \in U$ as a vector of length m , i.e., let $\vec{x} = (x_0, x_1, \dots, x_r)$ be such that $0 \leq x_i < m$ for all i such that $0 \leq i \leq r$ and such that



WeChat: cstutorcs

$$x = \sum_{i=0}^r x_i m^i$$

Email: tutorcs@163.com

- Let $\vec{a} = (a_0, a_1, \dots, a_r)$ be a vector of $r + 1$ **randomly chosen** elements from the set $\{0, 1, \dots, m - 1\}$
- Define a corresponding hash function $h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m$
- Note that $h_{\vec{a}}(x) = \langle \vec{x}, \vec{a} \rangle \bmod m$, where $\langle \vec{x}, \vec{a} \rangle$ denotes the dot product of vectors \vec{x} and \vec{a} (also called the scalar product).

Designing a universal family of hash Functions

- Choose the size m of the hash table to be a prime number.
- Let r be such that $|U|$ of the universe U of all keys satisfies $m^r \leq |U| < m^{r+1}$, i.e. $r = \lfloor \log_m |U| \rfloor$.
- Represent each key $x \in U$ as a vector of length m , i.e., let $\vec{x} = (x_0, x_1, \dots, x_r)$ be such that $0 \leq x_i < m$ for all i such that $0 \leq i \leq r$ and such that



WeChat: cstutorcs

$$x = \sum_{i=0}^r x_i m^i$$

Email: tutorcs@163.com

- Let $\vec{a} = (a_0, a_1, \dots, a_r)$ be a vector of $r + 1$ **randomly chosen** elements from the set $\{0, 1, \dots, m - 1\}$
- Define a corresponding hash function $h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m$
- Note that $h_{\vec{a}}(x) = \langle \vec{x}, \vec{a} \rangle \bmod m$, where $\langle \vec{x}, \vec{a} \rangle$ denotes the dot product of vectors \vec{x} and \vec{a} (also called the scalar product).

Proving universality of family of hash functions $h_{\vec{a}}$

- Assume x, y are two distinct keys.
- Let the corresponding sequences be (x_0, x_1, \dots, x_r) and (y_0, y_1, \dots, y_r) ;
- then



$$h_{\vec{a}}(x) = h_{\vec{a}}(y) \Leftrightarrow \sum_{i=0}^r x_i a_i \equiv \sum_{i=0}^r y_i a_i \pmod{m}$$

WeChat: cstutorcs
Assignment Project Exam Help
 $\Leftrightarrow \sum_{i=0}^r (x_i - y_i) a_i \equiv 0 \pmod{m}$
Email: tutorcs@163.com

- since $x \neq y$ there is $k \in \{0, 1, \dots, r\}$ such that $x_k \neq y_k$;
- let us assume that $x_0 \neq y_0$.

$$\text{then } (x_0 - y_0) a_0 = - \sum_{i=1}^r (x_i - y_i) a_i \pmod{m}$$

Proving universality of family of hash functions $h_{\vec{a}}$

- Assume x, y are two distinct keys.
- Let the corresponding sequences be (x_0, x_1, \dots, x_r) and (y_0, y_1, \dots, y_r) ;
- then



$$h_{\vec{a}}(x) = h_{\vec{a}}(y) \Leftrightarrow \sum_{i=0}^r x_i a_i \equiv \sum_{i=0}^r y_i a_i \pmod{m}$$

WeChat: cstutorcs
Assignment Project Exam Help
 $\Leftrightarrow \sum_{i=0}^r (x_i - y_i) a_i \equiv 0 \pmod{m}$

Email: tutorcs@163.com

- since $x \neq y$ there is k such that $x_k \neq y_k$;
- let us assume that $x_0 \neq y_0$.

$$\text{then } (x_0 - y_0) a_0 = - \sum_{i=1}^r (x_i - y_i) a_i \pmod{m}$$

Proving universality of family of hash functions $h_{\vec{a}}$

- Assume x, y are two distinct keys.
- Let the corresponding sequences be (x_0, x_1, \dots, x_r) and (y_0, y_1, \dots, y_r) ;
- then



$$h_{\vec{a}}(x) = h_{\vec{a}}(y) \Leftrightarrow \sum_{i=0}^r x_i a_i = \sum_{i=0}^r y_i a_i \pmod{m}$$

WeChat: estutorcs
Assignment Project Exam Help
 $\Leftrightarrow \sum_{i=0}^r (x_i - y_i) a_i = 0 \pmod{m}$
Email: tutorcs@163.com

- since $x \neq y$ there is k such that $x_k \neq y_k$;
- let us assume that $x_0 \neq y_0$.

$$\text{then } (x_0 - y_0) a_0 = - \sum_{i=1}^r (x_i - y_i) a_i \pmod{m}$$

Proving universality of family of hash functions $h_{\vec{a}}$

- Assume x, y are two distinct keys.
- Let the corresponding sequences be (x_0, x_1, \dots, x_r) and (y_0, y_1, \dots, y_r) ;
- then



$$h_{\vec{a}}(x) = h_{\vec{a}}(y) \Leftrightarrow \sum_{i=0}^r x_i a_i = \sum_{i=0}^r y_i a_i \pmod{m}$$

WeChat: estutorcs
Assignment Project Exam Help
 $\Leftrightarrow \sum_{i=0}^r (x_i - y_i) a_i = 0 \pmod{m}$
Email: tutorcs@163.com

- since $x \neq y$ there exists $k \in \mathbb{Z}$ such that $x_k \neq y_k$;
- let us assume that $x_0 \neq y_0$.

$$\text{then } (x_0 - y_0) a_0 = - \sum_{i=1}^r (x_i - y_i) a_i \pmod{m}$$

Proving universality of family of hash functions $h_{\vec{a}}$

- Assume x, y are two distinct keys.
- Let the corresponding sequences be (x_0, x_1, \dots, x_r) and (y_0, y_1, \dots, y_r) ;
- then



$$h_{\vec{a}}(x) = h_{\vec{a}}(y) \Leftrightarrow \sum_{i=0}^r x_i a_i = \sum_{i=0}^r y_i a_i \pmod{m}$$

WeChat: estutorcs
Assignment Project Exam Help
 $\Leftrightarrow \sum_{i=0}^r (x_i - y_i) a_i = 0 \pmod{m}$
Email: tutorcs@163.com

- since $x \neq y$ there exists $k \in \mathbb{Z}$ such that $x_k \neq y_k$;
- let us assume that $x_0 \neq y_0$;
<https://tutorcs.com>

- then $(x_0 - y_0) a_0 = - \sum_{i=1}^r (x_i - y_i) a_i \pmod{m}$

Proving universality of family of hash functions $h_{\vec{a}}$

- Assume x, y are two distinct keys.
- Let the corresponding sequences be (x_0, x_1, \dots, x_r) and (y_0, y_1, \dots, y_r) ;
- then



$$h_{\vec{a}}(x) = h_{\vec{a}}(y) \Leftrightarrow \sum_{i=0}^r x_i a_i = \sum_{i=0}^r y_i a_i \pmod{m}$$

WeChat: estutorcs
Assignment Project Exam Help
 $\Leftrightarrow \sum_{i=0}^r (x_i - y_i) a_i = 0 \pmod{m}$
Email: tutorcs@163.com

- since $x \neq y$ there exists $k \in \mathbb{Z}^+$ such that $x_k \neq y_k$;
- let us assume that $x_0 \neq y_0$;
<https://tutorcs.com>

- then $(x_0 - y_0) a_0 = - \sum_{i=1}^r (x_i - y_i) a_i \pmod{m}$

Universality of family of hash functions $h_{\vec{a}}$ (continued)

程序代写代做 CS编程辅导

- Since m is a prime, every non-zero element $z \in \{0, 1, \dots, m - 1\}$ has a multiplicative inverse z^{-1} , such that $z \cdot z^{-1} = 1 \pmod{m}$;



- since $x_0 - y_0 \neq 0$ we have that

WeChat: cstutorcs

($x_0 - y_0$) $\sum_{i=1}^r (x_i - y_i) a_i \pmod{m}$

Email: tutorcs@163.com

implies

$$a_0 = \left(- \sum_{i=1}^r (x_i - y_i) a_i \right) (x_0 - y_0)^{-1} \pmod{m}$$

QQ: 749389476

<https://tutorcs.com>

Universality of family of hash functions $h_{\vec{a}}$ (continued)

程序代写代做 CS编程辅导

- Since m is a prime, every non-zero element $z \in \{0, 1, \dots, m-1\}$ has a multiplicative inverse z^{-1} , such that $z \cdot z^{-1} = 1 \pmod{m}$;
- since $x_0 - y_0 \neq 0$ we have that

WeChat: cstutorcs

$$(x_0 - y_0)a_0 = - \sum_{i=1}^r (x_i - y_i)a_i \pmod{m}$$

implies

Email: tutorcs@163.com

$$a_0 = \left(- \sum_{i=1}^r (x_i - y_i)a_i \right) (x_0 - y_0)^{-1} \pmod{m}$$

Universality of family of hash functions $h_{\vec{a}}$ (continued)

程序代写代做 CS编程辅导

- However, $a_0 = \left(\frac{y_i - y_0}{x_i - x_0} - y_i \right) a_i \pmod{m}$



implies that

- for any two keys x, y such that $x_0 \neq y_0$
and
- for any randomly chosen τ numbers (t_1, t_2, \dots, t_n)

WeChat: cstutorcs
Assignment Project Exam Help

there exists **exactly one** a_0 (the one given by the above equation)
such that for $\vec{a} = \langle a_0, a_1, \dots, a_n \rangle$ we have

QQ: 749389476

<https://tutorcs.com>

Universality of family of hash functions $h_{\vec{a}}$ (continued)

程序代写代做 CS编程辅导

- Since there are:

- m^r sequences of the form $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$, each of which can uniquely be extended to a sequence $\vec{a}' = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}'}(y)$



- and m^{r+1} sequences of the form $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ in total,

WeChat: cstutorcs

we conclude that the probability to randomly choose a sequence $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$, i.e., such that x and y collide, is equal to

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476 $\frac{m^r}{m^{r+1}} = \frac{1}{m}$

<https://tutorcs.com>

- Thus, the family H is a universal collection of hash functions.

Universality of family of hash functions $h_{\vec{a}}$ (continued)

程序代写代做 CS编程辅导

- Since there are:

- m^r sequences of  $\langle a_1, \dots, a_r \rangle$, each of which can uniquely be extended to a sequence $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$

- and m^{r+1} sequences of the form $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ in total,

WeChat: cstutorcs

we conclude that the probability to randomly choose a sequence $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$, i.e., such that x and y collide, is equal to

Assignment Project Exam Help

Email: **tutorcs@163.com**

QQ: **749389476** $= \frac{m^r}{m^{r+1}} = \frac{1}{m}$

<https://tutorcs.com>

- Thus, the family H is a universal collection of hash functions.

Universality of family of hash functions $h_{\vec{a}}$ (continued)

程序代写代做 CS编程辅导

- Since there are:

- m^r sequences of  $\langle a_1, \dots, a_r \rangle$, each of which can uniquely be extended to a sequence $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$
- and m^{r+1} sequences of the form $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ in total,
WeChat: cstutorcs

we conclude that the probability to randomly choose a sequence $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$, i.e., such that x and y collide, is equal to **Email: tutorcs@163.com**

$$\text{QQ: 749389476} = \frac{m^r}{m^{r+1}} = \frac{1}{m}$$

<https://tutorcs.com>

- Thus, the family H is a universal collection of hash functions.

Universality of family of hash functions $h_{\vec{a}}$ (continued)

程序代写代做 CS编程辅导

- Since there are:

- m^r sequences of  $\langle a_1, \dots, a_r \rangle$, each of which can uniquely be extended to a sequence $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$
- and m^{r+1} sequences of the form $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ in total,
WeChat: cstutorcs

we conclude that the probability to randomly chose a sequence
Assignment Project Exam Help
 $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$, i.e., such that x and y collide, is equal to **Email: tutorcs@163.com**

$$\text{QQ: } 749389476 = \frac{m^r}{m^{r+1}} = \frac{1}{m}$$

<https://tutorcs.com>

- Thus, the family H is a universal collection of hash functions.

Universality of family of hash functions $h_{\vec{a}}$ (continued)

程序代写代做 CS编程辅导

- Since there are:

- m^r sequences of  $\langle a_1, \dots, a_r \rangle$, each of which can uniquely be extended to a sequence $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$
- and m^{r+1} sequences of the form $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ in total,
WeChat: cstutorcs

we conclude that the probability to randomly chose a sequence
Assignment Project Exam Help
 $\vec{a} = \langle a_0, a_1, \dots, a_r \rangle$ such that $h_{\vec{a}}(x) = h_{\vec{a}}(y)$, i.e., such that x and y collide, is equal to **Email: tutorcs@163.com**

$$\text{QQ: } 749389476 = \frac{m^r}{m^{r+1}} = \frac{1}{m}$$

<https://tutorcs.com>

- Thus, the family H is a universal collection of hash functions.

Using universal family of hash functions $h_{\vec{a}}$:

程序代写代做 CS编程辅导

- Pick $r = \lfloor \log_m |U| \rfloor$ such that $m^r \leq |U| < m^{r+1}$;



- For each run, pick function by randomly picking a vector $\vec{a} = (a_0, a_1, \dots, a_r)$ such that $0 \leq a_i < m$ for all i , $0 \leq i \leq r$.
- During each run use the function **WeChat: cstutorcs** all keys.

Assignment Project Exam Help

- Note that the dot (scalar) product $\langle x, a \rangle$ in

Email: **tutorcs@163.com**

$$h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m = \langle x, a \rangle \bmod m;$$

QQ: 749389476
<https://tutorcs.com>

can be computed very fast on modern hardware.

Using universal family of hash functions $h_{\vec{a}}$:

程序代写代做 CS编程辅导

- Pick $r = \lfloor \log_m |U| \rfloor$ such that $m^r \leq |U| < m^{r+1}$;
- For each run, pick function by randomly picking a vector $\vec{a} = (a_0, a_1, \dots, a_r)$ such that $0 \leq a_i < m$ for all i , $0 \leq i \leq r$.
- During each run use the function **WeChat: cstutorcs** all keys.

Assignment Project Exam Help

- Note that the dot product $\langle x, a \rangle$ in

Email: **tutorcs@163.com**

$$h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m = \langle x, a \rangle \bmod m;$$

QQ: 749389476
<https://tutorcs.com>

can be computed very fast on modern hardware.

Using universal family of hash functions $h_{\vec{a}}$:

程序代写代做 CS编程辅导

- Pick $r = \lfloor \log_m |U| \rfloor$ such that $m^r \leq |U| < m^{r+1}$;
- For each run, pick function by randomly picking a vector $\vec{a} = (a_0, a_1, \dots, a_r)$ such that $0 \leq a_i < m$ for all i , $0 \leq i \leq r$.
- During each run use that function on all keys.

Assignment Project Exam Help

- Note that the dot (scalar) product $\langle x, a \rangle$ in

Email: tutorcs@163.com

$$h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m = \langle x, a \rangle \bmod m;$$

QQ: 749389476
<https://tutorcs.com>

can be computed very fast on modern hardware.

Using universal family of hash functions $h_{\vec{a}}$:

程序代写代做 CS编程辅导

- Pick $r = \lfloor \log_m |U| \rfloor$ such that $m^r \leq |U| < m^{r+1}$;
- For each run, pick function by randomly picking a vector $\vec{a} = (a_0, a_1, \dots, a_r)$ such that $0 \leq a_i < m$ for all i , $0 \leq i \leq r$.
- During each run use that function on all keys.

Assignment Project Exam Help

- Note that the dot (scalar) product $\langle x, y \rangle$ in

QQ: 749389476
$$h_{\vec{a}}(x) = \left(\sum_{i=0}^r x_i a_i \right) \bmod m = \langle x, a \rangle \bmod m;$$
<https://tutorcs.com>

can be computed very fast on modern hardware.

Applications of Universal Hash Families: Perfect Hashing

Problem:

程序代写代做 CS编程辅导



- Assume that you need a **static hash table** to store n keys (i.e., a look-up table; no insertions or deletions, just search).

- The size of the table should be **WeChat: cstutorcs** in n .

Assignment Project Exam Help

Email: tutorcs@163.com

- The corresponding hash function should be very efficient to compute.

QQ: 749389476

<https://tutorcs.com>

To get such a table we will employ a randomised design method; however, the resulting hash function will be **completely deterministic**.

Applications of Universal Hash Families: Perfect Hashing

Problem:

程序代写代做 CS编程辅导



- Assume that you need a **static hash table** to store n keys (i.e., a look-up table; no insertions or deletions, just search).

- The size of the table should be linear in n .

- The table should be completely collision free.

Email: tutorcs@163.com

- The corresponding hash function should be very efficient to compute.

QQ: 749389476

<https://tutorcs.com>

To get such a table we will employ a randomised design method; however, the resulting hash function will be **completely deterministic**.

Applications of Universal Hash Families: Perfect Hashing

Problem:

程序代写代做 CS编程辅导



- Assume that you need a **static hash table** to store n keys (i.e., a look-up table; no insertions or deletions, just search).

- The size of the table should be linear in n .

- The table should be completely collision free.

Email: tutorcs@163.com

- The corresponding hash function should be very efficient to compute.

QQ: 749389476

<https://tutorcs.com>

To get such a table we will employ a randomised design method; however, the resulting hash function will be **completely deterministic**.

Applications of Universal Hash Families: Perfect Hashing

Problem:

程序代写代做 CS编程辅导



- Assume that you need a **static hash table** to store n keys (i.e., a look-up table; no insertions or deletions, just search).

- The size of the table should be linear in n .

- The table should be completely collision free.

Email: tutorcs@163.com

- The corresponding hash function should be very efficient to compute.

QQ: 749389476
<https://tutorcs.com>

To get such a table we will employ a randomised design method; however, the resulting hash function will be **completely deterministic**.

Applications of Universal Hash Families: Perfect Hashing

Problem:

程序代写代做 CS编程辅导



- Assume that you need a **static hash table** to store n keys (i.e., a look-up table; no insertions or deletions, just search).

- The size of the table should be linear in n .

- The table should be completely collision free.

Email: tutorcs@163.com

- The corresponding hash function should be very efficient to compute.

QQ: [749389476](#)

<https://tutorcs.com>

To get such a table we will employ a randomised **design method**; however, the resulting hash function will be **completely deterministic**.

Designing a Perfect Hash table

- Method: trial and error procedure will have low probability of many consecutive failures



- First step:

- given n keys we are constructing hash tables of size $m < 2n^2$ using universal hashing;

WeChat: cstutorcs

- probability that such a table is collision free will be $> 1/2$.

Assignment Project Exam Help

- How do we accomplish this? We use a randomised design procedure:

Email: tutorcs@163.com

QQ: 749389476

- We pick the least prime m such that $m > n^2$; then $m < 2n^2$
(Note: for every $x > 1$, there exists a prime m such that $x \leq m < 2x$; here $m > n^2$ because n^2 cannot be prime)

- We pick a random vector \vec{a} and hash all keys using the corresponding hash function $h_{\vec{a}}$ from the universal family

Designing a Perfect Hash table

- **Method:** trial and error procedure with very low probability of many consecutive failures



- First step:

- given n keys we are constructing hash tables of size $m < 2n^2$ using universal hashing;

WeChat: cstutorcs

- probability that such a table is collision free will be $> 1/2$.

Assignment Project Exam Help

- How do we accomplish this? We use a randomised design procedure:

Email: tutorcs@163.com

QQ: 749389476

- We pick the least prime m such that $m > n^2$; then $m < 2n^2$
(Note: for every $x > 1$, there exists a prime m such that $x \leq m < 2x$; here $m > n^2$ because n^2 cannot be prime)

- We pick a random vector \vec{a} and hash all keys using the corresponding hash function $h_{\vec{a}}$ from the universal family

Designing a Perfect Hash table

- **Method:** trial and error procedure with very low probability of many consecutive failures



- **First step:**

- given n keys we are constructing hash tables of size $m < 2n^2$ using universal hashing;

WeChat: cstutorcs

- probability that such a table is collision free will be $> 1/2$.

Assignment Project Exam Help

- How do we accomplish this? We use a randomised design procedure:

Email: tutorcs@163.com

QQ: 749389476

- We pick the least prime m such that $m > n^2$; then $m < 2n^2$
(Note: for every $x > 1$, there exists a prime m such that $x \leq m < 2x$; here $m > n^2$ because n^2 cannot be prime)

- We pick a random vector \vec{a} and hash all keys using the corresponding hash function $h_{\vec{a}}$ from the universal family

Designing a Perfect Hash table

- **Method:** trial and error procedure with very low probability of many consecutive failures



- **First step:**

- given n keys we are constructing hash tables of size $m < 2n^2$ using universal hashing;

WeChat: cstutorcs

- probability that such a table is collision free will be $> 1/2$.

Assignment Project Exam Help

- How do we accomplish this? We use a randomised design procedure:

Email: tutorcs@163.com

QQ: 749389476

- We pick the least prime m such that $m > n^2$; then $m < 2n^2$
(Note: for every $x > 1$, there exists a prime m such that $x \leq m < 2x$; here $m > n^2$ because n^2 cannot be prime)

- We pick a random vector \vec{a} and hash all keys using the corresponding hash function $h_{\vec{a}}$ from the universal family

Designing a Perfect Hash table

- **Method:** trial and error procedure with very low probability of many consecutive failures



- **First step:**

- given n keys we are constructing hash tables of size $m < 2n^2$ using universal hashing;

WeChat: cstutorcs

- probability that such a table is collision free will be $> 1/2$.

Assignment Project Exam Help

- How do we accomplish this? We use a randomised design procedure:

Email: tutorcs@163.com

QQ: 749389476

- We pick the least prime m such that $m > n^2$; then $m < 2n^2$
(Note: for every $x > 1$, there exists a prime m such that $x \leq m < 2x$; here $m > n^2$ because n^2 cannot be prime)

- We pick a random vector \vec{a} and hash all keys using the corresponding hash function $h_{\vec{a}}$ from the universal family

Designing a Perfect Hash table

- **Method:** trial and error procedure with very low probability of many consecutive failures



- **First step:**

- given n keys we are constructing hash tables of size $m < 2n^2$ using universal hashing;

WeChat: cstutorcs

- probability that such a table is collision free will be $> 1/2$.

Assignment Project Exam Help

- How do we accomplish this? We use a randomised design procedure:

Email: tutorcs@163.com

QQ: 749389476

- We pick the least prime m such that $m > n^2$; then $m < 2n^2$ (Note: for every $x > 1$, there exists a prime m such that $x \leq m < 2x$; here $m > n^2$ because n^2 cannot be prime)

- We pick a random vector \vec{a} and hash all keys using the corresponding hash function $h_{\vec{a}}$ from the universal family

Designing a Perfect Hash table

- **Method:** trial and error procedure with very low probability of many consecutive failures



- **First step:**

- given n keys we are constructing hash tables of size $m < 2n^2$ using universal hashing;

WeChat: cstutorcs

- probability that such a table is collision free will be $> 1/2$.

Assignment Project Exam Help

- How do we accomplish this? We use a randomised design procedure:

Email: tutorcs@163.com

QQ: 749389476

- We pick the least prime m such that $m > n^2$; then $m < 2n^2$

(Note: for every $x > 1$ there exists a prime m such that $x \leq m < 2x$; here $m > n^2$ because n^2 cannot be prime)

- We pick a random vector \vec{a} and hash all keys using the corresponding hash function $h_{\vec{a}}$ from the universal family

Designing a Perfect Hash table

- **Method:** trial and error procedure with very low probability of many consecutive failures



- **First step:**

- given n keys we are constructing hash tables of size $m < 2n^2$ using universal hashing;

WeChat: cstutorcs

- probability that such a table is collision free will be $> 1/2$.

Assignment Project Exam Help

- How do we accomplish this? We use a randomised design procedure:

Email: tutorcs@163.com

QQ: 749389476

- We pick the least prime m such that $m > n^2$; then $m < 2n^2$

(Note: for every $x > 1$ there exists a prime m such that $x \leq m < 2x$; here $m > n^2$ because n^2 cannot be prime)

- We pick a random vector \vec{a} and hash all keys using the corresponding hash function $h_{\vec{a}}$ from the universal family,

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Given n keys, there will be $\binom{n}{2}$ pairs of keys.



- By universality of hash functions used, for each pair of keys probability of collision is $\frac{1}{m}$.

- Since $m \geq n^2$ we have $\frac{1}{m} \leq \frac{1}{n^2}$.

WeChat: cstutorcs
Assignment Project Exam Help

- Thus, the expected total number of collisions in the table is at most

$$\binom{n}{2} \frac{1}{m} = \frac{n(n-1)}{2} \frac{1}{n^2} < \frac{1}{2}$$

QQ: 749389476
<https://tutorcs.com>

- Note that if $Y = \sum_{i=1}^j X_i$ then $E(Y) = \sum_{i=1}^j E(X_i)$ regardless of whether variables X_i are independent or not.

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Given n keys, there will be $\binom{n}{2}$ pairs of keys.



- By universality of hash functions used, for each pair of keys probability of collision is $\frac{1}{m}$.

- Since $m \geq n^2$ we have $\frac{1}{m} \leq \frac{1}{n^2}$.

WeChat: cstutorcs
Assignment Project Exam Help

- Thus, the expected total number of collisions in the table is at most

$$\binom{n}{2} \frac{1}{m} = \frac{n(n-1)}{2} \frac{1}{n^2} < \frac{1}{2}$$

QQ: 749389476
<https://tutorcs.com>

- Note that if $Y = \sum_{i=1}^j X_i$ then $E(Y) = \sum_{i=1}^j E(X_i)$ regardless of whether variables X_i are independent or not.

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Given n keys, there will be $\binom{n}{2}$ pairs of keys.



- By universality of hash functions used, for each pair of keys probability of collision is $\frac{1}{m}$.

- Since $m \geq n^2$ we have $\frac{1}{m} \leq \frac{1}{n^2}$.

WeChat: cstutorcs
Assignment Project Exam Help

- Thus, the expected total number of collisions in the table is at most

$$\binom{n}{2} \frac{1}{m} = \frac{n(n-1)}{2} \frac{1}{n^2} < \frac{1}{2}$$

QQ: 749389476
<https://tutorcs.com>

- Note that if $Y = \sum_{i=1}^j X_i$ then $E(Y) = \sum_{i=1}^j E(X_i)$ regardless of whether variables X_i are independent or not.

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Given n keys, there will be $\binom{n}{2}$ pairs of keys.



- By universality of hash functions used, for each pair of keys probability of collision is $\frac{1}{m}$.

- Since $m \geq n^2$ we have $\frac{1}{m} \leq \frac{1}{n^2}$.

WeChat: cstutorcs
Assignment Project Exam Help

- Thus, the expected total number of collisions in the table is at most

QQ: 749389476

$$\binom{n}{2} \frac{1}{m} = \frac{n(n-1)}{2} \frac{1}{n^2} < \frac{1}{2}$$

<https://tutorcs.com>

- Note that if $Y = \sum_{i=1}^j X_i$ then $E(Y) = \sum_{i=1}^j E(X_i)$ regardless of whether variables X_i are independent or not.

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Given n keys, there will be $\binom{n}{2}$ pairs of keys.



- By universality of hash functions used, for each pair of keys probability of collision is $\frac{1}{m}$.

- Since $m \geq n^2$ we have $\frac{1}{m} \leq \frac{1}{n^2}$.

WeChat: cstutorcs
Assignment Project Exam Help

- Thus, the expected total number of collisions in the table is at most

QQ: 749389476

$$\binom{n}{2} \frac{1}{m} = \frac{n(n-1)}{2} \frac{1}{n^2} < \frac{1}{2}$$

<https://tutorcs.com>

- Note that if $Y = \sum_{i=1}^j X_i$ then $E(Y) = \sum_{i=1}^j E(X_i)$ regardless of whether variables X_i are independent or not.

Designing a Perfect Hash table (continued)

- For the given n keys, we have constructed a table of size $m < 2n^2$, such that the expected total number of collisions is $< 1/2$.



- Let X be the random variable equal to the number of collisions in thus constructed table.
- By the Markov Inequality with $t = 1$ we now get that

WeChat: cstutorcs
 $P\{X \geq 1\} \leq \frac{E[X]}{1} \leq \frac{1}{2}$
Assignment Project Exam Help

Email: tutorcs@163.com

- Thus, if we keep picking hash functions at random from a universal family, the probability that there will be at least one collision in each of k consecutive attempts (i.e., that $X \geq 1$ in each attempt) is smaller than $(1/2)^k$, which rapidly tends to 0.

- Consequently, after a few random trial-and-error attempts we will obtain a collision free hash table of size $< 2n^2$.

Designing a Perfect Hash table (continued)

- For the given n keys, we have constructed a table of size $m < 2n^2$, such that the expected total number of collisions is $< 1/2$.



- Let X be the random variable equal to the number of collisions in thus constructed table.
- By the Markov Inequality with $t = 1$ we now get that

WeChat: cstutorcs

$P\{X \geq 1\} \leq \frac{E[X]}{1} \leq \frac{1}{2}$

Assignment Project Exam Help

Email: tutorcs@163.com

- Thus, if we keep picking hash functions at random from a universal family, the probability that there will be at least one collision in each of k consecutive attempts (i.e., that $X \geq 1$ in each attempt) is smaller than $(1/2)^k$, which rapidly tends to 0.

- Consequently, after a few random trial-and-error attempts we will obtain a collision free hash table of size $< 2n^2$.

Designing a Perfect Hash table (continued)

- For the given n keys, we have constructed a table of size $m < 2n^2$, such that the expected total number of collisions is $< 1/2$.



- Let X be the random variable equal to the number of collisions in thus constructed table.
- By the Markov Inequality with $t = 1$ we now get that

WeChat: cstutorcs
Assignment Project Exam Help

$$P\{X \geq 1\} \leq \frac{E[X]}{1} \leq \frac{1}{2}$$

Email: tutorcs@163.com

- Thus, if we keep picking hash functions at random from a universal family, the probability that there will be at least one collision in each of k consecutive attempts (i.e., that $X \geq 1$ in each attempt) is smaller than $(1/2)^k$, which rapidly tends to 0.
- Consequently, after a few random trial-and-error attempts we will obtain a collision free hash table of size $< 2n^2$.

Designing a Perfect Hash table (continued)

- For the given n keys, we have constructed a table of size $m < 2n^2$, such that the expected total number of collisions is $< 1/2$.



- Let X be the random variable equal to the number of collisions in thus constructed table.
- By the Markov Inequality with $t = 1$ we now get that

WeChat: cstutorcs
 $P\{X \geq 1\} \leq \frac{E[X]}{1} \leq \frac{1}{2}$
Assignment Project Exam Help

- Thus, if we keep picking hash functions at random from a universal family, the probability that there will be at least one collision in each of k consecutive attempts (i.e., that $X \geq 1$ in each attempt) is smaller than $(1/2)^k$, which rapidly tends to 0.
- Consequently, after a few random trial-and-error attempts we will obtain a collision free hash table of size $< 2n^2$.

Designing a Perfect Hash table (continued)

- For the given n keys, we have constructed a table of size $m < 2n^2$, such that the expected total number of collisions is $< 1/2$.



- Let X be the random variable equal to the number of collisions in thus constructed table.
- By the Markov Inequality with $t = 1$ we now get that

WeChat: cstutorcs
 $P\{X \geq 1\} \leq \frac{E[X]}{1} \leq \frac{1}{2}$
Assignment Project Exam Help

- Thus, if we keep picking hash functions at random from a universal family, the probability that there will be at least one collision in each of k consecutive attempts (i.e., that $X \geq 1$ in each attempt) is smaller than $(1/2)^k$, which rapidly tends to 0.
- Consequently, after a few random trial-and-error attempts we will obtain a collision free hash table of size $< 2n^2$.

Designing a Perfect Hash table (continued)

程序代写代做 CS 编程辅导

- How many trials N do we expect to have to make before we hit a collision free hash? 

- Let the probability  be denoted by p ; then $p < 1/2$, and the probability of a success is $1 - p$.

WeChat: cstutorcs

- Thus,

Assignment Project Exam Help

$$\begin{aligned} E[N] &= 1 \cdot (1 - p) + 2 \cdot (1 - p)^2 + 3 \cdot p^2(1 - p) + 4 \cdot p^3(1 - p) + \dots \\ &= (1 - p)(1 + 2p + 3p^2 + 4p^3 + \dots) \end{aligned}$$

QQ: 749389476

<https://tutorcs.com>

- We have already shown that $1 + 2p + 3p^2 + 4p^3 + \dots = \frac{1}{(1-p)^2}$.
- Thus, $E[N] = \frac{1}{1-p}$; since $p < 1/2$ we get $E[N] < 2$.

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- How many trials N do we expect to have to make before we hit a collision free hash? 

- Let the probability  be denoted by p ; then $p < 1/2$, and the probability of a success is $1 - p$.

WeChat: cstutorcs

- Thus,

Assignment Project Exam Help

$$\begin{aligned}E[N] &= 1 \cdot (1 - p) + 2 \cdot (1 - p)^2 + 3 \cdot p^2(1 - p) + 4 \cdot p^3(1 - p) + \dots \\&= (1 - p)(1 + 2p + 3p^2 + 4p^3 + \dots)\end{aligned}$$

QQ: 749389476

<https://tutorcs.com>

- We have already shown that $1 + 2p + 3p^2 + 4p^3 + \dots = \frac{1}{(1-p)^2}$.
- Thus, $E[N] = \frac{1}{1-p}$; since $p < 1/2$ we get $E[N] < 2$.

Designing a Perfect Hash table (continued)

程序代写代做 CS 编程辅导

- How many trials N do we expect to have to make before we hit a collision free hash? 

- Let the probability  be denoted by p ; then $p < 1/2$, and the probability of a success is $1 - p$.

WeChat: cstutorcs

- Thus,

Assignment Project Exam Help

$$\begin{aligned} E[N] &= 1 \cdot (1 - p) + 2 \cdot p(1 - p) + 3 \cdot p^2(1 - p) + 4 \cdot p^3(1 - p) + \dots \\ &= (1 - p)(1 + 2p + 3p^2 + 4p^3 + \dots) \end{aligned}$$

<https://tutorcs.com>

- We have already shown that $1 + 2p + 3p^2 + 4p^3 + \dots = \frac{1}{(1-p)^2}$.
- Thus, $E[N] = \frac{1}{1-p}$; since $p < 1/2$ we get $E[N] < 2$.

Designing a Perfect Hash table (continued)

程序代写代做 CS 编程辅导

- How many trials N do we expect to have to make before we hit a collision free hash? 



- Let the probability  be denoted by p ; then $p < 1/2$, and the probability of a success is $1 - p$.

WeChat: cstutorcs

- Thus,

Assignment Project Exam Help

$$\begin{aligned}E[N] &= 1 \cdot (1 - p) + 2 \cdot p(1 - p) + 3 \cdot p^2(1 - p) + 4 \cdot p^3(1 - p) + \dots \\&= (1 - p)(1 + 2p + 3p^2 + 4p^3 + \dots)\end{aligned}$$

<https://tutorcs.com>

- We have already shown that $1 + 2p + 3p^2 + 4p^3 + \dots = \frac{1}{(1-p)^2}$.
- Thus, $E[N] = \frac{1}{1-p}$; since $p < 1/2$ we get $E[N] < 2$.

Designing a Perfect Hash table (continued)

程序代写代做 CS 编程辅导

- How many trials N do we expect to have to make before we hit a collision free hash? 



- Let the probability  be denoted by p ; then $p < 1/2$, and the probability of a success is $1 - p$.

WeChat: cstutorcs

- Thus,

Assignment Project Exam Help

$$\begin{aligned}E[N] &= 1 \cdot (1 - p) + 2 \cdot p(1 - p) + 3 \cdot p^2(1 - p) + 4 \cdot p^3(1 - p) + \dots \\&= (1 - p)(1 + 2p + 3p^2 + 4p^3 + \dots)\end{aligned}$$

<https://tutorcs.com>

- We have already shown that $1 + 2p + 3p^2 + 4p^3 + \dots = \frac{1}{(1-p)^2}$.
- Thus, $E[N] = \frac{1}{1-p}$; since $p < 1/2$ we get $E[N] < 2$.

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Thus, on average, I two trials will be enough to obtain a collision free table $\lceil \frac{2n^2}{M} \rceil$.



- Recall that we aim to produce a collision free hash table of size linear in n for storing n keys.

WeChat: estutores
Assignment Project Exam Help

- Second step: Choose M to be the smallest prime larger than n .
Email: tutorcs@163.com
- Thus $n \leq M < 2n$; we now produce a hash table of size M again by choosing randomly from a universal family of hash functions.
QQ: 749389476
<https://tutorcs.com>

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Thus, on average, I two trials will be enough to obtain a collision free table $\lceil \frac{2n^2}{M} \rceil$.



- Recall that we aim to produce a collision free hash table of size linear in n for storing n keys.

WeChat: estutores
Assignment Project Exam Help

- **Second step:** Choose M to be the smallest prime larger than n .

- Thus $n \leq M < 2n$; we now produce a hash table of size M again by choosing randomly from a universal family of hash functions.
<https://tutorcs.com>

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Thus, on average, I two trials will be enough to obtain a collision free table $\lceil \frac{2n^2}{M} \rceil$.



- Recall that we aim to produce a collision free hash table of size linear in n for storing n keys.

WeChat: estutores
Assignment Project Exam Help

- **Second step:** Choose M to be the smallest prime larger than n .

- Thus $n \leq M < 2n$; we now produce a hash table of size M again by choosing randomly from a universal family of hash functions.

QQ: 749389476

Email: tutorcs@163.com

Designing a Perfect Hash table (continued)

- Assume that a slot i of this table has n_i many elements.
- We will hash these n_i elements into a secondary hash table of size $m_i < 2n_i^2$.
- We have to guarantee that the sum total of sizes of all secondary hash tables, i.e., $\sum_{i=1}^M m_i$ is linear in n .



WeChat: cstutorcs
Assignment Project Exam Help

- Note that

$$\binom{n_i}{2} = \frac{n_i(n_i - 1)}{2} = \frac{n_i^2}{2} - \frac{n_i}{2}$$

QQ: 749389476

- Thus, since n_i is the number of elements in the i^{th} slot, we get

$$\sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + \sum_{i=1}^M n_i = 2 \sum_{i=1}^M \binom{n_i}{2} + n \quad (2)$$

Designing a Perfect Hash table (continued)

- Assume that a slot i of this table has n_i many elements.
- We will hash these  elements into a secondary hash table of size $m_i < 2n_i^2$.
- We have to guarantee that the sum total of sizes of all secondary hash tables, i.e., $\sum_{i=1}^M m_i$ is linear in n .

WeChat: cstutorcs
Assignment Project Exam Help

- Note that

$$\binom{n_i}{2} = \frac{n_i(n_i - 1)}{2} = \frac{n_i^2}{2} - \frac{n_i}{2}$$

QQ: 749389476

- Thus, since n_i is the number of elements in the i^{th} slot, we get

$$\sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + \sum_{i=1}^M n_i = 2 \sum_{i=1}^M \binom{n_i}{2} + n \quad (2)$$

Designing a Perfect Hash table (continued)

- Assume that a slot i of this table has n_i many elements.
- We will hash these  elements into a secondary hash table of size $m_i < 2n_i^2$.
- We have to guarantee that the sum total of sizes of all secondary hash tables, i.e., $\sum_{i=1}^M m_i$ is linear in n .
WeChat: cstutorcs
Assignment Project Exam Help

- Note that

$$\binom{n_i}{2} = \frac{n_i(n_i - 1)}{2} = \frac{n_i^2}{2} - \frac{n_i}{2}$$

QQ: 749389476

- Thus, since n_i is the number of elements in the i^{th} slot, we get

$$\sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + \sum_{i=1}^M n_i = 2 \sum_{i=1}^M \binom{n_i}{2} + n \quad (2)$$

Designing a Perfect Hash table (continued)

- Assume that a slot i of this table has n_i many elements.
- We will hash these  elements into a secondary hash table of size $m_i < 2n_i^2$.
- We have to guarantee that the sum total of sizes of all secondary hash tables, i.e., $\sum_{i=1}^M m_i$ is linear in n .

WeChat: cstutorcs
Assignment Project Exam Help

- Note that

$$\binom{n_i}{2} = \frac{n_i(n_i-1)}{2} = \frac{n_i^2}{2} - \frac{n_i}{2}$$

QQ: 749389476

- Thus, since n_i is the number of elements in the i^{th} slot, we get

$$\sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + \sum_{i=1}^M n_i = 2 \sum_{i=1}^M \binom{n_i}{2} + n \quad (2)$$

Designing a Perfect Hash table (continued)

- Assume that a slot i of this table has n_i many elements.
- We will hash these  elements into a secondary hash table of size $m_i < 2n_i^2$.
- We have to guarantee that the sum total of sizes of all secondary hash tables, i.e., $\sum_{i=1}^M m_i$ is linear in n .

WeChat: cstutorcs
Assignment Project Exam Help

- Note that

$$\binom{n_i}{2} = \frac{n_i(n_i - 1)}{2} = \frac{n_i^2}{2} - \frac{n_i}{2}$$

QQ: 749389476

- Thus, since n_i is the <https://tutorcs.com> in the i^{th} slot, we get

$$\sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + \sum_{i=1}^M n_i = 2 \sum_{i=1}^M \binom{n_i}{2} + n \quad (2)$$

$$\text{Total size of tables: } \sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + n$$

程序代写代做 CS编程辅导

- However, $\binom{n_i}{2}$ is the number of collisions in slot i ;
- thus, $\sum_{i=1}^M \binom{n_i}{2}$ is the total number of collisions in the hash table.

- Since there are $\binom{n}{2}$ pairs of keys and for each pair of keys the probability of a collision with universal hashing is $1/M$, we obtain that the expected total number of collisions is $\binom{n}{2} \frac{1}{M}$.

Email: tutorcs@163.com

Thus,

$$E \left[\sum_{i=1}^M \binom{n_i}{2} \right] = \binom{n}{2} \frac{1}{M} = \frac{n(n-1)}{2M} \quad (3)$$

$$\text{Total size of tables: } \sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + n$$

程序代写代做 CS编程辅导

- However, $\binom{n_i}{2}$ is the number of collisions in slot i ;
- thus, $\sum_{i=1}^M \binom{n_i}{2}$ is the total number of collisions in the hash table.

- Since there are $\binom{n}{2}$ pairs of keys and for each pair of keys the probability of a collision with universal hashing is $1/M$, we obtain that the expected total number of collisions is $\binom{n}{2} \frac{1}{M}$.

Email: tutorcs@163.com

Thus,

$$E \left[\sum_{i=1}^M \binom{n_i}{2} \right] = \binom{n}{2} \frac{1}{M} = \frac{n(n-1)}{2M} \quad (3)$$

$$\text{Total size of tables: } \sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + n$$

程序代写代做 CS编程辅导

- However, $\binom{n_i}{2}$ is the number of collisions in slot i ;
- thus, $\sum_{i=1}^M \binom{n_i}{2}$ is the total number of collisions in the hash table.
- Since there are $\binom{n}{2}$ pairs of keys and for each pair of keys the probability of a collision with universal hashing is $1/M$, we obtain that the expected total number of collisions is $\binom{n}{2} \frac{1}{M}$.

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com

Thus,

$$E \left[\sum_{i=1}^M \binom{n_i}{2} \right] = \binom{n}{2} \frac{1}{M} = \frac{n(n-1)}{2M} \quad (3)$$

$$\text{Total size of tables: } \sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + n$$

程序代写代做 CS编程辅导

- However, $\binom{n_i}{2}$ is the number of collisions in slot i ;
- thus, $\sum_{i=1}^M \binom{n_i}{2}$ is the total number of collisions in the hash table.
- Since there are $\binom{n}{2}$ pairs of keys and for each pair of keys the probability of a collision with universal hashing is $1/M$, we obtain that the expected total number of collisions is $\binom{n}{2} \frac{1}{M}$.

Email: tutorcs@163.com

Thus,

$$E \left[\sum_{i=1}^M \binom{n_i}{2} \right] = \binom{n}{2} \frac{1}{M} = \frac{n(n-1)}{2M} \quad (3)$$

Total size of tables: $\sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + n$

So we have:

程序代写代做 CS编程辅导

$$E \left[\sum_{i=1}^M n_i^2 \right] = 2E \left[\sum_{i=1}^M \binom{n_i}{2} \right] + n;$$
$$E \left[\sum_{i=1}^M \binom{n_i}{2} \right] = \frac{n(n-1)}{2M};$$

WeChat: cstutorcs

Thus,

Assignment Project Exam Help

$$E \left[\sum_{i=1}^M n_i^2 \right] = \frac{n(n-1)}{M} + n$$

QQ: 749389476

But M was chosen so that $M \geq n$; thus

<https://tutorcs.com>

$$E \left[\sum_{i=1}^M n_i^2 \right] \leq \frac{n(n-1)}{n} + n = 2n - 1 < 2n$$

Total size of tables: $\sum_{i=1}^M n_i^2 = 2 \sum_{i=1}^M \binom{n_i}{2} + n$

So we have:

程序代写代做 CS编程辅导

$$E \left[\sum_{i=1}^M n_i^2 \right] = 2E \left[\sum_{i=1}^M \binom{n_i}{2} \right] + n;$$
$$E \left[\sum_{i=1}^M \binom{n_i}{2} \right] = \frac{n(n-1)}{2M};$$

WeChat: cstutorcs

Thus,

Assignment Project Exam Help

$$E \left[\sum_{i=1}^M n_i^2 \right] = \frac{n(n-1)}{M} + n$$

Email: tutorcs@163.com

QQ: 749389476

But M was chosen so that $M \geq n$; thus

<https://tutorcs.com>

$$E \left[\sum_{i=1}^M n_i^2 \right] \leq \frac{n(n-1)}{n} + n = 2n - 1 < 2n$$

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Applying the Markov Inequality once again we obtain

$$P\left\{\sum_{i=1}^M n_i \geq 2n\right\} \leq \frac{E\left[\sum_{i=1}^M n_i^2\right]}{4n} < \frac{2n}{4n} = \frac{1}{2} \quad (4)$$

WeChat: cstutorcs

- Thus, after a few attempts we will produce a hash table of size $M < 2n$ for which **Assignment Project Exam Help**
- If we choose primes $m_i < 2n^2$ then $\sum_{i=1}^M m_i < 8n$.
Email: tutorcs@163.com
- In this way the size of the primary hash table plus the sum of sizes of all secondary hash tables satisfies
QQ: 749389476

<https://tutorcs.com>

$$M + \sum_{i=1}^M m_i < 2n + 8n = 10n.$$

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Applying the Markov Inequality once again we obtain

$$P\left\{\sum_{i=1}^M n_i > 4n\right\} \leq \frac{E\left[\sum_{i=1}^M n_i^2\right]}{4n} < \frac{2n}{4n} = \frac{1}{2} \quad (4)$$

WeChat: cstutorcs

- Thus, after a few attempts we will produce a hash table of size $M < 2n$ for which $\sum_{i=1}^M n_i^2 < 4n$.
- If we choose primes $m_i < 2n^2$ then $\sum_{i=1}^M m_i < 8n$.
- In this way the size of the primary hash table plus the sum of sizes of all secondary hash tables satisfies

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$M + \sum_{i=1}^M m_i < 2n + 8n = 10n.$$

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Applying the Markov Inequality once again we obtain

$$P\left\{\sum_{i=1}^M n_i > 4n\right\} \leq \frac{E\left[\sum_{i=1}^M n_i^2\right]}{4n} < \frac{2n}{4n} = \frac{1}{2} \quad (4)$$

WeChat: cstutorcs

- Thus, after a few attempts we will produce a hash table of size $M < 2n$ for which $\sum_{i=1}^M n_i^2 < 4n$.
- If we choose primes $m_i < 2n^2$ then $\sum_{i=1}^M m_i < 8n$.
- In this way the size of the primary hash table plus the sum of sizes of all secondary hash tables satisfies

<https://tutorcs.com>

$$M + \sum_{i=1}^M m_i < 2n + 8n = 10n.$$

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Applying the Markov Inequality once again we obtain

$$P\left\{\sum_{i=1}^M n_i > 4n\right\} \leq \frac{E\left[\sum_{i=1}^M n_i^2\right]}{4n} < \frac{2n}{4n} = \frac{1}{2} \quad (4)$$

WeChat: cstutorcs

- Thus, after a few attempts we will produce a hash table of size $M < 2n$ for which $\sum_{i=1}^M n_i^2 < 4n$.
- If we choose primes $m_i < 2n^2$ then $\sum_{i=1}^M m_i < 8n$.
- In this way the size of the primary hash table plus the sum of sizes of all secondary hash tables satisfies

Email: tutorcs@163.com

$$M + \sum_{i=1}^M m_i < 2n + 8n = 10n.$$

Designing a Perfect Hash table (continued)

We now describe the entire randomized construction.

- ① Choose a prime number M such that $n \leq M < 2n$.
- ② Pick randomly a hash function h on with hash table size M from a universal hash function family.
- ③ Use it to hash all n elements into such a table.
- ④ Check if the numbers of elements n_i in slots $i = 1, 2 \dots M$ satisfy $\sum_{i=1}^M n_i^2 < 4n$.
WeChat: cstutorcs
- ⑤ If not, pick randomly another hash function and try again, repeating until the above condition is satisfied.
- ⑥ As we have shown (see equation 4), you will succeed fast (on average after only two trials).
Email: tutorcs@163.com
- ⑦ For each slot i of the table containing n_i elements use the first described randomised construction to obtain hash functions h_i which produce no collisions at all and such that the size of the corresponding hash tables are prime numbers m_i satisfying $m_i < 2n_i^2$.
QQ: 749389476
<https://tutorcs.com>



Designing a Perfect Hash table (continued)

We now describe the entire randomized construction.

- ① Choose a prime number M such that $n \leq M < 2n$.
- ② Pick randomly a hash function h on with hash table size M from a universal hash function family.
- ③ Use it to hash all n elements into such a table.
- ④ Check if the numbers of elements n_i in slots $i = 1, 2 \dots M$ satisfy $\sum_{i=1}^M n_i^2 < 4n$.
WeChat: cstutorcs
- ⑤ If not, pick randomly another hash function and try again, repeating until the above condition is satisfied.
Assignment Project Exam Help
- ⑥ As we have shown (see equation 4), you will succeed fast (on average after only two trials).
Email: tutorcs@163.com
- ⑦ For each slot i of the table containing n_i elements use the first described randomised construction to obtain hash functions h_i which produce no collisions at all and such that the size of the corresponding hash tables are prime numbers m_i satisfying $m_i < 2n_i^2$.
QQ: 749389476
<https://tutorcs.com>



Designing a Perfect Hash table (continued)

We now describe the entire randomized construction.

- ① Choose a prime number M such that $n \leq M < 2n$.
- ② Pick randomly a hash function h on with hash table size M from a universal hash function family.
- ③ Use it to hash all n elements into such a table.
- ④ Check if the numbers of elements n_i in slots $i = 1, 2 \dots M$ satisfy $\sum_{i=1}^M n_i^2 < 4n$.
WeChat: cstutorcs
- ⑤ If not, pick randomly another hash function and try again, repeating until the above condition is satisfied.
- ⑥ As we have shown (see equation 4), you will succeed fast (on average after only two trials).
Email: tutorcs@163.com
- ⑦ For each slot i of the table containing n_i elements use the first described randomised construction to obtain hash functions h_i which produce no collisions at all and such that the size of the corresponding hash tables are prime numbers m_i satisfying $m_i < 2n_i^2$.
QQ: 749389476
<https://tutorcs.com>

Designing a Perfect Hash table (continued)

We now describe the entire randomized construction.

- ① Choose a prime number M such that $n \leq M < 2n$.
- ② Pick randomly a hash function h on with hash table size M from a universal hash function family.
- ③ Use it to hash all n elements into such a table.
- ④ Check if the numbers of elements n_i in slots $i = 1, 2 \dots M$ satisfy $\sum_{i=1}^M n_i^2 < 4n$.
WeChat: cstutorcs
- ⑤ If not, pick randomly another hash function and try again, repeating until the above condition is satisfied.
Assignment Project Exam Help
- ⑥ As we have shown (see equation 4), you will succeed fast (on average after only two trials).
Email: tutorcs@163.com
- ⑦ For each slot i of the table containing n_i elements use the first described randomised construction to obtain hash functions h_i which produce no collisions at all and such that the size of the corresponding hash tables are prime numbers m_i satisfying $m_i < 2n_i^2$.
QQ: 749389476

Designing a Perfect Hash table (continued)

We now describe the entire randomized construction.

- ① Choose a prime number M such that $n \leq M < 2n$.
- ② Pick randomly a hash function on with hash table size M from a universal hash function family.
- ③ Use it to hash all n elements into such a table.
- ④ Check if the numbers of elements n_i in slots $i = 1, 2 \dots M$ satisfy $\sum_{i=1}^M n_i^2 < 4n$.
WeChat: cstutorcs
- ⑤ If not, pick randomly another hash function and try again, repeating until the above condition is satisfied.
- ⑥ As we have shown (see equation 4), you will succeed fast (on average after only two trials).
Email: tutorcs@163.com
QQ: 749389476
- ⑦ For each slot i of the table containing n_i elements use the first described randomised construction to obtain hash functions h_i which produce no collisions at all and such that the size of the corresponding hash tables are prime numbers m_i satisfying $m_i < 2n_i^2$.

Designing a Perfect Hash table (continued)


We now describe the entire randomized construction.

- ① Choose a prime number M such that $n \leq M < 2n$.
- ② Pick randomly a hash function on with hash table size M from a universal hash function family.
- ③ Use it to hash all n elements into such a table.
- ④ Check if the numbers of elements n_i in slots $i = 1, 2 \dots M$ satisfy $\sum_{i=1}^M n_i^2 < 4n$.
WeChat: cstutorcs
- ⑤ If not, pick randomly another hash function and try again, repeating until the above condition is satisfied.
- ⑥ As we have shown (see equation 4), you will succeed fast (on average after only two trials).
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
- ⑦ For each slot i of the table containing n_i elements use the first described randomised construction to obtain hash functions h_i which produce no collisions at all and such that the size of the corresponding hash tables are prime numbers m_i satisfying $m_i < 2n_i^2$.

Designing a Perfect Hash table (continued)

We now describe the entire randomized construction.

- ① Choose a prime number M such that $n \leq M < 2n$.
- ② Pick randomly a hash function  with hash table size M from a universal hash function family.
- ③ Use it to hash all  into such a table.
- ④ Check if the numbers of elements n_i in slots $i = 1, 2 \dots M$ satisfy $\sum_{i=1}^M n_i^2 < 4n$.

WeChat: cstutorcs
- ⑤ If not, pick randomly another hash function and try again, repeating until the above condition is satisfied.
- ⑥ As we have shown (see equation 4), you will succeed fast (on average after only two trials)

Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476
- ⑦ For each slot i of the table containing n_i elements use the first described randomised construction to obtain hash functions h_i which produce no collisions at all and such that the size of the corresponding hash tables are prime numbers m_i satisfying $m_i < 2n_i^2$.

Designing a Perfect Hash table (continued)

We now describe the entire randomised construction.

- ① Choose a prime number M such that $n \leq M < 2n$.
- ② Pick randomly a hash function with hash table size M from a universal hash function family.
- ③ Use it to hash all n elements into such a table.
- ④ Check if the numbers of elements n_i in slots $i = 1, 2 \dots M$ satisfy $\sum_{i=1}^M n_i^2 < 4n$.
WeChat: cstutorcs
- ⑤ If not, pick randomly another hash function and try again, repeating until the above condition is satisfied.
- ⑥ As we have shown (see equation 4), you will succeed fast (on average after only two trials).
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
- ⑦ For each slot i of the table containing n_i elements use the first described randomised construction to obtain hash functions h_i which produce no collisions at all and such that the size of the corresponding hash tables are prime numbers m_i satisfying $m_i < 2n_i^2$.

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Note that our procedure eventually produces a **fully deterministic** hash function.
- It is only that our search for such a function was a randomised procedure by “trial and error”
- How does the resulting hash function operate?



WeChat: cstutorcs

Assignment Project Exam Help

- ① For a given key x compute $h(x) = i_x$ which is an index $1 \leq i_x \leq M$ for the primary hashtable T of size $M < 2n$;
- ② in the slot i_x of T find the secondary hash function h_{i_x} and compute $h_{i_x}(x) = j_x$ which is an index in the secondary table t_{i_x} ;
- ③ x (with the associated record R_x for x) is stored in slot j_x of the secondary table

QQ: 749389476
<https://tutorcs.com>

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Note that our procedure eventually produces a **fully deterministic** hash function.
- It is only that our search for such a function was a randomised procedure by “trial and error”.
- How does the resulting hash function operate?

Assignment Project Exam Help

- ① For a given key x compute $h(x) = i_x$ which is an index $1 \leq i_x \leq M$ for the primary hashtable T of size $M < 2n$;
- ② in the slot i_x of T find the secondary hash function h_{i_x} and compute $h_{i_x}(x) = j_x$ which is an index in the secondary table t_{i_x} ;
- ③ x (with the associated record R_x for x) is stored in slot j_x of the secondary table

QQ: 749389476

<https://tutorcs.com>



WeChat: cstutorcs

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Note that our procedure eventually produces a **fully deterministic** hash function.
- It is only that our search for such a function was a randomised procedure by “trial and error”.
- How does the resulting hash function operate?

Assignment Project Exam Help

- ① For a given key x compute $h(x) = i_x$ which is an index $1 \leq i_x \leq M$ for the primary hashtable T of size $M < 2n$;
- ② in the slot i_x of T find the secondary hash function h_{i_x} and compute $h_{i_x}(x) = j_x$ which is an index in the secondary table t_{i_x} ;
- ③ x (with the associated record R_x for x) is stored in slot j_x of the secondary table

QQ: 749389476
<https://tutorcs.com>



Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Note that our procedure eventually produces a **fully deterministic** hash function.
- It is only that our search for such a function was a randomised procedure by “trial and error”.
- How does the resulting hash function operate?

Assignment Project Exam Help

- ① For a given key x compute $h(x) = i_x$ which is an index $1 \leq i_x \leq M$ for the primary hash table T of size $M < 2n$;
- ② in the slot i_x of T find the secondary hash function h_{i_x} and compute $h_{i_x}(x) = j_x$ index in the secondary table t_{i_x} ;
- ③ x (with the associated record R_x for x) is stored in slot j_x of the secondary table

QQ: 749389476
<https://tutorcs.com>



WeChat: cstutorcs

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Note that our procedure eventually produces a **fully deterministic** hash function.
- It is only that our search for such a function was a randomised procedure by “trial and error”.
- How does the resulting hash function operate?

Assignment Project Exam Help

- ① For a given key x compute $h(x) = i_x$ which is an index $1 \leq i_x \leq M$ for the primary hash table T of size $M < 2n$;
- ② in the slot i_x of T find the secondary hash function h_{i_x} and compute $h_{i_x}(x) = j_x$ which is an index in the secondary table t_{i_x} ;
- ③ x (with the associated record R_x for x) is stored in slot j_x of the secondary table

<https://tutorcs.com>



WeChat: cstutorcs

Email: tutors@163.com

QQ: 749389476

Designing a Perfect Hash table (continued)

程序代写代做 CS编程辅导

- Note that our procedure eventually produces a **fully deterministic** hash function.
- It is only that our search for such a function was a randomised procedure by “trial and error”.
- How does the resulting hash function operate?

Assignment Project Exam Help

- ① For a given key x compute $h(x) = i_x$ which is an index $1 \leq i_x \leq M$ for the primary hash table T of size $M < 2n$;
- ② in the slot i_x of T find the secondary hash function h_{i_x} and compute $h_{i_x}(x) = j_x$ which is an index in the secondary table t_{i_x} ;
- ③ x (with the associated record R_x for x) is stored in slot j_x of the secondary table t_{i_x}

QQ: 749389476

<https://tutorcs.com>



Designing a Perfect Hash table (continued)

程序代写代做 CS 编程辅导

	t_1	t_2	\dots	t_{i_x}	\dots	t_M
1						
2						
:						
:						



WeChat: cstutorcs

Secondary hash tables
Assignment Project Exam Help

x

$$h(x) = i_x$$

1
2
:
:
M

Email: tutorcs@163.com
QQ: 749389476
<https://tutorcs.com>

$i_x \quad h_{i_x} \quad j_x = h_{i_x}(x)$

primary hash table T