



程序代写
作业CS编程辅导

Advanced Algorithms
WeChat: estutres
COMP4121
Assignment Project Exam Help

Email: tutorcs@163.com
Aleks Ignjatovic

QQ: 749389476

School of Computer Science and Engineering
University of New South Wales
<https://tutorcs.com>

Order Statistics

Let us get to work: Order Statistics algorithms

程序代写代做 CS编程辅导

- **Problem:** Given r arrays, select the i^{th} smallest element;



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Let us get to work: Order Statistics algorithms

程序代写代做 CS编程辅导

- **Problem:** Given r arrays, select the i^{th} smallest element;
 - for $i = 1$ we get  num;

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Let us get to work: Order Statistics algorithms

程序代写代做 CS编程辅导

- **Problem:** Given n elements, select the i^{th} smallest element;
 - for $i = 1$ we get the minimum;
 - for $i = n$ we get the maximum;

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Let us get to work: Order Statistics algorithms

程序代写代做 CS编程辅导

- **Problem:** Given n elements, select the i^{th} smallest element;
 - for $i = 1$ we get the **minimum**;
 - for $i = n$ we get the **maximum**;
 - for $i = \lfloor \frac{n+1}{2} \rfloor$ we get the **median**.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Let us get to work: Order Statistics algorithms

程序代写代做 CS编程辅导

- **Problem:** Given n elements, select the i^{th} smallest element;

- for $i = 1$ we get the **minimum**;
- for $i = n$ we get the **maximum**;
- for $i = \lfloor \frac{n+1}{2} \rfloor$ we get the **median**.

WeChat: cstutorcs

- We can find both the minimum and the maximum in $O(n)$ many steps (linear time). Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Let us get to work: Order Statistics algorithms

程序代写代做 CS编程辅导

- **Problem:** Given n elements, select the i^{th} smallest element;

- for $i = 1$ we get the **minimum**;
- for $i = n$ we get the **maximum**;
- for $i = \lfloor \frac{n+1}{2} \rfloor$ we get the **median**.

WeChat: cstutorcs

- We can find both the minimum and the maximum in $O(n)$ many steps (linear time).
- Can we find the median also in linear time?

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Let us get to work: Order Statistics algorithms

程序代写代做 CS编程辅导

- **Problem:** Given n elements, select the i^{th} smallest element;

- for $i = 1$ we get the **minimum**;
- for $i = n$ we get the **maximum**;
- for $i = \lfloor \frac{n+1}{2} \rfloor$ we get the **median**.

WeChat: cstutorcs

- We can find both the minimum and the maximum in $O(n)$ many steps (linear time). **Assignment Project Exam Help**
- Can we find the median also in linear time? **Email: tutorcs@163.com**
- Clearly, we can do it in time $n \log n$, just MergeSort the array and find the middle element(s) of the sorted array. **QQ: 749389476**

<https://tutorcs.com>

Let us get to work: Order Statistics algorithms

程序代写代做 CS编程辅导

- **Problem:** Given n elements, select the i^{th} smallest element;

- for $i = 1$ we get the **minimum**;
- for $i = n$ we get the **maximum**;
- for $i = \lfloor \frac{n+1}{2} \rfloor$ we get the **median**.

WeChat: cstutorcs

- We can find both the minimum and the maximum in $O(n)$ many steps (linear time). Assignment Project Exam Help
- Can we find the median also in linear time? Email: tutorcs@163.com
- Clearly, we can do it in time $n \log n$, just MergeSort the array and find the middle element(s) of the sorted array.
- Can we do it faster? https://tutorcs.com

Fast algorithms for finding the median

程序代写代做 CS编程辅导

- We will show that  can be done in linear time, by both a deterministic and a randomized algorithm.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast algorithms for finding the median

程序代写代做 CS编程辅导

- We will show that  can be done in linear time, by both a deterministic and a randomised algorithm.
- Why bother with a randomised algorithm if it can be done in linear time with a deterministic algorithm?

WeChat: estutores
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast algorithms for finding the median

程序代写代做 CS编程辅导

- We will show that  can be done in linear time, by both a deterministic and a randomised algorithm.
- Why bother with a randomised algorithm if it can be done in linear time with a deterministic algorithm?
- Because in practice the randomised algorithm runs much faster, having much smaller constant c in the bound for the run time $T(n) \leq c \cdot n$.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast algorithms for finding the median

程序代写代做 CS编程辅导



- We will show that ~~the median can be found in linear time~~ can be done in linear time, by both a deterministic and ~~a~~ randomised algorithm.
- Why bother with a randomised algorithm if it can be done in linear time with a ~~deterministic algorithm~~?
- Because in practice the randomised algorithm runs much faster, having much smaller constant c in the bound for the run time $T(n) \leq c \cdot n$.
Email: tutorcs@163.com
- It turns out that it is easier to solve (both deterministically and with randomisation) the more general problem of finding the i^{th} smallest element for an arbitrary i than to find just the median.
QQ: 749389476
<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on one side of the partition only.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on one side of the partition only.

RAND-SELECT(A, p, r)



choose the i^{th} smallest elt of $A[p..r]^*$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on one side of the partition only.

RAND-SELECT(A, p, r)



choose the i^{th} smallest elt of $A[p..r]^*$

- ① if $p = r \ \& \ i = 1$ then return $A[p]$;

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on only one side of the partition only.

RAND-SELECT(A, p, r) choose the i^{th} smallest elt of $A[p..r]^*$



- ① if $p = r \ \& \ i = 1$ then return $A[p]$; else
- ② choose a random pivot pv from $A[p..r]$,

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on only one side of the partition only.

RAND-SELECT(A, p, r) choose the i^{th} smallest elt of $A[p..r]^*$



- ① if $p = r$ & $i = 1$ then return $A[p]$; else
- ② choose a random pivot pv from $A[p..r]$;
- ③ reorder the array $A[p..r]$ such that $A[q..(q+1)] \leq A[q]$ and $A[(q+1)..r] > A[q]$ where $A[q]$ is the randomly chosen pivot pv ;

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on only one side of the partition only.

RAND-SELECT(A, p, r) choose the i^{th} smallest elt of $A[p..r]^*$



- ① if $p = r$ & $i = 1$ then return $A[p]$; else
- ② choose a random pivot pv from $A[p..r]$;
- ③ reorder the array $A[p..r]$ such that $A[p..(q-1)] \leq A[q]$ and $A[(q+1)..r] > A[q]$ where $A[q]$ is the randomly chosen pivot pv ;
(fill the details how we do this in place, just as it is done in an implementation of the QuickSort)

QQ: 749389476

<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on only one side of the partition only.

RAND-SELECT(A, p, r) choose the i^{th} smallest elt of $A[p..r]^*$



- ① if $p = r \ \& \ i = 1$ then return $A[p]$; else
- ② choose a random pivot pv from $A[p..r]$;
- ③ reorder the array $A[p..r]$ such that $A[p..(q-1)] \leq A[q]$ and $A[(q+1)..r] > A[q]$ where $A[q]$ is the randomly chosen pivot pv ;
(fill the details how we do this in place, just as it is done in an implementation of the QuickSort)
- ④ $k \leftarrow q - p + 1$ (k is the number of elements $\leq pv = A[q]$)

<https://tutorcs.com>

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on only one side of the partition only.

RAND-SELECT(A, p, r) choose the i^{th} smallest elt of $A[p..r]^*$



- ① if $p = r \ \& \ i = 1$ then return $A[p]$; else
- ② choose a random pivot pv from $A[p..r]$;
- ③ reorder the array $A[p..r]$ such that $A[p..(q-1)] \leq A[q]$ and $A[(q+1)..r] > A[q]$ where $A[q]$ is the randomly chosen pivot pv ;
(fill the details how we do this in place, just as it is done in an implementation of the QuickSort)
- ④ $k \leftarrow q - p + 1$ (k is the number of elements $\leq pv = A[q]$)
- ⑤ if $k = i$ then return $A[q]$;

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on only one side of the partition only.

RAND-SELECT(A, p, r) choose the i^{th} smallest elt of $A[p..r]^*$



- ① if $p = r \ \& \ i = 1$ then return $A[p]$; else
- ② choose a random pivot pv from $A[p..r]$;
- ③ reorder the array $A[p..r]$ such that $A[p..(q-1)] \leq A[q]$ and $A[(q+1)..r] > A[q]$ where $A[q]$ is the randomly chosen pivot pv ;
(fill the details how we do this in place, just as it is done in an implementation of the QuickSort)
- ④ $k \leftarrow q - p + 1$ (k is the number of elements $\leq pv = A[q]$)
- ⑤ if $k = i$ then return $A[q]$; else
- ⑥ if $i < k$ then return RAND-SELECT($A, p, q - 1, i$);

Fast randomised algorithm for finding the median

- **Problem:** Given n elements, select the i^{th} smallest element.
- **Idea:** Divide-and-conquer; by doing “one half” of the randomised QuickSort, operating on only one side of the partition only.

RAND-SELECT(A, p, r) choose the i^{th} smallest elt of $A[p..r]^*$



- ① if $p = r \ \& \ i = 1$ then return $A[p]$; else
- ② choose a random pivot pv from $A[p..r]$;
- ③ reorder the array $A[p..r]$ such that $A[p..(q-1)] \leq A[q]$ and $A[(q+1)..r] > A[q]$ where $A[q]$ is the randomly chosen pivot pv ;
(fill the details how we do this in place, just as it is done in an implementation of the QuickSort)
- ④ $k \leftarrow q - p + 1$ (k is the number of elements $\leq pv = A[q]$)
- ⑤ if $k = i$ then return $A[q]$; else
- ⑥ if $i < k$ then return RAND-SELECT($A, p, q - 1, i$);
- ⑦ else return RAND-SELECT($A, q + 1, r, i - k$).

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Clearly, the worst case time is $\Theta(n^2)$.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Clearly, the worst case time is $\Theta(n^2)$.
- This happens, for example, in a very unlikely event that you always pick either the smallest or the largest element of the array.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Clearly, the worst case time is $\Theta(n^2)$.
- This happens, for example, in a very unlikely event that you always pick either the smallest or the largest element of the array.
- In such a case during each call of RAND-SELECT the size of the array drops only by 1.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Clearly, the worst case time is $\Theta(n^2)$.
- This happens, for example, in a very unlikely event that you always pick either the smallest or the largest element of the array.
- In such a case during each call of RAND-SELECT the size of the array drops only by 1.
- Due to reshuffling of elements around the pivot, each iteration of RAND-SELECT costs the length of the array, and you get

Email: tutorcs@163.com

$$T(n) = c(n + (n - 1) + (n - 2) + \dots + 1) = \Theta(n^2)$$

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Clearly, the worst case time is $\Theta(n^2)$.
- This happens, for example, in a very unlikely event that you always pick either the smallest or the largest element of the array.
- In such a case during each call of RAND-SELECT the size of the array drops only by 1.
- Due to reshuffling of elements around the pivot, each iteration of RAND-SELECT costs the length of the array, and you get

Email: tutorcs@163.com
 $T(n) = c(n + (n - 1) + (n - 2) + \dots + 1) = \Theta(n^2)$
QQ: 749389476

- This is very unlikely to happen; in fact, as we will now see, most of the time the partitions will be reasonably well balanced.

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Let us first assume that all the elements in the array are **distinct**.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Let us first assume that all the elements in the array are **distinct**.
- Let us call a partition balanced if the ratio between the number of elements in the smaller piece and the number of elements in the larger piece is not worse than 1 to 9 (9 is kind of arbitrary here, any small number > 2 would do).

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Let us first assume that all the elements in the array are **distinct**.
- Let us call a partition balanced if the ratio between the number of elements in the smaller piece and the number of elements in the larger piece is not worse than 1 to 9 (9 is kind of arbitrary here, any small number > 2 would do).
- What is the probability that we get a balanced partition after choosing the pivot?

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Let us first assume that all the elements in the array are **distinct**.
- Let us call a partition balanced if the ratio between the number of elements in the smaller piece and the number of elements in the larger piece is not worse than 1 to 9 (9 is kind of arbitrary here, any small number > 2 would do).
- What is the probability that we get a balanced partition after choosing the pivot?
- Clearly, this happens if we chose an element which is neither among the smallest 1/10 nor among the largest 1/10 of all elements.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Let us first assume that all the elements in the array are **distinct**.
- Let us call a partition balanced if the ratio between the number of elements in the smaller piece and the number of elements in the larger piece is not worse than 1 to 9 (9 is kind of arbitrary here, any small number > 2 would do).
- What is the probability that we get a balanced partition after choosing the pivot?
- Clearly, this happens if we chose an element which is neither among the smallest 1/10 nor among the largest 1/10 of all elements.
- Thus, the probability to end up with a balanced partition is $1 - 2/10 = 8/10$. <https://tutorcs.com>



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Analysis of RAND-SELECT(A, p, r, i)

程序代写代做 CS编程辅导

- Let us first assume that all the elements in the array are **distinct**.
- Let us call a partition balanced if the ratio between the number of elements in the smaller piece and the number of elements in the larger piece is not worse than 1 to 9 (9 is kind of arbitrary here, any small number > 2 would do).

WeChat: cstutorcs

Assignment Project Exam Help

- What is the probability that we get a balanced partition after choosing the pivot?
- Clearly, this happens if we chose an element which is neither among the smallest 1/10 nor among the largest 1/10 of all elements.

QQ: 749389476

- Thus, the probability to end up with a balanced partition is $1 - 2/10 = 8/10$. <https://tutorcs.com>
- Let us find the expected number of partitions between two consecutive balanced partitions.

Analysis of RAND-SELECT(A, p, r, i)

- The probability to get another balanced partition immediately after a balanced partition is $\frac{8}{10}$;



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

- The probability to get another balanced partition immediately after a balanced partition is $\frac{8}{10}$;
- The probability to get another balanced partition is $\frac{2}{10} \frac{8}{10}$;



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

- The probability to get another balanced partition immediately after a balanced partition is $\frac{8}{10}$;
- The probability to partitions to get another balanced partition is $\frac{2}{10} \cdot \frac{8}{10}$;
- In general, the probability that you will need k partitions to end up with another balanced partition is $(\frac{2}{10})^{k-1} \cdot \frac{8}{10}$.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Analysis of RAND-SELECT(A, p, r, i)

- The probability to get another balanced partition immediately after a balanced partition is $\frac{8}{10}$;
- The probability to partitions to get another balanced partition is $\frac{2}{10} \cdot \frac{8}{10}$;
- In general, the probability that you will need k partitions to end up with another balanced partition is $\left(\frac{2}{10}\right)^{k-1} \cdot \frac{8}{10}$.
- Thus, the expected number of partitions between two balanced partitions is

Assignment Project Exam Help

$$E = 1 \cdot \frac{8}{10} + 2 \cdot \frac{8}{10} \cdot \frac{8}{10} \left(\frac{2}{10}\right)^2 \cdot \frac{8}{10} + \dots$$

$$= \frac{8}{10} \cdot \sum_{k=0}^{\infty} (k+1) \left(\frac{2}{10}\right)^k = \frac{8}{10} S$$

where

$$S = 1 + 2 \cdot \frac{2}{10} + 3 \cdot \left(\frac{2}{10}\right)^2 + 4 \cdot \left(\frac{2}{10}\right)^3 + 5 \cdot \left(\frac{2}{10}\right)^4 + \dots$$

$$\text{Evaluating } S = \sum_{k=0}^{\infty} (k+1) \left(\frac{2}{10}\right)^k$$

程序代写代做 CS 编程辅导

- How do we evaluate such a sum S ??



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\text{Evaluating } S = \sum_{k=0}^{\infty} (k+1) \left(\frac{2}{10}\right)^k$$

程序代写代做 CS 编程辅导

- How do we evaluate such a sum S ??
- Trick # 1:



$$S = 1 + 2 \cdot \frac{2}{10} + 3 \cdot \left(\frac{2}{10}\right)^2 + 4 \cdot \left(\frac{2}{10}\right)^3 + 5 \cdot \left(\frac{2}{10}\right)^4 + \dots$$

$$= 1 + \frac{2}{10} + \left(\frac{2}{10}\right)^2 + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots$$

$$+ \frac{2}{10} + \left(\frac{2}{10}\right)^2 + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots$$

$$+ \left(\frac{2}{10}\right)^2 + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots$$

QQ: 2749389476

https://tutorcs.com

$$+ \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots$$

$$\text{Evaluating } S = \sum_{k=0}^{\infty} (k+1) \left(\frac{2}{10}\right)^k$$

程序代写代做 CS 编程辅导

- Summing each row separately we obtain

$$1 + \frac{2}{10} + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots = \frac{1}{1 - \frac{2}{10}} = \frac{10}{8}$$
$$+ \frac{2}{10} + \left(\frac{2}{10}\right)^2 + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots = \frac{2}{10} \frac{10}{8}$$
$$+ \left(\frac{2}{10}\right)^2 + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots = \left(\frac{2}{10}\right)^2 \frac{10}{8}$$

WeChat: csTutorcs
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476

$$+ \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots = \left(\frac{2}{10}\right)^3 \frac{10}{8}$$

<https://tutorcs.com>

...

$$\text{Evaluating } S = \sum_{k=0}^{\infty} (k+1) \left(\frac{2}{10}\right)^k$$

程序代写代做 CS 编程辅导

- Summing each row separately we obtain

$$1 + \frac{2}{10} + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots = \frac{1}{1 - \frac{2}{10}} = \frac{10}{8}$$
$$+ \frac{2}{10} + \left(\frac{2}{10}\right)^2 + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots = \frac{2}{10} \frac{10}{8}$$
$$+ \left(\frac{2}{10}\right)^2 + \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots = \left(\frac{2}{10}\right)^2 \frac{10}{8}$$

WeChat: csTutorcs
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476

$$+ \left(\frac{2}{10}\right)^3 + \left(\frac{2}{10}\right)^4 + \dots = \left(\frac{2}{10}\right)^3 \frac{10}{8}$$

<https://tutorcs.com> ...

- We can now sum the right hand side column:

$$\text{Evaluating } S = \sum_{k=0}^{\infty} (k+1) \left(\frac{2}{10}\right)^k$$

程序代写代做 CS编程辅导



$$\begin{aligned}S &= \frac{10}{8} \left(1 + \frac{1}{10} \left(\frac{2}{10} \right)^2 + \left(\frac{2}{10} \right)^3 + \left(\frac{2}{10} \right)^4 + \dots \right) \\&= \frac{10}{8} \frac{1}{1 - \frac{2}{10}} = \left(\frac{10}{8} \right)^2\end{aligned}$$

WeChat: 2cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\text{Evaluating } S = \sum_{k=0}^{\infty} (k+1) \left(\frac{2}{10}\right)^k$$

程序代写代做 CS编程辅导



$$S = \frac{10}{8} \left(1 + \frac{1}{10} \left(\frac{2}{10} \right)^2 + \left(\frac{2}{10} \right)^3 + \left(\frac{2}{10} \right)^4 + \dots \right)$$
$$= \frac{10}{8} \frac{1}{1 - \frac{2}{10}} = \left(\frac{10}{8} \right)^2$$

WeChat: 2cstutorcs
Assignment Project Exam Help

Thus, we obtain

Email: tutorcs@163.com

$$E = \frac{8}{10} S = \frac{8}{10} \left(\frac{10}{8} \right)^2 = \frac{10}{8} = \frac{5}{4} < 2$$

QQ: 749389476
<https://tutorcs.com>

A useful digression (Trick #2): $S = \sum_{k=0}^{\infty} (k+1) \left(\frac{2}{10}\right)^k$
evaluated another way.

程序代写代做 CS编程辅导



Note that

$$\sum_{k=0}^{\infty} q^k = \frac{1}{1-q}.$$

WeChat: cstutorcse

Assignment Project Exam Help

Email: tutorcs@163.com

$$\sum_{k=1}^{\infty} k q^{k-1} = \frac{1}{(1-q)^2}.$$

QQ: 749389476

Substituting $q = 2/10$ we get that $S = (10/8)^2$.

Performance of RAND-SELECT:

- So, on average, there are only $5/4$ partitions between two balanced partitions.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Performance of RAND-SELECT:

- So, on average, there are only $5/4$ partitions between two balanced partitions.
- Note that before the first balanced partition the size of the array can be bounded by $\leq 9/10 n$, after the second balanced partition the size of the array is $\leq (9/10)^2 n$ and so on...
WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Performance of RAND-SELECT:

- So, on average, there are only $5/4$ partitions between two balanced partitions.
- Note that before the first balanced partition the size of the array can be bounded by n , after the first balanced partition the size of the array is $\leq 9/10n$, after the second balanced partition the size of the array is $\leq (9/10)^2 n$ and so on...
- Consequently the total **average** (expected) run time satisfies

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Performance of RAND-SELECT:

- So, on average, there are only $5/4$ partitions between two balanced partitions.
- Note that before the first balanced partition the size of the array can be bounded by $\leq 9/10n$, after the second balanced partition the size of the array is $\leq (9/10)^2 n$ and so on...
- Consequently the total **average** (expected) run time satisfies

Assignment Project Exam Help
Email: tutorcs@163.com

$$T(n) < \frac{5}{4}n + \frac{5}{4} \cdot \frac{9}{10}n + \frac{5}{4} \left(\frac{9}{10}\right)^2 n + \frac{5}{4} \left(\frac{9}{10}\right)^3 n + \dots$$

$$= \frac{5/4 n}{1 - \frac{9}{10}} = \frac{50}{4} n = 12.5n$$

QQ: 749389476

<https://tutorcs.com>

- Where did we tacitly assume that all elements are distinct?

Performance of RAND-SELECT:

- So, on average, there are only $5/4$ partitions between two balanced partitions.
- Note that before the first balanced partition the size of the array can be bounded by $\leq 9/10n$, after the second balanced partition the size of the array is $\leq (9/10)^2 n$ and so on...
- Consequently the total **average** (expected) run time satisfies

Assignment Project Exam Help
Email: tutorcs@163.com

$$T(n) < \frac{5}{4}n + \frac{5}{4} \cdot \frac{9}{10}n + \frac{5}{4} \left(\frac{9}{10}\right)^2 n + \frac{5}{4} \left(\frac{9}{10}\right)^3 n + \dots$$

$$= \frac{5/4 n}{1 - \frac{9}{10}} = \frac{50}{4} n = 12.5n$$

<https://tutorcs.com>

- Where did we tacitly assume that all elements are distinct?
- How did we estimate the probability of choosing the pivot which results in a balanced partition?

Performance of RAND-SELECT:

- Note that if all elements are the same RAND-SELECT would run in quadratic time no matter which elements are chosen as pivots - they are all equal.
- **Homework:** Model RAND-SELECT so that it runs in linear time even when there are many repetitions.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Performance of RAND-SELECT:

- Note that if all elements are the same RAND-SELECT would run in quadratic time no matter which elements are chosen as pivots - they are all equal.
- **Homework:** Modify SELECT so that it runs in linear time even when there are many repetitions.
- You might want try to modify slightly the way how the array is reordered.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Performance of RAND-SELECT:

- Note that if all elements are the same RAND-SELECT would run in quadratic time no matter which elements are chosen as pivots - they are all equal.
- **Homework:** Model RAND-SELECT so that it runs in linear time even when there are many repetitions.
- You might want try to modify slightly the way how the array is reordered.
- In practice RAND-SELECT runs really fast, for the same reason the Randomised Quicksort runs fast: it can be implemented as a very tight loop.


QQ: 749389476

<https://tutorcs.com>

Performance of RAND-SELECT:

- Note that if all elements are the same RAND-SELECT would run in quadratic time no matter which elements are chosen as pivots - they are all equal.
- **Homework:** Model RAND-SELECT so that it runs in linear time even when there are many repetitions.
- You might want try to modify slightly the way how the array is reordered.
- In practice RAND-SELECT runs really fast, for the same reason the Randomised Quicksort runs fast: it can be implemented as a very tight loop.
- In 1972 Blum, Floyd, Pratt, Rivest and Tarjan designed a deterministic Order Statistic Selection which runs in linear time in the worst case.

程序代写代做 CS 编程辅导



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Performance of RAND-SELECT:

- Note that if all elements are the same RAND-SELECT would run in quadratic time no matter which elements are chosen as pivots - they are all equal.
- **Homework:** Model RAND-SELECT so that it runs in linear time even when there are many repetitions.
- You might want try to modify slightly the way how the array is reordered.
- In practice RAND-SELECT runs really fast, for the same reason the Randomised Quicksort runs fast: it can be implemented as a very tight loop.
- In 1972 Blum, Floyd, Pratt, Rivest and Tarjan designed a deterministic Order Statistic Selection which runs in linear time in the worst case.
- **Main idea:** Use a recursive call of the very same algorithm to choose a good pivot!

程序代写代做 CS 编程辅导



WeChat: estutores

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- **Algorithm Select** (程序代写代做 CS 编程辅导)

- Split the numbers in groups of five (the last group might contain less than 5 elements).
- Order each group in increasing order.



WeChat: cstutorcs

Assignment Project Exam Help

- Take the collection of all $\lfloor \frac{n}{5} \rfloor$ middle elements of each group (i.e., the medians of each group of five).



QQ: 749389476

https://tutors.com

Deterministic Linear Time Algorithm for Order Statistics

- **Algorithm Select** (程序代写代做 CS 编程辅导)

- Split the numbers in groups of five (the last group might contain less than 5 elements).
- Order each group in increasing order.



WeChat: cstutorcs

Assignment Project Exam Help

- Take the collection of all $\lfloor \frac{n}{5} \rfloor$ middle elements of each group (i.e., the medians of each group of five).



- Apply recursively SELECT algorithm to find the median p of this collection.

程序代写代做 CS编程辅导

- Algorithm Select (n, i) continued:



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Algorithm Select_(n, i) continued:

- partition all elements using p as a pivot;



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- **Algorithm Select_(n, i) continued:**

- partition all elements into two sets using p as a pivot;
- Let k be the number of elements in the subset of all elements smaller than the pivot.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Algorithm Select_(n, i) continued:

- partition all elements into two sets using p as a pivot;
- Let k be the number of elements in the subset of all elements smaller than the pivot p .
- if $i = k$ then return p

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Algorithm Select_(n, i) continued:

- partition all elements in the set using p as a pivot;
- Let k be the number of elements in the subset of all elements smaller than the pivot.
- **if** $i = k$ **then return** p
- **else if** $i < k$ **then recursively SELECT** the i^{th} smallest element of the set of elements smaller than the pivot.

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Algorithm Select_(n, i) continued:

- partition all elements in the set using p as a pivot;
- Let k be the number of elements in the subset of all elements smaller than the pivot.
- **if** $i = k$ **then return** p
- **else if** $i < k$ **then recursively SELECT** the i^{th} smallest element of the set of elements smaller than the pivot.
- **else** recursively SELECT the $(i - k)^{th}$ smallest element of the set of elements larger than the pivot.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

程序代写代做 CS编程辅导

- Algorithm Select_(n, i) continued:

- partition all elements into two sets using p as a pivot;
- Let k be the number of elements in the subset of all elements smaller than the pivot.
- **if** $i = k$ **then return** p
- **else if** $i < k$ **then recursively SELECT** the i^{th} smallest element of the set of elements smaller than the pivot.
- **else** recursively SELECT the $(i - k)^{th}$ smallest element of the set of elements larger than the pivot.

Email: tutorcs@163.com

- **Note:** This algorithm is the same as RAND-SELECT except for the way how we chose the pivot.

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

程序代写代做 CS编程辅导

- Algorithm Select_(n, i) continued:

- partition all elements into two sets using p as a pivot;
- Let k be the number of elements in the subset of all elements smaller than the pivot.
- **if** $i = k$ **then return** p
- **else if** $i < k$ **then recursively SELECT** the i^{th} smallest element of the set of elements smaller than the pivot.
- **else** recursively SELECT the $(i - k)^{th}$ smallest element of the set of elements larger than the pivot.

Email: tutorcs@163.com

- **Note:** This algorithm is the same as RAND-SELECT except for the way how we chose the pivot.
QQ: 749389476
- instead of choosing pivot randomly we called recursively the very same algorithm to pick the pivot as the median of the middle elements of the groups of five elements.

Deterministic Linear Time Algorithm for Order Statistics

- What have we accomplished by such a choice of the pivot?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What have we accomplished by such a choice of the pivot?



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What have we accomplished by such a choice of the pivot?



- Note that at least $\lceil (n/5)/2 \rceil = \lceil n/10 \rceil$ group medians are smaller or equal to the pivot; and at least that many larger than the pivot.

Assignment Project Exam Help
Email: tutors@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What have we accomplished by such a choice of the pivot?



- Note that at least $\lceil (n/5)/2 \rceil = \lceil n/10 \rceil$ group medians are smaller or equal to the pivot, and at least that many larger than the pivot.
- But this implies that at least $\lfloor 3n/10 \rfloor$ of the total number of elements are smaller than the pivot, and that many elements larger than the pivot.

Deterministic Linear Time Algorithm for Order Statistics

- What have we accomplished by such a choice of the pivot?



- Note that at least $\lceil (n/5)/2 \rceil = \lceil n/10 \rceil$ group medians are smaller or equal to the pivot, and at least that many larger than the pivot.
- But this implies that at least $\lfloor 3n/10 \rfloor$ of the total number of elements are smaller than the pivot, and that many elements larger than the pivot.
<https://tutorcs.com>
- (the same caveat: we are assuming all elements are distinct; otherwise we have to slightly tweak the algorithm to split all elements equal to the pivot evenly between the two groups.)

Deterministic Linear Time Algorithm for Order Statistics

- What is the run time of our algorithm?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What is the run time of our algorithm?

$$T(\text{[QR code]}/5) + T(7n/10) + Cn.$$



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What is the run time of our algorithm?

$$T(\text{[QR code]}/5) + T(7n/10) + Cn.$$



- Let us show that $T(\text{[QR code]}) = Cn$ for all n .

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What is the run time of our algorithm?

$$T(\text{[QR code]}/5) + T(7n/10) + Cn.$$



- Let us show that $T(\text{[QR code]}) = Cn$ for all n . Assume that this is true for all $k < n$ and let us prove it is true for n as well.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What is the run time of our algorithm?

$$T(\text{[QR code]}/5) + T(7n/10) + Cn.$$



- Let us show that $T(\text{[QR code]}) = Cn$ for all n . Assume that this is true for all $k < n$ and let us prove it is true for n as well.

- Note: this is a proof using the following form of induction:

$$\varphi(0) \ \& \ (\forall n)((\forall k < n)\varphi(k) \rightarrow \varphi(n)) \rightarrow (\forall n)\varphi(n).$$

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What is the run time of our algorithm?

$$T(\text{QR code}/5) + T(7n/10) + Cn.$$



- Let us show that $T(\text{QR code}) \leq Cn$ for all n . Assume that this is true for all $k < n$ and let us prove it is true for n as well.

- Note: this is a proof using the following form of induction:

$$\varphi(0) \wedge (\forall n)((\forall k < n)\varphi(k) \rightarrow \varphi(n)) \rightarrow (\forall n)\varphi(n).$$

- Thus, assume $T(n/5) \leq 11C \cdot n/5$ and $T(7n/10) \leq 11C \cdot 7n/10$;

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Deterministic Linear Time Algorithm for Order Statistics

- What is the run time of our algorithm?

$$T(\text{[QR code]}/5) + T(7n/10) + Cn.$$



- Let us show that $T(\text{[QR code]}) \leq Cn$ for all n . Assume that this is true for all $k < n$ and let us prove it is true for n as well.

- Note: this is a proof using the following form of induction:

$$\varphi(0) \& (\forall n)((\forall k < n)\varphi(k) \rightarrow \varphi(n)) \rightarrow (\forall n)\varphi(n).$$

- Thus, assume $T(n/5) < 11C \cdot n/5$ and $T(7n/10) < 11C \cdot 7n/10$; then

Email: tutorcs@163.com

$$T(n) \leq T(n/5) + \text{QQ:749389476} + Cn < 11C \cdot \frac{n}{5} + 11C \cdot \frac{7n}{10} + Cn$$

$$= 109 \frac{Cn}{10} < 11C \cdot n$$

Deterministic Linear Time Algorithm for Order Statistics

- What is the run time of our algorithm?

$$T(\text{[QR code]}/5) + T(7n/10) + Cn.$$



- Let us show that $T(\text{[QR code]}) < Cn$ for all n . Assume that this is true for all $k < n$ and let us prove it is true for n as well.

- Note: this is a proof using the following form of induction:

$$\varphi(0) \& (\forall n)((\forall k < n)\varphi(k) \rightarrow \varphi(n)) \rightarrow (\forall n)\varphi(n).$$

- Thus, assume $T(n/5) < 11C \cdot n/5$ and $T(7n/10) < 11C \cdot 7n/10$; then

Email: tutorcs@163.com

$$\begin{aligned} T(n) &\leq T(n/5) + T(7n/10) + Cn < 11C \cdot \frac{n}{5} + 11C \cdot \frac{7n}{10} + Cn \\ &= 109 \frac{Cn}{10} < 11C \cdot n \end{aligned}$$

which proves out statement that $T(n) < 11C \cdot n$.

程序代写代做 CS编程辅导



- Note that this algorithm uses genuine recursion (rather than just an iteration) so its execution involves lots of traffic on the stack, which makes this algorithm slow in practice; the randomised version of it, RAND-SELECT, significantly outperforms it.

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导



- Note that this algorithm uses genuine recursion (rather than just an iteration) so its execution involves lots of traffic on the stack, which makes this algorithm slow in practice; the randomised version of it, RAND-SELECT, significantly outperforms it.

WeChat: cstutorcs
Assignment Project Exam Help

- Similarly RAND-QUICKSORT in practice outperforms MERGESORT, which, unlike RAND-QUICKSORT, is guaranteed to run in time $O(n \log n)$

Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>