

程序代写 CS编程辅导



Advanced Algorithms

WeChat: estutores

COMP4121

Assignment Project Exam Help

Email: tutorcs@163.com

Aleks Ignjatovic

QQ: 749389476

School of Computer Science and Engineering

University of New South Wales

<https://tutorcs.com>

Database Access Problem

Database Access Problem

(More details can be found on pages 707-744 in *Algorithm Design* by Kleinberg and Tardos.)



- Assume that n processes want to access a database, and that the time is discrete, $t = 0, 1, 2, \dots$
- If at any instant t k processes (simultaneously) request access, there is a conflict and all processes are locked out of access.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

- One possible approach in such a situation is that each process at each instant t tosses a coin which produces outcome “request access” with a probability p or “do not request access” with probability $1 - p$.
- How should we choose p to maximise the probability of a successful access to the database for a process at any instant t ?

Database Access Problem

(More details can be found on pages 707-744 in *Algorithm Design* by Kleinberg and Tardos.)

- Assume that n processes want to access a database, and that the time is discrete, $t = 0, 1, 2, \dots$
- If at any instant t k processes (simultaneously) request access, there is a conflict and all processes are locked out of access.
- We assume that the processes cannot communicate with each other to agree on a joint strategy; each process has to decide if it will request access to database on its own, in isolation of other processes.
- One possible approach in such a situation is that each process at each instant t tosses a coin which produces outcome “request access” with a probability p or “do not request access” with probability $1 - p$.
- How should we choose p to maximise the probability of a successful access to the database for a process at any instant t ?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Database Access Problem

(More details can be found on pages 707-744 in *Algorithm Design* by Kleinberg and Tardos.)

- Assume that n processes want to access a database, and that the time is discrete, $t = 0, 1, 2, \dots$
- If at any instant t k processes (simultaneously) request access, there is a conflict and all processes are locked out of access.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

- One possible approach in such a situation is that each process at each instant t tosses a coin which produces outcome “request access” with a probability p or “do not request access” with probability $1 - p$.
- How should we choose p to maximise the probability of a successful access to the database for a process at any instant t ?

Database Access Problem

(More details can be found on pages 707-744 in *Algorithm Design* by Kleinberg and Tardos.)

- Assume that n processes want to access a database, and that the time is discrete, $t = 0, 1, 2, \dots$
- If at any instant t k processes (simultaneously) request access, there is a conflict and all processes are locked out of access.
- We assume that the processes cannot communicate with each other to agree on a joint strategy; each process has to decide if it will request access to database on its own, in isolation of other processes.
- One possible approach in such a situation is that each process at each instant t tosses a coin which produces outcome “request access” with a probability p or “do not request access” with probability $1 - p$.
- How should we choose p to maximise the probability of a successful access to the database for a process at any instant t ?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Database Access Problem

(More details can be found on pages 707-744 in *Algorithm Design* by Kleinberg and Tardos.)

- Assume that n processes want to access a database, and that the time is discrete, $t = 0, 1, 2, \dots$
- If at any instant t k processes (simultaneously) request access, there is a conflict and all processes are locked out of access.
- We assume that the processes cannot communicate with each other to agree on a joint strategy; each process has to decide if it will request access to database on its own, in isolation of other processes.
- One possible approach in such a situation is that each process at each instant t tosses a coin which produces outcome “request access” with a probability p and “do not request access” with probability $1 - p$.
- How should we choose p to maximise the probability of a successful access to the database for a process at any instant t ?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

https://tutorcs.com

Database Access Problem

(More details can be found on pages 707-744 in *Algorithm Design* by Kleinberg and Tardos.)

- Assume that n processes want to access a database, and that the time is discrete, $t = 0, 1, 2, \dots$
- If at any instant t k processes (simultaneously) request access, there is a conflict and all processes are locked out of access.
- We assume that the processes cannot communicate with each other to agree on a joint strategy; each process has to decide if it will request access to database on its own, in isolation of other processes.
- One possible approach in such a situation is that each process at each instant t tosses a coin which produces outcome “request access” with a probability p and “do not request access” with probability $1 - p$.
- How should we choose p to maximise the probability of a successful access to the database for a process at any instant t ?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorms@163.com

QQ: 749389476

https://tutorms.com

Database Access Problem

程序代写代做 CS编程辅导

- For a given probability p , the probability of the success of a process i at any instant is $\mathcal{P}(\mathcal{S}(i, t)) = p(1 - p)^{n-1}$, because a process i requests access with probability p and the probability that no other process requests access is $(1 - p)^{n-1}$.

WeChat: cstutorcs

- For what value of p does $\mathcal{P}(\mathcal{S}(i, t))$ have the largest possible value?
- Extremal points are found by solving

Assignment Project Exam Help

$$\frac{d}{dp} \mathcal{P}(\mathcal{S}(i, t)) = (1 - p)^{n-1} - p(n-1)(1 - p)^{n-2} = 0$$

Email: tutorcs@163.com

QQ: 749389476

- Dividing both sides by $(1 - p)^{n-2}$ we get that the above equality holds just in case $1 - p - p(n-1) = 0$ which is equivalent to $p = 1/n$, as one might expect.

<https://tutorcs.com>

程序代写代做 CS编程辅导

- For a given probability p , the probability of the success of a process i at any instant is $\mathcal{P}(\mathcal{S}(i, t)) = p(1 - p)^{n-1}$, because a process i requests access with probability p and the probability that no other process requests access is $(1 - p)^{n-1}$.
- For what value of p does $\mathcal{P}(\mathcal{S}(i, t))$ have the largest possible value?
- Extremal points are found by solving

WeChat: cstutorcs

Assignment Project Exam Help

$$\frac{d}{dp} \mathcal{P}(\mathcal{S}(i, t)) = (1 - p)^{n-1} - p(n-1)(1 - p)^{n-2} = 0$$

Email: tutorcs@163.com

QQ: 749389476

- Dividing both sides by $(1 - p)^{n-2}$ we get that the above equality holds just in case $1 - p - p(n - 1) = 0$ which is equivalent to $p = 1/n$, as one might expect.

<https://tutorcs.com>

程序代写代做 CS编程辅导

- For a given probability p , the probability of the success of a process i at any instant is $\mathcal{P}(\mathcal{S}(i, t)) = p(1 - p)^{n-1}$, because a process i requests access with probability p and the probability that no other process requests access is $(1 - p)^{n-1}$.
- For what value of p does $\mathcal{P}(\mathcal{S}(i, t))$ have the largest possible value?
- Extremal points are found by solving

$$\frac{d}{dp} \mathcal{P}(\mathcal{S}(i, t)) = (1 - p)^{n-1} - p(n-1)(1 - p)^{n-2} = 0$$

QQ: 749389476

- Dividing both sides by $(1 - p)^{n-2}$ we get that the above equality holds just in case $1 - p - p(n-1) = 0$ which is equivalent to $p = 1/n$, as one might expect.

程序代写代做 CS编程辅导

- For a given probability p , the probability of the success of a process i at any instant is $\mathcal{P}(\mathcal{S}(i, t)) = p(1 - p)^{n-1}$, because a process i requests access with probability p and the probability that no other process requests access is $(1 - p)^{n-1}$.
- For what value of p does $\mathcal{P}(\mathcal{S}(i, t))$ have the largest possible value?
- Extremal points are found by solving

$$\frac{d}{dp} \mathcal{P}(\mathcal{S}(i, t)) = (1 - p)^{n-1} - p(n-1)(1 - p)^{n-2} = 0$$

QQ: 749389476

- Dividing both sides by $(1 - p)^{n-2}$ we get that the above equality holds just in case $1 - p - p(n-1) = 0$ which is equivalent to $p = 1/n$, as one might expect.

程序代写代做 CS编程辅导

- So for the optimal process i at an instance t , $1/n$ the probability of success for a



$$\mathcal{P}(\mathcal{S}(i, t)) = p(1 - p)^{n-1} = \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}$$

WeChat: cstutorcs

- To establish the assignment problem (S), the following two facts are useful; both can be proved by establishing the signs of the relevant first derivatives.

Email: tutorcs@163.com

- 1 $(1 - \frac{1}{n})^n$ increases monotonically from $1/4$ up to $1/e$ as n increases from 2 to ∞ ($e = 2.718 \dots$).

QQ: 749389476

- 2 $(1 - \frac{1}{n})^{n-1}$ decreases monotonically from $1/2$ down to $1/e$ as n increases from 2 to ∞ .

<https://tutorcs.com>

程序代写代做 CS编程辅导

- So for the optimal process i at an inst



$$\mathcal{P}(\mathcal{S}(i, t)) = p(1 - p)^{n-1} = \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}$$

WeChat: cstutorcs

- To establish the asymptotic behaviour of $\mathcal{P}(\mathcal{S}(i, t))$ the following two facts are useful; both can be proved by establishing the signs of the relevant first derivatives:

- $\left(1 - \frac{1}{n}\right)^n$ increases monotonically from $1/4$ up to $1/e$ as n increases from 2 to ∞ ($e = 2.718\dots$).

- $\left(1 - \frac{1}{n}\right)^{n-1}$ decreases monotonically from $1/2$ down to $1/e$ as n increases from 2 to ∞ .

程序代写代做 CS编程辅导

- Thus, since we had



$$= \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}$$

we obtain

WeChat: cstutorcs

$\frac{1}{n} \cdot \frac{1}{n} \leq \mathcal{P}(\mathcal{S}(i, t)) \leq \frac{1}{n} \cdot \frac{1}{2}$

Assignment Project Exam Help

Email: tutorcs@163.com

- Thus $\mathcal{P}(\mathcal{S}(i, t)) = \Theta\left(\frac{1}{n}\right)$.

- So after t many instances, what is the probability that a particular process has succeeded?

QQ: 749389476

<https://tutorcs.com>

- It is actually easier to estimate the probability of failure after t instants:

程序代写代做 CS编程辅导

- Thus, since we had



$$= \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}$$

we obtain

WeChat: cstutorcs

$\frac{1}{n} \cdot \frac{1}{2} \leq \mathcal{P}(\mathcal{S}(i, t)) \leq \frac{1}{n} \cdot \frac{1}{2}$

Assignment Project Exam Help

- Thus $\mathcal{P}(\mathcal{S}(i, t)) = \Theta\left(\frac{1}{n}\right)$.

Email: tutorcs@163.com

- So after t many instants, what is the probability that a particular process has succeeded?

QQ: 749389476

<https://tutorcs.com>

- It is actually easier to estimate the probability of failure after t instants:

程序代写代做 CS编程辅导

- Thus, since we had



$$= \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}$$

we obtain

WeChat: cstutorcs

$\frac{1}{n} \cdot \frac{1}{n} \leq \mathcal{P}(\mathcal{S}(i, t)) \leq \frac{1}{n} \cdot \frac{1}{2}$

Assignment Project Exam Help

Email: tutorcs@163.com

- Thus $\mathcal{P}(\mathcal{S}(i, t)) = \Theta\left(\frac{1}{n}\right)$.
- So after t many instants, what is the probability that a particular process has succeeded?
- It is actually easier to estimate the probability of failure after t instants:

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Thus, since we had



$$= \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}$$

we obtain

WeChat: cstutorcs

$\frac{1}{n} \cdot \frac{1}{n} \leq \mathcal{P}(\mathcal{S}(i, t)) \leq \frac{1}{n} \cdot \frac{1}{2}$
Assignment Project Exam Help

Email: tutorcs@163.com

- Thus $\mathcal{P}(\mathcal{S}(i, t)) = \Theta\left(\frac{1}{n}\right)$.
- So after t many instants, what is the probability that a particular process has succeeded?
QQ: 749389476
- It is actually easier to estimate the probability of failure after t instants:
<https://tutorcs.com>

Database Access Problem

程序代写代做 CS编程辅导

$$\mathcal{P}(\text{failure after } t \text{ instants}) = \left(1 - \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}\right)^t$$



- Using the second order inequalities we get

$$\mathcal{P}(\text{failure after } t \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^t$$

Assignment Project Exam Help

- We can now observe a somewhat dangerous phenomenon:

- If we chose $t = en$ many consecutive instants (we ignore floors or ceilings necessarily in this case) then the probability of a failure is quite large, because

$$\mathcal{P}(\text{failure after } t = en \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^{en} \approx \frac{1}{e}$$

which is quite large, larger than 1/3.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Database Access Problem

程序代写代做 CS编程辅导

$$\mathcal{P}(\text{failure after } t \text{ instants}) = \left(1 - \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}\right)^t$$



- Using the second order inequalities we get

$$\mathcal{P}(\text{failure after } t \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^t$$

Assignment Project Exam Help

- We can now observe a somewhat strange phenomenon:

- If we chose $t = en$ many consecutive instants (we ignore floors or ceilings necessarily in this case) then the probability of a failure is quite large, because

$$\mathcal{P}(\text{failure after } t = en \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^{en} \approx \frac{1}{e}$$

which is quite large, larger than 1/3.

Database Access Problem

程序代写代做 CS编程辅导

$$\mathcal{P}(\text{failure after } t \text{ instants}) = \left(1 - \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}\right)^t$$



- Using the second order inequalities we get

$$\mathcal{P}(\text{failure after } t \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^t$$

Assignment Project Exam Help

- We can now observe a somewhat strange phenomenon:

- If we chose $t = en$ many consecutive instants (we ignore floors or ceilings necessarily in this case) then the probability of a failure is quite large, because

$$\mathcal{P}(\text{failure after } t = en \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^{en} \approx \frac{1}{e}$$

which is quite large, larger than 1/3.

程序代写代做 CS编程辅导

$$\mathcal{P}(\text{failure after } t \text{ instants}) = \left(1 - \frac{1}{n} \left(1 - \frac{1}{n}\right)^{n-1}\right)^t$$



- Using the second order inequalities we get

$$\mathcal{P}(\text{failure after } t \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^t$$

Assignment Project Exam Help

- We can now observe a somewhat strange phenomenon:

- If we chose $t = en$ many consecutive instants (we ignore floors or ceilings necessary to make quantities integers) then the probability of a failure is quite large, because

$$\mathcal{P}(\text{failure after } t = en \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^{en} \approx \frac{1}{e}$$

which is quite large, larger than $1/3$.

Database Access Problem

- However, if we increase the number of instants only slightly, by taking $t = en \cdot 2 \ln n$



$$\mathcal{P}(\text{failure after } t \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^{en \cdot 2 \ln n}$$

$$\text{WeChat: } \text{cstutorcs} = \left(\left(1 - \frac{1}{en}\right)^{en} \right)^{2 \ln n}$$

$$\text{Assignment Project Exam Help} \approx \left(\frac{1}{e}\right)^{2 \ln n}$$

$$\text{Email: } \text{tutorcs@163.com} \approx \frac{1}{e^2}$$

$$\text{QQ: } 749389476 = \frac{1}{n^2}$$

$$\text{https://tutorcs.com}$$

- Thus, a slight increase in the number of time instants, from en to $2en \ln n$ caused a dramatic reduction in the probability of failure of a process to access the database

Database Access Problem

- However, if we increase the number of instants only slightly, by taking $t = en \cdot 2 \ln n$



$$\mathcal{P}(\text{failure after } t \text{ instants}) \approx \left(1 - \frac{1}{en}\right)^{en \cdot 2 \ln n}$$

$$\text{WeChat: } \text{cstutorcs} = \left(\left(1 - \frac{1}{en}\right)^{en} \right)^{\ln n^2}$$

$$\text{Assignment Project Exam Help} \approx \left(\frac{1}{e}\right)^{n^2}$$

$$\text{Email: } \text{tutorcs@163.com} \approx \frac{1}{e^{n^2}}$$

$$\text{QQ: } 749389476 = \frac{1}{n^2}$$

$$\text{https://tutorcs.com}$$

- Thus, a slight increase in the number of time instants, from en to $2en \ln n$ caused a dramatic reduction in the probability of failure of a process to access the database.

Database Access Problem

程序代写代做 CS编程辅导

- What is the probability that at least one process has failed to access data base after n instants?



- If probability of failure of each process is less than $1/n^2$ and there are n processes, then the probability that at least one process failed cannot be larger than $n \cdot \frac{1}{n^2} = \frac{1}{n}$.

WeChat: cstutorcs

- Thus after $2en \ln n$ instants all processes succeeded to access the data base with probability at least $1 - 1/n$.

Assignment Project Exam Help

- So if the processes could communicate and agree upon the order in which they would access the database, it would take n instants for all of them to access the database.

Email: tutorcs@163.com

QQ: 749389476

- If they use randomised process which does not require any communication, then they will be able to access the database with probability $1 - 1/n$ in time which is larger only by a relatively small factor of $2e \ln n$.

<https://tutorcs.com>

Database Access Problem

程序代写代做 CS编程辅导

- What is the probability that at least one process has failed to access data base after n instants?
- If probability of failure of each process is less than $1/n^2$ and there are n processes, then the probability that at least one process failed cannot be larger than $n \cdot \frac{1}{n^2} = \frac{1}{n}$.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

- Thus after $2en \ln n$ instants all processes succeeded to access the data base with probability at least $1 - 1/n$.
- So if the processes could communicate and agree upon the order in which they would access the database, it would take n instants for all of them to access the database.
- If they use randomised process which does not require any communication, then they will be able to access the database with probability $1 - 1/n$ in time which is larger only by a relatively small factor of $2e \ln n$.

Database Access Problem

程序代写代做 CS编程辅导

- What is the probability that at least one process has failed to access data base after n instants?
- If probability of failure of each process is less than $1/n^2$ and there are n processes, then the probability that at least one process failed cannot be larger than $n \cdot \frac{1}{n^2} = \frac{1}{n}$.



WeChat: cstutorcs

- Thus after $2e n \ln n$ instants all processes succeeded to access the data base with probability at least $1 - 1/n$.

Assignment Project Exam Help

- So if the processes could communicate and agree upon the order in which they would access the database, it would take n instants for all of them to access the database.

Email: tutorcs@163.com

QQ: 749389476

- If they use randomised process which does not require any communication, then they will be able to access the database with probability $1 - 1/n$ in time which is larger only by a relatively small factor of $2e \ln n$.

<https://tutorcs.com>

Database Access Problem

程序代写代做 CS编程辅导

- What is the probability that at least one process has failed to access data base after n instants?
- If probability of failure of each process is less than $1/n^2$ and there are n processes, then the probability that at least one process failed cannot be larger than $n \cdot \frac{1}{n^2} = \frac{1}{n}$.



WeChat: cstutorcs

- Thus after $2e n \ln n$ instants all processes succeeded to access the data base with probability at least $1 - 1/n$.
- So if the processes could communicate and agree upon the order in which they would access the database, it would take n instants for all of them to access the database.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749589476

- If they use randomised process which does not require any communication, then they will be able to access the database with probability $1 - 1/n$ in time which is larger only by a relatively small factor of $2e \ln n$.

<https://tutorcs.com>

Database Access Problem

程序代写代做 CS编程辅导

- What is the probability that at least one process has failed to access data base after n instants?
- If probability of failure of each process is less than $1/n^2$ and there are n processes, then the probability that at least one process failed cannot be larger than $n \cdot \frac{1}{n^2} = \frac{1}{n}$.
- Thus after $2e n \ln n$ instants all processes succeeded to access the data base with probability at least $1 - 1/n$.
- So if the processes could communicate and agree upon the order in which they would access the database, it would take n instants for all of them to access the database.
- If they use randomised process which does not require any communication, then they will be able to access the database with probability $1 - 1/n$ in time which is larger only by a relatively small factor of $2e \ln n$.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>