

程序代写代做 CS编程辅导



COMP4418 Knowledge Representation and Reasoning

First-Order Logic 1

WeChat: cstutorcs

Maurice Pagnucco

School of Computer Science and Engineering

COMP4418, Week 2

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

First-Order Logic

程序代写代做 CS编程辅导

- First-order logic furnishes a much more expressive knowledge representation language than propositional logic
- We can directly talk about their properties, relations between them, etc. ...
- Here we discuss first-order logic and resolution
- However, there is a price to pay for this expressiveness in terms of decidability
- References:
 - Ivan Bratko, *Prolog Programming for Artificial Intelligence*, Addison-Wesley, 2001. (Chapter 15)
 - Stuart J. Russell and Peter Norvig, *Artificial Intelligence: A Modern Approach*, Prentice-Hall International, 1995. (Chapter 6)



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Overview

程序代写代做 CS编程辅导

- Syntax of First-Order Logic
- Semantics of First-Order Logic
- Conjunctive Normal Form
- Unification
- First-Order Resolution
- Soundness and Completeness
- Decidability
- Conclusion



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Syntax of First-Order Logic

程序代写代做 CS编程辅导



- **Constant Symbols:** a, b, \dots (objects)
- **Variables:** x, y, \dots
- **Function Symbols:** $f, mother_of, sine, \dots$
- **Predicate Symbols:** $Mother, likes, \dots$
- **Quantifiers:** \forall (universal); \exists (existential)

WeChat: tutorcs

Assignment Project Exam Help

Terms: constant, variable, functions applied to terms (refer to objects)

Email: tutorcs@163.com

- **Atomic Sentences:** predicate applied to terms (state facts)
- **Ground (closed) term:** a term with no variable symbols

QQ: 749389476

<https://tutorcs.com>

Syntax of First-Order Logic

程序代写代做 CS编程辅导

Sentence ::= AtomicSentence | Sentence Connective Sentence
 | Quantifier Variable Sentence | \neg Sentence | (Sentence)
AtomicSentence ::= Predicate (Term*)
Term ::= Function (Term*) | Constant | Variable
Connective ::= \rightarrow | \wedge | \vee | \leftrightarrow
Quantifier ::= \forall | \exists
Constant ::= **a** | **John** | ...
Variable ::= x | *men* | ...
Predicate ::= P | **Red** | **Between** | ...
Function ::= f | **Father** | ...

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Converting English into First-Order Logic

程序代写代做 CS编程辅导



- Everyone likes lying on the beach — $\forall x \text{ Beach}(x)$
- Someone likes Fido — $\exists x \text{ Likes}(x, \text{Fido})$
- No one likes Fido — $\neg \exists x \text{ Likes}(x, \text{Fido})$
- Fido doesn't like everyone — $\neg \forall x \text{ Likes}(\text{Fido}, x)$
- All cats are mammals — $\forall x (\text{Cat}(x) \rightarrow \text{Mammal}(x))$
- Some mammals are carnivorous — $\exists x (\text{Mammal}(x) \wedge \text{Carnivorous}(x))$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Nested Quantifiers

程序代写代做 CS编程辅导



Note that the order of quantifiers is very important

- Everything likes everything — $\forall x \forall y \text{ Likes}(x, y)$
- Something likes something — $\exists x \exists y \text{ Likes}(x, y)$
- Everything likes something — $\forall x \exists y \text{ Likes}(x, y)$
- There is something liked by everything — $\exists y \forall x \text{ Likes}(x, y)$

WeChat: estutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Scope of Quantifiers

程序代写代做 CS编程辅导



- The *scope* of a quantifier in a formula ϕ is that subformula ψ of ϕ of which that quantifier is the main logical operator

- Variables belong to the *innermost* quantifier that mentions them

WeChat: cstutorcs

- Examples:

- $Q(x) \rightarrow \forall y P(x, y)$ — scope of $\forall y$ is $P(x, y)$

Assignment Project Exam Help

- $\forall z P(z) \rightarrow \neg Q(z)$ — scope of $\forall z$ is $P(z)$ but not $Q(z)$

- $\exists x (P(x) \rightarrow \forall x P(x))$

Email: tutorcs@163.com

- $\forall x (P(x) \rightarrow Q(x)) \rightarrow (\forall x P(x) \rightarrow \forall x Q(x))$

QQ: 749389476

<https://tutorcs.com>

Terminology

程序代写代做 CS编程辅导



- *Free-variable occurrence* —
 - All variables in an atomic formula
 - The free-variable occurrences in $\neg\phi$ are those in ϕ
 - The free-variable occurrences in $\phi \oplus \psi$ are those in ϕ and ψ for any connective \oplus
 - The free-variable occurrences in $\forall x \phi$ and $\exists x \phi$ are those in ϕ except for occurrences of x
- *Open formula* — A formula in which free variables occur
- *Closed formula* — A formula with no free variables
- Closed formulae are also known as *sentences*

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Semantics of First-Order Logic

程序代写代做 CS编程辅导

- A world in which a sentence is true under a particular interpretation is known as a *model* of that sentence under the interpretation
- Constant symbols an interpretation specifies which object in the world a constant refers to
- Predicate symbols an interpretation specifies which relation in the model a predicate refers to
- Function symbols an interpretation specifies which function in the model a function symbol refers to
- Universal quantifier is true iff all instances are true
- Existential quantifier is true iff one instance is true



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Conversion into Conjunctive Normal Form

程序代写代做 CS编程辅导

1. Eliminate implication



$$\phi \equiv \neg\phi \vee \psi$$

2. Move negation inwards (negation normal form)

$$\neg(\phi \wedge \psi) \equiv \neg\phi \vee \neg\psi$$

$$\neg(\phi \vee \psi) \equiv \neg\phi \wedge \neg\psi$$

$$\neg \forall x \phi \equiv \exists x \neg\phi$$

$$\neg \exists x \phi \equiv \forall x \neg\phi$$

$$\neg\neg\phi \equiv \phi$$

3. Standardise variables

$$(\forall x P(x)) \vee (\exists x Q(x))$$

$$\text{becomes } (\forall x P(x)) \vee (\exists y Q(y))$$

QQ: 749389476

<https://tutorcs.com>

Conversion into Conjunctive Normal Form

程序代写代做 CS编程辅导

4. Skolemise

$$\exists x P(x) \Rightarrow P(a)$$

$$\forall x \exists y P(x, y) \Rightarrow \forall x P(x, f(x))$$

$$\forall x \forall y \exists z P(x, y, z) \Rightarrow \forall x \forall y P(x, y, f(x, y))$$



WeChat: cstutorcs

5. Drop universal quantifiers

6. Distribute \wedge over \vee

Assignment Project Exam Help

$$(\phi \wedge \psi) \vee \chi \equiv (\phi \vee \chi) \wedge (\psi \vee \chi)$$

Email: tutorcs@163.com

7. Flatten nested conjunctions and disjunctions

$$(\phi \wedge \psi) \wedge \chi \equiv \phi \wedge \psi \wedge \chi; (\phi \vee \psi) \vee \chi \equiv \phi \vee \psi \vee \chi$$

QQ: 749389476

(8. In proofs, rename variables in separate clauses — *standardise apart*)

<https://tutorcs.com>

CNF — Example 1

程序代写代做 CS编程辅导



$$\forall x[(\forall y P(x, y)) \rightarrow \neg \forall y (Q(x, y) \wedge \neg R(x, y))]$$

$$1. \forall x[\neg(\forall y P(x, y)) \vee \neg \forall y (\neg(Q(x, y) \wedge \neg R(x, y)))]$$

$$2. \forall x[(\exists y \neg P(x, y)) \vee \exists y (Q(x, y) \wedge \neg R(x, y))]$$

$$3. \forall x[(\exists y \neg P(x, y)) \vee \exists z (Q(x, z) \wedge \neg R(x, z))]$$

$$4. \forall x[\neg P(x, f(x)) \vee (Q(x, g(x)) \wedge \neg R(x, g(x)))]$$

$$5. \neg P(x, f(x)) \vee (Q(x, g(x)) \wedge \neg R(x, g(x)))$$

$$6. (\neg P(x, f(x)) \vee Q(x, g(x))) \wedge (\neg P(x, f(x)) \vee \neg R(x, g(x)))$$

$$8. \neg P(x, f(x)) \vee Q(x, g(x))$$

$$\neg P(y, f(y)) \vee \neg R(y, g(y))$$

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

CNF — Example 2

程序代写代做 CS编程辅导



$\neg \exists x \forall y \forall z ((P(y) \vee Q(z)) \rightarrow (P(x) \vee Q(x)))$
 $\neg \exists x \forall y \forall z (\neg (P(y) \vee Q(z)) \vee (P(x) \vee Q(x)))$ [Eliminate \rightarrow]
 $\forall x \neg \forall y \forall z (\neg (P(y) \vee Q(z)) \vee (P(x) \vee Q(x)))$ [Move \neg inwards]
 $\forall x \exists y \neg \forall z (\neg (P(y) \vee Q(z)) \vee (P(x) \vee Q(x)))$ [Move \neg inwards]
 $\forall x \exists y \exists z \neg (\neg (P(y) \vee Q(z)) \vee (P(x) \vee Q(x)))$ [Move \neg inwards]
 $\forall x \exists y \exists z (\neg \neg (P(y) \vee Q(z)) \wedge \neg (P(x) \vee Q(x)))$ [Move \neg inwards]
 $\forall x \exists y \exists z ((P(y) \vee Q(z)) \wedge (\neg P(x) \wedge \neg Q(x)))$ [Move \neg inwards]
 $\forall x ((P(f(x)) \vee Q(g(x))) \wedge (\neg P(x) \wedge \neg Q(x)))$ [Skolemise]
 $(P(f(x)) \vee Q(g(x))) \wedge \neg P(x) \wedge \neg Q(x)$ [Drop \forall]

<https://tutorcs.com>

Unification

程序代写代做 CS编程辅导

- Unification takes two atomic formulae and returns a *substitution* that makes them look the same

- Example:



$z, w/f(b, c)\}$

- Note:

1. Each variable has at most one associated expression
2. No variable with an associated expression occurs within any associated expression

WeChat: cstutorcs

Assignment Project Exam Help

- $\{x/g(y), y/f(x)\}$ is not a substitution
- Substitution σ that makes a set of expressions identical known as a *unifier*
- Substitution σ_1 is a *more general unifier* than a substitution σ_2 if for some substitution τ , $\sigma_2 = \sigma_1\tau$.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

First-Order Resolution

程序代写代做 CS编程辅导

- Generalised Resolution Rule

For clauses $\chi \vee \Phi$ and $\neg \psi \vee \zeta$



$\chi \vee \Phi$

$\neg \psi \vee \zeta$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutores@163.com

QQ: 749389478

<https://tutorcs.com>

- Where θ is a unifier for atomic formulae Φ and ψ
- $\chi \vee \zeta$ is known as the *resolvent*

Resolution — Example 1

程序代写代做 CS编程辅导

$\vdash \exists x(P(x) \rightarrow \forall xP(x))$

CNF($\neg \exists x(P(x) \rightarrow \forall xP(x))$)

$\forall x \neg (\neg P(x) \vee \forall x P(x))$ [Drive inwards]

$\forall x (\neg \neg P(x) \wedge \neg \forall x P(x))$ [Drive inwards]

$\forall x (P(x) \wedge \exists x \neg P(x))$ [Drive inwards]

$\forall x (P(x) \wedge \exists z \neg P(z))$ [Standardise variables]

$\forall x (P(x) \wedge \neg P(f(x)))$ [Skolemise]

$P(x) \wedge \neg P(f(x))$ [Drop \forall]

1. $P(x)$ [\neg Conclusion]

2. $\neg P(f(y))$ [\neg Conclusion]

3. $P(f(y))$ [1. $\{x/f(y)\}$]

4. \square [2, 3. Resolution]

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Resolution — Example 2

程序代写代做 CS编程辅导



1. $P(f(x)) \vee Q(g(x))$ [\neg Conclusion]

2. $\neg P(y)$ [\neg Conclusion]

3. $\neg Q(z)$ [\neg Conclusion]

4. $P(f(a)) \vee Q(g(a))$ [1. $\{x/a\}$]

5. $\neg P(f(a))$ [2. $\{y/f(a)\}$]

6. $\neg Q(g(a))$ [3. $\{z/g(a)\}$]

7. $Q(g(a))$ [4, 5. Resolution]

8. \square [6, 7. Resolution]

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Resolution — Example 3

程序代写代做 CS编程辅导

1. $man(Marcus)$ [Premise]
2. $Pompeian(Marcus)$ [Premise]
3. $\neg Pompeian(x) \vee Roman(x)$ [Premise]
4. $ruler(Caesar)$ [Premise]
5. $\neg Roman(y) \vee loyaltyto(y, Caesar) \vee hate(y, Caesar)$ [Premise]
6. $loyaltyto(z, f(z))$ [Premise]
7. $\neg man(w) \vee \neg ruler(u) \vee tryassassinate(w, u)$ [Premise]
8. $tryassassinate(Marcus, Caesar)$ [Premise]
9. $\neg hate(Marcus, Caesar)$ [¬ Conclusion]
10. $\neg Roman(Marcus) \vee loyaltyto(Marcus, Caesar) \vee hate(Marcus, Caesar)$ [5. {y/Marcus}]
11. $\neg Roman(Marcus) \vee loyaltyto(Marcus, Caesar)$ [9, 10. Resolution]



WeChat: cstutorcs

Assassinat Project Exam/lyan

Email: tutores@163.com

QQ: 749389476

https://tutorcs.com

Resolution — Example 3

程序代写代做 CS编程辅导

12. $\neg \text{Pompeian}(\text{Marcus}) \vee \text{Roman}(\text{Marcus})$ [3. $\{x/\text{Marcus}\}$]
13. $\text{loyaltyto}(\text{Marcus}, \text{Caesar}) \vee \neg \text{Pompeian}(\text{Marcus})$ [11, 12. Resolution]
14. $\text{loyaltyto}(\text{Marcus}, \text{Caesar})$ [3. Resolution]
15. $\neg \text{man}(\text{Marcus}) \vee \neg \text{ruler}(\text{Caesar}) \vee \neg \text{tryassassinate}(\text{Marcus}, \text{Caesar}) \vee$
 $\neg \text{loyaltyto}(\text{Marcus}, \text{Caesar})$ [7. $\{w/\text{Marcus}, u/\text{Caesar}\}$]
16. $\neg \text{man}(\text{Marcus}) \vee \neg \text{ruler}(\text{Caesar}) \vee \neg \text{tryassassinate}(\text{Marcus}, \text{Caesar})$ [14,
15. Resolution]
17. $\neg \text{ruler}(\text{Caesar}) \vee \neg \text{tryassassinate}(\text{Marcus}, \text{Caesar})$ [1, 16. Resolution]
18. $\neg \text{tryassassinate}(\text{Marcus}, \text{Caesar})$ [4, 17. Resolution]
19. \square [8, 18. Resolution]

<https://tutorcs.com>

Email: tutorcs@163.com

QQ: 749389476

WeChat: [cstutorcs](#)

Assignment Project Exam Help



Soundness and Completeness

程序代写代做 CS编程辅导



- Resolution is
 - *sound* (if $\lambda \vdash \rho$, then $\lambda \models \rho$)
 - *complete* (if $\lambda \models \rho$, then $\lambda \vdash \rho$)

WeChat: cstutorcs

Decidability

- First-order logic is not decidable
- How would you prove this?

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Conclusion

程序代写代做 CS编程辅导



- First-order logic allows us to speak about objects, properties of objects and relationships between objects
- It also allows quantification over variables
- First-order logic is quite an expressive knowledge representation language; much more so than propositional logic
- However, we do need to add things like equality if we wish to be able to do things like counting
- We have also traded expressiveness for decidability
- How much of a problem is this?
- If we add (Peano) axioms for mathematics, then we encounter Gödel's famous *incompleteness theorem* (which is beyond the scope of this course)

WeChat: cs_tutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>