

程序代写代做 CS编程辅导



COMP4418 Knowledge Representation and Reasoning

Prolog II

WeChat: cstutorcs

Maurice Pagnucco
School of Computer Science and Engineering
COMP4418, Week 3

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Prolog

程序代写代做 CS编程辅导

- Compound terms can contain other compound terms
- A compound term can contain the same kind of term, i.e., it can be recursive:
`tree(tree(empty, jack, empty), fred, tree(empty, jill, empty))`
- “empty” is an arbitrary symbol used to represent the empty tree
- A structure like this could be used to represent a binary tree that looks like:



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Binary Trees

程序代写代做 CS编程辅导

- A *binary tree* is either empty or is a structure that contains data and left and right subtrees which are also binary trees
- To test if some datum is in the tree:

```
in_tree(X, tree(_, X, _)).
```

```
in_tree(X, tree(Left, Y, _) :-
```

```
    X \= Y,
```

```
    in_tree(X, Left).
```

```
in_tree(X, tree(_, Y, Right) :-
```

```
    X \= Y,
```

```
    in_tree(X, Right).
```

QQ: 749389476

<https://tutorcs.com>



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

The Size of a Tree

程序代写代做 CS编程辅导



- ```
tree_size(empty, 0).
tree_size(tree(Left, Right), N) :-
 tree_size(Left, LeftSize),
 tree_size(Right, RightSize),
 N is LeftSize + RightSize + 1.
```

WeChat: cstutorcs

Assignment Project Exam Help

- The size of the empty tree is 0
- The size of a non-empty tree is the size of the left subtree plus the size of the right subtree plus one for the current node

Email: [tutorcs@163.com](mailto:tutorcs@163.com)  
QQ: 749389476

<https://tutorcs.com>

# Lists


程序代写代做 CS编程辅导



- A *list* may be *nil* or it may be a *cons* cell that has a *head* and a *tail*. The tail is another list.

- A list of numbers, [1, 2, 3] can be represented as:

`list(1, list(2, list(3, nil)))`



Email: [tutorcs@163.com](mailto:tutorcs@163.com)

- Since lists are used so often, Prolog has a special notation:

`[1, 2, 3] = list(1, list(2, list(3, nil)))`

<https://tutorcs.com>


# Examples of Lists

$[X, Y, Z] = [1, 2, 3]$ ? Only the two terms on either side of the equals sign

$$X = 1$$

$$Y = 2$$

$$Z = 3$$



Value match terms in corresponding positions

$[X|Y] = [1, 2, 3]$ ?

The head and tail of a list are separated by using `|` to indicate that the term following the bar should unify with the tail of the list

$$X = 1$$

$$Y = [2, 3]$$

$[X|Y] = [1]$ ?

The empty list is written as `[]`

$$X = 1$$

$$Y = []$$

<https://tutorcs.com>

# More list examples

程序代写代做 CS编程辅导

```
[X, Y|Z] = [fred, jim, jill]
```



There must be at least two elements in the list on the right

```
X = fred
```

```
Y = jim
```

```
Z = [jill, mary]
```

WeChat: cstutorcs

```
[X|Y] = [[a, f(e)], [n, b, [2]]]
```

Assignment Project Exam Help

The right hand list has two elements:

```
X = [a, f(e)]
```

```
Y = [[n, b, [2]]]
```

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

```
[a, f(e)] [n, b, [2]]
```

QQ: 749389476

Y is the tail of the list,

[n, b, [2]] is just one element

<https://tutorcs.com>

# List Membership

程序代写代做 CS编程辅导

```
member(X, [X|_]).
member(X, [_|Y]) :-
 member(X, Y).
```



- Rules about writing recursive programs.

- Only deal with one element at a time
- Believe that the recursive program you are writing has already been written and works
- Write definitions, not programs

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



# Appending Lists

程序代写代做 CS编程辅导



- A commonly performed operation on lists is to append one list to the end of another (or, concatenate), e.g.,

```
append([1, 2, 3], [4, 5], [1, 2, 3, 4, 5]).
```

WeChat: cstutorcs

- Start planning by considering the simplest case:

```
append([], [1, 2, 3], [1, 2, 3]).
```

Assignment Project Exam Help

- Clause for this case:

```
append([], L, L).
```

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Appending Lists

程序代写代做 CS编程辅导



- Next case:  
    `append([1], [2],`
- Since `append([], [2], [2])`:  
    `append([H|T1], L, [H|T2]) :- append(T1, L, T2).`
- Entire program is:  
    `append([], L, L).`  
    `append([H|T1], L, [H|T2]) :-`  
        `append(T1, L,`

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Reversing Lists

程序代写代做 CS编程辅导



- `rev([1, 2, 3], [3, 2, 1])`
- Start planning by considering the simplest case:  
`rev([], [])`.

WeChat: cstutorcs

- Note:  
`rev([2, 3], [3, 2])`.

Assignment Project Exam Help

and  
`append([3, 2], [1], [3, 2, 1])`.

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Reversing Lists

程序代写代做 CS编程辅导



- Entire program is:

```
rev([], []).
```

```
rev([A|B], C) :-
```

```
 rev(B, D),
```

```
 append(D, [A], C).
```

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# An Application of Lists

程序代写代做 CS编程辅导

- Find the total cost of a list:

`cost(flange, 3).`

`cost(nut, 1).`

`cost(widget, 2).`

`cost(splice, 2).`



WeChat: cstutorcs

- We want to know the total cost of [flange, nut, widget, splice]

`total_cost([], 0).`

`total_cost([A|B], C) :-`

`total_cost(B, B_cost),`

`cost(A, A_cost),`

`C is A_cost + B_cost.`

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>