

1. Lines 191-216 (the line numbers are for reference only. They may be slightly different in your case):

```
if os.path.exists(model_adv_path + '.meta'):
    tf_model_load(sess, model_adv_path)
else:
    train(sess, loss2, x_train, y_train, state2,
          args=train_params, r=args=get_params())
    saver = tf.train.Saver()
    saver.save(sess, model_path)

evaluate2()
source_samples = test_examples
attack_iterations = 50
CW_LEARNING_RATE = .2
adv_inputs = x_test[:source_samples]
adv_ys = None
yname = "y"
cw_params = {'binary_search_steps': 1,
             'yname': adv_ys,
             'max_iterations': attack_iterations,
             'learning_rate': CW_LEARNING_RATE,
             'batch_size': source_samples,
             'initial_const': 10}
cw = CarliniWagnerL2(model2, sess=sess)
adv = cw.generate_np(adv_inputs, **cw_params)
eval_params = {'batch_size': np.minimum(nb_classes, source_samples)}
adv_accuracy = model_eval(sess, x, y, preds2, adv, y_test[:source_samples], args=eval_params)
print('Test accuracy on adv. examples generated by C&W: {0:.4f}'.format(adv_accuracy))
```

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>