



程序代写代做 CS编程辅导

Graph Anomaly Detection



WeChat: cstutorcs

Assignment Project Exam Help

COMP90073
Email: tutorcs@163.com
Security Analytics

QQ: 749389476
Sarah Erfani, CIS

<https://tutorcs.com>
Semester 2, 2021

Outline

程序代写代做 CS编程辅导

- Why graphs?
- Extracting features from graphs
- Random walk
- Graph Convolutional Networks (GCNs)



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

All Real-world Data Does Not “Live” on Grid

程序代写代做 CS编程辅导

Social networks
Citation networks
Communication networks
Multi-agent systems




QQ: 749389476
 Protein interaction
 networks
<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com




Road maps



Outliers vs. Graph Anomalies

程序代写代做 CS编程辅导

- Anomalies answer the question of *what is interesting about a network*
- Cannot always be treated independently lying in a multi-dimensional space
- They may exhibit inter-dependencies



WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>




Figure. Graph-based anomaly detection (left) vs.
Point-based anomaly detection (right).

Automating Botnet Detection with Graph Neural Networks [3]

程序代写代做 CS编程辅导



Email: tutorcs@163.com

Figure: An example of CAIDA networks embedded with a synthetic P2P botnet.
Most of the red botnet nodes are able to reach the rest of the botnet within several hops. The botnet has a faster mixing rate than the background network.

QQ: 749389476

<https://tutorcs.com>

Why Graphs?

程序代写代做 CS 编程辅导

- **Inter-dependent nature of the data:** Data objects are often related to each other and exhibit dependencies. Most relational data can be thought of as inter-dependent, which necessitates taking account for related objects in finding anomalies.
- **Powerful representation:** The multiple paths lying between objects effectively capture their long-range correlations. Moreover, a graph representation facilitates the representation of rich datasets enabling the incorporation of node and edge attributes/types [Assignment Project Exam Help](#)
- **Relational nature of problem domains:** The nature of anomalies could exhibit themselves as relational.
[Email: tutorcs@163.com](mailto:tutorcs@163.com)
<QQ: 749389476>
- **Robust machinery:** One could argue that graphs serve as more adversarially robust tools.
<https://tutorcs.com>



Graph-specific Challenges

程序代写代做 CS 编程辅导

- **Inter-dependent Objects:** The relational nature of the data makes it challenging to quantify the business of graph objects. While in traditional anomaly detection, the data points are treated as independent and identically distributed (i.i.d.) from each other, the objects in graph data have long-range correlations.
- **Variety of Definitions:** The definitions of anomalies in graphs are much more diverse than in traditional anomaly detection, given the rich representation of graphs.
- **Size of Search Space:** The enumeration of possible substructures is combinatorial which makes the problem of finding out the anomalies a much harder task. This search space is enlarged even more when the graphs are attributed as the possibilities span both the graph structure and the attribute space.

WeChat: **tutorcs**

Assignment Project Exam Help


Email: **tutorcs@163.com**

QQ: **749389476**

<https://tutorcs.com>

Machine Learning Lifecycle

程序代写代做 CS编程辅导



Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

Features From Graphs

程序代写代做 CS 编程辅导

Aim: *Efficient task-independent feature learning for machine learning with graphs!*



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com



QQ: 749389476

<https://tutorcs.com>

Features From Graphs

程序代写代做 CS编程辅导

Aim: *Efficient task-independent feature learning for machine learning with graphs!*



WeChat: cstutorcs

Assignment Project Exam Help



Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Features From Graphs

程序代写代做 CS 编程辅导
Aim: Efficient task-independent feature learning for machine learning with graphs!



WeChat: cstutorcs

Assignment Project Exam Help



Basic approaches to extract graph features:

- Adjacency matrix
 - node: degree
 - pairs: # of common neighbours
 - groups: cluster assignments
- QQ: 749389476
- <https://tutorcs.com>

Features From Graphs

程序代写代做 CS 编程辅导

Aim: *Efficient task-independent* feature learning for machine learning with graphs!



Assignment Project Exam Help

- Anomaly Detection
- Attribute Prediction
- Clustering
- Link Prediction
- ...


Basic approaches to extract graph features:

- Adjacency matrix
- node: degree
- pairs: # of common neighbours
- groups: cluster assignments

QQ: 749389476

<https://tutorcs.com>

- **Idea:** Map each node in a network into a low-dimensional space



WeChat: `tutorcs`

$$f: u \rightarrow \mathbb{R}^d$$

Assignment Project Exam Help

vector representation

Email: `tutorcs@163.com`

QQ: 749389476

<https://tutorcs.com>

Why Node Embedding?

程序代写代做 CS编程辅导

- Encode network information and generate node representation
- Distributed representation of nodes
- Similarity of embeddings indicates their network similarity




WeChat: cstutorcs

Assignment Project Exam Help



Adjacency Matrix




Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Latent Dimensions



- Anomaly Detection
- Attribute Prediction
- Clustering
- Link Prediction
- ...

Illustrative Example of Node Embedding

程序代写代做 CS编程辅导

f(



Input

<https://tutorcs.com>




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476



Output

Why Node Embedding is Hard?

- Modern machine learning toolboxes are designed for data defined on Euclidean domains (with simple sequences or grids).






Images

Text/Speech



<https://tutorcs.com>

程序代写代做 CS 编程辅导




Why Node Embedding is Hard?

程序代写代做 CS编程辅导

- But graphs are far more complex!
- Complex topographical structures (e.g., no spatial locality like grids)
- No fixed node ordering or point (i.e., the isomorphism problem)
- Often dynamic and have multimodal features.

WeChat: cstutorcs




Networks

Assignment Project Exam Help

Email: tutorcs@163.com

VS.
QQ: 749389476

<https://tutorcs.com>



Images



Text

程序代写代做 CS编程辅导



- **Node Related Applications:** Node Classification and semi-supervised learning, Anomaly detection, Recommendation/Retrieval/Ranking, Clustering and community.



- **Edge Related Applications:** Edge prediction and Graph Reconstruction.

- **Graph Related Application:** Graph Classification, Visualization and pattern discovery, Network compression.


Assignment Project Exam Help




Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>




e₁₂, e₂₃, e₃₁, e₄₆, e₅₆, e₆₇, e₇₈, e₄₅, e₇₉, e₃₄



Node Embedding

程序代写代做 CS 编程辅导

- **Aim:** Encode nodes so that similarity in the embedding space (e.g., dot product) approximates similarity in the original graph



Original graph

WeChat: cstutorcs
 $\text{ENC}(u)$


Assignment Project Exam Help
 $\text{ENC}(v)$

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Encode nodes




Embedding space

Node Embedding

程序代写代做 CS 编程辅导

$$similarity(u, v) \approx Z_v \cdot Z_u$$



Original graph


WeChat: $\text{ENC}(u)$
Assignment Project Exam Help
 $\text{ENC}(v)$

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Encode nodes



Embedding space

程序代写代做 CS 编程辅导

1. Define a node similarity function (i.e., a measure of similarity in the original graph)



- **Similarity function:** show the relationships in vector space map to the relationships in original graph

2. Define an encoder (i.e., a mapping from nodes to embeddings)

WeChat: cstutorcs

- **Encoder:** maps each node to a lowdimensional vector

Assignment Project Exam Help

$\text{ENC}(u) = Z_u \xrightarrow{\quad} d \text{ dimensional}$

Email: tutorcs@163.com

QQ: 749389476

3. Optimize the parameters of the encoder so that:

<https://tutorcs.com>

$$\text{similarity}(u, v) \approx Z_v \cdot Z_u$$

程序代写代做 CS编程辅导

Assume we have a graph G :

- V is the vertex set.
- A is the adjacency matrix (binary).
- *No node features or extra initialization is used!*



WeChat: cstutorcs

General Idea of Random Walk:


Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Estimate probability of visiting node v on a random walk starting from node u using some random walk strategy R



程序代写代做 CS编程辅导

Aim: Build an embedding lookup, where each node is assigned to a unique d -dimensional embedding vector. This serves similarity.

- Given $G = (V, E)$
- Run short fixed-length random walks starting from each node u on the graph using some strategy R
- For each node u collect $N_R(u)$, the set of nodes visited on random walks starting from u
- Goal is to learn a mapping $z: u \rightarrow \mathbb{R}^d$
- Given node u , we want to learn feature representations that are predictive of the nodes in its neighbourhood $N_R(u)$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



程序代写代做 CS 编程辅导

Intuition: Optimize embeddings to maximize likelihood of random walk co-occurrences (using Stochastic Gradient Descent)

$$\mathcal{L} = -\log(P(v|z_u)) \quad \begin{matrix} \text{Tutor CS} \\ \text{u} \in V \quad v \in N_R(u) \end{matrix}$$

$-\log(P(v|z_u)) \rightarrow$

Predicted probability of
 u and v co-occurring
on random walk

WeChat: cstutorcs

- Parameterize $P(v|z_u)$ using softmax

Assignment Project Exam Help

Email: tutorcs@163.com

$$P(v|z_u) = \frac{\exp(z_u \cdot z_v)}{\sum_{n \in V} \exp(z_u \cdot z_n)}$$

QQ: 749389476

https://tutorcs.com

程序代写代做 CS 编程辅导

$$\mathcal{L} = \sum_{u \in V} \sum_{v \in V} -\log \left(\frac{\exp(\mathbf{z}_u \cdot \mathbf{z}_v)}{\sum_{n \in V} \exp(\mathbf{z}_u \cdot \mathbf{z}_n)} \right)$$


- Nested sum over nodes results in $O(|V|^2)$ complexity!

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

$$\mathcal{L} = \sum_{u \in V} \sum_{v \in V} -\log \left(\frac{\exp(\mathbf{z}_u \cdot \mathbf{z}_v)}{\sum_{n \in V} \exp(\mathbf{z}_u \cdot \mathbf{z}_n)} \right)$$


A QR code with a small logo in the center. The logo features a graduation cap and the text "Tutor CS".

- Nested sum over nodes results in $O(|V|^2)$ complexity!

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\mathcal{L} = \sum_{u \in V} \sum_{v \in N(u)} -\log \left(\frac{\exp(\mathbf{z}_u \cdot \mathbf{z}_v)}{\sum_{n \in V} \exp(\mathbf{z}_u \cdot \mathbf{z}_n)} \right)$$

程序代写代做 CS 编程辅导



- Nested sum over nodes results in $O(|V|^2)$ complexity!

Negative sampling [7]: Instead of normalizing w.r.t. all nodes, just normalize against k random “negative samples” n_i .

WeChat: cstutorcs
Assignment Project Exam Help

$$\log \left(\frac{\exp(\mathbf{z}_u \cdot \mathbf{z}_v)}{\sum_{n \in V} \exp(\mathbf{z}_u \cdot \mathbf{z}_n)} \right) \approx \log(\sigma(\mathbf{z}_u \cdot \mathbf{z}_v)) - \sum_{i=1}^k \log(\sigma(\mathbf{z}_u \cdot \mathbf{z}_{n_i})), n_i \sim P_V$$

Email: tutorcs@163.com
QQ: 749389476

Sigmoid

<https://tutorcs.com>

random distribution over
all nodes

程序代写代做 CS编程辅导

- Unsupervised:
 - learns features that capture graph structure independent of the labels' distribution.
- Expressivity:
 - Flexible stochastic definition of node similarity
- Efficiency:
 - Does not need to consider all node pairs when training (only need to consider pairs that co-occur on random walks)
 - Easy to parallelize. Several random walkers (in different threads, processes, or machines) can simultaneously explore different parts of the same graph.
 - Relying on information obtained from short random walks make it possible to accommodate *small changes* in the graph structure without the need for global re-computation.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- $O(|V|)$ parameters are needed:

- Every node has its own embedding
 - No sharing of parameters between nodes



- Inherently “transductive”:

WeChat: cstutorcs

- Cannot generate embeddings for nodes that are not seen during training

Assignment Project Exam Help

- Do not incorporate node features:

Email: tutorcs@163.com

- Many graphs have features that we can and should leverage

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Assume we have a graph G :

- V is the vertex set.
- A is the adjacency matrix (binary).
- $X \in \mathbb{R}^{m \times |V|}$ is a matrix of node features



WeChat: cstutorcs

Aim: Generate node embeddings $Z \in \mathbb{R}^{n \times f}$ based on local network neighbourhoods



Assignment Project Exam Help

- Capturing structure
- Borrowing feature information

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>



Where Should We Begin?

- Real-world graphs:



程序代写代做 CS编程辅导



WeChat: cstutorcs
or this:
Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

Naïve Approach

程序代写代做 CS 编程辅导

- Join adjacency matrix and features
- Feed them into a deep ne



	a	b	c	d
a	0 1 0 1	0 1		
b	1 0 1 1	0 1		
c	0 1 0 0	1 1		
d	1 1 0 0	0 1		

WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

Issues with this approach:

QQ: 749389476

- Large number of parameters
- Not applicable to graphs of different sizes
- Not invariant to node ordering


<https://tutorcs.com>




Intuition of Graph Convolutional Neural Network (GCN)

程序代写代做 CS编程辅导

- Revisiting CNN:



WeChat: cstutorcs



- Goal is to generalize convolutions beyond simple lattices
- Leverage node features/attributes (e.g., text, images)

程序代写代做 CS 编程辅导

Image: Single CNN layer with 3x3 filter:



WeChat: cstutorcs

Graph: Transform information at the neighbours and combine it:

Assignment Project Exam Help

- Transform “messages” h_i from neighbours: $W_i h_i$
- Add them up: $\sum W_i h_i$

Email: tutorcs@163.com



程序代写代做 CS编程辅导



Figure. 2D Convolution vs. Graph Convolution


程序代写代做 CS编程辅导



<https://tutorcs.com>

程序代写代做 CS 编程辅导

- **Idea:** Node's neighbourhood defines its computation graph
- Learn how to propagate information across the graph to compute node features



Input graph

WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

- **Idea:** Node's neighbourhood defines its computation graph
- Learn how to propagate information across the graph to compute node features



Input graph

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

A

程序代写代做 CS 编程辅导

- **Idea:** Node's neighbourhood defines its computation graph
- Learn how to propagate information across the graph to compute node features



Input graph


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com



QQ: 749389476

<https://tutorcs.com>




程序代写代做 CS编程辅导


- **Idea:** Node's neighbourhood defines its computation graph
- Learn how to propagate information across the graph to compute node features



程序代写代做 CS编程辅导


Model can be of arbitrary depth:

- Nodes have embeddings 
- Layer-0 embedding of node  is input feature, x_u
- Layer-K embedding gets information from nodes that are K hops away



程序代写代做 CS 编程辅导

- Intuition: Nodes aggregate information from their neighbours using neural networks
- Every node defines a complete graph based on its neighbourhood!



Neural networks


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>



程序代写代做 CS编程辅导

- Neighbourhood aggregation: Key distinctions are in how different approaches aggregate information across neighbors



Input graph


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>




Neighbourhood Aggregation Functions

- Basic approach: Average information from neighbour and apply a neural network



程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



程序代写代做 CS编程辅导

- Basic approach: Average neighbour messages and apply a neural network



$$h_v^0 = x_v$$

$$h_v^k = \sigma \left(W_k \sum_{u \in N(v)} \frac{h_u^{k-1}}{\text{Ans}(v)} + B_k h_v^{k-1} \right), \forall k \in \{1, \dots, K\}$$


WeChat: cstutorcs
 Assignment Project Exam Help

$$z_v = h_v^K$$

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Deep Encoder Formulation

程序代写代做 CS 编程辅导

- Basic approach: Average neighbour messages and apply a neural network

$$h_v^0 = x_v \quad \leftarrow \quad \text{In the beginning, node features are equal to node features}$$

$$h_v^k = \sigma \left(W_k \sum_{u \in N(v)} \frac{h_u^{k-1}}{|N(v)|} + B_k h_v^{k-1} \right), \forall k \in \{1, \dots, K\}$$


WeChat: cstutorcs
Assignment Project Exam Help

$$z_v = h_v^K$$

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Deep Encoder Formulation

- Basic approach: Average neighbour messages and apply a neural network




Deep Encoder Formulation

- Basic approach: Average neighbour messages and apply a neural network



Deep Encoder Formulation

- Basic approach: Average neighbour messages and apply a neural network



Training Model Parameters

- We can feed these embeddings into any loss function and run stochastic gradient descent to train the parameters

$$h_v^k = \sum_{u \in N(v)} \frac{h_u^{k-1}}{|N(v)|} + B_k h_v^{k-1}$$


WeChat: cstutorcs
Assignment Project Exam Help
Tutoring parameters

Email: tutorcs@163.com


- Many aggregations can be performed efficiently by (sparse) matrix operations.
Let $H^{k-1} = [h_1^{k-1} \dots h_n^{k-1}]$ QQ: 749389476
 - Mean rule: $H^k = D^{-1} A H^{k-1}$ <https://tutorcs.com>
 - Spectral rule: $H^k = D^{-1/2} A D^{1/2} H^{k-1}$

Inductive Capability

- Many application settings constantly encounter previously unseen nodes



- Assignment Project Exam Help**
- Inductive node embedding Generalize to entirely unseen graphs
- Email: tutorcs@163.com



Variational Graph Autoencoder (VGAE) [4]

程序代写代做 CS编程辅导



<https://tutorcs.com>

Deep Anomaly Detection on Attributed Networks [7]

程序代写代做 CS编程辅导




<https://tutorcs.com>



One-Class Graph Neural Networks for Anomaly Detection in Attributed Networks [5]

程序代写代做 CS编程辅导



<https://tutorcs.com>

程序代写代做 CS编程辅导

- Why it is important to maintain data graph structure?
- How to use random walk for generating graph embedding?
- How embed evolving featured graphs?
- How use graph embedding for anomaly detection?



WeChat: cstutorcs

Assignment Project Exam Help

Next: Contrast Data Mining Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

References

程序代写代做 CS编程辅导

1. Leman Akoglu, Hanghang Tong, Danai Koutra, "Graph-based Anomaly Detection and Description: A Survey", Data Mining and Knowledge Discovery, 2015.
2. Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. "Deepwalk: Online learning of social representations". In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 701-710. 2014.
3. Jiawei Zhou, Zhiying Xu, Alexander M. Rush, and Minlan Yu. "Automating Botnet Detection with Graph Neural Networks." *arXiv preprint arXiv:2003.06344* (2020).
4. Thomas N. Kipf, and Max Welling. "Variational graph auto-encoders." *arXiv preprint arXiv:1611.07308*. 2016. code <https://github.com/tkipf/gae>
Email: tutorcs@163.com
QQ: [749389476](#)
5. Xuhong Wang, Baihong Jin, Ying Du, Ping Cui, and Yupu Yang, "One-Class Graph Neural Networks for Anomaly Detection in Attributed Networks", *arXiv preprint arXiv:2002.09594v2* (2020)

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: [749389476](#)

<https://tutorcs.com>

References

程序代写代做 CS编程辅导

6. Kaize Ding, Jundong Li, Rohit Bhanushali, and Huan Liu. "Deep anomaly detection on attributed networks." In *Proceedings of the SIAM International Conference on Data Mining*, pp. 604-602, 2019.
7. Hongyun Cai, Vincent W. Zheng, and Kevin Chen-Chuan Chang. "A comprehensive survey of graph embedding: Problems, techniques, and applications." *IEEE Transactions on Knowledge and Data Engineering* 30, no. 9 (2018): 1616-1637.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>