



程序代写代做 CS编程辅导



# Andromeda Detection Using Support Vector Machines

WeChat: cstutorcs

Assignment Project Exam Help

COMP90073  
Email: tutorcs@163.com  
Security Analytics

QQ: 749389476  
Sarah Erfani, CIS

<https://tutorcs.com>  
Semester 2, 2021

# Outline

程序代写代做 CS编程辅导

- Review of SVM
- Support Vector Data Description (SVDD)
- One-class Support Vector Machine (OCSVM)  
**WeChat: cstutorcs**
- Recent developments of OCSVM/SVDD  
**Assignment Project Exam Help**

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>




程序代写代做 CS 编程辅导

$\{\mathbf{x}_i, y_i\}$  where  $i = 1 \dots L$ ,  $y_i \in \{-1, 1\}$ ,  $\mathbf{x}_i \in \mathbb{R}^D$

This hyperplane can be described by  $\mathbf{x} \cdot \mathbf{w} + b = 0$  where:

- $\mathbf{w}$  is normal to the hyperplane
- $\frac{b}{\|\mathbf{w}\|}$  is the perpendicular distance from the hyperplane to the origin.

WeChat: cstutorcs



Assignment Project Exam Help

Classification rule

Email: tutorcs@163.com

$$f(\mathbf{x}) = \text{sign}(\mathbf{x} \cdot \mathbf{w} + b) = \begin{cases} +1 & \text{if } \mathbf{x} \cdot \mathbf{w} + b \geq 0 \\ -1 & \text{if } \mathbf{x} \cdot \mathbf{w} + b < 0 \end{cases}$$

QQ: 749389476

<https://tutorcs.com>

Find  $\mathbf{w}$  and  $b$  such that:

$$\mathbf{x}_i \cdot \mathbf{w} + b \geq 0 \text{ for } y_i = +1$$


$$\mathbf{x}_i \cdot \mathbf{w} + b < 0 \text{ for } y_i = -1$$

for all  $i = 1 \dots L$

Training objective

# Large Margin Classifiers – Revision

- Find hyperplane **maximises** the margin => B1 is better than B2
- Margin: sum of shortest distances from the planes to the positive/negative samples



程序代写代做 CS编程辅导

**Primal problem:** solve for  $w$  and  $b$

$$\min \frac{1}{2} \|w\|^2$$

s.t.



$$\phi(x_i) + b \geq 1, \quad \forall i = 1, \dots, n$$

**Equivalent dual problem formulation:** solve for  $\alpha_1, \dots, \alpha_L$ : Lagrange multipliers for each data point

WeChat: cstutorcs

$$\max_{\alpha} \sum_{i=1}^L \alpha_i - \frac{1}{2} \sum_{i=1}^L \sum_{j=1}^L \alpha_i \alpha_j y_i y_j K(x_i, x_j)$$

s.t.

Email: tutorcs@163.com

QQ: 749389476

$\sum_{i=1}^L \alpha_i y_i = 0$

More  
convenient to  
solve

程序代写代做 CS编程辅导

- **Slack variables**  $\xi_i$  can be added to allow misclassification of difficult or noisy examples, resulting margin soft.



$$\min_{w,b,\xi_i} \frac{1}{2} \|w\|^2 + C \sum_{i=1}^n \xi_i$$

s.t.

WeChat: cstutorcs


$$y_i(w^T \phi(x_i) + b) \geq 1 - \xi_i, \forall i = 1, \dots, n$$

$$\xi_i \geq 0, \forall i = 1, \dots, n$$


Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>



- **Assumption:** All (or majority of) training examples belong to *normal* (positive) class.
- **Objective:** identify anomalies by modeling normal pattern




WeChat: cstutorcs  
Assignment Project Exam Help  
Email: tutorcs@163.com  
QQ: 749389476



<https://tutorcs.com>

程序代写代做 CS 编程辅导

- Find the minimal circumscribing hyperball in high-dimensional space encompassing (enclosed) all the observations.



WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

- Find the minimal circumscribing hyperball in high-dimensional space encompassing (enclosed) all the observations.



WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

- Find the minimal circumscribing hyperball in high-dimensional space encompassing (enclosed) all the observations.



WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

- Find the minimal circumscribing hyperball in high-dimensional space encompassing (enclosed) all the observations



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

- Find the minimal circumscribing hyperball in high-dimensional space encompassing (enclosed) all the observations

$$\min_{R, \xi, a} R^2$$



WeChat: cstutorcs


$$\begin{aligned} \|\phi(x_i) - a\|^2 &\leq R^2 + \xi_i, \forall i = 1, \dots, n \\ \xi_i &\geq 0, \forall i = 1, \dots, n \end{aligned}$$

Assignment Project Exam Help

Email: tutorcs@163.com

where,

- $R$ : Radius of the ball
  - $\xi$ : Slack variable
  - $a$ : Center of the ball
  - $\phi(\cdot)$ : non-linear function
- QQ: 749389476
- <https://tutorcs.com>



Lagrangian form:

$$L(a, R, \xi, \alpha, \gamma) = R^2 + C \sum_{i=1}^n \xi_i$$

$$R^2 + \xi_i - (\phi(x_i) - a)^T(\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

where,  $\gamma_i \geq 0$  and  $\alpha_i \geq 0$  are Lagrange multipliers.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Lagrangian form:

$$L(a, R, \xi, \alpha, \gamma) = R^2 + C \sum_{i=1}^n \xi_i$$


$$R^2 + \xi_i - (\phi(x_i) - a)^T(\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

where,  $\gamma_i \geq 0$  and  $\alpha_i \geq 0$  are Lagrange multipliers.

WeChat: cstutorcs

Assignment Project Exam Help

Set the derivatives with respect to the primal variables  $R, a, \xi$  equal to zero, we get

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

- $\frac{\partial L}{\partial R} = ?$
- $\frac{\partial L}{\partial a} = ?$
- $\frac{\partial L}{\partial \xi_i} = ?$

程序代写代做 CS编程辅导

Lagrangian form:

$$L(a, R, \xi, \alpha, \gamma) = R^2 + C \sum_{i=1}^n \xi_i$$


 $R^2 + \xi_i - (\phi(x_i) - a)^T(\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$

where,  $\gamma_i \geq 0$  and  $\alpha_i \geq 0$  are Lagrange multipliers.

WeChat: cstutorcs  
**Assignment Project Exam Help**

Set the derivatives with respect to the primal variables  $R, a, \xi$  equal to zero, we get

- $\frac{\partial L}{\partial R} = 2R - 2R \sum_{i=1}^n \alpha_i = 0$        $\sum_{i=1}^n \alpha_i = 1$
- $\frac{\partial L}{\partial a} = ?$       QQ: 749389476
- $\frac{\partial L}{\partial \xi_i} = ?$       <https://tutorcs.com>

程序代写代做 CS编程辅导

Lagrangian form:

$$L(a, R, \xi, \alpha, \gamma) = R^2 + C \sum_{i=1}^n \xi_i$$


 $R^2 + \xi_i - (\phi(x_i) - a)^T(\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$

where,  $\gamma_i \geq 0$  and  $\alpha_i \geq 0$  are Lagrange multipliers.

WeChat: cstutorcs  
**Assignment Project Exam Help**

Set the derivatives with respect to the primal variables  $R, a, \xi$  equal to zero, we get

- $\frac{\partial L}{\partial R} = 2R - 2R \sum_{i=1}^n \alpha_i = 0$        $\sum_{i=1}^n \alpha_i = 1$
- $\frac{\partial L}{\partial a} = 2a \sum_{i=1}^n \alpha_i - 2 \sum_{i=1}^n \alpha_i \phi(x_i) = 0$        $a = \sum_{i=1}^n \alpha_i \phi(x_i)$
- $\frac{\partial L}{\partial \xi_i} = ?$       QQ: 749389476  
<https://tutorcs.com>

程序代写代做 CS编程辅导

Lagrangian form:

$$L(a, R, \xi, \alpha, \gamma) = R^2 + C \sum_{i=1}^n \xi_i$$


$$R^2 + \xi_i - (\phi(x_i) - a)^T(\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

where,  $\gamma_i \geq 0$  and  $\alpha_i \geq 0$  are Lagrange multipliers.

WeChat: cstutorcs  
**Assignment Project Exam Help**

Set the derivatives with respect to the primal variables  $R, a, \xi$  equal to zero, we get

- $\frac{\partial L}{\partial R} = 2R - 2R \sum_{i=1}^n \alpha_i = 0$        $\sum_{i=1}^n \alpha_i = 1$
- $\frac{\partial L}{\partial a} = 2a \sum_{i=1}^n \alpha_i - 2 \sum_{i=1}^n \alpha_i \phi(x_i) = 0$        $a = \sum_{i=1}^n \alpha_i \phi(x_i)$
- $\frac{\partial L}{\partial \xi_i} = C - \alpha_i - \gamma_i = 0$        $C = \alpha_i + \gamma_i$

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$

程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

$$= R^2 + C \sum_{i=1}^n \xi_i$$

$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a \sum_{i=1}^n \alpha_i - R^2 \sum_{i=1}^n \alpha_i - \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i$$

WeChat: cstutorcs  
 Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$



程序代写代做 CS编程辅导

$$L(\mathbf{a}, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - \mathbf{a})^T (\phi(x_i) - \mathbf{a}) - \sum_{i=1}^n \gamma_i \xi_i$$

$$= R^2 + C \sum_{i=1}^n \xi_i$$

$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T \mathbf{a} + \mathbf{a}^T \mathbf{a} - R^2 \sum_{i=1}^n \alpha_i - \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i$$

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ \mathbf{a} &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$

程序代写代做 CS编程辅导

$$L(\mathbf{a}, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - \mathbf{a})^T (\phi(x_i) - \mathbf{a}) - \sum_{i=1}^n \gamma_i \xi_i$$

$$= R^2 + C \sum_{i=1}^n \xi_i$$

$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T \mathbf{a} + \mathbf{a}^T \mathbf{a} \sum_{i=1}^n \alpha_i - R^2 \sum_{i=1}^n \alpha_i - \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i$$

WeChat: cstutorcs  
 Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ \mathbf{a} &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$



程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

$$= R^2 + C \sum_{i=1}^n \xi_i$$

$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a \sum_{i=1}^n \alpha_i - R^2 \sum_{i=1}^n \alpha_i - \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$



程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

$$= R^2 + C \sum_{i=1}^n \xi_i$$

$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a \sum_{i=1}^n \alpha_i - R^2 \sum_{i=1}^n \alpha_i - \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i$$

WeChat: cstutorcs  
 Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$



程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

$$= R^2 + C \sum_{i=1}^n \xi_i$$

$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a \sum_{i=1}^n \alpha_i - R^2 \sum_{i=1}^n \alpha_i - \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i$$

WeChat: cstutorcs  
 Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$



程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

$$= R^2 + C \sum_{i=1}^n \xi_i$$

$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a \underbrace{\sum_{i=1}^n \alpha_i}_{=1} - R^2 \underbrace{\sum_{i=1}^n \alpha_i}_{=1} - \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i$$

WeChat: cstutorcs  
 Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$



程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

~~$$= R^2 + C \sum_{i=1}^n \xi_i$$~~



~~$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a$$~~

$$\underbrace{\sum_{i=1}^n \alpha_i}_{=1} \underbrace{- R^2 \sum_{i=1}^n \alpha_i}_{=C} \underbrace{- \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i}_{=0}$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$

程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

~~$$= R^2 + C \sum_{i=1}^n \xi_i$$~~



$$\begin{aligned}
 &+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a \\
 &\quad \underbrace{\sum_{i=1}^n \alpha_i}_{=a^T a} \underbrace{\phi(x_i)^T a}_{=1} \underbrace{- R^2 \sum_{i=1}^n \alpha_i}_{=1} \underbrace{- \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i}_{=C}
 \end{aligned}$$

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}
 \sum_{i=1}^n \alpha_i &= 1 \\
 a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\
 C &= \alpha_i + \gamma_i
 \end{aligned}$$

程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

~~$$= R^2 + C \sum_{i=1}^n \xi_i$$~~

~~$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a$$~~

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$= \sum_{i=1}^n \alpha_i k(x_i, x_i) - a^T a$$

$$\begin{aligned} \sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i \end{aligned}$$



程序代写代做 CS编程辅导

$$L(a, R, \xi, \alpha, \gamma)$$

$$= R^2 + C \sum_{i=1}^n \xi_i - \sum_{i=1}^n \alpha_i (\phi(x_i) - a)^T (\phi(x_i) - a) - \sum_{i=1}^n \gamma_i \xi_i$$

$$= R^2 + C \sum_{i=1}^n \xi_i$$



$$+ \sum_{i=1}^n \alpha_i k(x_i, x_i) - 2 \sum_{i=1}^n \alpha_i \phi(x_i)^T a + a^T a \sum_{i=1}^n \alpha_i - R^2 \sum_{i=1}^n \alpha_i - \sum_{i=1}^n (\alpha_i + \gamma_i) \xi_i$$

WeChat: cstutorcs  
 Assignment Project Exam Help  
 Email: tutorcs@163.com

$$= \sum_{i=1}^n \alpha_i k(x_i, x_i) - a^T a$$

QQ: 749389476

$$= \sum_{i=1}^n \alpha_i k(x_i, x_i) - \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j k(x_i, x_j)$$

$$\begin{aligned}\sum_{i=1}^n \alpha_i &= 1 \\ a &= \sum_{i=1}^n \alpha_i \phi(x_i) \\ C &= \alpha_i + \gamma_i\end{aligned}$$

程序代写代做 CS编程辅导

$$\operatorname{argmax}_{\alpha} \sum_{i=1}^n \alpha_i k(x_i, x_i) - \frac{1}{2} \sum_{i,j} \alpha_j \alpha_i k(x_i, x_j)$$



s.t.

$$0 \leq \alpha_i \leq C,$$

WeChat: cstutorcs


$$\sum_{i=1}^n \alpha_i = 1$$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



程序代写代做 CS编程辅导

$$\operatorname{argmax}_{\alpha} \sum_{i=1}^n \alpha_i k(x_i, x_i) - \frac{1}{2} \sum_{i,j} \alpha_j \alpha_i k(x_i, x_j)$$




s.t.

$$0 \leq \alpha_i \leq C,$$

WeChat: cstutorcs

$$\sum_{i=1}^n \alpha_i = 1$$

Assignment Project Exam Help



- $\|\phi(x_i) - a\|^2 < R^2 \rightarrow \alpha_i = 0$  Email: tutorcs@163.com
- $\|\phi(x_i) - a\|^2 = R^2 \rightarrow 0 < \alpha_i < C$  QQ: 749389476
- $\|\phi(x_i) - a\|^2 > R^2 \rightarrow \alpha_i = C$  <https://tutorcs.com>

程序代写代做 CS编程辅导

- $a = \sum_{i=1}^n \alpha_i \phi(x_i)$



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- $a = \sum_{i=1}^n \alpha_i \phi(x_i)$
- $R^2 = \|\phi(x_i) - a\|^2$ , where support vectors with  $0 < \alpha_i < C$



$$R^2 = k(x_i, x_i) - \sum_{j=1}^n \alpha_j k(x_i, x_j) + \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j k(x_i, x_j)$$

WeChat: estutorcs  
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- $a = \sum_{i=1}^n \alpha_i \phi(x_i)$
- $R^2 = \|\phi(x_i) - a\|^2$ , where support vectors with  $0 < \alpha_i < C$



$$R^2 = k(x_i, x_i) - \sum_{j=1}^n \alpha_j k(x_i, x_j) + \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j k(x_i, x_j)$$

Assignment Project Exam Help

- New sample  $z$  is identified as normal if  
Email: [tutorcs@163.com](mailto:tutorcs@163.com)

$$\|z - a\|^2 = (z \cdot z) - \sum_{i=1}^n \alpha_i (z \cdot x_i) + \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j (x_i \cdot x_j) \leq R^2$$

QQ: 749389476  
<https://tutorcs.com>

程序代写代做 CS编程辅导

- Map input data into a high dimensional feature space
- Iteratively finds the maximum margin in the hyperplane which best separates the training data from the origin
- Decision boundary
- Formulate the optimization problem so it returns positive for as many of the  $N$  training examples as possible



WeChat: cstutorcs


$w \cdot \phi(x_i) - \rho = 0$   
**Assignment Project Exam Help**

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



程序代写代做 CS编程辅导

- Solve quadratic problem



$$\|w\|^2 + \frac{1}{vn} \sum_{i=1}^n \xi_i - \rho$$

WeChat: cstutorcs

$$(w \cdot \phi(x_i)) \geq \rho - \xi_i, \forall i = 1, \dots, n$$

Assignment Project Exam Help

- $\nu$ :

$$\nu = \frac{1}{c}$$

- $\nu = \frac{1}{c}$
- A prior probability that a data point in the training set is an anomaly.
- Regulates the trade-off between false positives and false negatives in this model.
- Due to the importance of  $\nu$ , OCSVM is often referred to as  $\nu$ -SVM

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- The problem can be simplified to



$$\alpha \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j k(x_i, x_j)$$

WeChat: cstutorcs

s.t.  $0 \leq \alpha_i \leq \frac{1}{\sqrt{n}}$      $\sum_{i=1}^n \alpha_i = 1$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- The problem can be simplified to



$$\sum_{\alpha} \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j k(x_i, x_j)$$

WeChat: cstutorcs

$$\text{s.t. } 0 \leq \alpha_i \leq \frac{1}{vn}, \quad \sum_{i=1}^n \alpha_i = 1$$

Assignment Project Exam Help

- Soft margin SVM for binary classification

Email: tutorcs@163.com

$$\operatorname{argmin}_{\alpha} \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j y_i y_j k(x_i, x_j) - \sum_{i=1}^n \alpha_i$$

$$\text{s.t. } \alpha_i \geq 0, \quad \sum_{i=1}^n \alpha_i y_i = 0$$

程序代写代做 CS编程辅导

- The problem can be simplified to



$$\alpha \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j k(x_i, x_j)$$

WeChat: cstutorcs

s.t.  $0 \leq \alpha_i \leq \frac{1}{vn}$ ,  $\sum_{i=1}^n \alpha_i = 1$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

- Anomaly score for new sample  $z$ :

- $Score(z) = \sum_{i=1}^n \alpha_i k(z, x_i) + b$
  - $Score(z) < 0$ : Anomaly
  - $Score(z) \geq 0$ : Normal



WeChat: cstutorcs

Assignment Project Exam Help

- For especial case of (invariant) kernels, e.g., Gaussian, SVDD  $\cong$  OCSVM

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Deep SVDD [4]

程序代写代做 CS编程辅导



Figure: Deep SVDD learns a neural network transformation  $\phi(\cdot; \mathcal{W})$  with weights  $\mathcal{W}$  from input space  $\mathcal{X} \subseteq \mathbb{R}^d$  to output space  $\mathcal{F} \subseteq \mathbb{R}^p$  that attempts to map most of the data network representations into a hypersphere characterized by centre  $c$  and radius  $R$  of minimum volume. Mappings of normal examples fall within, whereas mappings of anomalies fall outside the hypersphere.

QQ: 749389476

<https://tutorcs.com>

# Hybrid Deep-1SVM [5]

程序代写代做 CS编程辅导




Figure: Deep model (AE) is trained to extract features that are relatively invariant to irrelevant variations in the input, so that the one-class SVM (1SVM) can effectively separate the normal data from anomalies in the learned feature space, using linear kernel.  
<https://tutorcs.com>

# Deep Learning and One-class SVM based Anomalous Crowd Detection [6]

程序代写代做 CS编程辅导




Figure: Original video and foreground video sequence are taken as the input of two branches of channel, then movement tracks are extracted to produce continuous motion maps. Training and testing on a hybrid deep learning model SDAE-DBN-PSVM, then follows to achieve anomalous event detection

程序代写代做 CS编程辅导

- What is SVDD?
- How to derive dual formulation of SVDD?
- How to extend SVM to OCSVM?



WeChat: cstutorcs

Assignment Project Exam Help

Next: Autoencoders and their applications  
Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

## References

- 程序代写代做 CS 编程辅导
1. David M.J. Tax, Robert P.W. Duin, "Support Vector Data Description", Machine Learning, 2004
  2. Bernhard Schölkopf, John Shawe-Taylor, Alex J. Smola and Robert C. Williamson "Estimating the Support of a High-Dimensional Distribution". Neural Computation, 2001.
  3. Charu C. Aggarwal, "Outlier Analysis", Springer, 2016. Chapter 3
  4. Lukas Ruff, Robert Vandermeulen, Nico Goernitz, Lucas Deecke, Shoaib Ahmed Siddiqui, Alexander Binder, Emmanuel Müller, and Marius Kloft. "Deep one-class classification." In *International Conference on Machine Learning (ICML)*, pp. 4393-4402. 2018.
  5. Sarah Erfani, Sutharshan Rajasegarar, Shanika Karunasekera, and Christopher Leckie. "High-dimensional and large-scale anomaly detection using a linear one-class SVM with deep learning." *Pattern Recognition* 58 (2016): 121-134.
- WeChat: estutores
- Assignment Project Exam Help
- Email: tutorcs@163.com
- QQ: 749389476
- https://tutorcs.com

## References

6. Meng Yang, Sutharshan Rajasegarar, Sarah M. Erfani, and Christopher Leckie. "Deep Learning based SVM based Anomalous Crowd Detection." In *IEEE International Joint Conference on Neural Networks (IJCNN)*, pp. 1-8., 2019.



程序代写代做 CS编程辅导  
WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>