



1. Give example scenarios that it is better to use adaptive window over sliding window for anomaly detection. Justify your answer.
2. We used the following example to explain the step by step iLOF's measurements update. We included point 11 in *reachdist* update (Figure 1) but not in lrd update (Figure 2). Explain why, given $k=2$.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>




Figure 1: *reachdist* update




Figure 2: lrd update

3. In iLOF deleting a point p_i from the existing dataset *a/ways* increases the k -distances of R_k -NN of p_i . Justify the reason
4. In what case performance of MiLOF resembles to iLOF?

程序代写代做 CS编程辅导

5. In the lecture we saw how we can derive SVDD's dual formulation from its primal formulation. Now given OCSVM's primal formulation as below, derive its dual formulation.



$$\begin{aligned} & \|w\|^2 + \frac{1}{vn} \sum_{i=1}^n \xi_i - \rho \\ & \text{s.t.} \\ & \rho - \xi_i, \forall i = 1, \dots, n \\ & \xi_i \geq 0, \forall i = 1, \dots, n \end{aligned}$$

6. Use OneClassSVM in Splunk to perform unsupervised outlier detection.

Some useful information regarding the parameters: <https://scikit-learn.org/stable/modules/generated/sklearn.svm.OneClassSVM.html>

7. You may use LIBSVM (<https://www.csie.ntu.edu.tw/~cjlin/libsvm/>) for the following exercises. The web page provides the necessary information for parameter tuning. Download the KDDCUP data set from the UCI Machine Learning Repository <https://archive.ics.uci.edu/ml/datasets/kdd+cup+1999+data>
- Use SVDD and OCSVM to identify the attacks.
 - How many data points are common among the identified anomalies using different methods?

QQ: 749389476

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com