

程序代写代做 CS编程辅导



COM111-1

Foundations of Computer Science

WeChat: cstutorcs

Lecture 11: Algorithmic Analysis

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



UNSW  
SYDNEY

# Outline

程序代写代做 CS编程辅导

Motivation

Standard Approach



Examples

WeChat: cstutorcs

Simplifying with Worst case and Big-O

Assignment Project Exam Help

Recursive Examples

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Outline

程序代写代做 CS编程辅导

Motivation

Standard Approach

Examples

Simplifying with Worst case and Big O

Recursive Examples

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



# Algorithmic analysis: motivation

程序代写代做 CS编程辅导

Want to compare algorithms, particularly ones that can solve *arbitrarily large* instances



We would like to be able to talk about the resources (running time, memory, energy consumption) required by a program/algorithm as a function  $f(n)$  of some parameter  $n$  (e.g. the size) of its input.

## Example

How long does a given sorting algorithm take to run on a list of  $n$  elements?

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

## 程序代写代做 CS编程辅导

### Problems



- The exact resources required for an algorithm are difficult to pin down. Heavy dependent on:
  - Environment the program is run in (hardware, software, choice of language, external factors, etc)
  - Choice of inputs used
- Cost functions can be complex, e.g.

**Email: tutorcs@163.com**

$$2n \log(n) + (n - 100) \log(n)^2 + \frac{1}{2^n} \log(\log(n))$$

**QQ: 749389476**

Need to identify the “important” aspects of the function.

**<https://tutorcs.com>**

# Order of growth

程序代写代做 CS编程辅导

## Example

Consider two time-complexities:

- $f_1(n) = \frac{1}{10}n^2$  milliseconds
- $f_2(n) = 10n \log n$  milliseconds

WeChat: cstutorcs

Input size	$f_1(n)$	$f_2(n)$
100	0.01s	2s
1000	1s	30s
10000	1m40s	6m40s
100000	2h47m	1h23m
1000000	11d14h	16h40h
10000000	3y3m	8d2h

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Outline

程序代写代做 CS编程辅导

Motivation

Standard Approach



Examples

WeChat: cstutorcs

Simplifying with Worst case and Big O

Assignment Project Exam Help

Recursive Examples

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Algorithmic analysis

程序代写代做 CS编程辅导

Asymptotic analysis is about how costs **scale** as the input increases.



Standard (default) all

- Consider **asymptotic growth** of cost functions
- Consider **worst-case** (highest cost) inputs
- Consider **running time** cost: number of **elementary operations**

Assignment Project Exam Help  
Email: [tutorcs@163.com](mailto:tutorcs@163.com)

**NB**

Other common analyses include.

- Average-case analysis
- Space (memory) cost

QQ: 749389476

<https://tutorcs.com>



# Elementary operations

Informally: A single computational “step”: something that takes a constant number of computation cycles.



Examples:

- Arithmetic operation
- Comparison of two values
- Assignment of a value to a variable
- Accessing an element of an array
- Calling a function
- Returning a value
- Printing a single character

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

**NB**

*Count operations up to a constant factor,  $O(1)$ , rather than an exact number.*

# Outline

程序代写代做 CS编程辅导

Motivation

Standard Approach



Examples

WeChat: cstutorcs

Simplifying with Worst case and Big O

Assignment Project Exam Help

Recursive Examples

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Examples

程序代写代做 CS编程辅导



## Example

Squaring a number (First version):

WeChat: cstutorcs

```
square( $n$ ):
```

Assignment Project Exam Help

```
    return  $n * n$ 
```

Running time:  $O(1)$

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Running time vs Execution time

程序代写代做 CS编程辅导

Previous example shows one difference between running time and execution time.



In general, running time *approximates* execution time:

- Simplifying assumptions about elementary operations
- Hidden constants in big-O
- Big-O only looks at limiting performance as  $n$  gets large.

WeChat: cstutorcs

Assigning Project Exams Help

## Examples

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

- Implementations of `square(n)` will take longer as  $n$  gets bigger
- A program that "solves chess" will run in  $O(1)$  time.

QQ: 749389476

<https://tutorcs.com>

# Examples

程序代写代做 CS编程辅导



## Example

Squaring a number (iterative version):

```
square(n) :  
  r := 0  
  for i = 1 to n  
    r := r + n  
  return r
```

WeChat: cstutorcs

$O(1)$

Assignment Project Exam Help

$n$  times

$O(n)$

$O(1)$

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

$O(1)$

QQ: 749389476

Running time:  $O(1) + O(n) + O(1) = O(n)$

<https://tutorcs.com>

# Examples

程序代写代做 CS编程辅导



## Example

Cubing a number (using a squaring program):

`cube( $n$ ) :`

`$r := 0$`

`for  $i = 1$  to  $n$  :`

`$r := r + \text{square}(n)$`

`return  $r$`

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

$O(1)$

$O(n^2)$

$O(1)$

Running time:  $O(1) + O(n^2) + O(1) = O(n^2)$

# Outline

程序代写代做 CS编程辅导

Motivation

Standard Approach



Examples

WeChat: cstutorcs

Simplifying with Worst case and Big-O

Assignment Project Exam Help

Recursive Examples

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Worst-case and big-O

程序代写代做 CS编程辅导

Worst-case input assumption and big-O combine to *simplify* the analysis:



## Example

Sum of squares (Using second squaring program):

sumOfSquares( $n$ ):

$r := 0$

for  $i = 1$  to  $n$ :

$r := r + \text{square}(i)$

return  $r$

WeChat: cstutorcs

Assignment Project Exam Help  $O(1)$

Email: [tutorcs@163.com](mailto:tutorcs@163.com)  $O(1)$  times  $O(n^2)$

QQ: 749389476  $O(1)$

Running time:  $O(1) + O(n) + O(1) = O(n)$



# Worst-case and big-O

程序代写代做 CS编程辅导

Worst-case input assumptions and big-O combine to *simplify* the analysis:



## Example

Finding an element ( $x$ ) in an array ( $L$ ) of length  $n$ :

WeChat: [cstutorcs](#)

```
find( $x, L$ ):  
  for  $i = 0$  to  $n - 1$ :  
    if  $L[i] == x$ :  
      return  $i$   
  return  $-1$ 
```

$O(1)$  |  $O(n)$  times |  $O(n)$   
Email: [tutorcs@163.com](mailto:tutorcs@163.com)  
 $O(1)$  |  $O(1)$   
QQ: [749389476](#) |  $O(1)$

Running time:  $O(n) + O(1) = O(n)$

<https://tutorcs.com>

# Worst-case and big-O

程序代写代做 CS编程辅导

Worst-case input assumptions and big-O combine to *simplify* the analysis:



NB

*Simplifications might lead to sub-optimal bounds, may have to do a better analysis to get best bounds*

- *Finer-grained upper bound analysis*
- *Analyse specific cases to find a matching lower bound ( $\text{big-}\Omega$ )*

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

NB

$\text{Big-}\Omega$  is a **lower bound** analysis of the worst-case; NOT a “best-case” analysis.

QQ: 749389476

<https://tutorcs.com>

# Worst-case and big-O

程序代写代做 CS编程辅导

Analyse specific cases to find a matching lower bound (big- $\Omega$ )

## Example

Let  $L_n$  be an  $n$ -element array of 0's.

Finding an element ( $x$ ) in an array ( $L$ ) of length  $n$ :

```
find( $x, L$ ):
```

```
  for  $i = 0$  to  $n - 1$ :
```

```
    if  $L[i] == x$ :
```

```
      return  $i$ 
```

```
  return  $-1$ 
```

WeChat: cstutorcs

Assignment & Project Exam Help

$\Omega(1)$

$\Omega(n)$  times

$\Omega(n)$

Email: [tutors@163.com](mailto:tutors@163.com)

$\Omega(1)$

QQ: 749389476

$\Omega(1)$

Running time of  $\text{find}(1, L)$ :  $\Omega(n)$

<https://tutorcs.com>

Therefore, running time of  $\text{find}(x, L)$ :  $\Theta(n)$



# Outline

程序代写代做 CS编程辅导

Motivation

Standard Approach

Examples

Simplifying with Worst case and Big O

Recursive Examples



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Recursive examples

## Example

程序代写代做 CS编程辅导

Factorial:

```
fact(n) :
```

```
  if n == 0
```

```
    return 1
```

```
  else :
```

```
    return n * fact(n - 1)
```

$O(1)$

$O(1)$

WeChat: cstutorcs

$O(1) + T(n - 1)$

Assignment Project Exam Help

Running time for  $\text{fact}(n)$ :  $T(n)$ , where:

Email: tutorms@163.com

$$T(0) \in O(1) + O(1) = O(1)$$

QQ: 749389476

$$T(n) = T(n - 1) + O(1)$$

https://tutorms.com

$$\in O(n)$$

Running time:  $T(n) \in O(n)$

# Recursive examples

## Example

程序代写代做 CS编程辅导

Summing elements of list (length  $n$ ):

```
sum(L) :
```

```
  if L.isEmpty
```

```
    return 0
```

```
  else :
```

```
    return L.data + sum(L.next)
```

$O(1)$

$O(1)$

WeChat: cstutorcs

Assignment Project Exam Help  $O(1) + T(n-1)$

Running time for  $\text{sum}(L)$ :  $T(n)$ , where:

Email: tutores@f63.com

$$T(0) \in O(1) = O(1)$$

$$T(n) = T(n-1) + O(1)$$

https://tutores.com

$$\in O(n)$$

# Recursive examples

## Example

程序代写代做 CS编程辅导

Insertion sort (L has  $n$  elements):



```
sort(L)
  if L.is_empty() :  $O(1)$ 
    return L  $O(1)$ 
  else :
    L2 := sort(L.next)  $T(n-1)$ 
    insert L.data into L2  $O(n)$ 
    return L2  $O(1)$ 
```

WeChat: cstutorcs  
Assignment Project Exam Help  
Email: [tutorcs@163.com](mailto:tutorcs@163.com)

Running time for  $\text{sort}(L)$ :  $T(n)$ , where:

$$\begin{aligned} T(0) &\in O(1) + O(1) = O(1) \\ T(n) &= T(n-1) + O(n) + O(1) \\ &\in O(n^2) \end{aligned}$$


QQ: 749389476  
<https://tutorcs.com>

# Recursive examples

## Example

程序代写代做 CS编程辅导

Euclidean algorithm for  $\text{gcd}(m, n)$  ( $N = m + n$ ):



```
gcd(m, n) :  
  if m > n :  
    return gcd(m - n, n)  $O(1)$   
  else if n > m :  
    return gcd(m, n - m)  $\leq T(N - 1)$   
  else :  
    return m  $O(1)$ 
```

WeChat: cstutors

Assignment Project Exam Help

Email: tutors@163.com

Running time for  $\text{gcd}(m, n)$ :  $T(N)$ , where:

$$\begin{aligned} T(1) &\in O(1) \\ T(N) &\leq T(N-1) + O(1) \\ &\in O(N) \end{aligned}$$

QQ: 749389476

https://tutors.com



# Recursive examples

程序代写代做 CS编程辅导



## Example

Euclidean algorithm for  $\gcd(m, n)$  ( $N = m + n$ ):

Running time:  $O(N)$

WeChat: cstutorcs

Assignment Project Exam Help

## NB

*$N$  is not the input size. Input size is  $\log(m) + \log(n)$*

QQ: 749389476


<https://tutorcs.com>

# Recursive examples

## Example

程序代写代做 CS编程辅导

Faster Euclidean algorithm for  $\text{gcd}(m, n)$  ( $N = m + n$ ):



```
gcd(m, n) :  
  if m > n > 0 :  $O(1)$   
    return gcd(m % n, n)  $\leq T(N/1.5)$   
  else if n > 0 :  $O(1)$   
    return gcd(m, n % m)  $\leq T(N/1.5)$   
  else : return max(m, n)  $O(1)$ 
```

Email: [tutors@163.com](mailto:tutors@163.com)

Running time for  $\text{gcd}(m, n)$ :  $T(N)$ , where:

$$\begin{aligned} T(1) &\in O(1) \\ T(N) &\leq T(N/1.5) + O(1) \\ &\in O(\log N) \end{aligned}$$

# Recursive examples

程序代写代做 CS编程辅导



## Example

Faster Euclidean algorithm  $\gcd(m, n)$  ( $N = m + n$ ):

What about lower bounds?

WeChat: cstutorcs

- Can show algorithm takes  $k$  steps to compute  $\gcd(F_k, F_{k-1})$  where  $F_k$  is the  $k$ -th Fibonacci number
- Can show  $1.5^k \leq F_k \leq 2^k$ , so  $k \in \Theta(\log F_k)$
- Therefore  $\gcd(F_k, F_{k-1}) \in \Omega(\log(F_k + F_{k-1}))$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Exercise

程序代写代做 CS编程辅导

## Exercise

RW: 4.3.22 The following algorithm raises a number  $a$  to a power  $n$ .



WeChat: [tutorcs](#)

Assignment, Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

Determine the running time of this algorithm.

# Exercise

## Exercise

程序代写代做 CS编程辅导

RW: 4.3.21 The following algorithm gives a fast method for raising a number  $a$  to a power  $n$ .



Fast-exp( $a, n$ ) :

$p = 1$   
WeChat: cstutorcs

$q = a$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

$i = n$   
 $p = p * q$   
 $q = q * q$   
 $i = \lfloor i/2 \rfloor$   
<https://tutorcs.com>

return  $p$

Determine the running time of this algorithm.