

In [ ]: %run utils.py

COMS 4281 Intro to Quantum Computing

程序代写代做CS编程辅导

## Problem Set 2 Quantum Algorithms

Due: November 11, 2022, 11:59pm.

Collaboration is encouraged (teams of at most 3). Please read the syllabus carefully for the rules of collaboration. In particular, everyone must write their own solutions



Write your collaborators here:

WeChat: cstutorcs

## Problem 1: Basic Fourier Math

### Problem 1.1

Email: tutorcs@163.com

For two strings  $x, y \in \{0, 1\}^n$  let  $x \cdot y$  denote

QQ: 749389476

$$x_1 y_1 + x_2 y_2 + \cdots + x_n y_n \pmod{2}.$$

Prove that for all  $x \in \{0, 1\}^n$ ,

https://tutorcs.com

$$\sum_{y \in \{0, 1\}^n} (-1)^{x \cdot y} = \begin{cases} 0 & \text{if } x \neq 0^n \\ 2^n & \text{if } x = 0^n \end{cases}$$

## Solution

### Problem 1.2

Let  $\omega_n = \exp\left(\frac{2\pi i}{n}\right)$  denote the  $n$ -th root of unity. Prove that for all integers  $j$ ,

$$\sum_{k=0}^{n-1} \omega_n^{jk} = \begin{cases} 0 & \text{if } j \text{ is not a multiple of } n \\ n & \text{if } j \text{ is a multiple of } n \end{cases}$$

## Solution

## Problem 1.3

Let  $N$  denote a positive integer between  $2^{n-1}$  and  $2^n$  and let  $1 < x < N$  denote an integer such that  $\gcd(x, N) = 1$  meaning that  $x$  is coprime to  $N$ . Let  $r$  be the order of  $x$  modulo  $N$ ; meaning that  $x^r \equiv 1 \pmod{N}$  (i.e., dividing  $x^r$  by  $N$  yields a remainder of 1). Recall the unitary map acting on  $n$  qubits such that for all  $0 \leq y < 2^n$ ,



$$\begin{cases} |xy \bmod N\rangle & \text{if } y < N \\ |y\rangle & \text{otherwise} \end{cases}$$

and recall the

$$|u_s\rangle = \frac{1}{\sqrt{r}} \sum_{k=0}^{r-1} \omega_r^{ks} |x^k \bmod N\rangle.$$

Show that

**WeChat: cstutorcs**

**Assignment Project Exam Help**

**Solution Email: tutorcs@163.com**

**Problem 1.4**

**QQ: 749389476**

Recall the Fourier Transform unitary  $F_N$  that acts as follows: for all  $0 \leq j < N$ ,

**https://tutorcs.com**

where

$$|f_j\rangle = \frac{1}{\sqrt{N}} \sum_{k=0}^{N-1} \omega_N^{-jk} |k\rangle.$$

Compute the vector  $F_N |j\rangle$ .

**Note:** The definition of  $|f_j\rangle$  differs from the one presented in class, because the exponent of  $\omega_N$  is  $-jk$  rather than  $jk$ .

**Solution**

## Problem 2: Modified Simon's Algorithm

In this problem you will analyze a variant of Simon's Problem. Suppose you are given black-

box query access to a function  $f : \{0, 1\}^n \rightarrow \{0, 1\}^n$  that encodes **two** secrets  $s, t \in \{0, 1\}^n$ . This means that

$$f(x) = f(y) \text{ if and only if } x + y \in \{0^n s, t, s + t\}$$

We will assume that  $s, t$  are both nonzero and are not equal to each other.

**Note:** the sum of two bit strings is another string where we've XOR'd the coordinates of  $x, y$ .



## Problem

Given such a function  $f$ , what is the size of its range? Meaning, how many possible strings can be output by  $f$ ?

## Problem 2.2 WeChat: cstutorcs

Write a classical + quantum hybrid algorithm that makes  $\text{poly}(n)$  queries to  $f$  and outputs, with high probability, the secrets  $s, t$ . You should use Simon's Algorithm for inspiration.

## Solution Email: tutorcs@163.com

## Problem 2.3 QQ: 749389476

Prove that your algorithm works.

## Solution https://tutorcs.com

## Problem 2.4

What if we now considered the situation where the function  $f$  is hiding not two but  $k$  secrets  $s^{(1)}, \dots, s^{(k)}$  (which are all nonzero and distinct strings). How would your answers to 7.2 and 7.3 change?

## Solution

## Problem 3: Quantum Minimum Finding

## Problem 3.1

Let  $M \geq 2$  be an integer. Devise a quantum algorithm that, in expectation, makes  $O(\sqrt{N})$  queries to a function  $f : \{0, 1\}^n \rightarrow \{0, 1, \dots, M-1\}$ , and computes  $\min_x f(x)$ . You can assume that  $f$  is injective.

**Hint:** Use that Grover's algorithm, when run on a function  $g : \{0, 1\}^n \rightarrow \{0, 1\}$  with  $T$  solutions, outputs a uniformly random  $x$  such that  $g(x) = 1$  using  $c\sqrt{N/T}$  queries in expectation for some constant  $c$ .

**Hint:** Your algorithm has bounded running time; you just need to show that the expected number of queries the algorithm finds the minimum is  $O(\sqrt{N})$ .

Solution



### Problem 3.2

Show that, assuming that Grover's algorithm is optimal for unstructured search (meaning that any quantum algorithm finding a preimage of  $f : \{0, 1\}^n \rightarrow \{0, 1\}$  requires  $\Omega(\sqrt{N})$  queries to  $f$ ), any quantum algorithm that finds the minimum of a function with high probability must also make  $\Omega(\sqrt{N})$  queries.

Solution

### Problem 3.3

Now let's implement our minimum finding algorithm for arbitrary 5 qubit functions. Below are helpers for converting functions into quantum oracles, and an implementation of the Grover's Diffusion gate, use those to help you implement minimum search, and test is on the examples given below.

For fun, track the number of oracle calls you use (`num_oracle_calls`), but you won't lose points for using too many oracle calls if your solution is correct asymptotically.

```
In [ ]: num_oracle_calls = 0

def inc_num_oracle_calls():
    global num_oracle_calls
    num_oracle_calls += 1

def reset_num_oracle_calls():
    global num_oracle_calls
    num_oracle_calls = 0

def append_oracle(input_circuit: QuantumCircuit,
                  f: Callable[[int], bool],
                  quantum_registers: List[int]) -> QuantumCircuit:
    ...
```

```

append_oracle takes a boolean function (with inputs from 0 to 31) and apper
...

inc_num_oracle_calls()
oracle_gate = UnitaryGate(np.diag([(-1)**f(i) for i in range(32)]))
input_circuit.append(oracle_gate, quantum_registers)
return input_circuit

```

程序代写代做 CS编程辅导

```

def append_diffusion_gate(input_circuit: QuantumCircuit,
                           quantum_registers: List[int]) -> QuantumCircuit:
    ...
    Takes an input circuit and appends a diffusion gate to the registers.
    The quantum registers must be length 5.
    ...

    if len(quantum_registers) != 5:
        return input_circuit
    for i in quantum_registers:
        input_circuit.h(i)
        diffuse = -1*np.eye(32)
        diffuse[0,0] = 1
        input_circuit.append(UnitaryGate(diffuse), quantum_registers)
    for i in quantum_registers:
        input_circuit.h(i)
    return input_circuit

def get_most_likely_outcome(quantum_circuit: QuantumCircuit) -> int:
    backend = Aer.get_backend('qasm_simulator')
    job_sim = backend.run(transpile(quantum_circuit, backend), shots=5024)
    result_sim = job_sim.result()
    counts = result_sim.get_counts(quantum_circuit)
    return int(max(counts, key = counts.get), 2)

```

WeChat: estutores

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Solution

In [ ]: <https://tutorcs.com>

Below are some suggested templates for functions that would be useful to implement. You don't have to use them if you don't want.

```

...

def grovers_search_known_sols(f: Callable[[int], bool], num_sols: int) -> int:
    ...
    Runs Grovers search, assuming there are num_sols number of solutions (we'll assume that the input space is dimension 32).
    ...

def grovers_search(f: Callable[[int], bool]) -> int:
    ...
    Runs Grovers search with an unknown number of solutions by halving the guess. Returns -1 if no answer is found.
    ...

### ===== END CODE =====

def find_min(f: Callable[[int], int]) -> int:

```

```
reset_num_oracle_calls()
y = random.randrange(0, 32)
```

```
### ===== BEGIN CODE =====
### ===== END CODE =====

return y
```

程序代写代做 CS编程辅导

Test your code with the following examples.

```
In [ ]: f1 = lambda x: 10 - np.sin(x / 16)
print("Minimum of f1 is: ", find_min(f1))
print("Oracle calls used: ", num_oracle_calls)
```

```
In [ ]: f2 = lambda x: 3
print("Minimum of f2 is: ", find_min(f2))
print("Oracle calls used: ", num_oracle_calls)
```

```
In [ ]: f3 = lambda x: 10 - np.sin(x / 16)
print("Minimum of f3 is: ", find_min(f3))
print("Oracle calls used: ", num_oracle_calls)
```

WeChat: cstutorcs

## Assignment Project Exam Help

### Problem 4: Exploring Order Finding

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

In this problem, we'll explore the quantum algorithm for Order Finding (which is different from the one covered in class; in fact this one is closer to the way Peter Shor implemented it). Consider the following function

$$f(x) = 3^x \bmod 16$$

where  $x$  ranges from 0 to 15, so that  $x$  can be represented using 4 bits.

<https://tutorcs.com>

#### Problem 4.1

What is the period  $r$  of this function? Meaning, what value of  $r$  is such that  $f(x + r) = f(x)$  for all  $x$ ?

#### Solution

#### Problem 4.2

Let's see how we could've figured this out using quantum computation! First, we create a quantum circuit with 8 qubits and 4 classical bits to store measurement outcomes.

Add gates to the order finding circuit to get to the following state:

$$\frac{1}{\sqrt{16}} \left( \sum_{i=0}^{15} |i\rangle \right) \otimes |0\rangle$$

Note that here  $|i\rangle$  and  $|0\rangle$  refer to integers, but in your circuit they will need to be represented in binary using 4 bits.

程序代写做CS编程辅导

```
In [ ]: order_finding_circuit = QuantumCircuit(8,4)

### =====
### =====
order_finding_circuit.draw(output="mpl")
```



## Problem 4.2

WeChat: cstutors

We provide code that implements the  $U_f$  unitary, which acts on 8 qubits (4 for input, 4 for ancilla) as follows:

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

```
In [ ]: def reverse_bits(i: int) -> int:
    '''
    Reverses the bits of a number up to 5 bits (0 through 31)
    '''
    return int('{:08b}'.format(i)[::-1], 2)

#This function returns the UnitaryGate object that you want to append to your circuit
def U_f() -> UnitaryGate:
    unitary = np.zeros([256, 256])
    for i in range(16):
        for j in range(16):
            input_basis_state = i * 16 + j
            exponentiated_j = pow(3, i, 16) ^ j
            output_basis_state = i * 16 + exponentiated_j
            unitary[reverse_bits(input_basis_state), reverse_bits(output_basis_state)] = 1
    return UnitaryGate(unitary, "U_f")

### ===== BEGIN CODE =====

### ===== END CODE =====

order_finding_circuit.draw(output="mpl")
```

## Problem 4.3

Suppose you measured the second register (the last 4 qubits) of the state described in Problem 4.2. What are the possible outcomes and their probabilities? What are the corresponding post-measurement states?

程序代写代做 CS编程辅导

Solution

Problem



Let's simulate the second register and collect measurement statistics. Write code to find the probability of each measurement outcome (for example, the integer 1 a certain percentage of the time, the integer 3 occurs  $Y\%$  of the time, etc.).

Note that the convention in Qiskit is to use little-endian representation of integers: the least significant bit goes first (so the ordering goes like  $|0000\rangle, |1000\rangle, |0100\rangle, |1100\rangle, \dots$ ).

WeChat: cstutorcs

```
In [ ]: order_finding_circuit.measure([4,5,6,7], [0,1,2,3])
order_finding_circuit.draw(output="mpl")
```

```
In [ ]: backend = Aer.get_backend("statevector_simulator")
result = execute(order_finding_circuit, backend=backend, shots=1024).result()
result.get_counts()
# Note that the output strings are reverse order
```

Assignment Project Exam Help

Email: tutors@163.com

```
In [ ]: ### ===== BEGIN CODE =====

### ===== END CODE =====
```

QQ: 749389476

Problem 4.5

<https://tutorcs.com>

Now let's get the post-measurement state *conditioned* on the second register measuring  $|j\rangle$  for  $j = 3$ . First, suppose we measure the second register and obtain outcome  $|3\rangle$ . What will the post measurement state on the first register be?

Solution

Problem 4.6

Now let's validate empirically that the post measurement state is what we found above. We've already got some skeleton code for you set up; you should fill in the rest. The result is that the variable `postmeasurement_state` should be the post measurement state of the 8 qubits, conditioned on the second register being in the state  $|3\rangle$  (or, in binary,  $|1100\rangle$ ).

```
In [ ]: j = 3
```



```
j_in_rev_binary = '1100' # Note this bitstring is in reverse order. Reversing i
#just repeating this 100 times until you get the result you want (the number 10
for k in range(100):
    result = execute(order_finding_circuit, backend=backend, shots=1).result()
### ==== BEGIN CODE =====
### ===== E=====
postmeasurement = circuit.get_statevector()
```

The variable `first_register` is a vector of dimension 1024. We are interested in the state of `first_register` (first 5 qubits), so let's extract that into a 32-dimensional vector `first`.

We then plot the squares of the amplitudes of `first_register`.

In [ ]:

```
first_register = [0]
for i in range(16):
    index = reverse_bits(i*16 + i)
    ampl = postmeasurement_state[index]
    first_register.append(ampl)

plt.bar(range(16), [np.absolute(f)**2 for f in first_register])
```

Does the plot agree with your theoretical calculations of the post-measurement state?

**Solution**

**Problem 1** <https://tutorcs.com>

Let  $|\psi\rangle$  denote the post-measurement state corresponding to the variable `first_register`. Suppose we apply the 4-qubit Fourier Transform unitary  $F_{16}$  to  $|\psi\rangle$  to get the state  $|\hat{\psi}\rangle$ .

First, compute by hand the Fourier transform  $F_{16}$  of  $|\psi\rangle$ , and determine an algebraic expression for the amplitudes of  $|\hat{\psi}\rangle$ .

If we then measured  $|\hat{\psi}\rangle$  in the standard basis, what outcomes are we most likely to get?

**Hint:** Your answers to Problem 1 may be helpful.

**Solution.**

We now plot the squares of the amplitudes of  $|\hat{\psi}\rangle$  below. Does it match your math above?

```
In [ ]: import numpy.fft as fft

mean = sum(first_register)/len(first_register)
fourier = fft.fft(np.array(first_register) - mean, axis=0)
# have to add in the normalization because numpy doesn't do it
fourier = fourier/np.sqrt(16)

# plot the amplitudes squared of the fourier transform
plt.bar(range(16), [abs(f)**2 for f in fourier])
```



## Problem

Suppose you have a state  $|\hat{\psi}\rangle$ . Explain how, by measuring this state in the standard basis multiple times, one can determine the period  $r$  of the function  $f(x)$ ? This should use the algebraic expression for the amplitudes that you obtained in Problem 4.7.

**WeChat: cstutorcs**

**Solution.**

**Assignment Project Exam Help**

**Email: tutorcs@163.com**

**QQ: 749389476**

**<https://tutorcs.com>**