CS 160 Compilers

Lecture 10: Parsing Algorithms

Yu Feng

Spring 2023

Extend CFGs for program parsing

- CFGs describe the structure of a program

- But we also need this structure in form of a tree, not just a yes/no answer

- Insight: We do not need all program structure, only the relevant part

- We call this an *abstract syntax tree (AST)*

ASTs

- Consider the grammar: E → int | (E) | E+E

- And the string: 5 + (2 + 3)

- After lexical analysis as string of tokens:

  - INT(5) ’+’ ’(’ INT(2) ’+’ INT(3) ’)’

  - During parsing, we built a parse tree

Example of parse tree



- Capture the nesting structure

- But too much information!

- Example: We do not care about the parentheses

Example of abstract syntax tree



- Also captures the nesting structure
- But abstracts from the concrete syntax
- More compact and easier to use

From CFG to AST

- Each grammar symbol has one attribute

Attribute Grammar

- For terminals (lexer tokens), the attribute is just the token

- Each production has a action computing its resulting attribute

- Written as: $X \rightarrow Y_1 \ldots Y_n \{action\}$

https://en.wikipedia.org/wiki/Attribute_grammar

An example

- Consider again the grammar E→int | (E) | E+E
- For each non-terminal on left-hand side, define its value in terms of symbols on right-hand side

- Recall: The value of each terminal is just its token

- Assume value of symbol S is given by S.val

- Grammar annotated with actions to compute the AST:

$$
\begin{array}{lll}
E & \rightarrow & \textsf{int}\ \{\texttt{E.val} = \texttt{int.val}\} \\
E & \rightarrow & E_1 + E_2\ \{\texttt{E.val} = \texttt{makeAstPlus}(\texttt{E}_1\texttt{.val}, \texttt{E}_2\texttt{.val})\} \\
E & \rightarrow & (E')\ \{\texttt{E.val} = \texttt{E}'\texttt{.val}\}
\end{array}
$$

An example



- You can think of semantic actions as defining a system of equations that describe the values of the let-hand sides in terms of values on the right-hand side
- Question: What order do we need to evaluate these equations to compute a solution?

Top-Down parsing: the idea

- The parse tree is c[illegible]d
    - From the top
    - From left to right
- Terminals are seen in order of appearance in the token stream:
    - t_2 t_5 t_6 t_8 t_9



Recursive Descent Parsing

Recursive descent parsing

- A Consider the gramm

  $\rightarrow T \mid T + E$

  $T \rightarrow \text{int} \mid \text{int} * T \mid (E)$

- Token stream is: (int_5)

- Start with top-level non-terminal E

- Try the rules for E in order

Recursive descent parsing

$E \rightarrow T \mid T + E$

$T \rightarrow int \mid int * T \mid (E$

Mismatch: int is not (!
Backtrack …

(int_5)

Recursive descent parsing

$E \rightarrow T \mid T + E$

$T \rightarrow \text{int} \mid \text{int} * T \mid (E)$



Mismatch: int is not (!
Backtrack …

$(\ \text{int}_5 \ )$

Recursive descent parsing

$E \rightarrow T \mid T + E$

$T \rightarrow \text{int} \mid \text{int} * T \mid (E$



Match: advance input

Accept: end of input

$(\ \text{int}_5 \ )$

TODOs by next lecture

- Hw3 will be out.
- Come to the discussion session if you have questions