

CS 160 Compilers

程序代写代做 CS编程辅导



# Lecture Revisiting DFA &

WeChat: cstutorcs

# NFA

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

Yu Feng  
Fall 2021

# Outline

程序代写代做CS编程辅导



- Today: Revisiting A & DFA
- High-level story: RegEx -> NFA -> DFA -> Table

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Finite automata



- Regular Expressions  $\Leftarrow$  on
- Finite Automata  $\Leftrightarrow$  Implementation

- A finite automata formally consists of:

- An input alphabet  $\Sigma$

- A set of states  $S$

- A start state  $n$

- A set of accepting states  $F \subseteq S$

- A set of transitions  $\text{state} \rightarrow_{\text{input}} \text{state}$

# Finite automata



- Transition  $S_1 \xrightarrow{\alpha} S_2$
- This means: In state  $S_1$  and input character  $\alpha$ , go to state  $S_2$
- If end of input and in accepting state  $\Rightarrow$  accept
- Otherwise  $\Rightarrow$  reject

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Finite Automata as State Graphs

程序代写代做CS编程辅导



A state:

The start state:

An accepting state:

A transition:

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# A simple example



- Here is an automaton that only accepts the string "1":

WeChat: cstutorcs



Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Another simple example



- A finite automaton accepting any number of 1's followed by a single 0
- Alphabet:  $\{0,1\}$

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



# Epsilon transitions



- A special kind of transition:  $\epsilon$ -transitions
- Machine can move from state A to B without reading any input

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



# Deterministic and Nondeterministic

程序代写代做 CS编程辅导  
Automata



- Deterministic Finite Automata (DFA)

- At most one transition per input on any state

WeChat: cstutorcs

- No  $\epsilon$  moves

Assignment Project Exam Help

- Nondeterministic Finite Automate (NFA)  
Email: [tutorcs@163.com](mailto:tutorcs@163.com)

- Can have multiple transitions for one input in a given state  
QQ: 749389476

- Can have  $\epsilon$ -moves  
<https://tutorcs.com>

# RE to NFA

程序代写代做 CS编程辅导






WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>




# In-class exercise

程序代写代做CS编程辅导



- Please draw the NFA for  $(b | c)^*$



WeChat: cstutorcs


Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

$R_1 | R_2$



$R^*$



# NFA to DFA: The Algorithm

程序代写代做CS编程辅导

$q_0 \leftarrow \epsilon^{-1}(\{n_0\})$ ;

$Q \leftarrow q_0$ ;

WorkList



while (WorkList  $\neq \emptyset$ ) do

remove  $q$  from WorkList;

for each character  $c \in \Sigma$  do

$t \leftarrow \epsilon\text{-closure}(\text{Delta}(q, c))$ ;

$T[q, c] \leftarrow t$ ;

if  $t \notin Q$  then

add  $t$  to  $Q$  and to WorkList;

end;

end;

Apply NFA's  
transition function to  
each element of  $q$


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



(a) NFA for “ $a(b \mid c)^*$ ” (With States Renumbered)

WeChat: cstutorcs

Assignment Project Exam Help


Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

Set Name	DFA States	NFA States	$\epsilon\text{-closure}(\Delta(q, *))$		
			a	b	c
$q_0$	$d_0$	$n_0$	$\{n_1, n_2, n_3, n_4, n_6, n_9\}$	– none –	– none –
$q_1$	$d_1$	$\{n_1, n_2, n_3, n_4, n_6, n_9\}$	– none –	$\{n_5, n_8, n_9, n_3, n_4, n_6\}$	$\{n_7, n_8, n_9, n_3, n_4, n_6\}$
$q_2$	$d_2$	$\{n_5, n_8, n_9, n_3, n_4, n_6\}$	– none –	$q_2$	$q_3$
$q_3$	$d_3$	$\{n_7, n_8, n_9, n_3, n_4, n_6\}$	– none –	$q_2$	$q_3$

(b) Iterations of the Subset Construction



(a) Resulting DFA

Engineering a compiler, C2.4

# TODOs by next lecture



- Hw2 will be out. (Come to the discussion session if you have questions)
- Come to the discussion session if you have questions

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>