

Question 1 C Memo

()

Mark the following True or False and justify your solution. Please feel free to discuss with students around you.



Q1.1 Stack canaries offer overflow from overwriting the return instruction pointer.

Q1.2 A format-string vulnerability can allow an attacker to overwrite values below the stack pointer.

Q1.3 ASLR, stack canaries, and NX bits all combined are insufficient to prevent exploitation of all buffer overflow attacks.

Short answer!

Q1.4 What vulnerability would arise if the stack canary was between the return address and the saved frame pointer?

Q1.5 Assume ASLR is enabled. What vulnerability would arise if the instruction `jmp *esp` exists in memory?

Question 2 Robin

0

Consider the following code snippet:

```
1 void robin(void) {  
2     char buf[16];  
3     int i;  
4  
5     if (fread(buf, 1, 1, stdin) != 1)  
6         return;  
7  
8     if (fgets(buf, 16, stdin) == NULL)  
9         return;  
10  
11     _____  
12 }
```

WeChat: cstutorcs

Assume that:

- There is no compiler padding or additional saved registers.
- The provided line of code in each subpart compiles and runs.
- `buf` is located at memory address `0xffffd8d8`
- Stack canaries are enabled, and all other memory safety defenses are disabled.
- The stack canary is four completely random bytes (**no null byte**).

For each subpart, mark whether it is possible to leak the value of the stack canary. If you put possible, provide an input to Line 5 and an input to Line 8 that would leak the canary. If the line is not needed for the exploit, you must write "Not needed" in the box.

Write your answer in Python syntax.

Q2.1 (3 min) Line 11 contains `gets(buf)`.

☐ Possible

☐ Not possible

Line 5:

Line 8:

Q2.2 (5 min) For this subpart only, enter an input that allows you to leak a single character from memory address 0xffffffff. Mark "Not possible" if this is not possible. Line 11 contains `printf("%c", buf[i]);`.

☐ Possible

☐ Not possible

Line 5:



Line 8:

WeChat: cstutorcs

Q2.3 (6 min) Line 11 contains `printf(buf);`.

☐ Possible

☐ Not possible

Line 5:

QQ: 749389476

Line 8:

<https://tutorcs.com>

Q2.4 (6 min) Line 11 contains `printf(i);`.

☐ Possible

☐ Not possible

Line 5:

Line 8:

Question 3 *Hulk Smash!*

Assume that:

- For your inputs, you may use SHELLCODE as a 16-byte shellcode.
- If needed, you may use `SHELLCODE` as input as OUTPUT, slicing it using Python syntax.
- All x86 instructions are 4 bytes long.
- For each provided address, run GDB once, and discover that:
 - The address `0xffffcd84` is the `hulk` method.
 - The address `0x080722d8` is the `main` function.

Consider the following function:

```
1 int hulk(FILE *f, char *eyes) {  
2     void (* green_ptr)(void) = &green; //function pointer  
3     char buf[32];  
4     char str[28];  
5     fread(buf, 1, 32, f);  
6     printf("%s", buf);  
7     fread(buf, 4, 32, stdin);  
8     if (strlen(eyes) > 28) {  
9         return 0;  
10    }  
11    strncpy(str, eyes, sizeof(buf));  
12    return 1;  
13 }
```

The following is the x86 code of `void green(void)`:

```
1 nop  
2 nop  
3 nop  
4 ret
```

Assume that ASLR is enabled including the code section, but all other memory safety defenses are disabled.

Q3.1 (3 min) Fill in the following stack diagram assuming that the program is paused after executing **Line 5**, including the arguments of `hulk` (the value in each box does not necessarily have to be four bytes long).



Q3.2 (10 min) Provide an input to each of the boxes below in order to execute SHELLCODE

Provide a string value for `eyes` (argument to `hulk`):

Email: tutorcs@163.com

Provide a string for the contents of the file that is passed in as the `f` argument of `hulk`:

QQ: 749389476

Provide an input to the second `fread` in `hulk`:

https://tutorcs.com