

COMP 251

程序代写代做 CS编程辅导

Algorithms



Structures (Winter 2022)

WeChat: **AVL**
cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Announcements

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Outline

程序代写代做 CS编程辅导

- Introduction.
- Operations.
- Application.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Introduction – Binary Search Trees

程序代写代做 CS 编程辅导



QQ: 749389476

- T is a rooted binary tree
- Key of a node $x >$ keys in its left subtree.
- Key of a node $x <$ keys in its right subtree.

BST – Operations

程序代写代做 CS编程辅导

- Search(T, k)
- Insert(T, k):
- Delete(T, k): $\mathcal{O}(h)$



Assignment Project Exam Help

Email: tutorcs@163.com


Where h is the height of the BST.
QQ: 749389476

<https://tutorcs.com>

BST – Height of a tree

程序代写代做 CS 编程辅导


Height(n): length of edges of longest downward path from node n to a leaf.



$$\text{Height}(x) = 1 + \max(\text{height}(\text{left}(x)), \text{height}(\text{right}(x)))$$

BST – Height of a tree - Example

程序代写代做 CS 编程辅导



WeChat: `cstutorcs`

$$= 1 + \max(h(b), h(g))$$

Assignment Project Exam Help
 $= 1 + \max(1 + \max(h(c), h(d)), 1 + h(h))$

Email: `tutorcs@163.com`

$$= 1 + \max(1 + \max(0, h(d)), 1 + 0)$$

QQ: 749389476

$$= 1 + \max(1 + \max(0, 1 + h(e))), 1$$

<https://tutorcs.com>

$$= 1 + \max(1 + \max(0, 1 + (1 + 0))), 1$$


$$= 4$$

BST – In-order traversal

程序代写代做 CS 编程辅导

```
inorderTraversal(treeNode x)
    if x != null
        inorderTraversal(x.leftChild);
        print x.value;
        inorderTraversal(x.rightChild);
```


WeChat: cstutorcs



- Print the nodes in the left subtree (A), then node x, and then the nodes in the right subtree (B)
 - In a BST, it prints first keys < x, then x, and then keys > x.

BST – In-order traversal

程序代写代做 CS 编程辅导



8, 12, 15, 20, 27, 36, 43, 57


All keys come out sorted!

BST – In-order traversal - Sort

程序代写代做 CS 编程辅导

1. Build a BST from the list of keys (unsorted)
2. Use in-order traversal on the BST to print the keys.

36	12	8	57	43	27
----	----	---	----	----	----



Running time of BST sort: insertion of n keys + tree traversal.

BST – Sort – Running time

程序代写代做 CS 编程辅导

- In-order traversal
- Running time of in-order traversal is $O(h)$



Best case: The BST is always balanced for every insertion.

WeChat: cstutorcs

$\Omega(n \log n)$

Assignment Project Exam Help

Email: tutorcs@163.com

Worst case: The BST is always un-balanced. All insertions on same side.

QQ: 749389476

$$\sum_{i=1}^n i = \frac{n \cdot (n-1)}{2} = O(n^2)$$

<https://tutorcs.com>

BST – Good vs Bad BSTs

程序代写代做 CS 编程辅导



Balanced
 $h = O(\log n)$

<https://tutorcs.com>

Unbalanced
 $h = O(n)$


AVL - Trees

程序代写代做 CS编程辅导

Definition: BST such that the heights of the two child subtrees of any node differ by one.



$$|h_{\text{left}} - h_{\text{right}}| \leq 1$$




- Invented by G. Adelson-Velsky and E.M. Landis in 1962.
- AVL trees are self-balanced binary search trees.
- Insert, Delete & Search take $O(\log n)$ in average and worst cases.
- To satisfy the definition, the height of an empty subtree is -1

QQ: 749389476

<https://tutorcs.com>

AVL – Trees -Example

程序代写代做 CS编程辅导




WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

yes

<https://tutorcs.com>
Taken from Langer2014



no

AVL – Trees -Example

程序代写代做 CS 编程辅导

Weird



common

example

root's left child

WeChat: cstutorcs is null

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Define the height of an
empty tree to be -1 .

Taken from Langer2014

AVL – Trees height – Worst case

程序代写代做 CS编程辅导

- AVL trees with a minimum number of nodes are the worst case examples.
 - every node's subtrees height by one.
 - we cannot make these worse / any more unbalanced.
 - If we add or remove a either get a non-AVL or balance one of the subtree.



Figure taken from Alin Tomescu recitation
<https://tutorcs.com>

"If we can bound the height of these worst-case examples of AVL trees,
then we've pretty much bounded the height of all AVL trees"

AVL – Trees height

程序代写代做 CS 编程辅导

N_h = minimum #nodes in an AVL tree of height h.



$$N_h = 1 + N_{h-1} + N_{h-2}$$

$$N_h > 1 + N_{h-2} + N_{h-3}$$

$$N_h > 2 * N_{h-2}$$

$$N_h > 2 * 2 * N_{h-4} > 2 * 2 * 2 * N_{h-6} > \dots > 2^{h/2}$$

$$N_h > 2^{h/2}$$

$$\Rightarrow \log(N_h) > \log(2^{h/2})$$

$$\Rightarrow 2 * \log(N_h) > h$$


$$\Rightarrow h = O(\log(n))$$

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Larger height when tree is unbalanced.

Outline

程序代写代做 CS编程辅导

- Introduction.
- Operations.
- Application.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Definition: Balance Factor

程序代写代做 CS编程辅导


- The **balance factor** of a binary tree is the difference in heights of its two subtrees ($hL - hR$). It must be one of the values $-1, 0, +1$.



Figure taken from randerson112358.medium.com.

Definition: Balance Factor


程序代写代做 CS 编程辅导



←: Left tree is higher (left-heavy)
<https://tutorcs.com>

= : Balanced

→ : Right tree is higher (right-heavy)




Definition: Rotations

程序代写代做 CS编程辅导

- Suppose we have.

Taken from Langer2014



- k_1, k_2 are keys
- A, B, C are subtrees (of unspecified shape)

$$A < k_1 < B < k_2 < C$$

- All keys in A are less than key k_1 . k_1 is less than all keys in B, which are less than k_2 . k_2 is less than all keys in C


Definition: Right Rotation

程序代写代做 CS 编程辅导





$B < k_2 < C$

right rotation




QQ: 749389476

<https://tutorcs.com>



Definition: Right Rotation

程序代写代做 CS 编程辅导



Definition: Right Rotation

程序代写代做 CS 编程辅导



rotateRight(root)

 newRoot = root.left

 root.left = newRoot.right

 newRoot.right = root

 return newRoot


}

<https://tutors.com>

} argument
and returned
value are
nodes, not
keys

Definition: Right Rotation

程序代写代做 CS 编程辅导




WeChat: cstutorcs

Assignment Project Exam Help

depths of
A nodes
decrease
by 1

QQ: 749389476

<https://tutorcs.com>




Taken from Langer2014

Definition: Left Rotation

程序代写代做 CS 编程辅导

Taken from Langer2014



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

rotateLeft(root) {

<https://tutorcs.com>

:

}




no change
in depth
of B
nodes

Exercise =>


Definition: Rotations

程序代写代做 CS 编程辅导

Right rotation



WeChat: cstutorcs



Assignment Project Exam Help

Email: tutorcs@163.com

Left rotation

QQ: 749389476

<https://tutorcs.com>

Rotations change the tree structure & **preserve the BST property**.


Operations: AVL insertion

程序代写代做 CS 编程辅导

1. Insert to standard BST
2. Restore tree properties




WeChat: cstutorcs



Operations: AVL insertion - Example

程序代写代做 CS 编程辅导



How to restore AVL property?

Operations: AVL insertion

程序代写代做 CS编程辅导

There are four ways (two pairs of ways) that the imbalance could have occurred, depending on where the insertion was:



- to the left subtree of the left child (outside)
- to the right subtree of the right child (outside)

WeChat: cstutorcs


- to the right subtree of the left child (inside).
- to the left subtree of the right child (inside)

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>



Taken from Langer2014

Operations: AVL insertion

程序代写代做 CS编程辅导




e.g. Insertion was
in tree C and
extended C 's height
from h to $h+1$,
creating imbalance
at subtree
rooted at k_1
(but not k_2).
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476
<https://tutorcs.com>

Question: How to rebalance k_1 ?

Operations: AVL insertion


程序代写代做 CS 编程辅导

Answer: rotate Left(k_1)



Operations: AVL insertion

程序代写代做 CS 编程辅导






How to rebalance k_1 ?

Operations: AVL insertion

程序代写代做 CS 编程辅导

Right rotation at k_2



Operations: AVL insertion

程序代写代做 CS 编程辅导

1. Suppose x is left-heavy node violating AVL
2. If x is right-heavy:
 - If x's right child is right-heavy or balanced: Left rotation (**case outside**)
 - Else: Right followed by left rotation (**case inside**)
3. If x is left-heavy:
 - If x's left child is left-heavy or balanced: Right rotation (**sym. of case outside**)
 - Else: Left followed by right rotation (**sym. of case inside**)



WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Operations: AVL insertion - Example


程序代写代做 CS 编程辅导



How to restore AVL property?

Operations: AVL insertion - Example


程序代写代做 CS 编程辅导



We remove the zig-zag pattern
<https://tutorcs.com>
Insert(T, 50)
RotateLeft(T, 43)

Operations: AVL insertion - Example

程序代写代做 CS 编程辅导



<https://tutorcs.com> AVL property restored!

RotateRight(T, 57)

AVL insertion: running time

程序代写代做 CS 编程辅导

- Insertion in $O(h)$
- At most 2 rotations which take $O(1)$
- Running time is $O(h) + O(1) = O(h) = O(\log n)$ in AVL trees.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

AVL sort: running time

程序代写代做 CS 编程辅导

Same as BST sort
AVL trees and AVL insertion instead.



- Worst case running time can be brought to $O(n \log n)$ if the tree is always balanced.
- Use AVL trees (trees are balanced).
- Insertion in AVL trees are $O(h) = O(\log n)$ for balanced trees.

<https://tutorcs.com>

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>