

COMP 251

程序代写代做 CS编程辅导



Algorithms

Structures (Winter 2022)

Disjoint Sets
WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Outline

- Introduction.
- Operations.

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Introduction - Motivation

程序代写代做 CS编程辅导

- You have a set of nodes (numbered 1-9) on a network. You are given a sequence of pairwise connections between them:



WeChat: [tutorcs](#)

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: [749389476](#)

<https://tutorcs.com>

Q: Are nodes 2 and 4 (indirectly) connected?

Q: Are nodes 3 and 8 connected?

Q: Are any of the paired connections redundant?

Q: How many sub-networks do we have?

Introduction - Motivation

程序代写代做 CS编程辅导

- You have a set of nodes (numbered 1-9) on a network. You are given a sequence of pairwise connections between them:



3-7

8-2

1-6

5-7

4-8

3-5

Data Structure



{3-5-7}

{2-4-8}

{9}

{1-6}

Disjoint sets

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Q: Are nodes 2 and 4 (indirectly) connected?

Q: Are nodes 3 and 8 connected?

Q: Are any of the paired connections redundant?

Q: How many sub-networks do we have?

Introduction - Motivation

程序代写代做 CS编程辅导

Q: Are nodes 2 and 4 (indirectly) connected?

Q: Are nodes 3 and 8 connected?

Q: Are any of the pairwise connections redundant?

Q: How many sub-networks do we have?

• These kind of questions arises in a huge number of areas.

- Networks
- Transistor interconnects
- Compilers
- Image segmentation
- Graph problems (upcoming topic)
- Etc

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>



Introduction - Partition

程序代写代做 CS编程辅导

Generalization: Set of object partitioned into disjoint subsets.



WeChat: estutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

$$S = S_1 \cup S_2 \cup \dots \cup S_n \left\{ \begin{array}{l} S_i \neq \emptyset \quad \forall i \in \{1, \dots, n\} \\ S_i \cap S_j = \emptyset \text{ iff } i \neq j \end{array} \right.$$

Introduction – Graph example

程序代写代做 CS编程辅导

Connected component: Set of nodes connected by a path.



Question: Given 2 nodes A & B, are they in the same component?

Introduction – Equivalence relation

程序代写代做 CS编程辅导

A relation that is:

- Reflexive $\forall a \in S, (a,a) \in R$
- Symmetric $\forall a,b \in S, (a,b) \in R \Rightarrow (b,a) \in R$
- Transitive $\forall a,b,c \in S, (a,b) \in R \text{ and } (b,c) \in R \Rightarrow (a,c) \in R$

WeChat: cstutorcs

Example:

Assignment Project Exam Help

For any undirected graph, the connections define an equivalence relation on vertices.

Email: tutores@163.com


QQ: 749389476

- For all $u \in V$, there is a path of length 0 from u to u .
- For all $u,v \in V$, There is a path from u to v , iff there is a path from v to u .
- For all $u,v,w \in V$, if there is a path from u to v and a path from v to w , then there is a path from u to w .

<https://tutorcs.com>

Introduction – Equivalence relation

程序代写代做 CS编程辅导



`equals()` defines an equivalence relation on objects

WeChat: cstutorcs

[http://docs.oracle.com/javase/7/docs/api/java/lang/Object.html#equals\(java.lang.Object\)](http://docs.oracle.com/javase/7/docs/api/java/lang/Object.html#equals(java.lang.Object))

Assignment Project Exam Help

reflexive

`a.equals(a)` returns true
Email: tutorcs@163.com

symmetric

`a.equals(b) == b.equals(a)`
QQ: 749389476

transitive

`a.equals(b)` and `b.equals(c)`
 \Rightarrow `a.equals(c)`

<https://tutorcs.com>


Taken from Langer2014

Introduction – Equivalence relation

程序代写代做 CS编程辅导

An equivalence relation is the same as a partition:

Each equivalence relation partitions the underlying set into disjoint equivalent classes (



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

	1	2	3	4	5	6	7
1	1	0	0	0	0	1	1
2	0	1	1	0	0	0	0
3	0	1	1	0	0	0	0
4	0	0	0	1	0	0	0
5	0	0	0	0	1	0	0
6	1	0	0	0	0	1	1
7	1	0	0	0	0	1	1

i is equivalent to j if they belong to the same set.

<https://tutorcs.com>

(more constrained than general relation)

Introduction – Disjoint set ADT

程序代写代做 CS编程辅导



i is equivalent to j if they belong to the same set.

Each set in the partition has a unique name (a representative member for convenience).

- $\text{find}(i)$ returns the representative of the set that contains i .
- $\text{same_set}(i, j)$ returns the boolean value $\text{find}(i) == \text{find}(j)$
- $\text{union}(i, j)$ merges the sets containing i and j .

Introduction - Operations

程序代写代做 CS编程辅导

- Maintain disjoint sets:

- $\{3, 5, 7\}, \{4, 2, 8\}, \{9\}$

- Each set has a representative:

- $\{3, 5, 7\}, \{4, 2, 8\}, \{9\}, \{1, 6\}$

- Find(x) returns the representative of the set containing x

- Find(1) = 5

- Find(4) = 8

- Union(x,y) takes the union of the two sets that contains x and y

- Union(5,1) = $\{3, 5, 7, 1, 6\}, \{4, 2, 8\}, \{9\}$

- Union(9,6) = $\{3, 5, 7\}, \{4, 2, 8\}, \{9, 1, 6\}$

<https://tutorcs.com>



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Introduction - Operations

程序代写代做 CS编程辅导

- Maintain disjoint sets:
 - {3, 5, 7}, {4, 2, 8}, {9}
- Each set has a representative:
 - {3, 5, 7}, {4, 2, 8}, {9}
- Q: Are nodes 2 and 4 (indirectly) connected?
 - Find(2) == Find(4)
- Q: Are nodes 3 and 8 connected?
 - Find(3) == Find(8)
- Q: How many sub-networks do we have?
 - Number of representatives.
- Q: Are any of the paired connections redundant?
 - Connections – (|S1-1| + |S2-1| + |S3-1| + |S4-1|) = 6 – (2+2+0+1) = 1



WeChat: estutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Outline

- Introduction.
- Operations.

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

Operations – find

程序代写代做 CS编程辅导

Rep[]

1	1
2	3
3	3
4	4
5	7
6	1
7	7
8	7
9	1



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476
Let $Rep[i] \in \{1, 2, \dots, n\}$ be the representative of the set containing i .
<https://tutorcs.com>
 $find(i) \{ return rep[i]; \}$

Operations – union

程序代写代做 CS编程辅导

- $\text{union}(i,j)$ merges the sets containing i and j .

Example: $\text{union}(i,j)$



$i \rightarrow$

1	1
2	3
3	3
4	4
5	7
6	1
7	7
8	7
9	1

$j \rightarrow$

1	1
2	3
3	3
4	4
5	7
6	1
7	7
8	7
9	1

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

1	1
2	1
3	1
4	4
5	7
6	1
7	7
8	7
9	1

Operations – union

程序代写代做 CS编程辅导

```
union(i,j) {  
    if rep[i] == rep[j] {  
        prev = rep[i];  
        for (k=i; k<=n; k++) {  
            if rep[k] == prev {  
                rep[k] = rep[j];  
            }  
        }  
    }  
}
```

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

- store value of rep[i] because it may change during the execution of the algorithm.
- O(n) running time... slow.

Union – forest & tree representation

程序代写代做 CS编程辅导

- Represent the disjoint sets by a forest of rooted trees.
 - Roots are the representatives (i.e. $\text{find}(i) == \text{findroot}(i)$).
 - Each node points to its parent.



Note:

The tree structure does not necessarily represent the relationship between the stored objects.

Union – table representation

程序代写代做 CS编程辅导

p[]

1	1
2	7
3	3
4	9
5	1
6	7
7	7
8	1
9	7
10	3
11	5



WeChat: cstutores


Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutores.com>

- Non-root nodes hold index of their parent.
- Root nodes store their own value.



Operations – Union

程序代写代做 CS编程辅导



on(9,11)

Root of the tree of 11 becomes the parent of the root of the tree of 9.




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Operations – Find & Union

程序代写代做 CS编程辅导

```
find(i) {  
    if p[i] =  
        retu  
    } else {  
        return find(p[i]);  
    }  
}
```



WeChat: cstutorcs

Remark: Arbitrarily

Assignment Project Exam Help

merge the set on i
into the set of j.

```
union(i, j) {  
    if find(i) != find(j) {  
        p[find(i)] = find(j);  
    }  
}
```

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Operations – Union - > Worst case

程序代写代做 CS编程辅导

union(1,2)

union(1,3)

union(1,4)

...

union(1,n)



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Then, find(1) is $O(n)$...



Union – Heuristic – Definitions

程序代写代做 CS编程辅导

- The **depth** of a node is the number of edges from the node to the tree's root node. A root node will have a depth of 0.
- The **height** of a node is the number of edges on the *longest path* from the node to a leaf. A leaf node will have a height of 0.



WeChat: estutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Image and definitions taken from:
<https://stackoverflow.com/>

Union – Heuristic – by size

程序代写代做 CS编程辅导

Heuristic to control the height of the trees after merging.



Idea: Merge tree with smaller number of nodes into the tree with the largest number of nodes (In practice, we can also use rank which is an upper bound on the height of nodes).


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Union – Heuristic – by size

程序代写代做 CS编程辅导

Claim: The depth of any node is at most $\log n$.

Proof:



- If union causes the depth of a node to increase, then this node must belong to the smallest tree.

WeChat: cstutorcs


Assignment Project Exam¹ Help

Email: tutores@163.com

QQ: 749389476

<https://tutorcs.com>

- Thus, when the depth increases, the size of the (merged) tree containing this node will at least double.
- But we can double the size of a tree at most $\log n$ times.



Union – Heuristic – by height

程序代写代做 CS编程辅导

Idea: Merge tree with smaller height into tree with larger height.



Claim: The height of trees obtained by union-by-height is at most $\log n$.

WeChat: cstutorcs

Assignment Project Exam Help

Corollary: An union-by-height tree of height h has at least $n_h \geq 2^h$ nodes.

Email: tutorcs@163.com

QQ: 749389476

Proof (Corollary):

- Base case: a tree of height 0 has one node.
- Induction: (hypothesis) $n_h \geq 2^h$. Show $n_{h+1} \geq 2^{h+1}$.

<https://tutorcs.com>

Heuristic – supplemental material

程序代写代做 CS编程辅导

The base case $k=0$ is easy, since a tree of height 0 always has just $1=2^0$ node (the root). Suppose is true for $h=k$. Now consider a union-by-height tree of height $k+1$. There must have been a union that brought two trees together and increased the height of one of them from k to $k+1$. Let those two trees (at the time of that union) be T_1 and T_2 . We know that both T_1 and T_2 were of height k before the union. [Why? If one of them were of height less than k , then union-by-height would have changed the root of that shorter one to make it point to the root of the taller one, and the height of the unioned tree would still be k . But it's not; the unioned tree is of height $k+1$.] Now we can apply the induction hypothesis: the trees T_1 and T_2 each have at least 2^k nodes. Thus, the unioned tree has at least $2^k + 2^k = 2^{k+1}$ nodes.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Taken from Langer 2014

Union – running time

程序代写代做 CS编程辅导



Quick Union {

Union by size
Union by height

WeChat: cstutorcs

find(i)	union(i,j)
$O(1)$	$O(n)$
$O(\log n)$	$O(\log n)$
$O(\log n)$	$O(\log n)$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Quick union makes 2
calls to find.

Note: These are worst case complexities.


union-find – heuristics – path compression

程序代写代做 CS编程辅导



- Find path = nodes on the trip to the root during the execution of find()
- Make all nodes on the find path direct children of root.

WeChat: cstutorcs



union-find – heuristics – path compression

程序代写代做 CS编程辅导

find



```
    p[i] == i {  
        return i;
```

WeChat: cstutorcs

```
    } else {
```

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

```
}
```

union-find – running time

程序代写代做 CS编程辅导

- Use union by size and path compression.
- **m union or find operations** take $O(m \alpha(n))$.

What is $\alpha(n)$?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

n	$\alpha(n)$
0 - 2	0
3	1
4 - 7	2
8 - 2047	3
2048 – $A_4(1)$	4

Where $A_4(1) \gg 10^{80}$!!

union-find – running time

程序代写代做 CS编程辅导

- Use union by size and path compression.

- Huge Practical problem



- 10^{10} edges connecting nodes.

- The heuristics reduces time from 3.000 years to 1 minute

WeChat: cstutorcs

- Supercomputer won't help much

- Good algorithm makes solution possible

Assignment Project Exam Help

- Good algorithms makes it possible to solve problems that could not otherwise be addressed.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Outline

- Introduction.
- Operations.

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>