

程序代写代做 CS编程辅导



# Reducing Probabilistic Reasoning (MAR)

WeChat: cstutorcs  
Assignment to Project Exam Help


# Weighted Model Counting (WMC)

Email: tutorcs@163.com  
QQ: 749389476

<https://tutorcs.com>

# Probabilistic Reasoning

程序代写代做 CS 编程辅导



WeChat: cstutorcs

A	B	$\Theta_{B A}$	A	C	$\Theta_{C A}$
$a_1$	$b_1$	.1	$a_1$	$c_1$	.1
$a_1$	$b_2$	.9	$a_1$	$c_2$	.9
$a_2$	$b_1$	.2	$a_2$	$c_1$	.2
$a_2$	$b_2$	.8	$a_2$	$c_2$	.8

---

Network instantiation

$a_1 b_1 c_1$

$.1 \cdot .1 \cdot .1 = .001$

Assignment Project Exam Help

$a_1 b_1 c_2$

$.1 \cdot .1 \cdot .9 = .009$

MPE: Find most likely instantiation that satisfies a given event (e.g.,  $B=b_2$ )

$a_1 b_2 c_1$

$.1 \cdot .9 \cdot .1 = .009$

Email: tutorcs@163.com

$a_1 b_2 c_2$

$.1 \cdot .9 \cdot .9 = .081$

MAR: Sum probabilities of instantiations that satisfy a given event (e.g.,  $B=b_2$ )

$a_2 b_1 c_1$

$.9 \cdot .2 \cdot .2 = .036$

QQ: 749389476

$a_2 b_1 c_2$

$.9 \cdot .2 \cdot .8 = .144$

Distribution

$a_2 b_2 c_1$

$.9 \cdot .8 \cdot .2 = .144$


Factor

$a_2 b_2 c_2$

$.9 \cdot .8 \cdot .8 = .576$

# The Pipeline

程序代写代做 CS编程辅导




reduce



compile

Tractable Boolean Circuit



Assignment Project Exam Help


Arithmetic Circuit (AC)

Email: tutorcs@163.com



QQ: 749389476

<https://tutorcs.com>



# Weighted Model Counting(WMC)



**Definition 11.3** (Weighted model counting, WMC). Let  $\Delta$  be a propositional sentence over Boolean variables  $X_1, \dots, X_n$ , and let  $Wt$  be a function that assigns a weight  $Wt(x_i) \geq 0$  to each value  $x_i$  of variable  $X_i$ . The *weighted model count* of  $\Delta$  is defined as the sum of weights assigned to its models.

$$\text{WMC}(\Delta) \stackrel{\text{def}}{=} \sum_{x_1, \dots, x_n \in \Delta} Wt(x_1, \dots, x_n),$$



Email: tutorcs@163.com

where

QQ: 749389476

$$Wt(x_1, \dots, x_n) \stackrel{\text{def}}{=} \prod_{i=1}^n Wt(x_i).$$

# Reduction: MAR $\rightarrow$ WMC



		A	B	$\Theta_{B A}$	A	C	$\Theta_{C A}$
		$a_1$	$b_1$	.1	$a_1$	$c_1$	.1
a <sub>1</sub>		$a_1$	$b_2$	.9	$a_1$	$c_2$	.9
$a_2$	.9	$a_2$	$b_1$	.2	$a_2$	$c_1$	.2
		$a_2$	$b_2$	.8	$a_2$	$c_2$	.8

WeChat: cstutorcs  
Assignment Project Exam Help

Indicator Variables (Boolean)

Email: tutorcs@163.com


$I_{a_1}, I_{a_2}, I_{b_1}, I_{b_2}, I_{c_1}, I_{c_2},$   
QQ: 749389476

Parameter Variables (Boolean)

<https://tutorcs.com>

$P_{a_1}, P_{a_2}, P_{b_1|a_1}, P_{b_2|a_1}, P_{b_1|a_2}, P_{b_2|a_2}, P_{c_1|a_1}, P_{c_2|a_1}, P_{c_1|a_2}, P_{c_2|a_2}.$

# Reduction: MAR $\rightarrow$ WMC



A	$\Theta_A$	A	B	$\Theta_{B A}$	A	C	$\Theta_{C A}$
$a_1$	.1	$a_1$	$b_1$	.1	$a_1$	$c_1$	.1
$a_2$	.9	$a_1$	$b_2$	.9	$a_1$	$c_2$	.9

variable  $X$  with values  $x_1, x_2, \dots, x_k$

$$I_{x_1} \vee I_{x_2} \vee \dots \vee I_{x_k}$$

$$\neg I_{x_i} \vee \neg I_{x_j}, \quad \text{for } i < j.$$

$$I_{u_1} \wedge I_{u_2} \wedge \dots \wedge I_{u_m} \wedge I_x \iff P_{x|u_1, u_2, \dots, u_m}.$$

$$Wt(I_x) = Wt(\neg I_x) = Wt(\neg P_{x|\mathbf{u}}) = 1 \text{ and } Wt(P_{x|\mathbf{u}}) = \theta_{x|\mathbf{u}}.$$



WeChat: cstutorcs


Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Reduction: MAR $\rightarrow$ WMC



	$A$	$B$	$\Theta_{B A}$		$A$	$C$	$\Theta_{C A}$
$A$							
$a_1$	$a_1$	$b_1$	.1		$a_1$	$c_1$	.1
	$a_1$	$b_2$	.9		$a_1$	$c_2$	.9
$a_2$	$a_2$	$b_1$	.2		$a_2$	$c_1$	.2
	$a_2$	$b_2$	.8		$a_2$	$c_2$	.8

variable  $X$  with values  $x_1, x_2, \dots, x_k$

$$I_{x_1} \vee I_{x_2} \vee \dots \vee I_{x_k}$$

$$\neg I_{x_i} \vee \neg I_{x_j}, \quad \text{for } i < j.$$

$$I_{u_1} \wedge I_{u_2} \wedge \dots \wedge I_{u_m} \wedge I_x \iff P_{x|u_1, u_2, \dots, u_m}.$$



For Clauses

$A$	$I_{a_1} \vee I_{a_2}$	$\neg I_{a_1} \vee \neg I_{a_2}$
$B$	$I_{b_1} \vee I_{b_2}$	$\neg I_{b_1} \vee \neg I_{b_2}$
$C$	$I_{c_1} \vee I_{c_2}$	$\neg I_{c_1} \vee \neg I_{c_2}$

WeChat: cstutorcs Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

$A$	$I_{a_1} \iff P_{a_1}$	$\neg I_{a_2} \iff P_{a_2}$
$B$	$I_{a_1} \wedge I_{b_1} \iff P_{b_1 a_1}$	$I_{a_1} \wedge I_{b_2} \iff P_{b_2 a_1}$
	$I_{a_2} \wedge I_{b_1} \iff P_{b_1 a_2}$	$I_{a_2} \wedge I_{b_2} \iff P_{b_2 a_2}$

$C$	$I_{a_1} \wedge I_{c_1} \iff P_{c_1 a_1}$	$I_{a_1} \wedge I_{c_2} \iff P_{c_2 a_1}$
	$I_{a_2} \wedge I_{c_1} \iff P_{c_1 a_2}$	$I_{a_2} \wedge I_{c_2} \iff P_{c_2 a_2}$

$$Wt(I_x) = Wt(\neg I_x) = Wt(\neg P_{x|\mathbf{u}}) = 1 \text{ and } Wt(P_{x|\mathbf{u}}) = \theta_{x|\mathbf{u}}.$$

Reduction: MAR  $\rightarrow$  WMC  
程序代写代做CS编程辅导



Let  $\mathcal{N}$  be a Bayesian network inducing probability distribution  $\Pr$   
 $\Delta_{\mathcal{N}}$  be its CNF encoding

WeChat: cstutorcs

Assignment Project Exam Help  
For any evidence  $\mathbf{e} = e_1, \dots, e_k$ ,  
Email: tutorcs@163.com

$$\Pr(\mathbf{e}) = \text{WMC}(\Delta_{\mathcal{N}} \wedge I_{e_1} \wedge \dots \wedge I_{e_k}),$$

<https://tutorcs.com>

# Reduction: MAR $\rightarrow$ WMC (why it works)

			A		B		C	
			$\Theta_{B A}$		$\Theta_{A B}$		$\Theta_{C A}$	
A	B	C	$a_1$	$b_1$	.1	$a_1$	$c_1$	.1
$a_1$	$b_1$		.1			$a_1$	$c_2$	.9
$a_2$	$b_2$			.9		$a_2$	$c_1$	.2
						$a_2$	$c_2$	.8

Indicator Clauses		
A	$I_{a_1} \vee I_{a_2}$	$\neg I_{a_1} \vee \neg I_{a_2}$
B	$I_{b_1} \vee I_{b_2}$	$\neg I_{b_1} \vee \neg I_{b_2}$
C	$I_{c_1} \vee I_{c_2}$	$\neg I_{c_1} \vee \neg I_{c_2}$

Parameter Clauses		
A	$I_{a_1} \iff P_{a_1}$	$I_{a_2} \Leftrightarrow P_{a_2}$
B	$I_{a_1} \wedge I_{b_1} \iff P_{b_1 a_1}$	$I_{a_1} \wedge I_{b_2} \iff P_{b_2 a_1}$
	$I_{a_2} \wedge I_{b_1} \iff P_{b_1 a_2}$	$I_{a_2} \wedge I_{b_2} \iff P_{b_2 a_2}$
C	$I_{a_1} \wedge I_{c_1} \iff P_{c_1 a_1}$	$I_{a_1} \wedge I_{c_2} \iff P_{c_2 a_1}$
	$I_{a_2} \wedge I_{c_1} \iff P_{c_1 a_2}$	$I_{a_2} \wedge I_{c_2} \iff P_{c_2 a_2}$



Truth assignment sets these variables to true and all others to false	Weight of truth assignment
$\omega_0 : I_{a_1} I_{b_1} I_{c_1} P_{a_1} P_{b_1 a_1} P_{c_1 a_1}$	$.1 \cdot .1 \cdot .1 = .001$
$\omega_1 : I_{a_1} I_{b_1} I_{c_2} P_{a_1} P_{b_1 a_1} P_{c_2 a_1}$	$.1 \cdot .1 \cdot .9 = .009$
$\omega_2 : I_{a_1} I_{b_2} I_{c_1} P_{a_1} P_{b_2 a_1} P_{c_1 a_1}$	$.1 \cdot .9 \cdot .1 = .009$
$\omega_3 : I_{a_1} I_{b_2} I_{c_2} P_{a_1} P_{b_2 a_1} P_{c_2 a_1}$	$.1 \cdot .9 \cdot .9 = .081$
$\omega_4 : I_{a_2} I_{b_1} I_{c_1} P_{a_2} P_{b_1 a_1} P_{c_1 a_2}$	$.9 \cdot .2 \cdot .2 = .036$
$\omega_5 : I_{a_2} I_{b_1} I_{c_2} P_{a_2} P_{b_1 a_1} P_{c_2 a_2}$	$.9 \cdot .2 \cdot .8 = .144$
$\omega_6 : I_{a_2} I_{b_2} I_{c_1} P_{a_2} P_{b_2 a_1} P_{c_1 a_2}$	$.9 \cdot .8 \cdot .2 = .144$
$\omega_7 : I_{a_2} I_{b_2} I_{c_2} P_{a_2} P_{b_2 a_1} P_{c_2 a_2}$	$.9 \cdot .8 \cdot .8 = .576$

WeChat: cstutorcs  
Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

$$\text{WMC}(\Delta_N \wedge I_{a_1} \wedge I_{c_2}) = Wt(\omega_1) + Wt(\omega_3) = .009 + .081 = .09 = \Pr(\mathbf{e}).$$

# Local Structure

程序代写代做 CS编程辅导



		A	B	$\theta_{B A}$	A	C	$\theta_{C A}$
A		true	true	1	true	true	.8
		.5	true	0	true	false	.2
false		.5	false	0	false	true	.2
			false	1	false	false	.8

Assignment Project Exam Help

--Zero/One parameters (logical constraints)


Email: tutorcs@163.com

--Equal parameters

QQ: 749389476

Context-Specific Independence (CSI)


<https://tutorcs.com>



x	y	z	$\Pr(z x,y)$
t	t	t	.8
t	t	f	.2
t	f	t	.8
t	f	f	.2
⋮			

# Encoding Local Structure

程序代写代做CS编程辅导



$A$	$\Theta_A$
$a_1$	.1
$a_2$	.9

$A$	$B$	$\Theta_{B A}$
$a_1$	$b_1$	.1
$a_1$	$b_2$	.9
$a_2$	$b_1$	.2
$a_2$	$b_2$	.8

$A$	$C$	$\Theta_{C A}$
$a_1$	$c_1$	.1
$a_1$	$c_2$	.9
$a_2$	$c_1$	.2
$a_2$	$c_2$	.8




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



$A$	$\theta_A$
true	.5
false	.5

$A$	$B$	$\theta_{B A}$
true	true	1
true	false	0
false	true	0
false	false	1

$A$	$C$	$\theta_{C A}$
true	true	.8
true	false	0

## Indicator Clauses

$A$	$I_{a_1} \vee I_{a_2}$	$\neg I_{a_1} \vee \neg I_{a_2}$
$B$	$I_{b_1} \vee I_{b_2}$	$\neg I_{b_1} \vee \neg I_{b_2}$
$C$	$I_{c_1} \vee I_{c_2}$	$\neg I_{c_1} \vee \neg I_{c_2}$


## Parameter Clauses

$$A \quad I_{a_1} \iff P_{a_1} \quad I_{a_2} \iff P_{a_2}$$

$B$	$I_{a_1} \wedge I_{b_1} \iff P_{b_1 a_1}$	$I_{a_1} \wedge I_{b_2} \iff P_{b_2 a_1}$
$B$	$I_{a_2} \wedge I_{b_1} \iff P_{b_1 a_2}$	$I_{a_2} \wedge I_{b_2} \iff P_{b_2 a_2}$
$C$	$I_{a_1} \wedge I_{c_1} \iff P_{c_1 a_1}$	$I_{a_1} \wedge I_{c_2} \iff P_{c_2 a_1}$
$C$	$I_{a_2} \wedge I_{c_1} \iff P_{c_1 a_2}$	$I_{a_2} \wedge I_{c_2} \iff P_{c_2 a_2}$

# Encoding Local Structure

程序代写代做CS编程辅导



		$A$	$B$	$\theta_{B A}$
		true	true	1
		true	false	0
		false	true	0
		false	false	1

		$A$	$C$	$\theta_{C A}$
		true	true	.8
		true	false	.2
		false	true	.2
		false	false	.8

$$I_a \vee I_{\bar{a}}$$

$$\neg I_a \vee \neg I_{\bar{a}}$$

$$I_b \vee I_{\bar{b}}$$

$$\neg I_b \vee \neg I_{\bar{b}}$$

$$I_c \vee I_{\bar{c}}$$

$$\neg I_c \vee \neg I_{\bar{c}}$$

$$I_a \iff P_a$$

$$I_{\bar{a}} \iff P_{\bar{a}}$$

$$I_a \wedge I_b \iff P_{b|a}$$

$$I_a \wedge I_{\bar{b}} \iff P_{\bar{b}|a}$$

$$I_{\bar{a}} \wedge I_b \iff P_{b|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{b}} \iff P_{\bar{b}|\bar{a}}$$

$$I_a \wedge I_c \iff P_{c|a}$$


$$I_a \wedge I_{\bar{c}} \iff P_{\bar{c}|a}$$

$$I_{\bar{a}} \wedge I_c \iff P_{c|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{c}} \iff P_{\bar{c}|\bar{a}}$$

# Encoding Local Structure

程序代写代做CS编程辅导



	A	B	$\theta_{B A}$
A	$\theta_A$		
true	true	1	
true	false	0	
false	true	0	
false	false	1	

	A	C	$\theta_{C A}$
A	$\theta_A$		
true	true	.8	
true	false	.2	
false	true	.2	
false	false	.8	

<https://tutorcs.com>

$$\begin{array}{lll} I_a \vee I_{\bar{a}} & I_b \vee I_{\bar{b}} & I_c \vee I_{\bar{c}} \\ \neg I_a \vee \neg I_{\bar{a}} & \neg I_b \vee \neg I_{\bar{b}} & \neg I_c \vee \neg I_{\bar{c}} \end{array}$$


$$\begin{array}{ll} I_a \iff P_a & I_{\bar{a}} \iff P_{\bar{a}} \end{array}$$

$$\begin{array}{ll} I_a \wedge I_b \iff P_{b|a} & I_a \wedge I_{\bar{b}} \iff P_{\bar{b}|a} \\ I_{\bar{a}} \wedge I_b \iff P_{b|\bar{a}} & I_{\bar{a}} \wedge I_{\bar{b}} \iff P_{\bar{b}|\bar{a}} \end{array}$$

$$\begin{array}{ll} I_a \wedge I_c \iff P_{c|a} & I_a \wedge I_{\bar{c}} \iff P_{\bar{c}|a} \\ I_{\bar{a}} \wedge I_c \iff P_{c|\bar{a}} & I_{\bar{a}} \wedge I_{\bar{c}} \iff P_{\bar{c}|\bar{a}} \end{array}$$

# Encoding Local Structure

程序代写代做CS编程辅导



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

	$A$	$B$	$\theta_{B A}$
$A$	$\theta_A$		
true	.5	true	1
true	.5	false	0
false	.5	true	0
false	.5	false	1

	$A$	$C$	$\theta_{C A}$
true	true	true	.8
true	true	false	.2
true	false	false	.2
false	true	false	.2
false	false	false	.8

<https://tutorcs.com>

$$I_a \vee I_{\bar{a}}$$

$$\neg I_a \vee \neg I_{\bar{a}}$$

$$I_b \vee I_{\bar{b}}$$

$$\neg I_b \vee \neg I_{\bar{b}}$$

$$I_c \vee I_{\bar{c}}$$

$$\neg I_c \vee \neg I_{\bar{c}}$$

$$I_a \iff P_a$$

$$I_{\bar{a}} \iff P_{\bar{a}}$$

$$I_a \wedge I_b \iff P_{b|a}$$

$$I_a \wedge I_{\bar{b}} \iff P_{\bar{b}|a}$$

$$I_{\bar{a}} \wedge I_b \iff P_{b|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{b}} \iff P_{\bar{b}|\bar{a}}$$

$$I_a \wedge I_c \iff P_{c|a}$$


$$I_a \wedge I_{\bar{c}} \iff P_{\bar{c}|a}$$

$$I_{\bar{a}} \wedge I_c \iff P_{c|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{c}} \iff P_{\bar{c}|\bar{a}}$$

# Encoding Local Structure

程序代写代做CS编程辅导



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

	$A$	$B$	$\theta_{B A}$
$A$	$\theta_A$		
true	.5	true	1
true	.5	false	0
false	.5	true	0
false	.5	false	1

	$A$	$C$	$\theta_{C A}$
true	true	true	.8
true	true	false	.2
true	false	true	.2
true	false	false	.8
false	true	true	.2
false	true	false	.2
false	false	true	.8
false	false	false	.2

<https://tutorcs.com>

$$I_a \vee I_{\bar{a}}$$

$$\neg I_a \vee \neg I_{\bar{a}}$$

$$I_b \vee I_{\bar{b}}$$

$$\neg I_b \vee \neg I_{\bar{b}}$$

$$I_c \vee I_{\bar{c}}$$

$$\neg I_c \vee \neg I_{\bar{c}}$$

$$I_a \iff P_a$$

$$I_{\bar{a}} \iff P_{\bar{a}}$$

$$I_a \wedge I_b \iff P_{b|a}$$

$$I_a \wedge I_{\bar{b}} \iff P_{\bar{b}|a}$$

$$I_{\bar{a}} \wedge I_b \iff P_{b|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{b}} \iff P_{\bar{b}|\bar{a}}$$

$$I_a \wedge I_c \iff P_{c|a}$$


$$I_a \wedge I_{\bar{c}} \iff P_{\bar{c}|a}$$

$$I_{\bar{a}} \wedge I_c \iff P_{c|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{c}} \iff P_{\bar{c}|\bar{a}}$$

# Encoding Local Structure

程序代写代做CS编程辅导



Equal Par



$$I_a \wedge I_c \iff P_{|a|c}$$

WeChat: cstutorcs

$$I_{\bar{a}} \wedge I_{\bar{c}} \iff P_{|\bar{c}|\bar{a}}$$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

	$A$	$B$	$\theta_{B A}$
$A$			$\theta_A$
true	true		1
true	false		0
false	true		0
false	false		1

	$A$	$C$	$\theta_{C A}$
true	true		.8
true	false		.2
false	true		.2
false	false		.8

<https://tutorcs.com>

$$I_a \vee I_{\bar{a}}$$

$$\neg I_a \vee \neg I_{\bar{a}}$$

$$I_b \vee I_{\bar{b}}$$

$$\neg I_b \vee \neg I_{\bar{b}}$$

$$I_c \vee I_{\bar{c}}$$

$$\neg I_c \vee \neg I_{\bar{c}}$$

$$I_a \iff P_a$$

$$I_{\bar{a}} \iff P_{\bar{a}}$$

$$I_a \wedge I_b \iff P_{b|a}$$

$$I_a \wedge I_{\bar{b}} \iff P_{\bar{b}|a}$$

$$I_{\bar{a}} \wedge I_b \iff P_{b|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{b}} \iff P_{\bar{b}|\bar{a}}$$

$$I_a \wedge I_c \iff P_{c|a}$$



$$I_a \wedge I_{\bar{c}} \iff P_{\bar{c}|a}$$

$$I_{\bar{a}} \wedge I_c \iff P_{c|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{c}} \iff P_{\bar{c}|\bar{a}}$$

# Encoding Local Structure

程序代写代做CS编程辅导



	A	B	$\theta_{B A}$
A	$\theta_A$		
true	true	1	
true	false	0	
false	true	0	
false	false	1	

	A	C	$\theta_{C A}$
A	$\theta_A$		
true	true	.8	
true	false	.2	
false	true	.2	
false	false	.8	

$$I_a \vee I_{\bar{a}}$$

$$\neg I_a \vee \neg I_{\bar{a}}$$

$$I_b \vee I_{\bar{b}}$$

$$\neg I_b \vee \neg I_{\bar{b}}$$

$$I_c \vee I_{\bar{c}}$$

$$\neg I_c \vee \neg I_{\bar{c}}$$

$$I_a \iff P_a$$

$$I_{\bar{a}} \iff P_{\bar{a}}$$

$$I_a \wedge I_b \iff P_{b|a}$$

$$I_a \wedge I_{\bar{b}} \iff P_{\bar{b}|a}$$

$$I_{\bar{a}} \wedge I_b \iff P_{b|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{b}} \iff P_{\bar{b}|\bar{a}}$$

$$I_a \wedge I_c \iff P_{c|a}$$

$$I_a \wedge I_{\bar{c}} \iff P_{\bar{c}|a}$$

$$I_{\bar{a}} \wedge I_c \iff P_{c|\bar{a}}$$

$$I_{\bar{a}} \wedge I_{\bar{c}} \iff P_{\bar{c}|\bar{a}}$$

# Encoding Local Structure

without local structure

$$\begin{array}{lll} I_a \vee I_{\bar{a}} & I_b \vee I_{\bar{b}} & I_c \vee I_{\bar{c}} \\ \neg I_a \vee \neg I_{\bar{a}} & \neg I_b \vee \neg I_{\bar{b}} & \neg I_c \vee \neg I_{\bar{c}} \end{array}$$

$$\begin{array}{ccc} I_a & \iff & P_a \\ I_{\bar{a}} & \iff & P_{\bar{a}} \end{array}$$

$$\begin{array}{ccc} I_a \wedge I_b & \iff & P_{b|a} \\ I_a \wedge I_{\bar{b}} & \iff & P_{\bar{b}|a} \\ I_{\bar{a}} \wedge I_b & \iff & P_{b|\bar{a}} \\ I_{\bar{a}} \wedge I_{\bar{b}} & \iff & P_{\bar{b}|\bar{a}} \end{array}$$
  

$$\begin{array}{ccc} I_a \wedge I_c & \iff & P_{c|a} \\ I_a \wedge I_{\bar{c}} & \iff & P_{\bar{c}|a} \\ I_{\bar{a}} \wedge I_c & \iff & P_{c|\bar{a}} \\ I_{\bar{a}} \wedge I_{\bar{c}} & \iff & P_{\bar{c}|\bar{a}} \end{array}$$



with local structure

$$\begin{array}{lll} I_a \vee I_{\bar{a}} & I_b \vee I_{\bar{b}} & I_c \vee I_{\bar{c}} \\ \neg I_a \vee \neg I_{\bar{a}} & \neg I_b \vee \neg I_{\bar{b}} & \neg I_c \vee \neg I_{\bar{c}} \end{array}$$

WeChat: cstutorcs

$$\neg I_a \vee \neg I_{\bar{b}}$$

Email: tutorcs@163.com

$$\neg I_{\bar{a}} \vee \neg I_b$$

QQ: 749389476

$$(I_a \vee I_c) \vee (I_{\bar{a}} \wedge I_{\bar{c}}) \iff P_1 \text{ (weight of } P_1 \text{ is .8)}$$

$$(I_a \wedge I_{\bar{c}}) \vee (I_{\bar{a}} \wedge I_c) \iff P_2 \text{ (weight of } P_2 \text{ is .2)}$$

<https://tutorcs.com>

$$I_a \vee I_{\bar{a}} \iff P_3 \text{ (weight of } P_3 \text{ is .5)}$$

A	$\theta_A$	A		B	$\theta_{B A}$	A		C	$\theta_{C A}$
		true	false	true	0	false	true	.8	
true	.5	true	false	false	0	true	false	.2	
false	.5	false	true	true	0	false	true	.2	
				false	1	false	false	.8	

# WMC using Tractable Circuits



$$\begin{array}{ll} I_a \vee I_{\bar{a}} & I_b \vee I_{\bar{b}} \\ \neg I_a \vee \neg I_{\bar{a}} & \neg I_b \vee \neg I_{\bar{b}} \end{array}$$

$$\begin{array}{l} \neg I_a \vee \neg I_{\bar{b}} \\ \neg I_{\bar{a}} \vee \neg I_b \end{array}$$

$$\begin{array}{ll} (I_a \wedge I_c) \vee (I_{\bar{a}} \wedge I_{\bar{c}}) & \iff P_1 \quad (\text{weight of } P_1 \text{ is } .8) \\ (I_a \wedge I_{\bar{c}}) \vee (I_{\bar{a}} \wedge I_c) & \iff P_2 \quad (\text{weight of } P_2 \text{ is } .2) \\ I_a \vee I_{\bar{a}} & \iff P_3 \quad (\text{weight of } P_3 \text{ is } .5) \end{array}$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

and → \*

or → +

negative literals → 1

positive parameter literals → weight



NNF Circuit: Decomposable, Deterministic, Smooth

# WMC using Tractable Circuits



$$\begin{array}{ll} I_a \vee I_{\bar{a}} & I_b \vee I_{\bar{b}} \\ \neg I_a \vee \neg I_{\bar{a}} & \neg I_b \vee \neg I_{\bar{b}} \end{array}$$

$$\begin{array}{l} \neg I_a \vee \neg I_{\bar{b}} \\ \neg I_{\bar{a}} \vee \neg I_b \end{array}$$

$$(I_a \wedge I_c) \vee (I_{\bar{a}} \wedge I_{\bar{c}}) \iff P_1 \quad (\text{weight of } P_1 \text{ is } .8)$$

$$(I_a \wedge I_{\bar{c}}) \vee (I_{\bar{a}} \wedge I_c) \iff P_2 \quad (\text{weight of } P_2 \text{ is } .2)$$

$$I_a \vee I_{\bar{a}} \iff P_3 \quad (\text{weight of } P_3 \text{ is } .5)$$


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>



Arithmetic Circuit (AC)


# Local Structure 程序代写代做 CS编程辅导



A	B	$\theta_{B A}$
true	true	1
true	false	0
false	true	0
false	false	1

A	C	$\theta_{C A}$
true	true	.8
true	false	.2
false	true	.2
false	false	.8

AC without local structure



WeChat: cstutorcs


Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476



<https://tutorcs.com>

AC with local structure




# Reasoning with ACS

程序代写代做 CS 编程辅导



A	B	$\theta_{B A}$	A	C	$\theta_{C A}$
true	true	1	true	true	.8
true	false	0	true	false	.2
false	true	0	false	true	.2
false	false	1	false	false	.8

no evidence



WeChat: cstutorcs


Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

evidence : b, c̄




# Classical Probabilistic Reasoning Algorithms



WeChat: cstutorcs  
Assignment Project Exam Help  
Email: tutorcs@163.com  
QQ: 749389476



$$O(n \exp\{w\})$$



Relational networks (251 networks)  
<https://tutorcs.com>

have massive logical constraints and context-specific independence

reductions now common in probabilistic programming

# Other Reductions



- Variables with large card
- Better exploitation of local structure
- Minimize size of CNF
- ....

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

## 程序代写代做 CS 编程辅导

## Partition Function Estimation: A Quantitative Study. IJCAI-21



Method Name	Problem Classes								Total
	ne- (65)	BN (60)	Ising (52)	Segment (50)	ObjDetect (35)	Protein (29)	Misc (27)	Total	
Ace	5	60	51	50	0	16	15	611	
Fractional Belief Propagation (FBP)	293	65	58	41	48	32	29	9	575
Loopy Belief Propagation (BP)	292	65	58	41	46	32	29	10	573
Generalized Belief Propagation (GBP)	281	65	36	41	40	34	29	9	541
Edge Deletion Belief Propagation (EDBP)	245	42	56	50	49	35	28	23	528
GANAK	353	58	53	4	0	0	7	14	489
Double Loop Generalised BP (HAK)	99	65	58	43	43	35	29	14	486
Tree Expectation Propagation (TREEEP)	101	65	58	50	48	35	29	15	401
SampleSearch	89	56	33	52	37	35	29	25	356
Bucket Elimination (BE)	98	32	15	72	58	25	29	22	333
Conditioned Belief Propagation (CBP)	109	32	21	41	50	35	29	8	325
Join Tree (JT)	98	32	15	52	50	19	26	21	313
Dynamic Importance Sampling (DIS)	24	65	55	52	50	35	29	27	307
Weighted Mini Bucket Elimination (WMB)	68	13	17	50	50	20	28	12	258
miniC2D	187	1	30	31	0	0	0	1	250
WeightCount	93	0	27	0	0	0	0	0	120
WISH	0	0	0	9	0	0	0	0	9
FocusedFlatSAT	6	0	0	0	0	0	0	0	6

# Backpropagation

程序代写代做CS编程辅导


Compute marginals in bu





$$\frac{\partial f}{\partial \lambda_x}(\mathbf{e}) = \Pr(x, \mathbf{e} - X)$$

$$\theta_{x|\mathbf{u}} \frac{\partial f}{\partial \theta_{x|\mathbf{u}}}(\mathbf{e}) = \Pr(x, \mathbf{u}, \mathbf{e})$$

Further applications to learning parameters  
using gradient descent and EM



# Model-Based Supervised Learning using ACs




can be trained discriminatively from labeled data using gradient descent

<https://tutorcs.com>

can integrate domain knowledge (independence, logical constraints, functional dependencies)

**new AC compilation algorithm:** can exploit functional dependencies computationally without knowing their identities



程序代写代做 CS编程辅导



# Arithmetic Circuits (ACs)



Assignment Project Exam Help

A Modern Perspective  
Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# From Boolean to Arithmetic Circuits




# A Different Perspective

程序代写 做 CS 编程辅导



# A Different Perspective

程序代写 做 CS 编程辅导



# MPE and Marginal Factors



Factor

A	B	C	
T	T	T	0.08
T	T	F	1.24
T	F	T	0.10
T	F	F	3.10
F	T	T	0.00
F	T	F	0.00
F	F	T	9.42
F	F	F	0.06

WeChat: cstutorcs  
MPE

find maximal value of row that satisfies some event (e.g., B=F)  
(subsumes SAT, Assignment Project Exam Help)

Email: tutorcs@163.com  
MAR

sum values of rows that satisfy some condition (e.g., B=F)  
(subsumes MAJ-SAT, #SAT and WMC)

<https://tutorcs.com>

程序代写代做 CS编程辅导




# Two Fundamental Notions Three Fundamental Questions

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

# Fundamental Notion: Arithmetic Circuit (AC)



indicator variables, constants, additions, multiplications

# Fundamental Notion: Evaluating AC at evidence



# Three Fundamental Questions



- What factor  $f(X)$  does an AC represent?  
(the reference factor)
- When does an AC **compute marginals** of factor  $f(X)$ ?  
(in linear time)
- When does an AC **compute MPE** of factor  $f(X)$ ?  
(in linear time)

WeChat: cstutorcs  
Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Factor Represented by an AC

$A$	$B$	$f(A,B)$
$a$	$b$	?
$a$	$\bar{b}$	?
$\bar{a}$	$b$	?
$\bar{a}$	$\bar{b}$	?




<https://tutorcs.com>

evaluate AC at complete variable instantiations (evidence that fixes values of  $A$  and  $B$ )

# Factor Represented by an AC

$A$	$B$	$f(A,B)$
$a$	$b$	?
$a$	$\bar{b}$	?
$\bar{a}$	$b$	?
$\bar{a}$	$\bar{b}$	?




<https://tutorcs.com>

evaluate AC at complete variable instantiations (evidence that fixes values of  $A$  and  $B$ )

# Factor Represented by an AC

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	?
$\bar{a}$	$b$	?
$\bar{a}$	$\bar{b}$	?




<https://tutorcs.com>

evaluate AC at complete variable instantiations (evidence that fixes values of  $A$  and  $B$ )

# Factor Represented by an AC

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	?
$\bar{a}$	$\bar{b}$	?




<https://tutorcs.com>

evaluate AC at complete variable instantiations (evidence that fixes values of  $A$  and  $B$ )

# Factor Represented by an AC

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	?




<https://tutorcs.com>

evaluate AC at complete variable instantiations (evidence that fixes values of  $A$  and  $B$ )

# Factor Represented by an AC

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12



<https://tutorcs.com>

evaluate AC at complete variable instantiations (evidence that fixes values of  $A$  and  $B$ )

# Key Observation 程序代写代做 CS编程辅导



it is easy to construct an AC that  
represents  
Assignment Project Exam Help  
the factor of a Bayesian network  
WeChat: cstutors  
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$A$	$f_1(A)$
$a$	1
$\bar{a}$	2

$A$	$B$	$f_2(A, B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	5
$\bar{a}$	$\bar{b}$	6



程序代写代做 CS 编程辅导

$A$	$B$	$f(A, B)$
$a$	$b$	$1 * 3$
$a$	$\bar{b}$	$1 * 4$
$\bar{a}$	$b$	$2 * 5$
$\bar{a}$	$\bar{b}$	$2 * 6$

$A$	$f(A)$
$a$	$1 \cdot \lambda_a$
$\bar{a}$	$2 \cdot \lambda_{\bar{a}}$

$A$	$B$	$f(A, B)$
$a$	$b$	$3 \cdot \lambda_a \lambda_b$
$a$	$\bar{b}$	$4 \cdot \lambda_a \lambda_{\bar{b}}$
$\bar{a}$	$b$	$5 \cdot \lambda_{\bar{a}} \lambda_b$
$\bar{a}$	$\bar{b}$	$6 \cdot \lambda_{\bar{a}} \lambda_{\bar{b}}$

WeChat: cstutorcs

AC: Size linear in the size of input factors

Assignment Project Exam Help

Email: tutorcs@163.com

$= [1(1) + 2(0)] * [3(1)(0) + 4(1)(1) + 5(0)(0) + 6(0)(1)]$

QQ: 749389476

<https://tutorcs.com>

$$1 \cdot \lambda_a + 2 \cdot \lambda_{\bar{a}}$$

$$3 \cdot \lambda_a \lambda_b + 4 \cdot \lambda_a \lambda_{\bar{b}} + 5 \cdot \lambda_{\bar{a}} \lambda_b + 6 \cdot \lambda_{\bar{a}} \lambda_{\bar{b}}$$

# Three Fundamental Questions



- What factor  $f(X)$  does an AC represent?  
(the reference factor)
- When does an AC **compute marginals** of factor  $f(X)$ ?  
(in linear time)
- When does an AC **compute MPE** of factor  $f(X)$ ?  
(in linear time)

WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Does AC Compute Marginals?

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12




<https://tutorcs.com>

Does AC evaluate correctly at every partial variable instantiation (evidence)?

# Does AC Compute Marginals?

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12




<https://tutorcs.com>

Evaluate at  $a$

# Does AC Compute Marginals?

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12

$$f(a) = 7$$



<https://tutorcs.com>


Evaluate at  $a$

# Does AC Compute Marginals?

程序代写代做CS编程辅导

A	B	$f(A,B)$
a	b	3
a	$\bar{b}$	4
$\bar{a}$	b	10
$\bar{a}$	$\bar{b}$	12


$$f(a) = 7$$



# This AC Does Compute Marginals



$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12



# Factor Computed by AC

程序代写代做 CS 编程辅导

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



# Factor Computed by AC

程序代写代做 CS 编程辅导

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



# Factor Computed by AC

程序代写代做 CS 编程辅导

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



# Factor Computed by AC

程序代写代做 CS 编程辅导

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



# AC Computes Marginals

程序代写 | 代码代做 | CS编程辅导

$A$	$B$	$f(A,B)$
$a$	$b$	3
$a$	$\bar{b}$	4
$\bar{a}$	$b$	10
$\bar{a}$	$\bar{b}$	12

$$f(a) = 7$$



$$7 = f(a)$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



# AC Computes Marginals

程序代写 | 代码代做 | CS编程辅导

A	B	$f(A,B)$
a	b	3
a	$\bar{b}$	4
$\bar{a}$	b	10
$\bar{a}$	$\bar{b}$	12

$$f(\bar{b}) = 16$$



$$16 = f(\bar{b})$$


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



# AC Computes Marginals

程序代写 | 代码代做 | CS编程辅导

A	B	$f(A,B)$
a	b	3
a	$\bar{b}$	4
$\bar{a}$	b	10
$\bar{a}$	$\bar{b}$	12

$$f(\tau) = 29$$



$$29 = f(\tau)$$


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



程序代写代做 CS编程辅导



WeChat: cstutorcs  
Why Did This AC Compute Marginals?  
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Three Fundamental Questions



- What factor  $f(X)$  does an AC represent?  
(the reference factor)
- When does an AC compute marginals of factor  $f(X)$ ?  
(in linear time)
- When does an AC compute MPE of factor  $f(X)$ ?  
(in linear time)

WeChat: cstutorcs  
Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

# This AC Also Computes MPE

程序代写  
代做CS编程辅导



A	B	$f(A,B)$
a	b	3
a	$\bar{b}$	4
$\bar{a}$	b	10
$\bar{a}$	$\bar{b}$	12



# This AC Also Computes MPE

程序代写  
代做CS编程辅导


A	B	$f(A,B)$
a	b	3
a	$\bar{b}$	4
$\bar{a}$	b	10
$\bar{a}$	$\bar{b}$	12



# This AC Does Not Compute MRE

程序代写 代做CS编程辅导


$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78



# This AC Does Not Compute MRE

程序代写 代做CS编程辅导

$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78



程序代写代做 CS编程辅导



WeChat: cstutorcs  
Why Did This AC Not Compute MPE?  
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Properties of Arithmetic Circuits




If an AC computes a factor  $f$ , then it will compute other quantities (marginals, MPE,...) depending on what properties it satisfies (decomposability, smoothness, determinism).

QQ: 749389476

<https://tutorcs.com>


# Properties of Arithmetic Circuits



**Decomposable**  
 $\text{vars}(AC_A) \cap \text{vars}(AC_B) = \emptyset$



**Selective**  
at most one +-input is non-zero  
under any complete instantiation  
 $\text{https://tutorcs.com}$




**Smooth**  
 $\text{vars}(AC_A) = \text{vars}(AC_B)$

**Complete**


# Not Decomposable

程序代写代做 CS 编程辅导




# Not Decomposable

程序代写代做 CS 编程辅导




# Not Deterministic

程序代写代做 CS 编程辅导




# Not Smooth

程序代写代做 CS编程辅导



# Not Smooth

程序代写代做 CS编程辅导



# Computing Marginals and MPE



If an AC computes a factor  $f$ , then it will compute marginals and MPE (in linear time) if it is **decomposable, smooth and deterministic.**

ACs: Marginals (2003), MPE (2006) Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

If an AC computes a factor  $f$ , then it will compute marginals if it is **decomposable and smooth.**

SPNs: Marginals (2011) SPNs MPE

程序代写代做 CS编程辅导




# The Roles of Decomposability, Smoothness and Determinism

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Fundamental Notion Subcircuit



WeChat: cstutorcs


Assignment Project Exam Help  $\lambda_a$   $\lambda_{\bar{a}}$  2

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

# Fundamental Notion Subcircuit




# Fundamental Notion Subcircuit



# Decomposability and Smoothness

**Decomposable** →  
subcircuit term is consistent

**Smooth** →  
subcircuit term mentions  
all variables




**Decomposable and Smooth** →  
subcircuit term is a complete variable instantiation

# AC Not Decomposable




term:  $\bar{a} \ b \ a$



subcircuit term is **not consistent**

# AC Not Smooth


程序代写代做 CS编程辅导



subcircuit term does not mention every variable

# Role of Decomposability and Smoothness

$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78



subcircuit term is a **complete variable instantiation**


# Role of Decomposability and Smoothness

$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78



term:  $a\bar{b}$


coefficient:  $5*2 = 10$



subcircuit term is a **complete variable instantiation**

# Role of Decomposability and Smoothness

$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78




subcircuit term is a **complete variable instantiation**

# Role of Decomposability and Smoothness

$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78




term:  $\bar{a}\bar{b}$



subcircuit term is a **complete variable instantiation**

# Role of Decomposability and Smoothness


$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78



subcircuit term is a **complete variable instantiation**

# Role of Decomposability and Smoothness

$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78



subcircuit term is a **complete variable instantiation**

# Role of Determinism

程序代写代做 CS 编程辅导

## Decomposable & Smooth

subcircuit term is a complete variable instantiation



## Determinism →

1-to-1 mapping between  
subcircuits and complete  
variable instantiations





Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

$\begin{array}{|c|c|c|} \hline A & B & f(A,B) \\ \hline 0 & 0 & 4 \\ \hline 0 & 1 & 5 \\ \hline 1 & 0 & 10 \\ \hline 1 & 1 & 12 \\ \hline \end{array}$

<https://tutorcs.com>



excluding subcircuits with zero coefficients

# Understanding the MAR & MPE Algorithms



**Setting indicator values** to 0/1 modifies coefficients of subcircuits: **zeros out coefficients** of subcircuits that are not compatible with evidence  
Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>


# Marginals Algorithm

程序代写代做 CS 编程辅导

$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78



term:  $\bar{a}\bar{b}$   
coefficient:  $5*3 = 15$   
coefficient:  $9*7 = 63$



sums coefficients of subcircuits that are compatible with evidence


# Marginals Algorithm

程序代写代做 CS 编程辅导

$A$	$B$	$f(A,B)$
$a$	$b$	56
$a$	$\bar{b}$	64
$\bar{a}$	$b$	68
$\bar{a}$	$\bar{b}$	78



term:  $\bar{a}\bar{b}$   
coefficient:  $5*3 = 15$   
coefficient:  $9*7 = 63$



sums coefficients of subcircuits that are compatible with evidence

# MPE Algorithm


Proposed in 2006, analysis in 2017

A	B	$f(A,B)$
a	b	3
a	$\bar{b}$	4
$\bar{a}$	b	10
$\bar{a}$	$\bar{b}$	12

程序代写代做 CS编程辅导

term:  $\bar{a} \bar{b}$

coefficient:  $6 * 2 = 12$



finds largest coefficient of subcircuits compatible with evidence

# Decomposable and Smooth ACs



**Theorem 1.** If an AC computes a factor  $f$ , and AC is decomposable and smooth, then the AC computes the marginals of  $f$ .

WeChat: cstutorcs

Assignment Project Exam Help  
These circuits are known as **SPNs**  
**(Sum-Product Networks, 2011)** Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Deterministic, Decomposable and Smooth ACs

**Theorem 3.** If an AC is deterministic, decomposable and deterministic, then to evaluate MPE, we can evaluate the maximizer circuit. WeChat: cstutorcs



These are the original ACs  
(Arithmetic Circuits, 2003)

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

# SPNs and Selective SPNs

程序代写代做 CS 编程辅导

SPNs (2011)



WeChat: cstutorcs

Assignment Project Exam Help  
Arithmetic Circuits (AC)

Email: tutorcs@163.com

Original (wrong) claim: SPNs also compute MPE in linear time  
QQ: 749389476

Later claim: SPNs with determinism compute MPE in linear time  
<https://tutorcs.com>  
These were called **selective SPNs**, which is another name for  
ACs that are decomposable, deterministic and smooth.

# Why Determinism is Needed

**Decomposable & Smooth**

subcircuit term is a complete variable instantiation



WeChat: cstutorcs

**Determinism →**

1-to-1 mapping between  
subcircuits and complete  
variable instantiations

Assignment Project Exam Help





Email: tutorcs@163.com

QQ: 749389476

$\begin{array}{|c|c|c|} \hline A & B & f(A,B) \\ \hline 0 & 0 & 1 \\ \hline 0 & 1 & 4 \\ \hline 1 & 0 & 10 \\ \hline 1 & 1 & 12 \\ \hline \end{array}$

*excluding subcircuits with zero coefficients*

程序代写代做CS编程辅导



# Hardness of MPE

程序代写代做CS编程辅导



**Theorem 2.** The MPE decision problem is NP-complete in decomposable and smooth ACs.

WeChat: cstutorcs

Original proof 2016, new proof 2017 Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Implications of Relaxing Determinism

- **Positive:** Separation
- **Negative:** Parametric Incompleteness



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Separation

程序代写代做 CS编程辅导



**Theorem 4.** There is a function  $f$  of factors  $f(X_1, \dots, X_n)$  such that  
(1)  $f(X_1, \dots, X_n)$  can be computed by a polysize decomposable  
and smooth AC

WeChat: cstutorcs

(2) any AC that computes  $f(X_1, \dots, X_n)$  and is deterministic,  
decomposable and smooth must have exponential size

QQ: 749389476

<https://tutorcs.com>

# Implications of Relaxing Determinism

- Positive: Separation
- Negative: Parametric Incompleteness



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

# Complete Parameters



**Definition 10** A set of parameters  $\Theta$  is complete for factor  $f(\mathbf{X})$  iff for every instantiation  $\theta \in \Theta$ , the parameter  $f(\mathbf{x})$  can be expressed as a product of parameters in  $\Theta$ .

WeChat: cstutorcs

Assignment Project Exam Help

$a_1 b_1 c_1$	.001	Email: tutorcs@163.com
$a_1 b_1 c_2$	.009	QQ: 749389476
$a_1 b_2 c_1$	.009	$\Theta = \{ .1, .2, .8, .9 \}$
$a_1 b_2 c_2$	.081	
$a_2 b_1 c_1$	.036	
$a_2 b_1 c_2$	.144	<a href="https://tutorcs.com">https://tutorcs.com</a>
$a_2 b_2 c_1$	.144	
$a_2 b_2 c_2$	.576	


# Complete Parameters

程序代写代做 CS 编程辅导

The parameters of a Bayesian network



use for its factor



A	B	$\Theta_A$
$a_1$	$b_1$	.1
$a_1$	$b_2$	.9

A	B	$\Theta_{B A}$	A	C	$\Theta_{C A}$
$a_1$	$b_1$	.1	$a_1$	$c_1$	.1
$a_1$	$b_2$	.9	$a_1$	$c_2$	.9
$a_2$	$b_1$	.2	$a_2$	$c_1$	.2
$a_2$	$b_2$	.8	$a_2$	$c_2$	.8

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

$$\Theta = \{ .1, .2, .8, .9 \}$$

Network instantiation	
$a_1b_1c_1$	.001
$a_1b_1c_2$	.009
$a_1b_2c_1$	.009
$a_1b_2c_2$	.081
$a_2b_1c_1$	.036
$a_2b_1c_2$	.144
$a_2b_2c_1$	.144
$a_2b_2c_2$	.576

# Notation

$\mathcal{AC}(\mathbf{X}, \Theta)$

Arithmetic Circuit (AC) over variables  $\mathbf{X}$   
and whose constants come from parameters  $\Theta$

程序代写代做 CS编程辅导



WeChat: cstutorcs  
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

# Parametric Incompleteness



**Theorem 5 (Completeness)** Consider a factor  $f(\mathbf{X})$  and complete parameters  $\Theta$ . There exists an arithmetic circuit  $AC(\mathbf{X}, \Theta)$  that computes the factor marginals and is deterministic, decomposable and smooth.

WeChat: cstutorcs  
Assignment Project Exam Help



A	B	$\Theta_{B A}$
$a_1$	$b_1$	.1
$a_2$	$b_2$	.9

A	B	$\Theta_{B A}$	A	C	$\Theta_{C A}$
$a_1$	$b_1$	.1	$a_1$	$c_1$	.1
$a_1$	$b_2$	.9	$a_1$	$c_2$	.9
$a_2$	$b_1$	.2	$a_2$	$c_1$	.2
$a_2$	$b_2$	.8	$a_2$	$c_2$	.8

Email: tutorcs@163.com  
QQ: 749389476  
<https://tutorcs.com>

Theorem 5 does not hold if we drop determinism

Enforcing decomposability and smoothness is not sufficient: You need to search for AC parameters

# Parametric Incompleteness

程序代写代做CS编程辅导

Boolean Factor

A	B	C	
T	T	T	0
T	T	F	1
T	F	T	1
T	F	F	1
F	T	T	0
F	T	F	1
F	F	T	0
F	F	F	0



An AC that computes all minterms of a Boolean factor is an AC that can count models

WeChat: cstutorcs

$$\Theta = \{0, 1\}$$

Email: tutorcs@163.com

**Theorem 6 (Parametric Incompleteness)** Let  $f(\mathbf{X})$  be a Boolean factor and  $\Theta = \{0, 1\}$  ( $\Theta$  is complete for  $f$ ). A circuit  $\mathcal{AC}(\mathbf{X}, \Theta)$  cannot compute  $f(\mathbf{X})$  if it is decomposable, smooth and free of dead nodes, but not deterministic.

QQ: 749389476

<https://tutorcs.com>

# ACs, SPNs, and Probabilistic Circuits



- **Loose usage:** Computation graphs, with indicator variables, adders and multipliers

- **Computer theory:** ACs (not the same as computation graphs)

- **Property-driven (more precise usage):**

WeChat: cstutorcs

- **AC (2003):** decomposable, deterministic and smooth
- **SPN (2011):** decomposable and smooth
- **Selective SPN:** decomposable, deterministic and smooth ( $\neq$  AC)

- **Probabilistic Circuits (umbrella term):**

Restrictive as factors do not need to represent probabilities (they are general mappings from instantiations to positive numbers)

- **There are other circuit types:** QQ: 749389476

- **PSDD (2014):** structured decomposability, partitioned determinism
- ....

<https://tutorcs.com>

- **Guide:** Focus on properties

All implications of what we studied/know on the Boolean side

# Big Ideas & Milestones



A Differential Approach to Inference in Bayesian Networks  
Adnan Darwiche, JACM 2003

Introduced ACs (decomposable, smooth, deterministic)

On the Robustness of Most Probable Explanations  
Hei Chan, Adnan Darwiche, UAI 2006

WeChat: cstutorcs  
Introduced MPE algorithm for ACs (and subcircuits)

Learning Arithmetic Circuits  
Daniel Lowd, Pedro Domingos, UAI 2008

Assignment Project Exam Help  
Introduced learning ACs from data

Sum-Product Networks  
Hoifung Poon, Pedro Domingos, UAI 2011

Email: tutorcs@163.com  
Introduced handcrafting ACs

QQ: 749389476  
Dropped determinism

On Relaxing Determinism in Arithmetic Circuits  
Arthur Choi and Adnan Darwiche, ICML 2017

<https://tutorcs.com>  
Provided a comprehensive theory that explained roles  
of decomposability, smoothness and determinism  
(this lecture)

# Tractable Boolean and Arithmetic Circuits



Adnan Darwiche, Computer Science Department, UCLA

WeChat: cstutorcs

Tractable Boolean and arithmetic circuits have been studied extensively in AI for over two decades now. These circuits were originally proposed as “compiled objects,” meant to facilitate logical and probabilistic reasoning, as they permit various types of inference to be performed in linear-time and a feed-forward fashion like neural networks. In more recent years, the role of tractable circuits has significantly expanded as they became a computational and semantical backbone for some approaches that aim to integrate knowledge, reasoning and learning. In this chapter, we review the foundations of tractable circuits and some associated milestones, while focusing on their core properties and techniques that make them particularly useful for the broad aims of neuro-symbolic AI.

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>