

# CS 320 Midterm (10%) - Fall 2021

程序代写代做 CS编程辅导

Instructor: Tyler Caraza-Harter

First/Given Name: \_\_\_\_\_ Last/Surname: \_\_\_\_\_

Net ID: \_\_\_\_\_ pwisc.edu

Fill in these fields (left to right) form (use pencil):



1. LAST NAME (surname) and Given name), fill in bubbles
2. IDENTIFICATION NUMBER and ID number, fill in bubbles
3. Under A of SPECIAL CODES, write your lecture number, fill in bubbles. 1=8:50am, 2=11am
4. Under B of SPECIAL CODES, tell us about the nearest person (if any) to your left. 0=no person to the left in your row, 1=somebody you do not know is there, 2=somebody you do know is there.
5. Under C of SPECIAL CODES, do the same as B, but for the person to your right
6. **Under D of SPECIAL CODES, write 5 and fill in bubble 5.** This is very important!

Make sure you fill all the special codes above accurately in order to get graded.

You have 40 minutes to take the exam. Use a #2 pencil to mark all answers. When you're done, please hand in these sheets in addition to your filled-in scantron. You may not sit adjacent to your friends or other people you know in the class (having only one empty seat is considered "adjacent"). You may only reference your notesheet. You may not use books, your neighbors, calculators, or other electronic devices on this exam. Please place your student ID face up on your desk. Turn off and put away portable electronics now.

WeChat: estutores

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

(Black Page for You to Do Scratch Work)

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

Q1. Where is a deque most useful in BFS code?

- (A) to track which nodes have been visited
- (B) to track nodes to be visited in the future
- (C) to store the path from



Q2. What is something h

- (A) how large a zip file is
- (B) how much memory is
- (C) how much storage space is being used
- (D) what the largest compressed file is inside of a zip file

Q3. What will the length of Y be equal to after the following runs?

```
with open("coords.txt") as f:  
    X = f.read()  
    Y = f.read()
```

- (A) 0
- (B) len(X)
- (C) total length of the file
- (D) whatever the length of the second line in the file is

Q4. The DOM (Document Object Model) of a web page is a BST (Binary Search Tree).

- (A) True
- (B) False

程序代写代做 CS编程辅导

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Q5. If a Flask app has the following handlers, what does it print when a user visits the home page in a browser?

```
@app.route("/")
def home():
    print("X")
    return '<html><body></body></html>'
```

```
@app.route("/plot.p
def f():
    print("Y")
    return "TODO"
```

```
@app.route("/out.sv
def g():
    print("Z")
    return "TODO"
```



程序代写代做 CS编程辅导

WeChat: cstutorcs

(A) X only (B) X and Y (C) X and Z (D) X, Y, and Z

Q6. What does `nums` contain after the following runs?

```
nums = []
def h(z):
    if z > 2:
        h(z-1)
    nums.append(z)
h(5)
print(nums)
```

(A) [2, 3, 4] (B) [2, 3, 4, 5] (C) [] (D) [4, 3, 2] (E) [5, 4, 3, 2]

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Q7. Does the regular expression `r"\d.+b"` match anything in the string `"1B.abdc"`?

(A) yes (B) no

Q8. What type does `check_output` return?


(A) int (B) bytes (C) bool (D) str (E) utf8

Q9. What is the complexity of the following code, if  $N$  is the length of the list `L`? Choose the best answer.

```
for num in L:
    avg = sum(L) / len(L)
    if num > 2 * avg:
        print("outlier!")
```

(A)  $O(1)$  (B)  $O(N)$  (C)  $O(N^2)$  (D)  $O(N^2 + 1)$  (E)  $O(N^3)$

Q10. What can be said about the following graph?



程序代写代做 CS编程辅导



- (A) it is not acyclic and not connected
- (B) it is connected but not acyclic
- (C) it is acyclic but not connected
- (D) it is both connected and acyclic

WeChat: cstutorcs

Assignment Project Exam Help

Q11. What error might we get when running the following code?

```
dog.fetch("A", "B")
```

Email: tutorcs@163.com

- (A) `TypeError: fetch() takes 1 positional argument but 3 were given`
- (B) `TypeError: fetch() takes 2 positional arguments but 2 were given`
- (C) `TypeError: fetch() takes 3 positional arguments but 2 were given`
- (D) `TypeError: fetch() takes 4 positional arguments but 4 were given`

QQ: 749389476

<https://tutorcs.com>

Q12. What is the complexity of the following code, if  $N$  is the length of the list `L`? Choose the best answer.

```

for i in range(len(L)):
    for j in range(3):
        if i+j < len(L):
            print(L[i+j])
  
```

- (A)  $O(1)$
- (B)  $O(N)$
- (C)  $O(N^2)$
- (D)  $O(N^2 + 1)$
- (E)  $O(N^3)$

Q13. If `L` is a list with 100 items, what index should replace `????` to make the code probably run SLOWEST?

```
L.insert(????, "new entry")
```

- (A) -1
- (B) 0
- (C) 50
- (D) 99
- (E) 100

Q14. Each function can have at most one frame on the stack at a time.

- (A) True (B) False

程序代写代做 CS编程辅导

Q15. If a BST is constructed using the algorithm we learned in class, and the insert order is [6, 7, 4, 10], where will 10 be?

- (A) root.left.left (B) root.right.left (C) root.left.right (D) root.right.right



Q16. Which algorithm is r

- (A) DFS (B) BFS

Q17. What is printed?

```
h = []
for item in [5, -1, 3, 0.5, 0]:
    heapq.heappush(h, item)
print(heapq.heappop(h))
```

- (A) 5 (B) -1 (C) 3 (D) 0.5 (E) 0

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

Q18. Suppose the following runs without error:

```
# code hidden
X.next = Y
Y.next = X
Z.next = Y
```

Which of the following refers to the same object as X?

- (A) X.next (B) Z.next (C) X.next.next.next (D) Y.next.next.next (E) Z.next.next.next

QQ: 749389476

https://tutorcs.com

Q19. For git, "headless" means:

- (A) there is no branch named HEAD  
 (B) there is no tag named HEAD  
 (C) the HEAD branch does not point to the main commit  
 (D) the latest commit is untagged  
 (E) HEAD does not point to any branch

Q20. What is `x` ?

```
class C:  
    def __init__(self, vals):  
        self.vals = vals
```

```
    def __len__(self):  
        return 1
```

```
    def __getitem__(self, i):  
        return 2
```

```
obj = C([3, 5, 4])
```

```
x = len(obj.vals) #
```



(A) 1   (B) 2   (C) 3   (D) 4   (E) 5

程序代写代做 CS编程辅导

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>