

# CS 220 - Spring 2020 Instructor: Tyler Caraza-Harter

Midterm — 20%



(Last) Surname: \_\_\_\_\_ (First) Given name: \_\_\_\_\_

NetID (email): \_\_\_\_\_ @wisc.edu

Fill in these fields (look at the scantron form (use #2 pencil):

1. LAST NAME (surname) and FIRST NAME (given name), fill in bubbles
2. IDENTIFICATION NUMBER is your Campus ID number, fill in bubbles
3. Under *A* of SPECIAL CODES, write your lecture number, fill in bubbles:
  - 1 - MWF 9:55am (Tyler morning)
  - 2 - MWF 2:25pm (Tyler afternoon)
4. Under *B* of SPECIAL CODES, tell us about the nearest person (if any) to your left
  - 0 - no person to the left in your row
  - 1 - somebody you **do not** know is there
  - 2 - somebody you **do** know is there
5. Under *C* of SPECIAL CODES, do the same as *B*, but for the person to your right
6. Leave special codes *DE* blank
7. Under *F* of SPECIAL CODES, write **8** and fill in bubble **8**

QQ: 749389476

Make sure you fill all the special codes above accurately in order to get graded.

<https://tutorcs.com>

You have 2 hours to take the exam. Use a #2 pencil to mark all answers. When you're done, please hand in these sheets in addition to your filled-in scantron.

You may not sit adjacent to your friends or other people you know in the class (having only one empty seat is considered "adjacent"). You may only reference your notesheet. You may not use books, your neighbors, calculators, or other electronic devices on this exam. Please place your student ID face up on your desk. Turn off and put away portable electronics now.

We won't always include imports in examples, but assume it has been done in a standard way (for example, assume `from pandas import DataFrame, Series` before each code example). Sometimes there will be multiple right answers – choose the best one. For example, saying an order of growth is in  $O(N)$  is more informative (and therefore better) than saying it is in  $O(N^2)$ , assuming both are true.

---

Good luck! [feel free to do scratch work here]

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help


Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

## Trees

程序代写代做 CS编程辅导



```
def contains(node, target):
    if node == None:
        return False

    if node.val == target:
        return True
    elif target < node.val:
        return contains(node.left, target)
    else:
        return contains(node.right, target)
```

"R" means "right child"  
"L" means "left child"

WeChat: cstutorcs

- Which leaf should be removed to make the above binary tree a BST?  
A. 1   B. 4.5   C. 5   D. 8   E. 99
- What is `root.left.right.left`?  
A. None   B. node 1   C. node 2   D. node 4   E. node 4.5
- If somebody calls `contains(root, 1)`, how many times will `contains` be invoked? Assume `root` refers to node 6.  
A. 1   B. 2   C. 4   D. 6   E. 12
- What is/are the *base case(s)* for `contains`?  
A. when `node == None`  
B. when `node.val == target`  
C. all of the above  
D. none of the above
- (T/F) When inserting nodes to a BST, inserting in random order will typically produce a **more balanced** tree than inserting in ascending order.  
A. True   B. False

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

## Complexity

程序代写代做 CS编程辅导

Assume a correct and efficient `merge_sort` implementation (like the one in lab 3). Let  $N$  be `len(nums)`.

```
def cumulative_v1(nums):
    nums = merge_sort(nums)
    results = []
    for i in range(len(nums)):
        total = 0
        for j in range(0, i+1):
            total += nums[j]
        results.append(total)
    return results
```

WeChat: cstutorcs

```
def cumulative_v2(presorted_nums):
    results = deque()
    total = 0
    for x in presorted_nums:
        total += x
        results.append(total)
    return results
```

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

6. (T/F) replacing `results.append(total)` with `results.insert(0, total)` in the first function would make the code more efficient.

QQ: 749389476

A. True    B. False

<https://tutorcs.com>

7. What is the time complexity of `cumulative_v1`?

A.  $O(1)$     B.  $O(\log N)$     C.  $O(N)$     D.  $O(N \log N)$     E.  $O(N^2)$

8. What is the time complexity of `cumulative_v2`?

A.  $O(1)$     B.  $O(\log N)$     C.  $O(N)$     D.  $O(N \log N)$     E.  $O(N^2)$

9. Which orders of growth are equivalent to  $O(2 * N^2)$ ?

A.  $O(2 * N^3)$     B.  $O(3 * N^2)$     C. all of the above    D. none of the above

10. A loop that iterates 100 times, each time printing the **length** of a list that contains  $N$  elements (and doing nothing else) has what complexity?

A.  $O(1)$     B.  $O(\log N)$     C.  $O(N)$     D.  $O(N \log N)$     E.  $O(N^2)$

## Web

程序代写代做 CS编程辅导

```
from flask import Flask, request
app = Flask(__name__)
```

```
@app.route("/a.html")
def b():
    with open("a.html") as f:
        return f.read()
```



```
@app.route("/b.html")
def a():
    q = "<html><body>{}</body></html>".format("B" + "e"*10)
    return q
```

WeChat: cstutorcs

```
@app.route("/c.html")
def c():
    mult = int(request.args.get("mult", "1"))
    return "ha" * mult
```

Assignment Project Exam Help

```
if __name__ == "__main__":
    app.run(host="127.0.0.1")
```

Email: tutorcs@163.com

11. Which function runs when “http://localhost/a.html” is visited? Careful, trick question!

QQ: 749389476

A. a()    B. b()    C. c()

12. Which page is static?

https://tutorcs.com

A. a.html    B. b.html    C. c.html

13. Which page uses a query string?

A. a.html    B. b.html    C. c.html

14. @app.route("/a.html") is an example of a(n):

A. attributer    B. decorator    C. firewall    D. IP address    E. POST request

15. (T/F) The following will find at least one match:

```
re.findall(r"^\d\d", "K9")
```


A. True    B. False

## Graphs

Assume the following search method is in a Node class. Assume the method is correct, with self.name referring to the node's name (e.g., "1", "2", etc.). Assume self.graph is a graph object (not shown) and self.children is a list of child nodes.

```
def search(self, dst):
    if self.name == dst:
        return [self.name]
    if self.name in self.visited:
        return None
    self.graph[self.name].visited.add(self.name)

    if self.name == dst:
        return [self.name, ]
    for child in self.children:
        childpath = child.search(dst)
        if childpath:
            return [self.name, ] + childpath
    return None
```



16. (T/F) The search method is an example of depth-first search.

A. True B. False

17. What is the graph an example of? Choose the most informative answer.

A. directed graph B. DAG C. tree D. BST

18. What is the shortest path from node 9 to node 1?

A. 9,1 B. 9,2,1 C. 9,2,5,1 D. 9,10,3,5,1

19. If node4 refers to the node with name "4", which of the following nodes will be checked last by node4.search("11")? By "checked", we mean this part: self.name == dst. Hint: node "6" will be visited before node "8".

A. 2 B. 3 C. 5 D. 9 E. 10

20. If search were modified, what kind of coding mistake could cause a stack overflow?

A. not adding nodes to visited  
B. iterating over node children in reverse order  
C. deleting the line that makes the recursive call to search  
D. changing all the returns to return None

## Object Oriented Programming

程序代写代做 CS编程辅导

```
class Vehicle:
    def honk(self, mult=1):
        print("beep")

class Bus(Vehicle):
    def __init__(self, capacity):
        self.capacity = capacity
        self.filled = 0

    def board(self, passengers):
        passengers = min(passengers, self.capacity-self.filled)
        self.filled += passengers
        return passengers
```



WeChat: cstutorcs

```
class Car:
    pass
```

Assignment Project Exam Help

```
v = Vehicle()
b1 = Bus(32)
b2 = Bus(32)
c = Car()
b1.board(30)
result = b2.board(4)
```

Email: tutorcs@163.com

QQ: 749389476

21. Which call will fail?

- A. b1.honk()   B. b2.honk(3)   C. c.honk(3)   D. v.honk(3)

<https://tutorcs.com>

22. What will result be?

- A. 0   B. 2   C. 4   D. 32   E. 64

23. What special method does `print` prefer to use, if available?

- A. `__init__`   B. `__repr__`   C. `__str__`

24. In this code, `self` is the name of a(n):


- A. attribute   B. class   C. constructor   D. receiver parameter

25. (T/F) Calling `b2.capacity()` will return 32.

- A. True   B. False

## Reproducibility

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

26. (T/F) The current state is in “headless” mode.

A. True B. False

27. Which command will create a new commit with changes from both C5 and C3?

A. add B. commit C. merge D. branch E. checkout

28. What does `time.time()` return?

- A. `datetime` object representing current time
- B. milliseconds to run entire program
- C. milliseconds since 1950
- D. seconds since 1970
- E. seconds to run the prior piece of code

29. What type does `subprocess.check_output(...)` return by default?

A. bool B. bytes C. list D. process

30. What is a running program is called?

A. binary B. executable C. jogger D. port E. process



---

Congrats on finishing the first CS 320 exam anybody has ever taken!

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

---

(Blank Page: you may tear this off for scratch work, but hand it in with your exam)

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>