



程序代写代做 CS编程辅导

Lecture 12

Control Flow III



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

**How to
Avoid
Spaghetti
Code?**



Last Time: if-else



程序代写代做 CS编程辅导

Task:

1. Create an array in RAM with values {1, 1, 2, 3, 5, 8, 13, 21}
2. Define two variables, `even_sum` and `odd_sum` in RAM
3. Loop through the array and calculate the sum of even and odd numbers



This is an if-else problem

WeChat: [cstutorcs](#)

How do we check if a number is even?

Assignment Project Exam Help

```
if (element x is even)
```

```
{
```

```
    even_sum += x;
```

```
}
```

```
else
```

```
{
```

```
    odd_sum += x;
```

```
}
```

```
...
```

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

```
bit_w #BIT0, x
```

If `BIT0` is set (i.e., 1) then the carry bit in SR will be set

```
jc / jnc
```

How to implement if-else?



程序代写代做 CS编程辅导

Better to change the order of the blocks



```
if (x is even)
    even_sum += x;
else
    odd_sum += x;
}
```

WeChat: cstutorcs

Assignment Project Exam Help



Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

NOT
good

better



Good Implementation of if-else



程序代写代做 CS编程辅导



Definitions

```
.data
    .retain
    .retainrefs
```

```
even_sum: .word    0
odd_sum:  .word    0
```

```
array:    .word    1, 1, 2, 3, 5,
LENGTH:   .set     16
```

LENGTH of array in bytes

```
.text
;-----
; Main loop here
;-----
        clr.w    R4                ; R4 serves as index, start at 0
        ; indices are 0, 1, 2, ..., LENGTH - 2
read:    mov.w    array(R4), R5     ; read array(R4)
        bit.w    #BIT0, R5         ; check least significant bit
        jz       odd              ; carry set if bit is 1, i.e., odd number
even:    add.w    R5, even_sum      ; we are here if array(R4) is even
        jmp     proceed           ; proceed index to next element
odd:     add.w    R5, odd_sum       ; we are here if array(R4) is odd

proceed: incd.w    R4                ; index points to next element
        cmp.w    #LENGTH, R4       ; check array boundary
        jlo      read              ; break if LENGTH > index

main:    jmp      main
        nop
```

Code

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Not so Good Implementation



程序代写代做 CS编程辅导

```
.data
    .retain
    .retainrefs
```

```
even_sum: .word 0
odd_sum:  .word 0
```

```
array:    .word 1, 1, 2, 3, 5,
LENGTH:  .set 16
```



LENGTH of array in bytes

```
.text
```

```
-----
; Main loop here
-----
        clr.w   R4                ; R4 serves as index, start at 0
; indices are 0, 2, ..., LENGTH - 2
read:    mov.w   array(R4), R5     ; read array(R4)
        bit.w   #BIT0, R5         ; check least significant bit
        jnc     even             ; Carry set if bit is 1, i.e., odd number
        jmp     odd
even:    add.w   R5, even_sum      ; we are here if array(R4) is even
        jmp     proceed          ; proceed index to next element
odd:     add.w   R5, odd_sum       ; we are here if array(R4) is odd

proceed: incd.w   R4              ; index points to next element
        cmp.w   #LENGTH, R4      ; check array boundary
        jlo     read             ; break if LENGTH > index

main:    jmp     main
        nop
```

NOT
good



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A Library of Coding Primitives



程序代写代做 CS编程辅导

Array operations that are widely used in real-life MCU applications



Usually single instruction level language: `mean(array)` in MATLAB
but we need to write several lines of code in assembly

or

`MAD = mean(abs(array-mean(array)))` in MATLAB in assembly Midterm 1

WeChat: cstutorcs

Assignment Project Exam Help

Also:

`min(array)`

`max(array)`

`flip(array)` or `array.reverse()`

even

multiplication

division by a power of two

Email: tutorcs@163.com

Today

QQ: 749389476

<https://tutorcs.com>

Starting next week

Minimum in an Array



程序代写代做 CS编程辅导

How do we find the minimum element in an array?

One possibility is



```
min_value = array[0]
for (ii = 1; ii < length; ii++) {
    if array[ii] < min_value
        min_value = array[ii];
}
```

Can be done easily
in assembly too!

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

However, things get more complicated when we distinguish between different types of elements; e.g. smallest nonnegative element, smallest even number etc.

QQ: 749389476

Then

<https://tutorcs.com>

```
min_value = first even element in array
```

Not difficult
but code gets messy

Minimum in an Array



程序代写代做 CS编程辅导

How do we find the minimum element in an array?

There is a universal initial min-value that results in the same exact steps of execution as pre



```
min_value = infinity;  
for (ii = 0; ii < length; ii++) {  
    if array[ii] < min_value  
        min_value = array[ii];  
}
```

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

What is `infinity`?

The largest possible value for the type we use
e.g. signed 16-bit integer, unsigned 16-bit integer etc.

$0x7FFF = 32,767_{10}$ $0xFFFF = 65,535_{10}$
<https://tutorcs.com>

With this approach we no longer need to find the first even element in the array



Maximum in an Array

程序代写代做 CS编程辅导

How do we find the maximum element in an array?

```
max_value = -infinity
for (ii = 0; ii < 10; ii++) {
    if array[ii] > max_value
        max_value = array[ii];
}
```



WeChat: cstutorcs

Assignment Project Exam Help

where `-infinity` is the **smallest possible value** for the type we are using

Email: tutorcs@163.com

e.g., signed 16-bit integer, unsigned 16-bit integer etc.

QQ: 749389476

$0x8000 = -32,768_{10}$

0

<https://tutorcs.com>

Both Min and Max in an Array



程序代写代做 CS编程辅导

How do we find the minimum and maximum simultaneously?

and efficiently

```
min_value = infinit
max_value = -infini
for (ii = 0; ii < length; ii++) {
    if array[ii] < min_value
        min_value = array[ii];
    if array[ii] > max_value
        max_value = array[ii];
}
```



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Can we do any better?
i.e., reduce number of
comparisons?

If length of array is n ,
 $\Rightarrow 2n$ comparisons

We can do $3n/2$ comparisons:

Compare two elements in the array ...

... compare the larger with max_value

... compare the smaller with min_value

3 comparisons for 2 elements

Today's Coding Task



程序代写代做 CS编程辅导

Task: Given an array of ten signed integers, find the min. nonnegative value

Define word `min_posit` AM

Create following array in I



array: `.word -37, 101, -59, -47, 23, 11, 79, -131, -5, 163`

WeChat: [cstutorcs](#)

Easy in a high level language once we have a loop that finds the minimum

Assignment Project Exam Help

```
min_value = infinity;
```

```
for (ii = 0; ii < length; ii++) {
```

```
    if (array[ii] < min_value) && (array[ii] >= 0)
```

```
        min_value = array[ii];
```

```
}
```

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

where && = AND

How do we do compound conditionals in assembly?

if (cond1 && cond2)



程序代写代做 CS编程辅导

Task: If x is divisible by 4, divide it by 4

Naïve and literal
implementation

When is a number divisible

When its last two bits are both 0



```
if ( (BIT0 of x is 0)
    && (BIT1 of x is 0) )
{
    x = x/4;
}
...
```


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



`if (cond1 && cond2)`



程序代写代做 CS编程辅导

Task: If x is divisible by 4, divide it by 4

When is a number divisible by 4?

When its last two bits are both 0



```
if ( (BIT0 of x is 0)
    && (BIT1 of x is 0) )
{
    x = x/4;
}
...
```

WeChat: [cstutorcs](#)


Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Negation to the rescue



`if (cond1 || cond2)`



程序代写代做 CS编程辅导

Task: Count the numbers in an array that are NOT divisible by 4

When is a number NOT divisible by 4?

When one of its last two bits are 1



WeChat: [cstutorcs](#)

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

`||` = OR

```
if ( (BIT0 of x is 1)
    || (BIT1 of x is 1) )
{
    count++;
}
...
```



Wait a Second




程序代写代做 CS编程辅导

In both cases we have checked the same condition: divisibility by 4

`if (BIT0==1 || BIT1==1)`



`if (BIT0==0 && BIT1==0)`




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



How to check divisibility by 4?



程序代写代做 CS编程辅导

How do you check if a number is not divisible by 4?

`if (BIT0==1 || BIT1=` or `if ~(BIT0==0 && BIT1==0)`



Neither!

`bit.w #BIT1|BIT0,`

WeChat: cstutorcs Bitwise OR

Assignment Project Exam Help

The carry bit is set when either bit is set, i.e., the number is not divisible by 4

Email: tutorcs@163.com

Moral of the day:

QQ: 749389476

- There are no compound conditionals in assembly, use your logic
- Before starting implementing in assembly, check if you can simplify your logic
- Before solving a given problem, check if there is a simpler solution


<https://tutorcs.com>

Today's Coding Task



程序代写代做 CS编程辅导

Task: Given an array of ten signed integers, find the min. nonnegative value



WeChat: cstutorcs

How do we solve this? The questions already suggests a way:

Assignment Project Exam Help

- Loop through the array
- If current element is negative, skip to next element
- If current element is not negative, check whether it is the minimum
- Stop if done with all elements

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

One Solution



程序代写代做 CS编程辅导

```
.data
min_pos: .space 2

.text
; Assemble into program memory.
; Override ELF conditional linking
; And retain any sections that have
.retain
.retainrefs

array: .word -37, 17, 23, 11, 79, -131, -5, 163
;-----
RESET    mov.w    #__STACK_END,SP      ; Initialize stackpointer
StopWDT  mov.w    #WDTPW|WDTHOLD,&WDTCTL ; Stop watchdog timer
;-----
; Main loop here
;-----
    mov.w    #0x7FFF, min_pos ; min_pos = 0x7FFF (max 16-bit signed #)
    clr.w    R4

read_next: tst.w    array(R4)
            jn      proceed      ; skip if negative

non_neg:   cmp.w    array(R4), min_pos ; if min_pos - array(R4) > 0 replace
            jlo     proceed

            mov.w    array(R4), min_pos

proceed:   incd.w   R4
            cmp.w    #2*10, R4      ; check for end of array
            jlo     read_next      ; break if R4==20

main:     jmp      main
            nop
```

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>