ECE 2560 Introduction to Microcontroller-Based Systems



程序代写代做 CS编程辅导

Lecture 18



Agenda for the class: cstutorcs

Prep for the Project

Doing Real-World Math With the MCU Help

Q-Format Numbersil: tutorcs@163.com

CCS Tools: Load Memory & Graph

In class coding demo

https://tutorcs.com

Last Time: Stack Frames



程序代写代做 CS编程辅导

The subroutine contract specifies the structure of the stack frame

e.g., a stack frame with type lues and one output value

Caller pushes input_1, then input_2

subroutine will see when it is first called

WeChat: With the subroutine call PC is placed cstutorcs onto the stack

0(SP) saved PC 2(SP) output 4(SP) input_2 6(SP) input_1

Assignation Project Exam Help

reads input_1 and input_2

Email: tutorcs@163 comites output into the

OO: 749389476

ret removes PC from stack

https://addecs.com

- reads output from stack frame
- cleans up the rest of the stack

Temporary Variables on Stack



程序代写代做 CS编程辅导

We can also create a similar structure in stack without calling a subroutine

⇒ Dynamic data allocat

e.g., copy of an array with

 $ts x = \{x(0), x(2), x(4), x(6)\}$

WeChat: cstutorcs

Assignment Project Exam4Help

incd.w R4

Email: tutorcs 163.co 184, R4

- SP jne rep

QQ: 749389476

https://tutorcs.com

add.w #8, SP

release memory on stack after use!!

6(SP) x(0)

x(6)

x(4)

x(2)

0(SP)

2 (SP)

4 (SP)

Project




程序代与代做 CS编程辅导

(Tentative) Task: You will be given some information buried in noise and you

will recover it

Will use sin(x) and cos(x)



Find a way of dealing with fractional numbers in code and CCS

Load data into memor which to the provided in a file

Plot the graph of sin(x), cos(x), data points

Assignment Project Exam Help

Project the data points to sin(x) and cos(x) to find the buried information

Email: tutorcs@163.com

You will write two subroutines:

Inner product

QQ: 749389476

Signed multiplication https://tutorcs.com

These can use the subroutines we have already developed: e.g., x times y

Fixed-Point Rational Numbers



程序代写代做 CS编程辅导

There is only so much math we can do with integers only

We cannot even properly proper

We can write this number with integer and fractional part

$$110.11 = 4 + 2 + 1/2 + 1/4 = 6.75$$

 $1010.10 = 10.5$ WeChat: cstutorcs

0.01 = 0.25

11.00 = 3.00

Note: Demo only. Never find decimal values like this!

Assignment Project Exam Help

Email: tutorcs@163.com

All these numbers have 2 fractional bits after the radix point

- ⇒ Fixed-point representation with two fractional bits
- ⇒ Called Q2 format by Texassin/struments with Q Value 2

This is only how we interpret a binary sequence, HW does not care !!

Q Format



程序代写代做 CS编程辅导

What does Q Value mean?

Q Value alone is incompleted by the verto consider the number of bits too A 16-bit signed number with the property of the prop

$$0 \times 002B = 0000 \ 0000 \ 0010 \ 1011$$
 signed Q(14.2) number = $(10.75)_{10}$ 14 integer bits 2 fractional bits

Assignment Project Exam Help

imagine a radix point here Email: tutorcs@163.com

An 8-bit **signed** number with Q value 7 749389476

signed Q(1.7) number

```
0xF2 = 1111 0010 https://tutorcs.com
radix point 7 fractional bits Value here
```

Value in decimal? Complicated!

Q Format to Decimal Conversion



在厅代与代做 CS编程辅导

Good news: It is easy if you do it the easy way

Better news: You will ma o it for you (most of the time)

What is the easy way?

Do not attempt to add up place values – too complicated with (–)ve numbers Instead, divide the integer was the think ber by the correct power of two

Assignment Project Exam Help the Q value

An 8-bit signed number with Q value 7

Email: tutorcs@163.com

Integer value of 0xF2 is -14 QQ: 749389476 $0xF2 = 1111 \ 0010$ Shifting radix point 7 positions to the left radix point 7 fractional ttps://ht here

> \Rightarrow decimal value of 0xF2 in Q(1.7) format is -14/128 = -0.0546875


Q Format ↔ Decimal



程序代与代欧 CS 编程辅手

All you need is a Hex ↔ Decimal convertor and a calculator

Q value 0



signed!

46.0) the decimal value is -11832 / **2**º

-11832 / **2**²

-11832 / **2**⁸

WeChat. cstutores

-11832 / **2**¹⁵

If we want to convert from decimal to Q format Exam Help

Q value 15

We have to watch the range of numbers!!

e.g., Q(1.15) can represent maly inturboers @ 1663 range [-1, 1)

open

Once you fix the range, multiply by the **correct power of 2**

https://tutorcs.com

5.245 in Q(9.7): 5. 245 x
$$2\frac{7}{4}$$
 = 671.36 approx. 0×0.29 F

Q value 7

Q Format Arithmetic



程序代写代做 CS编程辅导

This is only how we interpret a binary sequence, HW does not care !!

Addition and subtractio 具体的

- Let the HW do add an the light to the light to the HW do add an the light to the light
- Just make sure to only subtract numbers in the same Q format corresponds to aligning the radix point when adding and subtracting WeChat: cstutorcs

Multiplication is easy too but watch the format change Assignment Project Exam Flelp

- Let the HW multiply
- Always watch for overflowail to trotats of rlots.com
- The Q values are added!! 749389476 same as decimal point placement in decimal multiplication

https://tutorcs.com

Multiplying a Q(1.7) number with a Q(2.5) number \Rightarrow Q(4.12) number

 $x / 2^{7}$

y / **2**⁵

xy / 212

Changing between Q Formats




程序代写代做 CS编程辅导

Decreasing the Q value without changing the encoded value

e.g., from Q(1.7) to Q(4.4 decreases from 7 to 4

0.1000000 = 0x80



both numbers encode decimal value 0.5

Shift the radix point 3 positions to the stigint and divide by 27-4 = 23

Assignment Project Exam Help

Increasing the Q Value

e.g., from Q(8.0) to Q(4.4 Emailalut orcreases iron to 4

$$0000001. = 0x01$$

$$00000001. = 0x01$$
 $\stackrel{QQ:}{=} 749389476 = 0x10$

both numbers encode decimal value 1.0

https://tutorcs.com

Shift the radix point 4 positions to the left = multiply by 24

Motivation




程序代写代做 CS编程辅导

Why do we need all this?

Because there is so much integers e.g., sin(x) produces num range [- 1, 1] without fractions the respective, only a square wave!

For the project we will use sm(x) at another s



properly!

ECE 2560 Introduction to Microcontroller-Based Systems – Irem Eryilmaz

Importing Data into the MCU



程序代写代做 CS编程辅导

CCS enables importing external data into the RAM/FRAM of the MCU Several file formats are significant we will use TI Data format

```
1. Trting
                                 length in
                                  words
        number
                       (hex)
                                   (hex)
               WeChat: cstutorøs
                   ignment Project Exam Help
header line
               Email: tutorcs@163.com
 one data
                    749389476
  sample
  per line
                     //tutorcs.com
```

Importing Data into the MCU



Disassembly | Memory Browser X

Find and Replace

Copy To Clipboard

Copy To Memory

Load Memory.

Save Memory...

Configure...

0x4400 <Memory Rendering 26> X

0x004400

0x004410

0x004420 0x004430

0x004440

0x004450

0x004470


0x004490


0x0044A0

程序代写代做 CS编程辅导

You can import data only during an active debug session

Find "Load Memory" unde





Browse for the file you want to it plots of the 1 boad We mory" dialogue




Configuring the Q Format




程序代写代做 CS编程辅导


You will see the values in the file populate the MCU memory

Choose "16-bit Signed In right click on the memory browser to access the "Configure" or



associated with the data
WeChat: cstutorcs






Graphing



程序代写代做 CS编程辅导

You can graph only during an active debug session

Find "Graph >> Single Tir the Tools Tab



Graphing



程序代写代做 CS编程辅导

CCS will graph the values in the specified memory locations

Double check axes and verification by a result of the same of the

