

# ECS713: Functional Programming

## week 9: Monadic Programming

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Week 9

## Monadic Programming

### Monadic Programming: Functor, Applicative, Monad

- Assignment Project Exam Help  
<https://tutorcs.com>  
WeChat: cstutorcs
- understand the role played by these three fundamental type classes: Functor, Applicative and Monad
  - make a given data type an instance of these classes in a reasonable way

### Monadic Programming: Monads

- understand the the different monad operations
- give examples of monads

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Functor

```
Prelude> :t map
```

```
map :: (a -> b) -> [a] -> [b]
```

```
class Functor f where
```

```
fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help


<https://tutorcs.com>

WeChat: cstutorcs

- map converts a function  $(a \rightarrow b)$  into a function  $([a] \rightarrow [b])$
- fmap converts a function  $(a \rightarrow b)$  into a function  $(f\ a \rightarrow f\ b)$ , where  $f$  is a suitable type constructor
- fmap is like map, but for more general types

```
Prelude> :t map
```


```
map :: (a -> b) -> [a] -> [b]
```



**[1,2,3,4]**

```
Prelude> :t map
```


```
map :: (a -> b) -> [a] -> [b]
```



**map (^2) [1,2,3,4]**

```
Prelude> :t map
```

```
map :: (a -> b) -> [a] -> [b]
```



**map even [1,2,3,4]**

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cs\_tutorcs

- Other types also give a shaped container for a collection of values.
- For these types:  $\text{fmap } g :: fa \rightarrow fb$  keeps the shape and applies  $g$  to each of the values.



```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

```
data Btree a = Empty | Leaf a | Node (Btree a) (Btree a) a
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs


```
fmap g Empty = Empty
```

```
fmap g (Leaf a) = Leaf (g a)
```

```
fmap g (Node L R a) = Node (fmap g L) (fmap g R) (g a)
```

```
data BTree a = Empty | Leaf a | Node (BTree a) (BTree a) a

fmap g Empty = Empty
fmap g (Leaf a) = Leaf (g a)
fmap g (Node L R a) = Node (fmap g L) (fmap g R) (g a)
```




**Node (Node (Leaf 1) (Leaf 2) 3) (Leaf 4) 5**

```

data BTree a = Empty | Leaf a | Node (BTree a) (BTree a) a

fmap g Empty = Empty
fmap g (Leaf a) = Leaf (g a)
fmap g (Node L R a) = Node (fmap g L) (fmap g R) (g a)

```



**fmap (^2) (Node (Node (Leaf 1) (Leaf 2) 3) (Leaf 4) 5)**

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

```
data Btree a = Empty | Leaf a | Node (Btree a) (Btree a) a
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
fmap g Empty = Empty
```

```
fmap g (Leaf a) = Leaf (g a)
```

```
fmap g (Node L R a) = Node (fmap g L) (fmap g R) (g a)
```

# Other examples

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help

**Maybe a**  
<https://tutorcs.com>

WeChat: cstutorcs

```
data Maybe a = Nothing | Just a
```

```
fmap g Nothing = Nothing
```

```
fmap g (Just a) = Just (g a)
```

# Other examples

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help

**Either a b**

<https://tutorcs.com>

WeChat: cstutorcs

```
data Either a b = Left a | Right b
```

```
fmap g (Left a) = Left a
```

```
fmap g (Right b) = Right (g b)
```

# Other examples

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help

**Either a b**

<https://tutorcs.com>

WeChat: cstutorcs

```
data Either a b = Left a | Right b
```

```
fmap g (Left a) = Left (g a)
```

```
fmap g (Right b) = Right b
```

# Other examples

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help

(a,b)  
<https://tutorcs.com>

WeChat: cstutorcs

```
fmap g (a,b) = (a, g b)
```



# Other examples

Assignment Project Exam Help

- Records (whose fields are not functions)  
<https://tutorcs.com>  
WeChat: cstutorcs
- Datatypes that do not involve functions

# Different examples: functions

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help

**f = x -> ()**  
<https://tutorcs.com>

WeChat: cstutorcs

```
fmap :: (a -> b) -> (x -> a) -> (x -> b)  
fmap g h = g . h
```

# A non-example

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help

**f = () -> y**  
<https://tutorcs.com>

WeChat: cstutorcs

```
fmap :: (a -> b) -> (a -> y) -> (b -> y)  
fmap g h = ???
```

```
fmapr :: (a -> b) -> (b -> y) -> (a -> y)  
fmapr g h = h . g
```


# A hard example: continuations

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

Assignment Project Exam Help  
<https://tutorcs.com>  
WeChat: cstutorcs

```
fmap :: (a -> b) -> ((a -> x) -> x) -> ((b -> x) -> x)  
fmap g h = \k -> h $ k . g
```

# mapping pipelines



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



**We should not care about the build order**

$$\text{fmap } (h.g) = (\text{fmap } h).(\text{fmap } g)$$

# Summary

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- A **functor** is a type constructor that is mappable.
- We can apply the functor to a whole pipeline of functions.

Assignment Project Exam Help

# Applicative

<https://tutores.com>  
WeChat: cstutores

- Functors are fine for unary functions
- Suppose we have a binary function:

Assignment Project Exam Help

<https://tutores.com>

- $g :: a \rightarrow b \rightarrow c$

WeChat: cstutorcs

- Can we get a binary map:

- $\text{bmap } g :: f\ a \rightarrow f\ b \rightarrow f\ c$



# Applicative

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: estutorcs

- Functors are not strong enough to give us this binary map
- We need something called an **applicative**

# Applicative: v0

- Suppose  $f$  is a functor

- If we have  $g :: a \rightarrow b \rightarrow c$

- Then  $\text{uncurry } g :: (a,b) \rightarrow c$

<https://tutorcs.com>

- So  $\text{fmap } (\text{uncurry } g) :: f (a,b) \rightarrow f c$

WeChat: cstutorcs

- We need a  $p :: f a \rightarrow f b \rightarrow f (a,b)$

- Then  $\text{fmap } (\text{uncurry } g) . p :: f a \rightarrow f b \rightarrow f c$

# Applicative: v0 (lists)

- Suppose  $f$  is a functor

- If we have  $g :: a \rightarrow b \rightarrow c$

- Then  $\text{uncurry } g :: (a,b) \rightarrow c$

Assignment Project Exam Help

<https://tutorcs.com>

- So  $\text{fmap } (\text{uncurry } g) :: f (a,b) \rightarrow f c$

WeChat: cstutorcs

- We need a  $p :: [a] \rightarrow [b] \rightarrow [(a,b)]$

- Then  $\backslash as \rightarrow \text{fmap } (\text{uncurry } g) . p \text{ as} :: f a \rightarrow f b \rightarrow f c$

# Applicative: v0 (lists)

```
p :: [a] -> [b] -> [(a,b)]
-- p as bs = concat $ fmap (\a -> fmap (\b -> (a,b)) bs) as
p as bs = [(a,b) | a <- as, b <- bs]
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
*Main> p [1..4] [1,2]
[(1,1),(1,2),(2,1),(2,2),(3,1),(3,2),(4,1),(4,2)]
*Main>
```

# Applicative: v0 (lists)

```
p :: [a] -> [b] -> [(a,b)]
p as bs = concat $ fmap (\a -> fmap (\b -> (a,b)) bs) as
p as bs = [(a,b) | a<-as, b <- bs]
q as bs = concat $ fmap (\b -> fmap (\a -> (a,b)) as) bs
q as bs = [(a,b) | b <- bs, a <- as]
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
*Main> p [1..4] [1,2]
[(1,1),(1,2),(2,1),(2,2),(3,1),(3,2),(4,1),(4,2)]
*Main> q [1..4] [1,2]
[(1,1),(2,1),(3,1),(4,1),(1,2),(2,2),(3,2),(4,2)]
```

# Applicative: v0 (lists)

```
p :: [a] -> [b] -> [(a,b)]
```

```
p as bs = concat $ fmap (\a -> fmap (\b -> (a,b)) bs) as
```

```
bmap g = \as -> fmap (uncurry g) . p as
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
*Main> p [1..4] [1,2]
```

```
[(1,1),(1,2),(2,1),(2,2),(3,1),(3,2),(4,1),(4,2)]
```

```
*Main> bmap (-) [1..4] [1,2]
```

```
[0,-1,1,0,2,1,3,2]
```

# Applicative: v1

- Suppose  $f$  is a functor

- If we have  $g :: a \rightarrow b \rightarrow c$

- Then  $\text{fmap } g :: f\ a \rightarrow f\ (b \rightarrow c)$

WeChat: cstutorcs

- We need a  $(<*>) :: f\ (b \rightarrow c) \rightarrow f\ b \rightarrow f\ c$

- Then

$\backslash as\ bs \rightarrow \text{fmap } g\ as\ <*>\ bs :: f\ a \rightarrow f\ b \rightarrow fc$

# Applicative: v1 (lists)

```
fs <*> xs = [f x | f <- fs, x <- xs]
```

```
bmap1 g = \as bs -> fmap g as <*> bs
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
*Main> bmap (-) [1..4] [1,2]
```

```
[0,-1,1,0,2,1,3,2]
```

```
*Main> bmap1 (-) [1..4] [1,2]
```

```
[0,-1,1,0,2,1,3,2]
```



# Applicative -> Functor

- We want every Applicative to be a Functor.
- To make that happen we need another function:
  - $\text{pure} :: a \rightarrow f a$
- With that:
  - $\text{fmap } g \text{ xs} = \text{pure } g \text{ <^*> xs}$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Two versions of Applicative

- Type classes have certain required functions
- Sometimes some of the required functions can be defined in terms of others.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- For example:
  - in Eq, we have  $==$  and  $\neq$ , and either can be defined in terms of the other.
  - Eq has two minimal presentations, we can give either  $==$  or  $\neq$  and the other will be inferred.
- Applicative also has two minimal presentations

# The usual Applicative

```
class Functor f => Applicative f where
  {-# MINIMAL pure, ((<*>) | liftA2) #-}
  -- | Lift a value.
  pure :: a -> f a
  -- | Sequential application.
  (<*>) :: f (a -> b) -> f a -> f b
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# The less usual Applicative

```
class Functor f => Applicative f where
  {-# MINIMAL pure, ((<*>) | liftA2) #-}
  -- | Lift a value.
  pure :: a -> f a
  -- | Lift a binary function to actions.
  liftA2 :: (a -> b -> c) -> f a -> f b -> f c
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# The relation between them

```
class Functor f => Applicative f where
  {-# MINIMAL pure, ((<*>) | liftA2) #-}
  -- | Lift a value.
  pure :: a -> f a
  -- | Sequential application.
  (<*>) :: f (a -> b) -> f a -> f b
  -- | Lift a binary function to actions.
  liftA2 :: (a -> b -> c) -> f a -> f b -> f c
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
(<*>) fs as = liftA2 id fs as
```

```
liftA2 f x = (<*>) (fmap f x)
```

Assignment Project Exam Help  
<https://tutorcs.com>  
WeChat: cstutorcs

# Monads I

# Aims

- The use of monads to handle effects is one of the most distinctive and challenging features of Haskell.  
Assignment Project Exam Help  
<https://tutorcs.com>  
WeChat: cstutorcs
- But it also has lessons for other programming paradigms.
- In this presentation we set out the problem.

# Learning Objectives

Assignment Project Exam Help

- learn why Monads are a key construct for Haskell
- learn what Monads are and what they do

<https://tutorcs.com>

WeChat: cstutorcs



# Pure Functional Programming

- The basic idea of functional programming is that we construct pieces of data by applying functions to existing data.  
Assignment Project Exam Help  
<https://tutorcs.com>
- We don't change data, we produce new data instead.  
WeChat: cstutorcs
- The Haskell type systems tells us what we need to know about plug compatibility: it tells us what functions we can apply to which data.

```
*Main Lib> :t words  
words :: String -> [String]
```

Assignment Project Exam Help

- The function words takes a String as input and produces a list of Strings.
- It is a pure function, it has no side effects.



# Effects

- Some functions are not pure, they have effects.
- Examples:
  - they carry out **IO**
  - they can produce an **exception**
  - they produce something alongside the return value
  - they are **non-deterministic**
  - they make use of a **State**

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Haskell and Effects

- Haskell documents this through its type system:
- Examples:
  - they carry out IO: use the IO type constructor: **IO a**  
Assignment Project Exam Help
  - they can produce an exception: use **Either Exception a** to allow the return of the exception as a value:  
<https://tutorcs.com>  
WeChat: cstutorcs
  - they produce something alongside the return value: return a tuple containing the something alongside the return value: **(Something, a)**
  - they are non-deterministic: return the (lazy) list of possible return values: **[a]**
  - they make use of a State: pass the state explicitly as input (if just reading the State) and as both input and output (if changing it): **State -> (State,a)**

# Example

- Let's suppose we want to take the logarithm of the head of a list of numbers.

```
Prelude> :t log $ head xs
log $ head xs :: (Floating a, Enum a) => a
Prelude>
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- We can just pipe the list through the functions head and log
- But:

```
Prelude> head []
*** Exception: Prelude.head: empty list
Prelude> log (-2)
NaN
```

# Use Either to allow return of an Exception

```
safeHead [] = Left "exception: head []"  
safeHead (x:xs) = Right x
```

```
safeLog x | x <= 0 = Left "exception: log of negative"  
          | otherwise = Right $ log x
```

Assignment Project Exam Help


<https://tutorcs.com>

WeChat: cstutorcs

# But now: a broken pipeline



```
safeHead [] = Left "exception: head []"  
safeHead (x:xs) = Right x  
safeLog x | x <= 0 = Left "exception: log of negative"  
           | otherwise = Right $ log x
```



# But now: a broken pipeline

```
safeLog $ safeHead [1..4]
```

```
<interactive>:1:1: error:
```

- Non type-variable argument in the constraint: Floating (Either String b) (Use FlexibleContexts to permit this)

- When checking the inferred type


```
it :: forall b. (Ord b, Floating (Either String b), Enum b, Num b) =>  
Either String (Either String b)
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: estutores

```
| otherwise = Right $ log x
```





# Typeclasses and higher-order functions to the rescue

**Problem:** We need a way of applying a function of type (in this instance):  $\text{Float} \rightarrow \text{Either String Float}$  to a value of type:  $\text{Either String Float}$ .

**Analogy:** Haskell has higher-order functions, and one of these is ordinary application:  $(\$) :: (a \rightarrow b) \rightarrow a \rightarrow b$

Assignment Project Exam Help

**Solution:** Following that model we just need to equip  $\text{Either}$  with a strange application function:

<https://tutorcs.com>

WeChat: cstutorcs

$(>>=) :: \text{Either String Float} \rightarrow (\text{String} \rightarrow \text{Either String Float}) \rightarrow \text{Either String Float}$

or more generally:

$(>>=) :: \text{Either String a} \rightarrow (a \rightarrow \text{Either String b}) \rightarrow \text{Either String b}$

- Read this as value feeding into function, so we are finding a way to feed a value of type  $\text{Either String a}$  into a function that expects a value of type  $a$ . This function is called **bind**.

# Typeclasses and higher-order functions to the rescue

$(>>=) :: \text{Either String } a \rightarrow (a \rightarrow \text{Either String } b) \rightarrow \text{Either String } b$

- Read this as value feeding into function, so we are finding a way to feed a value of type `Either String a` into a function that expects a value of type `a`.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
(>>=) :: Either String a -> (a -> Either String b) -> Either String b
(>>=) (Left s) f = Left s
(>>=) (Right a) f = f a
```

- So in  $(e >>= f)$ , if the evaluation of  $e$  produces an error, we get that, otherwise it terminates normally, and we just feed the value produced into  $f$ .

# Typeclasses and higher-order functions to the rescue

- We also (less obviously) need a way of converting a basic value of type `b` to something of type `Either String b`.
- This is the purpose of the `return` function.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
return :: b -> Either String b
return b = Right b
```

# Typeclasses and higher-order functions to the rescue

- So what we need is a typeclass that specifies types that have these functions.
- This is (in essence) the monad class.
- Below taken from Prelude.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
class Applicative m => Monad m where
  -- @
  (>>=)      :: forall a b. m a -> (a -> m b) -> m b

  -- | Inject a value into the monadic type.
  return     :: a -> m a
```

# Typeclasses and higher-order functions to the rescue

```
class Applicative m => Monad m where
  -- @
  (>>=)      :: forall a b. m a -> (a -> m b) -> m b

  -- | Inject a value into the monadic type.
  return     :: a -> m a
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
instance Monad Either a where
  (>>=) :: Either String a -> (a -> Either String b) -> Either String b
  (>>=) (Left s) f = Left s
  (>>=) (Right a) f = f a
  return :: b -> Either a b
  return b = Right b
```

# Summary

- In Haskell, effects are encapsulated in the return types of functions.
- Monads allow us to compose functions that may produce effects.  
Assignment Project Exam Help  
<https://tutorcs.com>  
WeChat: cstutorcs
- They are a type-class that contains two operations:
  - bind ( $>>=$ ) provides composition
  - return allows us to include the pure world in the effectful.

# ECS713: Functional Programming

## week 9: Monads and Effects

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Part 2: Example of computational effects as monads

# Aims

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutors

- To give some examples of monads and how they relate to computational effects.



# Learning Objectives

- Be familiar with the Haskell monads for:
  - exceptions (Either)
  - non-determinism (Lists)
  - logs (Pair)
  - state
  - IO

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Basic Idea

- In the pure world a function that takes input  $a$  and produces output  $b$  gets type  $a \rightarrow b$
- In the effectful world, a function that takes input  $a$  and produces output  $b$  gets type  $a \rightarrow m\ b$   
[Assignment Project Exam Help](https://tutorcs.com)  
<https://tutorcs.com>  
[WeChat: cstutorcs](#)
- Here,  $m$  is a type constructor, a monads, that encapsulates the effect.
- So  $a \rightarrow mb$  could be  $a \rightarrow IO\ b$ , if the function does IO
- Or it could be  $a \rightarrow (Either\ String\ b)$ , if the function produces an exception.
- IO and Either are both monads.

# Monads

```
class Applicative m => Monad m where
  -- @
  (>>=)      :: forall a b. m a -> (a -> m b) -> m b

  -- | Inject a value into the monadic type.
  return     :: a -> m a
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Exceptions

- A function that produces an exception can either:
  - return normally
  - or produce an exception
- This is modelled by a datatype that has two constructors:
  - Right: for normal values
  - Left: for exceptions

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Either

```
data Either a b = Left a | Right b
  deriving ( Eq, Ord, Read, Show )
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
instance Monad (Either a) where
  (>>=) :: Either a b -> (b -> Either a c) -> Either a c
  (>>=) (Left a) f = Left a
  (>>=) (Right b) f = f b
  return :: b -> Either a b
  return b = Right b
```

```
(>>=) :: Either String b -> (b -> Either String c) -> Either String c  
(>>=) (Left s) f = Left s  
(>>=) (Right b) f = f b
```

- In this monad
  - $e \gg= f$  works out as follows:
    - if  $e$  produces an exception:  $\text{Left}$  “whatever”, we get that as result.
    - otherwise it produces  $\text{Right } a$ , and we return  $(f a)$ , which can either be:
      - an exception:  $\text{Left}$  “another error”
      - or  $\text{Right } b$ .

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Either

Assignment Project Exam Help

<https://tutorcs.com>  
WeChat: cstutorcs

- The inclusion of pure values is just the function Right
  - `return = Right`

# Non-determinism: lists

- The standard way to model non-determinism is to produce the list of all possible results.
- Haskell is a lazy functional language, which means it will not compute more than necessary. Typically this might be the first element of this list.  
Assignment Project Exam Help  
<https://tutorcs.com>  
WeChat: cstutorcs
- So if you were writing a program to model coin-tossing,
  - the result of a single toss would be the list of all possible outcomes: [Head, Tail]
  - the result of two tosses would be [[Head,Head],[Head,Tail],[Tail,Head],[Tail,Tail]].



# List monad

```
instance Monad [a] where
  (>>=) :: [a] -> (a -> [b]) -> [b]
  (>>=) as f = concat $ map f $ as

return :: b -> [b]
return b = [b]
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- In this monad
  - a pure value is deterministic, and so has only one possible result.
  - return sends that value to the list that contains only that one element.
- $e \gg= f$  works out as follows:
  - e produces a list of possible results,
  - we apply f to each of those results to get a list of lists of possible answers
  - we concatenate all those possible answers together to get the final list of possibilities

# List monad

```
instance Monad [ ] where
  (>>=) :: [a] -> (a -> [b]) -> [b]
  (>>=) as f = concat $ map f $ as

  return :: b -> [b]
  return b = [b]
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
-- initial value: two possibilities
e = [1,2]
-- function, input produces 3 possibilities, all the same
f = replicate 3
```

```
map f e
[[1,1,1],[2,2,2]]
e >>= f
[1,1,1,2,2,2]
```

# Logs

- With exceptions we get either a value or an exception
- With logs we get both a value and a log.
- This means we model the result as the pair (log,value), and so as a member of the type (String, b).
- Or more accurately as a datatype that is isomorphic to this

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Logs

```
data Log a = Log String a
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
instance Monad Log where
```

```
(>>=) :: Log a -> (a -> Log b) -> Log b
```

```
(>>=) (Log s a) f = let (Log s' b) = f a in (Log (s++s') b)
```

```
return :: b -> Log b
```

```
return b = Log "" b
```

# State

- State is more complicated. Let's suppose we have a type `State`, representing the possible states we are interested in.
- If we have a function that uses and changes the State, then the data the function uses is its parameter and the initial State. The result it produces is the result of the function and the final changed State. So we model the function as having type:
  - $(\text{State}, a) \rightarrow (\text{State}, b)$
- But this does not fit the  $a \rightarrow m\ b$  pattern, so we curry it, switching the order of the parameters to:
  - $a \rightarrow \text{State} \rightarrow (\text{State}, b)$ .
- This does fit the  $a \rightarrow m\ b$  pattern with  $m\ b = \text{State} \rightarrow (\text{State}, b)$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# State

```
- type State s a = s -> (s,a)
data State s a = State (s -> (s,a))
```

```
instance Monad State s where
  (>>=) :: State s a -> (a -> State s b) -> State s b
  (>>=) (State f) g =
    State (\s ->
      let (s',b) = f s
          State h = g b
      in h s')

return :: a -> State s a
return a = State f where f s = (s,a)
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# IO

- IO is still more complex because we don't have any type expression that represents it.  
<https://tutorcs.com>  
WeChat: cstutorcs
- This means we can't implement bind and return in the same kind of way.
- But...

# IO

- We know that
- `return "a string" :: IO String`
- so `return` (part of the monad structure) is just `return` (part of the IO structure)

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



# IO

```
(>>=) :: IO a -> (a -> IO b) -> IO b
(>>=) e f = do
  x <- e
  f x
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- We can program up bind using this do block.
- Later we will see that we can use do blocks with any monad, and that this is always an equivalent of bind.

# Summary

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- We've now seen how five different types of effect can be implemented as monads.
- In each case bind and return make sense.

# ECS713: Functional Programming

## week 9: Monads and Effects

Assignment Project Exam Help

<https://tutorcs.com>

Part 3: Functors, Applicatives and Equations

WeChat: cstutorcs

# Aims

- To fill in some details about:
  - how Monads are built on other typeclasses
  - how to declare them in practice
  - what properties the operations bind and return must have.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Learning Objectives

- Be familiar with the typeclasses:
  - Functor
  - Applicative
  - and how they relate to Monads
- Know how to declare monads.
- Understand the equations needed for the Functor and Monad classes

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Monad is an extension

- The type class Monad is an extension of two other classes

- Functor

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- Applicative

- **This means every monad also has to be made an instance of these.**
- The declarations given in video 2 will not work because of this.

# Monad equations

Assignment Project Exam Help

- To work in the way we expect, [bind](https://tutorcs.com) and [return](https://tutorcs.com) must have certain properties.
- These are expressed as equations.

WeChat: cstutorcs

# Monad is an extension: Functor

Assignment Project Exam Help

- Functor is the typeclass of types that have a map function.
- Every Monad is also a Functor.

<https://tutorcs.com>

WeChat: cstutorcs



# Functor

- Functor is the typeclass of types with a “map” operation:

```
class Functor t where  
  fmap :: (a -> b) -> t a -> t b
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- Every Monad is also a Functor, with map defined as:

```
fmap f ta = ta >>= (return . f)
```

# Functor

- fmap is the functor equivalent of map
- Often, an element of type  $a$  is given by some shape (eg a list) that has entries tagged with elements of  $a$   
<https://tutorcs.com>  
WeChat: cstutorcs
- fmap leaves the shape the same but applies the function to each of the elements
- This is fine for unary functions, but there is no similar recipe for binary ones,  $a \rightarrow b \rightarrow c$  not just  $a \rightarrow b$ .

# Applicative

```
class Functor t => Applicative t where
  {-# MINIMAL pure, ((<*>) | liftA2) #-}
  pure :: a -> t a
  liftA2 :: (a -> b -> c) -> t a -> t b -> t c
  (<*>) :: t (a -> b) -> t a -> t b
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- liftA2 is the binary equivalent of fmap
- <\*> is a souped up version of unary fmap
- You only need one of these.

# $\langle * \rangle$ and liftA2 are equivalent

```
class Functor t => Applicative t where
  {-# MINIMAL pure, ((\langle * \rangle) | liftA2) #-}
  pure :: a -> t a
  liftA2 :: (a -> b -> c) -> t a -> t b -> t c
  (\langle * \rangle) :: t (a -> b) -> t a -> t b
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
-- does not use functor
(\langle * \rangle) = liftA2 id
-- uses functor
liftA2 f x y = (fmap f x) \langle * \rangle y = ((pure f) \langle * \rangle x) \langle * \rangle y
```

# Every Monad is an Applicative

```
class Functor t => Applicative t where
  {-# MINIMAL pure, ((<*>) | liftA2) #-}
  pure :: a -> t a
  liftA2 :: (a -> b -> c) -> t a -> t b -> t c
  (<*>) :: t (a -> b) -> t a -> t b
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
pure = return
liftA2 f x y = (x >>= (return . f)) >>= (\x1 -> y >>= (\x2 -> return (x1 x2)))
tf <*> ta = tf >>= (\x1 -> ta >>= (\x2 -> return (x1 x2)))
```

# Every Monad is an Applicative

```
class Functor t => Applicative t where
  {-# MINIMAL pure, ((<*>) | liftA2) #-}
  pure :: a -> t a
  liftA2 :: (a -> b -> c) -> t a -> t b -> t c
  (<*>) :: t (a -> b) -> t a -> t b
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
pure = return
```


```
liftA2 f tx ty = do
  x <- tx
  y <- ty
  return f x y
```

```
tf <*> ta = do
  f <- tf
  a <- ta
  return f a
```

# Equations

- Formally membership of a type class only requires that we implement functions of particular types.
- But they are often required to have particular properties.  
Assignment Project Exam Help  
<https://tutorcs.com>
- For example, in Ord,  $\leq$  is required to be an ordering, not an arbitrary function  $a \rightarrow a \rightarrow \text{Bool}$ .  
WeChat: cstutorcs
- In Functor, Applicative and Monad all require certain properties of their operations.
- These ensure that code behaves as expected.


# Functor equations



- `fmap` of the identity on `a` is the identity on `ta`  
`fmap id == id`
- we might compose `f` and `g` before or after applying `fmap`  
`fmap (g . f) == (fmap g) . (fmap f)`




# Monad equations




– binding into return does nothing  
 $mb \gg= \text{return} == mb$

# Monad equations



– return and bind is just function application  
 $\text{return } a \geq f = f \ a$

# Monad equations



- There are two ways to get from  $ma$  to  $mc$ .
- Apply successive binds
- Or use the monadic composite of  $f$  and  $g$ , and bind into it.
- They produce equal results.

$$(ma \gg= f) \gg= g == ma \gg= (\backslash a \rightarrow f a \gg= g)$$

# Example Declaration

```
data Log a = Log String a
```

```
instance Monad Log where
```

```
  return a = Log "" a
```

```
  (Log s a) >>= f = let (Log s' b) = f a in Log (s++s') b
```

Assignment Project Exam Help

– These two are necessary

<https://tutorcs.com>

```
instance Applicative Log where
```

WeChat: cstutorcs

```
  pure = return
```

```
  tf <*> ta = tf >>= (\x1 -> ta >>= (\x2 -> return (x1 x2)))
```

```
instance Functor Log where
```

```
  fmap f ta = ta >>= (return . f)
```

# Example Declaration

```
data Log a = Log String a
```

```
instance Monad Log where
```

```
  return a = Log "" a
```

```
  (Log s a) >>= f = let (Log s' b) = f a in Log (s++s') b
```

– These two are necessary

```
instance Applicative Log where
```

```
  pure = return
```

```
  tf <*> ta = do
```

```
    f <- tf
```

```
    a <- ta
```

```
    return (f a)
```

```
instance Functor Log where
```

```
  fmap f ta = do
```

```
    a <- ta
```

```
    return (f a)
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

# Summary

- Functor is the typeclass of types with a unary map operator.
- Applicative is the typeclass of types with a binary map operator.  
Assignment Project Exam Help  
<https://tutorcs.com>
- Monad extends both of these.  
WeChat: cstutorcs
- Bind and return have to satisfy equations.
- Monad declarations have to include boilerplate making the Monad into a Functor and an Applicative.