

程序代写代做 CS编程辅导

# FIT2014 Theory of Computation



Lecture 12

## Context-Free Grammars

WeChat: cstutorcs

Assignment Project Exam Help

slides by Graham Farr

based in part on previous slides by David Albrecht

Email: [tut@cs.monash.edu.au](mailto:tut@cs.monash.edu.au)

QQ: 749389476

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

<https://tutorcs.com>

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

# Overview

程序代写代做 CS编程辅导



- ▶ Inductive Definitions
- ▶ Context Free Grammars
- ▶ Parse Trees
- ▶ Derivations

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Arithmetic Expressions

程序代写代做 CS编程辅导



1. All integers are Arithmetic Expressions
2. If  $A$  and  $B$  are Arithmetic Expressions, so are:

- (i)  $A + B$
- (ii)  $A - B$
- (iii)  $A * B$
- (iv)  $A / B$
- (v)  $(A)$

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Production Rules

程序代写代做 CS编程辅导



$AE \rightarrow \text{integer}$

$AE \rightarrow AE + AE$

$AE \rightarrow AE - AE$

$AE \rightarrow AE * AE$

$AE \rightarrow AE / AE$

$AE \rightarrow (AE)$

WeChat: cstutorcs  
Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

$S \rightarrow A$

$A \rightarrow \text{integer}$

$A \rightarrow A + A$

$A \rightarrow A - A$

$A \rightarrow A * A$

$A \rightarrow A / A$

$A \rightarrow (A)$

# Backus-Naur Form (a.k.a. Backus Normal Form)

$S \rightarrow A$

$A \rightarrow \text{integer} \mid A + A \mid A - A \mid A / A \mid (A)$

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



John Backus (1924–2007)

<https://mathshistory.st-andrews.ac.uk/Biographies/Backus/>





Peter Naur (1928–2016)

<https://datamuseum.dk/>

Historical example: fragment of the BNF of ALGOL 60

#### 4.1. COMPOUND STATEMENTS AND BLOCKS

##### 4.1.1. Syntax

```
<unlabelled basic statement> ::= <assignment statement>|  
    <go to statement>|<any statement>|<procedure statement>  
<basic statement> ::= <unlabelled basic statement>|<label>:  
    <basic statement>  
<unconditional statement> ::= <basic statement>|<for statement>|  
    <compound statement>|<block>  
<statement> ::= <unconditional statement>|  
    <conditional statement>  
<compound tail> ::= <statement>, <compound tail>  
    <compound tail>  
<block head> ::= <begin declaration>|<block head> ;  
    <declaration>  
<unlabelled compound> ::= <begin> <compound tail>  
<unlabelled block> ::= <block head> ; <compound tail>  
<compound statement> ::= <unlabelled compound>|  
    <label>:<compound statement>  
<block> ::= <unlabelled block>|<label>:<block>
```

WeChat: cstutorcs  
Assignment Project Exam Help  
Email: tutors@163.com  
QQ: 749389476  
<https://tutorcs.com>

from: J. W. Backus *et al.*, *Comm. ACM* **3** (5) (May 1960) 299–314.

# EQUAL

程序代写代做 CS编程辅导



A string is in EQUAL if it has an equal number of a's and b's.

$\{\epsilon, ab, ba, aabb, abab, abba, baba, \dots\}$

Assignment Project Exam Help

An a-type string has one more a than b.

A b-type string has one more b than a.

QQ: 749389476

<https://tutorcs.com>

# EQUAL

A string is in EQUAL if it is

- ▶  $\varepsilon$ , or
- ▶  $a$  followed by a string of  $b$ -type
- ▶  $b$  followed by a string of  $a$ -type



A string is of  $a$ -type if it is

- ▶ just  $a$ , or
- ▶  $a$  followed by a string in EQUAL, or
- ▶  $b$  followed by two strings of  $a$ -type.

A string is of  $b$ -type if it is

- ▶ just  $b$ , or
- ▶  $b$  followed by a string in EQUAL, or
- ▶  $a$  followed by two strings of  $b$ -type.

$$S \longrightarrow \varepsilon$$

$$S \longrightarrow aB$$

$$S \longrightarrow bA$$

$$A \longrightarrow a$$

$$A \longrightarrow aS$$

$$A \longrightarrow bAA$$

$$B \longrightarrow b$$

$$B \longrightarrow bS$$

$$B \longrightarrow aBB$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorescs@163.com

QQ: 749389476

<https://tutorcs.com>



# Context Free Grammar (CFG)

程序代写代做 CS编程辅导

A Context Free Grammar consists of



1. An alphabet

▶ The letters are called terminals

2. Another set of symbols

▶ We call these symbols nonterminals

▶ often represented by upper-case letters.

▶ One of these symbols is the **Start symbol**.

▶ S is often used as the start symbol.

3. A finite set of **production rules** of the form:

One nonterminal  $\rightarrow$  finite string of terminals and/or nonterminals

QQ: 749389476

<https://tutorcs.com>

# Context Free Grammar (CFG)

程序代写代做 CS编程辅导



## Definition

The **language generated** by a Context Free Grammar (CFG) consists of those *strings of terminals* which can be produced from the start symbol using the production rules.

Assignment Project Exam Help

A language generated by a CFG is called a **Context Free Language (CFL)**.

QQ: 749389476

<https://tutorcs.com>

# EQUAL

Production rules:  
程序代写代做CS编程辅导



$S \rightarrow \varepsilon$

$S \rightarrow bA$

$S \rightarrow aB$

$A \rightarrow a$

$A \rightarrow aS$

$A \rightarrow bAA$

$B \rightarrow b$

$B \rightarrow bS$

$B \rightarrow aBB$

Terminals:  $a, b$

Nonterminals:  $S, A, B$

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

This CFG generates the language EQUAL.

# History

Pāṇini (c520BC–c460BC)

- ▶ studied *Sanskrit*

Noam Chomsky (b. 1928)

- ▶ studied *natural languages*

John Backus

- ▶ studied *programming languages*

程序代写代做 CS编程辅导



<https://mathshistory.st-andrews.ac.uk/Biographies/Panini/>

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



Noam Chomsky, during visit to Australia in 2011 to accept Sydney Peace Prize.  
<http://www.abc.net.au/news/2011-06-02/noam-chomsky/2741826>

$S \rightarrow aS \mid Sa \mid \varepsilon$

1.  $S \rightarrow Sa$
2.  $S \rightarrow aS$
3.  $S \rightarrow \varepsilon$

程序代写代做 CS编程辅导



on of aaaa

$S \Rightarrow Sa$  (Rule 1)  
WeChat: cstutorcs

$\Rightarrow aSa$  (Rule 2)

Assignment Project Exam Help

$\Rightarrow aaSa$  (Rule 2)


Email: tutorcs@163.com

$\Rightarrow aaSaa$  (Rule 1)

QQ: 749389476 (Rule 3)

$\Rightarrow aaaa$   
<https://tutorcs.com>

# Parse Tree



程序代写代做 CS编程辅导



on of aaaa

$S \Rightarrow Sa$  (Rule 1)

$\Rightarrow aSa$  (Rule 2)

Assignment Project Exam Help

$\Rightarrow aaSa$  (Rule 2)

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

$\Rightarrow aaSaa$  (Rule 1)

QQ: 749389476 (Rule 3)

$\Rightarrow aaaaa$   
<https://tutorcs.com>

# EQUAL

1.  $S \rightarrow \epsilon$
2.  $S \rightarrow bA$
3.  $S \rightarrow aB$
4.  $A \rightarrow a$
5.  $A \rightarrow aS$
6.  $A \rightarrow bAA$
7.  $B \rightarrow b$
8.  $B \rightarrow bS$
9.  $B \rightarrow aBB$

程序代写代做 CS编程辅导




Derivation of baaabbab

$S \Rightarrow bA$  (Rule 2)  
 $\Rightarrow baS$  (Rule 5)  
 $\Rightarrow baaB$  (Rule 3)  
 $\Rightarrow baaaBB$  (Rule 9)  
 $\Rightarrow baaaBb$  (Rule 7)  
 $\Rightarrow baaabSb$  (Rule 8)  
 $\Rightarrow baaabbAb$  (Rule 2)  
 $\Rightarrow baaabbab$  (Rule 4)

WeChat: cstutorcs  
Assignment Project Exam Help  
Email: [tutorcs@163.com](mailto:tutorcs@163.com)  
QQ: 749389476  
<https://tutorcs.com>

# Parse Tree



程序代写代做 CS编程辅导



Derivation of baaabbab

$S \Rightarrow bA$  (Rule 2)

$\Rightarrow baS$  (Rule 5)

$\Rightarrow baaB$  (Rule 3)

$\Rightarrow baaaBB$  (Rule 9)

$\Rightarrow baaaBb$  (Rule 7)

$\Rightarrow baaabSb$  (Rule 8)

$\Rightarrow baaabbAb$  (Rule 2)

$\Rightarrow baaabbab$  (Rule 4)

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



# PARENTHESES: the Dyck Language

PARENTHESES is the language over the two-letter alphabet  $\{ (, ) \}$  consisting of all strings of correctly matched parentheses.

PARENTHESES =  $\{ \epsilon, (), ()(), ()(()), (())(), (()()), ((())), \dots \}$ .

Non-members:  $()()$   $((((()$



Expressing PARENTHESES strings in terms of smaller PARENTHESES strings:

Any non-empty string of parentheses must start with  $($ . Where is its matching  $)$ ?

It could be at the other end:

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

( ..... )  
smaller PARENTHESES string

It could be before the other end:

( ..... ) ( ..... )  
smaller PARENTHESES string      smaller PARENTHESES string

# PARENTHESES: the Dyck Language

Inductive Definition

A **string of parentheses**  $S$  is defined inductively as follows:

- ▶ the empty string,  $\varepsilon$
- ▶  $(S')$ , where  $S'$  is a string of parentheses
- ▶  $S_1S_2$ , where  $S_1, S_2$  are strings of parentheses.

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



Context-Free Grammar

1.  $S \rightarrow \varepsilon$
2.  $S \rightarrow (S)$
3.  $S \rightarrow SS$


# PARENTHESES: the Dyck Language

1.  $S \rightarrow \epsilon$
2.  $S \rightarrow$
3.  $S \rightarrow$

程序代写代做 CS编程辅导



Derivation of  $()((()))$



WeChat: cstutorcs  $S \Rightarrow SS$  (Rule 3)

Assignment Project Exam Help  $\Rightarrow (S)S$  (Rule 2)

Email: tutorcs@163.com  $\Rightarrow (S)(S)$  (Rule 2)

QQ: 749389476  $\Rightarrow ()(S)$  (Rule 1)

$\Rightarrow ()((S))$  (Rule 2)

$\Rightarrow ()(())$  (Rule 1)

Walther von Dyck (1856–1934)


[https://mathshistory.st-andrews.](https://mathshistory.st-andrews.ac.uk/Biographies/Von_Dyck/)

[ac.uk/Biographies/Von\\_Dyck/](https://mathshistory.st-andrews.ac.uk/Biographies/Von_Dyck/)

# PARENTHESES: the Dyck Language

程序代写代做 CS编程辅导

Parse tree:



Derivation of  $() (())$

$S \Rightarrow SS$  (Rule 3)  
 $\Rightarrow (S)S$  (Rule 2)  
 $\Rightarrow (S)(S)$  (Rule 2)  
 $\Rightarrow ()(S)$  (Rule 1)  
 $\Rightarrow ()((S))$  (Rule 2)  
 $\Rightarrow ()(())$  (Rule 1)

WeChat: cstutorcs  
Assignment Project Exam Help  
Email: [tutorcs@163.com](mailto:tutorcs@163.com)  
QQ: 749389476  
<https://tutorcs.com>

# Exercises

程序代写代做 CS编程辅导



- ▶ Suppose we have two types of brackets, such as round and square:  $()$  and  $[]$ . Find a context-free language for the set of all valid strings of such brackets.

- ▶ Find a context-free grammar for PALINDROMES

Assignment Project Exam Help

- ▶ For other languages we have met:
  - ▶ find context-free grammars for them, OR
  - ▶ if you think they don't have one, think about why.

<https://tutorcs.com>

## A simple property of derivations

程序代写代做 CS编程辅导

At any stage, the string to the left of the first nonterminal must be a prefix of the final (derived) string.



$$\begin{aligned} S &\Rightarrow \dots \\ &\vdots \\ &\Rightarrow x_1 \dots x_k AB \dots \\ &\Rightarrow x_1 \dots x_k aXYB \dots \quad (\text{using } A \rightarrow aXY) \\ &\vdots \\ &\Rightarrow x_1 \dots \text{http://tutorcs.com} \quad (\text{derived string}) \end{aligned}$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

http://tutorcs.com

4 + 2\*3

程序代写代做 CS编程辅导

$$\begin{aligned} S &\rightarrow E \\ E &\rightarrow T + E \mid T - E \mid T \\ T &\rightarrow F * T \mid F / T \mid F \\ F &\rightarrow \text{integer} \mid (E) \end{aligned}$$




WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



Leftmost derivation:

$$\begin{aligned} S &\Rightarrow E \\ &\Rightarrow T + E \\ &\Rightarrow F + E \\ &\Rightarrow 4 + E \\ &\Rightarrow 4 + T \\ &\Rightarrow 4 + F * T \\ &\Rightarrow 4 + 2 * T \\ &\Rightarrow 4 + 2 * F \\ &\Rightarrow 4 + 2 * 3 \end{aligned}$$

4 + 2\*3

程序代写代做 CS编程辅导

$$\begin{aligned} S &\rightarrow E \\ E &\rightarrow T + E \mid T - E \mid T \\ T &\rightarrow F * T \mid F / T \mid F \\ F &\rightarrow \text{integer} \mid (E) \end{aligned}$$



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



**Rightmost** derivation:

$$\begin{aligned} S &\Rightarrow E \\ &\Rightarrow T + E \\ &\Rightarrow T + T \\ &\Rightarrow T + F * T \\ &\Rightarrow T + F * F \\ &\Rightarrow T + F * 3 \\ &\Rightarrow T + 2 * 3 \\ &\Rightarrow F + 2 * 3 \\ &\Rightarrow 4 + 2 * 3 \end{aligned}$$



# Leftmost and rightmost derivations

程序代写代做 CS编程辅导



In a **Leftmost derivation**, the leftmost non-terminal is always replaced first.

In a **Rightmost derivation**, the rightmost non-terminal is always replaced first.

**Theorem.**

WeChat: cstutorcs

Whenever a string has a derivation, it also has a leftmost derivation of the same length.

Assignment Project Exam Help

**Proof.** See Tute 4.

Email: tutorcs@163.com

Does the same hold for rightmost derivations?

QQ: 749389476

<https://tutorcs.com>

## A simple property of leftmost derivations

Whenever a production

$$X \longrightarrow \text{terminals} \text{ Non-terminal } theRest$$

is applied, the terminal letters of  $\text{terminals}$  are appended to the current prefix to give a larger prefix of the derived string

程序代写代做 CS编程辅导

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

https://tutorcs.com

$$\begin{aligned} S &\Rightarrow \dots \\ &\vdots \\ &\Rightarrow x_1 \dots x_k \text{ } \overbrace{A}^{\text{terminals}} B \dots \\ &\Rightarrow x_1 \dots x_k \text{ } \overbrace{aXY}^{\text{terminals}} B \dots \quad (\text{using } A \longrightarrow aXY) \\ &\vdots \\ &\Rightarrow x_1 \dots x_k a \dots \dots \dots \quad (\text{derived string}) \end{aligned}$$

# Revision

程序代写代做 CS编程辅导

- ▶ Context Free Grammars

- ▶ Definition. How to use



- ▶ Parse Trees

- ▶ Definition. How to make them.

WeChat: cstutorcs

- ▶ The Dyck language

Assignment Project Exam Help

- ▶ Leftmost and rightmost derivations.

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

Read:

Sipser, Ch. 2, pp. 101–108.

<https://tutorcs.com>