

程序代写代做 CS编程辅导

FIT2014 Theory of Computation



Lecture 16

Chomsky Normal Form, Cocke-Younger-Kasami algorithm

WeChat: cstutorcs

Assignment Project Exam Help

slides by Graham Farr

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

<https://tutorcs.com>

This material has been reproduced and communicated to you by or on behalf of Monash University  
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

# Overview

- ▶ Chomsky Normal Form
- ▶ Nullability
- ▶ CYK Parsing algorithm

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Chomsky Normal Form

程序代写代做 CS编程辅导



A CFG is said to be in **Chomsky Normal Form** if all the productions are in the form

Nonterminal  $\rightarrow$  Nonterminal Nonterminal

(called a **live production**)

or

WeChat: cstutorcs

Assignment Project Exam Help

Nonterminal  $\rightarrow$  terminal

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

(called a **dead production**).

QQ: 749389476

<https://tutorcs.com>

# Chomsky Normal Form

## Theorem.

For any context-free language  $L$ , the empty words in  $L$  can be generated by a grammar in Chomsky Normal Form.

程序代写代做 CS编程辅导



## Proof.

Outline:

WeChat: cstutorcs

Assignment Project Exam Help

1. Eliminate  $\varepsilon$ -productions. (i.e., production rules of the form  $X \rightarrow \varepsilon$ )
2. Eliminate unit productions. (i.e., production rules of the form  $X \rightarrow Y$ )
3. Give each terminal its own corresponding nonterminal that produces it.
4. Use these nonterminals to eliminate terminals, except where they appear alone.
5. Break down rules that produce at least three nonterminals, using new nonterminals, to give a set of rules producing just two nonterminals.

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389446

<https://tutorcs.com>

1. Eliminate all  $\varepsilon$ -productions.

For every production rule  $X \rightarrow \varepsilon$ :

For every other rule with  $X$  in the body (right-hand side):

Create new rules with all possible replacements of occurrences of  $X$  by  $\varepsilon$   
(and keep the old rule)

Remove the rule  $X \rightarrow \varepsilon$



For example:

old rules with $X$ in body	new rules
$A \rightarrow bXQ$	$A \rightarrow bXQ$ and $A \rightarrow bQ$
$A \rightarrow bXQX$	$A \rightarrow bXQX$ and $A \rightarrow bQX$
$A \rightarrow X$	$A \rightarrow X$ and $A \rightarrow \varepsilon$

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Chomsky Normal Form

Keep doing this until there are no more  $\epsilon$ -productions.

Once this step is complete: no  $\epsilon$ -productions with an empty right-hand side.



*Housekeeping:*

Suppose we have a nonterminal that *never* appears on the **left** of any rule.

(This situation may be created by our elimination of some  $\epsilon$ -productions.)

Then we can delete all rules where it appears on the **right**.

- ▶ If a rule has such a nonterminal on the **right**, then that nonterminal can never be replaced, so such a rule can never be used in any derivation of a string of terminals.
- ▶ This deletion is not strictly necessary for getting a valid CNF grammar. But it can yield a simpler result.

程序代写代做CS编程辅导

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutores@163.com

QQ: 749389476

<https://tutores.com>

# Chomsky Normal Form

2. Eliminate all unit productions

For every production rule  $X \rightarrow Y$ :

For every rule with  $Y$  on

Create a new rule with  $Y$  on the left instead of  $Y$  (& keep the old rule).

Remove the rule  $X \rightarrow Y$



For example:

old rules with  $Y$  on left

new rules

$Y \rightarrow abQR$

$Y \rightarrow abQR$  and

$X \rightarrow abQR$

$Y \rightarrow Q$

$Y \rightarrow Q$  and

$X \rightarrow Q$  (unless  $X \rightarrow Q$  has been dealt with previously)

$Y \rightarrow X$

$Y \rightarrow X$  and

$X \rightarrow X$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

https://tutorcs.com

# Chomsky Normal Form

程序代写代做 CS编程辅导

2. (*continued*)

Keep doing this until there are no unit productions.



*Once this step is complete:* every  $\alpha$ 's right-hand side is either

- ▶ a single terminal, or
- ▶ at least two symbols (terminals and/or nonterminals)

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



# Chomsky Normal Form

程序代写代做 CS编程辅导

3. Give each terminal its own corresponding nonterminal that produces it.

For each terminal  $z$ , create a nonterminal  $X_z$  and a new rule  $X_z \rightarrow z$ .

For example:

If our terminals are  $a, b$ , then create new nonterminals  $X_a, X_b$  and new rules

Assignment Project Exam Help

Email:  $X_a \rightarrow a$   
 $X_b \rightarrow b$   
tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



# Chomsky Normal Form

程序代写代做 CS编程辅导

4. In all rules that don't just have a single terminal, replace each terminal by its corresponding new nonterminal.



$Y \rightarrow abQR$  becomes  $Y \rightarrow X_a X_b QR$

WeChat: cstutorcs

Assignment Project Exam Help

Once this step is complete: every rule's right-hand side is either

- ▶ a single terminal, or
- ▶ at least two nonterminals.

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Chomsky Normal Form

5. For every rule with more than two nonterminals on the right, create new nonterminals as needed to replace the rule by a set of rules with just two nonterminals on the right.

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

Example:

old rule	new rules	
$Y \rightarrow Z_1 Z_2 Z_3$	$Y \rightarrow Z_{12} Z_3$	and
	$Z_{12} \rightarrow Z_1 Z_2$	and
$Y \rightarrow Z_1 Z_2 Z_3 Z_4$	$Y \rightarrow Z_{12} Z_{34}$	and
	$Z_{12} \rightarrow Z_1 Z_2$	and
	$Z_{34} \rightarrow Z_3 Z_4$	
$Y \rightarrow Z_1 Z_2 Z_3 Z_4 Z_5$	$Y \rightarrow Z_{1234} Z_5$	and
	$Z_{1234} \rightarrow Z_{12} Z_{34}$	and
	$Z_{12} \rightarrow Z_1 Z_2$	and
	$Z_{34} \rightarrow Z_3 Z_4$	

Once this step is complete:  
every rule's right-hand side is either

- ▶ a single terminal, or
- ▶ exactly two nonterminals.

... where  $Z_{12}, Z_{34}, Z_{1234}$  are new nonterminals.

$$\begin{aligned}
 S &\rightarrow bA \\
 S &\rightarrow aB \\
 A &\rightarrow a \\
 A &\rightarrow aS \\
 A &\rightarrow bAA \\
 B &\rightarrow b \\
 B &\rightarrow bS \\
 B &\rightarrow aBB
 \end{aligned}$$

Steps  
3 & 4

程序代写代做 CS编程辅导



WeChat: estutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{aligned}
 S &\rightarrow X_b A \\
 S &\rightarrow X_a B \\
 &\rightarrow a \\
 &\rightarrow X_a S \\
 A &\rightarrow X_b AA \\
 B &\rightarrow X_b S \\
 B &\rightarrow X_a BB \\
 X_a &\rightarrow a \\
 X_b &\rightarrow b
 \end{aligned}$$

Step 5

$$\begin{aligned}
 S &\rightarrow X_b A \\
 S &\rightarrow X_a B \\
 A &\rightarrow a \\
 A &\rightarrow X_a S \\
 A &\rightarrow YA \\
 B &\rightarrow b \\
 B &\rightarrow X_b S \\
 B &\rightarrow ZB \\
 X_a &\rightarrow a \\
 X_b &\rightarrow b \\
 Y &\rightarrow X_b A \\
 Z &\rightarrow X_a B
 \end{aligned}$$

# Consequences

程序代写代做 CS编程辅导

Cocke-Younger-Kasami (CYK) (today)



- ▶ Given a CFG and a string, decides whether or not the string can be generated by the CFG.
- ▶ polynomial time
- ▶ a bottom-up parsing algorithm

WeChat: cstutorcs

Assignment Project Exam Help

Pumping Lemma for CFG (next lecture)

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

- ▶ for proving that certain languages are not context-free.

QQ: 749389476

<https://tutorcs.com>

# Nullability

程序代写代做 CS编程辅导

Given a CFG, how to decide whether or not it generates the empty string?

A nonterminal  $A$  is **nullable** if the empty string can be derived from it:



$$A \Longrightarrow \dots \Longrightarrow \varepsilon.$$

WeChat: cstutorcs

Algorithm:

Assignment Project Exam Help

1. For every rule of the form  $X \rightarrow \varepsilon$ , mark  $X$  as nullable.

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

2. While there is a rule  $Y \rightarrow Y_1 Y_2 \dots Y_k$  that *only* produces nonterminals and all those nonterminals have been marked:

QQ: 749389476

▶ Mark  $Y$ .

<https://tutorcs.com>

3. If  $S$  has been marked, Accept, else Reject.

# CYK Algorithm

程序代写代做 CS编程辅导

For each CFG and string  $s$ , we can decide whether or not  $s$  is generated by the CFG.



Input:  $s = t_1 t_2 \dots t_n$ , where each  $t_i$  is a letter and  $n \geq 0$ .

WeChat: cstutorcs

If  $s = \varepsilon$  then use the Nullability algorithm.

Assignment Project Exam Help

*From now on,  $s$  is nonempty.*

Email: tutorcs@163.com

Find the Chomsky Normal Form for the non-empty words generated by the grammar.

QQ: 749389476

<https://tutorcs.com>

For each letter  $t_k$  find the nonterminals which can produce  $t_k$ .

# CYK Algorithm

程序代写代做 CS编程辅导



For each pair of consecutive letters  $t_i, t_{i+1}$  (where  $1 \leq i \leq n-1$ ), find the nonterminals that can generate the pair, as follows:

- For each pair  $X, Y$  such that


$X$  generates  $t_i$  and  $Y$  generates  $t_{i+1}$

find all  $W$  such that there is a rule  $W \rightarrow XY$ .

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>





# CYK Algorithm

程序代写代做 CS编程辅导

For each triple of consecutive letters  $t_i t_{i+1} t_{i+2}$ , find the nonterminals that can generate the triple, as follows:



- ▶ For each pair  $X, Y$  such that  $X \xRightarrow{*} t_i t_{i+1}$  and  $Y \xRightarrow{*} t_{i+1} t_{i+2}$ , find all  $W$  such that there is a rule  $W \rightarrow XY$ .

- ▶ For each pair  $X, Y$  such that  $X \xRightarrow{*} t_i$  and  $Y \xRightarrow{*} t_{i+1} t_{i+2}$ , find all  $W$  such that there is a rule  $W \rightarrow XY$ .



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

https://tutorcs.com



# CYK Algorithm

For each **quadruple** of consecutive letters  $t_i t_{i+1} t_{i+2} t_{i+3}$ ,  
find the nonterminals that can generate it:





WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Continue, in this way ...

Eventually, find all nonterminals that can produce  $s = t_1 t_2 \dots t_n$ .

If  $S$  is one of them,

then Accept, as  $s$  can be generated; otherwise, Reject, as  $s$  cannot be generated.

# CYK Algorithm

$$S \rightarrow aSa$$
$$S \rightarrow b$$

程序代写代做 CS编程辅导


$$S \rightarrow TA$$
$$S \rightarrow b$$
$$A \rightarrow a$$
$$T \rightarrow AS$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Input string: aabaa

Single  
letters

$$A \rightarrow a$$
$$S \rightarrow b$$

Pairs

$$?? \Rightarrow AA \Rightarrow aa$$
$$T \Rightarrow AS \Rightarrow ab$$
$$?? \Rightarrow SA \Rightarrow ba$$
$$?? \Rightarrow AA \Rightarrow aa$$

# CYK Algorithm

Triples

$?? \Rightarrow aa b$

$?? \Rightarrow AT \Rightarrow a ab$

$S \Rightarrow TA \Rightarrow ab a$

$?? \Rightarrow a ba$

$?? \Rightarrow ba a$

$?? \Rightarrow b aa$

4-tuples 程序代写代做 CS编程辅导 5-tuples



$aab a$

$aa ba$

$a aba$

$S \Rightarrow TA \Rightarrow aaba a$

$?? \Rightarrow aab aa$

$?? \Rightarrow aa baa$

$?? \Rightarrow a abaa$

??  $\Rightarrow SA \Rightarrow aba a$  WeChat: cstutorcs

$?? \Rightarrow ab aa$

Assignment Project Exam Help

$?? \Rightarrow a baa$

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

So  $S$  can generate  $aabaa$ , and we are done.

# CYK Algorithm

程序代写代做 CS编程辅导



## Exercises:

Write the algorithm more formally.

WeChat: cstutorcs

Prove by induction that the algorithm works.

Assignment Project Exam Help

Determine the complexity of the algorithm, in big-O notation.

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

# Revision

程序代写代做 CS编程辅导



- ▶ Know the uses of Chomsky Normal Form, and be able to convert a grammar to it.
- ▶ Avoid confusion between Chomsky Normal Form (CNF) and Conjunctive Normal Form (CNF)!
- ▶ Know and use the CYK algorithm.

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

Reading: Sipser, pp. 108–111. QQ: 749389476

<https://tutorcs.com>