

程序代写代做 CS编程辅导

FIT2014 Theory of Computation



Lecture 17

The Pumping Lemma for Context-Free Languages

WeChat: cstutorcs

Assignment Project Exam Help

slides by Graham Farr

Email: tutorcs@163.com

QQ: 749389476

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

<https://tutorcs.com>

This material has been reproduced and communicated to you by or on behalf of Monash University in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Overview

程序代写代做 CS编程辅导



- ▶ Pumping Lemma for CFLs
- ▶ Proof
- ▶ application:
showing that some languages
are *not* context-free

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

all languages

CFLs

regular
languages



Pumping Lemma for Regular Languages (paraphrased)

Recall:

程序代写代做 CS编程辅导

If a Finite Automaton
with N states
accepts



a sufficiently long string,
then the path taken by the string

WeChat: cstutorcs

in the FA
contains a repeated state.

Assignment Project Exam Help

Email: tutorcs@163.com

This enables us to “pump” the string

QQ: 749389476

by repeating one substring —
to generate an infinite family
of members of the language.

https://tutorcs.com

EQUAL

Parse tree for **bbbbaaaa**

1. $S \rightarrow \varepsilon$
2. $S \rightarrow bA$
3. $S \rightarrow aB$
4. $A \rightarrow a$
5. $A \rightarrow aS$
6. $A \rightarrow bAA$
7. $B \rightarrow b$
8. $B \rightarrow bS$
9. $B \rightarrow aBB$



程序代写代做 CS编程辅导


WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Nonterminal repetition in parse tree paths



$uvxyz$

程序代写代做 CS编程辅导



WeChat: cstutors

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>




uv^2xy^2z




uv^3xy^3z

Nonterminal repetition in parse tree paths



$uvxyz$

程序代写代做 CS编程辅导



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

uxz

Nonterminal repetition in parse tree paths

程序代写代做 CS编程辅导

Nonterminals: S, E, T, F

In a parse tree:

If



length of a root-to-leaf path $> \#$ nonterminals

then

some nonterminal appears twice on that path.


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Nonterminal repetition in parse tree paths

How can we *ensure* that this happens?

How to guarantee that the parse tree for a *sufficiently long* string has a path with a repeated state



Consider:

length of a path from root to leaf = # non-leaf nodes in that path.

Each non-leaf node has a nonterminal symbol.

If

max root-to-leaf path length $> \#$ nonterminal symbols in the grammar

then some nonterminal symbol occurs twice on that path.

How to guarantee that the parse tree for a *sufficiently long* string has a *sufficiently long* root-to-leaf path?

程序代写代做 CS编程辅导

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

https://tutorcs.com

Nonterminal repetition in binary parse tree paths

Let's use *binary* parse trees

程序代写代做 CS编程辅导

Binary parse tree:

$$2^{\text{max path length}} \geq \# \text{ leaves length}$$



If

$$\text{word length} > 2^{\# \text{ nonterminals}}$$

WeChat: cstutorcs

Assignment Project Exam Help


then

Email: tutorcs@163.com

$$2^{\text{max path length}} > 2^{\# \text{ nonterminals}},$$

$$\therefore \text{max path length} > \# \text{ nonterminals}$$

QQ: 749389476
<https://tutorcs.com>



and so there will be a repeated symbol
in a root-to-leaf path.

Nonterminal repetition in binary parse tree paths

Let's use *binary* parse trees, from **Chomsky Normal Form grammars!**

Binary **CNF** parse tree:

$$2^{\text{max path length}-1} \geq \# \text{ leaves}$$



If

$$\text{word length} > 2^{\# \text{ nonterminals}-1}$$

then

$$2^{\text{max path length}-1} > 2^{\# \text{ nonterminals}-1},$$

$$\therefore \text{max path length} > \# \text{ nonterminals}$$

and so there will be a repeated symbol
in a root-to-leaf path.


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Pumping Lemma for CFLs

Let L be any context-free language that has a CFG in CNF with k non-terminal symbols. Then for every word $w \in L$ with $|w| > 2^{k-1}$ letters, there exist strings u, v, x, y, z



$y \neq \varepsilon$
 y not both ε

such that

- ▶ $w = uvxyz$
 - ▶ $|vxy| \leq 2^k$, and
 - ▶ for all $i \geq 0$, $uv^ixy^iz \in L$
- i.e.,

$uxz, uvxyz, uvvxyz, \dots, uv^ixy^iz, \dots \in L.$

Symbolically:

$$\forall w \in L : |w| > 2^{k-1} \Rightarrow (\exists u, v, x, y, z : (w = uvxyz) \wedge (vy \neq \varepsilon) \wedge (|vxy| \leq 2^k) \wedge (\forall i \geq 0 : uv^ixy^iz \in L))$$

Pumping Lemma for CFLs

程序代写代做 CS编程辅导

Proof. (outline)

Take any word $w \in L$ with $|w| > 2^k$.



Let T be a parse tree for w , using the CNF CFG for L .

WeChat: cstutorcs

By our earlier Observations on root-to-leaf paths in CNF parse trees, some root-to-leaf path P in T contains a repeated nonterminal symbol.

Assignment Project Exam Help

Email: tutorcs@163.com

Among all pairs of nodes in P containing the same nonterminals, choose the pair q, r , with q above r , such that q is as far as possible down the path P .

QQ: 749389476

This ensures all nonterminals below q on P are distinct.

(Reason to be revealed later.)

https://tutorcs.com

Pumping Lemma for CFLs

Reading the letters of w from left to right, from the leaves of the tree, define:

- u be the letters of w to the left of the subtree T_q rooted at node q .
- v be the letters at the leaves that are to the left of the subtree T_r rooted at r .
- x be the letters at the leaves that are to the right of the subtree T_r .
- y be the letters of T_q that are to the right of the subtree T_r .
- z be the remaining letters of w , i.e., those to the right of T_q .




WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Pumping Lemma for CFLs

程序代写代做 CS编程辅导



We have:

- ▶ $w = uvxyz$ by construction
- ▶ Since q, r are distinct nodes of the path P with q above r , the tree T_r is a proper subtree of T_q .
- ▶ Furthermore, since the grammar is in CNF, q has two children, and only one of them is above r , so T_q has some leaves that do not belong to T_r .
- ▶ Therefore $vy \neq \varepsilon$.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Pumping Lemma for CFLs

程序代写代做 CS编程辅导



- ▶ By our choice of q and r , nonterminals appearing below q on P are distinct.
- ▶ Since we have k nonterminals, the subpath of P from q downwards has $\leq k + 2$ nodes (being q , then at most k nonterminals, then the leaf).
WeChat: cstutorcs
- ▶ Therefore it has length $\leq k + 1$.
Assignment Project Exam Help
Therefore T_q has $\leq 2^k$ leaves.
Email: tutorcs@163.com
These leaves are the strings v, x, y , in order.
- ▶ Therefore $|vxy| \leq 2^k$.
QQ: 749389476

<https://tutorcs.com>

Pumping Lemma for CFLs

程序代写代做 CS编程辅导



- ▶ Replacement of T_q by T_r gives a parse tree for uxz .
- ▶ Replacement of T_r by T_q gives a parse tree for $uvvxxyz$.
- ▶ The new copy of T_q contains a copy of T_r .
Replacing that copy of T_r by T_q gives a parse tree for $uvvvxxyyz$.
- ▶ Any parse tree with a copy of T_r can be enlarged, to be a parse tree of a longer string, by replacing T_r by T_q .
- ▶ These observations can be turned into a full formal proof by induction.

QQ: 749389476

<https://tutorcs.com>



A Tale of Two Pumping Lemmas

程序代写代做 CS编程辅导

If a Finite Automaton
with N states
accepts



a sufficiently long string,
then the path taken by the string
in the FA
contains a repeated state.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

This enables us to “pump” the string —
by repeating one substring —
to generate an infinite family
of members of the language.


If a Context-Free Grammar in CNF
with k nonterminals
generates

a sufficiently long string,
then some root-to-leaf path
in the parse tree
contains a repeated nonterminal.

This enables us to “pump” the string —
by repeating two substrings —
to generate an infinite family
of members of the language.

Pumping Lemma for CFLs: application

Consequence

Using the Pumping Lemma for  can show there are non-context-free languages.

Method

Assume L is context-free.

Then it has a Context-Free Grammar in CNF.

Let k be the number of nonterminal symbols in this CFG.

Choose a suitable word $w \in L$, of length $> 2^k$.

Show that, for any u, v, x, y, z such that $w = uvxyz$ and $vy \neq \varepsilon$ and $|vxy| \leq 2^k \dots$
 \dots there exists $i \geq 0$ s.t. $uv^ixy^iz \notin L$.

Contradiction.

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Compare quantifiers above with those in the Pumping Lemma for CFLs.

Non-context-free languages

$$L := \{a^n b^n a^n : n \geq 0\} = \{\varepsilon, aba, aabbbaa, aaabbbbaaa, \dots\}.$$

Theorem.

L is not context-free.



Proof. (by contradiction)

Assume that L is context-free. WeChat has a CFG.

Then there is a CFG in Chomsky Normal Form that generates $L \setminus \{\varepsilon\}$.

Let $k = \#$ nonterminals in this CNF CFG.

Take $N > 2^{k-1}/3$.

Choose $w = a^N b^N a^N$.

Consider any u, v, x, y, z such that


- ▶ $vy \neq \varepsilon$,
- ▶ $|vxy| \leq 2^k$, and
- ▶ $w = uvxyz$.

Think: are $uxz, uvxyz, uvvxyyz, \dots, uv^i xy^i z, \dots$ all in L ?

Non-context-free languages

Case 1: v and y are each all a's, or all b's, or empty.

For example:



Then $uvvxyyz$ can no longer have three equal-length stretches of a's and b's, since:

- ▶ The two strings v, y must each lie entirely within one stretch, and there are three stretches, so one of these stretches is unaltered by pumping.
- ▶ But at least one of the other stretches is lengthened, because $vy \neq \epsilon$.

So $uv^2xy^2z \notin L$.

<https://tutorcs.com>

Revision

程序代写代做 CS编程辅导



WeChat: cstutorcs

Reading: Sipser, pp. 125–129.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

all languages

CFLs

regular
languages

?