

# 程序代写代做 CS编程辅导

Clayton School of Information Technology  
Faculty of Information Technology



Monash University

Theory of Computation  
FINAL EXAM

WeChat: cstutorcs

Assignment Project Exam Help

Instructions: Email: [tutorcs@163.com](mailto:tutorcs@163.com)

10 minutes reading time.

3 hours writing time. QQ: 749389476

No books, calculators or devices.

Total marks on the exam = 120.

<https://tutorcs.com>

Working Space  
程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

### Question 1

Use De Morgan's Laws to prove that  $\neg(P \wedge Q) \wedge (\neg P \wedge \neg Q)$  is a tautology.

You may use other principles of propositional logic too, if you wish. But your proof must make significant use of De Morgan's Laws.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

*Official use only*

4

### Question 2

(6 marks)

Suppose you have predicates `algorithm` and `TuringMachine` with the following meanings, where variable  $X$  represents an arbitrary function:

`algorithm(X)`: there is an algorithm for  $X$ .  
`TuringMachine`: Turing machine for computing  $X$ .

- (a) Write a universal quantification with the meaning:

“Every function can be computed by a Turing machine.”

**WeChat: cstutorcs**

- (b) By what name is this assertion usually known?

**Assignment Project Exam Help**

- (c) What reasons are there for believing that this assertion is true?

**Email: tutorms@163.com**

**QQ: 749389476**

**<https://tutorcs.com>**

### Question 3

(3 marks)

Give a regular expression for the language of all strings over alphabet  $\{a,b\}$  whose first and last letters are different.

Official use only

**Question 4**

程序代写代做 CS编程辅导

**(4 marks)**

Let  $L$  be the language of nonempty strings over  $\{a,b\}$  that both start and finish with any letter but all other letters must be  $a$ . Draw a Finite Automaton to recognise  $L$ .



WeChat: cstutorcs

Assignment Project Exam Help

**Question 5****(3 marks)**

When converting a Nondeterministic Finite Automaton (NFA) to an equivalent Finite Automaton (FA), how do you determine which states in the NFA are combined to form the single Start state in the FA?

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

*Official use only*

7

**Question 6**

The following table describes a Finite Automaton with three states.

程序代写代做CS编程辅导

(4 marks)

Find another FA that is equivalent to this one and has only two states.

Write your two-



state	a	b
1	2	3
2	1	3
3	1	2

YOUR ANSWER

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Official use only

4

Question 7

程序代写代做 CS编程辅导 (4 marks)

Explain why the class of regular languages over the alphabet  $\{a,b\}$  is closed under interchange of  $a$  and  $b$ .

Definition:

If  $L$  is any language over the alphabet  $\{a,b\}$ , then the *interchange of  $a$  and  $b$*  forms a new language as follows: if  $w$  is a string in  $L$ , and replace every  $a$  by  $b$  and every  $b$  by  $a$ , simultaneously. So, if  $w = abb$  becomes  $baa$ .



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Official use only

4

Question 8

Consider the following Context-Free Grammar. Its non-terminals are  $S$  and  $L$ .

程序代写代做 CS编程辅导

$$S \rightarrow L \quad (1)$$

$$L \rightarrow haL \quad (2)$$

$$L \rightarrow aL \quad (3)$$

$$L \rightarrow h \quad (4)$$



Give

(a) a derivation, and

(b) a parse tree,

for the string `ahahaah`.

WeChat: cstutorcs

Label each step in the derivation on its right by the rule used. Use the spaces below for your answers.

Assignment Project Exam Help

(a)

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

(b)

Official use only

7



Working Space  
程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

**Question 9**

程序代写代做 CS编程辅导

**(3 marks)**

Give a regular grammar for the language of positive integers represented in binary with leading bit 1. (The *leading* bit is the most significant bit, i.e., the leftmost bit.)



WeChat: cstutorcs

**Question 10****(6 marks)**

Given the following Context-Free Grammar:

Assignment Project Exam Help

$$S \rightarrow \varepsilon \quad (1)$$

$$S \rightarrow T \quad (2)$$

Email: tutors@163.com


$$T \rightarrow aT \quad (4)$$

$$T \rightarrow b \quad (5)$$

QQ: 749389476

complete the following diagram to give a Pushdown Automaton for the language generated by the grammar.

https://tutorcs.com



Official use only

9

**Question 11**

(10 marks)

This question uses the same grammar as the previous question.

程序代写代做 CS编程辅导

Let  $L$  be the language generated by this grammar.

(a) Prove by induction that every string of the form  $a^m b^n$ , where  $m \geq n - 1$  and  $n \geq 1$ , belongs to  $L$ .



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

(b) Prove or disprove: some string in  $L$  has a derivation, using this grammar, that is neither a leftmost derivation nor a rightmost derivation.

*Official use only*

10

Working Space  
程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

### Question 12

Recall that the Fibonacci numbers,  $F_n$ , are defined recursively as follows:

$$F_1 = 1,$$

$$F_n = F_{n-1} + F_{n-2} \quad \text{for } n \geq 3.$$

The first few numbers are

1, 1, 2, 3, 5, 8, 13, 21, 34, ...

Note that the Fibonacci numbers are (after the first term) an *increasing* sequence of positive integers.

The language FIBONACCI is defined to be the set of all strings of the letter **a** whose length is a Fibonacci number. So,

$$\text{FIBONACCI} = \{ a^{F_n} : n \in \mathbb{N} \}.$$

(a) Prove that the difference,  $F_n - F_{n-1}$ , between two consecutive Fibonacci numbers increases as  $n$  increases, i.e.,  $F_n - F_{n-1} > F_{n-1} - F_{n-2}$  for all  $n \geq 5$ .

(b) Using (a), prove that the language FIBONACCI is not context-free.

Official use only

# 程序代写代做 CS编程辅导



WeChat: cstutorcs

## Question 13


Consider the following Turing machine.

Assignment Project Exam Help (9 marks)

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



Trace the execution of this Turing machine, writing your answer in the spaces provided on the next page.

The lines show the configuration of the Turing machine at the start of each step. For each line, fill in the state and the contents of the tape. On the tape, you should indicate the currently-scanned character by underlining it, and you should show the first blank character as  $\Delta$  (but there is no need to show subsequent blank characters).

To get you started, the first line has been filled in already.

At start of step 1: State: 1 Tape: s c 0 1 1

At start of step 2: State: 2 Tape:           

At start of step 3: State: 3 Tape:           

At start of step 4: State: 4 Tape:           

At start of step 5: State: 5 Tape:           

At start of step 6: State: 6 Tape:           

At start of step 7: State: 7 Tape:           

At start of step 8: State: 8 Tape:           

At start of step 9: State: 9 Tape:           

At start of step 10: State: 10 Tape:           

At start of step 11: State: 11 Tape:           

At start of step 12: State: 12 Tape:           

程序代写代做 CS编程辅导

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Official use only

**Question 14****(5 marks)**

For each of the following decision problems, indicate whether or not it is decidable.

You may assume that, when Turing machines are encoded as strings, this is done using the Code-Word Language (CWL).

Decision Problem

your answer  
(tick **one** box in each row)

Input: a Turing machine  $M$  and a positive integer  $k$ .  
Question: Does  $M$  accept a string of at most  $k$  letters?

☐  
Decidable☐  
Undecidable

Input: a Turing machine  $M$ , and a positive integer  $k$ .  
Question: Does the encoding of  $M$  have at least  $k$  letters?

☐  
Decidable☐  
Undecidable

Input: a Turing machine  $M$ , and a positive integer  $k$ .  
Question: When  $M$  is given an encoding of itself as input, does the computation go for at least  $k$  steps?

☐  
Decidable☐  
Undecidable

Input: a Turing machine  $M$ .  
Question: Does  $M$  eventually print an encoding of  $M$  on the tape and then halt?

☐  
Decidable☐  
Undecidable

Input: a Turing machine  $M$ , and a string  $w$ .  
Question: Does  $M$  reject  $w$ ?

☐  
Decidable☐  
Undecidable

程序代写代做 CS编程辅导

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

*Official use only*

5



Working Space  
程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

### Question 15

(12 marks)

The Venn diagram on the right shows several classes of languages. For each language (a)–(l) in the list below, indicate which classes it belongs to, and which it doesn't belong to, by placing its corresponding letter in the correct region of the diagram.

If a language does not belong to any of these classes, then place its letter above the top of the diagram.

You may assume that all languages are encoded as strings, this is done using the Code-Word Language.



- (a) The set of all adjacency matrices.
- (b) The set of all 2-colourable graphs. (A graph is *2-colourable* if each vertex can be coloured Black or White in such a way that adjacent vertices receive different colours.)
- (c) The set of all 3-colourable graphs. (Definition is like 2-colourable, except now the available colours are Red, White and Black.)
- (d) The set of all satisfiable Boolean expressions in Conjunctive Normal Form with at least two literals in each clause.
- (e) EQUAL, the set of all strings over alphabet  $\{a,b\}$  with an equal number of  $a$ 's and  $b$ 's.
- (f) The set of all strings of parentheses such that the parentheses are correctly matched.
- (g) The set of all strings in which every letter is next to an identical letter.
- (h) The set of all Finite Automata that define the empty language.
- (i) The set of all Turing Machines with polynomial time complexity.
- (j) The set of all Turing machines which, when given themselves as input, eventually either reject or loop forever.
- (k) The set of all Turing machines whose language of accepted strings is regular.
- (l) The set of all Turing machines that have ever been written.

程序代写代做 CS编程辅导

recursively enumerable (r.e.)



decidable

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Context-Free

<https://tutorcs.com>

Regular

Finite

Official use only

12

**Question 16****(7 marks)**

Prove that the following problem is undecidable.

程序代写代做 CS编程辅导

Input: a Turing machine  $M$  and a positive integer  $t$ .

Question: Is there a string  $x$  which, if given as input to  $M$ , causes it to eventually erase everything on the tape (every letter by Blank), after which it never writes any other symbol?

You may use the fact that the halting problem is undecidable.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

**Question 17****(3 marks)**

Explain how to obtain, from any language that is recursively enumerable but not decidable, another closely related language that is not recursively enumerable. (Proof is not required.)

*Official use only*

10

Question 18

程序代写代做 CS编程辅导 (15 marks)

Consider the language 3-EDGE-COLOURABILITY, which consists of all graphs  $G$  such that we can assign colours to the edges of the graph so that (i) each edge is Red, White or Black, and (ii) any two edges incident at a common vertex must get different colours.

Let  $H$  be the fo



WeChat: cstutorcs

Assignment Project Exam Help

(a) Construct a Boolean expression  $E_H$  in Conjunctive Normal Form such that the satisfying truth assignments for  $E_H$  correspond to solutions to the 3-EDGE-COLOURABILITY problem on the above graph  $H$  (i.e., they correspond to colourings of the edges of  $H$ , using at most three colours and which give different colours to incident edges).

To do this, use variable names  $a_R, a_W, a_B, b_R, b_W, b_B, c_R, c_W, c_B, d_R, d_W, d_B$ , where variable  $e_X$  is True if and only if edge  $e$  gets colour  $X$  (where  $e \in \{a, b, c, d\}$  and  $X \in \{R, W, B\}$ ).

QQ: 749389476

<https://tutorcs.com>

(b) Give a polynomial-time reduction from 3-EDGE-COLOURABILITY to SATISFIABILITY.

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

*Official use only*

15

Question 19

程序代写代做 CS编程辅导 (8 marks)

Prove that the HAMILTONIAN CIRCUIT problem is NP-complete, by reduction from HAMILTONIAN PATH. You may assume that HAMILTONIAN PATH is NP-complete.

Definitions:

A **Hamiltonian path** in  $G$  is a path that includes every vertex of  $G$ . All the vertices on the path must be distinct.

A **Hamiltonian circuit** in  $G$  is a circuit that includes every vertex of  $G$ . All the vertices on the circuit must be distinct.

HAMILTONIAN PATH

Input: Graph  $G$ .

Question: Does  $G$  have a Hamiltonian path?

HAMILTONIAN CIRCUIT

Input: Graph  $G$ .

Question: Does  $G$  have a Hamiltonian circuit?

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Official use only

8

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

END OF EXAMINATION