

程序代写代做 CS编程辅导

FIT2014 Theory of Computation



Lecture 14

Context-Free Languages and Pushdown Automata

WeChat: cstutorcs

Assignment Project Exam Help

slides by Graham Farr
Email: tutorcs@163.com

QQ: 749389476

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

<https://tutorcs.com>

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Overview

- ▶ CFL \longrightarrow PDA
- ▶ PDA \longrightarrow CFL

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

We will show ...



$$\{\text{CFLs}\} = \{\text{languages recognised by a PDA}\}$$

WeChat: cstutorcs

... in two parts:

Assignment Project Exam Help

$$1. \{\text{CFLs}\} \subseteq \{\text{languages recognised by a PDA}\}$$

Email: tutorcs@163.com

$$2. \{\text{languages recognised by a PDA}\} \subseteq \{\text{CFLs}\}$$

<https://tutorcs.com>

CFL \longrightarrow PDA

Theorem.

$\{ \text{CFLs} \} \subseteq \{ \text{languages recognised by a PDA} \}$

程序代写代做 CS编程辅导



Proof outline and main ideas:

Let L be a CFL.

WeChat: cstutorcs

Let G be a CFG for L .

Assignment Project Exam Help

We need to show that there is a PDA that recognises L .

Email: tutorcs@f63.com

If $w \in L$ then w has a leftmost derivation.

QQ: 749389476

Idea: leftmost derivation may be viewed as

<https://tutorcs.com>

- ▶ growing a prefix of w that we know to be correct, and
- ▶ managing the rest of w (including all nonterminals) with a stack.

Leftmost derivation: stack view

Grammar fragment:

| | | |
|-----|---------------|-------|
| ... | ... | ... |
| S | \rightarrow | peX |
| X | \rightarrow | YcZ |
| Y | \rightarrow | ar |
| Z | \rightarrow | ey |
| ... | ... | ... |

程序代写代做 CS编程辅导



peX

pearcey

X

\Rightarrow

peYcZ

pearcey

YcZ

WeChat: cstutorcs

Assignment Project Exam Help

\Rightarrow

pearcZ

pearcey

cZ

Email: tutorcs@163.com

QQ: 749389476

pearcey

Z

<https://tutorcs.com>

\Rightarrow

pearcey

pearcey

CFL \longrightarrow PDA

程序代写代做 CS编程辅导



We construct the required PDA vs.

We start with four basic states, then add more states for each production rule ...

We'll need a new character (not currently a terminal or non-terminal),
to mark the end of our stack.

We'll use \$.


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>


CFL \longrightarrow PDA

程序代写代做 CS编程辅导




CFL \longrightarrow PDA

程序代写代做 CS编程辅导



CFL \longrightarrow PDA

程序代写代做 CS编程辅导



WeChat: cstutorcs

$a, X \rightarrow \epsilon$

Assignment Project Exam Help

Email: tutores@163.com

QQ: 749389476

<https://tutores.com>

CFL \longrightarrow PDA

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

If a terminal is on top of stack:
everything before it in target string
must have been read in.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$a, a \rightarrow \epsilon$

$b, b \rightarrow \epsilon$

$c, c \rightarrow \epsilon$

\vdots

So we need loop transitions
to check such letters off ...

For terminals

CFL \longrightarrow PDA

This construction gives a PDA that accepts precisely those strings with a leftmost derivation by G ,

i.e., precisely those strings with a derivation by G ,



i.e., precisely those strings in L .

WeChat: cstutorcs

Assignment Project Exam Help

Full formal proof: see Sipser, Ch. 2, Section 2.2.

QQ: 749389476

<https://tutorcs.com>

Now for the other way round ...

PDA \longrightarrow CFL

Theorem.

$\{ \text{languages recognised by a PDA} \} \subset \{ \text{CFLs} \}$

程序代写代做 CS编程辅导



Proof ideas:

Let L be a language recognised by some PDA M .

We need to show that \exists a CFG G that generates L .

WeChat: cstutorcs

Assignment Project Exam Help

First, we make some simple modifications to M .

Email: tutorcs@163.com

Then we give productions that describe certain ways of going through the PDA ...

QQ: 749389476

First, modifications to M :

<https://tutorcs.com>

Ensure it has just one Final State,

and that the stack is empty when it reaches the Final State.



original Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



\$: new symbol

$$\forall x \in \text{stack alphabet}$$

PDA \longrightarrow CFL



More modifications: ensure that each transition with a push or pop, but *not both*.

These are ok:



Assignment Project Exam Help

These are *not*:



So we change them ...

PDA \longrightarrow CFL



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



PDA \longrightarrow CFL

程序代写代做 CS编程辅导

A string is accepted by this (modified) M if one of its paths through M

- ▶ starts in the Start State s ,
- ▶ finishes in the Final State
- ▶ with the stack empty at start and finish.



WeChat: cstutorcs

For every pair of states p, q , define a non-terminal symbol A_{pq} :

Assignment Project Exam Help

- ▶ intended to generate all strings which, starting at p with an empty stack, can take some path through M which ends at q with an empty stack.

Email: tutorcs@163.com

QQ: 749389476

Aim: a grammar such that, for every string,

<https://tutorcs.com>

it is accepted by $M \iff$ it can be derived from A_{st} .

PDA \longrightarrow CFL

Consider how a computation in M for a string w moves from p to q , with empty stack at start and finish.



We have two cases:

Case 1:

The computation also has an empty stack at some other state r on the path.

Then we can break the computation from p to q into two parts:


- ▶ the first part, going from p to r (starting and ending with empty stack),
- ▶ the second part, going from r to q (starting and ending with an empty stack).

We model this with the production

$$A_{pq} \longrightarrow A_{pr}A_{rq}$$

PDA \longrightarrow CFL

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$A_{pq} \longrightarrow A_{pr}A_{rq}$$

PDA \longrightarrow CFL

程序代写代做 CS编程辅导

Case 2:

The computation never has an ϵ -transition, except at p and q .



Because it starts and finishes with an empty stack:

- ▶ the first transition must push a symbol onto the stack,
- ▶ the last transition must pop a symbol from the stack,
- ▶ the two symbols must be the same (call it z)
 - ▶ ... else the stack would have to have been emptied at some stage, to remove the first symbol before the last symbol arrives.
- ▶ and this symbol stays at the bottom of the stack the whole time.

WeChat: cstutorcs

Assignment Project Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

PDA \longrightarrow CFL

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

$$A_{pq} \longrightarrow xA_{p'q'}y$$

PDA \longrightarrow CFL

In the computation from p' to q' , the stack is not empty, but it always has z sitting at the bottom.



The “substack” above z is empty and q' .

The computation path from p' to q' starts and ends with a stack containing just z , with z on the bottom of every stack along the way.

This is equivalent to starting and ending with an empty stack.

We model this with the production

$$A_{pq} \longrightarrow xA_{p'q'}y$$

PDA \longrightarrow CFL

程序代写代做 CS编程辅导

Also, for each state p , add the



$\longrightarrow \varepsilon$

Finally, add the production

WeChat: cstutorcs

$S \longrightarrow A_{st}$

Assignment Project Exam Help

where, as usual, the non-terminal S is the Start symbol.

Email: tutorcs@163.com

This set of productions give a CFG for L .

QQ: 749389476

For formal proof (making good use of induction), see Sipser.

<https://tutorcs.com>

Revision

程序代写代做 CS编程辅导

Some things to think about:

► CFG \rightarrow PDA:

- What conditions would we have to satisfy, so that the PDA we construct is *deterministic*?
- If the PDA produced by this construction *only has the four states we started with* — so that the extra transitions we added are *all loops* — what can we say about the language we started with?

► CFG \rightarrow PDA \rightarrow CFG:

- If you start with a CFG and then do the construction both ways to get another CFG, will it ever be the same as the CFG you started with?

Reading: Sipser, pp. 117–125



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>