



MONASH
University

FIT5202 – Data Processing for Big Data

Stream Join Processing

Edited by

Chee-Ming Ting

Developed by
Prajwol Sangat



程序代写代做 CS 编程辅导




MONASH INFORMATION TECHNOLOGY

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Last Week

程序代写代做 CS编程辅导

- Streaming Data Processing
- Streaming Processing Technology



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

This week

程序代写代做 CS编程辅导

- Overview of Stream processing
- Time based window stream join (Unbounded)
 - Tuple slide
 - Time slide
- Tuple based window stream join (Unbounded)
- Bounded stream join



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Overview of Stream Join



Bounded Stream Join

- If both streams R and S are bounded streams
- There is a start and an end

Unbounded Stream Join

- If any of the streams is unbounded
- There is a start but no end

Assignment Project Exam Help

Challenges:

Email: tutorcs@163.com

QQ: 749389476


□ How to join streams with no end?

□ Due to network latency, some data arrives late compared to other related tuples

程序代写代做 CS 编程辅导

Recap - Windowing System in Unbounded Streams


Time-based Window



WeChat: $cstutorcs$ t_{now} $t_{now - k}$

Assignment Project Exam Help

*Tuple-based Window
(Count-based Window)*



<https://tutorcs.com>

Window-based Stream Join



A General Stream Join Process:

- When a tuple r arrives from Input stream R :
 - Scan stream S 's window to find tuples matching r , and get join result
 - Insert new tuple r into window for stream R
 - Invalidate all expired tuples in stream R 's window

Hence, stream join is based on the data in the current window!!

- Tuples in the window cannot be matched with expired tuples (discarded from window) and with incoming tuples that arrived later

<https://tutores.com>

Review – Hash Join

程序代写代做 CS编程辅导

Hash S Table

Table S	
Arts	8
Business	15
CompSc	2
Dance	12
Engineering	7
Finance	21
Geology	10
Health	11
IT	16

hashed into →

Hash Table	
Index	Entries
1	Geology/10
2	CompSc/2
3	Dance/12
4	
5	
6	Business/15
7	Engineering/7
8	Arts/8
9	IT/18
10	
11	
12	



WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Probe Table R into hash table

Table R	
Index	Entries
Adele	8
Bob	22
Clement	16
Dave	23
Ed	11
Fung	25
Goli	3
Harry	17
Irene	14
Joanna	2
Kelly	6
Lian	20
Meng	1
Noor	5
Omar	19

→

Hash Table	
Index	Entries
1	Geology/10
2	CompSc/2
3	Health/11
4	
5	
6	Business/15
7	Engineering/7
8	Arts/8
9	IT/18
10	
11	
12	

Figure 5.7. Probing Table R

Hash Join

程序代写代做 CS编程辅导



Hash Join:

- Hash every tuple in window S_i
- Probe every tuple in window R_i

Email: tutorcs@163.com

QQ: 749389476

Hash Table S

<https://tutorcs.com>

Hash Join

程序代写代做 CS编程辅导



Hash Join:

Assignment Project Exam Help

- Hash every tuple in window S_i
- Probe every tuple in window R_j

Email: tutorcs@163.com

What's the problem?

QQ: 749389476

Problem: If r comes in first and then s comes in later, then r will not be compared with the s
→ If r and s has same key, we will miss join operation

<https://tutorcs.com>

Symmetric Hash Join

Step 1:

When r arrives at input stream R



Assignment Project Exam Help

Symmetric Hash Join Process:

- When a tuple r arrives at an input stream R :
 - Probe r to the hash table S
 - Hash tuple r into hash table R
 - Insert new tuple r into stream R


QQ: 749389476

<https://tutorcs.com>

Symmetric Hash Join

Step 2:


Probe r into hash table S



Symmetric Hash Join

Step 3:

Hash r into hash table R



Assignment Project Exam Help

Symmetric Hash Join Process:

- When a tuple r arrives at an input stream R :
 - Probe r to the hash table S
 - Hash tuple r into hash table R
 - Insert new tuple r into stream R

QQ: 749389476

<https://tutorcs.com>

Hash Table S

Symmetric Hash Join

Step 4:

- When s comes in, probe into hash table R to get join results
- After that, hash s into own hash table, and insert into stream S

Symmetric Hash Join Process:

- When a tuple r arrives at an input stream R :
 - Probe r to the hash table S
 - Hash tuple r into hash table R
 - Insert new tuple r into stream R


QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导



Assignment Project Exam Help



Hash Table S

By using two hash tables (symmetric), we don't miss the join of any incoming tuple.

This week

程序代写代做 CS编程辅导

- Overview of Stream processing
- Time based window stream join (Unbounded)
 - Tuple slide
 - Time slide
- Tuple based window stream join (Unbounded)
- Bounded stream join



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Time-based Window Stream Join



Assignment Project Exam Help

Unbounded Stream Join (Window-based)

- Join is only applied to tuples in the window
- But window is a running window.**

QQ: 749389476

<https://tutorcs.com>

Email: tutorcs@163.com

Each window has fixed time duration

- Any numbers of tuples within that window will be considered for the join operation

Time-based Window Stream Join



t_{now}

t_{now-k}

Assignment Project Exam Help


Unbounded Stream Join (Window-based):

- Join is only applied to tuples in the window
- **But window is a running window...**
- **How to slide the window?**
 - Tuple **Slide** - Slide window based on number of tuples (move window when tuples come in)
 - Time **Slide** - Slide window based on time interval (e.g., move window every 30s)

<https://tutorcs.com>

Tuple Slide Stream Join

程序代写代做 CS编程辅导



Tuple Slide Stream Join:

Email: tutorcs@163.com


- When a new tuple r arrives at stream R
 - Slide all the windows (remove expired tuples)
 - Join r with all tuples in the new window in stream S
 - Add r to the window in stream R

QQ: 749389476

<https://tutorcs.com>

Tuple Slide Stream Join

程序代写代做 CS编程辅导



Tuple Slide Stream Join:
Email: tutorcs@163.com

- When a new tuple *r* arrives at stream *R*
 - Slide all the windows (remove expired tuples)
 - Join *r* with all tuples in the new window in stream *S*
 - Add *r* to the window in stream *R*

<https://tutorcs.com>

Tuple Slide Stream Join

程序代写代做 CS编程辅导



Tuple Slide Stream Join:

Email: tutorcs@163.com

- When a new tuple r arrives at stream R
 - Slide all the windows (remove expired tuples)
 - Join r with all tuples in the new window in stream S → which join method? → Symmetric Hash join
 - Add r to the window in stream R

<https://tutorcs.com>

Tuple Slide (Using M-Join)

How to join more than two streams at same time?

- Use **M-Join** – a multiway streaming join
- Based on symmetric hash join (work similarly to two-stream)

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com
M-Join (the real m-way join)

QQ: 749389476

<https://tutorcs.com>

20

Tuple Slide (Using M-Join)

程序代写代做 CS 编程辅导



Repeat same procedure when tuple s arrives

- Probe s into hash table R & T , and find the match
- Then, hash s to hash table S

Advantages: can still match r and s although s arrive later than r

Repeat the same when tuple t arrives

Time Slide (Using M-Join)

How M-join works with time-slide window




<https://tutorcs.com>

Time Slide (Using M-Join)

- Let one box here represents one unit time or one basic window.

Ex: 1 unit time = 1 minute

- Window size = 6 mins
- slide = 2mins




Time Slide (Using M-Join)

程序代写代做 CS编程辅导

Question:

How to process or join tuples in the new basic windows?



Time Slide (Using M-Join)



Time Slide (using M-Join):

• Process Stream R:

- Take all tuples from basic windows r_1 and r_2 , and probe to hash tables S and T
- Take all tuples from basic windows r_1 and r_2 to hash table R

Time Slide (Using M-Join) 程序代写代做 CS编程辅导



Time Slide (Using M-Join) 程序代写代做 CS编程辅导



Time Slide (Using M-Join) 程序代写代做 CS编程辅导



Time Slide (using M-Join):

- Process Stream S:

- Take all tuples from basic windows s_1 and s_2 , and probe to hash tables R and T
- Take all tuples from basic windows s_1 and s_2 to hash table S

QQ: 749389476

<https://tutorcs.com>

Time Slide (Using M-Join) 程序代写代做 CS编程辅导



Time Slide (Using M-Join) 程序代写代做 CS编程辅导



Time Slide (using M-Join):

- Process Stream T:
 - Take all tuples from basic windows t_1 and t_2 , and probe to hash tables S and R
 - Take all tuples from basic windows t_1 and t_2 to hash table T

QQ: 749389476

<https://tutorcs.com>

This week

程序代写代做 CS编程辅导

- Overview of Stream processing
- Time based window stream join (Unbounded)
 - Tuple slide
 - Time slide
- Tuple based window stream join (Unbounded)
- Bounded stream join



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Tuple-based Window Stream Join



Ex: window size =100 tuples

- When 1 tuple comes in , oldest tuple needs to be removed to include it in the window because the size has to be 100

Assignment Project Exam Help


- **Size of the window** is k number of tuples
- When a tuple *r* arrives in stream *R*, we readjust the window size of stream *R*. What about stream *S*? If the size of the window is based on stream *R*, window in stream *S* might have less number of tuples (thus violates the tuple-based window rule)
- If we allow **window size to be different**, what is the **semantic of the window**?

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Tuple-based Window Stream Join



- Should we have the **same window size** for all streams in the join?
- If this is the case, in an extreme case, windows among streams will not overlap
- What is the semantic of the window, and hence the join?

Assignment Project Exam Help

Email: tutorcs@163.com

**Not many research in Tuple-based Window Join,
because lack of understanding on how tuple-based window may be applied to stream join.**

<https://tutorcs.com>

- If we slide windows for both R & S at the same time → **window size will be different**
- OR, we have different sliding mechanism for S, e.g., no slide until it has new tuples → **same window size**
 - **Problem:** If two streams have different arrival rate (e.g. R is faster than S)
 - Tuples in S will get very old
- When performing join, you join new data in R with old data in S

Inspired by how soccer players handshake

程序代写代做 CS 编程辅导




Figure 1: Handshake join idea.




Figure 3: Handshake join sketch. Streams flow by each other in opposite directions; comparisons (and result generation) happens in parallel as the streams pass by.

WeChat: cstutorcs

- Even then... this is not a Tuple-based Window Stream Join
- It is still a Time-based Window Stream Join
- But monitoring each tuple (and when it is expired) looks more natural in this Soccer Handshake method.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Looks nice, but there are
problems...

<https://tutorcs.com>

- Streams flow by each other in opposite directions.
- Ex: stream R moves from left to right and stream S moves from right to left
- Comparison/join occurs when streams pass by

Handshake Join

程序代写代做 CS编程辅导



- After a handshake of a pair of tuples is done, both streams R and S move forward at the same time
QQ: 749389476
- As a result, we will miss a handshake because one tuple from R moves to the right, and one tuple from S moves to the left, and one handshake will be missed
<https://tutorcs.com>

Handshake Join

程序代写代做 CS编程辅导




Handshake Join (Solution 1)



Solution 1:

Alternating basic window must be left empty in the stream.



Handshake Join (Solution 1)



Solution 1:



WeChat: cstutores
Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Handshake Join (Solution 1)



程序代写代做 CS编程辅导

Handshake Join (Solution 2)



QQ: 749389476

Main Idea: After a handshake happens, the streams do not move forward, but each tuple in the stream performs a handshake with the next tuple, and then after that both streams move forward.
<https://tutordes.com>

40

程序代写代做 CS编程辅导

Handshake Join (Solution 2)



程序代写代做 CS编程辅导

Handshake Join (Solution 2)



Solution 2:



WeChat: cstutores
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Stream S

<https://tutorcs.com>



- Overview of Stream processing
- Time based window stream join (Unbounded)
 - Tuple slide
 - Time slide
- Tuple based window stream join (Unbounded)
- Bounded stream join
 - How to join two data streams that has end?
e.g. data from railway sensor, when train stops, data is not streaming

QQ: 749389476

<https://tutorcs.com>

Bounded Stream Join

程序代写代做 CS编程辅导



- No window → it's easy...

▪ The semantic is hence the same as that of relational join

▪ It is also called a “Pipelining Join”

▪ Processing options:

- Offline (the same as relational join processing)

- Online (this is pipelining join)

QQ: 749389476

Wait until all data come in, and perform traditional relational join processing


<https://tutorcs.com>

Perform join while data is streaming

Symmetric Hash Join



程序代写代做CS编程辅导



How is it different from window-based join for unbounded stream?

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476


<https://tutorcs.com>

45

- Window-based join:
Remove entries from hash table when tuple expire
- Bounded stream join:
 - No removal of entries from hash table
 - Hash tables R & S will hold entire stream data
 - because stream will end at some point

Symmetric Hash Join

Step 2:



Symmetric Hash Join Process:

- When a tuple r arrives at an input stream R :
 - Probe r to the hash table S
 - Hash tuple r into hashtable R
 - Insert new tuple r into stream R


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Symmetric Hash Join

Step 3:



Assignment Project Exam Help

Symmetric Hash Join Process:

- When a tuple r arrives at an input stream R :
 - Probe r to the hash table S
 - Hash tuple r into hash table R
 - Insert new tuple r into stream R

QQ: 749389476

<https://tutorcs.com>

Symmetric Hash Join

Step 4:



Assignment Project Exam Help

Symmetric Hash Join Process:

Email: tutorcs@163.com

- When a tuple r arrives at an input stream R :
 - Probe r to the hash table S
 - Hash tuple r into hash table R
 - Insert new tuple r into stream R

QQ: 749389476


<https://tutorcs.com>

M-Join

程序代写代做 CS编程辅导

Step 1:

Similarly for M-join, no removal of entries from the hash table because there is no windowing and the stream is going to end.



M-Join

Step 2:




M-Join Process:

- When a tuple r arrives at an input stream R :
 - Probe r to all other hash tables
 - Hash tuple r into hash table R
 - Insert new tuple r into stream R

M-Join

Step 3:



M-Join Process:

- When a tuple r arrives at an input stream R :
 - Probe r to all other hash tables
 - Hash tuple r into hash table R
 - Insert new tuple r into stream R

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

M-Join

Step 3:



AM-Join

程序代写代做 CS编程辅导

Step 1:





程序代写代做 CS编程辅导

Step 3:

eam R



Hash Table R

tuples s and t not
yet processed

Hash Table S

Assignment Project Exam Help

Stream T



Hash Table T

	101
	011
	111
	101

update
BiHT

AM-Join Process

- When a tuple r arrives at an input stream R :
- Probe r to the Bit-vector Hash Table (BiHT)
- Hash tuple r into hash table R
- Insert new tuple r into stream R

QQ: 749389476
Update BiHT

https://tutorcs.com

AM-Join

程序代写代做 CS编程辅导

Step 4:

101
011
111
101

BiHT



<https://tutorcs.com>

程序代写代做 CS编程辅导

Step 4:

	101
	011
	111
	101

BiHT



Stream R



Hash Table R


tuples s and t not yet processed



Stream S



Hash Table S



Stream T



Hash Table T

AM-Join Process:

- When a tuple r arrives at an input stream R :
 - Probe r to the Bit-vector Hash Table (BiHT)
 - Hash tuple r into hash table R
 - Insert new tuple r into stream R

QQ: 749389476
Update BiHT

<https://tutorcs.com>

AM-Join

程序代写代做 CS编程辅导



Stream R



Hash Table R

tuples s and t not
yet processed



Hash Table S

Stream T




Hash Table T

<https://tutorcs.com>

DEMO

程序代写代做 CS编程辅导

- Symmetric Hash



WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

Symmetric Hash Join Process:

- When a tuple *r* arrives at an input stream *R*:
 - Probe *r* to the hash table *S*
 - Hash tuple *r* into hash table *R*
 - Insert new tuple *r* into stream *R*

QQ: 749389476

<https://tutorcs.com>

Thank You

程序代写代做 CS编程辅导



Questions?



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>