



程序代写代做 CS 编程辅导

MONASH
INFORMATION
TECHNOLOGY



Machine Learning: Clustering


WeChat: cstutorcs
Assignment Project Exam Help

Prajwol Sangat

Updated by Chee-Ming Tang (23 April 2020)
Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>



This week

程序代写代做 CS编程辅导



Chapter 17 Parallel Clustering and Classification

WeChat: cstutorcs

Assignment Project Exam Help

17.1 Clustering and Classification

17.2 Parallel Clustering

17.3 Parallel Classification

17.4 Summary

17.5 Biographical Notes

17.6 Exercises

QQ: 749389476

<https://tutorcs.com>

Machine Learning Fundamentals - Revision

Supervised learning



Supervised learning cover patterns in the data that relate to data attributes with a target (class) attribute.

- These patterns are then utilized to predict the values of the target attribute in future data instances.

Assignment Project Exam Help

Unsupervised learning: The data have no target attribute.

Email: tutorcs@163.com

- Exploring the data to find some intrinsic structures in them.

<https://tutorcs.com>

Clustering: an illustration

Finds groups (or clusters) of objects

A cluster comprises a number of "similar" objects

A member is closer to another member within the same group than to a member of a different group

Groups have no category or label

Unsupervised learning



WeChat: cstutorcs

Assignment Project Exam Help

Salary

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Age

What is clustering for? 程序代写代做 CS 编程辅导

Let's see some real examples



Example 1: Cluster students based on their examination marks, gender, heights, nationality, etc.
WeChat: cstutorcs

Assignment Project Exam Help
Example 2: In marketing, segment customers according to their similarities
Email: tutorcs@163.com

- To do targeted marketing.

QQ: 749389476

<https://tutorcs.com>

What is clustering for? 程序代写代做 CS 编程辅导

Clustering is one of the most useful machine learning techniques.

- Used in almost every field: medicine, psychology, botany, sociology, archeology, marketing, insurance, libraries, etc.

WeChat: cstutorcs

- Most popular applications of clustering are:
recommendation engines,
market segmentation,
social network analysis,
image segmentation,
anomaly detection

QQ: 749389476

<https://tutorcs.com>



Some Applications in Digital Health

Partitioning of Heart sound signal





Fig. 2. Dynamic clustering of heart sound into four fundamental components.

Noman, Fuad, Sh-Hussain Salleh, Chee-Ming Ting. "A markov-switching model approach to heart sound segmentation and classification." *IEEE Journal of Biomedical and Health Informatics* 24, no. 3 (2019).

QQ: 749389476

<https://tutorcs.com>

Partitioning of brain regions into clusters (communities)



Ting, Chee-Ming, et al. "Detecting Dynamic Community Structure in Functional Brain Networks Across Individuals: A Multilayer Approach." *IEEE Trans Medical Imaging* (2020).

What is clustering for? 程序代写代做 CS 编程辅导

Similarities Measures


- Key factor in clustering measure
- Measure the degree of similarity between two objects
- Distance measure: the shorter the distance, the more similar are the two objects (zero distance means identical objects)
- Euclidean Distance:



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com



$$\text{Euclidean distance } (a, b) = \sqrt{(a_1 - b_1)^2 + (a_2 - b_2)^2}$$

$$dist(x_i, x_j) = \sqrt{\sum_{k=1}^h (x_{ik} - x_{jk})^2}$$

QQ: 749389476
<https://tutorcs.com>

Clustering Techniques



Goal of clustering:

- maximize intra-cluster similarity
- minimize inter-cluster similarity

Hierarchical clustering

- Seeks to build a hierarchy of clusters
- Strategies:

Agglomerative: Bottom up approach

Divisive: Top down approach

WeChat: cstutorcs


Assignment Project Exam Help

Email: tutors@163.com


QQ: 749389476

<https://tutorcs.com>

Partitional vs Hierarchical



Each sample(point) is assigned to a unique cluster



Creates a nested and hierarchical set of partitions/clusters

K-Means clustering (Partitional clustering)

K-means is a **partitional clustering** algorithm

Let a set of data points (data objects) D be

$$\{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n\},$$



where $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{ir})$ is a **vector** in a real-valued space $X \subseteq R^r$,


and r is the number of attributes (dimensions) in the data.

The k -means algorithm partitions the given data into k clusters.

- Each cluster has a cluster **center**, called **centroid**.
- k is specified by the user

QQ: 749389476

<https://tutorcs.com>



K-Means clustering



Algorithm k-Means:

- **(Initialization)** Specified number of clusters, and guesses the k seed cluster centers
- **(Assignment Step)** Assign each data point to the cluster with the closest centroid
WeChat: cstutorcs
Current clusters may receive or lose their members
- **(Update Step)** Each cluster must re-calculate the mean (centroid)
- The process is repeated until the clusters are stable (no change of members)

Assignment Project Exam Help

Email: tutorcs@163.com

Algorithm: k-means

Input:

$D = \{x_1, x_2, \dots, x_n\}$

//Data objects

k //Number of desired clusters

Output:

K //Set of clusters

1. Assign initial values for means m_1, m_2, \dots, m_k
2. Repeat
3. Assign each data object x_i to the cluster which has the closest mean
4. Calculate new mean for each cluster
5. Until convergence criteria is met

K-Means Clustering: Step 1

Algorithm: k-means, Dist:



Euclidean Distance



- Specifies k number of clusters, and guesses the k seed cluster centroid


<https://tutorcs.com>

K-Means Clustering: Step 2

Algorithm: k-means, Dist:



Euclidean Distance



Iteratively looks at each data point and assigns it to the closest centroid


<https://tutorcs.com>

K-Means Clustering: Step 3

Algorithm: k-means, Dist:



Euclidean Distance




Re-calculate the mean (centroid) for each cluster based on the membership of the cluster

K-Means Clustering: Step 4

Algorithm: k-means, Dist:



Euclidean Distance



Iteratively looks at each data point and assigns it to the closest centroid,

Help

Current clusters may receive or lose their members


<https://tutorcs.com>

K-Means Clustering: Step 5

Algorithm: k-means, Dist:



Euclidean Distance



Re-calculate the mean (centroid) for each cluster based on the membership of the cluster

k-Means: Step-By-Step Example



- Data $D = \{5, 19, 25, 21, 4, 1, 6, 10, 2, 20, 14, 11, 27, 9, 3, 16\}$
- Number of clusters: $k = 3$
- Initial centroids: $m_1=6, m_2=8, m_3=18$
- **First Iteration**

Clusters:

- $C_1=\{1, 2, 3, 4, 5, 6\}$
- $C_2=\{7\}$
- $C_3=\{8, 9, 10, 11, 14, 16, 17, 19, 20, 21, 23, 25, 27\}$

WeChat: cstutorcs

Assignment Project Exam Help

Re-calculated centroids $m_1=15, m_2=10$ and $m_3=16.9$

First Iteration: Calculating euclidean distance, determining the cluster membership and calculating new centroid.																				
D	5	19	25	21	4	1	17	23	8	7	6	10	2	20	14	11	27	9	3	16
d(m1, Di)	1	13	19	15	2	5	11	17	2	1	0	4	4	14	8	5	21	3	3	10
d(m2, Di)	2	12	18	14	3	6	10	16	1	0	1	3	5	13	7	4	20	2	4	9
d(m3, Di)	3	11	17	13	4	7	9	15	0	1	2	2	6	12	8	3	19	1	5	8

QQ: 749389476
<https://tutorcs.com>

k-Means: Step-By-Step Example

- Clusters:

$$C_1 = \{1, 2, 3, 4, 5, 6\}$$

$$C_2 = \{7\}$$

$$C_3 = \{8, 9, 10, 11, 14, 16, 17, 19, 20, 21, 23, 25, 27\}$$



- New centroids: $m_1=3.5$, $m_2=7$, and $m_3=16.9$

- **Second Iteration**

Clusters:

- $C_1 = \{1, 2, 3, 4, 5\}$
- $C_2 = \{6, 7, 8, 9, 10, 11\}$
- $C_3 = \{14, 16, 17, 19, 20, 21, 23, 25, 27\}$

Assignment Project Exam Help

Email: tutorcs@163.com

Re-calculated centroids: $m_1=3$, $m_2=8.5$, and $m_3=20.2$

Second Iteration: Calculating euclidean distance, determining the cluster membership and calculating new centroid.

D	5	19	25	21	4	1	17	23	8	7	6	10	2	20	14	11	27	9	3	16
d(m1, Di)	1.5	15.5	21.5	17.5	0.5	2.5	13.5	19.5	4.5	3.5	2.5	6.5	1.5	16.5	10.5	7.5	23.5	5.5	0.5	12.5
d(m2, Di)	2	12	18	14	3	6	10	16	1	0	1	3	5	13	7	4	20	2	4	9
d(m3, Di)	11.9	2.1	8.1	4.1	12.9	15.9	0.1	6.1	3.9	9.9	10.1	6.9	14.9	3.1	2.9	5.9	10.1	7.9	13.9	0.9

QQ: 749389476

<https://tutorcs.com>

k-Means: Step-By-Step Example

- Clusters:

$$C_1 = \{1, 2, 3, 4, 5\}$$

$$C_2 = \{6, 7, 8, 9, 10, 11\}$$

$$C_3 = \{14, 16, 17, 19, 20, 21, 22\}$$



- New centroids: $m_1=3$, $m_2=8.5$, and $m_3=20.2$

- Third Iteration**

- Clusters:

- $C_1 = \{1, 2, 3, 4, 5\}$

- $C_2 = \{6, 7, 8, 9, 10, 11, 14\}$

- $C_3 = \{16, 17, 19, 20, 21, 23, 25, 27\}$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

Re-calculated centroids: $m_1=3$, $m_2=9.29$, and $m_3=21$

Third Iteration: Calculating euclidean distance, determining the cluster membership and calculating new centroid.

D	5	19	25	21	4	1	17	23	8	7	6	10	2	20	14	11	27	9	3	16
d(m1, Di)	2	16	22	18	1	2	14	20	5	4	3	7	1	17	11	8	24	6	0	13
d(m2, Di)	3.5	10.5	16.5	12.5	4.5	7.5	8.5	14.5	0.5	1.5	2.5	1.5	6.5	11.5	5.5	2.5	18.5	0.5	5.5	7.5
d(m3, Di)	15.2	1.2	4.8	0.8	16.2	19.1	3.2	2.8	12.2	13.2	14.2	10.2	18.2	0.2	6.2	9.2	6.8	11.2	17.2	4.2

QQ: 749389476

<https://tutorcs.com>

k-Means: Step-By-Step Example

- Clusters:

$$C_1 = \{1, 2, 3, 4, 5\}$$

$$C_2 = \{6, 7, 8, 9, 10, 11, 14\}$$

$$C_3 = \{16, 17, 19, 20, 21, 23, 24\}$$



- New centroids: $m_1=3$, $m_2=9.29$, and $m_3=21$

- Fourth Iteration**

Clusters:

- $C_1 = \{1, 2, 3, 4, 5, 6\}$

- $C_2 = \{7, 8, 9, 10, 11, 14\}$

- $C_3 = \{16, 17, 19, 20, 21, 23, 25, 27\}$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

Re-calculated centroids: $m_1=3.5$, $m_2=9.83$, and $m_3=21$

Fourth Iteration: Calculating euclidean distance, determining the cluster membership and calculating new centroid.

D	5	19	25	21	4	1	17	23	8	7	6	10	2	20	14	11	27	9	3	16
d(m1, Di)	2	16	22	18	1	2	14	20	5	4	3	7	1	17	11	8	24	6	0	13
d(m2, Di)	4.3	9.7	15.7	11.7	5.3	8.3	7.7	13.7	1.3	2.3	3.3	0.7	7.3	10.7	4.7	1.7	17.7	0.3	6.3	6.7
d(m3, Di)	16.0	2.0	4.0	0.0	17.0	20.0	4.0	2.0	13.0	14.0	15.0	11.0	19.0	1.0	7.0	10.0	6.0	12.0	18.0	5.0

QQ: 749589476

<https://tutorcs.com>

k-Means: Step-By-Step Example



- Clusters:

$$C_1 = \{1, 2, 3, 4, 5\}$$

$$C_2 = \{7, 8, 9, 10, 11\}$$

$$C_3 = \{16, 17, 19, 20, 21, 23, 25, 27\}$$

- New centroids: $m_1 = 3.5, m_2 = 8.83, m_3 = 21$

- **Fifth Iteration**

Assignment Project Exam Help

No data movement from clusters (Process Terminated)

m_1	m_2	m_3	C_1	C_2	C_3
6	7	8	1, 2, 3, 4, 5, 6	7	8, 9, 10, 11, 14, 16, 17, 19, 20, 23, 25, 27
3.5	7	16.9	1, 2, 3, 4, 5	6, 7, 8, 9, 10, 11	14, 16, 17, 19, 20, 21, 23, 25, 27
3	8.5	20.2	1, 2, 3, 4, 5	6, 7, 8, 9, 10, 11, 14	16, 17, 19, 20, 21, 23, 25, 27
3	9.29	21	1, 2, 3, 4, 5, 6	7, 8, 9, 10, 11, 14	16, 17, 19, 20, 21, 23, 25, 27
3.5	9.83	21	1, 2, 3, 4, 5, 6	7, 8, 9, 10, 11, 14	16, 17, 19, 20, 21, 23, 25, 27

QQ: 749389476

<https://tutorcs.com>

Evaluating K-Means Clusters

程序代写代做 CS编程辅导

- One common measure is sum of squared error (SSE)



$$SSE = \sum_{i=1}^K \sum_{x \in C_i} d(x, m_i)^2$$

WeChat: cstutorcs

- x is a data point in cluster C_i
- m_i is the centroid of cluster C_i

Assignment Project Exam Help

Example: How to calculate SSE?

Fifth Iteration: Calculating euclidean distance, determining the cluster membership and calculating new centroid.																				
D	5	19	25	21	4	1	17	23	8	7	6	10	2	20	14	11	27	9	3	16
d(m1, Di)	1.5	15.5	21.5	17.5	0.5	2.5	13.5	19.5	4.5	3.5	2.5	6.5	1.5	16.5	10.5	7.5	23.5	5.5	0.5	12.5
d(m2, Di)	4.8	9.2	15.2	11.2	5.8	8.8	7.2	13.2	1.8	2.8	3.8	0.2	1.8	0.2	4.2	1.2	17.2	0.8	6.8	6.2
d(m3, Di)	16.0	2.0	4.0	0.0	17.0	20.0	4.0	2.0	13.0	14.0	13.0	11.0	19.0	1.0	7.0	10.0	6.0	12.0	18.0	5.0

Clusters:

$C_1 = \{1, 2, 3, 4, 5, 6\}$

$C_2 = \{7, 8, 9, 10, 11, 14\}$

$C_3 = \{16, 17, 19, 20, 21, 23, 25, 27\}$

centroids: $m_1 = 3.5$, $m_2 = 9.83$, and $m_3 = 21$

Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>

22

$$\sum_{x \in C_1} d^2(m_1, x)$$



$$\sum_{x \in C_2} d^2(m_2, x)$$



$$\sum_{x \in C_3} d^2(m_3, x)$$

K-Means Clustering

程序代写代做 CS编程辅导

The number of clusters is predefined. The algorithm does not discover the ideal number of clusters. During the process, the number of clusters remains fixed – it does not shrink nor expand. The final composition of clusters is very sensitive to the choice of initial centroid values. Different initialisations may result in different final clusters composition.

Assignment Project Exam Help

Initial centroids: 6, 7, 8 or 3, 9, 16



Initial centroids: 5, 19, 25



Figure 17.4 Different clustering results for different initial centroids

<https://tutorcs.com>

K-Means Clustering: Pros and Cons

Pros

- Simple and fast for low dimensional data (time complexity of K Means is linear i.e. $O(n)$)
- Scales to large data sets
- Easily adapts to new data points



Cons

- It will not identify outliers
- Restricted to data which has the notion of a centre (centroid)

Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>

K-means clustering



Exercise 1

- Data $D = \{8, 11, 12, 14, 15, 16, 17, 18, 19, 20\}$
- Number of clusters: 3
- Initial centroids: $m_1=11$, $m_2=12$, and $m_3=28$
- Use the k -means *serial* algorithm to cluster the data in three clusters

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Finding Optimal number of the clusters

As k increases, clusters become

The neighbouring clusters become distinct from one another.



How to choose an optimal k?

- Elbow Method

Plot sum of squared errors as a function of k (Elbow plot)

Select the value of k at the "elbow" ie the point after which the SSE start decreasing in a linear fashion.

optimal value for k = 4

- Silhouette analysis


Measure of how close each point in one cluster is compared to points in the neighbouring clusters and provides a way to assess number of clusters.

If most points have a high silhouette value, then the clustering configuration is appropriate.

QQ: 749389476

If many points have a low or negative value, then the clustering configuration may have too many or too few clusters.

<https://tutorcs.com>



WeChat: cstutorcs


Assignment Project Exam Help

Email: tutores@163.com

```
For n_clusters = 2 The average silhouette_score is : 0.7049787496083262
For n_clusters = 3 The average silhouette_score is : 0.5882004012129721
For n_clusters = 4 The average silhouette_score is : 0.6505186632729437
For n_clusters = 5 The average silhouette_score is : 0.56376469026194
For n_clusters = 6 The average silhouette_score is : 0.4504666294372765
```

DEMO

程序代写代做 CS编程辅导




<https://tutorcs.com>

<https://instaview365.com/request-a-demo/>

This week

程序代写代做 CS编程辅导



Chapter 17 Parallel Clustering and Classification

WeChat: cstutorcs

Assignment Project Exam Help

17.1 Clustering and Classification

17.2 Parallel Clustering

17.3 Parallel Classification

17.4 Summary

17.5 Biographical Notes

17.6 Exercises

QQ: 749389476

<https://tutorcs.com>


Parallel K-means clustering

Data parallelism of



- ❑ Create parallelism from the beginning because of partitioning of the dataset.
- ❑ Data is partitioned into multiple partition
- ❑ Each processor will work independently to create three clusters
- ❑ The final clusters from each processor are respectively united

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com
QQ: 749389476



<https://tutorcs.com>

Parallel K-means

程序代写代做 CS编程辅导

Data parallelism

- Example: Data partitioning using rows
- Initial centroids: 6, 7, 8
- Each processor will run k_Means locally
- At the end of each iteration, info about sum & count of data points in each local cluster is shared to calculate new centroid/mean
- Data does not move among processors (it stays where it was allocated initially)
- Data move across clusters within same processor



WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

3

Initial dataset: 5, 19, 25, 21, 4, 1, 17, 23, 8, 7, 6, 10, 2, 20, 14, 11, 27, 9, 3, 16

Processor 1
Data partition 1:
5, 21, 17, 7, 2, 11, 3

Iteration 1
Cluster 1
Mean=6
Dataset=2, 3, 5
Sum=10; Count=3
Cluster 2
Mean=7
Dataset=7
Sum=7; Count=1
Cluster 3
Mean=8
Dataset=11, 17, 21
Sum=49; Count=3

Processor 2
Data partition 2:
19, 4, 23, 6, 20, 27, 16

Cluster 1
Mean=6
Dataset=4, 6
Sum=10; Count=2
Cluster 2
Mean=7
Dataset=NIL
Sum=0; Count=0
Cluster 3
Mean=8
Dataset=16, 19, 20, 23, 27
Sum=105; Count=5

Processor 3
Data partition 3:
25, 1, 8, 10, 14, 9

Cluster 1
Mean=6
Dataset=1
Sum=1; Count=1
Cluster 2
Mean=7
Dataset=NIL
Sum=0; Count=0
Cluster 3
Mean=8
Dataset=8, 9, 10, 14, 25
Sum=66; Count=5

Iteration 2
Cluster 1
Mean=3.5
Dataset=2, 5
Sum=7; Count=3
Cluster 2
Mean=7
Dataset=7, 11
Sum=18; Count=2
Cluster 3
Mean=16.92
Dataset=17, 21
Sum=38; Count=2

Cluster 1
Mean=3.5
Dataset=4
Sum=4; Count=1
Cluster 2
Mean=7
Dataset=6
Sum=6; Count=1
Cluster 3
Mean=16.92
Dataset=16, 19, 20, 23, 27
Sum=105; Count=5

Cluster 1
Mean=3.5
Dataset=1
Sum=1; Count=1
Cluster 2
Mean=7
Dataset=8, 9, 10
Sum=27; Count=3
Cluster 3
Mean=16.92
Dataset=14, 25
Sum=39; Count=2

Parallel K-means

Data parallelism

k-means

Processor 1: Cluster 1 = 2, 3, 5

Cluster 2 = 7, 11

Cluster 3 = 17, 21

Processor 2: Cluster 1 = 4, 6

Cluster 2 = NIL

Cluster 3 = 16, 19, 20, 23, 27

Processor 3: Cluster 1 = 1

Cluster 2 = 8, 9, 10, 14


Cluster 3 = 25

Cluster 1 = 1, 2, 3, 4, 5, 6

Cluster 2 = 7, 8, 9, 10, 11, 14

Cluster 3 = 16, 17, 19, 20, 21, 23, 25, 27

Initial dataset: 5, 19, 25, 21, 4, 1, 17, 23, 8, 7, 6, 10, 2, 20, 14, 11, 27, 9, 3, 16



Parallel K-means clustering

Result Parallelism

- Focuses on clusters partitioning
- Each processor will work on a particular target cluster
- For example, from the very beginning, processor 1 will produce only one cluster assigned to it, that is cluster 1.
- During the iteration, the memberships of cluster can change. -→ data movement across processors



WeChat: cstutorcs


Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

(b) Result Parallelism k -means



Parallel K-means 程序代写代做 CS编程辅导

Result parallelism k-

- Example: Data partitioning using round robin
- Each processor is allocated only one cluster.
- Three initial means are distributed among the three processors.
- Data points may move from one processor to another at each iteration to join a cluster in a different processor
- Since a cluster is processed by one processor, calculating the mean is straightforward because all the data points within a cluster are located at the same processor



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Initial dataset: 5, 19, 25, 21, 4, 1, 17, 23, 8, 7, 6, 10, 2, 20, 14, 11, 27, 9, 3, 16

Processor 1
Data partition 1:
2, 3, 5, 7, 11, 17, 21, 17

Processor 2
Data partition 2:
4, 6, 16, 19, 20, 23, 27

Processor 3
Data partition 3:
1, 8, 9, 10, 14, 25

Iteration 1
Cluster 1
Mean=6
Dataset={1, 2, 3, 4, 5, 6}

Cluster 2
Mean = 7
Dataset={ }

Cluster 3
Mean = 8
Dataset={8, 9, 10, 11, 14, 16, 17, 19, 20, 21, 23, 25, 27}

Iteration 2
Cluster 1
Mean = 3.5
Dataset={1, 2, 3, 4, 5}

Cluster 1
Mean = 7
Dataset={6, 7, 8, 9, 10, 11}

Cluster 3
Mean = 16.9
Dataset={14, 16, 17, 19, 20, 21, 23, 25, 27}

Parallel K-means 程序代写代做 CS编程辅导

Result parallelism k-



At the end, the final cluster result is basically the union of all local clusters from each processor.

Processor 1 cluster 1 = 1, 2, 3, 4, 5, 6

Processor 2 cluster 2 = 7, 8, 9, 10, 11, 14

Processor 3 cluster 3 = 16, 17, 19, 20, 21, 23, 25, 27

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

al dataset: 5, 19, 25, 21, 4, 1, 17, 23, 8, 7, 6, 10, 2, 20, 14, 11, 27, 9, 3, 16

Processor 1

Data partition 1:
2, 3, 5, 7, 11, 17, 21, 17

Iteration 1

Cluster 1

Mean=6

Dataset=1, 2, 3, 4, 5, 6

Processor 2

Data partition 2:
4, 6, 16, 19, 20, 23, 27

Iteration 1

Cluster 2

Mean = 7

Dataset = 7

Processor 3

Data partition 3:
1, 8, 9, 10, 14, 25

Iteration 1

Cluster 3

Mean = 8

Dataset = 8, 9, 10, 11, 14, 16, 17, 19, 20, 21, 23, 25, 27

<https://tutorcs.com>

What have we learnt today?



Partitional (k-means) clustering of data
Algorithmic example

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>