

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Overview

程序代写代做 CS编程辅导

- Example of a parallel partitioning algorithm for numerical computation.

- Note: This lecture include has a demonstration. Hence, although the content of the notes may be simple, additional computing resources are enclosed with this lecture notes in Moodle.



WeChat: cstutorcs

Learning outcome(s) related to this topic

Assignment Project Exam Help

Email: tutorcs@163.com

- Design and develop parallel algorithms for various parallel computing architectures (LO3)

QQ: 749389476

<https://tutorcs.com>

Numerical Integration

程序代写代做 CS编程辅导

- A general divide-and-conquer technique divides the region continually into parts until it meets some optimization function decide when certain regions are sufficiently divided. Let us take an example, i.e., numerical integration.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Numerical Integration

程序代写代做 CS编程辅导



$$\int_a^b f(x)dx$$

- ❑ To integrate the function (i.e., to compute the ‘area under the curve’), we can divide the area into separate parts, each of which can be calculated by a separate process.
- ❑ Each region could be approximated using an approximation given by rectangle, where $f(p)$ and $f(q)$ are the heights of the two edges of the rectangular region and c is the width (interval).
- ❑ The complete integration can be approximated by the summation of rectangular regions from a to b by aligning the rectangles so that the upper midpoint each rectangle intersect with the function. This has the advantage that errors on each side of midpoint end tend to cancel.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorms@163.com

QQ: 749389476


https://tutorms.com

Numerical Integration

程序代写代做 CS编程辅导
(Rectangles)



- Each region under the curve is calculated using an approximation given by rectangles which are aligned.



Numerical Integration (Trapezoid)



- Here we take the intersections of the lines with the function to form trapezoidal regions as shown in the fig.

WeChat: cstutorcs

- Each region is now calculated as $\frac{1}{2}(f(p) + f(q))\Delta x$

Assignment Project Exam Help

- Such approximate numerical methods for computing a definite integral using linear combination of values are called **quadrature methods**

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

Numerical Integration (Trapezoid)



$$\frac{1}{2} (f(p) + f(q)) \delta$$



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Numerical Integration

程序代写代做CS编程辅导
(Trapezoid)

❑ Let us consider a trapezoidal method.

❑ Prior to start of the integration, one process is statically assigned to be responsible for computing each region. By making the interval smaller, we come closer to attaining the exact solution.



WeChat: cstutorcs

❑ Since each calculation is of the same form, the single process multiple data (SPMD) model is appropriate (i.e., data parallelism).

Assignment Project Exam Help

Email: tutorcs@163.com

❑ Suppose we were to sum the area from $x=a$ to $x=b$ using p processes, numbered 0 to $p-1$. The size of the region for each process is $(b-a)/p$. To calculate the area in the described manner, a section of SPMD pseudo-code could be as follows

QQ: 749389476

<https://tutorcs.com>

Numerical Integration – Trapezoid

(Basic pseudocode)

程序代写代做 CS编程辅导

Process P_i

```
if (i == master) {
    printf("Enter number of intervals required ");
    scanf("%d",&n);
}
bcast(&n, P_group);
region = (b - a)/p;
start = a + region * i;
end = start + region;
d = (b - a)/n;
area = 0.0;
for (x = start; x < end; x = x + d)
    area = area + f(x) + f(x+d);
area = 0.5 * area * d;
reduce_add(&integral, &area, P_group);
```



/* read number of intervals required */

/* length of region for each process */

/* starting x coordinate for process */

/* ending x coordinate for process */

/* size of interval */

/* form sum of areas */

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A reduce operation is used to add the areas computed by the individual processes.

Numerical Integration – Trapezoid

(Basic pseudocode)
程序代写代做CS编程辅导

- Please refer to the drawings and code with this lecture notes for further explanation on partitioning and parallel code for numerical integration.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

References

程序代写代做 CS编程辅导



Wilkinson .B, Allen .D, Chapter 4: Partitioning and Divide-And-Conquer Strategies , in *Parallel Programming – Techniques and Applications Using Networked Workstations and Parallel Computers*, Pearson Education Inc., 2005, pp. 122 – 126.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>