

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

ANANTH GRAMA • ANSHUL GUPTA

GEORGE KARYPIS • VIPIN KUMAR

Topic Overview

程序代写代做 CS编程辅导



Introduction to

Parallel Computing

Second Edition

- Matrix Algorithms & Problem Statement
- Decomposition
- Decomposition – Fox's method

WeChat: cstutorcs

A portion of the content in the following slides were created by:

Assignment Project Exam Help

a) Gergel V.P., Nizhni Novgorod, **Introduction to Parallel Programming: Matrix Multiplication**, 2005.

Email: tutorcs@163.com

QQ: 749389476

b) Ananth Grama, Anshul Gupta, George Karypis, and Vipin Kumar, **Introduction to Parallel Computing**, Addison Wesley, 2003.

<https://tutorcs.com>

Matrix Algorithms: Introduction



- Due to their regular structure, parallel computations involving matrices and vectors readily lend themselves to data-decomposition.
- Typical algorithms rely on input, output, or intermediate data decomposition.
- Most algorithms use one- and two-dimensional block, cyclic, and block-cyclic partitionings.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Problem Statement

Matrix multiplication:

or



$A \cdot B$

$$\begin{pmatrix} c_{0,0} & c_{0,1} & \dots & c_{0,l-1} \\ \vdots & \vdots & \ddots & \vdots \\ c_{m-1,0} & c_{m-1,1} & \dots & c_{m-1,l-1} \end{pmatrix} = \begin{pmatrix} a_{0,0} & a_{0,1} & \dots & a_{0,n-1} \\ \vdots & \vdots & \ddots & \vdots \\ a_{m-1,0} & a_{m-1,1} & \dots & a_{m-1,n-1} \end{pmatrix} \begin{pmatrix} b_{0,0} & b_{0,1} & \dots & b_{0,l-1} \\ \vdots & \vdots & \ddots & \vdots \\ b_{n-1,0} & b_{n-1,1} & \dots & b_{n-1,l-1} \end{pmatrix}$$

WeChat: cstutorcs

The matrix multiplication problem can be reduced to the execution of $m \cdot l$ independent operations of matrix A rows and matrix B columns inner product calculation

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

$$c_{ij} = (a_i, b_j^T) = \sum_{k=0}^{n-1} a_{ik} \cdot b_{kj}, \quad 0 \leq i < m, \quad 0 \leq j < l$$

<https://tutorcs.com>

Data parallelism can be exploited to design parallel computations

Sequential Algorithm

```
// Sequential algorithm for matrix multiplication
```

```
double MatrixA[Size];
```

```
double MatrixB[Size];
```

```
double MatrixC[Size];
```

```
int i,j,k;
```

```
...
```

```
for (i=0; i<Size; i++)
```

```
    for (j=0; j<Size; j++){
```

```
        MatrixC[i][j] = 0;
```

```
        for (k=0; k<Size; k++){
```

```
            MatrixC[i][j] = MatrixC[i][j] + MatrixA[i][k]*MatrixB[k][j];
```

```
        }
```

```
    }
```

```
}
```



WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Sequential Algorithm

- Algorithm performs matrix C rows calculation sequentially
- At every iteration after loop on i variable a single row of matrix A and all columns of matrix B are processed



- $m \cdot l$ inner products are calculated to perform the matrix multiplication
- The complexity of the matrix multiplication is $O(mnl)$.

Block-Striped Composition

- **A fine-grained task** – the basic subtask is calculation of element of matrix **C**



$$c_{ij} = (a_i, b_j^T), \quad a_i = (a_{i0}, a_{i1}, \dots, a_{in-1}), \quad b_j^T = (b_{0j}, b_{1j}, \dots, b_{n-1j})^T$$

WeChat: cstutorcs

- Number of basic subtasks is equal to n^2 .
- As a rule, the number of available processors is less than n^2 ($p < n^2$), so it will be necessary to perform the subtask scaling

<https://tutorcs.com>


Block-Striped Decomposition

程序代写代做 CS编程辅导


- **The aggregated subtask** – the calculation of one row of matrix (number of subtasks is n)
- **Data distribution** – rowwise block-striped decomposition for matrix **A** and columnwise block-striped decomposition for matrix **B**

微信: cs_tutorcs

A



B



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Block-Striped Decomposition

程序代写代做 CS编程辅导

Analysis of Informal Dependencies



Each subtask holds one row of matrix **A** and one column of matrix **B**,

- At every iteration each subtask performs the inner product calculation of its row and column, as a result the corresponding element of matrix **C** is obtained
- Then every subtask i , $0 \leq i < n$, transmits its column of matrix **B** for the subtask with the number $(i+1) \bmod n$.

QQ: 749389476

After all algorithm iterations all the columns of matrix **B** were come within each subtask one after another

Block-Striped Decomposition

程序代写代做 CS编程辅导

Aggregating and Distributing the Subtasks among the Processors:



- In case when the number of processors p is less than the number of basic subtasks, calculations can be aggregated in such a way that each processor would execute several inner products of matrix A rows and matrix B columns. In this case after the completion of computation, each aggregated basic subtask determines several rows of the result matrix C .
- Under such conditions the initial matrix A is decomposed into p horizontal stripes and matrix B is decomposed into p vertical stripes.
- Subtasks distribution among the processors have to meet the requirements of effective representation of the ring structure of subtask information dependencies.

WeChat: TutorCS

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<http://tutorcs.com>

Block-Striped Decomposition

程序代写代做 CS编程辅导

Efficiency Analysis

– Speed-up and efficiency generalized estimates



$$S_p = \frac{n^3}{(n^3/p)} = p \quad E_p = \frac{n^3}{p \cdot (n^3/p)} = 1$$

WeChat: cstutorcs
Assignment Project Exam Help

Developed method of parallel computations allows
to achieve ideal speed-up and efficiency characteristics


Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>

Block-Striped Decomposition

程序代写代做 CS编程辅导

- Another possible approach for the data distribution is the row-wise block-striped decomposition



<https://tutorcs.com>

Block-Striped Decomposition

程序代写代做 CS编程辅导

Analysis of Information Dependencies

- Each subtask i performs one row of matrix A and one row of matrix B ,
- At every iteration the subtasks perform the element-to-element multiplications of the rows; as a result the row of partial results for matrix C is obtained.
- Then every subtask i , $0 \leq i < n$, transmits its row of matrix B for the subtask with the number $(i+1) \bmod n$.

QQ: 749389476

After all algorithm iterations all rows of matrix B were
come within every subtask one after another



WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

<https://tutorcs.com>

Block-Striped Decomposition – Fox's method

程序代写代做 CS编程辅导

Data distribution  **keyboard scheme**



WeChat: cstutorcs

Assignment Project Exam Help

Basic subtask is a procedure, that calculates all elements of one block of matrix **C**

Email: tutores@163.com

QQ: 749389476

<https://tutorcs.com>

$$\begin{pmatrix} A_{00} & A_{01} & \dots & A_{0q-1} \\ \vdots & \vdots & \ddots & \vdots \\ A_{q-10} & A_{q-11} & \dots & A_{q-1q-1} \end{pmatrix} \times \begin{pmatrix} B_{00} & B_{01} & \dots & B_{0q-1} \\ \vdots & \vdots & \ddots & \vdots \\ B_{q-10} & B_{q-11} & \dots & B_{q-1q-1} \end{pmatrix} = \begin{pmatrix} C_{00} & C_{01} & \dots & C_{0q-1} \\ \vdots & \vdots & \ddots & \vdots \\ C_{q-10} & C_{q-11} & \dots & C_{q-1q-1} \end{pmatrix}, \quad C_{ij} = \sum_{s=0}^{q-1} A_{is} B_{sj}$$

Block-Striped Decomposition – Fox's method

程序代写代做 CS编程辅导

Analysis of Information Dependencies



- Subtask with (i,j) calculates the block \mathbf{C}_{ij} of the result matrix \mathbf{C} . As a result, subtasks form the $q \times q$ two-dimensional grid,
- Each subtask holds 4 matrix blocks.
 - block \mathbf{C}_{ij} of the result matrix \mathbf{C} , which is calculated in the subtask,
 - block \mathbf{A}_{ij} of matrix \mathbf{A} , which was placed in the subtask before the calculation starts,
 - blocks \mathbf{A}_{ij}' and \mathbf{B}_{ij}' of matrix \mathbf{A} and matrix \mathbf{B} , that are received by the subtask during calculations.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Block-Striped Decomposition – Fox's method

程序代写代做 CS编程辅导

Analysis of Information Dependencies – during iteration l , $0 \leq l < q$, algorithm performs

- The subtask (i, j) transmits its block A_{ij} of matrix A to all subtasks of the same horizontal row in the grid; the j index, which determines the position of the subtask in the row, can be obtained using equation:

$$j = (j + l) \bmod q,$$

where \bmod operation is the procedure of calculating the remainder of integer-valued division.

- Every subtask performs the multiplication of received blocks A_{ij}' and B_{ij}' and adds the result to the block C_{ij}

Email: tutorcs@163.com

$$C_{ij} = C_{ij} + A_{ij}' \times B_{ij}'$$


- Every subtask (i, j) transmits its block B_{ij}' to the neighbor, which is previous in the same vertical line (the blocks of subtasks of the first row are transmitted to the subtasks of the last row of the grid).

<https://tutorcs.com>

Block-Striped Decomposition – Fox's method

程序代写代做 CS编程辅导

Scheme of Information Dependences



Block-Striped Decomposition – Fox's method

程序代写代做 CS编程辅导

Scaling and Distributing the Subtasks among the Processors



- The sizes of the blocks can be selected so that the number of subtasks will coincide with the number of available processors p ,
WeChat: cstutorcs
- The most efficient execution of the parallel Fox's algorithm can be provided when the communication network topology is a two-dimensional grid,
Assignment Project Exam Help
Email: tutorcs@163.com
- In this case the subtasks can be distributed among the processors in a natural way: the subtask (i,j) has to be placed to the $p_{i,j}$ processor
QQ: 749389476
<https://tutorcs.com>

Block-Striped Decomposition – Fox's method

程序代写代做 CS编程辅导

Scaling and Distributing the Subtasks among the Processor



- The sizes of the blocks can be selected so that the number of subtasks will coincide with the number of available processors p ,
- The most efficient execution of the parallel Fox's algorithm can be provided when the communication network topology is a two-dimensional grid,
- In this case the subtasks can be distributed among the processors in a natural way: the subtask (i,j) has to be placed to the p_{ij} processor

WeChat: tutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<http://tutorcs.com>

In depth discussion & example

程序代写代做 CS编程辅导



- Please refer to the related report attached with these slides, “*Design and Implementation of Parallel Matrix Multiplication Algorithms using Message Passing Interface*” by Chin-Kit Ng for further in-depth discussion and code examples.

WeChat: cstutorcs

- Serial matrix multiplication example
- Bernstein analysis for data dependency
- Parallel matrix multiplication examples using POSIX and MPI

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>