

Logic and AI Programming:

Introduction to Logic

Introduction to Prolog

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Autumn Term

October – December

Course Material

Course material will be available via CATE,
including: **Assignment Project Exam Help**

- ✓ Notes **<https://tutorcs.com>**
- ✓ Tutorial Exercises **WeChat: cstutorcs**
- ✓ Tutorial Exercise Solutions
- ✓ Coursework

CONTENTS

Introduction to logic

Propositional logic

- Syntax
- Semantics (Truth Tables)
- Rules of inference (Natural Deduction)

Predicate logic

- Syntax
- Informal semantics
- Rules of inference (Natural Deduction)

Prolog programming

Time permitting: Probabilistic Prolog or
Abductive Reasoning



Books

background reading on logic

Assignment Project Exam Help

- Any book on logic will have useful examples.
- Richard Spencer-Smith, Logic and Prolog,
Harvester Wheatsheaf, (The library has a
number of copies)
<https://tutorcs.com>
WeChat: cstutorcs
- Jim Woodcock and Martin Loomes, Software Engineering Mathematics”, Pitman Publishing



Books

Prolog



- Ivan Bratko, "Prolog programming for artificial intelligence", Addison-Wesley, Third Edition, 2001 and later.

WeChat: cstutorcs

Assessments and Examination

- One Logic Coursework
- One Prolog Lab Assessment
- One Examination in May:

Paper M1 (Program Design and Logic) will have:

- two questions on Logic and
- two questions on Object-Oriented Design

Relevance of this course to Spring Term Modules

- Logic-based Learning course
- Introduction to Artificial Intelligence
- System Verification
- Argumentation and Multi-Agent Systems

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

and to a lesser extent


- Databases
 - Database languages, e.g. relational calculus and some features of SQL
 - Datalog: emerging e.g. in data integration, information extraction, network monitoring, security and cloud computing

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Logic has many applications in computing



For example:

- Basis of a family of programming languages, e.g. **Prolog**, **ASP (Answer Set Programming)**.
<https://tutorcs.com>
WeChat: cstutorcs
- Basis of verification tools to reason about C, Java and JavaScript programs, and algorithms for concurrency, e.g. using **Separation Logic**.

- Software engineering: Formal specifications and formal verification of programs.

Assignment Project Exam Help

How do you make sure a program is
“correct”? <https://tutorcs.com>

WeChat: cstutorcs

Review, again and again and

- Review the spec
- Review the design description
- Review the code

Test, again and again and

- Unit testing
- Integration testing
- Validation testing

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

But that is not enough.

How many tests do you run to be sure the system is correct?

- ✓ Logic provides a way of proving the system correct and
- ✓ this can be automated too.



Logic is also useful more generally in life

- Clear thinking
- Judging validity of arguments and justification of conclusions
- Spotting inconsistencies
- Awareness and avoidance of ambiguities of natural language

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: tutorcs



Which of the following arguments are valid?



➤ Advertisement for a computing book: If you don't use computers you don't need this book. But you are a person who uses computers. So you need this book.

Assignment Project Exam Help
<https://tutorcs.com>
WeChat: cstutorcs

➤ If you work hard you will succeed. So if you do not succeed you have not worked hard.

Which of the following arguments are valid?

- Heard in a radio interview with a well-known politician. All our problems have come from the EU. So nothing good has resulted for us from our membership of the EU.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

More reasoning exercises

1. All the trees in the park are flowering trees.
2. Some of the trees in the park are dogwoods.
3. All dogwoods in the park are flowering trees.

If the first two statements are true, the third statement is

<https://tutorcs.com>

WeChat: cstutorcs

- A. true
- B. false
- C. uncertain



More reasoning exercises

- Assignment Project Exam Help
<https://tutorcs.com>
WeChat: cstutorcs
1. All the tulips in Zoe's garden are white.
 2. All the roses in Zoe's garden are yellow.
 3. All the flowers in Zoe's garden are either white or yellow

If the first two statements are true, the third statement is

- A. true
- B. false
- C. uncertain

More reasoning exercises

Fact 1: All dogs like to run.

Fact 2: Some dogs like to swim.

Fact 3: Some dogs look like their owners.

If these three statements are facts, which of the following statements must also be a fact?

- I. All dogs who like to swim look like their owners.
 - II. Dogs who like to swim also like to run.
 - III. Dogs who like to run do not look like their owners.
- A. I only
 - B. II only
 - C. II and III only
 - D. None of the statements is a known fact.

Some arguments – Are they valid?

- It has been proven that all heroin addicts smoked marijuana in their youth. Therefore, smoking marijuana leads to heroin addiction. <https://tutorcs.com> WeChat: cstutorcs
- We cannot win the war on poverty without spending money. So if we do spend money we will conquer poverty.

Another argument – Is it valid?

- One of the old arguments of tobacco spokesmen against the claim that smoking causes lung cancer: Lung cancer is more common among male smokers than it is among female smokers. If smoking were the cause of lung cancer, this would not be true. The fact that lung cancer is more common among male smokers means that it is caused by something in the male make-up. It follows that lung cancer is not caused by smoking, but something in the male make-up.

Propositional Logic

- A good place to start.
- It is the core of many logics.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Components of a logic

- Language:
 - alphabet : symbols
 - syntax : rules for putting together the symbols to make grammatically correct sentences.
- Semantics:
 - meaning of the symbols and the sentences.
- Inference rules

The Propositional Language: Alphabet

- **Propositional symbols**

e.g. use `_computers`, `_need_book`, `p`, `q`, `r`, `s`, `p1`

- **Logical connectives:**

\wedge : and (conjunction)

\vee : (inclusive) or (disjunction)

\neg : not (negation)

sometimes denoted as \sim

\rightarrow : implication (if-then)

\leftrightarrow : double implication (if and only if)

The Propositional Language:

Syntax of a grammatically correct sentence

(well formed formula, wff)

- A propositional symbol is a wff.
- If W , W_1 and W_2 are wffs then so are
 - $\neg(W)$ sometimes written as $\sim(W)$
 - $(W_1 \wedge W_2)$
 - $(W_1 \vee W_2)$
 - $(W_1 \rightarrow W_2)$ $(W_2 \leftarrow W_1)$
 - $(W_1 \leftrightarrow W_2)$
- There are no other wffs.

Examples

Suppose p, q, r, s, t are propositions. Then:

$(p \rightarrow q)$ is a wff

$(r \wedge \vee t)$ is not a wff

$(p \neg \rightarrow q)$ is not a wff

$((p \rightarrow q) \vee ((p \wedge r) \rightarrow \neg(s)))$ is a wff

$((p \rightarrow q) \vee ((p \wedge r) \rightarrow \neg(s)))$

Draw a *parse tree*.

Examples

Passing the exams and the project implies passing the MSc.

Assignment Project Exam Help

$(\text{pass_exams} \wedge \text{pass_proj}) \rightarrow \text{pass_MSc}$

WeChat: cstutorcs

You do not pass the MSc and you do not get a certificate if you do not pass the exams or you do not pass the project.

$(\neg \text{pass_MSc} \wedge \neg \text{get_certificate}) \rightarrow (\neg \text{pass_exams} \vee \neg \text{pass_proj})$

Exercise

Formulate the first two arguments from the beginning of the notes.

- Advertisement <https://tutorcs.com> book: If you don't use computers you don't need this book. But you are a person who uses computers. So you need this book.
- If you work hard you will succeed. So if you do not succeed you have not worked hard.

Some notes on simplifying syntax

- To avoid ending up with a large number of brackets one can drop the outermost brackets. <https://tutorcs.com>

WeChat: cstutorcs

Examples:

$(p \rightarrow q)$ can be written as $p \rightarrow q$

$((p \rightarrow q) \vee r)$ can be written as $(p \rightarrow q) \vee r$.

- “ \neg ” binds more closely than the other connectives. This can be used to drop some brackets. <https://tutorcs.com>

WeChat: cstutorcs

Example

$(\neg (p) \wedge q) \rightarrow t$ can be written as

$(\neg p \wedge q) \rightarrow t$

- \wedge and \vee bind more closely than \rightarrow and \leftrightarrow . This can be used to drop some brackets.

Examples:

$(\neg p \wedge q) \rightarrow t$ can be written as $\neg p \wedge q \rightarrow t$.

$(p \wedge q) \rightarrow (r \vee s)$ can be written as $p \wedge q \rightarrow r \vee s$.

Binding Strength of the Connectives

To avoid having to use many brackets, there is
a convention of ordering the connectives.


Assignment Project Exam Help

<https://tutorcs.com>

Also : WeChat: cstutorcs

- Order of precedence
- Binding priority

Binding Strength of the Connectives



Binding conventions: Examples

- $p \vee q \wedge r$ is understood as $p \vee (q \wedge r)$
- $\neg p \vee q$ is understood as $(\neg p) \vee q$
- $p \rightarrow q \leftrightarrow r$ is understood as $(p \rightarrow q) \leftrightarrow r$

I prefer the first and third bracketed versions.

They are more clear, and having a few brackets is not much of a burden! Please don't write unreadable formulas like

$$p \vee \neg q \rightarrow \neg r \leftrightarrow \neg \neg s \wedge t \vee \neg u$$

Use brackets to remove ambiguity

Example:

$P \rightarrow Q \rightarrow R$ Assignment Project Exam Help

is ambiguous. <https://tutorcs.com>

In general WeChat: cstutorcs

$P \rightarrow (Q \rightarrow R)$

and

$(P \rightarrow Q) \rightarrow R$

are not equivalent (do not have the same meaning).

Binding conventions

So $p \rightarrow q \rightarrow r$
is a problem.

It needs brackets to disambiguate it.

WeChat: cstutorcs

But $p \wedge q \wedge r$ and $p \vee q \vee r$
are fine (to be discussed later).

Exercise:

Which of the following are wffs?


Assume

p, q, r, sad, happy,
tall, rich, work_hard,
steal, borrow, and possess
are propositional symbols.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



- $\text{rich} \rightarrow \text{happy}$
- $(p \vee q) \wedge (r \rightarrow p)$
- $p \vee \rightarrow q$
- $\text{sad} \rightarrow \neg \text{happy}$
- $\neg \text{happy} \leftarrow \text{sad}$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- $\text{rich} \rightarrow \neg\neg\text{happy}$
- $\text{rich} \leftrightarrow (\text{work_hard} \vee \text{steal})$
- $(\text{steal} \wedge \vee \text{borrow}) \rightarrow \text{possess}$
- $(\text{steal} \vee \text{borrow}) \rightarrow \text{possess}$
- $\text{steal} \vee \text{borrow} \rightarrow \text{possess}$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- $(p \wedge q \rightarrow r) \wedge (\neg p \rightarrow \neg q)$

- $p \rightarrow \neg p$

- $p \wedge \neg p$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

We will look at

➤ *Parse trees* Assignment Project Exam Help

➤ *Principle of connectives* <https://tutorcs.com>

➤ *Subformulas* WeChat: cstutorcs

in the lecture.

Notes on terminology

- \neg is a **unary** operator.
- The other connectives are **binary** operators.
- $X \vee Y$ is called the **disjunction** of **X** and **Y**.
- $X \vee Y$ X and Y are **disjuncts**.
- $X \wedge Y$ is called the **conjunction** of **X** and **Y**.
- $X \wedge Y$ X and Y are **conjuncts**.
- $\neg X$ is called the **negation** of **X**.

Notes on terminology cntd.

- $A \rightarrow B$ is called an implication.
Assignment Project Exam Help
A is called the antecedent,
<https://tutores.com>
B is called the consequent.
WeChat: cstutorcs

A *Literal* is a proposition or the negation of a proposition.

Semantics

Provides

- The meaning of the simple (atomic) units
- Rules for putting together the meaning of the atomic units to form the meaning of the complex units (sentences).

Semantics specifies under what circumstances a sentence is *true* or *false*.

T (truth) and

F (falsity)

are known as **truth values**.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Constructing Truth Tables for the connectives

Assignment Project Exam Help	
https://tutorcs.com	
T	F
WeChat: cstutorcs	
F	T

A	B	$A \wedge B$
T	T	T
T	F	F
F	T	F
F	F	F

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example

Assignment Project Exam Help

John is not happy, but he is comfortable.

WeChat: cstutorcs

Represent as $\neg h \wedge c$

Four possible cases

Example cntd.

h	c	$\neg h$	$\neg h \wedge c$
T	T	F	F
T	F	F	F
F	T	T	T
F	F	T	F

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

A	B	$A \vee B$
T	T	T
T	F	T
F	T	T
F	F	F

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

A	B	$A \rightarrow B$
T	T	T
T	F	F
F	T	T
F	F	T

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Compare \wedge with \rightarrow

A	B	$A \wedge B$
T	T	T
T	F	F
F	T	F
F	F	F

A	B	$A \rightarrow B$
T	T	T
T	F	F
F	T	T
F	F	T

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

A	B	$A \leftrightarrow B$
T	T	T
T	F	F
F	T	F
F	F	T

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Note

For any wffs A and B, " $A \leftrightarrow B$ " is true exactly when A and B have the same truth values, i.e. when they are both true or both false.

WeChat: cstutorcs

The truth value of a wff is uniquely
determined by the truth value of its
components

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example:

The truth table for the wff $(p \vee q) \wedge (r \rightarrow p)$
is as follows:

p	q	r	$p \vee q$	$r \rightarrow p$	$(p \vee q) \wedge (r \rightarrow p)$
T	T	T	T	T	T
T	T	F	T	T	T
T	F	T	T	T	T
T	F	F	T	T	T
F	T	T	T	F	F
F	T	F	T	T	T
F	F	T	F	F	F
F	F	F	F	T	F

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Exercise:

How many rows will there be in a truth table
for a wff containing n propositional
symbols?

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

2^n



Exercise:

Recall we said the two wffs

$P \rightarrow (Q \rightarrow R)$ and $(P \rightarrow Q) \rightarrow R$

$(P \rightarrow Q) \rightarrow R$

in general do not have the same meaning.

Under which interpretation(s) do the truth values of the two wffs differ?

Notes

The connective “ \vee ” stands for *inclusive or*, i.e.

$p \vee q$ is interpreted as true when either proposition is true or both are.

<https://tutorcs.com>

Often in English when we use “or” we intend *exclusive or*, e.g.

- I’ll go shopping *or* I’ll stay at home.
- We will meet at his house *or* at the club.

Notes cntd.

In this propositional language there is no connective for exclusive or, but we can still express the concept, e.g.

$$(\text{goShopping} \vee \text{stayHome}) \wedge \neg(\text{goShopping} \wedge \text{stayHome})$$

In general “ $p \text{ xor } q$ ” can be represented as:

$$(p \vee q) \wedge \neg(p \wedge q)$$

Exercise:

Draw the truth table of the first wff above.

A	B	$A \vee B$	$\neg(A \wedge B)$	$A \text{ xor } B$
				$(A \vee B) \wedge \neg(A \wedge B)$
T	T	T	F	F
T	F	T	T	T
F	T	T	T	T
F	F	F	T	F

Notes cntd.

- Law of excluded middle:

A proposition (and consequently a *Well*) is either true or false – there is no middle ground, no "unknown". <https://tutorcs.com>

- So propositional *Well* is a *2-valued* logic.
- There are other logics, including *3-valued* ones.
- SQL, for example, implements 3-valued logic, where comparisons with NULL, including that of another NULL gives *UNKNOWN*.

Example NULL Values

Table T of people and their hair colours:

<u>Name</u>	<u>Hat Size</u>	<u>Hair Colour</u>
Helen	NULL	Brown
John	Medium	Red
Tom	Large	NULL

Select Name

From T

Where Hat Size=Large AND Hair Colour \neq Brown

A	B	$A \vee B$
T	T	T
T	F	T
F	T	T
F	F	F
T	U	T
U	T	T
F	U	U
U	F	U
U	U	U

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- A proposition (and consequently a wff) cannot be both true and false.

<https://tutorcs.com>

Exercise:

WeChat: cstutorcs

Draw the truth table for $A \wedge \neg A$.

A	$\neg A$	$A \wedge \neg A$
T	F	F
F	T	F

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes cntd.

- The interpretation of “ \rightarrow ” may be unintuitive sometimes.
- The semantics of “ \rightarrow ” is very simple in logic. <https://tutorcs.com>
[Assignment Project Exam Help](#)
- $A \rightarrow B$ is simply the same as $\neg A \vee B$.
[WeChat: estutorcs](#)
- In English we use “if .. then” in many different ways, and sometimes quite confusingly.
- Don't read $A \rightarrow B$ as “A causes B”.

Some definitions

Definition :

A wff which is true in every interpretation of its constituent parts is called a **tautology**.

<https://tutorcs.com>

Example $A \vee \neg A$

$A \rightarrow A$

The two wffs above represent the **Law of excluded middle**.

A	$\neg A$	$A \vee \neg A$
T	F	T
F	T	T

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Definition

A wff which evaluates to false in every interpretation of its constituent parts is called an **inconsistency (contradiction)**, or is said to be **inconsistent**.

Example

$$A \wedge \neg A$$

Definition

A wff which is neither a tautology, nor an inconsistency is a **contingency**, or is said to be **contingent**.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Exercise

For each of the following determine if it is a tautology, inconsistency or contingency by drawing the truth table.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

a. $P \wedge (P \vee Q)$


b. $(P \vee Q) \wedge (P \rightarrow Q)$

c. $Q \wedge \neg P \wedge (P \vee (Q \rightarrow P))$

d. $(P \wedge (Q \vee P)) \leftrightarrow P$

e. $(P \rightarrow Q) \rightarrow (\neg P \vee Q)$

f. $((P \rightarrow Q) \wedge (R \rightarrow S) \wedge (P \vee R)) \rightarrow (Q \vee S)$



Definition: Equivalence

Two wffs are **equivalent** iff their truth values are the same under every interpretation.

<https://tutorcs.com>

A is equivalent to B is represented as
 $A \equiv B$.

" \equiv " is the metasymbol for equivalence.

Some useful equivalences

Double Negation Rule

$$\neg\neg A \equiv A$$

<https://tutorcs.com>

Implication Rule

$$A \rightarrow B \equiv \neg A \vee B$$

Some useful equivalences

Commutative Rules

$$A \wedge B \equiv B \wedge A$$

$$A \vee B \equiv B \vee A$$

Associative Rules

$$(A \wedge B) \wedge C \equiv A \wedge (B \wedge C)$$

$$(A \vee B) \vee C \equiv A \vee (B \vee C)$$

Some useful equivalences

Idempotence

Assignment Project Exam Help

$$A \wedge A \equiv A$$

<https://tutorcs.com>

$$A \vee A \equiv A$$

WeChat: cstutorcs

Some useful equivalences

Distributive Rules

$$A \vee (B \wedge C) \equiv (A \vee B) \wedge (A \vee C)$$

$$A \wedge (B \vee C) \equiv (A \wedge B) \vee (A \wedge C)$$

WeChat: cstutorcs

De Morgan's Rules

$$\neg(A \vee B) \equiv \neg A \wedge \neg B$$

$$\neg(A \wedge B) \equiv \neg A \vee \neg B$$

Some useful equivalences

$$A \leftrightarrow B \equiv$$

$$(A \rightarrow B) \wedge (B \rightarrow A)$$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Some useful equivalences

$A \wedge B \equiv B$ if ????

Assignment Project Exam Help


$A \wedge B \equiv B$ if A is a tautology

<https://tutorcs.com>
WeChat: cstutorcs

$A \vee B \equiv B$ if ????

$A \vee B \equiv B$ if A is an inconsistency

Exercise



Show

$$A \rightarrow B \equiv \neg(A \wedge \neg B)$$

<https://tutorcs.com>

Example

WeChat: cstutorcs

$$\begin{aligned} \text{I get an MSc} \rightarrow \text{I get big salary} &\equiv \\ \neg(\text{I get an MSc} \wedge \neg \text{I get big salary}) & \end{aligned}$$

Exercises

Show

$$A \leftrightarrow B \equiv (A \wedge B) \vee (\neg A \wedge \neg B)$$

<https://tutorcs.com>

Show

WeChat: cstutorcs

$$A \leftrightarrow B \equiv \neg A \leftrightarrow \neg B$$

Showing $A \leftrightarrow B \equiv \neg A \leftrightarrow \neg B$

$$\text{LHS} \equiv (A \rightarrow B) \wedge (B \rightarrow A)$$

$$\text{RHS} \equiv (\neg A \rightarrow \neg B) \wedge (\neg B \rightarrow \neg A)$$

$$\equiv (\neg B \rightarrow \neg A) \wedge (\neg A \rightarrow \neg B) \quad \text{commutativity of } \wedge$$

WeChat: cstutorcs

Compare LHS with RHS:

$$\text{LHS} \equiv (A \rightarrow B) \quad \wedge \quad (B \rightarrow A)$$

|

|

$$\text{RHS} \equiv (\neg B \rightarrow \neg A) \quad \wedge \quad (\neg A \rightarrow \neg B)$$

And both correspondences are an instance of one equivalence:

$$X \rightarrow Y \equiv Y \rightarrow X$$

So this equivalence is enough to prove $LHS \equiv RHS$.

Showing $X \rightarrow Y \equiv \neg Y \rightarrow \neg X$

$X \rightarrow Y \equiv$ Assignment Project Exam Help

$\neg X \vee Y \equiv$ <https://tutorcs.com> implication rule

$\neg X \vee \neg\neg Y \equiv$ WeChat: cstutorcs double negation

$\neg\neg Y \vee \neg X \equiv$ commutativity of \vee

$\neg Y \rightarrow \neg X$ implication rule

Back to Exercise

For each of the following determine if it is a tautology, inconsistency or contingency by drawing the truth table.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

a. $P \wedge (P \vee Q)$

b. $(P \vee Q) \wedge (P \rightarrow Q)$

c. $Q \wedge \neg P \wedge (P \vee (Q \rightarrow P))$

d. $(P \wedge (Q \vee P)) \leftrightarrow P$

e. $(P \rightarrow Q) \rightarrow (\neg P \vee Q)$

f. $((P \rightarrow Q) \wedge (R \rightarrow S) \wedge (P \vee R)) \rightarrow (Q \vee S)$

