

程序代写代做 CS编程辅导



cs2001

Introduction

Theory of Computation

Lecture 6

WeChat: cstutorcs

Ruth Urner
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

January 25, 2023

<https://tutorcs.com>

程序代写代做 CS编程辅导



Mathematical statements and proofs

Reading: WeChat: cstutorcs 0.3 andd 0.4

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Basic elements of mathematical text

程序代写代做 CS编程辅导

Definition

A statement that clearly defines an object/structure/concept based on previously defined terms.



Theorem

WeChat: cstutorcs

A statement that has been proven to be true.

Assignment Project Exam Help

Proof

Email: tutorcs@163.com

A clean, deductive argument for why a statement is true.

QQ: 749389476

Lemma

<https://tutorcs.com>

A “helper theorem”, typically only stated as a step in a proof of some theorem.

Examples of what not to do..

程序代写代做 CS编程辅导

Definition
A statement defines an object/structure/concept based on previous terms.

Warning: definitions can not be circular!

WeChat: cstutorcs

Example: Define $x > y$ as "x-y is positive"

Assignment Project Exam Help

Define x is positive as $x > 0$

Email: tutores@163.com

QQ: 749389476

<https://tutorcs.com>

Examples of what not to do..

程序代写代做 CS编程辅导

Definition
A statement defines an object/structure/concept based on previous terms.

Counter-example to the claim:
The claim:
9 is odd
and
 $9 = 3 \cdot 3$ is
not prime.
Thus the
claim is false.

Theorem WeChat: cstutorcs
A statement that has been proven to be true.

Proof A clean, deductive argument for why a statement is true.

~~Email: tutorcs@163.com~~

What not do: proof by example

Example: QQ: 749389476 "All odd natural numbers are prime"

"Proof" (by example): 1, 3, 5, 7, ...

To refute a statement by using a counter-example is a sufficient proof.

Some comments

- Understanding a statement is not the same as understanding why the statement is true (or false). The first step in attempting to prove a statement, is always **sure you understand the statement fully.**
- When you attempt something, I recommend to always first develop an **intuition** about the statement and what may be the proof. Eg, first come up with some simple **examples to illustrate the statement**, then **develop an intuition** for why the statement is true, then **develop a proof** for it.



WeChat: estidores

Assignment Project Exam Help

- Understanding whether a proof is correct and complete, is an important skill. It's **important** that you learn to evaluate whether your own proofs are correct.

QQ: 749389476

- If you want to prove a statement, you need to **provide a general argument**. If you want to disprove a statement, you need to present a **counter-example**.
- Learning to prove mathematical statements is a skill that develops with practice. **Be patient with yourself :)**

Email: tutorcs@163.com

https://tutorcs.com

Types of proofs—constructive proofs

程序代写代做 CS编程辅导



If the statement that we are aiming to proof is a claim about **WeChat: cstutorcs** **existence** of some object, then often we can prove the statement by constructing such an object. **Assignment Project Exam Help**

Email: **tutorcs@163.com**

QQ: **749389476**

<https://tutorcs.com>

Types of proofs—constructive proof example

Definition

程序代写代做 CS编程辅导

For a natural number $k \in \mathbb{N}$, we call a graph $G = (V, E)$ a **k -regular graph** if every vertex in V has degree k .



Theorem

For every even natural number $n \geq 4$, there exists a 3-regular graph with n vertices.

Assignment Project Exam Help

Email: tutorcs@163.com

Proof

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Types of proofs-construction

a 2-regular graph:



not a 3-regular graph

↑
not a 3-regular
graph
for any k
where k > 2

Definition

For a natural

k -regular graph



we call a graph $G = (V, E)$ a

k -regular graph if every vertex in V has degree k .

for construction of existence
often "proof by construction" is useful

Theorem

For every even natural number $n \geq 4$, there exists a 3-regular graph with n vertices.

WeChat: cstutorcs

proof (by construction).

Let $n \geq 4$ be an even natural number.

vertex set $V = [n] = \{1, 2, \dots, n\}$.

We define the following edges:

$$E = \{\{i, i+1\} \mid i \in \{1, \dots, n-1\}\} \cup \{\{n, 1\}\}$$

$$\cup \left\{ \left\{ i, \frac{n}{2} + i \right\} \mid i \in \{1, 2, \dots, \frac{n}{2}\} \right\}$$

This results in a graph where every vertex has degree 3.

https://tutorcs.com



Types of proofs—“by way of contradiction”

程序代写代做 CS编程辅导



Sometimes, in order to prove that some statement is true, we assume that the statement is false and then show that this assumption leads to a contradiction. This in turn implies that the statement is true.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Types of proofs—“by way of contradiction”



Screenshot of a software interface showing a toolbar with various icons like Save, Undo, Redo, and Print. Below the toolbar, there's a message: "What you share here? Recording On".

Saved as PNG Show in Folder

Talking: Ruth Urner

Sometimes, in order to prove that some statement is true, we assume that the statement is false and then show that this assumption leads to a contradiction. This, in turn, implies that the statement is true.

To prove statement P , we assume $(\neg P) \Rightarrow F$ is a true statement.

$(\neg P) \Rightarrow F$ is a true statement.
Email: tutorcs@163.com

This then lets us conclude that $(\neg P)$ must be false, and thus the statement P must be true.

QQ: 749389476

<https://tutorcs.com>

Types of proofs— examples of proofs “by way of contradiction”

程序代写代做 CS编程辅导

Theorem

$\sqrt{2}$ is not a rational



Proof

See textbook.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Types of proofs— examples of proofs “by way of contradiction”

程序代写代做 CS编程辅导

Theorem

There are infinitely many prime numbers.



Proof

WeChat: cstutorcs

Assignment Project Exam Help


Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Types of proofs—examples of proofs “by way of contradiction”



Theorem

There are infinitely many numbers.

Proof

B.w.o.c. (by way of contradiction), let's assume there are only finitely many primes, that is that there are only finitely, say $n \in \mathbb{N}$, many prime numbers $p_1, p_2, p_3, \dots, p_n$.
(and let's assume $p_i > 1$ for all i).

Now, let's consider the number

$$N = (p_1 \cdot p_2 \cdot p_3 \cdots \cdot p_n) + 1$$

We have $N \neq p_i$ for all i , and none of the p_i divides

N . Thus N must be a new prime number, a contradiction to the assumption that there are only n primes.

<https://tutorcs.com>

Talking: Ruth Urner

Thus the assumption was false, and therefore there aren't infinitely many prime numbers.

Types of proofs— examples of proofs “by way of contradiction”

程序代写代做 CS编程辅导

Theorem

The set \mathbb{R} of real numbers is not countable.



Proof

We'll prove this in the tutorial on Friday.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Types of proofs—proof by (structural) induction

程序代写代做 CS编程辅导



We can use a proof by induction, if we want to prove a statement about elements of a set that is (or can be) defined inductively.
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Inductive definition of sets – motivating example

程序代写代做 CS编程辅导

Say, I'd like to define all (biological) relatives of mine
(living and dead ones)



- I can not make

(I don't know them all, especially not those that lived a thousand years ago..)

WeChat: cstutorcs

- I can not give a precise characteristic

Assignment Project Exam Help

(Maybe I could if I was a biologist, but I am not..)

- But I know some operations that will allow me to get from me to all of them!

QQ: 749389476

The idea is to start with me, and consider everyone that can be reached by successively considering all children and all parents of previously reached people.

<https://tutorcs.com>

Inductive definition of sets – motivating example

程序代写代做 CS编程辅导



Here is a more formal way of defining all my biological relatives:

Consider the following three components:

1. **Universe:** all people
2. **Core set:** me
3. **Operations:** parent-of, child-of

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

The set of all my relatives: Start with me, and successively apply the operations parent-of and child-of. The set of all my relatives are all people that can be “reached” this way.

QQ: 749389476

<https://tutorcs.com>

Inductive definition of sets – general pattern

程序代写代做 CS编程辅导

An inductive definition consists of

1. A universe set U
 2. A core set $C \subseteq U$
 3. A finite set $O = \{o_1, o_2, \dots, o_n\}$ of operations from
 $o_i : U^{r_i} \rightarrow U$ for some arities $r_i \in \mathbb{N}$
- WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

We define $\mathcal{I}(U, C, O)$ as the set of elements that we obtain by
starting with the core set and putting all those elements of U into
 $\mathcal{I}(U, C, O)$ that one can reach by successively applying the
operations in O .

QQ: 749389476

<https://tutorcs.com>

Structural induction—general definition

程序代写代做 CS编程辅导

Consider some induction hypothesis on a defined set $\mathcal{A} = \mathcal{I}(U, C, O)$. To show that all elements of \mathcal{A} satisfy a certain property \mathcal{P} we prove the following:



Base case Show that all elements $c \in C$ of the core set satisfy the property \mathcal{P} .

WeChat: cstutorcs

Induction hypothesis Assume that some $a_1, a_2, \dots, a_n \in I(U, C, O)$ satisfy the property (where n is the largest arity of the operations in O).

Assignment Project Exam Help

Emails tutorcs@163.com

Induction step Show that for all operation $o_i \in O$, if the induction hypothesis holds, then the property also holds for $o_i(a_1, a_2, \dots, a_{r_i})$.

QQ: 749389476

<https://tutorcs.com>

Structural induction

程序代写代做 CS编程辅导



- When proving something by (structural) induction, it is very important that you clearly state the hypothesis and make it clear to yourself where in the induction step you are actually using it. If it is not clear where you use it, there is likely something wrong with your proof..!

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Structural induction-example

程序代写代做 CS编程辅导

Game with cups

We consider three cups on a table as follows:



∩ U

(That is, two upright and the middle one upside down.)

WeChat: cstutorcs

- We can now play with the cups by, at each step, flipping exactly two of them
- Eg, flipping the two left ones results in

Email: tutorcs@163.com

QQ: 749389476

Question: Can we, by repeatedly flipping two cups, end up with all cups upright
<https://tutorcs.com>

U U U?

Structural induction-example

程序代写代做 CS编程辅导



First, we note that we can define the set of all reachable cup-configurations as a recursively defined set:

- **Universe:** $U_c = \text{All ways to place three cups on the table.}$
WeChat: cstutorcs
(Question for you: How big is this universe?)
- **Coreset:** The initial configuration, $C_c = \{\text{UUU}\}$
- **Operations:** $O_c = \{\text{flip-left-two, flip-outer-two, flip-right-two}\}$
Email: tutorcs@163.com

Question: Is $\text{UUU} \in \mathcal{I}(U_c, C_c, O_c)$?

QQ: 749389476
<https://tutorcs.com>

程序代写代做 CS 编程辅导

Structural induction-example



First, we note that we want to define the set of all reachable cup-configurations. This is an inductively defined set:

- **Universe:** $U_c = \text{All ways to place three cups on the table.}$

(Question for you: How many ways are there?)

- **Coreset:** The initial configuration, $C_c = \{U \cap U\}$

- **Operation:** $O_c = \{\text{flip-left-two}, \text{flip-outer-two}, \text{flip-right-two}\}$

→ This defines (inductively) the set of all reachable

Question: Is $|U| \leq |L^*(U, C_c, O_c)|?$ (This is a game.)

Email: tutorcs@163.com

→ No!

QQ: 749389476 that the number

of upside cups is always even.

<https://tutorcs.com>



Structural induction-example

程序代写代做 CS编程辅导



Conjecture: It is not possible to get all cups upright..

We will prove the following property by induction:
In all reachable states, the number of upright cups is even.
Assignment Project Exam Help

Email: tutorcs@163.com

Since $\cup\cup\cup$ has an odd number of upright cups, this will imply
QQ: 749389476
that this state is not reachable.

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Structural induction-example

2) if we flip two up cups, then XYZ must have had two up (since now) plus we end up with zero up-cups.
3) if we flip two down cups, XYZ must have had one up and one up with 2 up cups.



Proof by

Base case



Initial configuration
XYZ, there are two (i.e even number of) up-cups.

WeChat: cstutorcs

Induction hypothesis: Assume XYZ is a sequence of n up-cups.

Induction step: If we flip two up-cups, XYZ, there

are three cases: 1) if we flip one up and one

QQ: 749389476

number of up-cups stays the same.

<https://tutorcs.com>

The base property is maintained under the operation, and therefore holds for all subsequent configurations by induction.

Structural induction-example

程序代写代做 CS编程辅导



Property: The number of up-cups is even.

Proof by induction WeChat: cstutorcs

Base case In the initial configuration $U_0 C_0 O_0$ the property holds
(2 cups are up, which is even).

Email: tutorcs@163.com

Induction hypothesis Assume that for some configuration

QQ: 749389476

$XYZ \in \mathcal{I}(U_c, C_c, O_c)$ the number of up-cups is even.

<https://tutorcs.com>

Structural induction-example

程序代写代做 CS编程辅导

Induction step First, note that if the number of up-cups in XYZ is even, it is either 0 or 2 (since 0 and 2 are the only even numbers smaller than 3). This observation motivates the following case distinction:



Case 1: It is 0 Then flipping two cups results in 2 up-cups, which is even again.

WeChat: cstutorcs

Case 2: It is 2 Then we either flip the two up-cups in XYZ or we flip one up-cup and one down-cup. In the first case, we end up with 0 up-cups, which is even, in the second case, we maintain 2 up-cups.

Email: tutorcs@163.com

Thus in all cases, the number of up-cups in $\text{flip-left-two}(XYZ)$, $\text{flip-outer-two}(XYZ)$, $\text{flip-right-two}(XYZ)$ is even again.

<https://tutorcs.com>

Question for you: Where did we use the induction hypothesis?

Types of proofs—proof by induction

程序代写代做 CS编程辅导



When we use a structural induction proof for the set of natural numbers, we often simply call it “proof by induction”
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Example of proof by induction for natural numbers

Theorem

程序代写代做 CS编程辅导

For a natural number $n \geq 1$, we let $S(n)$ denote the sum of the natural numbers up to n . Then the following equality holds:



$$\frac{1}{2} \cdot n \cdot (n + 1)$$

Proof

This is part of exercise 0.11, and we'll prove it in the Tutorial on Friday.

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Example of proof by induction for natural numbers

Theorem

For a natural
natural numbe



More... Undo Redo Clear Save

I have what you share here? Recording On

Stop Record

Share

Print

Format

Undo

Redo

Clear

Save

Speaker Volume

Talking: Ruth Urner

Stop Record

Share

Print

Format

Undo

Redo

Clear

Save

Stop Record

Share

Print

Format

Undo

Redo

Clear

Save

Stop Record

Share

Print

Format

Undo

Redo

Clear

Save

Stop Record

Share

Print

Format

Undo

Redo

Clear

Save

Inductive WeChat: estutorcs

Universal natural numbers \mathbb{N}

Assignment Project Exam Help

Core set : $\{0\}$

Email: tutorcs@163.com

Operation : $O_n : n \mapsto n+1$

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Example of proof by induction for natural numbers

Defining
integers \mathbb{Z}
inductively:

Universe: \mathbb{R}

Core-set: $\{0\}$

Operations:

$O_1: n \mapsto n+1$

$O_2: n \mapsto n-1$

Theorem

For a natural
natural numbe



Inductive WeChat: estutorcs

Universes and numbers \mathbb{R}

Assignment Project Exam Help

Core set : $\{0\}$

Email: tutorcs@163.com

Operation : $O_1: n \mapsto n+1$

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导



Regular Languages

Wechat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导



Finite Automata

WeChat: cstutorcs

Reading: ITC Section 1.1
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Finite Automata

程序代写代做 CS编程辅导



A finite automaton or ~~finite state machine~~ is a simple computational model.

WeChat: cstutorcs

Assignment Project Exam Help

We will work with this model of computation for the next part of this course.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A simple automaton–sliding door example


Consider an automatic sliding door with two pads that receive signals if someone is standing on them:



WeChat: cstutorcs

Assignment Project Exam Help

We can model the controller of the sliding door as a simple automaton:
Email: tutorcs@163.com



Here we use: $C = \text{CLOSED}$, $O = \text{OPEN}$, $F = \text{FRONT}$, $R = \text{REAR}$, $B = \text{BOTH}$, $N = \text{NEITHER}$

A simple automaton—sliding door example

程序代写代做 CS编程辅导



Here we use: $C = \text{CLOSED}$, $O = \text{OPEN}$, $F = \text{FRONT}$, $R = \text{REAR}$, $B = \text{BOTH}$, $N = \text{NEITHER}$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com
The behavior of the door can be described in terms of the following transition function:


QQ: 749389476

	NEITHER	FRONT	REAR	BOTH
CLOSED	CLOSED	OPEN	CLOSED	CLOSED
OPEN	CLOSED	OPEN	OPEN	OPEN

<https://tutorcs.com>

State diagram of M_1

We can use a state diagram to describe a finite automaton M_1 :



WeChat: cstutorcs

Interpretation of the state diagram: The arrow “coming out of nowhere” going into the leftmost state, signals, that this marks the start state. This automaton can read letters from the alphabet $\Sigma = \{0, 1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has a label σ , and moves along that arrow to a new state.

Examples:

QQ: 749389476

- If we feed the string 10010 to M_1 , we move through the states q_1, q_2, q_3, q_2, q_3 , the last one is not an accept state, which is not an accept state.
- If we feed the string 1101 to M_1 , we end up in state q_2 , which is an accept state (accept states are the nodes with a double circle).
- If we feed the empty string ϵ to M_1 , we end up in state q_1 , which is not an accept state.


程序代写代做 CS编程辅导

State diagram of M_1

We can use a [QR code](#)



to describe a finite automaton M_1 :



Interpretation of the state diagram: The arrow "going out of nowhere" going into the leftmost state, signals, that this state is the **start state**. This automaton can read letters from the **alphabet** $\Sigma = \{0, 1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has label σ , and moves along that arrow to a new state.

Examples:

- If we feed the string 00101 to M_1 , we see that it ends at state q_4 .

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

State diagram of M_1

We can use a st



...rcribe a finite automaton M_1 :

Interpretation of the state diagram: The arrow "going out of nowhere" going into the leftmost state, signals, that this state is the **start state**. This automaton can read letters from the **alphabet** $\Sigma = \{0, 1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has label σ , and moves along that arrow to a new state.

WeChat: cstutorcs
Assignment Project Exam Help

Examples:

- If we feed the string 00101 to M_1 , we move through the states $q_1, q_2, q_3, q_2, q_2, q_3$, and end up in state q_3 , which is not an accept state.
- If we feed the string 1101 to M_1 , ends up in q_2 , string is accepted.

QQ: 749389476

<https://tutorcs.com>

Formal definition of a finite automaton

程序代写代做 CS编程辅导



Definition

A finite automaton is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the set of states,
2. Σ is a finite set called the alphabet,
3. $\delta : Q \times \Sigma \rightarrow Q$ is the transition function,
4. $q_0 \in Q$ is the start state, and
5. $F \subseteq Q$ is the set of accept states.

<https://tutorcs.com>

程序代写代做 CS编程辅导

Formal definition of a finite



Definition

A **finite automaton** is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the **set of states**,
2. Σ is a finite set called the **alphabet**,
3. $\delta : Q \times \Sigma \rightarrow Q$ is the **transition function**,
4. $q_0 \in Q$ is the **start state**, and
5. $F \subseteq Q$ is the **set of accept states**.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Formal description of M_1



The above state diagram corresponds to the following formal description:

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

WeChat: cstutorcs

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$,
3. δ is defined by the following table:

Email: tutorcs@163.com

	0	1
q1	q1	q2
q3	q2	q2

QQ: 749389476

4. q_1 is the start state,
5. $F \subseteq \{q_2\}$.

Given the description of an automaton, we can ask: which strings will lead to an accept state when fed into the automaton? As we have seen in the example computations with M_1 before, some strings do and others don't. The set of strings that do lead to an accept state form a language over Σ , the **language of M_1** .

程序代写代做 CS编程辅导

Formal description of M_1



The above state diagram corresponds to the following formal description:

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

$$Q = \{q_1, q_2, q_3\}$$

$$\Sigma = \{0, 1\}$$

q_1 is starting state

$$F = \{q_3\}$$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Language accepted by an automaton

程序代写代做 CS编程辅导



Let Σ be the alphabet and M be an automaton M . Then we let

$$L(M) = \{w \in \Sigma^k \mid k \in \mathbb{N} \text{ and } w \text{ is accepted by } M\}$$

WeChat: cstutorcs

denote the language of machine M . The is $L(M)$ is the set of all words over Σ that are accepted by machine M .

Email: tutorcs@163.com

For the language $A = L(M)$ we also say machine M recognizes (or accepts) A .

QQ: 749389476

<https://tutorcs.com>

Formal definition of acceptance

程序代写代做 CS编程辅导



Definition

Let $M = (Q, \Sigma, \delta, q_0, F)$ a finite automaton and $w = w_1 w_2 \dots w_n$ a string over Σ . We say that M accepts w if there exists a sequence $s_0 s_1 s_2 \dots s_n$ of states such that

1. $s_0 = q_0$,

2. $\delta(s_i, w_{i+1}) = s_{i+1}$ for $i = 0, 1, \dots, n-1$,

3. $s_n \in F$.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Language accepted by M_1



For the machine M_1 we get

$$L(M_1) =$$

Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Task for you: figure out what exactly is the set of words accepted by this automaton.

程序代写代做 CS 编程辅导

Language accepted by ...



What is the language of M_1 ?

WeChat: cstutorcs

- all words that end with 1 are accepted
Assignment Project Exam Help
 $\{w_1 w_2 \dots w_n \in \Sigma^* \mid w_k = 1\} \subseteq L(M_1)$
- but there are other words (e.g. 100) that don't end with 1 and are also accepted.
Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>