

程序代写代做 CS编程辅导



Introduction

Theory of Computation

Lecture 3

WeChat: cstutorcs

Ruth Urner
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476
January 16, 2023

<https://tutorcs.com>

程序代写代做 CS编程辅导



Basic mathematical notation and terminology

Assignment Project Exam Help
Reading: TTC Section 0.2

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Set operations

程序代写代做 CS编程辅导

By default, we will assume that all our sets are **subsets of the natural numbers**. We assume a universe $U = \mathbb{N}$. Then we can define:



- The **set-difference** $A \setminus B$ of two sets A and B

WeChat: cstutorcs

Assignment Project Exam Help

- The **intersection** $A \cap B$ of two sets A and B

Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>

- The **union** $A \cup B$ of two sets A and B

程序代写代做 CS编程辅导

Set operations



By default, we assume that all our sets are **subsets** of the **natural numbers**. We assume a universe $U = \mathbb{N}$. Then we can define

- The **set-difference** $A \setminus B$ of two sets A and B

$A \setminus B$ WeChat: cstutorcs

$$A = \{1, 3, 5, 7\}, B = \{1, 2, 3\}$$

$$A \setminus B = \{5, 7\}$$

always:

$$A \setminus B \subseteq A$$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Set operations



By default, we assume that all our sets are **subsets** of the **natural numbers**. If we assume a universe $U = \mathbb{N}$. Then we can define

- The **set-difference** $A \setminus B$ of two sets A and B

In general, **WeChat: cstutorcs**
 $A = \{1, 3, 5, 7\}, B = \{1, 2, 3\}$
 $A - B = \{5, 7\}$

Assignment Project Exam Help

Q: Is it possible that $A - B = B - A$ for some sets A and B ?

A: Yes: **QQ: 749389476**, if $A \neq \emptyset$ and $A - B = B - A = \emptyset$.
Or, if $A = B = \{1, 2\}$, then $A - B = B - A = \emptyset$.

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Set operations



By default, we assume that all our sets are **subsets** of the **natural numbers**. We assume a universe $U = \mathbb{N}$. Then we can define

- The set difference $A \setminus B$ of two sets A and B :
 $A = \{1, 3, 5, 7\}$, $B = \{1, 2, 3\}$
 $A \setminus B = \{5, 7\}$

WeChat: cstutorcs

- The intersection of two sets A and B :

$A \cap B$ is the set of all elements that are members of both A and B .

$A \cap B = \{n \in \mathbb{N} \mid n \in A \text{ and } n \in B\}$
QQ: 749389476
or universe

<https://tutorcs.com>

程序代写代做 CS编程辅导

Set operations



- The set-difference $A \setminus B$ of two sets A and B

WeChat: cstutorcs

- The intersection $A \cap B$ of two sets A and B

$$A = \{1, 3, 5, 7\}, B = \{1, 2, 3\}$$
$$A \cap B = \{1, 2, 3\}$$

Email: tutores@163.com

- The union $A \cup B$ of two sets A and B

$$A \cup B \text{ is a set of all elements in } A \text{ and all elements in } B. A \cup B = \{n \in \mathbb{N} \mid n \in A \text{ or } n \in B\}$$

QQ: 749389476
<https://tutorcs.com>

More set operations

程序代写代做 CS编程辅导

By default, we will assume that all our sets are **subsets of the natural numbers**.
can define:

- The **complement** of a set A

WeChat: cstutorcs

- The **(cartesian) product** of two sets A and B

Email: tutorcs@163.com

- The set A^k of ~~k tuples~~ of elements of A

<https://tutorcs.com>



程序代写代做 CS编程辅导

More set operations



By default, we assume that all our sets are **subsets of the natural numbers**. We can define:

- The **complement** of a set A is the set of all elements in the universe that are not in A .

$$A = \{n \in \mathbb{N} \mid n \text{ divisible by } 23\} = \{\text{even numbers}\}$$

$$\overline{A} = \{n \in \mathbb{N} \mid n \text{ is not divisible by } 23\}$$

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

More set operations



WeChat: cstutorcs

- The (cartesian) product of two sets A and B

Assignment Project Exam Help

A and B.

$A = \{1, 3\}$, $B = \{1, 2, 3\}$

Email: tutorcs@163.com


$A \times B = \{(1, 1), (1, 2), (1, 3), (3, 1), (3, 2), (3, 3)\}$

QQ: 749389476, (7, 1), (7, 2), (7, 3)

<https://tutorcs.com>

程序代写代做 CS 编程辅导

More set operations



By default, we assume that all our sets are **subsets of the natural numbers**. We can define:

- The **complement** of a set A

WeChat: cstutorcs

- The **(cartesian) product** of $A \times B$ two sets A and B

Assignment Project Exam Help

- The set A^k of k -tuples A^k of elements of A

$$A = \{(1, 1), (1, 2), (2, 1), (2, 2)\}$$

$$A^3 = \{(1, 1, 1), (1, 1, 2), (1, 2, 1), (1, 2, 2), (2, 1, 1), (2, 1, 2), (2, 2, 1), (2, 2, 2)\}$$

$$\text{QQ: } 749389476 \dots (4, 4, 4)$$

<https://tutorcs.com>

More set operations

程序代写代做 CS编程辅导

- The power set $\mathcal{P}(A)$ of set A



WeChat: cstutorcs

Assignment Project Exam Help

- The symmetric difference $A \Delta B$ between two sets A and B

QQ: 749389476

Email: tutores@163.com

<https://tutorcs.com>

程序代写代做 CS 编程辅导

More set operations

You are screen sharing Stop Share

Draw Stamp Eraser Paint Undo Redo Clear Save

And can see what you share here Recording On

Taking:

- The **pow** is tea

$A = \{\}$

$P(A) = \{\emptyset, \{\}, \{1\}, \{2\}, \{3\}, \{1, 2\}, \{1, 3\}, \{2, 3\}, \{1, 2, 3\}\}$

WeChat: cstutorcs

Assignment Project Exam Help

Notes

\emptyset is a member of the powerset of every set

Email: tutorcs@163.com

Set itself is always a member of its own powerset

Warning: QQ: 749389476, $\{1\} \notin A, \{1\} \in P(A)$

<https://tutorcs.com>

程序代写代做 CS 编程辅导

More set operations

- The ~~pow~~

$$\underline{A} = \underline{\underline{2, 3}}$$



set A

$$B = \{1, 2, 3\}$$

$$A \Delta B = \{1, 5, 7\}$$

$$A \Delta B$$



WeChat: cstutorcs

A_nB

- The symmetric difference $A \Delta B$ between two sets A and B is the set of all elements in $A \cup B$ that are not in $A \cap B$.

Email: tutorcs@163.com

$$A \Delta B = (A \cup B) \setminus (A \cap B)$$

QQ: 749389476

<https://tutorcs.com>

Sets, multi-sets, sequences

程序代写代做 CS编程辅导

- Recall: **Sets** contain elements only once and the order does not matter



- Multi-sets** can contain elements multiple times, but do not contain an order of their elements

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

- Sequences** or **tuples** are collections of elements in a fixed order.

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Sets, multi-sets, sequences



- Multi-sets can contain elements multiple times, but do not contain an order of their elements.

$\{1, 1, 3, 5\}$ is not equal to $\{1, 3, 5\}$
as a multiset, but equal as sets

$\{1, 1, 3, 5\}$ is equal to $\{1, 3, 5\}$
as a multiset.

Assignment Project Exam Help

Email: tutores@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Sets, multi-sets, sequences



- Recall: Sets can contain an element only once and the order does not matter.

- Multi-sets can contain elements multiple times, but do not contain an order of their elements.

Assignment Project Exam Help

- Sequences or tuples are collections of elements in a fixed order.

Email: tutorcs@163.com

$(3, 1, 5)$ is a 3-tuple

$(1, 1, 1, 2, 2, 3, 4)$ is an 8-tuple

$(2i)_{i \in \mathbb{N}}$ is the sequence of even numbers
 $\subseteq \{2, 4, 6, 8, 10, \dots\}$

<https://tutorcs.com>

Relations

程序代写代做 CS编程辅导

Definition:

A relation R between two sets A and set B is a subset of $A \times B$.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

We sometimes use notation aRb to state that $(a, b) \in R$.

程序代写代做 CS 编程辅导

Relations

Definition:

A relation R



" \leq " is

and set B is a subset of $A \times B$.

over the natural numbers :

$$\{(0,1), (0,0), (1,1), (0,2), (1,2), \dots\}$$

WeChat: cstutorcs

$$A = \{1, 3, 5, 7, 9\}, B = \{1, 2, 3\}, \text{ then}$$

$$R = \{(1,1), (3,3)\} \text{ is a relation between } A \text{ and } B.$$

$$R' = \{(3,2), (3,1), (3,5), (7,3)\}$$

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Relations



Definition:
A relation R is a set of ordered pairs (a, b) where set A and set B is a subset of $A \times B$.

$$2 \leq 4$$

5 ≤ WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

We sometimes use notation R to state that $(a, b) \in R$.

QQ: 749389476

<https://tutorcs.com>

Relations

程序代写代做 CS编程辅导



- If R is a relation between A and itself, that is $R \subseteq A \times A$, we also call R a ~~binary relation~~ or a relation of arity 2 on A .
- A subset $R \subseteq A^k$ of k -tuples of elements of A , is also called a ~~k-ary relation~~, or a relation of arity k .

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Equivalence relations

程序代写代做 CS编程辅导



Definition:

A binary relation R on some set A is called an equivalence relation if it has the following properties

- reflexive
- symmetric
- transitive

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Equivalence relations

\leq as a

is \sim

$=$ is an



is transitive but not symmetric
an equivalence relation

Definition:

A binary relation R on some set A is called an **equivalence relation** if it has the following properties:

- reflexive

for every $a \in A$, $(a, a) \in R$

- symmetric

if $(a, b) \in R$ for some $a, b \in A$, then
 $(b, a) \in R$

- transitive

if $(a, b) \in R$ and $(b, c) \in R$, then $(a, c) \in R$

$\equiv_{\text{mod} 5}$ (remainder modulo 5) is an equivalence

relation on the natural numbers

$6 \equiv_{\text{mod} 5} 11$, $6 \equiv_{\text{mod} 5} 21$, $11 \equiv_{\text{mod} 5} 21$

<https://tutorcs.com>

Talking: Ruth Urner

Functions

程序代写代做 CS编程辅导

Definition:

A **function** f from set A to set B is a relation between A and B that satisfies the following properties:



- For every $a \in A$, there exists a $b \in B$ such that $(a, b) \in f$
- If $(a, b) \in f$ and $(a, b') \in f$, then $b = b'$.

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

Instead of $(a, b) \in f$, we usually use notation $f(a) = b$.

Alternatively, we also use the notation $f : a \mapsto b$.

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Functions

i	f(i)
1	1
3	1
5	3
7	2


for functions,
we can use
such tables
to define
them

$$f(x) = |x|$$

$$g(x) = \sin(x)$$

Definition:

A function f is a relation between A and B that satisfies



Let B is a relation between A and B properties:

- For every $a \in A$, there exists a $b \in B$ such at $(a, b) \in f$
- If $(a, b) \in f$, then b is unique.

$$A = \{1, 3, 5, 7\}, B = \{1, 2, 3\}$$

$$f: A \rightarrow B = \{\text{Assignment Project Exam Help}\}$$

$R = \{(1, 1), (5, 1), (1, 2), (7, 2)\}$ is not a function;

Instead of $(a, b) \in R$, we usually use notation $f(a) = b$. it violates both

Alternatively, we also use the notation $f: a \mapsto b$.

QQ: 749389476

<https://tutorcs.com>

properties (input 1
gets mapped to two outputs
and input 3 doesn't get
mapped to any output)

Functions – important properties

We use the notation

程序代写代做CS编程辅导

to state that f is a function from A to B .

We call A the domain of f and B the co-domain of the function f .
Note that the textbook uses range for the co-domain.



Further, the image of the function f is the following subset of co-domain:

WeChat: cstutorcs
 $\{b \in B \mid \text{there exists an } a \in A \text{ with } f(a) = b\}$

Assignment Project Exam Help

Functions can be:

Email: tutorcs@163.com

- one-to-one:

QQ: 749389476
We call a function $f : A \rightarrow B$ one-to-one if $f(a) = b$ and $f(a') = b$ for some $b \in B$ implies that $a = a'$.

<https://tutorcs.com>

- onto:

We call a function $f : A \rightarrow B$ onto if for all $b \in B$ there exists an $a \in A$ with $f(a) = b$.

程序代写代做 CS 编程辅导

Functions – important properties

We use the n



to state that

$f : A \rightarrow B$

from A to B.

co-domain

We call A the domain of the function f and B the ~~range~~ of the function f.

WeChat: cstutorcs

We call the set

$$Im(f) = \{ b \in B \mid \exists a \in A \text{ such that } b = f(a) \} \subseteq B$$

Email: tutorcs@163.com

The image of the function f.

~~QQ: 749389476~~

<https://tutorcs.com>

程序代写代做 CS 编程辅导


Functions – important properties

Let

$$A = \mathbb{R}, B = \mathbb{R}$$

$f(x) = \sin(x)$
is neither
one-to-one
nor onto

$$g(x) = x^3$$



We use the notation



$f : A \rightarrow B$

to state that

from A to B .

We call A the **domain** of the function f and B the **range** of the function f .

WeChat: cstutorcs

Functions can be:

- **one-to-one:**

Assignment Project Exam Help

We call a function $f : A \rightarrow B$ **one-to-one** if $f(a) = b$ and $f(a') = b$ for some $b \in B$ implies that $a = a'$.

- **onto:**

Email: tutorcs@163.com

We call a function $f : A \rightarrow B$ **onto** if for all $b \in B$ there exists an $a \in A$

with $f(a) = b$.
QQ: 749389476

<https://tutorcs.com>



程序代写代做 CS编程辅导



Graphs

WeChat: cstutorcs

Reading: ITC Section 0.2
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Graphs

程序代写代做 CS编程辅导

We illustrate graphs as points and connecting lines:



An **undirected graph** ([or `https://tutorcs.com`](https://tutorcs.com)) (V, E) is defined as a pair of

- a set V of **vertices** (also called **nodes**)
- and a set E of **edges**,

where each edge in E is a (multi-set) subset of V of size 2.

程序代写代做 CS编程辅导

Graphs

We illustrate gr



Saved as PNG Show in Folder

connecting lines:



Formally:

$$G = (\{1, 2, 3, 4, 5\},$$

$$\{\{1, 5\}, \{1, 3\}, \{5, 2\},$$

$$\{2, 3\}, \{1, 2\}, \{1, 3\}\})$$

WeChat: cstutorcs
Assignment Project Exam Help

Email: tutorcs@163.com

An undirected graph (or simply a graph) $G = (V, E)$ is defined as a pair of

- a set V of vertices (also called nodes)

- and a set E of edges,

where each edge $\in E$ is a (multi-set) subset of V of size 2.

<https://tutorcs.com>

程序代写代做 CS编程辅导

Graphs

We illustrate gr



connecting lines:



- Is G (or E) reflexive?
no
- Transitive?
no
- Symmetric?
yes

An undirected graph (or simply a graph) $G = (V, E)$ is defined as a pair of

- a set V of vertices (also called nodes)

- and a set E of edges,

where each edge in E is a (multi-set) subset of V of size 2.

<https://tutorcs.com>



Graphs

程序代写代做 CS编程辅导

Graphs can be used to illustrate relationships between objects.



QQ: 749389476

<https://tutorcs.com>


Some definitions and terminology for graphs

程序代写代做 CS编程辅导

Let $G = (V, E)$ be a graph. Define:



- a vertex $v \in V$ is adjacent to edge $e \in E$ if $v \in e$



WeChat: cstutorcs

- the degree $d(v)$ of a vertex $v \in V$ is the number of edges v is adjacent to

Assignment Project Exam Help

- a path in a graph is a sequence

$p = (v_1, v_2, \dots, v_n)$ of vertices such that

$\{v_i, v_{i+1}\} \in E$ for all $i \in \{1, 2, \dots, n\}$

<https://tutorcs.com>

- a simple path is a path in which no vertex occurs more than once

程序代写代做 CS编程辅导

Some definitions and terminology for graphs

Let $G = (V, E)$



- a vertex v is adjacent to edge $e \in E$ if $v \in e$

- the **degree** $d(v)$ of a vertex v is the number of edges v is adjacent to

- a **path** in a graph is a sequence $p = (v_1, v_2, \dots, v_n)$ of vertices such that $\{v_i, v_{i+1}\} \in E$ for all $i \in \{1, 2, \dots, n-1\}$
- a **simple path** is a path in which no vertex occurs more than once


WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



example of a path

(5, 2, 3, 1, 3)

not a simple path!

example of a


simple path

(4, 5, 1, 3)

Some definitions and terminology for graphs

程序代写代做 CS编程辅导

Let $G = (V, E)$ be a graph. We define:



- a **subgraph** G' of graph G is a graph $G' = (V', E')$ with $V' \subseteq V$ and $E' \subseteq E$
- graph G is **connected**, if for every two distinct vertices $v, v' \in V$, there is a path from v to v' (that is, a path which has v as its first and v' as its last vertex)
- we call an edge $e \in E$ a **self-loop** if $e = \{v, v\}$ for some $v \in V$ (that is, the edge connects some vertex v to itself)


程序代写代做 CS编程辅导

Some definitions and properties for graphs



Let $G = (V, E)$ be a graph. We

WeChat: cstutorcs



- a **subgraph** G' of graph G is a graph $G' = (V', E')$ with $V' \subseteq V$ and $E' \subseteq E$
- graph G is **connected**, if for every two distinct vertices $v, v' \in V$ there is a path from v to v' (that is, a path which has v as its first and v' as its last vertex)
- we call an edge $e \in E$ a **self-loop** if $e = \{v, v\}$ for some $v \in V$ (that is, the edge connects some vertex v to itself)

Assignment Project Exam Help

Email: tutorcs@163.com


QQ: 749389476

<https://tutorcs.com>

Some definitions and terminology for graphs

程序代写代做 CS编程辅导

Let $G = (V, E)$ be a graph. We define:



- a **cycle** in a graph is a path in which the first and last vertex are identical

WeChat: cstutores

Assignment Project Exam Help

- a **simple cycle** in a graph is a cycle that contains at least three different vertices and doesn't contain any vertex more than once (except for the first and last)

Email: tutorcs@163.com

QQ: 749389476

- a **tree** is a graph that is connected and doesn't contain any simple cycles; vertices of degree one in a tree are called **leaves**; sometimes we declare one vertex in a tree to be special and call it a **root**

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Some definitions and terminology for graphs



Let $G = (V, E)$. We define:



- a **cycle** in a graph is a path for which the first and last vertices are identical.

WeChat: cstutorcs

- a **simple cycle** in a graph is a cycle that contains at least three different vertices and doesn't contain any vertex more than once (except for the first and last).


Assignment Project Exam Help

- a **tree** is a graph that is connected and doesn't contain any simple cycles; vertices of degree one in a tree are called **leaves**; sometimes we declare one vertex in a tree to be the **root**.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>



Cycle in G :

(5, 2, 3, 1, 5)

(also a simple cycle)

Cycle 18 is not simple:

(5, 2, 3, 1, 2, 5)

Directed graphs

程序代写代做 CS编程辅导

We illustrate directed graphs as points and connecting arrows:



A **directed graph** $G = (V, E)$ is formally defined as a pair of

- a set V of vertices
- and a set E of edges,

where each edge in E is a **2-tuple** (or **pair**) of members of V .


程序代写代做 CS编程辅导

Directed

For directed graphs the edge set E is a relation over the vertex set V . In the example graph $G = (V, E)$ the relation is not reflexive, not transitive, not symmetric.

We illustrate di-

rected graphs by points and connecting arrows:



A directed graph $G = (V, E)$ is formally defined as a pair of

- a set V of vertices

- and a set E of edges,

where each edge $\in E$ is a 2-tuple (or pair) of members of V .

<https://tutorcs.com>

Some definitions and terminology for directed graphs

程序代写代做 CS编程辅导

- For an edge $e = (v_1, v_2)$ in directed graph, we call e an incoming edge to v_2 and an outgoing edge for v_1 .
- The in-degree $d_{in}(v)$ of vertex v in a directed graph is the number of its incoming edges. The out-degree $d_{out}(v)$ is the number of outgoing edges from v .
WeChat: cstutorcs
- A directed path in a directed graph is a sequence $p = (v_1, v_2, \dots, v_n)$ of vertices such that $(v_i, v_{i+1}) \in E$ for all $i \in \{1, 2, \dots, n\}$.
Assignment Project Exam Help
Email: tutorcs@163.com
- A directed graph is strongly connected if every two distinct vertices v and w are connected by a directed path.
QQ: 749389476
<https://tutorcs.com>
- A directed cycle in a directed graph is a directed graph for which the first and last vertex coincide.

程序代写代做 CS 编程辅导

Some definitions and terminology for directed graphs

- For an edge $e = (v_1, v_2)$ in a directed graph, we call e an **incoming edge** for v_2 and an **outgoing edge** for v_1 .
- The **in-degree** $d_{\text{in}}(v)$ of a vertex v in a directed graph is the number of its incoming edges. The **out-degree** $d_{\text{out}}(v)$ is the number of outgoing edges from v .

WeChat: cstutorcs

- A **directed path** in a directed graph is a sequence $p = (v_1, v_2, \dots, v_n)$ of vertices such that $(v_i, v_{i+1}) \in E$ for all $i \in \{1, 2, \dots, n-1\}$.

Assignment Project Exam Help

- A directed graph is **strongly connected** if every two distinct vertices v and v' in V are connected by a directed path.



QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导



Strings and Languages

WeChat: cstutorcs

Reading: ITC Section 0.2
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Alphabet, words, languages

程序代写代做 CS编程辅导

An **alphabet** is a non-empty finite set of **symbols**.

Examples:

- $\Sigma = \{0, 1\}$.
- $\Gamma = \{a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z\}$



WeChat: cstutorcs

A **string** or **word** over some alphabet Σ is a finite sequence of symbols from Σ .
Assignment Project Exam Help

Examples:

Email: tutorcs@163.com

- ruth
- 00101

QQ: 749389476

<https://tutorcs.com>

A **language** is a **set of words** (set of strings).

程序代写代做CS编程辅导

Alphabet, words, languages



An **alphabet**



finite set of **symbols**.

Examples:

- $\Sigma = \{0, 1\}$
- $\Gamma = \{a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z\}$

WeChat: cstutorcs

A string or word over some alphabet Σ is a finite sequence of symbols from Σ .

Assignment Project Exam Help

Examples:

- ruth
- 00101

word over Γ
word over Σ or Γ

Email: tutorcs@163.com

A language is a set of words (set of strings).

QQ: 749389476
 $\{\text{ruth}\}$ $\{\text{ruth, abc, chair, dog}\}$

<https://tutorcs.com>

程序代写代做CS编程辅导

Alphabet, words, languages



An alphabet



finite set of symbols.

Examples:

- $\Sigma = \{0, 1\}$
- $\Gamma = \{a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z\}$

$$\Sigma = \{\textcircled{1}, \textcircled{2}, \textcircled{3}\}$$



WeChat: cstutorcs

A string or word over some alphabet Σ is a finite sequence of symbols from Σ .

Assignment Project Exam Help

Examples:

- ruth
- 00101

Email: tutorcs@163.com

A language is a set of words (set of strings).

QQ: 749389476

<https://tutorcs.com>

Some definitions and terminology for strings and languages

程序代写代做 CS编程辅导



- the **length** of a string w is the number of symbols in w
 - the **empty string** ϵ is a string of length 0 (that is, without any symbols)
 - the **reverse** w^R of a string w is the string w written backwards.
 - the **concatenation** of strings $w = s_1 s_2 \dots s_n$ and $z = t_1 t_2 \dots t_m$ is the string $wz = s_1 s_2 \dots s_n t_1 t_2 \dots t_m$
- Assignment Project Exam Help**
WeChat: cstutorcs
Email: tutorcs@163.com
QQ: 749389476
<https://tutorcs.com>

程序代写代做CS编程辅导

Some definitions and terminology for strings and languages



- the **length** of a string w is the number of symbols in w
- the **empty string** ϵ is a string of length 0 (that is, without any symbols)

WeChat: cstutorcs

- the **reverse** w^R of a string w is the number of symbols in w
- the **concatenation** of strings $w = s_1s_2\dots s_n$ and $z = t_1t_2\dots t_m$ is the string $wz = s_1t_1s_2t_2\dots s_nt_m$

Assignment Project Exam Help

Email: tutores@163.com

$$w = 01011, z = 1101, wz = 01011101$$

QQ: 749389476

<https://tutorcs.com>

Some definitions and terminology for strings and languages

程序代写代做 CS编程辅导

- a **substring** z of  is a consecutive subsequence of symbols from w
- a **prefix** x of **string** w is a substring that starts at the first position in w ; that is, x is a prefix of w if there exists a string z such that $w = xz$

Assignment Project Exam Help

- x is a **proper prefix** of w if x is a prefix of w and $w \neq x$
- a **prefix-free language** over some alphabet Σ is a language where no word in the language is a proper prefix of some other word

QQ: 749389476

Email: tutorcs@163.com

<https://tutorcs.com>

程序代写代做 CS编程辅导

Some details about the presentation and languages



- a substrings of $w = 0123456789$



is a consecutive subsequence of

= can not a substring of w

= cea is a substring of w

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做CS编程辅导

Some definitions and terminology for strings and languages



- a **substring** of string w is a consecutive subsequence of symbols



- a **prefix** x of string w is a substring that starts at the first position in w ; that is, x is a prefix of w if there exists a string z such that $w = xz$.

WeChat: cstutorcs a proper prefix of w

$w = ocean$, $x = \underline{oc}$ is a prefix of w

- x is a **proper prefix** of w if it is a prefix of w and $x \neq w$.

$w = ocean$, $x = ocean$ is a prefix, but not a proper prefix of w

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做CS编程辅导

Some definitions and terminology for strings and languages

$\Sigma = \{0, 1\}$
 $\{00, 11\}$
 $01, 001, 111$
 $0101\}$
not a prefix-free language
00 is a prefix of 001
01 is a prefix of 0101
 $\{00, 11\}$
0101 is a prefix of 010101
is a prefix-free language



- a **substring** of string w is a consecutive subsequence of symbols
- a **prefix** x of string w is a substring that starts at the first position in w ; that is, x is a prefix of w if there exists a string z such that $w = xz$

WeChat: cstutorcs

- x is a **proper prefix** of w if it is a prefix of w and $x \neq w$

- a **prefix-free language** over some alphabet Σ is a language where no word in the language is a proper prefix of some other word

QQ: 749389476

<https://tutorcs.com>

Ordering words

程序代写代做 CS编程辅导

Given an ordering of the symbols in some alphabet Σ , we can define orderings of the words over Σ :



- Lexicographic order

Definition: We have $w \leq_{lex} z$ in lexicographic order for strings $w = s_1 s_2 \dots s_n$

WeChat: cstutorcs

and $z = t_1 t_2 \dots t_m$ if w is a proper prefix of z or if there exists an index

Assignment Project Exam Help $j < \min\{n, m\}$ such that $s_j < t_j$ or all $s_i = t_i$ ($i > j$) and $s_{j+1} < t_{j+1}$.

Email: tutorcs@163.com

- Short-lex order (or string order)

Definition: We have $w \leq_{str} z$ in string order for strings $w = s_1 s_2 \dots s_n$ and

QQ: 749389476

$z = t_1 t_2 \dots t_m$ if w is shorter than z or if w and z have the same length and

<https://tutorcs.com>

$w \leq_{lex} z$ in lexicographic order.

程序代写代做CS编程辅导

Ordering words



Given an ordering \leq on symbols in some alphabet Σ , we can define ordering on words over Σ :

- Lexicographic order

Definition: We have $w \leq_{lex} z$ in **lexicographic order** for strings $w = s_1 s_2 \dots s_n$ and $z = t_1 t_2 \dots t_m$ if we can prove that there exists an index

$j < \min\{n, m\}$ such that $s_i = t_i$ for all $i \in \{1, 2, \dots, j\}$ and $s_{j+1} < t_{j+1}$.

Assignment Project Exam Help

- Short-lex order (or string order)

Definition: We have $w \leq_{str} z$ in **string order** for strings $w = s_1 s_2 \dots s_n$ and $z = t_1 t_2 \dots t_m$ if we can prove that w and z have the same length and $w \leq_{lex} z$ in lexicographic order.

QQ: 749389476

ruth
apple

apartment

cat
dog

https://tutorcs.com