

程序代写代做 CS编程辅导



Introduction

Theory of Computation

Lecture 9

WeChat: cstutorcs

Ruth Urner
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476
Febuary 6, 2023

<https://tutorcs.com>

程序代写代做 CS编程辅导



Regular Languages

WeChat: cstutorcs

Reading: ITC Section 1.1
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Regular language

程序代写代做 CS编程辅导



Definition

A language L over some alphabet Σ is called a **regular language** if there exists a finite automaton M such that $L = L(M)$, that is, if there exists a finite automaton that recognizes it.

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Regular language



Definition ✓

A language L is called a regular language if there exists a finite automaton M such that $L = L(M)$, that is, if there exists a finite automaton that recognizes it.

Assignment Project Exam Help

• $\{ \omega \in \{0,1\}^* \mid \omega \text{ contains } 001 \text{ as a substring} \}$

Email: tutorcs@163.com

• $\{ \omega \in \{0,1\}^* \mid \text{The number of } 1 \text{ is odd} \}$

QQ: 749389476

<https://tutorcs.com>

Regular operations on languages

程序代写代做 CS编程辅导

Definition:

Let A and B be languages. Then we define the following operations that each form a new language:



- **Union:** $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.
WeChat: cstutorcs
Assignment Project Exam Help
- **Concatenation:** $A \circ B = \{wv \mid w \in A \text{ and } v \in B\}$.
Email: tutorcs@163.com
- **Star:** $A^* = \{w_1w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$
QQ: 749389476
<https://tutorcs.com>

程序代写代做 CS 编程辅导

Regular c



In particular
for an
alphabet
 Σ , the set
 Σ^* is the
set of
all finite
words over
 Σ .

Ex:

$$A = \{01\}$$

$$B = \{1, 11\}$$



13

$$A \times B \ni (01, 110)$$

not $\in \Sigma^*$

Definition:

Let A and B

then we define the following operations that each form a new language:

- Union: WeChat: costurores $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.

Ex: $A \cup B = \{01, 001, 0001, 1, 11, 110, 110\}$

- Concatenation: $A \circ B = \{w_1 w_2 \mid w_1 \in A \text{ and } w_2 \in B\}$

Ex: $A \circ B = \{011, 0011, 00011, 0111, 00111, 000111\}$

- Star:

$$A^* = \{w_1 w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$$

Ex: $A^* = \{0, 1, 001, 0001, 01001, 001001, 010001, 0000110, 00000111, 0000001111, \dots\}$

\hookrightarrow infinite set of words...

<https://tutorcs.com>

Talking: Ruth Urner

程序代写代做 CS 编程辅导

In particular
for an
alphabet
 Σ , the set
 Σ^* is the
set of
all finite
words over
 Σ .

$B \subseteq A^*$
 $A \subseteq B^*$

Regular op

$$\Sigma = \{0, 1\}$$

$$A = \{0\}$$

$$B = \{1\}$$

Ex:



Definition:

Let A and B

then we define the following operations that each form a new language:

- Union: WeChat: $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.

Ex: $A \cup B = \{01, 001, 0001, 1, 11, 110, 10\}$

- Concatenation: $A \circ B = \{w_1 w_2 \mid w_1 \in A \text{ and } w_2 \in B\}$

Ex: $A \circ B = \{011, 0011, 00011, 0111, 00111, 000111\}$

- Star:

$$A^* = \{w_1 w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$$

Ex: $A^* = \{0, 1, 00, 000, 0000, 0100, 00100, 000100, 010100, 010010, \dots\}$

\uparrow
infinite set of words...

<https://tutorcs.com>

$$A \times B = \{01, 110\}$$

$$\text{not } \in \Sigma^*$$

$$C = \{0, 1\}$$

$$B \subseteq C^*$$

$$A \subseteq C^*$$

$$D = \{0, 1, 00, 000\}$$

$$B \subseteq D$$

$$A \subseteq D^*$$

$$C = \{0, 1, 00, 000\}$$

$$D \subseteq C$$

$$E \subseteq D$$

$$F \subseteq E$$

$$G \subseteq F$$

$$H \subseteq G$$

End of presentation. Click to exit.

程序代写代做 CS编程辅导

$$\Sigma = \{0, 1\}$$

Mouse Select Text



You are screen sharing Stop Share

Talking:

$$A = \{1\}$$

$$A^* = \{\varepsilon, 1, 11, 111\}$$



WeChat: cs_tutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

$$\exists \quad , \quad |A^*| = \infty$$

$$\Sigma' = \{0, 1, 2\}$$

Automation

$$(Q, \Sigma, \delta, s_0, F)$$

↑
alphabet is part of the
definition of an automata

<https://tutorcs.com>

Regular operations reproduce regular languages

程序代写代做 CS编程辅导



Theorem

The set of all regular languages is **closed** under the three regular operations.
WeChat: cstutorcs

Assignment Project Exam Help

That is: if A and B are regular languages, then A^* , $A \cup B$ and $A \circ B$ are also regular languages.
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Problem 1.4 from ITC

Here we design an automaton that recognizes the **intersection** of two languages for which we have simple automata recognizing them.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>


We will now use a similar “product” for the general construction of an automaton that recognizes the **union** of two regular languages.

程序代写代做 CS 编程辅导

Problem 1.4 from ITC

E = {a, b}

Here we design a DFA which we have si



given two languages A and B.

A = {w | w contains at least 3 a's}

B = {w | w contains at least 2 b's}

We define automaton M_1 with $L(M_1) = A$

WeChat: cstutorcs



Assignment Project Exam Help

and automaton M_2 with $L(M_2) = B$

Email: tutorcs@163.com



QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Problem 1.4 from ITC

$$M = (Q, \Sigma, \delta)$$

$$\Sigma = \{a, b\}$$

S_1

$$(q_{1a}, q_{1b})$$

$$\{(q_{1a}, q_{1b})\}$$

For the state diagram we write
 $q_{1ab} = (q_{1a}, q_{1b})$

$$S_2 = \{a, b\}$$

Here we design a
which we have si

given two

$$A = \{w \in \Sigma^* \mid w \text{ contains at least 3 a's}\}$$

$$B = \{w \in \Sigma^* \mid w \text{ contains at least 2 b's}\}$$

We can now construct automaton M that
WeChat: cstutorcs
 $A \cap B$ as follows:



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

cognizes the intersection of two languages for

recognizing them.

$A \cap B$

$\Sigma = \{a, b\}^*$

w contains at
least 3 a's and
at least 2 b's}

程序代写代做 CS 编程辅导

Modification of the
Problem 1.4 from ITC

$$M = (Q, \Sigma, Q_0, \delta)$$

$$\Sigma = \{a, b\}$$

Q,

$$(q_{0a}, q_{0b}),$$

$$\{ \dots \}$$

For the state diagram
we write
 $q_{1ab} = (q_{1a}, q_{1b})$

$$q_{1a} = (q_{1a}, q_{1b})$$

$\Sigma = \{a, b\}$
Here we design a
which we have si



cognizes the intersection of two languages for
recognizing them.

intersection
union

given two
languages A and B.

A = {w | w contains at least 3 a's}

B = {w | w contains at least 2 b's}

We can now construct automaton M that
accepts $A \cap B$ as follows:

WeChat: cstutorcs
 $A \cup B =$



<https://tutorcs.com>

Regular languages closed under unions

程序代写代做 CS编程辅导

We start by proving if A and B are regular languages over some alphabet Σ , then $A \cup B$.



Proof:

To prove that $A \cup B$ is regular, we need to show that there exists an automaton WeChat: cstutorcs

$M = (Q, \Sigma, \delta, q_0, F)$
Assignment Project Exam Help

with

Email: cstutorcs@163.com

Since A and B are regular, we know there exist automata $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ with QQ: 749389476

<https://tutorcs.com> = B

程序代写代做 CS编程辅导

Regular languages closed under unions

Since M_1 and M_2 the goal is to construct an automaton that recognizes $A \cup B$ using the components of M_1 and the

general
case

We start by p
some alphabet



and B are regular languages over $A \cup B$.

Goal for

To show that $A \cup B$ is regular, we need
WeChat: cstutorcs
show that there exists an automaton

that recognizes $A \cup B$

We know that A and B are regular languages. Hence there exist

languages $L(M_1)$ and $L(M_2)$

automata $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ such that

$A = L(M_1)$ and $B = L(M_2)$.

<https://tutorcs.com>

Regular languages closed under unions

程序代写代做 CS编程辅导

Proof continued:

We now define the regular automaton M as follows:



1. $Q = Q_1 \times Q_2$ WeChat: cstutorcs
2. We use the same alphabet Σ Assignment Project Exam Help
3. $\delta((s_1, s_2), a) = (\delta_1(s_1, a), \delta_2(s_2, a))$ Email: tutorcs@163.com
4. $q_0 = (q_1, q_2)$ QQ: 749389476
5. $F = \{(s_1, s_2) \in Q \mid s_1 \in F_1 \text{ or } s_2 \in F_2\}$ <https://tutorcs.com>

程序代写代做 CS 编程辅导

Regular languages citoorcs

Stop Sharing Stop Share

Home

Talking: Ruth Urner

$M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$

$M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$

We now define the product automaton M as follows:

Proof continues

QR code linking to the proof.

1. $Q = Q_1 \times Q_2$
2. We use the same alphabet Σ
3. $\delta((s_1, s_2), a) = (\delta_1(s_1, a), \delta_2(s_2, a))$
4. $q_0 = (q_1, q_2)$
5. $F = \{(s_1, s_2) \in Q \mid q_1 \in F_1 \text{ and } s_2 \in F_2\}$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Regular languages closed under unions



Proof contin

We now define the product automaton M as follows:

1. $Q = Q_1 \times Q_2$
2. We use the same alphabet Σ
3. $\delta((s_1, s_2), a) = (\delta_1(s_1, a), \delta_2(s_2, a))$
4. $q_0 = (q_1, q_2)$
5. $F = \{(s_1, s_2) \in Q \mid q_1 \in F_1 \text{ and } s_2 \in F_2\}$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导



Non-deterministic finite automata

WeChat: cstutorcs

Reading: ITC Section 1.2
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

DFA versus NFAs

程序代写代做 CS编程辅导

To show that regular languages are also closed under the concatenation and star operations, it is convenient to employ the concept of a Non-deterministic Finite Automaton (NFA for short).



In the automata we have seen so far, every state has exactly one outgoing edge for every symbol. That is, for every state, the "reaction" to any input symbol is uniquely determined. Such an automaton is also called a Deterministic Finite Automaton (DFA for short).

QQ: 749389476

We will generalize this to also allow non-unique (think randomized or parallelized) computations. NFAs are a model for such computations.

<https://tutorcs.com>

Example: the NFA N_1

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

For the machine N_1 we get

QQ: 749389476

$L(N_1) = \{w \mid w \text{ contains } 11 \text{ or } 101 \text{ as a substring}\}$

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Example: the NFA N_1

Differences



ε can be "read"

same states
have several
instructions
for the same
letter

WeChat: cstutorcs

source states
Assignment Project Exam Help
for all letters

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Talking: Ruth Umer

程序代写代做 CS 编程辅导

Example: the NFA N_1

Differences



E can be "read"

{ Examples or words

10110 ✓
accepted

1000 X
not accepted

WeChat: cstutorcs

source states
for all letters

Email: tutorcs@163.com

A word is accepted by an NFA if
there is at least one path reading
the word that leads to an accept state.

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Example: the NFA N_1

Differences



ϵ can be "read"

ϵ



{ Examples or words

10110 ✓
accepted

1000 X
not accepted

WeChat: cstutorcs

source states
for all letters

Email: tutorcs@163.com

$$(\mid \mid \mid \mid = \mid \epsilon \mid \mid)$$

same states
have several
instructions
for the same
letter

A word is accepted by an NFA if
there is at least one path reading
the word that leads to an accept state.

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Example: the NFA / M

The diagram shows a Non-deterministic Finite Automaton (NFA) with four states: q_1 , q_2 , q_3 , and q_4 . State q_1 is the start state, indicated by an incoming arrow. Transitions are as follows: $q_1 \xrightarrow{0,1} q_2$, $q_2 \xrightarrow{\epsilon} q_3$, $q_2 \xrightarrow{1} q_4$, $q_3 \xrightarrow{0,1} q_4$, and $q_4 \xrightarrow{1} q_3$.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

https://tutorcs.com

Consider word: leave

the word is accepted since leave exist branches leading to accept states

A computation stops

程序代写代做 CS 编程辅导

Example: the NFA N_1

10001
not accepted



WeChat: cstutorcs

Assignment Project Exam Help

For the machine N_1 we get

Email: tutorcs@163.com
($\{0, 1\}^*$ contains 101
or 11 as a substring)

QQ: 749389476

<https://tutorcs.com>

Reminder:
For alphabet
 Σ , the set
of all words
over Σ is
denoted by
 Σ^* .

Talking: Ruth Urner

Formal definition of a non-deterministic finite automaton

程序代写代做 CS编程辅导

For an alphabet Σ , we have $\Sigma_\epsilon = \Sigma \cup \{\epsilon\}$.



Definition

A non-deterministic finite automaton is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

WeChat: cstutorcs

Assignment Project Exam Help

1. Q is a finite set called the set of states
2. Σ is a finite set called the alphabet,
3. $\delta : Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$ is the transition function,
4. $q_0 \in Q$ is the start state, and
5. $F \subseteq Q$ is the set of accept states.

Email: tutorcs@163.com

QQ: 749389476

<https://tutors.com>

程序代写代做 CS编程辅导

Formal description of the NFA N_1

N_1



Formal description of $N_1 = (Q, \Sigma, \delta, q_0, F)$

$$Q = \{q_1, q_3, q_4, q_5\}, q_0 = q_1, F = \{q_5\}.$$

$$\Sigma = \{0, 1, \epsilon\}$$

Assignment Project Exam Help

$$\begin{array}{c|cc} s & 0 & 1 \\ \hline q_1 & \{\epsilon, q_3\} & \{q_1, q_3\} \end{array}$$

$$\begin{array}{c|cc} s & 0 & 1 \\ \hline q_2 & \{\epsilon, q_3\} & \{\epsilon, q_3\} \end{array}$$

$$\begin{array}{c|cc} s & 0 & 1 \\ \hline q_3 & \emptyset & \{q_1\} \end{array}$$

$$\begin{array}{c|cc} s & 0 & 1 \\ \hline q_4 & \{\epsilon, q_3\} & \{q_4\} \end{array}$$

Email: tutorcs@163.com

These are the same word!!

QQ: 749389476

ε | ε | ε ε | ε ε | ε ε | ε ε

<https://tutorcs.com>

Formal description of the NFA N_1



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

For the machine N_1 we get

$$L(N_1) = \{w \mid w \text{ contains } 11 \text{ or } 101 \text{ as a substring}\}$$

Formal definition of acceptance for NFAs

程序代写代做 CS编程辅导

For a string $w = w_1 w_2 \dots w_n$ where $w_i \in \Sigma$ for some alphabet Σ , we let strings $z_0 w_1 z_1 w_2 z_2 \dots z_{n-1} w_n z_n$ where each z_i is a sequence of 0 or more symbols ϵ represent the string w as a string over Σ .



Definition

Let $N = (Q, \Sigma, \delta, q_0, F)$ a non-deterministic finite automaton (NFA) and let w be a string over Σ . We say that N accepts w if we can write $w = y_1 y_2 \dots y_m$ with $y_i \in \Sigma_\epsilon$ and there exists a sequence s_0, s_1, \dots, s_m of states such that

1. $s_0 = q_0$, Email: tutorcs@163.com
2. $s_{i+1} \in \delta(s_i, y_{i+1})$ for $i = 0, 1, \dots, m$, and QQ: 749389476
3. $s_m \in F$.

<https://tutorcs.com>

We then define the language $L(N)$ recognized by NFA N in the same way as for DFAs, namely as the set of all words that are accepted by N .

程序代写代做 CS编程辅导

Formal definition of acceptance for NFAs

$|w| = \omega$
 $|\Sigma| = \epsilon$
 $\{\epsilon\} \subset \Sigma$
 $w \in \Sigma^*$

For a string $w = z_0 w_1 z_1 w_2 z_2 \dots z_n w_n z_n$ where each z_i is a sequence of 0 or more symbols ϵ representing some word in Σ^* .



Definition

Let $N = (Q, \Sigma, \delta, q_0, F)$ a non-deterministic finite automaton (NFA) and let w be a string over Σ . We say that N accepts w if we can write $w = y_1 y_2 \dots y_m$ with $y_i \in \Sigma^*$ and there exists a sequence $s_0 s_1 s_2 \dots s_m$ of states such that

1. $s_0 = q_0$,
2. $s_{i+1} \in \delta(s_i, y_{i+1})$ for $i = 0, 1, \dots, m$, and
3. $s_m \in F$.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Example: the NFA N_2

程序代写代做 CS编程辅导



Assignment Project Exam Help

Email: tutorcs@163.com

For the machine N_2 we get
QQ: 749389476

$L(N_2) = \{w \mid w \text{ contains } 1 \text{ at the third position from the end}\}$
<https://tutorcs.com>

程序代写代做 CS编程辅导

Example: the NFA N_2



WeChat: cstutorcs
0101 ✓ 0001 ✗
1 1 1 1 ✗ 0 0 0 0 1 ✗
Assignment Project Exam Help

For the machine N_2 we get

Email: tutorcs@163.com

QQ: 749389476
 $= \{ w = w_1 w_2 \dots w_n \in \Sigma^* \mid w_{n-2} = 1 \}$ at the third position from the end }

<https://tutorcs.com>