

程序代写代做 CS编程辅导



Introduction

cs2001

Theory of Computation

Lecture 8

WeChat: cstutorcs

Ruth Urner
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476
Febuary, 2023

<https://tutorcs.com>

程序代写代做 CS编程辅导



WeChat: cstutorcs

Ruth Urner

Office hours

Mo: 3-4

Thu: 11-12

on zoom

(link in bio)

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导



WeChat: cstutorcs

Ruth Urner

Assignment Project Exam Help

February 2023

Email: tutorcs@163.com

$$S = \{s_1, s_2, s_3, \dots, s_{107}\}$$

QQ: 749389476

$$s_i, s_j, i \in \{1, \dots, 107\}$$

<https://tutorcs.com>

程序代写代做 CS编程辅导



Finite Automata

WeChat: cstutorcs

Reading: ITC Section 1.1
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Finite Automata

程序代写代做 CS编程辅导



A finite automaton or ~~finite state machine~~ is a simple computational model.

WeChat: cstutorcs

Assignment Project Exam Help

We will work with this model of computation for the next part of this course.

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

A simple automaton–sliding door example

Consider an automatic sliding door with two pads that receive signals if someone is standing on them:




WeChat: cstutorcs

Assignment Project Exam Help

We can model the controller of the sliding door as a simple automaton:

Email: tutorcs@163.com



Here we use: $C = \text{CLOSED}$, $O = \text{OPEN}$, $F = \text{FRONT}$, $R = \text{REAR}$, $B = \text{BOTH}$, $N = \text{NEITHER}$

A simple automaton—sliding door example

程序代写代做 CS编程辅导



Here we use: $C = \text{CLOSED}$, $O = \text{OPEN}$, $F = \text{FRONT}$, $R = \text{REAR}$, $B = \text{BOTH}$, $N = \text{NEITHER}$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com
The behavior of the door can be described in terms of the following transition function:


QQ: 749389476

| | NEITHER | FRONT | REAR | BOTH |
|--------|---------|-------|--------|--------|
| CLOSED | CLOSED | OPEN | CLOSED | CLOSED |
| OPEN | CLOSED | OPEN | OPEN | OPEN |

<https://tutorcs.com>

State diagram of M_1

We can use a state diagram to describe a finite automaton M_1 :



WeChat: cstutorcs

Interpretation of the state diagram: The arrow “coming out of nowhere” going into the leftmost state, signals, that this marks the start state. This automaton can read letters from the alphabet $\Sigma = \{0,1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has a label σ , and moves along that arrow to a new state.

Examples:

QQ: 749389476

- If we feed the string 10010 to M_1 , we move through the states q_1, q_2, q_3, q_2, q_3 , the last one is not an accept state, which is not an accept state.
- If we feed the string 1101 to M_1 , we end up in state q_2 , which is an accept state (accept states are the nodes with a double circle).
- If we feed the empty string ϵ to M_1 , we end up in state q_1 , which is not an accept state.


程序代写代做 CS 编程辅导

State diagram of M_1

We can use a [QR code](#)



to describe a finite automaton M_1 :



Interpretation of the state diagram: The arrow "going out of nowhere" going into the leftmost state, signals, that this state is the **start state**. This automaton can read letters from the **alphabet** $\Sigma = \{0, 1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has label σ , and moves along that arrow to a new state.

Examples:

- If we feed the string 00101 to M_1 , we see that it ends at state q_4 .

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

State diagram of M_1

We can use a st

scribe a finite automaton M_1 :



Interpretation of the state diagram: The "edge coming out of nowhere" going into the leftmost state, signals, that this state is the **start state**. This automaton can read letters from the **alphabet** $\Sigma = \{0, 1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has label σ , and moves along that arrow to a new state.

WeChat: cstutorcs
Assignment Project Exam Help

Examples:

- If we feed the string 00101 to M_1 , we move through the states $q_1, q_2, q_3, q_2, q_2, q_3$, and end up in state q_3 , which is not an accept state.
- If we feed the string 1101 to M_1 , ends up in q_2 , string is accepted.

QQ: 749389476

<https://tutorcs.com>

Formal definition of a finite automaton

程序代写代做 CS编程辅导



Definition

A **finite automaton** is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the **set of states**,
2. Σ is a finite set called the **alphabet**,
3. $\delta : Q \times \Sigma \rightarrow Q$ is the **transition function**,
4. $q_0 \in Q$ is the **start state**, and
5. $F \subseteq Q$ is the **set of accept states**.

<https://tutorcs.com>

程序代写代做 CS编程辅导

Formal definition of a finite



Definition

A **finite automaton** is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the **set of states**,
2. Σ is a finite set called the **alphabet**,
3. $\delta : Q \times \Sigma \rightarrow Q$ is the **transition function**,
4. $q_0 \in Q$ is the **start state**, and
5. $F \subseteq Q$ is the **set of accept states**.

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Formal description of M_1



The above state diagram corresponds to the following formal description:

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

WeChat: cstutorcs

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$,
3. δ is defined by the following table:

Email: tutorcs@163.com

| | 0 | 1 |
|----|----|----|
| q1 | q1 | q2 |
| q3 | q2 | q2 |

QQ: 749389476

4. q_1 is the start state,
5. $F \subseteq \{q_2\}$.

Given the description of an automaton, we can ask: which strings will lead to an accept state when fed into the automaton? As we have seen in the example computations with M_1 before, some strings do and others don't. The set of strings that do lead to an accept state form a language over Σ , the **language of M_1** .

程序代写代做 CS编程辅导

Formal description of M_1



The above state diagram corresponds to the following formal description:

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

$$Q = \{q_1, q_2, q_3\}$$

$$\Sigma = \{0, 1\}$$

q_1 is starting state

$$F = \{q_2\}$$

WeChat: cstutorcs

| | 0 | 1 |
|-------|-------|-------|
| 0 | q_1 | q_1 |
| 1 | q_2 | q_2 |
| q_1 | q_3 | q_3 |
| q_2 | q_2 | q_2 |
| q_3 | q_1 | q_1 |

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Language accepted by an automaton

程序代写代做 CS编程辅导



Let Σ be the alphabet and M be an automaton M . Then we let

$$L(M) = \{w \in \Sigma^k \mid k \in \mathbb{N} \text{ and } w \text{ is accepted by } M\}$$

WeChat: cstutorcs

denote the language of machine M . The is $L(M)$ is the set of all words over Σ that are accepted by machine M .

Email: tutorcs@163.com

For the language $A = L(M)$ we also say machine M recognizes (or accepts) A .

QQ: 749389476

<https://tutorcs.com>

Formal definition of acceptance

程序代写代做 CS编程辅导



Definition

Let $M = (Q, \Sigma, \delta, q_0, F)$ a finite automaton and $w = w_1 w_2 \dots w_n$ a string over Σ . We say that M accepts w if there exists a sequence $s_0 s_1 s_2 \dots s_n$ of states such that

1. $s_0 = q_0$,

2. $\delta(s_i, w_{i+1}) = s_{i+1}$ for $i = 0, 1, \dots, n-1$,

3. $s_n \in F$.

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Language accepted by M_1

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

For the machine M_1 we get Email: tutorcs@163.com

QQ: 749389476

$L(M_1) = \{w \mid w \text{ contains at least one } 1 \text{ and the number of } 0\text{s after the last } 1 \text{ is even}\}$

<https://tutorcs.com>

Task for you: convince yourself that this is exactly the set of words accepted by this automaton.

程序代写代做 CS 编程辅导

Language accepted by ...



What is the language of M_1 ?


WeChat: cstutorcs

- all words that end with 1 are accepted
Assignment Project Exam Help
 $\{w_1 w_2 \dots w_n \in \Sigma^* \mid w_k = 1\} \subseteq L(M_1)$
- but there are other words (e.g. 100) that don't end with 1 and are also accepted.
Email: tutorcs@163.com
QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Language accepted by M_1



WeChat: cstutorcs

For the machine M_1 we get

0100 gets accepted

$L(M_1) = \text{Assignment Project Exam Help}$

Email: tutorcs@163.com


QQ: 749389476

Task for you: figure out what exactly is the set of words accepted by this automaton.

<https://tutorcs.com>

程序代写代做 CS编程辅导

Language accepted by M_1



WeChat: cstutorcs

For the machine M_1 we get

$L(M_1) = \{ \text{all binary words where 1 and the number of 0's is even} \}$

Email: tutorcs@163.com


QQ: 749389476

Task for you: figure out what exactly is the set of words accepted by this automaton.

<https://tutorcs.com>

Examples automaton M_2

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

For the machine M_2 we get

$$L(M_2) = \{w \in \{0, 1\}^* \mid w \text{ ends with letter 1}\}$$

Task for you: convince yourself that this is exactly the set of words accepted by this automaton.

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Examples automaton M_2



Talking: Ruth Urner

Words accepted | Words not accepted

WeChat: cstutorcs

001 ✓

010 ✓

0111

Assignment Project Exam Help

000 X

001 X

Email: tutorcs@163.com X


$L(M_2) = \{ \text{We} \dots \text{1} \text{S} \text{ words with 1 S} \}$

QQ: 749389476

https://tutorcs.com

Examples automaton M_3

程序代写代做 CS编程辅导



WeChat: cstutorcs

Assignment Project Exam Help

For the machine M_3 we get

Email: tutorcs@163.com

$$L(M_3) = \{w \mid w \in \{0\}^* \cup \text{empty string or ends with letter 0}\}$$

Task for you: convince yourself that this is exactly the set of words accepted by this automaton.

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Examples automaton



You are screen sharing Stop Share



Talking: Ruth Urner

Words accepted { Words not accepted
WeChat: cstutorcs

010 ✓ 001 X
Assignment Project Exam Help


0110 ✓ 0101 X

Email: tutorcs@163.com

$L(M_3) = \{w \in \{0,1\}^* \mid w \text{ ends with } 0\}$
Set M_3 contains only the empty word ϵ
<https://tutorcs.com>

More examples: M_4

程序代写代做 CS编程辅导



程序代写代做 CS编程辅导


More examples: M4



Words accepted

aabba ✓

baaabab ✓



Words that
are not accepted

abb X

baaba X

$L(M_4) = \{ \text{words } w \text{ such that } w \neq \epsilon \text{ and } w \text{ starts}$

$\text{and ends with the same letter}\}$

<https://tutorcs.com>

Design an automaton that verifies if a string contains an odd number of 1s

程序代写代做 CS编程辅导



Design an automaton that verifies if a string contains an odd number of 1s

verifies if a string contains an odd number of 1s

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutores@163.com
QQ: 749389476
<https://tutorcs.com>

Talking: Ruth Urner

Design an automaton that verifies if a string contains 001 as a substring

程序代写代做 CS编程辅导



程序代写代做 CS编程辅导



Regular Languages

WeChat: cstutorcs

Reading: ITC Section 1.1
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Regular language

程序代写代做 CS编程辅导



Definition

A language L over some alphabet Σ is called a **regular language** if there exists a finite automaton M such that $L = L(M)$, that is, if there exists a finite automaton that recognizes it.

WeChat: cstutorcs
Assignment Project Exam Help
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Regular language



Definition ✓

A language L is called a regular language if there exists a finite automaton M such that $L = L(M)$, that is, if there exists a finite automaton that recognizes it.

Assignment Project Exam Help

- $\{ \omega \in \{0,1\}^* \mid \omega \text{ contains } 001 \text{ as a substring} \}$

Email: tutorcs@163.com

- $\{ \omega \in \{0,1\}^* \mid \text{The number of } 1 \text{ is odd} \}$

QQ: 749389476

<https://tutorcs.com>

Regular operations on languages

程序代写代做 CS编程辅导

Definition:

Let A and B be languages. Then we define the following operations that each form a new language:



- **Union:** $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.
WeChat: cstutorcs
Assignment Project Exam Help
- **Concatenation:** $A \circ B = \{wv \mid w \in A \text{ and } v \in B\}$.
Email: tutorcs@163.com
- **Star:** $A^* = \{w_1w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$
QQ: 749389476
<https://tutorcs.com>

程序代写代做 CS 编程辅导

Regular c



In particular
for an
alphabet
 Σ , the set
 Σ^* is the
set of
all finite
words over
 Σ .

Ex:

$$A = \{01\}$$

$$B = \{1, 11\}$$



13

$$A \times B \ni (01, 110)$$

not $\in \Sigma^*$

Definition:

Let A and B

then we define the following operations that each form a new language:

- Union: WeChat: costurores $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.

Ex: $A \cup B = \{01, 001, 0001, 1, 11, 110, 110\}$

- Concatenation: $A \circ B = \{w \mid w = x \in A \text{ and } y \in B\}$

Ex: $A \circ B = \{011, 0011, 00011, 0111, 00111, 000111\}$

- Star:

$$A^* = \{w_1 w_2 \dots w_k \mid w_i \in A \text{ and } k \in \{0, 1, \dots, k\}\}$$

Ex: $A^* = \{ \dots, 01, 001, 0001, 01001, 00101, 010001, 0001001, 010101, 0100101, \dots \}$

\uparrow infinite set of words...

<https://tutorcs.com>

QQ: 749389476

Talking: Ruth Urner

程序代写代做 CS 编程辅导

In particular
for an
alphabet
 Σ , the set
 Σ^* is the
set of
all finite
words over
 Σ .

$B \subseteq A^*$
 $A \subseteq B^*$

Regular op

$$\Sigma = \{0, 1\}$$

$$A = \{0\}$$

$$B = \{1\}$$

Ex:



Definition:

Let A and B

then we define the following operations that each form a new language:

- Union: WeChat: $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.

Ex: $A \cup B = \{01, 001, 0001, 1, 11, 110, 10\}$

- Concatenation: $A \circ B = \{w_1 w_2 \mid w_1 \in A \text{ and } w_2 \in B\}$

Ex: $A \circ B = \{011, 0011, 00011, 0111, 00111, 000111\}$

- Star:

$A^* = \{w_1 w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$

Ex: $A^* = \{0, 01, 001, 0001, 0100, 00100, 000100, 010101, 0100101, \dots\}$

\uparrow
infinite set of words...

<https://tutorcs.com>

$$A \times B = \{01, 110\}$$

$$\text{not } \in \Sigma^*$$

$$C = \{0, 1\}$$

$$B \subseteq C^*$$

$$A \subseteq C^*$$

$$D = \{0, 1, 00, 11\}$$

$$B \subseteq D$$

$$A \subseteq D^*$$

$$C = \{0, 1, 00, 11, 000, 110, 0010, 1001, 0100, 1110, 000100, 010101, 0100101, \dots\}$$

Talking: Ruth Urner

End of presentation. Click to exit.

程序代写代做 CS编程辅导

$$\Sigma = \{0, 1\}$$

Mouse Select Text



You are screen sharing Stop Share

Talking:

$$A = \{1\}$$

$$A^* = \{ \epsilon, 1, 11, 111 \}$$



WeChat: cs_tutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

$$\exists \quad , \quad |A^*| = \infty$$

$$\Sigma' = \{0, 1, 2\}$$

Automation

$$(Q, \Sigma, \delta, s_0, F)$$

↑
alphabet is part of the
definition of an automata

<https://tutorcs.com>

Regular operations reproduce regular languages

程序代写代做 CS编程辅导



Theorem

The set of all regular languages is **closed** under the three regular operations.
WeChat: cstutorcs

Assignment Project Exam Help

That is: if A and B are regular languages, then A^* , $A \cup B$ and $A \circ B$ are also regular languages.
Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Problem 1.4 from ITC

Here we design an automaton that recognizes the **intersection** of two languages for which we have simple automata recognizing them.



WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>


We will now use a similar “product” for the general construction of an automaton that recognizes the **union** of two regular languages.

程序代写代做 CS 编程辅导

Problem 1.4 from ITC

E = {a, b}

Here we design a DFA which we have si



given two languages A and B.

A = {w | w contains at least 3 a's}

B = {w | w contains at least 2 b's}

We define automaton M_1 with $L(M_1) = A$

WeChat: cstutorcs



Assignment Project Exam Help

and automaton M_2 with $L(M_2) = B$

Email: tutorcs@163.com



QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导

Problem 1.4 from ITC

$$M = (Q, \Sigma, \delta)$$

$$\Sigma = \{a, b\}$$

Q,

$$(q_{0a}, q_{0b})$$

$$\{(q_{1a}, q_{1b})\}$$

For the state diagram we write
 $q_{1ab} = (q_{1a}, q_{1b})$

$\Sigma = \{a, b\}$
Here we design a
which we have si



cognizes the intersection of two languages for
recognizing them.

given two A and B .

$A = \{w \in \Sigma^* \mid w \text{ contains at least 3 } a's\}$

$B = \{w \in \Sigma^* \mid w \text{ contains at least 2 } b's\}$

We can now construct automaton M that
WeChat: cstutorcs
 $A \cap B$ as follows:



$A \cap B$
 $\Sigma = \{a, b\}$
 $w \text{ contains at least 3 } a's \text{ and at least 2 } b's\}$

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Modification of the
Problem 1.4 from ITC

$$M = (Q, \Sigma, Q_0, \delta)$$

$$\Sigma = \{a, b\}$$

Q,

$$(q_{0a}, q_{0b}),$$

$$\{ \dots \}$$

For the state diagram
we write
 $q_{1ab} = (q_{1a}, q_{1b})$

$\Sigma = \{a, b\}$
Here we design a
which we have si



cognizes the intersection of two languages for
recognizing them.

intersection
union

given two

$A = \{w \in \Sigma^* \mid w \text{ contains at least 3 } a's\}$

$B = \{w \in \Sigma^* \mid w \text{ contains at least 2 } b's\}$

We can now construct automaton $\underline{\Delta}$ that

WeChat: cstutorcs

$A \cap B$ as follows:

$$A \cup B =$$

Σ^*

w contains at least

or at

least 2 b's }

← 6 accept states!



Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Regular languages closed under unions

程序代写代做 CS编程辅导

We start by proving if A and B are regular languages over some alphabet Σ , then $A \cup B$.



Proof:

To prove that $A \cup B$ is regular, we need to show that there exists an automaton WeChat: cstutorcs

$M = (Q, \Sigma, \delta, q_0, F)$
Assignment Project Exam Help

with

Email: cstutorcs@163.com

Since A and B are regular, we know there exist automata $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ with QQ: 749389476

<https://tutorcs.com> = B

程序代写代做 CS编程辅导

Regular languages closed under unions

Since M_1 and M_2 the goal is to construct an automaton that recognizes $A \cup B$ using the components of M_1 and the

general
case

We start by p
some alphabet



and B are regular languages over $A \cup B$.

Goal for

To show that $A \cup B$ is regular, we need
WeChat: cstutorcs
show that there exists an automaton

that recognizes $A \cup B$.

We know that A and B are regular languages. Hence there exist

languages $L(M_1)$ and $L(M_2)$

automata $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ such that

$A = L(M_1)$ and $B = L(M_2)$.

<https://tutorcs.com>

Regular languages closed under unions

程序代写代做 CS编程辅导

Proof continued:

We now define the regular automaton M as follows:



1. $Q = Q_1 \times Q_2$ WeChat: cstutorcs
2. We use the same alphabet Σ Assignment Project Exam Help
3. $\delta((s_1, s_2), a) = (\delta_1(s_1, a), \delta_2(s_2, a))$ Email: tutorcs@163.com
4. $q_0 = (q_1, q_2)$ QQ: 749389476
5. $F = \{(s_1, s_2) \in Q \mid s_1 \in F_1 \text{ or } s_2 \in F_2\}$ <https://tutorcs.com>

程序代写代做 CS 编程辅导

Regular languages citoorcs

Stop Sharing Stop Share

Home

Talking: Ruth Urner

$M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$

$M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$

We now define the product automaton M as follows:

Proof continues

QR code linking to the proof continuation.

1. $Q = Q_1 \times Q_2$
2. We use the same alphabet Σ
3. $\delta((s_1, s_2), a) = (\delta_1(s_1, a), \delta_2(s_2, a))$
4. $q_0 = (q_1, q_2)$
5. $F = \{(s_1, s_2) \in Q \mid q_1 \in F_1 \text{ and } s_2 \in F_2\}$

WeChat: cstutorcs

Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS编程辅导



Non-deterministic finite automata

WeChat: cstutorcs

Reading: ITC Section 1.2
Assignment Project Exam Help

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

DFA versus NFAs

程序代写代做 CS编程辅导

To show that regular languages are also closed under the concatenation and star operations, it is convenient to employ the concept of a Non-deterministic Finite Automaton (NFA for short).



In the automata we have seen so far, every state has exactly one outgoing edge for every symbol. That is, for every state, the "reaction" to any input symbol is uniquely determined. Such an automaton is also called a Deterministic Finite Automaton (DFA for short).

QQ: 749389476

We will generalize this to also allow non-unique (think randomized or parallelized) computations. NFAs are a model for such computations.

<https://tutorcs.com>

Example: the NFA N_1

程序代写代做 CS编程辅导



Assignment Project Exam Help

Email: tutorcs@163.com

For the machine N_1 we get

QQ: 749389476

$L(N_1) =$
<https://tutorcs.com>

程序代写代做 CS 编程辅导

Example: the NFA N_1

Differences



ε can be "read"

same states
have several
instructions
for the same
letter

WeChat: cstutorcs

source states
Assignment Project Exam Help
for all letters

Email: tutorcs@163.com

QQ: 749389476

<https://tutorcs.com>

Talking: Ruth Umer

程序代写代做 CS 编程辅导

Example: the NFA N_1

Differences



E can be "read"

{ Examples or words

10110 ✓
accepted

1000 X
not accepted

WeChat: cstutorcs

source states
for all letters

Email: tutorcs@163.com

A word is accepted by an NFA if
there is at least one path reading
the word that leads to an accept state.

QQ: 749389476

<https://tutorcs.com>

程序代写代做 CS 编程辅导

Example: the NFA N_1

Differences



ϵ can be "read"

ϵ



{ Examples or words

10110 ✓
accepted

1000 X
not accepted

WeChat: cstutorcs

source states
for all letters

Email: tutorcs@163.com

$$(\mid \mid \mid \mid = \mid \epsilon \mid \mid)$$

same states
have several
instructions
for the same
letter

A word is accepted by an NFA if
there is at least one path reading
the word that leads to an accept state.

QQ: 749389476

<https://tutorcs.com>