SOFTWARE IMPLEMENTATION PROCEDURE

PROJECT: Traduce Señas

TEAM MEMBERS:
Luis Alejandro Duarte Aldana
Juan Mauricio Suaza Solorzano
Juan Camilo Fierro Esquivel

NATIONAL LEARNING SERVICE – SENA
Software Analysis and Development

2026

Table of Contents

Introduction 3
Scope 3
Deployment architecture 4
Prerequisites 4
Deployment procedure 5
Step 1. Prepare the server 5
Step 2. Get the code 5
Step 3. Configure the environment variables 5
Step 4. Build and start the backend 6
Step 5. Verify the backend 6
Step 6. Publish the web and desktop version 6
Step 7. Distribute the mobile application 6
Step 8. Create the administrator user 6
Step 9. Load the initial content 7
Implementation acceptance tests 7
Rollback plan 7
Post-operation 7
Conclusions 8
References 9

Introduction

The deployment procedure describes, step by step, how to put Traduce Señas into operation in a production or test environment: what is needed, the order in which the components are installed, how to verify that everything works, and how to roll back to the previous version if something fails.


The procedure is intended for the system administrator or the team member responsible for the deployment, and it starts from a clean server with internet access.

Scope

It covers the deployment of the complete backend (API Gateway, five microservices, databases, and RabbitMQ), the publication of the web and desktop versions, and the distribution of the mobile application. It does not cover the configuration of domains or certificates of a specific organization, which are mentioned as prerequisites.

Deployment architecture

Figure 1
System deployment diagram



Note. Own elaboration.

Only the API Gateway (port 8080) and the web server are exposed to the network. The microservices (3001 to 3005), the databases, and RabbitMQ are only accessible within the internal Docker network; the database ports are published only on 127.0.0.1 for administration tasks.

Prerequisites

Table 1
Server requirements

Resource	Minimum	Recommended
Processor	2 vCPU	4 vCPU
RAM	4 GB	8 GB
Disk	20 GB	50 GB SSD
Operating system	64-bit Linux (Ubuntu 22.04 LTS) or Windows with Docker Desktop	Ubuntu 24.04 LTS
Software	Docker 24+, Docker Compose 2.20+, Git 2.40+	Same, with Node.js 20 LTS for maintenance tasks

Resource	Minimum	Recommended
Network	Ports 80/443 and 8080 open to the internet	Reverse proxy with HTTPS in front of the gateway

Table 2
Information to have before starting

Data	Use
JWT_SECRET (32 characters or more)	Signs session tokens; generate with «openssl rand -base64 48»
POSTGRES_PASSWORD	Password for the five PostgreSQL databases
MONGO_ROOT_PASSWORD	MongoDB password
RABBITMQ_PASSWORD	RabbitMQ password
EMAIL_USER / EMAIL_PASS	SMTP account for sending verification and recovery codes, and the weekly and monthly reports to administrators
APP_URL	Public address of the web app (default https://traducesenas.tech); it is the target of the button in the administrator emails
CORS_ORIGINS	Authorized web domains, separated by commas
TLS certificate	HTTPS required in production

Note. Passwords must not contain the characters @ : / ? # because they are included in the connection URLs.

Deployment procedure

Step 1. Prepare the server

```
sudo apt update && sudo apt upgrade -y
curl -fsSL https://get.docker.com | sh
sudo usermod -aG docker $USER      # log out and log back in
docker --version && docker compose version
```

Step 2. Get the code

```
git clone https://github.com/mauro-1508/backendTS.git backend
git clone https://github.com/tadeo77789/frontendTS.git frontend
cd backend && git checkout main   # or the tag of the version to deploy
```

Step 3. Configure the environment variables

```
cp .env.example .env
nano .env    # complete JWT_SECRET, POSTGRES_PASSWORD, MONGO_ROOT_PASSWORD,
             # RABBITMQ_PASSWORD, EMAIL_USER, EMAIL_PASS and CORS_ORIGINS
```

Docker Compose stops with an error message if any required variable is missing; this prevents starting with default passwords.

Step 4. Build and start the backend

```
docker compose up --build -d
docker compose ps     # all containers must be in running/healthy state
```

The SQL files in each service's db/ folder are applied only when the database volume is created for the first time. On a volume that already exists, new migrations are applied by hand, with the platform running, after taking a backup and without recreating the volume. The complete, ordered list of those commands is in 10-devops/local-setup.md. Always apply them in order and deploy profile-service before the frontend.

Step 5. Verify the backend

```
curl http://localhost:8080/health                # gateway
docker compose logs -f api-gateway    # check for errors
# RabbitMQ panel (server only): http://127.0.0.1:15672
```

Step 6. Publish the web and desktop version

```
cd ../frontend
# Adjust the gateway URL in src/app/config/api.config.ts (for example
https://api.midominio.co)
docker build -t traduce-senas-web .
docker run -d --name traduce-web -p 80:80 traduce-senas-web
```

Step 7. Distribute the mobile application

1. Set the public URL of the gateway (with HTTPS) in api.config.ts.
2. Generate the installer with EAS Build: «npx eas build --platform android» (AAB/APK) or «--platform ios» (IPA).
3. For pilot tests, distribute the APK directly or through Expo Go; for the public, publish it on Google Play and the App Store.

Step 8. Create the administrator user

Register an account from the application, verify the email address, and assign the ADMIN role with an existing administrator (POST /api/iam/users/:id/roles) or, on the first installation, by inserting the relationship into the user_roles table of the iam database.

Step 9. Load the initial content

- Import the sign templates for the alphabet and the words (ADMIN role, route /api/sign-templates).
- Verify that the alphabet appears in the application with its 27 letters (A–Z and Ñ).
- Review the categories and signs published in the lexicon.

Implementation acceptance tests

Table 3
Post-deployment checklist

N.º	Verification	Expected result
1	GET /health on the gateway	200 OK
2	Registration of a new user	Verification email received; account active after verification
3	Login	Token received; main panel visible
4	Translation with the camera	Text displayed and saved in the history
5	«First translation» achievement	Appears in «My achievements» (event processed by profile-service)
6	Statistics with ADMIN role	Charts with the event from test 4
7	Access to statistics with USER role	403 Forbidden
8	Web version in a desktop browser	Interface adapted and camera working

Note. The flow of tests 2 to 6 was run with Docker in the team's local environment on October 5, 2026, with a satisfactory result.

Rollback plan

1. Before each deployment, create a backup: «docker compose exec postgres-iam pg_dump …» for each database and «mongodump» for MongoDB.
2. Tag the deployed version in Git (for example, v1.2.0).
3. If verification fails: «docker compose down», return to the previous tag with «git checkout v1.1.0» and run «docker compose up --build -d».
4. If the migration modified data, restore the backups with «psql < respaldo.sql» and «mongorestore».
5. Record the incident in the corrective actions document.

Post-operation

Table 4
Operation tasks

Task	Frequency	Command or action
Database backup	Daily	pg_dump per service and mongodump, kept for 7 days
Log review	Daily	docker compose logs --since 24h

Task	Frequency	Command or action
Dependency update	Monthly	npm audit and controlled update in a branch
Recognition accuracy review	Monthly	Compare unrecognized translations by sign
Restore test	Quarterly	Restore a copy in a test environment

Conclusions

Thanks to Docker Compose, deploying the complete backend is reduced to configuring an .env file and running a single command, and the web version is delivered as an Nginx container. The checklist and the rollback plan make it possible to deploy safely and revert within minutes if something fails.

References

Broadcom. (2026). *RabbitMQ documentation*. https://www.rabbitmq.com/docs

Docker Inc. (2026). *Docker Compose documentation*. https://docs.docker.com/compose/

Expo. (2026). *Expo documentation*. https://docs.expo.dev/

Newman, S. (2021). *Building microservices: Designing fine-grained systems* (2nd ed.). O'Reilly Media.

OWASP Foundation. (2021). *OWASP Top 10: 2021*. https://owasp.org/Top10/

Sommerville, I. (2016). *Software engineering* (10th ed.). Pearson.