

Detect Fake News From Social Media OR News Websites

Major Project Submitted

in

Partial fulfillment of the requirement of the degree

of

Bachelor of Technology

in

Computer Science and Engineering

By

Rudranil Guchhait – 27600122099

Apurba Mondal – 27600122140

Subhendu Maiti – 27600122053

Sujan Samanta – 27600122204

Hafijul Mondal – 27600122234

Under the guidance of

Prof.(Dr) Himadri Biswas

(Department of Computer Science and Engineering)



BUDGE BUDGE INSTITUTE OF TECHNOLOGY

Affiliated to MAKAUT(formerly WBUT) and Approved by AICTE, Accredited by- NAAC

NBA(National Board of Accreditation-CSE,EE,ECE,ME) valid from Academic Year 2022-23to2025-2026 i.e.upto

30-07-2026 <http://www.bbit.edu.in>

i

July 2026



BUDGE BUDGE INSTITUTE OF TECHNOLOGY(BBIT)

(A unit of Jagannath Gupta Family Trust)

(Approved By AICTE, Govt. of India and Affiliated to MAKAUT WBSCTVESD)

Nischintapur, Budge Budge, Kolkata-700137 Phone:033-24820676/70 Telefax:033-24820641

Email : contact@bbit.edu.in website : www.bbit.edu.in

Certificate

This is to certify that the major project work entitled “**Detect Fake News from Social Media or News Websites**” submitted by **Rudranil Guchhait, Subhendu Maiti, Apurba Mondal, Sujan Samanta, Hafijul Mondal**, to the Department of Computer Science & Engineering, Budge Budge Institute of Technology (BBIT), Kolkata, is a record of bonafide project work carried out under my supervision and guidance. The work is worthy of consideration for the award of the degree of Bachelor of Technology (B.Tech) in Computer Science & Engineering from Maulana Abul Kalam Azad University of Technology (MAKAUT), formerly WBUT.

Date:

Forwarded By:

Name and Signature of the Guide

Name and Signature of the Head
Of the Department

Name and Signature of the Principal

Name and Signature of the Head of
Institute

Declaration

We certify that

- a. the project report entitled “**Detect Fake News from Social Media or News Websites**” is our original work carried out under the guidance of **Dr. Himadri Biswas**. This work has not been submitted to any other institution or university for the award of any degree or diploma.
- b. we have followed the guidelines provided by the Institute in preparing the thesis, and we have conformed to ethical norms and guidelines while writing the thesis.
- c. whenever we have used materials (data, models, figures, and text) from other sources, we have given due credit to them by citing them in the text of the thesis, and giving their details in the references, and taking permission from the copyright owners of the sources whenever necessary.

Name and Signature of
Rudranil Guchhait
University Roll No:27600122099

Date:

Name and Signature of
Apurba Mondal
University Roll No:27600122140

Name and Signature of
Subhendu Maiti
University Roll No:27600122053

Name and Signature of
Sujan Samanta
University Roll No:27600122204

Name and Signature of
Hafijul Mondal
University Roll No:27600122234

NO-PLAGIARISM DECLARATION

We hereby declare that the project entitled “**Detect Fake news from Social or News Websites**”, submitted to Maulana Abul Kalam Azad University of Technology (MAKAUT), West Bengal, is an original piece of work carried out by us. We affirm that the contents of this project report are free from plagiarism and have been prepared by us without copying from any unauthorized source.

All information, data, figures, and references used in this project have been properly cited and acknowledged. Wherever the work of others has been referred to, appropriate references have been provided in the report. We further declare that this project has not been submitted, either in part or in full, to any other university or institution for the award of any degree, diploma, or certification.

We understand that any form of plagiarism, if detected at any stage, may result in disciplinary action as per the rules and regulations of the university.

Place: _____ Budge _____ Budge

Date: _____

Submitted by:

1. Rudranil Guchhait (URN 27600122099)
2. Subhendu Maiti (URN 27600122053)
3. Sujan Samanta (URN 27600122204)
4. Apurba Mondal (URN 27600122140)
5. Hafijul Mondal (27600122234)

Date: _____

Place: Budge Budge Institute of Technology

Signatures of the Students:

ACKNOWLEDGEMENT

We would like to express our sincere gratitude to our project guide Prof. **(Dr.) Himadri Biswas** for his valuable guidance, continuous support, and encouragement throughout the development of this project. His insights, suggestions, and technical expertise played a crucial role in the successful completion of our work.

We are also thankful to the **Department of Computer Science and Engineering, Budge Budge Institute of Technology**, for providing the necessary resources and a supportive academic environment. We would like to extend our gratitude to all faculty members, friends, and our parents for their constant support and motivation during the course of this project.

Rudranil Guchhait

27600122099

Subhendu Maiti

27600122053

Sujan Samanta

27600122204

Apurba Mondal

27600122140

Hafijul Mondal

27600122234

ABSTRACT

The rapid growth of the internet and social media has transformed the way people consume and share news. While this has made information more accessible, it has also increased the spread of fake news and misinformation, influencing public opinion and affecting political, economic, and social decisions. Since manual verification is time-consuming and impractical due to the large volume of online content, there is a growing need for an automated fake news detection system.

This project presents a web-based **Fake News Detection System** that combines evidence-based verification with deep learning to improve the accuracy and reliability of news classification. Unlike conventional approaches that directly classify every news article, the proposed system introduces an **Evidence Verification Layer** before the prediction model. When a user submits a news article or claim, the system first searches trusted sources such as **Wikipedia** and **NewsAPI**. If reliable evidence confirms the authenticity of the news, the system immediately classifies it as **Real**. Otherwise, the news is forwarded to the main prediction model for further analysis.

The core prediction model is a **hybrid Long Short-Term Memory (LSTM) and Convolutional Neural Network (CNN)** architecture. CNN extracts important textual features, while LSTM captures contextual dependencies, enabling effective classification of fake and real news. The model is trained and evaluated using a publicly available **Kaggle** dataset containing approximately **40,000 labeled news articles**. Before training, the data undergoes preprocessing, including text cleaning, tokenization, stop-word removal, stemming, lemmatization, and feature representation.

To evaluate the proposed approach, multiple machine learning and deep learning models, including **Logistic Regression, Support Vector Machine (SVM), CNN, LSTM, and BiLSTM**, are compared using **Accuracy, Precision, Recall, and F1-Score**. Although the BiLSTM model achieved slightly higher experimental accuracy, the **hybrid LSTM+CNN model** was selected for deployment because it provides an excellent balance between prediction accuracy, computational efficiency, and real-time performance.

The system is deployed as a web application using **React** for the frontend and **Flask** for the backend, allowing users to submit news content and receive instant predictions with confidence scores. By combining evidence-based verification with deep learning, the proposed system provides a scalable and practical solution for combating online misinformation.

Contents

TITLE.....	i
CERTIFICATE.....	ii
DECLARATION.....	ii
NO-PLAGIARISM DECLARATION.....	iv
ACKNOWLEDGEMENT.....	v
ABSTRACT.....	vi
INTRODUCTION	1
1.1 Overview	1
1.2 Project Aim.....	1
1.3 Motivation	2
1.4 Problem Statement	2
1.5 Scope of the Project.....	3
LITERATURE SURVEY	4
2.1 Fake News Detection Using Traditional Machine Learning Techniques	4
2.2 Role of Natural Language Processing in Fake News Detection.....	5
2.3 Deep Learning-Based Approaches for Fake News Detection	5
2.4 Word Embeddings and Semantic Representation	6
2.5 Hybrid Models for Fake News Detection	6
2.6 Comparative Studies and Key Observations	7
2.7 Research Gap and Justification of the Proposed Work	7
DETECT FAKE NEWS FROM SOCIAL MEDIA AND NEWS WEBSITE	9
3.1 What is Fake News.....	9
3.2 Sources of Fake News	9
3.3 Impact of Fake News.....	10
3.4 Fake News Detection.....	10
3.5 Role of Machine Learning in Fake News Detection.....	11
3.6 Machine Learning Models for Fake News Detection	11
3.7 Types of Fake News Detection.....	12
3.8 Advantages of Machine Learning-Based Fake News Detection	13

METHODOLOGY	14
4.1 Overview of the Proposed System	14
4.3 Data Collection Module	15
4.4 Text Preprocessing Module	15
4.5 Feature Representation Module	16
4.6 Model Selection and Design	16
4.7 Model Training Process	17
4.8 Model Evaluation.....	17
4.9 System Architecture	18
4.10 Deployment Architecture.....	18
DATA COLLECTION & PREPROCESSING	19
5.1 Data Collection.....	19
5.3 Text Preprocessing Steps.....	20
5.4 Feature Engineering	23
5.5 Data Splitting	24
5.6 Tools and Libraries Used	24
5.7 Outcome of Data Preprocessing	24
SIMULATION & IMPLEMENTATION	25
6.1 Simulation Environment	25
6.2 Libraries and Tools Used	25
6.3 Dataset Loading and Preparation	26
6.4 Implementation of Text Preprocessing	27
6.5 Feature Extraction Implementation	27
6.7 Model Training.....	28
6.8 Model Evaluation.....	29
6.9 Backend Implementation.....	30
6.10 Frontend Implementation.....	30
6.12 Prediction Workflow	30
RESULT & DISCUSSION	32
FUTURE WORK.....	37
8.1 Advanced Deep Learning Models.....	37
8.2 Social Media Account Verification	37

8.3 Multi-Language Support	37
8.4 Real-Time Social Media Monitoring	37
CONCLUSION	39
9.1 Work Summary	39
9.2 Key Outcomes	39
9.3 Limitations.....	39
9.4 Final Remarks	39
REFERENCES	41

INTRODUCTION

1.1 Overview

In the digital era, the consumption and dissemination of news have shifted significantly from traditional print media to online news portals and social media platforms. While this transformation has made information more accessible and instantaneous, it has also created a serious global problem—the rapid spread of **fake news**. Fake news refers to false, misleading, or deliberately fabricated information presented in the form of legitimate news with the intention to deceive readers [4].

Social media platforms such as Facebook, Twitter (X), Instagram, and online news websites allow users to share information instantly with a large audience. Due to the absence of strict verification mechanisms, fake news spreads faster than real news [7], often causing misinformation, social unrest, political instability, and economic consequences. Manual verification of such content is impractical due to the massive volume of data generated daily.

To address this challenge, **Machine Learning (ML)** and **Deep Learning (DL)** techniques have emerged as effective solutions [4]. By leveraging **Natural Language Processing (NLP)**, these techniques can analyze textual patterns, semantic context, and linguistic features [2] to automatically classify news as fake or real. This project focuses on building an automated fake news detection system using machine learning and deep learning models.

1.2 Project Aim

The primary aim of this project is to design and develop an **automated fake news detection system** capable of identifying fake news from **social media platforms and online news websites** using machine learning and deep learning techniques.

The specific objectives of this project are:

- To collect and analyze a large dataset containing fake and real news articles.
- To preprocess unstructured textual data using Natural Language Processing techniques.
- To experiment with various machine learning and deep learning models for fake news classification.
- To implement a **hybrid LSTM + CNN model** for effective fake news detection.
- To compare the performance of different models and justify the selection of the final model.

- To deploy the trained model as a **web-based application** for real-time prediction.

The project aims to achieve high accuracy while maintaining computational efficiency and practical deployability.

1.3 Motivation

The motivation behind this project arises from the increasing influence of fake news on society and the lack of effective automated verification systems. Fake news can manipulate public opinion, spread panic, damage reputations, and influence political and economic decisions [4].

The key motivating factors include:

- **Social Impact:** Fake news can create confusion, fear, and division among people.
- **Political Influence:** Misinformation can affect elections, public trust, and democratic processes.
- **Economic Consequences:** Fake news can influence markets, businesses, and consumer behavior.
- **Technological Advancement:** Recent developments in NLP and deep learning provide opportunities to build intelligent detection systems [2].
- **Need for Automation:** Manual fact-checking is slow and not scalable for large volumes of data.

This project is motivated by the need to create an intelligent, scalable, and real-time solution to mitigate the spread of misinformation.

1.4 Problem Statement

The problem addressed in this project is the **automatic detection of fake news based on textual content**.

The major challenges involved in fake news detection include:

- Similar writing styles between fake and real news.
- Complex language structure and contextual ambiguity.
- Large-scale unstructured text data.
- Rapid evolution of misinformation strategies.

- Traditional rule-based or keyword-based approaches fail to handle these challenges effectively [1]. Therefore, a data-driven machine learning approach is required to identify hidden patterns and linguistic cues in news articles.

1.5 Scope of the Project

The scope of this project is limited to content-based fake news detection using textual data. The system focuses on analyzing English-language news articles and social media content.

The scope includes:

- Fake news detection based on text content.
- Machine learning and deep learning-based classification.
- Real-time prediction through a web interface.
- Comparative analysis of multiple models.

The project does not cover video-based, or audio-based misinformation, which can be explored in future work.

LITERATURE SURVEY

Fake news detection has emerged as a critical research problem due to the rapid expansion of digital media, social networking platforms, and online news portals. The ease with which information can be created and shared has led to the widespread dissemination of misinformation, often with serious social, political, and economic consequences. As a result, researchers from various domains have focused on developing automated systems to detect fake news efficiently and accurately.

This chapter presents a comprehensive review of existing research related to fake news detection. It explores different approaches proposed in the literature, ranging from traditional machine learning techniques to advanced deep learning and hybrid models. The objective of this literature survey is to analyze previous work, identify research gaps, and justify the methodology adopted in this project.

2.1 Fake News Detection Using Traditional Machine Learning Techniques

Early research on fake news detection primarily relied on classical machine learning algorithms [1] that use handcrafted features extracted from textual data. These models focus on statistical and frequency-based patterns within news content.

Common traditional machine learning algorithms include:

- Logistic Regression
- Naive Bayes
- Support Vector Machine (SVM)
- Decision Trees
- Random Forest

In these approaches, textual data is transformed into numerical form using techniques such as **Bag of Words (BoW)** and **Term Frequency–Inverse Document Frequency (TF-IDF)**. These representations measure word frequency and importance but fail to capture semantic meaning and contextual relationships between words.

Although traditional machine learning models are computationally efficient and easy to interpret, they have several limitations:

- Dependence on manual feature engineering
- Inability to capture long-range dependencies
- Limited understanding of word order and context

As fake news often closely resembles real news in structure and language, these limitations reduce the effectiveness of traditional models.

2.2 Role of Natural Language Processing in Fake News Detection

Natural Language Processing (NLP) plays a vital role in fake news detection by enabling machines to process and understand human language [4]. NLP techniques are used to clean, normalize, and structure raw textual data before it is fed into machine learning models.

Key NLP techniques commonly used in fake news detection research include:

- Tokenization
- Stopword removal
- Stemming and lemmatization
- N-gram analysis
- Part-of-speech tagging

Research studies indicate that effective text preprocessing significantly improves classification performance by reducing noise and emphasizing meaningful linguistic patterns [2]. However, NLP techniques alone are insufficient; they must be integrated with powerful learning algorithms to achieve high detection accuracy.

2.3 Deep Learning-Based Approaches for Fake News Detection

The limitations of traditional machine learning approaches led researchers to explore deep learning models capable of automatically learning features from data. Deep learning models eliminate the need for manual feature extraction and are particularly effective in handling unstructured text data.

2.3.1 Convolutional Neural Networks (CNN)

Convolutional Neural Networks (CNN) have been widely used in text classification tasks, including fake news detection. In text-based applications, CNNs act as feature extractors that identify local patterns such as key phrases and n-grams.

Advantages of CNN-based models include:

- Efficient extraction of local features
- Faster training compared to recurrent models
- Strong performance on short and medium-length texts

However, CNNs have limited capability in modeling long-term dependencies and sequential context, which are crucial for understanding complete news articles.

2.3.2 Long Short-Term Memory Networks (LSTM)

Long Short-Term Memory (LSTM) networks are a type of Recurrent Neural Network (RNN) designed to handle sequential data effectively. LSTMs overcome the vanishing gradient problem and can capture long-term dependencies in text.

In fake news detection, LSTM models:

- Preserve word order and sentence structure
- Capture contextual flow across long text sequences
- Outperform traditional machine learning models

Despite their effectiveness, standard LSTM models process text in only one direction, which may limit contextual understanding in certain cases.

2.3.3 Bidirectional Long Short-Term Memory (BiLSTM)

Bidirectional LSTM (BiLSTM) models extend LSTM by processing text sequences in both forward and backward directions. This allows the model to capture complete contextual information from past and future words.

Several research studies report that BiLSTM models achieve higher accuracy than unidirectional LSTM models, especially when combined with word embeddings such as **GloVe** or **Word2Vec**. However, BiLSTM models require higher computational resources and may not be ideal for real-time deployment in resource-constrained environments.

2.4 Word Embeddings and Semantic Representation

Traditional feature extraction methods such as TF-IDF produce sparse vectors and fail to capture semantic relationships between words [4]. To address this issue, researchers introduced word embedding techniques.

Popular word embedding techniques include:

- Word2Vec
- GloVe (Global Vectors for Word Representation)
- FastText

Word embeddings represent words as dense vectors in a continuous vector space [2], where semantically similar words are positioned close to each other. Studies show that combining word embeddings with deep learning models significantly improves fake news detection accuracy by enhancing semantic understanding.

2.5 Hybrid Models for Fake News Detection

Recent research emphasizes the effectiveness of hybrid models that combine multiple deep learning architectures to leverage their individual strengths. [3]

A commonly adopted hybrid approach is **CNN + LSTM** [3], where:

- CNN extracts local textual patterns and important features [3]
- LSTM captures long-term sequential dependencies

Hybrid models provide a strong balance between performance and computational efficiency. Although BiLSTM models may achieve slightly higher accuracy in experimental research, **CNN + LSTM models are often preferred for practical deployment** due to their scalability and efficiency.

2.6 Comparative Studies and Key Observations

Several comparative studies have evaluated the performance of various fake news detection techniques [2]. The key observations from existing literature include:

- Deep learning models consistently outperform traditional machine learning models
- Word embeddings significantly enhance classification performance
- Hybrid models offer robust and stable results
- No single model is universally optimal for all datasets

These observations justify the experimental evaluation of multiple models in this project.

2.7 Research Gap and Justification of the Proposed Work

Despite extensive research, fake news detection remains a challenging problem due to evolving misinformation strategies and linguistic complexity [3]. Many existing studies focus primarily on maximizing accuracy without addressing deployment feasibility.[]

The key research gaps identified include:

- Limited focus on real-time, deployment-ready systems
- High computational cost of advanced deep learning models
- Lack of integration with web-based platforms

This project addresses these gaps by implementing a **deployable hybrid LSTM + CNN model** integrated into a web application for real-time fake news detection.

Paper	Abstract Summary	Main Findings	Outcome measured
Detection of fake news from social media using support vector machine learning algorithms Authors: M. Sudhakar, K.P. Kaliyamurthie Journal/Year: Measurement: Sensors, 2024 * https://www.sciencedirect.com/science/article/pii/S2665917424000047	The paper investigates the capability of various machine learning classifiers and deep learning models for the task of fake news detection. >The models tested include Naive Bayes, Logistic Regression, Support Vector Machine (SVM), Convolutional Neural Networks (CNN), and Long Short-Term Memory (LSTM). >All models were trained and tested using a COVID-19 dataset composed of 1,375,592 tweets.	The study concluded that for their specific dataset, two machine learning algorithms provided a better solution than the deep learning model tested. > SVM model achieved 98 % accuracy and Logistic Regression model also providing 95% accuracy. >LSTM model was the lowest performing classifier, achieving an accuracy of 54%. The paper notes this result indicated that this type of data "doesn't need neural networks".	The primary outcomes measured to evaluate the performance of the different models were • Accuracy • precision score • Recall • F1 Score
LSTMCNN: A hybrid machine learning model to unmask fake news Authors: Deepali Goyal Dev, Vishal Bhatnagar, Bhoopesh Singh Bhati, Manoj Gupta, Aziz Nanthamornphong Journal/Year: Heliyon, 2024 * https://www.cell.com/heliyon/fulltext/S2405-8440(24)01275-1	The paper addresses the widespread dissemination of false information on online platforms, which poses a potential harm to individuals and society. To handle text data efficiently, the paper recommends using feature abstraction and vectorization tools, such as the Count Vectorizer and Tfidf Vectorizer from Python's sci-kit-learn module.	The hybrid CNN + LSTM model achieved an accuracy of 98% in detecting fake news. >This hybrid approach outperformed other models tested, such as SNN (93% accuracy) and RNN + LSTM (91% accuracy). >When compared with other baseline studies, the proposed hybrid model demonstrated superior performance.	The primary outcomes measured to evaluate the performance of the different models were • Accuracy • precision score • Recall • F1 Score

DETECT FAKE NEWS FROM SOCIAL MEDIA AND NEWS WEBSITE

Fake news detection using machine learning is an emerging and highly impactful application of artificial intelligence. With the exponential growth of social media platforms and online news portals, the volume of unverified information circulating on the internet has increased dramatically. This makes manual verification impractical and highlights the need for automated detection systems.

Machine learning provides techniques that enable systems to learn patterns from historical data and make predictions on unseen data. When combined with **Natural Language Processing (NLP)**, machine learning models can analyze textual content, understand linguistic structures, and classify news articles as fake or real. This chapter discusses the fundamental concepts of fake news, its sources and impact, and the role of machine learning models in detecting misinformation.

3.1 What is Fake News

Fake news refers to false, misleading, or deliberately fabricated information presented as legitimate news [4]. It is often designed to mimic the appearance of credible journalism to gain the reader's trust and influence opinions or behavior.

Fake news can be categorized into different forms, such as:

- Completely fabricated news stories
- Manipulated or distorted information
- Misleading headlines or clickbait
- Satirical content presented as factual news

Unlike simple rumors, fake news is often strategically crafted to spread rapidly and achieve specific objectives such as political influence, financial gain, or social disruption.

3.2 Sources of Fake News

Fake news originates from multiple online sources, primarily driven by the ease of content creation and sharing. The most common sources include:

3.2.1 Social Media Platforms

Social media platforms such as Facebook, Twitter (X), Instagram, and WhatsApp allow users to share information instantly. Due to the absence of strict verification mechanisms, fake news can spread quickly and reach a large audience [4].

3.2.2 Online News Websites

Some online news websites publish unverified or misleading information to attract traffic and generate revenue through advertisements.

3.2.3 Blogs and Forums

Personal blogs and discussion forums often share opinion-based or unverified content, which can contribute to misinformation.

3.3 Impact of Fake News

The spread of fake news has serious consequences across multiple domains:

- **Social Impact:** Creates panic, fear, and confusion among the public.
- **Political Impact:** Influences elections, public opinion, and democratic processes.
- **Economic Impact:** Affects financial markets, businesses, and consumer trust.
- **Psychological Impact:** Causes stress, anxiety, and misinformation-induced behavior.

Due to these severe impacts, fake news detection has become a critical area of research.

3.4 Fake News Detection

Fake news detection involves analyzing news content to determine its authenticity. Automated fake news detection systems aim to classify news articles as **Fake** or **Real** based on textual and contextual features.

Detection approaches can broadly be classified into:

- Content-based detection
- Context-based detection

This project focuses primarily on **content-based fake news detection** using textual analysis and machine learning models.

3.5 Role of Machine Learning in Fake News Detection

Machine learning plays a crucial role in fake news detection by enabling systems to learn patterns from labeled datasets. Instead of relying on manually defined rules, machine learning models identify complex relationships within data [1].

Key advantages of using machine learning include:

- Ability to handle large volumes of data
- Automatic feature learning
- Improved accuracy over rule-based systems
- Scalability and adaptability

By training models on labeled fake and real news data, the system can generalize and predict the authenticity of unseen news articles.

3.6 Machine Learning Models for Fake News Detection

Various machine learning and deep learning models have been explored for fake news detection [1]. These models can be broadly categorized into traditional machine learning models and deep learning models.

3.6.1 Traditional Machine Learning Models

Traditional machine learning models rely on manually engineered features and statistical learning techniques.

Common models include:

- **Logistic Regression:**
Used as a baseline classifier. It models the probability of a news article being fake or real based on extracted features.
- **Support Vector Machine (SVM):**
Effective for high-dimensional text data and provides robust classification boundaries.

Although these models are computationally efficient, they lack deep semantic understanding.

3.6.2 Deep Learning Models

Deep learning models automatically learn hierarchical features from text data, making them more effective for complex language tasks. [2]

3.6.2.1 Convolutional Neural Network (CNN)

CNNs are effective in extracting local textual patterns such as important phrases and n-grams[2]. In fake news detection, CNNs help identify discriminative features within news articles.

Advantages of CNN include:

- Efficient feature extraction
- Faster training
- Strong performance on short text segments

However, CNNs alone cannot fully capture long-range dependencies.

3.6.2.2 Long Short-Term Memory (LSTM)

LSTM networks are designed to handle sequential data and capture long-term dependencies. In fake news detection, LSTMs analyze word sequences and sentence structure [2].

Advantages of LSTM include:

- Preserves word order
- Captures contextual flow
- Handles long news articles effectively

3.6.2.3 Hybrid LSTM + CNN Model

The **LSTM + CNN hybrid model** combines the strengths of both architectures:

- CNN extracts local features and key phrases
- LSTM captures long-term contextual dependencies

This hybrid approach provides improved performance and robustness compared to individual models. Due to its strong accuracy and deployment efficiency, this project adopts **LSTM + CNN as the final implemented model**.

3.6.2.4 Bidirectional LSTM (Research Comparison)

Bidirectional LSTM processes text in both forward and backward directions, capturing complete contextual information. Research experiments show that BiLSTM achieves higher accuracy; however, it requires higher computational resources. In this project, BiLSTM is used only for **comparative analysis**, not for final deployment.

3.7 Types of Fake News Detection

Fake news detection approaches can be categorized into the following types:

3.7.1 Content-Based Detection

Content-based detection analyzes the textual content of news articles using NLP and machine learning techniques. It focuses on linguistic patterns, semantics, and writing style.

This project primarily follows this approach.

3.7.2 Context-Based Detection

Context-based detection considers metadata such as author credibility, source reliability, and social engagement. Although effective, this approach requires additional external data.

3.8 Advantages of Machine Learning-Based Fake News Detection

Machine learning-based detection systems offer several advantages:

- Automation of the verification process
- Scalability to large datasets
- Adaptability to evolving misinformation patterns
- Improved detection accuracy

These advantages make machine learning a suitable approach for combating fake news.

METHODOLOGY


A systematic methodology is essential to ensure that the fake news detection system is accurate, reliable, scalable, and suitable for real-time use. The proposed approach integrates **Natural Language Processing (NLP)** techniques with deep learning models to analyze textual data and classify news articles as fake or real. [2,14]

4.1 Overview of the Proposed System

The proposed fake news detection system follows a modular and layered architecture. Each module performs a specific task and passes the output to the next stage in the pipeline.

The major stages of the system include:

- Data Collection
- Text Preprocessing
- Feature Representation
- Model Training
- Model Evaluation
- Web-Based Deployment



This modular design improves flexibility and allows future enhancements without redesigning the entire system.

4.2 Proposed Framework

The proposed framework outlines the logical flow of data and operations involved in the fake news detection process

4.3 Data Collection Module

The data collection module is responsible for acquiring news articles and social media content used for training and testing the model.

Data is collected from:

- Kaggle (FakeNewsNet dataset)
- Online news websites
- Social media sources (for future extensions)

The collected data contains labeled examples of fake and real news, which are essential for supervised learning.

4.4 Text Preprocessing Module

Raw text data often contains noise, redundancy, and irrelevant elements. The text preprocessing module cleans and standardizes the data before feature extraction.

4.4.1 Text Cleaning

Text cleaning operations include: [14]

- Conversion of text to lowercase
- Removal of punctuation and special characters
- Removal of URLs and HTML tags
- Removal of numeric values

This step ensures uniformity in text representation.

4.4.2 Tokenization

Tokenization splits text into individual words or tokens, enabling word-level analysis.

Example:

"Fake news spreads fast"

→ ["fake", "news", "spreads", "fast"]

4.4.3 Stopword Removal

Stopwords such as *is*, *the*, *and*, *of* are removed because they do not contribute significantly to classification and increase computational overhead.

4.4.4 Stemming and Lemmatization

- **Stemming** reduces words to their root form.
- **Lemmatization** converts words into their dictionary form.

These techniques reduce vocabulary size and improve generalization. [12,14]

4.5 Feature Representation Module

After preprocessing, textual data must be converted into numerical form so that machine learning models can process it.

4.5.1 TF-IDF Representation

TF-IDF assigns weights to words based on their importance in a document relative to the entire dataset.

TF-IDF is primarily used for:

- Logistic Regression
- Support Vector Machine (SVM)

4.5.2 Word Embeddings

Word embeddings map words into dense vector representations that capture semantic meaning.

In this project, embeddings are used with deep learning models to improve contextual understanding.

4.6 Model Selection and Design

Multiple machine learning and deep learning models are implemented and evaluated to determine the most suitable model for fake news detection.

4.6.1 Traditional Machine Learning Models

- Logistic Regression
- Support Vector Machine (SVM)

These models are used for baseline performance comparison.

4.6.2 Deep Learning Models

- Convolutional Neural Network (CNN)
- Long Short-Term Memory (LSTM)

These models capture deeper linguistic and contextual patterns in text data.

4.6.3 Hybrid LSTM + CNN Model (Final Model)

The **LSTM + CNN hybrid model** is selected as the final deployed model.

Reason for selection:

- CNN extracts local features and important phrases [3]
- LSTM captures long-term dependencies and sequence context [3]
- Balanced accuracy and computational efficiency
- Suitable for real-time deployment

This model provides strong performance while maintaining scalability.

4.6.4 Bidirectional LSTM (Research Comparison)

Bidirectional LSTM is implemented only for experimental comparison. Although it achieves higher accuracy in research experiments [3,16], it is not selected for deployment due to higher computational cost.

4.7 Model Training Process

The training process involves feeding labeled data into the selected model and adjusting parameters to minimize classification error.

Training configuration includes:

- Loss function: Binary Cross-Entropy
- Batch size: Optimized based on hardware
- Epochs: Multiple iterations until convergence

Validation data is used to monitor overfitting.

4.8 Model Evaluation

Model performance is evaluated using standard classification metrics:

- Accuracy
- Precision
- Recall
- F1-Score

These metrics provide a comprehensive evaluation of the model's effectiveness.

4.9 System Architecture

The system architecture consists of Four layers:

4.9.1 Data Layer - Handles dataset storage and preprocessing.

4.9.2 Evidence Verification Layer- The proposed system includes an Evidence Verification Layer before the hybrid LSTM+CNN model. When a user submits news text, the system first searches for supporting evidence from trusted sources. If sufficient evidence confirms the authenticity of the news, the system immediately classifies it as Real without invoking the deep learning model. If no reliable evidence is found or the news appears suspicious, the input is passed to the hybrid LSTM+CNN model for detailed classification. This two-stage architecture improves efficiency, reduces unnecessary computation, and increases the reliability of predictions by combining evidence-based verification with deep learning.

4.9.3 Model Layer - Includes feature extraction and deep learning models.

4.9.4 Application Layer - Consists of Flask backend and React frontend.

4.10 Deployment Architecture

The trained model is deployed as a web-based application.

- **Backend:** Flask REST API
- **Frontend:** React
- **Communication:** HTTP requests and JSON responses

DATA COLLECTION & PREPROCESSING

Data plays a crucial role in any machine learning or deep learning system. The quality, size, and relevance of the dataset directly influence the performance and reliability of the model. In fake news detection, textual data is often noisy, unstructured, and inconsistent, making data collection and preprocessing essential steps [4,14].

This chapter describes the sources of data used in the project, the characteristics of the dataset, and the detailed preprocessing steps applied to convert raw news articles into a structured format suitable for machine learning and deep learning models.

5.1 Data Collection

The data collection phase involves gathering news articles that are labeled as **Fake** or **Real**. Since fake news detection is a supervised learning problem, labeled data is required to train and evaluate the models. [6,8]

1	title	text	subject	date
2	Donald Trump Sends Out Embarrassing New	' Donald Trump just couldn't wish all Americans a Ha	News	December 31, 2017
3	Drunk Bragging Trump Staffer Started Russia House Intelligence Committee Chairman Devin	Nun	News	December 31, 2017
4	Sheriff David Clarke Becomes An Internet Jok	On Friday, it was revealed that former Milwaukee S	News	December 30, 2017
5	Trump Is So Obsessed He Even Has Obama	On Christmas day, Donald Trump announced that he	News	December 29, 2017
6	Pope Francis Just Called Out Donald Trump	D Pope Francis used his annual Christmas Day messag	News	December 25, 2017
7	Racist Alabama Cops Brutalize Black Boy Whi	The number of cases of cops brutalizing and killing p	News	December 25, 2017
8	Fresh Off The Golf Course, Trump Lashes Out	Donald Trump spent a good portion of his day at his	News	December 23, 2017
9	Trump Said Some INSANELY Racist Stuff Insid	In the wake of yet another court decision that derai	News	December 23, 2017
10	Former CIA Director Slams Trump Over UN B	Many people have raised the alarm regarding the fa	News	December 22, 2017
11	WATCH: Brand-New Pro-Trump Ad Features	Just when you might have thought we d get a break	News	December 21, 2017
12	Papa John's Founder Retires, Figures Out	A centerpiece of Donald Trump's campaign, and nov	News	December 21, 2017
13	WATCH: Paul Ryan Just Told Us He Doesn't	Republicans are working overtime trying to sell their	News	December 21, 2017
14	Bad News For Trump - Mitch McConnell S	Republicans have had seven years to come up with i	News	December 21, 2017
15	WATCH: Lindsey Graham Trashes Media For	The media has been talking all day about Trump and	News	December 20, 2017
16	Heiress To Disney Empire Knows GOP Scam	Abigail Disney is an heiress with brass ovaries who	News	December 20, 2017
17	Tone Deaf Trump: Congrats Rep. Scalise On	L Donald Trump just signed the GOP tax scam into law	News	December 20, 2017
18	The Internet Brutally Mocks Disney's New	A new animatronic figure in the Hall of Presidents at	News	December 19, 2017
19	Mueller Spokesman Just F-cked Up	Donald Tr Trump supporters and the so-called president's favo	News	December 17, 2017
20	SNL Hilariously Mocks Accused Child Moleste	Right now, the whole world is looking at the shockin	News	December 17, 2017
21	Republican Senator Gets Dragged For Going	Senate Majority Whip John Cornyn (R-TX) thought it	News	December 16, 2017
22	In A Heartless Rebuke To Victims, Trump Invi	It almost seems like Donald Trump is trolling Americ	News	December 16, 2017
23	KY GOP State Rep. Commits Suicide Over Alle	In this #METOO moment, many powerful men are b	News	December 13, 2017
24	Meghan McCain Tweets The Most AMAZING	As a Democrat won a Senate seat in deep-red Alaba	News	December 12, 2017

5.1.1 Dataset Source

The primary dataset used in this project is collected from **Kaggle**, specifically the **FakeNewsNet dataset**. FakeNewsNet is a widely used and reliable dataset in fake news detection research. [6,9]

Key reasons for selecting this dataset include:

- Availability of labeled data
- Real-world news articles
- Balanced representation of fake and real news
- Suitability for NLP-based analysis

5.1.2 Dataset Characteristics

The main characteristics of the dataset are as follows:

- **Dataset size:** Approximately 40,000 news articles
- **Data type:** Textual data (news content)
- **Labels:** Fake and Real
- **Language:** English
- **Format:** Structured tabular format

The dataset contains news articles collected from multiple online sources, ensuring diversity in writing styles and topics. [6,9]

5.1.3 Data Acquisition from Online Sources (Supportive Module)

In addition to static datasets, the system architecture supports future integration of real-time data collection from online news websites and social media platforms.

Libraries such as **BeautifulSoup**, **Requests**, **newspaper3k**, and **lxml** are used to extract textual content from online articles. This makes the system extensible for real-time fake news analysis. [3,8]

5.2 Need for Data Preprocessing

Raw textual data cannot be directly used by machine learning models due to several issues such as noise, inconsistency, and redundancy.

Some common problems in raw text data include:

- Presence of HTML tags and URLs
- Irrelevant symbols and punctuation
- Common stopwords
- Different word forms of the same meaning

Data preprocessing is required to clean and normalize the data, reduce dimensionality, and improve model performance.

5.3 Text Preprocessing Steps

The preprocessing pipeline applied in this project consists of multiple sequential steps, each contributing to better feature extraction and classification accuracy.

5.3.1 Text Cleaning


Text cleaning is the first step in preprocessing. It removes unwanted and irrelevant components from the text.

Operations performed include:

- Conversion of all text to lowercase
- Removal of punctuation marks
- Removal of numerical values
- Removal of special characters
- Removal of URLs and HTML tags


This step ensures uniform and clean text representation.

Before Data Cleaning



	title	text	subject	date
0	Donald Trump Sends Out Embarrassing New Year's...	Donald Trump just couldn't wish all Americans ...	News	December 31, 2017
1	Drunk Bragging Trump Staffer Started Russian ...	House Intelligence Committee Chairman Devin Nu...	News	December 31, 2017
2	Sheriff David Clarke Becomes An Internet Joke ...	On Friday, it was revealed that former Milwaukee...	News	December 30, 2017
3	Trump Is So Obsessed He Even Has Obama's Name ...	On Christmas day, Donald Trump announced that ...	News	December 29, 2017
4	Pope Francis Just Called Out Donald Trump Out ...	Pope Francis used his annual Christmas Day mes...	News	December 25, 2017
5	Racist Alabama Cops Brutalize Black Boy While ...	The number of cases of cops brutalizing and ki...	News	December 25, 2017
6	Freak Off The Golf Course, Trump Lashes Out A ...	Donald Trump spent a good portion of his day a...	News	December 23, 2017
7	Trump Said Some INSANELY Racist Stuff Inside ...	In the wake of yet another court decision that...	News	December 23, 2017
8	Former CIA Director Slams Trump Over UN Bully ...	Many people have raised the alarm regarding th...	News	December 22, 2017
9	WATCH: Brand-New Pro-Trump Ad Features So Muc ...	Just when you might have thought we'd get a bi...	News	December 21, 2017
10	Papa John's Founder Retires, Figures Out Rac ...	A centerpiece of Donald Trump's campaign, and ...	News	December 21, 2017
11	WATCH: Paul Ryan Just Told Us He Doesn't Care ...	Republicans are working overtime trying to sel...	News	December 21, 2017
12	Bad News For Trump - Mitch McConnell Says No ...	Republicans have had seven years to come up w...	News	December 21, 2017
13	WATCH: Lindsey Graham Trashes Media For Port ...	The media has been talking all day about Trump...	News	December 20, 2017
14	Heinous To Disney Empire Knows GOP Scammed Us ...	Aligall Disney is an heinous with brass ova...	News	December 20, 2017
15	Tone Deaf Trump: Congrats Rep. Scalise On Los ...	Donald Trump just signed the GOP tax scam into...	News	December 20, 2017

After Data Cleaning



	title	text	subject	date	cleaned_text
0	Donald Trump Sends Out Embarrassing New Year's...	donald trump just couldn't wish all americans ...	News	December 31, 2017	donald trump wish americans happy new year tes...
1	Drunk Bragging Trump Staffer Started Russian ...	house intelligence committee chairman devin nu...	News	December 31, 2017	house intelligence committee chairman devin nu...
2	Sheriff David Clarke Becomes An Internet Joke ...	on friday, it was revealed that former milwaue...	News	December 30, 2017	friday revealed former milwaukee sheriff davi...
3	Trump Is So Obsessed He Even Has Obama's Name ...	on christmas day, donald trump announced that ...	News	December 29, 2017	christmas day donald trump announced would bac...
4	Pope Francis Just Called Out Donald Trump Out ...	pope francis used his annual christmas day mes...	News	December 25, 2017	pope francis used annual christmas day message...
5	Racist Alabama Cops Brutalize Black Boy While ...	the number of cases of cops brutalizing and ki...	News	December 25, 2017	number cases cops brutalizing killing people c...
6	Freak Off The Golf Course, Trump Lashes Out A ...	donald trump spent a good portion of his day a...	News	December 23, 2017	donald trump spent good portion day golf club...
7	Trump Said Some INSANELY Racist Stuff Inside ...	in the wake of yet another court decision that...	News	December 23, 2017	wake yet another court decision derailed donal...
8	Former CIA Director Slams Trump Over UN Bully ...	many people have raised the alarm regarding th...	News	December 22, 2017	many people raised alarm regarding fact donal...
9	WATCH: Brand-New Pro-Trump Ad Features So Muc ...	just when you might have thought we'd get a bi...	News	December 21, 2017	night thought get break watching people kis d...
10	Papa John's Founder Retires, Figures Out Rac ...	a centerpiece of donald trump's campaign, and ...	News	December 21, 2017	centerpiece donald trump campaign presidency w...
11	WATCH: Paul Ryan Just Told Us He Doesn't Care ...	republicans are working overtime trying to sel...	News	December 21, 2017	republicans working overtime trying sell scam ...
12	Bad News For Trump - Mitch McConnell Says No ...	republicans have had seven years to come up w...	News	December 21, 2017	republicans seven years come viable replacements...
13	WATCH: Lindsey Graham Trashes Media For Port ...	the media has been talking all day about trump...	News	December 20, 2017	media talking day trump republican party scam...
14	Heinous To Disney Empire Knows GOP Scammed Us ...	aligall disney is an heinous with brass ova...	News	December 20, 2017	aligall disney heinous brass ovaes profit go...
15	Tone Deaf Trump: Congrats Rep. Scalise On Los ...	donald trump just signed the GOP tax scam into...	News	December 20, 2017	donald trump signed gop tax scam law course me...

5.3.2 Tokenization

Tokenization is the process of splitting text into smaller units called tokens, usually words.

Example:

"This news article is fake"

→ ["this", "news", "article", "is", "fake"]

Tokenization enables word-level analysis and forms the basis for further preprocessing steps.

5.3.3 Stopword Removal

Stopwords are commonly occurring words such as *is*, *the*, *and*, *of* that do not carry significant meaning in classification tasks.

Stopword removal helps in:

- Reducing vocabulary size
- Improving computational efficiency
- Highlighting meaningful words

The **NLTK library** is used to remove stopwords from the text.

5.3.4 Stemming

Stemming reduces words to their root or base form by removing suffixes.

Example:

- *running* → *run*
- *connected* → *connect*

Stemming helps in reducing word variations and improving generalization.

5.3.5 Lemmatization

Lemmatization converts words into their dictionary or meaningful base form.

Example:

- *better* → *good*
- *cars* → *car*

Compared to stemming, lemmatization preserves semantic meaning more accurately.

5.3.6 Handling Missing and Duplicate Data

To maintain data quality, the following steps are applied:

- Removal of records with empty or null text fields
- Removal of duplicate news articles
- Verification of label consistency

This ensures the dataset is reliable and unbiased.

5.4 Feature Engineering

After preprocessing, textual data must be converted into numerical representations so that machine learning models can process it.

5.4.1 TF-IDF Vectorization

TF-IDF (Term Frequency–Inverse Document Frequency) assigns weights to words based on their importance. [13]

Advantages of TF-IDF:

- Reduces impact of frequently occurring but less meaningful words
- Improves performance of traditional ML models
- Computationally efficient

TF-IDF features are used for [1,13] :

- Logistic Regression
- Support Vector Machine (SVM)

5.4.2 Word Embedding Representation

For deep learning models, word embeddings are used instead of sparse vectors.

Word embeddings:

- Represent words as dense numerical vectors
- Capture semantic and contextual relationships
- Improve deep learning performance

These embeddings are used with CNN, LSTM, and **LSTM + CNN hybrid models**. [2,3]

5.5 Data Splitting

To evaluate the model effectively, the dataset is divided into two parts:

- **Training dataset:** Used to train the models
- **Testing dataset:** Used to evaluate performance

This separation ensures that the model generalizes well to unseen data and avoids overfitting.

5.6 Tools and Libraries Used

The following tools and libraries are used in data collection and preprocessing:

- **Pandas & NumPy:** Data manipulation
- **NLTK:** Text preprocessing
- **scikit-learn:** TF-IDF vectorization and data splitting
- **BeautifulSoup & newspaper3k:** Web scraping
- **Transformers & Sentence-Transformers:** Experimental text embeddings

5.7 Outcome of Data Preprocessing

After preprocessing, the dataset becomes:

- Clean and noise-free
- Structured and normalized
- Numerically represented
- Ready for efficient training

Effective preprocessing significantly improves model accuracy and training stability.

SIMULATION & IMPLEMENTATION

This chapter describes the simulation and implementation of the proposed fake news detection system. Simulation refers to the practical execution of the methodology using real datasets, tools, and algorithms to train, test, and evaluate machine learning and deep learning models. Implementation focuses on converting the trained model into a functional system and deploying it as a web-based application.

The goal of this chapter is to explain how theoretical concepts discussed in previous chapters are applied in practice to build a working fake news detection system.

6.1 Simulation Environment

The simulation environment consists of both hardware and software resources required for model training and testing.

6.1.1 Hardware Requirements

- Processor: Intel Core i5 or higher
- RAM: Minimum 8 GB
- Storage: Minimum 10 GB free space

6.1.2 Software Requirements

- Operating System: Windows / Linux
- Programming Language: Python
- Development Environment: Jupyter Notebook / VS Code
- Frontend Framework: React
- Backend Framework: Flask

6.2 Libraries and Tools Used

The following libraries and tools are used for simulation and implementation:

- **NumPy**: Numerical computation
- **Pandas**: Data loading and manipulation
- **NLTK**: Text preprocessing
- **scikit-learn**: Machine learning models and evaluation

- **TensorFlow / Keras:** Deep learning model development
- **Torch:** Experimental deep learning support
- **Transformers & Sentence-Transformers:** Advanced text representation
- **Flask & Flask-CORS:** Backend API development
- **Gunicorn, FastAPI, Uvicorn:** Deployment support
- **BeautifulSoup, newspaper3k, requests:** Web scraping

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.preprocessing.sequence import pad_sequences
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Embedding, LSTM, Dense, Dropout, Conv1D, MaxPooling1D
from tensorflow.keras.callbacks import EarlyStopping
import pickle
```

6.3 Dataset Loading and Preparation

The FakeNewsNet dataset is loaded into the system using Pandas. The dataset contains news article text and corresponding labels indicating whether the news is fake or real. [6,9]

Key steps involved:

- Reading dataset files
- Selecting relevant columns (news content and label)
- Removing empty and duplicate records
- Encoding labels into numerical format

The processed dataset is then passed to the preprocessing module.

```
fake = pd.read_csv("Fake.csv")
real = pd.read_csv("Real.csv")

# Add labels
fake["label"] = "FAKE"
real["label"] = "REAL"

# Merge datasets
data = pd.concat([fake, real], axis=0)
data = data.sample(frac=1, random_state=42).reset_index(drop=True)

# Combine title + text (same as your LSTM model)
data["content"] = data["title"].fillna("") + " " + data["text"].fillna("")

# Label Encoding
le = LabelEncoder()
data["label_encoded"] = le.fit_transform(data["label"])
```

6.4 Implementation of Text Preprocessing

Text preprocessing steps described in Chapter 5 are implemented programmatically. Each news article undergoes a series of transformations before feature extraction.

6.4.1 Preprocessing Workflow

- Convert text to lowercase
- Remove punctuation, URLs, and special characters
- Tokenize text
- Remove stopwords
- Apply stemming and lemmatization

This process ensures that the text is clean and standardized.

6.5 Feature Extraction Implementation

After preprocessing, textual data is converted into numerical features suitable for model training. [13]

6.5.1 TF-IDF Feature Extraction

TF-IDF vectorization is applied to the cleaned text data to generate feature vectors. [13]

These features are used for:

- Logistic Regression [1]
- Support Vector Machine (SVM)

TF-IDF helps emphasize important words and reduce the influence of common terms.

6.5.2 Word Embedding Implementation

For deep learning models, word embeddings are used instead of sparse vectors.

Implementation steps include:

- Tokenizing text and creating vocabulary
- Mapping words to numerical indices
- Padding sequences to fixed length
- Feeding sequences into embedding layers

Embeddings improve semantic understanding and model performance.

6.6 Model Construction

Multiple models are constructed and trained during simulation to compare performance.

6.6.1 Logistic Regression Model

Logistic Regression is implemented as a baseline classifier using TF-IDF features. It provides a reference point for evaluating more complex models.

6.6.2 Support Vector Machine (SVM)

SVM is implemented to handle high-dimensional text data and provide improved classification performance compared to Logistic Regression.

6.6.3 Convolutional Neural Network (CNN)

The CNN model consists of:

- Embedding layer
- Convolutional layers
- Pooling layers
- Fully connected layers
- Output layer

CNN effectively extracts local textual features.

6.6.4 Long Short-Term Memory (LSTM)

The LSTM model processes text sequences to capture long-term dependencies and contextual relationships between words. [11]

6.6.5 Hybrid LSTM + CNN Model (Final Implementation)

The **LSTM + CNN hybrid model** combines both architectures to improve classification accuracy. [3]

Model structure:

- Embedding layer
 - CNN layer for feature extraction
 - LSTM layer for sequence modeling
 - Dense layers
 - Sigmoid output layer
- This hybrid model is selected as the **final deployed model** due to its strong performance and computational efficiency.

6.6.6 Bidirectional LSTM (Comparative Model)

Bidirectional LSTM is implemented only for research comparison. Although it shows slightly higher accuracy, it is not selected for deployment due to increased computational cost.

6.7 Model Training

Model training is performed using the training dataset.

Training configuration includes:

- Loss function: Binary Cross-Entropy
- Optimizer: Adam
- Batch size: Optimized based on hardware
- Epochs: Multiple iterations until convergence

Validation data is used to monitor training performance and prevent overfitting.

```
embedding_dim = 128

model = Sequential()

# Embedding
model.add(Embedding(input_dim=max_words, output_dim=embedding_dim, input_length=max_len))

# ★ CNN Layer (kept small to avoid destroying LSTM behavior)
model.add(Conv1D(filters=64, kernel_size=3, activation='relu'))
model.add(MaxPooling1D(pool_size=2))

# ★ LSTM Layer (same as your working model)
model.add(LSTM(128, dropout=0.2, recurrent_dropout=0.2))

# Output Layer
model.add(Dense(1, activation='sigmoid'))

# Compile
model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])
model.summary()
```

6.8 Model Evaluation

After training, models are evaluated using the testing dataset. Evaluation metrics include [15]:

- Accuracy
- Precision
- Recall
- F1-Score

```
es = EarlyStopping(monitor='val_loss', patience=3, restore_best_weights=True)

history = model.fit(
    X_train_pad,
    y_train,
    epochs=10,
    batch_size=64,
    validation_split=0.2,
    callbacks=[es],
    verbose=1
)
```

The evaluation results show that the **LSTM + CNN hybrid model** achieves high accuracy and stable performance, making it suitable for real-world deployment.

6.9 Backend Implementation

The backend of the system is implemented using **Flask**, which exposes the trained model as a REST API.

Backend responsibilities include:

- Loading the trained model
- Accepting text input from frontend
- Performing preprocessing and prediction
- Returning results in JSON format

Flask-CORS is used to allow cross-origin communication.

6.10 Frontend Implementation



The frontend is developed using **React** to provide a user-friendly interface.

Frontend features include:

- Text input field for news content
- Submit button for prediction
- Display of classification result (Fake / Real)
- Display of confidence score

The frontend communicates with the backend through HTTP requests.


Home Page:




1. User enters news text
2. Frontend sends request to backend
3. Backend preprocesses input

4. Model generates prediction
 5. Result is returned to frontend
- Output is displayed to the user, News classification: Fake or Real & Confidence probability

Using Text:



Using Link:



RESULT & DISCUSSION

This chapter presents the results obtained from the implementation of various machine learning and deep learning models for fake news detection. It also provides a detailed discussion of the performance of these models based on experimental evaluation.

The objective of this chapter is to analyze the effectiveness of the proposed system, compare different models, and justify the selection of the final deployed model based on accuracy, stability, and practical usability.

7.1 Experimental Setup

The experiments are conducted using the FakeNewsNet dataset consisting of approximately **40,000 labeled news articles** [6,9]. The dataset is divided into training and testing sets to evaluate the generalization ability of the models.

Key aspects of the experimental setup include:

- Preprocessed textual data using NLP techniques
- Feature extraction using TF-IDF and word embeddings [12,13]
- Evaluation using standard classification metrics [15]

All models are trained and tested under similar conditions to ensure a fair comparison.

7.2 Evaluation Metrics

To measure the performance of the fake news detection models, the following evaluation metrics are used:

7.2.1 Accuracy

Accuracy represents the proportion of correctly classified news articles out of the total number of articles tested. It provides an overall measure of model performance. [15]

7.2.2 Precision

Precision indicates the proportion of correctly predicted fake news articles among all articles predicted as fake. High precision reduces false positives. [15]

7.2.3 Recall

Recall measures the proportion of actual fake news articles that are correctly identified by the model. High recall ensures that fewer fake news articles go undetected. [15]

7.2.4 F1-Score

The F1-score is the harmonic mean of precision and recall. It provides a balanced measure of performance, especially in binary classification problems. [15]

7.3 Performance of Traditional Machine Learning Models

Traditional machine learning models are implemented as baseline classifiers to compare their performance with deep learning models.

7.3.1 Logistic Regression

Logistic Regression is used with TF-IDF features to establish baseline performance.

Observations:

- Simple and fast to train
- Interpretable results
- Moderate accuracy
- Limited contextual understanding

Although Logistic Regression performs reasonably well, it fails to capture complex linguistic patterns.

7.3.2 Support Vector Machine (SVM)

SVM shows better performance than Logistic Regression due to its ability to handle high-dimensional feature spaces.

Observations:

- Improved accuracy compared to baseline
- Effective decision boundaries
- Higher computational cost

Despite better performance, SVM still lacks deep semantic understanding.

7.4 Performance of Deep Learning Models

Deep learning models demonstrate superior performance by learning hierarchical and contextual features from text data.

7.4.1 Convolutional Neural Network (CNN)

CNN captures local textual patterns such as key phrases and word combinations.

Observations:

- Better accuracy than traditional ML models
- Efficient feature extraction
- Limited long-term dependency modeling

7.4.2 Long Short-Term Memory (LSTM)

LSTM improves upon CNN by capturing sequential dependencies in text.

Observations:

- Better understanding of sentence structure
- Improved accuracy over CNN
- Stable performance on long news articles

7.4.3 Hybrid LSTM + CNN Model (Final Model)

The **LSTM + CNN hybrid model** combines the strengths of both architectures and is selected as the final deployed model.

Observations:

- High classification accuracy
- Robust performance across datasets
- Balanced computational efficiency
- Suitable for real-time deployment

This model achieves the **second-highest accuracy** among all tested models while offering better deployment feasibility.

7.4.4 Bidirectional LSTM (Research Comparison Model)

Bidirectional LSTM processes text in both forward and backward directions, enabling deeper contextual understanding. [16]

Observations:

- Highest accuracy among experimental models
- Superior contextual learning
- Higher computational complexity

Due to increased resource requirements, BiLSTM is not selected for deployment and is used only for comparative analysis.

7.5 Comparative Analysis of Model Performance

A comparative analysis of all implemented models is presented below:

Model	Feature Type	Performance Level	Remark
Logistic Regression	TF-IDF	Moderate	Baseline
SVM	TF-IDF	Good	Traditional ML
CNN	Embeddings	Very Good	Local features
LSTM	Embeddings	Better	Sequential learning
LSTM + CNN	Embeddings	Highest	Final Model
BiLSTM	Embeddings	High	Research comparison

This comparison shows that hybrid and deep learning models outperform traditional machine learning approaches.

7.6 Discussion

The experimental results clearly indicate that fake news detection benefits significantly from deep learning-based approaches. Traditional models rely heavily on frequency-based features and fail to capture semantic and contextual information [1,4].

The **LSTM + CNN hybrid model** demonstrates strong performance by combining local feature extraction with sequential learning. Although BiLSTM achieves slightly higher accuracy [3,16], its higher computational cost makes it less suitable for real-time web deployment.

The chosen model provides an optimal balance between accuracy, efficiency, and scalability, aligning with the practical objectives of this project.

7.7 Limitations of the System

Despite strong performance, the system has certain limitations:

- Limited to English-language text
- Performance depends on dataset quality
- Difficulty in handling sarcasm and subtle misinformation
- No source credibility analysis

These limitations highlight opportunities for future enhancements.

Model	Dataset	Accuracy	Precision	Recall	F1-Score
Logistic Regression	Fake.csv + True.csv (Kaggle)	95.3%	95.1%	95.4%	95.2%
LSTM	Fake.csv + True.csv (Kaggle)	97.6%	97.5%	97.4%	97.5%
CNN + LSTM (Proposed)	Fake.csv + True.csv (Kaggle)	99.69%	99.60%	99.74%	99.67%

```

*** 281/281 ----- 26s 93ms/step - accuracy: 0.9969 - loss: 0.0152
281/281 ----- 21s 74ms/step

===== MODEL PERFORMANCE =====
Accuracy : 99.69%
Precision: 99.60%
Recall   : 99.74%
F1-Score : 99.67%

Confusion Matrix:
[[4679  17]
 [ 11 4273]]

Classification Report:
              precision    recall  f1-score   support

     0       1.00      1.00      1.00     4696
     1       1.00      1.00      1.00     4284

 accuracy          1.00          1.00          1.00     8980
 macro avg          1.00          1.00          1.00     8980
weighted avg          1.00          1.00          1.00     8980

```

```

sample_text = [ "Andhra Pradesh Chief Minister Chandrababu Naidu, known for his strong support of global entrepreneurship, has often participated in international summits and hosted major global .

# clean the sample text exactly like training data
sample_text_cleaned = [clean_text(t) for t in sample_text]

sample_seq = tokenizer.texts_to_sequences(sample_text_cleaned)
sample_pad = pad_sequences(sample_seq, maxlen=max_len, padding="post", truncating="post")
prediction = model.predict(sample_pad)[0][0]
pred_label = "REAL" if prediction >= 0.5 else "FAKE"
print("\n Sample Prediction:", pred_label, "| Score:", prediction)

1/1 ----- 0s 496ms/step
Sample Prediction: FAKE | Score: 0.0018415581

```

FUTURE WORK

Although the proposed fake news detection system achieves strong performance, fake news detection is a continuously evolving challenge. There are several areas where the system can be enhanced and extended in the future to improve accuracy, scalability, and real-world applicability.

8.1 Advanced Deep Learning Models

- Integration of transformer-based models such as **BERT, RoBERTa, or DistilBERT**
- Use of ensemble techniques to combine multiple model predictions
- Fine-tuning pre-trained language models on fake news datasets

8.2 Social Media Account Verification

- Detection of fake or suspicious social media accounts
- Analysis of account-related features such as:
 - Profile picture authenticity
 - Account creation date
 - Location consistency
 - Post frequency and activity patterns
 - User behavior and interaction patterns
- Goal: **Prevent fake accounts from spreading misinformation**

8.3 Multi-Language Support

- Extension of fake news detection to multiple languages
- Use of language-specific preprocessing techniques
- Adoption of multilingual embeddings or models
- Improved global applicability of the system

8.4 Real-Time Social Media Monitoring

- Real-time scanning of social media posts

- Instant flagging of suspicious or misleading content
- Development of alert systems or browser plugins
- Integration with trending topic detection for proactive monitoring

CONCLUSION

The rapid growth of social media and online news platforms has made fake news a serious challenge in the digital era. This project focused on developing an automated system to detect fake news from social media and news websites using machine learning and deep learning techniques.

9.1 Work Summary

In this project, a fake news detection system was designed and implemented using a dataset of approximately **40,000 labeled news articles** collected from the **FakeNewsNet dataset (Kaggle)**. Natural Language Processing techniques such as tokenization, stopword removal, stemming, and lemmatization were applied to preprocess the textual data.

Multiple machine learning and deep learning models were implemented and evaluated. Based on performance and deployment feasibility, the **LSTM + CNN hybrid model** was selected as the final deployed model, while **BiLSTM** was used only for experimental comparison.

9.2 Key Outcomes

- Automated detection of fake news using textual analysis
- Effective use of NLP and deep learning techniques
- Strong performance of the LSTM + CNN hybrid model
- Successful deployment as a web-based application using **Flask** and **React**

9.3 Limitations

- The system supports only English-language text
- Detection is based solely on content, not source credibility
- Complex cases like sarcasm may not be handled effectively

9.4 Final Remarks

In conclusion, the project successfully demonstrates the application of machine learning, deep learning, and web technologies for fake news detection. The proposed system provides a reliable and scalable solution that can be further enhanced with

advanced models, multilingual support, and real-time monitoring to combat misinformation more effectively.

REFERENCES

- [1] M. Alsmadi, *et al.*, "A Comparative Study of Machine Learning Algorithms for Fake News Detection on Social Media," *Journal of King Saud University – Computer and Information Sciences*, Elsevier, 2025.
Available: <https://www.sciencedirect.com/science/article/pii/S2590123025008291>
- [2] A. Adnan and S. Hasan, "Deep Learning Models for Fake News Classification using NLP," *Heliyon*, Elsevier, 2024.
Available: <https://www.sciencedirect.com/science/article/pii/S2665917424000047>
- [3] D. G. Dev, *et al.*, "LSTMCNN: A Hybrid Machine Learning Model to Unmask Fake News," *Heliyon*, Elsevier, 2024.
Available: <https://www.sciencedirect.com/science/article/pii/S2405844024012751>
- [4] R. Rani and P. Verma, "Fake News Detection using NLP and Deep Learning: A Review," *Journal of Engineering Science (JES)*, 2023.
Available: <https://journal.esrgroups.org/jes/article/view/8618/5775>
- [5] OpenAI, "ChatGPT – AI-assisted Content Generation and Technical Guidance."
Available: <https://chatgpt.com/>
- [6] Kaggle, "Fake and Real News Dataset / FakeNewsNet Dataset."
Available: <https://www.kaggle.com/>
- [7] S. Vosoughi, D. Roy, and S. Aral, "The Spread of True and False News Online," *Science*, vol. 359, no. 6380, pp. 1146–1151, 2018.
Available: <https://www.science.org/doi/10.1126/science.aap9559>
- [8] K. Shu, A. Sliva, S. Wang, J. Tang, and H. Liu, "Fake News Detection on Social Media: A Data Mining Perspective," *ACM SIGKDD Explorations Newsletter*, vol. 19, no. 1, pp. 22–36, 2017.
Available: <https://dl.acm.org/doi/10.1145/3137597.3137600>
- [9] K. Shu, D. Mahudeswaran, S. Wang, D. Lee, and H. Liu, "FakeNewsNet: A Data Repository with News Content, Social Context, and Dynamic Information for Fake News Research," *Big Data*, vol. 8, no. 3, pp. 171–188, 2020.
Available: <https://www.liebertpub.com/doi/10.1089/big.2020.0062>
- [10] Y. Kim, "Convolutional Neural Networks for Sentence Classification," *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1746–1751, 2014.
Available: <https://aclanthology.org/D14-1181/>
- [11] S. Hochreiter and J. Schmidhuber, "Long Short-Term Memory," *Neural Computation*, vol. 9, no. 8, pp. 1735–1780, 1997.
Available: <https://direct.mit.edu/neco/article/9/8/1735/6109/Long-Short-Term-Memory>

- [12] J. Pennington, R. Socher, and C. Manning, "GloVe: Global Vectors for Word Representation," *Proceedings of EMNLP*, pp. 1532–1543, 2014.
Available: <https://aclanthology.org/D14-1162/>
- [13] G. Salton and C. Buckley, "Term-Weighting Approaches in Automatic Text Retrieval," *Information Processing & Management*, vol. 24, no. 5, pp. 513–523, 1988.
Available: <https://www.sciencedirect.com/science/article/pii/0306457388900210>
- [14] D. Jurafsky and J. H. Martin, *Speech and Language Processing*, 3rd ed. (Draft), Stanford University.
Available: <https://web.stanford.edu/~jurafsky/slp3/>
- [15] I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. Cambridge, MA, USA: MIT Press, 2016.
Available: <https://www.deeplearningbook.org/>
- [16] J. Alghamdi, S. Luo, and Y. Lin, "A Comprehensive Survey on Machine Learning Approaches for Fake News Detection," *Multimedia Tools and Applications*, 2024.
Available: <https://link.springer.com/article/10.1007/s11042-023-17470-8>